arXiv:2501.02516v1 [eess.AS] 5 Jan 2025

A Frequency-aware Augmentation Network for Mental Disorders Assessment from Audio

Shuanglin Li¹, Siyang Song², Rajesh Nair³, and Syed Mohsen Naqvi¹

¹Intelligent Sensing and Communications Research Group, Newcastle University, U.K.

²School of Computing and Mathematical Sciences, University of Leicester, U.K.

³Cumbria, Northumberland, Tyne and Wear, CNTW-NHS Foundation Trust, U.K.

Abstract—Depression and Attention Deficit Hyperactivity Disorder (ADHD) stand out as the common mental health challenges today. In affective computing, speech signals serve as effective biomarkers for mental disorder assessment. Current research, relving on labor-intensive hand-crafted features or simplistic timefrequency representations, often overlooks critical details by not accounting for the differential impacts of various frequency bands and temporal fluctuations. Therefore, we propose a frequencyaware augmentation network with dynamic convolution for depression and ADHD assessment. In the proposed method, the spectrogram is used as the input feature and adopts a multi-scale convolution to help the network focus on discriminative frequency bands related to mental disorders. A dynamic convolution is also designed to aggregate multiple convolution kernels dynamically based upon their attentions which are input-independent to capture dynamic information. Finally, a feature augmentation block is proposed to enhance the feature representation ability and make full use of the captured information. Experimental results on AVEC 2014 and self-recorded ADHD dataset prove the robustness of our method, an RMSE of 9.23 was attained for estimating depression severity, along with an accuracy of 89.8% in detecting ADHD.

Index Terms—Attention deficit hyperactivity disorder; Depression; deep learning; audio-based disorder assessment

I. INTRODUCTION

Mental health is crucial for effectively handling life's challenges, with depression and ADHD being notable concerns that affect millions worldwide [1]. These disorders are recognized by the World Health Organization (WHO) as common, yet often go underdiagnosed and under-treated due to their complex symptoms and the global shortage of specialized mental health professionals [2]. This situation underscores the necessity for innovative diagnostic tools to support the early detection and management of depression and ADHD. Developing such tools could alleviate the healthcare burden by complementing the expertise of clinicians, leading to faster diagnosis and tailored treatments. Ultimately, enhancing diagnostic capabilities for these mental health conditions promises to improve patient care and outcomes significantly [3].

In the last decade, deep learning has driven breakthroughs in areas like speech and image recognition [4]–[6] and some studies suggest combining deep learning with additional data has shown promise in detecting mental conditions such as depression and ADHD [2], [7], [8]. Wang et al. [9] have innovatively transformed EEG data into 2D images to train via AlexNet, enhancing the efficiency of depression diagnosis by analyzing EEG channel features and their correlation with the condition. In parallel, Zhao et al. [10] developed a dynamic graph convolutional network that utilizes sparse connections between brain regions from fMRI data to aid in detecting ADHD. Despite the critical role of psychological signals in mental health diagnostics, their collection often requires costly and invasive equipment, such as MRI scanners and EEG headsets.

Speech signals, as a cost-effective, non-invasive diagnostic tool for mental health conditions, have been extensively studied. Recent research [11] has explored how speech patterns correlate with depression levels indicated by the Beck Depression Inventory-II (BDI-II) score [12]. The main challenge is identifying speech features that signify conditions like depression. Although depressive speech may show paralinguistic markers like variability in fundamental frequency, jitter, and shimmer [13], these traditional acoustic features often fail to capture specific symptoms, leading researchers to pursue extensive but less effective feature sets [14].

To address these limitations, recent studies have shifted towards using time-frequency representations of speech signals such as Fourier spectrogram and mel-spectrogram to aid in the detection of mental disorders [15]. However, such methods treat each time and frequency component equally and the commonly used convolutional neural networks with a single convolutional kernel do not consider the temporal variations which are vital for the effect estimation [16], [17]. Moreover, there are studies suggesting that not all frequency bands hold equal significance in mental health conditions when using speech signals [18].

In this paper, we propose a frequency-aware augmentation network with dynamic convolution to aid in the assessment of depression and ADHD. Specifically, we use three parallel depth-wise convolution networks to give different attention weights to different frequency bands of the input spectrogram. Additionally, to capture temporal variation changes, the dynamic convolution (Dy-CNN) is designed by aggregating multiple kernels to capture contextual information. Finally, a feature augmentation block is designed to enhance the feature propagation and representation abilities. In summary, the main contributions of this study can be summarized as follows:

- 1) Development of a frequency-aware augmentation network: This innovative network is tailored to emphasize the discriminate frequency bands in speech signals that are crucial for identifying the signs of depression and ADHD.
- 2) The implementation integrates dynamic convolution to allow the model to adaptively aggregate convolution kernels based on their relevance, thereby capturing essential temporal fluctuations in speech signals. Additionally, the introduction of a Feature Augmentation Block significantly enhances the network's feature representation capabilities and improves information flow efficiency.

The results from our evaluations of the Audio/Video Emotion Challenge (AVEC) 2014 [19] dataset and our multi-modal ADHD dataset highlight the effectiveness of the proposed framework.

II. PROPOSED METHOD

This section details each proposed module, with Fig.1 presents the comprehensive diagram of the proposed method.

A. Frequency-aware Spectrogram Reweight

Recent studies indicate that unique local patterns in speech signals vary across frequency ranges, with lower bands effectively distinguishing normal from disordered speech [20], [21]. This finding motivates us to adjust spectrogram weights by frequency band. To analyze these, we convert the audio signal S(n) into a time-frequency domain representation using the Short-Time Fourier Transformation (STFT).

$$STFT(S(n)) = \mathbf{S}_{\mathbf{r}} + i \times \mathbf{S}_{\mathbf{i}}$$
(1)

where $\mathbf{S}_{\mathbf{r}}$ and $\mathbf{S}_{\mathbf{i}}$ denote the real and imaginary parts of the S(n), respectively. The magnitude spectrogram $\mathbf{S}_{\mathbf{m}} \in \mathbb{R}^{T \times F}$, is then calculated with the real $\mathbf{S}_{\mathbf{r}}$ and the imaginary $\mathbf{S}_{\mathbf{i}}$ components as:

$$\mathbf{S}_{\mathbf{m}} = \sqrt{(\mathbf{S}_{\mathbf{r}})^2 + (\mathbf{S}_{\mathbf{i}})^2} \tag{2}$$

After capturing the magnitude spectrogram, it is fed to three parallel 1-D depthwise convolutions, denoted as D-Convk for $k \in \{1, 2, 3\}$ with an additional fully connected layer designed to learn a weight vector $\mathbf{W} \in \mathbb{R}^{F}$, which aims to assign specific weights to each frequency bin. To apply these weights, \mathbf{W} is broadcasted to match the dimensions of the spectrogram $\mathbf{S}_{\mathbf{m}} \in \mathbb{R}^{T \times F}$, then a dot product is performed between the broadcasted \mathbf{W} and $\mathbf{S}_{\mathbf{m}}$, effectively applying the weights across the spectrogram to achieve the weighting:

$$\mathbf{W} = [W_0, \dots, W_f, \dots, W_{F-1}]^T \in \mathbb{R}^F$$
(3)

$$\widetilde{\mathbf{S}}_m = \mathbf{S}_m \odot \mathbf{W} \tag{4}$$

This procedure captures the information on mental speech disorders hidden in the spectrogram, and the re-weighted spectrogram $\widetilde{\mathbf{S}}_m$ retains the same dimension as the input feature.

B. Dynamic Convolution

Traditional convolutional techniques use static kernels, limiting the extraction of sample-wise contextual data. The dynamic convolution addresses this by using multiple convolution kernels that adjust to speech changes in mental disorders through an attention mechanism. This allows for a more precise adaptation to input data, enhancing feature extraction. Fig. 2 visually contrasts conventional and dynamic convolution networks.

Specifically, we implement an attention mechanism by alternating fully connected layers and ReLU activation function to compute attention weights $\{\alpha_1, \ldots, \alpha_N\}$ for N convolutional kernels, ensuring the same dimensions for both input and output. The process of dynamic convolution is:

$$y = \left(\sum_{n=1}^{N} \alpha_n K_n\right) * x,\tag{5}$$

where x and y denote the input and output features, respectively, and K_n represents the n-th convolutional kernel weighted by the attention weight α_n , derived from a sequence of fully connected layers applied to the input features and a softmax function is utilized to constraint the attention weights α_n sum-to-one.

C. Feature Augmentation Block

As shown in Fig. 3, the feature augmentation block is strategically designed to bolster the model's capability to represent features more effectively based on the designed Dy-CNN. Drawing inspiration from the work [22], [23], we incorporate the dense block and transition layer to achieve this enhancement. The dense block facilitates improved feature propagation and reuse by aggregating channel responses from various layers. Concurrently, the transition layer is tasked with streamlining the model by reducing the number of channels and applying pooling operations to isolate regions with pronounced convolution responses. This dual approach not only amplifies the model's ability to capture and utilize relevant features but also addresses the challenge of gradient vanishing, thereby making the training process more robust and efficient.

III. EXPERIMENTAL EVALUATIONS AND RESULTS

A. Datasets

We conducted experiments on one public AVEC 2014 [19] depression database and one self-recorded multi-modal ADHD dataset.

The AVEC 2014 depression database specifically focuses on evaluating automatic depression detection algorithms through two human-computer interaction tasks, "Northwind" and "Freeform". It comprises 150 speech files from 84 subjects, with these files evenly divided among training, development, and test sets. Each of these sets contains 50 samples, covering a wide duration range from 6 seconds to 4 minutes. Notably, for experimental purposes, the training, development, and test sets from both tasks are merged to form a consolidated dataset,



Fig. 1. The proposed frequency-aware augmentation network with dynamic convolution for depression and ADHD assessment. The spectrogram is extracted from the raw audio wave and then processed through parallel 1-D depthwise convolutions, accompanied by an additional fully connected layer to learn a frequency-aware weighting matrix \mathbf{W} , which is applied for re-weighting the spectrogram. Subsequently, the re-weighted spectrogram undergoes further analysis through dynamic convolutional neural networks (Dy-CNN) and feature augmentation modules, leading to the final prediction stage. D-Conv means 1-D depthwise convolution. " \odot " denotes the dot product operation. Dy-CNN and FC are the abbreviations of dynamic convolution and fully connected layers.



Fig. 2. (a) The conventional convolutional neural network. (b) The dynamic convolution neural network where the dynamic Kernels generator module obtains the kernels. (c) The dynamic Kernels generator module. The BN and FC are the abbreviations of batch normalization and fully connected layers.



Fig. 3. The structure of the proposed feature augmentation block

resulting in 100 speech files per set for subsequent analyses, and each subject is labeled with BDI-II scores.

In our Intelligent Sensing ADHD Trial (ISAT) [24], we developed a multimodal ADHD dataset featuring audio and video modalities, recorded in an environment simulating a quiet, interference-free medical clinic. We enrolled 22 native English speakers, dividing them into 10 ADHD-diagnosed subjects and 12 controls, verified by the Cumbria, Northumberland, Tyne and Wear National Health Service (CNTW-NHS) Foundation Trust with the ASRSv1.1 checklist [25]. Recruitment was through university poster advertisements. This study focuses on the audio modality, employing a DIVA instrument-derived questionnaire [26] covering social interactions, self-esteem, and work life to guide participant interviews. A total of 462 audio recordings were obtained using portable microphones.

B. Evaluation Metric

For the depression assessment, which is inherently a regression task aimed at predicting the BDI-II scores, we utilize the Root Mean Square Error (RMSE) and Mean Absolute Error (MAE) as our primary evaluation metrics as popular in depression assessment. These metrics are defined as follows:

$$RMSE = \sqrt{\frac{1}{N} \sum_{i=1}^{N} (y_i - \hat{y}_i)^2}$$
(6)

$$MAE = \frac{1}{N} \sum_{i=1}^{N} |y_i - \hat{y}_i|$$
(7)

where y_i and \hat{y}_i represent the actual and predicted BDI-II scores for the *i*-th sample, respectively. Conversely, ADHD detection is approached as a classification task, necessitating metrics that can evaluate the model's ability to accurately categorize subjects. Therefore, we adopt accuracy (Acc.), precision (Pre.), recall (Re.), and F1-Score (F1) as the evaluation metrics for this task.

C. Experiments setup

In our study involving the AVEC 2014 corpora, following the state-of-the-art literature [27], we also processed the speech signals at a sampling rate of 8 kHz and segmented them into 3-second intervals with a 50% overlap between consecutive segments. The labeling of each segment was based on the corresponding BDI-II score of the audio source. Throughout all the network layers, the ReLU served as the activation function. We chose the Root Mean Square Error (RMSE) as our loss function for this regression-focused task, aligning with Equation 6. The Adam optimization algorithm was employed to train the model, using a batch size of 32, momentum of 0.9, and a learning rate of 0.0001.

In our ADHD dataset analysis, we resampled raw audio to 16kHz, cleaned up abnormalities using Audacity [28], and standardized clip lengths to 10 seconds in line with previous work [29], interpolating shorter clips with silence. Spectrograms were produced using a Fast Fourier Transform (FFT) size of 1024 and a hop length of 160. We implemented a batch size of 16 and an initial learning rate of 0.0001, optimizing with Adam and cross-entropy loss.



Fig. 4. The comparison of the original spectrogram and the weighted spectrogram: The horizontal axis represents time, and the vertical axis represents frequency. (A) is the original depressive spectrogram, and (B) is the weighted depressive spectrogram. (C) and (D) are the ADHD spectrogram and the weighted ADHD spectrogram, respectively. A better view in color is provided.

D. Experimental Results and Discussions

1) Visualization of Frequency-aware Re-weighting: Figure 4 presents an intuitive visual comparison between the original and specifically weighted spectrograms of individuals diagnosed with depression and ADHD. By applying targeted frequency-wise weighting to the spectrograms, there's a noticeable emphasis on the lower frequency bands while simultaneously paying less attention to the higher frequency bands. This observation underscores the effectiveness of employing refined weighting strategies on spectrograms, significantly enhancing the detection and analysis of speech signal characteristics linked to mental disorders. The strategic focus on lower frequencies, crucial for conveying speech information related to mental health conditions, facilitates a more distinct recognition of patterns specific to disorders. Additionally, it may provide valuable insights into the mechanisms behind speech alterations associated with mental health issues. Thus, this approach holds significant potential for the development of diagnostic and therapeutic tools using speech signals as non-invasive biomarkers for assessing mental health.

 TABLE I

 Experimental results comparison with previous methodologies

 using the AVEC 2014 dataset.

Methods	RMSE	MAE
Valstar et al. [19]	12.56	10.03
Varun et al. [30]	11.51	9.74
Jan et al. [31]	10.28	8.07
He et al. [32]	9.99	8.19
Niu et al. [15]	9.66	8.02
Zhao et al. [27]	9.57	7.94
Proposed Method	9.23	7.08

2) Comparison of AVEC 2014 with previous methods: Table 1 showcases the comparison of the results on the AVEC 2014 database. It can be concluded that the methods rely on hand-crafted features, showing progressive improvements in RMSE and MAE values, but still exhibit higher MAE error rates., The method in [15] utilizing solely Mel-Frequency Cepstral Coefficients (MFCC), marks a shift towards automatic feature extraction with slightly better results. Besides, [32] and [27] employ Fourier spectrograms, indicating the effectiveness of spectral features in capturing relevant information, which is reflected in their improved accuracy. The Proposed Method, enhancing this approach by reweighting the Fourier spectrogram frequency-wise, achieves the best performance with the lowest RMSE and MAE values. This suggests that more sophisticated, tailored feature extraction methods, particularly those that emphasize frequency domain nuances, are crucial for enhancing predictive accuracy in automatic depression level detection.

3) Comparison of Multimodal ADHD Dataset with Different Network Architectures: Table 2 highlights the development of network architectures based on audio for detecting ADHD, ultimately leading to the superior performance of the newly proposed CGRU method. This method integrates the feature extraction capabilities of CNNs with the sequential processing strengths of GRUs, achieving considerable accuracy, precision, recall, and F1 scores. The advancement of the proposed method over previous widely used approaches demonstrates the effectiveness of reweighting the spectrogram and capturing dynamic information, allowing for a nuanced analysis of audio signals, significantly enhancing the model's predictive accuracy and reliability in ADHD detection tasks.

TABLE II Comparison of ADHD Detection across different audio-based network architectures.

Methods	Acc.	Pre.	Re.	F1.
†Othmani et al. [33]	0.710	0.747	0.761	0.700
†Makiuchi et al. [34]	0.753	0.791	0.793	0.744
†Shivhare et al. [35]	0.730	0.738	0.793	0.724
†Zeng et al. [36]	0.741	0.763	0.794	0.734
Proposed Method	0.898	0.919	0.914	0.893

†We reproduce the method by ourselves and use the ADHD dataset as the target corpus.

IV. CONCLUSIONS AND FUTURE WORK

In this paper, a novel framework that utilizes frequency re-weighting and dynamic convolution as well as a feature augmentation block is proposed for depression and ADHD assessment from speech signals. Experiments on AVEC 2014 and the ADHD datasets demonstrated the effectiveness of our proposed method and suggested a suitable way for speechbased mental disorder detection. In the future, we will explore the phase information to improve the intelligibility of the spectrogram and novel blocks to enhance the feature representations, besides, we will extend our work to multi-modality as well.

REFERENCES

- V. Patel, S. Saxena, C. Lund *et al.*, "The Lancet commission on global mental health and sustainable development," *The Lancet*, vol. 392, no. 10157, pp. 1553–1598, 2018.
- [2] C. Nash, R. Nair, and S. M. Naqvi, "Machine learning in ADHD and depression mental health diagnosis: A survey," *IEEE Access*, 2023.
- [3] —, "Insights into detecting adult ADHD symptoms through advanced dual-stream machine learning," *IEEE Transactions on Neural Systems* and Rehabilitation Engineering, 2024.
- [4] Z. Fu, F. Angelini, J. Chambers, and S. M. Naqvi, "Multi-level cooperative fusion of GM-PHD filters for online multiple human tracking," *IEEE Transactions on Multimedia*, vol. 21, no. 9, pp. 2277–2291, 2019.
- [5] Y. Xian, Y. Sun, W. Wang, and S. M. Naqvi, "A multi-scale feature recalibration network for end-to-end single-channel speech enhancement," *IEEE Journal of Selected Topics in Signal Processing*, vol. 15, no. 1, pp. 143–155, 2020.
- [6] L. Xie, Y. Yang, Z. Fu, and S. M. Naqvi, "Position and orientation-aware one-shot learning for medical action recognition from signal data," *IEEE Transactions on Multimedia*, 2024.
- [7] J. Posner, G. V. Polanczyk, and E. J. S. Sonuga-Barke, "Attention deficit hyperactivity disorder," *The Lancet*, vol. 395, pp. 450–462, 2020.
- [8] L. He, M. Niu, P. Tiwari *et al.*, "Deep learning for depression recognition with audiovisual cues: A review," *Information Fusion*, vol. 80, pp. 56– 86, 2022.
- [9] B. Wang, Y. Kang, D. Huo *et al.*, "Depression signal correlation identification from different EEG channels based on CNN feature extraction," *Neuroimaging*, vol. 328, p. 111582, 2023.
- [10] K. Zhao, B. Duka, H. Xie *et al.*, "A dynamic graph convolutional neural network framework reveals new insights into connectome dysfunctions in ADHD," *Neuroimage*, vol. 246, p. 118774, 2022.
- [11] D. M. Low, K. H. Bentley, and S. S. Ghosh, "Automated assessment of psychiatric disorders using speech: A systematic review," *Laryngoscope Investigative Otolaryngology*, vol. 5, pp. 96 – 116, 2019.
- [12] A. McPherson and C. Martin, "A narrative review of the beck depression inventory (BDI) and implications for its use in an alcohol-dependent population," *Journal of Psychiatric and Mental Health Nursing*, vol. 17, no. 1, pp. 19–30, 2010.
- [13] N. Cummins, S. Scherer, J. Krajewski et al., "A review of depression and suicide risk assessment using speech analysis," *Speech Communication*, vol. 71, pp. 10–49, 2015.
- [14] S. Li, R. Nair, and M. Naqvi, "Acoustic and text features analysis for adult ADHD screening: A data-driven approach utilizing DIVA interview," *IEEE Journal of Translational Engineering in Health and Medicine*, 2024.
- [15] M. Niu, J. Tao, B. Liu, and C. Fan, "Automatic depression level detection via lp-norm pooling," *Interspeech*, pp. 4559–4563, 2019.
- [16] M. Niu, J. Tao, B. Liu, J. Huang, and Z. Lian, "Multimodal spatiotemporal representation for automatic depression level detection," *IEEE Transactions on Affective Computing*, 2020.
- [17] M. Niu, B. Liu, J. Tao, and Q. Li, "A time-frequency channel attention and vectorization network for automatic depression level prediction," *Neurocomputing*, vol. 450, pp. 208–218, 2021.
- [18] S. Li, R. Nair, and S. M. Naqvi, "Detecting ADHD from speech using full-band and sub-band convolution fusion network," *IEEE Sensors*, 2023.

- [19] M. Valstar, B. Schuller, M. Pantic et al., "AVEC 2014: 3d dimensional affect and depression recognition challenge," *Proceedings of the ACM International Workshop on Audio/Visual Emotion Challenge*, pp. 3–10, 2014.
- [20] M. G. A. Zulfiqar and A. Mohammed, "An automatic health monitoring system for patients suffering from voice complications in smart cities," *IEEE Access*, vol. 5, pp. 3900–3908, 2017.
- [21] Y. Li, Y. Sun, W. Wang, and S. M. Naqvi, "U-shaped transformer with frequency-band aware attention for speech enhancement," *Transactions* on Audio, Speech, and Language Processing, 2023.
- [22] Y. Liu, Y. Song, I. McLoughlin *et al.*, "An effective deep embedding learning method based on dense-residual networks for speaker verification," *ICASSP*, pp. 6683–6687, 2021.
- [23] J. Han, Y. Long, L. Burget, and J. Černocký, "Dpccn: Densely-connected pyramid complex convolutional network for robust speech separation and extraction," *ICASSP*, pp. 7292–7296, 2022.
 [24] Y. Li, S. Li, C. Nash, S. M. Naqvi, and R. Nair, "24 intelligent sensing
- [24] Y. Li, S. Li, C. Nash, S. M. Naqvi, and R. Nair, "24 intelligent sensing in ADHD trial ISAT-pilot study," *Journal of Neurology, Neurosurgery* and Psychiatry, vol. 94, p. 2, 2023.
- [25] R. C. Kessler, L. Adler, M. Ames *et al.*, "The world health organization adult ADHD self-report scale (ASRS): a short screening scale for use in the general population," *Psychological medicine*, vol. 35, no. 2, pp. 245–256, 2005.
- [26] J. J. S. Kooij and M. Francken, "Diagnostic Interview for ADHD in adults (DIVA 2.0)," 2010.
- [27] Z. Zhao, Q. Li, B. Schuller *et al.*, "Hybrid network feature extraction for depression assessment from speech," *Interspeech*, pp. 4956–4960, 2020.
- [28] A. software is copyright (c) 1999-2016 Audacity Team. The name Audacity is a registered trademark of Dominic Mazzoni.
- [29] S. Li, Y. Sun, R. Nair, and S. M. Naqvi, "Enhancing ADHD detection using DIVA interview-based audio signals and a two-stream network," *IEEE International Performance Computing and Communications Conference*, 2023.
- [30] V. Jain, J. L. Crowley, A. K. Dey *et al.*, "Depression estimation using audiovisual features and fisher vector encoding," pp. 87–91, 2014.
- [31] A. Jan, H. Meng, Y. F. B. A. Gaus, and F. Zhang, "Artificial intelligence system for automatic depression level analysis through visual and vocal expressions," *IEEE Transactions on Cognitive and Developmental Systems*, vol. 10, no. 3, pp. 668–680, 2017.
- [32] L. He and C. Cao, "Automated depression analysis using convolutional neural networks from speech," *Journal of Biomedical Informatics*, vol. 83, pp. 103–111, 2018.
- [33] A. Othmani, D. Kadoch, K. Bentounes, H. Abdenou *et al.*, "Towards robust deep neural networks for affect and depression recognition from speech," pp. 5–19, 2021.
- [34] M. R. Makiuchi, T. Warnita *et al.*, "Speech paralinguistic approach for detecting dementia using gated convolutional neural network," *Transactions on Information and Systems*, vol. 104, pp. 1930–1940, 2021.
- [35] N. Shivhare, S. Rathod, and M. Khan, "Automatic speech analysis of conversations for dementia detection using LSTM and GRU," 2021 International Conference on Computational Intelligence and Computing Applications, pp. 1–7, 2021.
- [36] W. Zeng, Y. Guo, G. He, and J. Zheng, "Research and implementation of an improved CGRU model for speech emotion recognition," *International Conference on Control and Intelligent Robotics*, pp. 778–782, 2022.