Re-examining Granger Causality from Causal Bayesian Networks Perspective

Adedayo, S. A. [https://orcid.org/0000-0003-2990-142X]1

¹UniVie Doctoral School of Computer Science, University of Vienna, Austria

Abstract

Characterizing cause-effect relationships in complex systems could be critical to understanding these systems. For many, Granger causality (GC) remains a computational tool of choice to identify causal relations in time series data. Like other causal discovery tools, GC has limitations and has been criticized as a non-causal framework. Here, we addressed one of the recurring criticisms of GC by endowing it with proper causal interpretation. This was achieved by analyzing GC from Reichenbach's Common Cause Principles (RCCPs) and causal Bayesian networks (CBNs) lenses. We showed theoretically and graphically that this reformulation endowed GC with a proper causal interpretation under certain assumptions and achieved satisfactory results on simulation.

Keywords: Granger Causality, CSL, time series, CBNs, RCCP

1 Introduction

The emergence of machine learning (ML) has been phenomenal, with ML-based models outperforming human intelligence, as in the case of AlphaGo [1] and, more recently, large language models (LLMs). With these advances, ML became state-of-the-art for scientific discovery in various fields of study [2]. However, ML algorithms fail to answer the crucial question "what" brings about an effect and "what if" questions i.e., ML cannot identify causal relationships in data and counterfactual questions. Hence, the need for causality and causal inference—a field that focuses on unravelling causal interactions in data.

Characterising these interactions in complex dynamical systems is a fundamental question in science [3]. Causal structure learning (CSL)—a computational causal discovery field, taking advantage of statistics and machine learning (ML) to unravel causal relations in data—is particularly appealing because it enables us to answer counterfactual questions [4, 5, 6, 7].

We adopt Pearl's causality framework. [8] defines a causal relation between two variables X and Y if any manipulation on X has a direct effect on Y. Causal relationships are governed by structural equations such that $X_i = f_i(Pa(X_i), U_i)$, where Pa. are the parent variables of X_i , and f_i is any deterministic function, and U_i is an unobserved noise term. Causal inference is performed by interventions, formalized as the do-calculus operator do(X = x), which fixes a variable X to a desired value x, thus allowing estimation of causal effects while adjusting for confounders [8].

The main contribution of this work is the endowment of the Granger causality framework with causal reasoning solely on theoretical groundings. This revision birthed an algorithm. The paper's outline is as follows: Section 1 introduces causal discovery and its trends over the years. Section 2 overviews CSL in observational datasets and formalises Granger's causality and Reichenbach's common cause principles (RCCPs) and causal Bayesian networks (CBNs). Section 3 built on the intuitions from Section 2, and interpreted GC from CBN perspectives as conditional (in)dependence tests, presented our proposed fix as an algorithm and presented results on simulation data. Finally, section 4 concludes the paper.

2 Background

We introduce the reader to the essential framework that builds up to this work. The available algorithms in CSL are categorized into constraint- and score-based, and hybrid methods [9] although much of the focus has been on constraint- and score-based methods [10]. [11, 12] reviewed some popular available CSL algorithms. While our introduction is concise, we refer the reader to the referenced materials for in-depth introductions.

2.1 Granger Causality

Granger causality (GC) is a computational tool for causal discovery in many fields ranging from econometrics to neuroscience. Despite its various criticisms, being a predictive tool, i.e., non-causal, and its susceptibility to latent confounders. [13, 14] presented a computational tool to infer causal relations from time series data. He postulated that a time series X^i Granger causes another time series X^j if the inclusion of the pasts of X^i and X^j in the predictive model has a better prediction than that obtained using only the past of X^j . This can be formalized mathematically as follows;

$$X^{i} \xrightarrow{GC} X^{j} = var \left[X^{j}_{t} - \hat{X}^{j}_{t} \middle| X^{j}_{0:t-\tau} \right] > var \left[X^{j}_{t} - \hat{X}^{j}_{t} \middle| X^{j}_{0:t-\tau}, X^{i}_{0:t-\tau} \right]$$
(1)

where τ is a lag parameter

An F-Test in equation 2 was adopted to determine the model significance. RSS_{full} , computed residual sum of the square of the full model, which uses pasts of both variables in question and RSS_{red} , the residual sum of the square of the reduced or self-prediction model, which uses only the past states of the variable to be predicted. $p_2 - p_1$ and $n - p_2$ are both degrees of freedom. n is the number of data points, p_1 and p_2 are number of parameters of models RSS_{red} and RSS_{full} , respectively. Note $p_2 > p_1$.

$$F = \frac{RSS_{red} - RSS_{full}/(p_2 - p_1)}{RSS_{full}/(n - p_2)}$$
(2)

Several extensions to GC have been proposed over the years ranging from linear to non-linear domains [15, 16, 17, 18, 19]. [19], a linear extension to GC in time-domain time series and proposed an F-test (equation 3) to assess the significance of models with the other variable's pasts in the prediction to infer links.

$$F_{X^{i} \xrightarrow{GC} X^{j}} = ln \frac{\left| var\left(X_{t}^{j} - \hat{X}_{t}^{j^{(r^{i})}} \right) \right|}{\left| var\left(X_{t}^{j} - \hat{X}_{t}^{j^{(f)}} \right) \right|}$$
(3)

Granger developed both bivariate and multivariate Granger causality. Bivariate Granger causality (BVGC) is limited to two variables, examining the reduction in prediction variance of a variable X^i from its past and that of another variable X^j . If the prediction variance is significantly lower compared to that obtained using only the pasts of X^i , then X^j is said to *Granger cause* X^i . Multivariate Granger causality extends this concept to multivariate datasets. This approach attempts to control for indirect effects and spurious relationships [14, 20].

Granger causality obeys the time causality and the slight time difference (Δt) between the cause and effect, hence GC order (lag parameter τ), for determining connections between a cause and effect. Numerous implementations and/or extensions to GC exist [21, 22, 23, 24, 25, 26, 27] aiming to circumvent the limitations of GC. To date, GC is still being criticised for not being causal. Here, we propose a fix to one of GC's major criticisms—associational link inference. We came by this solution by re-examining Granger's framework from a causal Bayesian networks (CBNs) perspective.

Granger understands his framework does not reveal the true causal structure [28], but claimed that under some assumptions, predictability of a variable by another can imply a mechanistic cause-effect relationship, hence *predictability implies causality*. In this work, we examined GC from CBN's perspective. We identified GC's failure to identify associational dependence. We solved this problem with Reichenbach's common cause principles. We likened the principles to the two GC cases - bivariate and multivariate- and devised a means to infer more causally stable inferences from data.

2.2 Reichenbach's Common Cause Principles

Reichenbach introduced the common cause principle (RCCP) in [29] and defined the importance of time in causation. The introduction of time only sounds logical as no effect happens before its cause in all physical systems. For a more extensive read on RCCP, we refer readers to [30]. Reichenbach uses probability measure to define (in)dependency. Events A and B are dependent *iff* their joint probability is greater than the product of their marginals (equation 4). Looking more in-depth, if neither of the variables is the cause or effect, but 4 still holds, [29] postulated that the two variables must have a common cause, occurring earlier, thus inducing some associational relation between the two variables. This third variable could render the pair conditionally independent. Reichenbach found the connection between probabilistic measure and causation. RCCP has been regarded as the basis of the Causal Markov Condition. Reichenbach formulated the following principles depicted in 4 to 8 for the (in)dependency of any two variables.

We denote the marginal probabilities of any variables A and B as P(A) and P(B), and their joint probability is denoted by P(A, B). In contrast, a conditional joint probability is written as P(A, B|C). Equation 4 denotes dependency between variables A and B; in other terms, unconditional dependency is equivalent to bivariate Granger causality. On the other hand, equations 5 through 8 defines conditional (in)dependency of variables A and B where C and C' are the conditioning set of variables, and the absence of this conditioning set denoting the multivariate Granger causality. In Reichenbach's principle, a link between any two variables exists if and only if equations 4 - 8 are satisfied.

$$P(A,B) > P(A).P(B) \tag{4}$$

$$P(A, B|C) = P(A|C).P(B|C)$$
(5)

$$P(A, B|C') = P(A|C').P(B|C')$$
(6)

$$P(A|C) > P(A|C') \tag{7}$$

$$P(B|C) > P(B|C') \tag{8}$$

2.3 Causal Bayesian Networks (CBNs)

CBN is a specific aspect of probabilistic graphical models (PGMs) that explicitly model causal relationships in data. CBNs are often interchangeably used with *causal graphical models*, which stem from Bayesian networks. In Bayesian networks, a joint distribution of variables contained in data, say $P(X_1, X_2, ..., X_n)$ can be modelled as a chain rule define in equation 9

$$P(X_1, X_2, ..., X_n) = P(X_1) \prod_{i} P\left(X_i \middle| X_{i-1}, ..., X_1\right)$$
(9)

Working with equation 9 requires an exponential number of parameters. Hence, an efficient way is to model each variable in the joint distribution with its local dependencies. This factorizes the probability distribution according to the dependencies, reducing the number of parameters to be computed as shown in the equation 10. This is achievable due to an assumption called *local Markov assumption*. This factorization is termed the chain rule for Bayesian networks. $Pa(\cdot)$ is an operator describing the parent(s) or group of variables directly influencing a variable.

$$P(X_1, X_2, \dots, X_n) = \prod_i P\left(X_i \middle| Pa(X_i)\right)$$
(10)

These cause-effect relationships in CBNs are denoted as graphs \mathcal{G} . These graphs summarise the connectivity matrix of the joint distribution $P(\mathcal{X})$. Nodes denote the variables, and edges show the variables' interactions. The edges are usually directed, showing which variables are *causes* and which are *effects*. According to Bayesian Network Factorization, $P(\mathcal{X}) = \prod_{i=1}^{n} P(X^i | Pa(X^i))$.

The concept of acyclicity in complex systems' causal graphs may not necessarily be the most efficient. An example is the biological brain, in which neurons are interconnected in no particular order or rules and with humongous feedback loops. With such interwoven connectivities, enforcing acyclicity, as assumed by many CSL algorithms on such datasets, may be inefficient. More so, the possibilities of bi-directionality in such a network should not be undermined. In our proposition, we neither enforce nor punish acyclicity and bi-directionality.

In CBN, we can interpret GC as a conditional independence test. This means testing for statistical (in)dependence between the residuals $\epsilon_{X_{t-\tau}^i}$ and $\epsilon_{X_t^j}$. Residuals $\epsilon_{X_{t-\tau}^i}$ and $\epsilon_{X_t^j}$ are a result of regressing the conditioning set Z, which is the pasts of the state predictors up to the chosen lag value, where;

$$\epsilon_{X_{t-\tau}^i} = X_{t-\tau}^i \left| \left[X_{t-\tau+n}^i, X_{t-(n+1)}^j \right] \right|$$
(11)

$$\epsilon_{X_t^j} = X_t^j \left| \left[X_{t-\tau+n}^i, X_{t-(n+1)}^j \right]$$
(12)

If there exists a statistically significant dependence between the two residuals, then we say $X_{t-\tau}^i \longrightarrow X_t^j$ where n is the number of pasts considered for the test.

This can be illustrated graphically as shown in Figure 1.



Figure 1: GC interpretation in CBN as conditional (in)dependence test. Figure 1a depicts conventional GC using the pasts of $X_{t-1}^i(i.e.\tau = 1$ in this analogy) and X_t^j , both marked green to depict pairs of interest and dashed green arrow showing the dependence test. This, in CBN, as shown in Figure 1b, is interpreted as a conditional (in)dependence test by conditioning on the pasts of both X_{t-1}^i and X_t^j . The red-shaded states are the states in the conditioning sets.

3 Our Solution

A major limitation after formalising the Granger Causality framework is that its inferences are not causal. Here, we propose a fix to this problem, thus enabling the GC inferred structure to be causal. We introduced the reader to Causal Bayesian Networks (CBNs), highlighted our propositions and illustrated them with examples. We refer the reader to [8, 31] for a more extensive introduction to CBNs.

For simplicity, we denote a multivariate time series data as $\mathcal{X} \simeq \{X_{t-\tau}, \ldots, X_t\}, t \in \mathcal{T}$ where \mathcal{T} is an index set of timesteps, with $X_t = \{X_t^1, X_t^2, X_t^3\}$ for all $t \in \tau$: τ is the time difference of information flow from

cause to effect. For illustration, we consider multivariate data \mathcal{X} with three (3) variables as it enables us to illustrate all three building blocks (chains, forks and colliders) of CBN. For the sake of this illustration, we denote all other variables in the world that might be contained in a multivariate dataset with X^3 . We will use this to interpret GC from a causal perspective. Note that any number of variables is possible in multivariate data, but we have summarised the other variables into X^3 . The following paragraphs formalize BVGC and MVGC; afterwards, we propose our solution:

• Bivariate Granger Causality (BVGC) tests the association between two variables, say X^1 and X^2 by comparing the variance between the predictions and the target resulting from using pasts of both variables compared to using only the past of the predictor variable without taking account the possible effect of other variables (possible confounders) in the data. Since a *cause* must precede its *effect*, a lag parameter τ defining the order of the GC translates to checking for associational (in)dependency between previous states of $X^1_{t-\tau}$ and the present state of the other. Equation 13 formalises BVGC, where k is the number of pasts considered after τ .

$$X_{t-\tau}^1 \xrightarrow{?} X_t^2 | X_{t-(\tau+1)}^1, X_{t-1:t-\tau}^2$$

$$\tag{13}$$

• Multivariate Granger Causality (MVGC) only tests for conditional (in)dependency of any variable pair controlling for all other variables in the data. It uses combinations of vector auto-regressive (VAR) models from all other variables up to a selected lag parameter.

$$X_{t-\tau}^{1} \xrightarrow{?} X_{t}^{2} | X_{t-(\tau+1)}^{1}, X_{t-1:t-\tau}^{2}, X_{t:t-\tau}^{3}$$
(14)

From the above analogies, a combination of dependencies from both propositions 1 and 2 must hold in other to infer a causal link between two variables. The propositions are as follows:

Proposition 1: Unconditional dependence between any variable pair must hold.

$$X_{t-\tau}^{i} \not\perp X_{t}^{j} \tag{15}$$

Illustration: BVGC tests pairwise (in)dependency between two variables without considering the effect of confounders. Equation 13 is generalized and simplified into equation 15 by removing the conditioning. This removal can be justified by a few reasons: if the variable pair are indeed dependent, adding more information to the regression model can be redundant and make the model more complex. This will hold as the dependence between the variable pair would be enough without requiring more information from the previous states if the system is a physical system¹. Removing the conditioning set also improves runtime. BVGC inferred links are not always causal due to a lack of consideration for confounders. However, it is very vital in detecting (in)dependence of two variables as it helps us fulfil equation 4.

Example: Given any two time series $X_{t-\tau}^i$ and X_t^j , $\{i, j \in V\}$. Assume $X_{t-\tau}^i$ is statistically independent of X_t^j , (i.e. $X_{t-\tau}^i \perp X_t^j$). Thus, $X_{t-\tau}^i$ and X_t^j cannot be causal (i.e. $X_{t-\tau}^i \nleftrightarrow X_t^j$).

Proposition 2: Conditional dependence given all other variables between any variable pair must hold.

$$X_{t-\tau}^{i} \not\sqcup X_{t}^{j} | Z \tag{16}$$

Illustration: MVGC tests pairwise (in)dependency between two variables given all other variables in the dataset as described in equation 14. The conditioning set Z includes the pasts of the variable pair in question and that of all other variables.

¹Physical systems are characterised as Markov [32]

Example: Given the same multivariate datasets used above, for any two variables of interest, say $X_{t-\tau}^i$, X_j^t and Z being the remainder of the variables in the data which could be a potential collider or common cause of variable pair in question. where $Z = X_{t-\tau-k}^1, X_{t-1:t-\tau-k}^2, X_{t:t-\tau-k}^3$.

Proposition 3: Combining² propositions 1 and 2 enforces all RCCPs and reveals only true causal links.

$$\left(X_{t-\tau}^{i} \not\!\!\perp X_{t}^{j}\right) \wedge \left(X_{t-\tau}^{i} \not\!\!\perp X_{t}^{j} \middle| Z\right)$$

$$(17)$$

Illustration: Taking the logical-and of the binarized inference from both unconditional and conditional dependence test satisfactorily enforced all Reichenbach's principles. BVGC, on its own, will infer more connections as we do not condition on possible confounders, which leads to inferring spurious links. On the other hand, MVGC would reveal some of these connections from BVGC are not true connections and weed them out. However, MVGC would also infer spurious connections when colliders are conditioned on; in turn, BVGC would have detected and failed to infer. Hence, the *logical-and* operation on results of both BVGC and MVGC gives rise to a true causal connectivity matrix.

Table 1 summarizes our illustrations via logical examples for the three building blocks in CBN. We design the examples such that the time causality is obeyed. The true DAG column shows the assumed ground truth, and the Variables in red are the observed variables in the MVGC. The green statements are the wrongly inferred dependency (false positives color coded as green). Dependency is bi-directional. Hence, we wrote dependency statements in the causal directions. Blue texts show the correct and expected links that hold, and the missing inference occurred as a failure of the two cases passing the dependency tests.

- 1. Chains: Chains describe a variable causing another, which in turn causes another. In our example, associational flow of information through X_{t-1}^3 will facilitate BVGC to wrongly infer a direct link between X_{t-2}^1 and X_t^2 $(X_{t-2}^1 \not \perp X_t^2)$. However, testing the same link with MVGC will be able to detect the spurious link inferred by BVGC hence, revealing X_{t-2}^1 and X_t^2 are not dependent $(i.e., X_t^2 \perp X_{t-2}^1 | X_{t-1}^3)$
- 2. Forks: Forks describes the case of a common cause or confounder. Like chains, they belong to the same Markov equivalence class (MEC), i.e. shares the same set of conditional independence statements. We assumed X_{t-1}^3 is a common cause of both X_t^1 and X_t^2 as shown in Figure 1c. X_{t-1}^3 induces dependency between X_t^1 and X_t^2 by constantly dictating the events of both X_t^1 and X_t^2 over time. This enables BVGC to infer a link between the two as both will be a better predictor of the other, hence $(X_{t-2}^1 \not \downarrow X_t^2)$. In contrast, deploying MVGC conditions on the common cause X_{t-1}^3 thereby rendering X_t^1 and X_t^2 conditionally independent $(i.e., X_t^1 \perp X_t^2 | X_{t-1}^3)$.
- 3. **Collider:** Colliders are a special case and do not share MEC. Testing for a link between X_{t-1}^1 and X_{t-1}^2 while observing X_t^3 (i.e., $X_{t-1}^1 \xrightarrow{?} X_{t-1}^2 | X_t^3$), as in the case of MVGC. We reveal a direct link between X_{t-1}^1 and X_{t-1}^2 . This link, however, is not valid (false positive) but was induced by association flow via X_t^3 we conditioned on. In contrast, BVGC will show no link because the two variables are marginally independent, i.e., $P(X_{t-1}^1, X_{t-1}^2) = P(X_{t-1}^1)P(X_{t-1}^2)$. Deploying BVGC to test dependence between X_{t-1}^1 and X_{t-1}^2 will reveal X_{t-1}^1 and X_{t-1}^2 are independent (i.e., $X_{t-1}^1 \perp X_{t-1}^2$). On the other hand, conditional dependence test (MVGC) will wrongly infer a link as a result of conditioning on X_t^3 ($X_{t-1}^1 \not \perp X_{t-1}^2 | X_t^3$).

Technically, proposition 1 helps detect colliders, also known as Y- or V- structures, which MVGC would wrongly infer, while proposition 2 detects associational dependence in both chains and Forks.

 $^{^2 \}mathrm{Combination}$ operation using the logical-and symbolized as \wedge

Table 1: Illustrating BVGC and MVGC expected results on data and how our proposition identifies true causal links. False positives are depicted in green, blue indicates correctly identified links (i.e., true positives), and the red variables indicate conditioned variables.

True DAG	BVGC	MVGC	Inferences
Chain			
$X_{t-2}^1 \longrightarrow X_{t-1}^3 \longrightarrow X_t^2$	$X^1_{t-2}\not\!\!\perp X^2_t$	$X_{t-2}^1 \perp \perp X_t^2 \mid X_{t-1}^3$	
	$X^3_{t-1} \not\!\!\perp X^2_t$	$X_{t-1}^3 \not\!\!\perp X_t^2 \mid X_{t-2}^1$	$X^3_{t-1} \longrightarrow X^2_t$
	$X_{t-2}^1 \not\!\!\perp X_{t-1}^3$	$X_{t-2}^1 \not\!\!\perp X_{t-1}^3 \mid X_t^2$	$X^1_{t-2} \longrightarrow X^3_{t-1}$
Forks			
$X^1_t \longleftarrow X^3_{t-1} \longrightarrow X^2_t$	$X^2_t \not\!\!\perp X^1_t$	$X_t^2 \perp\!\!\!\perp X_t^1 \mid X_{t-1}^3$	
	$X^3_{t-1} \not\!\!\perp X^2_t$	$X_{t-1}^3 \not\!\!\perp X_t^2 \mid X_t^1$	$X^3_{t-1} \longrightarrow X^2_t$
	$X^3_{t-1} \not\!\!\perp X^1_t$	$X^3_{t-1} \not\!\!\perp X^1_t \mid X^2_t$	$X^3_{t-1} \longrightarrow X^1_t$
Colliders			
$X_{t-1}^1 \longrightarrow X_t^3 \longleftarrow X_{t-1}^2$	$X_{t-1}^1 \perp \!\!\!\perp X_{t-1}^2$	$X_{t-1}^1 \not\!\!\perp X_{t-1}^2 \mid X_t^3$	
	$X_{t-1}^2 \not\!\!\perp X_t^3$	$X_{t-1}^2 \not\!\!\perp X_t^3 \mid X_{t-1}^1$	$X_{t-1}^2 \longrightarrow X_t^3$
	$X_{t-1}^1 \not\!\!\perp X_t^3$	$X_{t-1}^1 \not\!\!\perp X_t^3 \mid X_{t-1}^2$	$X^1_{t-1} \longrightarrow X^3_t$

Following these illustrations, we can see variations in the results obtained in both GC cases. BVGC and MVGC did brilliantly well, complementing each other's shortcomings. In the case of the true causal links, both BVGC and MVGC fulfil both propositions 1 and 2, hence the discovery of true causal links (in colour blue in the inferences column). In larger datasets with more than three variables, it is logical to see that true causal links can be inferred when propositions 1 and 2 are fulfilled. With this establishment, we then introduce our algorithm.

3.1 The Algorithm

We formalise the above-discussed propositions into an algorithm³ Given a multivariate time series dataset X. GC analysis parameters, i.e., GC order (lags parameter), F-Test and statistical significance level (α), can be chosen based on the researcher's data intuition.

Let the lag parameter be denoted as τ , n, the number of variables and \hat{A} , the inferred matrix.

 $^{^{3}}$ It is advised to run BVGC and MVGC in parallel to improve runtime speed, as the two operations are independent of one another.

Function c-GC

 $\begin{array}{l} \textbf{Input: } data, \tau \\ \textbf{X} \leftarrow shiftdata(data, \tau) \\ m, n \leftarrow \textbf{X}.shape[0], \ data.shape[0] \quad \#m := n * \tau + 1 \\ \textbf{for } i \rightarrow m \ \textbf{do} \\ & \left| \begin{array}{c} \textbf{for } j \rightarrow n \ \textbf{do} \\ & \left| \begin{array}{c} A_{BVGC}^{i,j} & \leftarrow \text{BVGC}(\textbf{X}^{i},\textbf{X}^{j}) \\ & A_{MVGC}^{i,j} & \leftarrow \text{MVGC}(\textbf{X}^{i},\textbf{X}^{j} \middle| Z) \end{array} \right. \#Z := \textbf{X} \setminus \begin{bmatrix} \textbf{X}^{i}, \textbf{X}^{j} \end{bmatrix} \\ \textbf{end} \\ \textbf{end} \\ \hline A \leftarrow A_{BVGC} & \land \ A_{MVGC} \\ \textbf{Output: } \hat{A} \end{array}$

Assumptions We denote the true graph \mathcal{G} that generates data \mathcal{X} . The assumptions we make for this algorithm are as follows:

- Causal sufficiency implies that all causes and effects are contained in the \mathcal{X} . This is emphasizing the absence of unobserved variables.
- Faithfulness: All conditional (in)dependence in graph \mathcal{G} are implied by its causal structure, indicating that causal structure fulfils the causal Markov assumption coined from RCCP.

3.2 Experiment

We simulated data with an autoregressive model (ARM) with a known ground truth matrix A_{τ} : $\tau = 1, 2, 3$ dictating connections in the time series data simulation. A total of n = 30 and $\mathcal{T} = 5000$ and $\tau = 3$ samples were simulated with connectivities randomly varying between a lag of 1 and 3. This indicates that A combines several connectivity matrices A_1 to A_3 . For the scope of this paper, we do not investigate whether the granularity of connection time steps is detected but rather focus on the overall inference \hat{A} .

Equation 18 formalises the simulation in mathematical expression;

$$X_{t+1}^{i} = X_{t}^{i} + \sum_{X^{j} \in Pa(X^{i})} A_{\tau}^{i,j} X_{t}^{j} + \epsilon_{t+1}^{i}$$
(18)



Figure 2: Simulated data

Ground truth connectivity matrix A combines all A_{τ} at all τ . A can contain latent variables and cycles to replicate the chaotic connectivity structure of a complex system such as a biological brain. ϵ indicates

a time-correlated non-Gaussian additive noise imposed on each variable in the data. Figure 2a shows the simulated time series before the additive noise (Figure 2b) was imposed on each time series. Figure 3a shows the ground truth, and Figure 3b depicts the inferred matrix.



Figure 3: Side by side view of ground truth matrix A and inferred matric \hat{A}

The obtained result from the analysis is satisfactory. The algorithm was able to almost all links (i.e. true positives (TP)) colour-coded yellow in figure 3b but three (3) true negatives (TN).

4 Conclusions

In this work, we presented a new method of estimating Granger causality to solve one of its significant criticisms of not being causal but rather a predictive tool. Our approach leveraged the causal Bayesian network and interpreted GC as conditional independence tests. Taking the *logical-and* operation on both BVGC and MVGC results will solve the criticism of GC being only predictive. A notable point, however, is that this framework has not solved the latent confounder problems of GC. However, we present a method to enhance the GC inferred connectivity matrix to be considered fully causal. Our simulation experiments indicated that this method is efficient with its ability to unravel cycles in structures.

Acknowledgements

We want to acknowledge Dean Rance for their vital discussions. We also want to thank the Zebrafish Neuroscience Interdisciplinary Training Hub (ZENITH) under the Marie Skłodowska-Curie Actions grant agreement #813457 for funding this study.

References

- David Silver et al. "Mastering the game of go without human knowledge". In: nature 550.7676 (2017), pp. 354–359.
- Yolanda Gil et al. "Amplify scientific discovery with artificial intelligence". In: Science 346.6206 (2014), pp. 171–172.
- [3] Oliver M Cliff et al. "Unifying Pairwise Interactions in Complex Dynamics". In: arXiv preprint arXiv:2201.11941 (2022).
- [4] Tadeg Quillien and Christopher G Lucas. "Counterfactuals and the logic of causal selection". In: (2022).
- [5] Jonas Peters, Dominik Janzing, and Bernhard Schölkopf. *Elements of causal inference: foundations and learning algorithms*. The MIT Press, 2017.
- [6] Léon Bottou et al. "Counterfactual Reasoning and Learning Systems". In: CoRR abs/1209.2355 (2012). arXiv: 1209.2355. URL: http://arxiv.org/abs/1209.2355.

- [7] Daphna Buchsbaum et al. "The power of possibility: Causal learning, counterfactual reasoning, and pretend play". In: *Philosophical Transactions of the Royal Society B: Biological Sciences* 367.1599 (2012), pp. 2202–2212.
- [8] Judea Pearl et al. "Models, reasoning and inference". In: *Cambridge, UK: CambridgeUniversityPress* 19.2 (2000), p. 3.
- Ehsan Mokhtarian et al. "A Recursive Markov Blanket-Based Approach to Causal Structure Learning." In: arXiv preprint arXiv:2010.04992 (2020).
- [10] Nandini Ramanan and Sriraam Natarajan. "Causal learning from predictive modeling for observational data". In: *Frontiers in big Data* 3 (2020), p. 535976.
- [11] Christina Heinze-Deml, Marloes H Maathuis, and Nicolai Meinshausen. "Causal structure learning". In: Annual Review of Statistics and Its Application 5 (2018), pp. 371–391.
- [12] Daniel Chicharro and Stefano Panzeri. "Algorithms of causal inference for the analysis of effective connectivity among brain regions". In: *Frontiers in neuroinformatics* 8 (2014), p. 64.
- [13] Clive WJ Granger. "Some recent development in a concept of causality". In: Journal of econometrics 39.1-2 (1988), pp. 199–211.
- [14] Clive WJ Granger. "Investigating causal relations by econometric models and cross-spectral methods". In: Econometrica: journal of the Econometric Society (1969), pp. 424–438.
- [15] Yonghong Chen et al. "Analyzing multiple nonlinear time series with extended Granger causality". In: *Physics letters A* 324.1 (2004), pp. 26–35.
- [16] Nicola Ancona, Daniele Marinazzo, and Sebastiano Stramaglia. "Radial basis function approach to nonlinear Granger causality of time series". In: *Physical Review E* 70.5 (2004), p. 056221.
- [17] David Bell, Jim Kay, and Jim Malley. "A non-parametric approach to non-linear causality testing". In: Economics Letters 51.1 (1996), pp. 7–18.
- [18] Gary Chamberlain. "The general equivalence of Granger and Sims causality". In: Econometrica: Journal of the Econometric Society (1982), pp. 569–581.
- [19] John Geweke. "Measurement of linear dependence and feedback between multiple time series". In: Journal of the American statistical association 77.378 (1982), pp. 304–313.
- [20] Helmut Lütkepohl. New introduction to multiple time series analysis. Springer Science & Business Media, 2005.
- [21] Ali Shojaie and Emily B Fox. "Granger causality: A review and recent advances". In: Annual Review of Statistics and Its Application 9 (2022), pp. 289–319.
- [22] Xiaowen Chen et al. "Granger causality analysis for calcium transients in neuronal networks: challenges and improvements". In: *bioRxiv preprint* (2022). DOI: 10.1101/2022.06.27.497721.
- [23] Xiaotong Wen, Govindan Rangarajan, and Mingzhou Ding. "Is Granger causality a viable technique for analyzing fMRI data?" In: *PloS one* 8.7 (2013), e67428.
- [24] Halbert White and Xun Lu. "Granger causality and dynamic structural systems". In: Journal of Financial Econometrics 8.2 (2010), pp. 193–243.
- [25] Alex J Cadotte et al. "Granger causality relationships between local field potentials in an animal model of temporal lobe epilepsy". In: *Journal of neuroscience methods* 189.1 (2010), pp. 121–129.
- [26] Michael Eichler and Vanessa Didelez. "On Granger causality and the effect of interventions in time series". In: *Lifetime data analysis* 16.1 (2010), pp. 3–32.
- [27] Cunlu Zou and Jianfeng Feng. "Granger causality vs. dynamic Bayesian network inference: a comparative study". In: BMC bioinformatics 10.1 (2009), pp. 1–17.
- [28] Halbert White, Karim Chalak, and Xun Lu. "Linking granger causality and the pearl causal model with settable systems". In: *NIPS Mini-Symposium on Causality in Time Series*. PMLR. 2011, pp. 1–29.
- [29] Hans Reichenbach. The direction of time. Vol. 65. Univ of California Press, 1956.
- [30] Gábor Hofer-Szabó, Miklós Rédei, and László E Szabó. "On Reichenbach's common cause principle and Reichenbach's notion of common cause". In: *The British Journal for the Philosophy of Science* 50.3 (1999), pp. 377–399.
- [31] Peter Spirtes et al. Causation, prediction, and search. MIT press, 2000.
- [32] Stéphane Attal. "Markov chains and dynamical systems: the open system point of view". In: arXiv preprint arXiv:1010.2894 (2010).