Steering Flexible Linear Objects in Planar Environments by Two Robot Hands Using Euler's Elastica Solutions

A. Levin¹ and E. D. Rimon¹ and A. Shapiro²

Abstract—The manipulation of flexible objects such as cables, wires and fresh food items by robot hands forms a special challenge in robot grasp mechanics. This paper considers the steering of flexible linear objects in planar environments by two robot hands. The flexible linear object, modeled as an elastic nonstretchable rod, is manipulated by varying the gripping endpoint positions while keeping equal endpoint tangents. The flexible linear object shape has a closed form solution in terms of the grasp endpoint positions and tangents, called Euler's elastica. This paper obtains the elastica solutions under the optimal control framework, then uses the elastica solutions to obtain closed form criteria for non self-intersection, stability and obstacle avoidance of the flexible linear object. The new tools are incorporated into a planning scheme for steering flexible linear objects in planar environments populated by sparsely spaced obstacles. The scheme is fully implemented and demonstrated with detailed examples.

I. Introduction

Robotic manipulation of flexible linear objects such as cables, wires and fresh food items forms a special challenge in robot grasp mechanics. In these problems, one or two robot hands apply endpoint forces and torques that together with external influences such as gravity and contacts with the environment affect the object shape during manipulation. Robotic applications include cable routing and untangling [13, 19, 28], surgical suturing [11, 12], knot tying [30, 29], compliant mechanisms [26], fresh food handling [31], architectural elements fabrication [6] and agricultural robotics [1].

This paper focuses on robotic steering of flexible linear objects in planar environments. The object, modeled as a nonstretchable elastic rod, is to be steered from start to target positions by two robot hands while avoiding self-collision and contact with the environment, except for endpoint contacts at the start or target positions (Fig. 1). Examples of flexible linear objects that can be steered in two-dimensions are strip like objects such as ribbon cables, plastic ties and fresh food items, since such objects preserve their strip flatness during manipulation by two robot hands. This paper provides analysis of flexible linear objects mechanics in two-dimensions, then a scheme for steering such objects based on closed form solutions for their shape and stability that depend only on the gripping hands relative position during manipulation.

Related work: We use the term *flexible cable* for flexible linear objects manipulated in two-dimensions. The modeling of these objects relies on *Euler-Bernoulli bending moment law* [9]. When a flexible cable is held at an equilibrium state by endpoint forces and moments in the plane, the cable curvature at every point is proportional to the cable bending moment



Figure 1. Top view of a flexible cable steered by two robot grippers in a planar environment populated by obstacles. The cable must reach target position while avoiding self-collision and contact with obstacles (except for endpoint contacts at the start or target).

at this point. The coefficient of proportionality is the *cable stiffness* at each point.

The mechanics literature has used the Euler-Bernoulli law to obtain solutions for flexible cable equilibrium shapes in twodimensions [17]. The solutions, called *Euler's elastica*, form a one-parameter family of periodic shapes aligned along a linear axis [16]. The axis is parallel to the opposing forces applied at the cable endpoints and passes through the zero curvature cable points. While flexible cable equilibrium shapes have been fully characterized in the mechanics literature, verification of their stability typically relies on numerical techniques [3, 15]. Sachkov [23, 22, 24] describes analytic bounds for flexible cable stability that are used in this paper's steering scheme.

In the robotics literature, sampling based approaches are used to plan flexible cable steering paths. Moll [18] samples cable endpoint positions, then computes their stable shapes by numerical optimization of the flexible cable total elastic energy. Bretl [7] uses Sachkov's approach to describe the cable total elastic energy minimization as an optimal control problem. Bretl shows that the adjoint differential equation which describes the equilibrium shapes of a flexible cable held by robot hands is fully determined by a small number of *co-state variables* [7]. In 2-D environments these are endpoint forces and moments (three variables) while in 3-D environments these are endpoint forces and toques (six variables).

Using this insight, Bretl developed sampling based planners for steering flexible cables in 2-D and 3-D environments [7]. However, each sampled co-state requires solution of the adjoint differential equation to obtain the cable shape, then computation of the cable co-state to endpoint Jacobian to verify that each sampled cable shape is stable. Sintov [25] extended this work into a two stage approach. First a roadmap of stable cable shapes is computed for sampled co-states. Then a cable

This work receives funding from the European Union's Horizon Europe research and innovation program under grant agreement no. 101070600, project SoftEnable. ¹ Dept. of ME, Technion, Israel. ² Dept. of ME, Ben-Gurion University, Israel.

steering path is computed in the physical environment using numerical self-intersection and obstacle avoidance tests.

While this paper focuses on Euler's elastica as a means to model flexible object shapes, robotic manipulation of heterogeneous flexible objects in agricultural robotics [32] and fresh food handling [31] requires complementary approaches. Papers such as [1], [33] and [14] describe adaptive and learning based approaches to manipulation of such complex flexible objects. One hopes that this paper's modeling approach will become part of adaptive and learning based manipulation techniques for complex flexible objects.

Paper contributions: This paper considers steering flexible cables in two-dimensions using two robot hands. By maintaining equal endpoint tangents, the cable steering problem is reduced to *five configuration variables:* the cable base-frame configuration and the cable endpoints relative position. The paper starts with a derivation of Euler's elastica solutions for flexible cable equilibrium shapes under the optimal control approach. The derivation complements Bretle [7] that focused on the adjoint equation and the use of its co-states to steer flexible cables in 3-D environments. This paper focuses on flexible cable steering in two-dimensions in order to take advantage of the closed form elastica solutions.

When considering flexible cables in 2-D environments, Euler's elastica form periodic shapes aligned with a linear axis. This paper describes analytic equations that determine the cable shape in terms of the cable's relative endpoint positions imposed by the robot hands. The paper next describes the range of the elastica *modulus parameter* that ensures non self-intersection, followed by a simple geometric rule that ensures stability of the flexible cable during steering.

To ensure obstacle avoidance during steering, the paper describes an approximation of the flexible cable equilibrium shapes by quadratic arcs determined by control points located on the cable. The piecewise quadratic approximation allows efficient collision checks against obstacles in the environment. The new tools are incorporated into a fully implemented planning scheme for steering flexible linear objects in planar environments populated by sparsely spaced obstacles.

The paper is structured as follows. Section II derives the flexible cable equilibrium shapes and formulates the flexible cable steering problem. Section III characterizes the non selfintersecting flexible cable shapes. Section IV describes a geometric rule that ensures flexible cable stability during steering. Section V describes an approximation of the flexible cable equilibrium shapes by quadratic arcs. Section VI incorporates these tools into a motion planning scheme that steers flexible cable among sparsely spaced obstacles. Section VII describes execution examples of the steering scheme. The conclusion discusses future research such as gravitational effects and interaction with the environment. An appendix verifies formulas for flexible cable curvature and tangent used in this paper.

II. Euler's Elastica as an Optimal Control Problem

This section obtains the flexible cable equilibrium shapes as an optimal control problem solution. The solution parameters are then related to the cable endpoint positions and the cable steering problem is formulated. Consider a non-stretchable flexible cable of length L in \mathbb{R}^2 . The cable is parametrized by (x(s), y(s)) for $s \in [0, L]$. The cable state variables are its (x(s), y(s)) coordinates and tangent direction $\phi(s)$, thus defining the state vector $S = (x, y, \phi)$. Under arclength parametrization with unit norm tangent, the cable curvature is given by $\kappa(s) = \frac{d}{ds}\phi(s)$. The cable curvature forms a continuous and piecewise smooth control input, $u(s) = \kappa(s)$, for the cable system equations given by

$$\begin{aligned} \dot{x}(s) &= \cos \phi(s) \\ \dot{y}(s) &= \sin \phi(s) \\ \dot{\phi}(s) &= u(s) \end{aligned} \qquad s \in [0, L].$$
(1)

Eq. (1) states that the cable shape, parametrized by arclength, is determined by its curvature as control input. When the flexible cable is modeled as an elastic rod and there are no external influences such as gravity and contacts with the environment, the cable's *total elastic energy* is given by

$$\mathcal{E} = \int_0^L \frac{1}{2} E I \cdot \kappa^2(s) ds \tag{2}$$

where E > 0 is the cable Young's modulus of elasticity and I > 0 is the cable cross-sectional 2'nd moment of inertia [27]. The cable stiffness, EI, is assumed to be a known parameter.

Let two robot hands impose positions and tangents at the flexible cable endpoints, $S(0) = (x(0), y(0), \phi(0))$ and $S(L) = (x(L), y(L), \phi(L))$. The locally stable cable shapes are local minima of \mathcal{E} under the endpoint constraints and the cable fixed length constraint captured by Eq. (1). Since \mathcal{E} represents *bending energy* that grows monotonically with increasing cable curvature (up to plastic yield limit), stable cable shapes always exist when held with fixed endpoint positions and tangents.

The *Hamiltonian* [4, 10] of the cable system defined by Eq. (1) and the elastic energy \mathcal{E} is given by

$$H(S(s), \lambda(s), u(s)) = \lambda_x(s) \cos \phi(s) + \lambda_y(s) \sin \phi(s) + \lambda_\phi(s)u(s) + \frac{1}{2}EI \cdot u^2(s)$$

where $\lambda(s) = (\lambda_x(s), \lambda_y(s), \lambda_\phi(s))$ are the *co-state variables*.
The co-states $(\lambda_x(s), \lambda_y(s))$ and $\lambda_\phi(s)$ represent internal force
and bending moment that develop at the cable points. The en-
ergy extremal cable shapes represent equilibrium states of the
cable held by the robot hands. Along an extremal cable shape,
the vector $\lambda(s)$ is determined by the *adjoint equation* [20]

$$\dot{\lambda}(s) = -\frac{\partial}{\partial S} H(S(s), \lambda(s), u(s)) \qquad S = (x, y, \phi)$$

thus leading to the system of adjoint differntial equations

$$\dot{\lambda}_x(s) = 0$$

$$\dot{\lambda}_y(s) = 0$$
 (3)

$$\lambda_{\phi}(s) = \lambda_x(s) \sin \phi(s) - \lambda_y(s) \cos \phi(s)$$

while the control $u(s) = \kappa(s)$ satisfies the additional condition $\frac{\partial}{\partial s}$

$$\frac{\partial}{\partial u}H(S(s),\lambda(s),u(s)) = 0, \tag{4}$$

thus leading to the algebraic equation $\lambda_{\phi}(s) + EI \cdot u(s) = 0$

(5)

which is the Euler-Bernoulli bending moment law.

From Eq. (3) one obtains that $\lambda_x(s)$ and $\lambda_y(s)$ are constants along energy extremal cable shapes. These constants define the co-state parameters λ_r and ϕ_0

$$\begin{pmatrix} \lambda_x \\ \lambda_y \end{pmatrix} = \lambda_r \cdot \begin{pmatrix} \cos \phi_0 \\ \sin \phi_0 \end{pmatrix} \qquad \lambda_r = \sqrt{\lambda_x^2 + \lambda_y^2}$$



Figure 2. Top view of a flexible cable of length L embedded in its periodic elastica solution. The elastica axis with angle ϕ_0 passes through the elastica zero curvature points and is parallel to the opposing forces of magnitude λ_r applied at the cable endpoints.

which represent the magnitude and direction of the opposing forces applied at the cable endpoints (blue arrows in Fig. 2). The system described by Eq. (1) is autonomous (no terms explicitly depend on s). Hence the Hamiltonian is *constant* along energy extremal cable shapes, $H(s) = H^*$ for $s \in [0, L]$. Substituting $\lambda_{\phi}(s) = -EI \cdot u(s)$ according to Eq. (5) in H(s)and then substituting $u(s) = \kappa(s)$ gives

 $\lambda_r \cdot \left(\cos\phi(s)\cos\phi_0 + \sin\phi(s)\sin\phi_0\right) - \frac{1}{2}EI \cdot \kappa^2(s) = H^*.$ (6) Taking the derivative of both sides with respect to s gives

$$\lambda_r \cdot \left(-\sin\phi(s)\cos\phi_0 + \cos\phi(s)\sin\phi_0\right) - EI \cdot \frac{d}{ds}\kappa(s) = 0 \quad (7)$$

where we canceled the common factor $\kappa(s) = \frac{d}{ds}\phi(s)$. Substituting the system equations $\dot{x}(s) = \cos\phi(s)$ and $\dot{y}(s) = \sin\phi(s)$ into Eq. (6)–(7) gives

$$\lambda_r \cdot \begin{bmatrix} \cos \phi_0 & \sin \phi_0 \\ \sin \phi_0 & -\cos \phi_0 \end{bmatrix} \begin{pmatrix} \dot{x}(s) \\ \dot{y}(s) \end{pmatrix} = \begin{pmatrix} \frac{1}{2} EI \cdot \kappa^2(s) + H^* \\ EI \cdot \frac{d}{ds} \kappa(s) \end{pmatrix}.$$

Integrating both sides, $x(s) = \int_0^s \dot{x}(t)dt$ and $y(s) = \int_0^s \dot{y}(t)dt$, gives the cable (x, y) coordinates in terms of its curvature

$$\begin{pmatrix} x(s) \\ y(s) \end{pmatrix} = \begin{pmatrix} x(0) \\ y(0) \end{pmatrix}$$

+ $\frac{1}{\lambda_r} \begin{bmatrix} \cos \phi_0 & \sin \phi_0 \\ \sin \phi_0 & -\cos \phi_0 \end{bmatrix} \begin{pmatrix} \int_0^s \frac{1}{2} EI \cdot \kappa^2(t) dt + H^* \cdot s \\ EI \cdot (\kappa(s) - \kappa(0)) \end{pmatrix}$ (8)

where $s \in [0, L]$. When a flexible cable is steered with equal endpoint tangents, its equilibrium shapes possess *inflection points*, zero curvature points at which the cable curvature switches sign (Fig. 2). Such cable shapes are called *inflectional elastica*.¹ The curvature of the inflectional elastica is given by an elliptic cosine function of the cable path length parameter [17][p. 402-404]

$$\kappa(s) = -\lambda A \cdot cn \left(\sqrt{\lambda} \cdot (s + s_0), \mathbf{k} \right) \qquad s \in [0, L] \qquad (9)$$

where $cn(\cdot)$ has an *ellipse modulus* 0 < k < 1 discussed below, $\lambda = \lambda_r/EI$, A is an *amplitude parameter* discussed below, and s_0 is a *phase parameter* that is used to locate the cable start point (Fig. 3). Verification that $\kappa(s)$ satisfies the energy extremal conditions of Eqs. (3)-(4) appears in the appendix.



Figure 3. The elastica solutions are characterized by the phase parameter, s_0 , the amplitude parameter, A, and the modulus parameter, 0 < k < 1, determined by $\phi(s^*)$. Note that $A = 2k/\sqrt{\lambda}$, where λ represents the magnitude of the force applied at the cable endpoints.

The elliptic cosine function is a periodic cosine-like function having two zeroes per period [21]. The *elastica axis* shown in Fig. 2 is defined as the line that passes through the elastica inflection points. Some intuition on this axis can be gained by the following observations. In Eq. (8), the term $EI \cdot (\kappa(s) - \kappa(0))$ multiplies the column vector $(\sin \phi_0, -\cos \phi_0)$. Since $\kappa(s)$ is a periodic cosine-like function, ϕ_0 is the elastica axis angle. It also follows from Eq. (8) that the elastica *height* above its axis is $h(s) = A \cdot cn(\sqrt{\lambda} \cdot (s+s_0), k)$ (Fig. 3), which explains the amplitude parameter A.

The geometric meaning of the modulus parameter, k, is based on the cable tangent, $\phi(s)$, which is given in terms of an elliptic sine function, $sn(\cdot)$ (see appendix for verification) $\sin\left(\frac{1}{2}(\phi(s)-\phi_0)\right) = -k \cdot sn(\sqrt{\lambda} \cdot (s+s_0), k) \quad s \in [0, L].$ (10) The elliptic sine function is a periodic sine-like function satisfying $cn^2(u) + sn^2(u) = 1$. It follows from Eqs. (9)-(10) that $sn(\sqrt{\lambda} \cdot (s+s_0), k) = \pm 1$ at the zero curvature points. Substituting this value in Eq. (10) gives

$$k = \left| \sin \left(\frac{1}{2} (\phi(s^*) - \phi_0) \right) \right| \qquad \kappa(s^*) = 0.$$
(11)
The modulus parameter, $0 < k < 1$, thus represents the flexible
cable *incidence angle* with its elastica axis (Fig. 3). This paper

cable *incidence angle* with its elastica axis (Fig. 3). This paper will also use an equivalent parameter that captures the *sign* of the incidence angle, $-1 < \sigma < 1$, defined as

$$\sigma = \cos \left(\phi(s^*) - \phi_0 \right) \qquad \kappa(s^*) = 0$$

where $k^2 = (1 - \sigma)/2$.

Determination of flexible cable shape from endpoint constraints: Let us formulate three equations that capture the flexible cable equilibrium shapes in terms of the endpoint constraints, $S(0) = (x(0), y(0), \phi(0))$ and $S(L) = (x(L), y(L), \phi(L))$. The flexible cable equilibrium shapes will be characterized by three parameters: the co-state λ_r or equivalently $\lambda = \lambda_r / EI$, the elastica modulus parameter k and the phase parameter s_0 .

First consider the parameter H^* in Eq. (8). Since $H(s) = H^*$ for $s \in [0, L]$, the value of H^* can be determined at any point along the cable. At the zero curvature points, $\kappa(s^*) = 0$, Eq. (6) gives

 $H^* = \lambda_r \cdot (\cos \phi(s^*) \cos \phi_0 + \sin \phi(s^*) \sin \phi_0) = \lambda_r \sigma.$ Next consider the amplitude A in Eq. (9). The elastica highest

¹Non-inflectional elastica form spiral-like shapes when held with equal endpoint tangents. Such shapes may be useful in robotic applications, but the current paper focuses on the more common inflectional elastica.

point with respect to its axis occurs at $s = -s_0$, where $s+s_0=0$ and cn(0, k) = 1 (Fig. 3). Substituting $H^* = \lambda_r \sigma$ in Eq. (6), then evaluating H(s) at $s = -s_0$ using the relations $\lambda = \lambda_r / EI$ and $k^2 = (1-\sigma)/2$ gives the amplitude

$$\lambda_r - \frac{1}{2}EI \cdot (\lambda A)^2 = \lambda_r \sigma \Rightarrow A = \frac{2k}{\sqrt{\lambda}}.$$
 (12)

We can now formulate three equations for λ , k and s_0 in terms of the cable endpoint constraints. The cable (x, y) coordinates, Eq. (8), evaluated at s = L give two equations

$$\begin{pmatrix} x(L) \\ y(L) \end{pmatrix} - \begin{pmatrix} x(0) \\ y(0) \end{pmatrix}$$

$$= \frac{1}{\lambda_r} \begin{bmatrix} \cos \phi_0 & \sin \phi_0 \\ \sin \phi_0 & -\cos \phi_0 \end{bmatrix} \begin{pmatrix} \int_0^L \frac{1}{2} EI \cdot \kappa^2(t) dt + (\lambda_r \sigma) \cdot L \\ EI \cdot (\kappa(L) - \kappa(0)) \end{pmatrix}$$

$$= \frac{1}{\lambda} \begin{bmatrix} \cos \phi_0 & \sin \phi_0 \\ \sin \phi_0 & -\cos \phi_0 \end{bmatrix} \begin{pmatrix} \int_0^L \frac{1}{2} \kappa^2(t) dt + (\lambda \sigma) \cdot L \\ \kappa(L) - \kappa(0) \end{pmatrix}$$

$$(13)$$

where we substituted $H^* = \lambda_r \sigma$ and $\lambda = \lambda_r / EI$. The endpoint curvatures in Eq. (13) are $\kappa(0) = -2k\sqrt{\lambda} \cdot cn(\sqrt{\lambda} \cdot s_0, k)$ and $\kappa(L) = -2k\sqrt{\lambda} \cdot cn(\sqrt{\lambda} \cdot (s_0 + L), k)$, based on Eq. (9). The elastica axis direction, ϕ_0 , is obtained by evaluating Eq. (10) for $\phi(s)$ at s = 0

 $\phi_0 = \phi(0) + 2\sin^{-1} \left(\mathbf{k} \cdot sn(\sqrt{\lambda} \cdot s_0, \mathbf{k}) \right).$ (14) The third equation is obtained by evaluating Eq. (10) at the

cable endpoints
$$s=0$$
 and $s=L$

$$\frac{1}{2}(\phi(L) - \phi(0)) = \sin^{-1}(\mathbf{k} \cdot sn(\sqrt{\lambda} \cdot s_0, \mathbf{k})) - \sin^{-1}(\mathbf{k} \cdot sn(\sqrt{\lambda} \cdot (s_0+L), \mathbf{k})).$$
(15)

Equations (13)-(15) provide three equations in λ , k and s_0 whose solution by numerical means gives the flexible cable shape as a function of its relative endpoint states, S(L)-S(0). The cable *base frame configuration* is defined as $(x(0), y(0), \phi(0))$, and together with S(L)-S(0) gives a total of six configuration variables. This paper describes a steering scheme that maintains equal endpoint tangets, thus giving a total of five configuration variables.

The elastica full period length: The elliptic cosine and sine functions period is $4K(\mathbf{k})$, where $K(\mathbf{k})$ is the complete elliptic integral of the first kind.² Denote by \tilde{L} the *full period length* of the elastica that contains the physical cable. The argument $\sqrt{\lambda} \cdot (s+s_0)$ in Eqs. (9)-(10) satisfies the full-period relation $\sqrt{\lambda} \cdot \tilde{L} = 4K(\mathbf{k})$, which gives $\tilde{L} = 4K(\mathbf{k})/\sqrt{\lambda}$.

The 2-D cable steering problem: A flexible cable modeled by Euler's elastica is held by two robot grippers in a planar environment populated by sparsely spaced obstacles. Find a path for the robot grippers that steers the flexible cable from start to target endpoint states using equal endpoint tangents, such that the cable maintains stable equilibrium shapes while avoiding self-intersection and contact with the environment, except for endpoint contacts at the start or target positions.

The sparse obstacles assumption highlights a caveat in the cable steering problem. Two robot grippers are able to control the flexible cable shape only within the elastica family of solutions. Obstacle avoidance is therefore feasible only among sparsely spaced obstacles (see Section VII).

²It is defined as $K(\mathbf{k}) = \int_0^{\pi/2} \frac{d\theta}{\sqrt{1-\mathbf{k}^2 \sin^2 \theta}}$, a standard analytic function of the modulus parameter k [21].



III. Non Self-Intersecting Flexible Cable Shapes

This section uses the elastica solutions to identify the non selfintersecting flexible cable shapes, which remarkably involve only the modulus parameter k.

A flexible cable can possibly self-intersect when its tangent angle with respect to its elastica axis, $\phi(s)-\phi_0$, exceeds $\pm 90^{\circ}$ for some $s \in [0, L]$ (Fig. 3). Using Eq. (10) for $\phi(s)$, the flexible cable can self-intersect only when $|\sin(\frac{1}{2}(\phi(s)-\phi_0))| \ge \frac{1}{\sqrt{2}}$ for some $s \in [0, L]$. When this happens, the cable crosses its elastica axis at an angle $|\sin(\frac{1}{2}(\phi(s^*) - \phi_0))| \ge \frac{1}{\sqrt{2}}$ where $\kappa(s^*) = 0$. Hence, according to Eq. (11) for the modulus parameter, 0 < k < 1, self-intersection can possibly occur when

k =
$$\left| \sin \left(\frac{1}{2} (\phi(s^*) - \phi_0) \right) \right| \ge \frac{1}{\sqrt{2}} \qquad \kappa(s^*) = 0.$$

Next consider the projection of the flexible cable (x(s), y(s))coordinates on its elastica axis, denoted $\bar{x}(s)$. A full period of the elastica that contains the physical cable starts at $s+s_0=0$ and ends at $s+s_0=\tilde{L}$, where \tilde{L} is the full-period length of the elastica that contains the physical cable (Fig. 2). Define the equivalent path length parameter $\bar{s}=s+s_0$. According to Eq. (8)

$$\bar{x}(\bar{s}) = \frac{1}{\lambda_r} \cdot \int_0^{\bar{s}} \frac{1}{2} EI \cdot \kappa^2(t) dt + \frac{1}{\lambda_r} H^* \cdot \bar{s} \qquad \bar{s} \in [0, \tilde{L}].$$
(16)

When $k \ge \frac{1}{\sqrt{2}}$, each full period of the elastica contains two *fold* points located at \bar{s}_{max} and $\tilde{L} - \bar{s}_{max}$ at which $|\phi(\bar{s}) - \phi_0| = 90^\circ$ (Fig. 4). Evaluating this condition using Eq. (10) for $\phi(s)$ gives

 $\mathbf{k} \cdot sn(\sqrt{\lambda} \cdot \bar{s}_{max}, \mathbf{k}) = \frac{1}{\sqrt{2}} \Rightarrow \bar{s}_{max} = \frac{1}{\sqrt{\lambda}}sn^{-1}(\frac{1}{\sqrt{2}\cdot\mathbf{k}}, \mathbf{k}).$ where $sn^{-1}(\cdot)$ is the inverse elliptic sine function. As long as $\bar{x}(\bar{s}_{max}) \leq \bar{x}(\tilde{L}/2)$, the fold points do not touch each other

 $x(s_{max}) \le x(L/2)$, the fold points do not touch each other (Fig. 4). Hence, using Eq. (16) for $\bar{x}(\bar{s})$, the flexible cable is not self-intersecting when $t\bar{s}_{max}$

$$\int_{0}^{s_{max}} \frac{1}{2} EI \cdot \kappa^{2}(t) dt + H^{*} \cdot \bar{s}_{max} \leq \int_{0}^{L/2} \frac{1}{2} EI \cdot \kappa^{2}(t) dt + H^{*} \cdot \frac{\bar{L}}{2}$$
(17)

where we canceled the common factor $1/\lambda_r$. Substituting $H^* = \lambda_r \cdot (1-2k^2)$ and $\kappa(t) = -2\sqrt{\lambda}k \cdot cn(\sqrt{\lambda}t, k)$ in Eq. (17) gives the non self-intersection condition

$$\begin{split} &\int_{0}^{\bar{s}_{max}} 2\mathbf{k}^2 cn^2 (\sqrt{\lambda}t,\mathbf{k}) dt + (1\!-\!2\mathbf{k}^2) \cdot \bar{s}_{max} \\ &\leq \int_{0}^{\tilde{L}/2} 2\mathbf{k}^2 cn^2 (\sqrt{\lambda}t,\mathbf{k}) dt + (1\!-\!2\mathbf{k}^2) \cdot \frac{\tilde{L}}{2} \end{split}$$



Figure 5. (a)-(b) Two families of energy extremal cable shapes, $(x_1(s), y_1(s))$ determined by $s_0 = a_0$ and $(x_2(s), y_2(s))$ determined by $s_0 = b_0$. All cable shapes have same length of L = 1. (c) When the two families of extremal cable shapes approach the limit $a_0 = b_0 = \frac{\tilde{L}}{4}$, their common endpoint reaches a conjugate point along the limit cable shape.

where we canceled the common factor $\lambda_r = EI \cdot \lambda$. A change of integration variable, $u = \sqrt{\lambda} \cdot t$ with $du = \sqrt{\lambda} \cdot dt$, gives an equivalent non self-intersection condition that depends only on k

$$\int_{0}^{u_{max}(\mathbf{k})} 2\mathbf{k}^{2} cn^{2}(u, \mathbf{k}) du + (1 - 2\mathbf{k}^{2}) \cdot u_{max}(\mathbf{k})$$

$$\leq \int_{0}^{2K(\mathbf{k})} 2\mathbf{k}^{2} cn^{2}(u, \mathbf{k}) du + (1 - 2\mathbf{k}^{2}) \cdot 2K(\mathbf{k})$$
(18)

 $\leq \int_0^{2\pi/(w)} 2k^2 cn^2(u, k) du + (1 - 2K^-) \cdot 2K(\kappa)$ with integration limits $u_{max}(k) = \sqrt{\lambda} \cdot \bar{s}_{max} = sn^{-1} \left(\frac{1}{\sqrt{2} \cdot k}, k\right)$ and $u = \sqrt{\lambda} \cdot \frac{1}{2} \tilde{L} = 2K(k)$ since $\tilde{L} = 4K(k)/\sqrt{\lambda}$. The two sides of Eq. (18) depend only on k and intersect at $k_{max} = 0.855$ (Fig. 4). The range $0 < k < k_{max}$ guarantees that the flexible cable is *not* self-intersecting, irrespective of the other elastica parameters.

Remark: The range 0 < k < 0.855 provides a conservative rule for non self-intersection. Elastica solutions with modulus parameter in the range $0.855 \le k < 1$ are self-intersecting, but the physical cable may occupy a short segment of such elastica that is not self-intersecting.

IV. Flexible Cable Stability

This section uses the elastica solutions to obtain a simple geometric characterization of the stable cable shapes to be used during steering. Recall that the elastica inflection points are zero curvature points (Fig. 2). The following theorem adapted from Sachkov [23] characterizes the stable cable shapes in terms of the number of inflection points.

Theorem 1 [Stability]: Let a flexible cable be held with fixed endpoint positions and tangents at an equilibrium state. Cable shapes that contain zero, one or two inflection points are **possibly stable** while cable shapes that contain three or more inflection points are **definitely unstable**.

Proof sketch: Stable cable shapes form local minima of their total elastic energy, $\mathcal{E} = \int_0^L \frac{1}{2} EI \cdot \kappa^2(s) ds$. First consider cables whose length is much shorter than the full period length of the elastica containing the physical cable, $L \ll \tilde{L}$. Equilibrium shapes of these cables form local minima of \mathcal{E} , since \mathcal{E} possesses a positive definite second variation at the equilibrium state. As L increases relative to \tilde{L} , the second variation of \mathcal{E} eventually ceases to be positive definite at a *conjugate point* [8][Theorem 26.3].

In order to describe the notion of a conjugate point, consider a flexible cable held at a fixed initial point and fixed tangent at this point. The cable equilibrium shape is fully determined as the solution of the cable system equations (Eq. (1)) and the cable adjoint equations (Eq. (3)) for each initial value of the co-states (λ_x, λ_y) and $\lambda_{\phi}(0)$. In Section II, the co-states were replaced by the co-state parameter λ , the elastica modulus k and the phase parameter s_0 .

One technique to identify a conjugate point (which marks loss of stability) is described in [8][Definition 27.4]. Consider two families of energy extremal cable shapes sharing a fixed initial point and fixed tangent at this point, parameterized by λ , k and s_0 . If the two distinct families merge into a single extremal cable shape at the limit $(\lambda, k, s_0) \rightarrow (\lambda^*, k^*, s_0^*)$ while intersecting at their respective endpoints, the *endpoint* of the limit cable shape associated with (λ^*, k^*, s_0^*) forms a *conjugate point* along the limit cable shape.

Using this insight, consider two families of energy extremal cable shapes having the same modulus parameter, $k = k^*$, the same co-state parameter, $\lambda = \lambda^*$, and variable phase parameter s_0 . From Section II, the full period length of the elastica that contains the physical cable is given by $\tilde{L} = 4K(k)/\sqrt{\lambda}$. Hence all cable shapes of both families have full period length of $\tilde{L} = 4K(k^*)/\sqrt{\lambda^*}$.

Consider the family of energy extremal cable shapes given by Eq. (8), $(x_1(s), y_1(s))$, whose phase parameter is $s_0 = a_0$ $\binom{x_1(s)}{y_1(s)} = \binom{x(0)}{y(0)} + \frac{1}{\lambda^*} \begin{bmatrix} \cos \phi_0 & \sin \phi_0 \\ \sin \phi_0 & -\cos \phi_0 \end{bmatrix} \begin{pmatrix} \int_0^s \frac{1}{2} \kappa^2(t) dt + \sigma \cdot s \\ \kappa_1(s) - \kappa_1(0) \end{pmatrix}$ where $s \in [0, \tilde{L}], \sigma = 1 - 2(k^*)^2$ and $\kappa_1(s) = -\lambda^* A \cdot cn(\sqrt{\lambda^*} \cdot (s + a_0), k^*)$ (using Eq. (9)), where $A = 2k^*/\sqrt{\lambda^*}$.

Next consider an alternative family of energy extremal cable shapes, $(x_2(s), y_2(s))$, whose phase parameter $s_0 = b_0$ is set symmetrically with respect to a_0 about the inflection points: if a_0 lies in the interval $[0, \frac{\tilde{L}}{2}]$ then $b_0 = \frac{\tilde{L}}{2} - a_0$; if a_0 lies in the complimentary interval $(\frac{\tilde{L}}{2}, \tilde{L}]$ then $b_0 = \frac{3\tilde{L}}{2} - a_0$. Thus

 $\begin{pmatrix} x_2(s) \\ y_2(s) \end{pmatrix} = \begin{pmatrix} x(0) \\ y(0) \end{pmatrix} + \frac{1}{\lambda^*} \begin{bmatrix} \cos \phi_0 & \sin \phi_0 \\ \sin \phi_0 & -\cos \phi_0 \end{bmatrix} \begin{pmatrix} \int_0^s \frac{1}{2}\kappa^2(t)dt + \sigma \cdot s \\ \kappa_2(s) - \kappa_2(0) \end{pmatrix}$ where $s \in [0, \tilde{L}], \sigma$ is the same as above and $\kappa_2(s) = -\lambda^* A \cdot cn(\sqrt{\lambda^*} \cdot (s+b_0), \mathbf{k}^*)$ with A the same as above.

The two families of cable shapes start at (x(0), y(0)). One can also verify that the two families start along the same tangent direction, $\phi_1(0) = \phi_2(0)$, for each matched choice of a_0 and b_0 (Fig. 5(a)-(b)). One can also verify that the two families of cable shapes intersect at their respective endpoints, $(x_1(\tilde{L}), y_1(\tilde{L})) = (x_2(\tilde{L}), y_2(\tilde{L}))$, for each matched choice of a_0 and b_0 (Fig. 5(a)-(b)).

The key step of the proof is to study the limit of the two families when $a_0 = b_0$. When $a_0 \in [0, \frac{\tilde{L}}{2}]$, this limit occurs when $a_0 \rightarrow \frac{\tilde{L}}{4}$ and then $b_0 = \frac{\tilde{L}}{2} - a_0 \rightarrow \frac{\tilde{L}}{4}$ (the elastica 1'st inflection point). When $a_0 \in (\frac{\tilde{L}}{2}, \tilde{L}]$, the limit occurs when $a_0 \rightarrow \frac{3\tilde{L}}{4}$ and then $b_0 = \frac{3\tilde{L}}{2} - a_0 \rightarrow \frac{3\tilde{L}}{4}$ (the elastica 2'nd inflection point). In either case, the limit cable shape starts at an inflection point, passes through a midpoint inflection point (Fig. 5(c)). Since the two families of extremal cable shapes intersect at their respective endpoints, the endpoint of the limit cable shape at the third inflection point forms a *conjugate point* along the limit cable shape.

Theorem 1 is next applied to flexible cables held with equal endpoint tangents. In this case the stable cable shapes consist



Figure 6. The $(\phi(s), \kappa(s))$ contours of $H(s) = H^*$ form convex loops that describe full periods of the elastica. When a flexible cable is held with equal endpoint tangents, the cable occupies a segment with vertically aligned endpoints on a particular loop, with one or two inflection points.

of two types (L is the physical cable length, \tilde{L} the full period length of the elastica that contains the physical cable).

Corollary 4,1: Under the conditions of Theorem 1, when a flexible cable is held with equal endpoint tangents, the stable cable shapes either contain a single inflection point at the cable midpoint and then $L < \tilde{L}$, or contain two interior inflection points and then $L = \tilde{L}$.

Proof: The possibly stable cable shapes contain zero, one or two inflection points according to Theorem 1. From Section II, the Hamiltonian is constant along energy extremal cable shapes, $H(s) = H^*$ for $s \in [0, L]$. According to Eq. (6) for H(s) $\lambda_r \cdot \cos(\phi(s) - \phi_0) - \frac{1}{2}EI \cdot \kappa^2(s) = \lambda_r \cdot (1 - 2k^2)$ $s \in [0, L]$ (19) where we substituted $H^* = \lambda_r \cdot (1 - 2k^2)$. The flexible cable tangent and curvature, $(\phi(s), \kappa(s))$, are variables while λ_r , EI and k are fixed parameters. The $(\phi(s), \kappa(s))$ contours described by Eq. (19) form convex loops centered at the origin, shown in Fig. 6 for different values of the modulus parameter k (the other parameters do not affect these loops). Each loop represents full period of the elastica, $s \in [0, \tilde{L}]$. Since each loop crosses the ϕ -axis exactly at two points at which $\kappa(s) = 0$, each full period of the elastica contains exactly two inflection points.

When a flexible cable is held with equal endpoint tangents, its endpoints lie on the same vertical line in the $(\phi(s), \kappa(s))$ plane (Fig. 6). The physical cable therefore occupies one of two segments on a particular loop, such that the segment is bounded by vertically aligned endpoints. Any such segment crosses the ϕ -axis at least once, hence the physical cable must have at least one inflection point. When a segment crosses the ϕ -axis at a single point (one inflection point), the segment occupies less than a full loop and then $L < \tilde{L}$ (Fig. 6). When a segment crosses the ϕ -axis at two points (two inflection points), its vertically aligned endpoints merge and the segment forms a full loop with $L = \tilde{L}$ (Fig. 6).

Determination of stable cable shapes from endpoint positions: The two types of stable cable shapes partition the cable relative endpoint positions as follows. Let the cable start point be fixed at the origin with the cable tangent fixed along the *x*-axis (Fig. 7). The cable *relative endpoint space* is defined



Figure 7. The cable start point is fixed at the origin with tangent fixed along the x-axis. The cable distal endpoint varies while its tangent is fixed along the x-axis. The outer stability region represents endpoint positions where the stable cable shapes have a midpoint inflection point and $L < \tilde{L}$. The inner stability region represents endpoint positions where the stable cable shapes have two interior inflection points and $L = \tilde{L}$.

as the position of its distal endpoint, (x(L), y(L)), with the cable endpoint tangent, $\phi(L)$, fixed along the x-axis (Fig. 7).

From Corollary 1, the length of any stable cable shape is either $L < \tilde{L}$ (one inflection point) or $L = \tilde{L}$ (two inflection points). As L becomes shorter than \tilde{L} , the physical cable occupies smaller portion of the full elastica period. If the modulus parameter is held fixed when L becomes shorter than \tilde{L} , the cable flattens while its distal endpoint moves away from the origin. To allow the cable endpoint reach points located on the vertical y-axis, a maximal flattening parameter limits the cable flattening to the range $\rho \cdot \tilde{L} \le L \le \tilde{L}$, where $0 < \rho < 1$. For instance, $\rho = 1/2$ is used in Fig. 7.

We also need to limit the modulus parameter k as follows. At k = 0 the cable forms a horizontal straight line with (x(L), y(L)) = (0, L) (Fig. 7). As k increases, the flexible cable folds inward towards the origin. Eventually k reaches a critical value at which the cable distal endpoint reaches the origin. When $L = \tilde{L}$, this event occurs when the cable forms a figure eight. The critical value, k_c , is determined by the condition $\bar{x}(\tilde{L}) = \bar{x}(0)$, where \bar{x} is the cable coordinate along its elastica axis. Using Eq. (16) for \bar{x} , it can be verified that $k_c = 0.909$. In the following characterization of the stability regions the parameter k will vary in the interval $[0, k_c]$.

Consider the stability regions depicted in relative endpoint space of Fig. 7. The outer boundary consists of two curves, α and β . The curve α traces the endpoint of a maximally flattened cable satisfying $L = \rho \cdot \tilde{L}$. It is specified by the elastica solution $\alpha(\mathbf{k}) = (x(L), y(L))$ of Eq. (8), using $\mathbf{k} \in [0, \mathbf{k}_c]$ as the curve parameter. This curve consists of an upper piece determined by $s_0 = \frac{\tilde{L}}{4} + \frac{\tilde{L}-L}{2}$ (cable starts at a distance $\frac{\tilde{L}-L}{2}$ from the elastica first inflection point at $\frac{\tilde{L}}{4}$), and a lower piece determined by the phase parameter by $s_0 = \frac{3\tilde{L}}{4} + \frac{\tilde{L}-L}{2}$ (cable starts at a distance $\frac{\tilde{L}-L}{2}$ from the elastica first inflection point at $\frac{\tilde{L}}{4}$).

The curve β in Fig. 7 traces the cable endpoint when it folds inward towards the origin, obtained by decreasing the elastica



Figure 8. (a) Approximation of a flexible cable shape (thin curve) having two interior inflection points p_1 and p_3 and a maximum curvature point p_2 by four convex quadratic arcs. (b) Approximation of a flexible cable shape (thin curve) having a midpoint inflection point p_2 and two extreme curvature points p_1 and p_3 by four convex quadratic arcs, two of which form shorter arcs.

full period length from $\tilde{L} = L/\rho$ down to $\tilde{L} = L$ while keeping the modulus parameter fixed at k_c . This curve is specified by the elastica solution $\beta(\tilde{L}) = (x(\tilde{L}), y(\tilde{L}))$ of Eq. (8), using $\tilde{L} \in [L, L/\rho]$ as the curve parameter. The upper and lower pieces of β are determined by the phase parameters $s_0 = \frac{\tilde{L}}{4} + \frac{\tilde{L}-L}{2}$ and $s_0 = \frac{3\tilde{L}}{4} + \frac{\tilde{L}-L}{2}$.

The region bounded by α and β contains an inner loop marked as γ in Fig. 7. The inner loop traces the endpoint of a flexible cable of length $L = \tilde{L}$, having two inflection points at the cable endpoints in addition to a midpoint inflection point. This curve is specified by the elastica solution $\gamma(\mathbf{k}) = (x(L), y(L))$ of Eq. (8), using $\mathbf{k} \in [0, \mathbf{k}_c]$ as the curve parameter. The upper piece of γ is determined by the phase parameter $s_0 = \frac{L}{4}$ (cable starts at the elastica first inflection point and ends after full period length). The lower piece of γ is determined by $s_0 = \frac{3L}{4}$ (cable starts at the elastica second inflection point and ends after full period length).

The relative position of the cable endpoint indicates *two* types of stable cable shapes when held with equal endpoint tangents. All cable endpoints in the outer region between γ and the outer loop formed by α and β are associated with stable cable shapes of length $L < \tilde{L}$. The stable cable shapes for endpoints in this region contain a single inflection point at their midpoint (Fig. 7). All cable endpoints in the *inner* region bounded by γ are associated with stable cable shapes of length $L = \tilde{L}$. The stable cable shapes for endpoints in this region contain the stable cable shapes of length $L = \tilde{L}$. The stable cable shapes for endpoints in this region contain two interior inflection points (Fig. 7).

V. Flexible Cable Approximation by Quadratic Arcs

This section describes an approximation of flexible cable stable equilibrium shapes by convex quadratic arcs to be used for efficient collision checking during flexible cable steering.

Control points selection: Each full period of the elastical consists of four convex arcs having equal length. To describe these arcs, consider the $(\phi(s), \kappa(s))$ contours depicted in Fig. 6. The contours form concentric convex loops that describe full periods of the elastica, $s \in [0, \tilde{L}]$. Each loop contains four special points: the upper point $(0, \kappa_{max})$ of maximum

curvature where $\phi(0) = 0$, the rightmost point $(\phi(\frac{L}{4}), 0)$ which is the first inflection point at which $\kappa = 0$, the bottom point $(0, -\kappa_{max})$ of minimum curvature where $\phi(\frac{\tilde{L}}{2}) = 0$, and the leftmost point $(\phi(\frac{3\tilde{L}}{4}), 0)$ which is the second inflection point at which $\kappa = 0$.

When a flexible cable forms a stable shape with equal endpoint tangents, it occupies up to full period length of the elastica (Corollary 4.1). The cable starts according to its phase parameter, $s_0 \in [0, \tilde{L}]$, and ends at $s_0 + L$ such that $L \leq \tilde{L}$. The flexible cable *control points* are its two endpoints, its extreme curvature points when such points exist, and the cable inflection points (one or two such points exist in a full period of the elastica). The flexible cable can thus have up to six control points that divide the cable into up to five convex arcs (Fig. 8).

Bézier polynomial construction: Let the flexible cable control points be indexed according to their appearance on the cable, p_0, \ldots, p_n such that p_0 and p_n are the cable endpoints and $n \leq 5$ (Fig. 8). Every pair of control points, p_i and p_{i+1} , bounds a convex arc approximated by a convex quadratic arc as follows. The control points p_i and p_{i+1} are first augmented with an intermediate control point, q_i , located at the intersection point of the cable's tangent lines at p_i and p_{i+1} (Fig. 8). The position of p_i and p_{i+1} and the tangents at these points are obtained from the elastica solution of Eq. (8). This data feeds a simple formula for computing q_i which is omitted. Using Bézier's technique [5], each triplet p_i , q_i and p_{i+1} defines the quadratic polynomial

$$P_i(t) = (1-t)^2 \cdot \vec{p}_i + 2(1-t)t \cdot \vec{q}_i + t^2 \cdot \vec{p}_{i+1} \quad t \in [0,1]$$
(20)

where i=0...n-1. Some intuition for $P_i(t)$ can be obtained by considering its midpoint position

$$P_i(\frac{1}{2}) = \frac{1}{4}\vec{p}_i + \frac{1}{2}\vec{q}_i + \frac{1}{4}\vec{p}_{i+1}.$$

The midpoint coefficients form barycentric coordinates that place the midpoint closer to the intermediate control point q_i within the triangle formed by p_i , q_i and p_{i+1} . Additional intuition can be gained from the quadratic polynomial tangent

$$P'_i(t) = 2((t-1) \cdot \vec{p}_i + (1-2t) \cdot \vec{q}_i + t \cdot \vec{p}_{i+1}) \quad t \in [0,1].$$

The endpoint tangents $P'_i(0) = 2(\vec{q_i} - \vec{p_i})$ and $P'_i(1) = 2(\vec{p_{i+1}} - \vec{q_i})$ are aligned with two edges of the triangle formed by p_i , q_i and p_{i+1} . In particular, these tangents are collinear with the elastica tangents at p_i and p_{i+1} for i=0...n-1. The Bézier polynomials construction is summarized as Algorithms 1 and 2.

Example: Fig. 8(a) shows an equilibrium shape that contains two interior inflection points p_1 and p_3 and a maximum curvature point p_2 . The elastica parameters are $L = \tilde{L}$, $s_0 = 0$ and k = 0.7746. The control points divide the cable into four convex arcs of length $\tilde{L}/4$. Fig. 8(b) shows a different stable equilibrium shape that contains a midpoint inflection point p_2 and two extreme curvature points p_1 and p_3 . The elastica parameters in Fig. 8(b) are $L = \frac{2}{3}\tilde{L}$, $s_0 = 0.916\tilde{L}$ and k = 0.8515. The control points divide the cable into four convex arcs with shorter first and fourth arcs (since $L = \frac{2}{3}\tilde{L}$). In both examples, the four quadratic polynomials pass through the control points p_0, \ldots, p_4 with tangents collinear with the cable tangents at the control points. A measure of the approximation quality is the *excess length* of the piecewise quadratic approximation relative to the cable length. It is 1.6% longer in Fig. 8(a) and 4.2% longer in Fig. 8(b).

Algorithm 1 Control Points Selection

Input: cable start state $(x(0), y(0), \phi(0))$, cable length L, cable elastica parameters λ , k and s_0 with $\tilde{L} = 4K(k)/\sqrt{\lambda}$. **Data structures:** control points set \mathcal{P} , number of control points 2n+1,

next control point position s^* . Initialize: $\hat{p_0} = (\hat{x(0)}, y(0)), \phi_0 = \phi(0), \mathcal{P} = \{p_0\}, i = 0, s^* = 0.$ Set s^* :

 $\begin{array}{l} \text{fet } s^* \text{:} \\ 1) \quad \text{If } s_0 \leq \frac{\tilde{L}}{4} \text{ and } s_0 + L \geq \frac{\tilde{L}}{4} \text{ set } s^* = \frac{\tilde{L}}{4}. \\ 2) \quad \text{If } s_0 \leq \frac{\tilde{L}}{2} \text{ and } s_0 + L \geq \frac{\tilde{L}}{2} \text{ set } s^* = \frac{\tilde{L}}{2}. \\ 3) \quad \text{If } s_0 \leq \frac{3\tilde{L}}{2} \text{ and } s_0 + L \geq \frac{3\tilde{L}}{2} \text{ set } s^* = \frac{3\tilde{L}}{2}. \\ 4) \quad \text{If } s_0 \leq \tilde{L} \text{ and } s_0 + L \geq \tilde{L} \text{ set } s^* = \tilde{L}. \end{array}$

while $s_0 \le s^* \le s_0 + L$ do $p_{i+1} = (x(\overline{s^*} - s_0), y(s^* - s_0))$ using elastical solution of Eq. (8). $\phi_{i+1} = \phi((s^* - s_0))$ using elastica tangent formula of Eq. (10). Compute control point q_i using (p_i, ϕ_i) and (p_{i+1}, ϕ_{i+1}) . $\mathcal{P} \leftarrow \mathcal{P} \cup \{q_i, p_{i+1}\}.$ $s^* = s^* + \widetilde{L}/4.$ i = i + 1.end while $n = i, p_n = (x(L), y(L)), \phi_n = \phi(0).$ Compute control point q_{n-1} using (p_{n-1}, ϕ_{n-1}) and (p_n, ϕ_n) . $\mathcal{P} \leftarrow \mathcal{P} \cup \{q_{n-1}, p_n\}.$

Output: control points $\mathcal{P} = \{p_0, q_0, p_1, q_1, \dots, p_n\}.$

Algorithm 2 Bézier Polynomials Construction

Use Algorithm 1 to compute control points $\mathcal{P} = \{p_0, q_0, p_1, \dots, p_n\},\$ n < 5.for i = 0 to n - 1 do Compute quadratic polynomial $P_i(t)$ according to Eq. (20). end for **Output:** flexible cable approximation by $P_0(t), \ldots, P_{n-1}(t)$.

VI. Flexible Cable Steering Scheme

This section describes the flexible cable steering scheme which relies on the tools developed in previous sections. The scheme consists of three stages. In the first stage the flexible cable relative endpoint positions are computed as a function of three elastica parameters. The second stage uses the relative endpoint positions and their elastica parameters to initialize a 5-D grid of the cable configuration space. The third stage performs motion planning in the flexible cable 5-D configuration space.

Computation of cable relative endpoint positions: The flexible cable relative endpoint positions, denoted $(X_L, Y_L) =$ (x(L) - x(0), y(L) - y(0)), are computed using three elastica parameters: the modulus parameter, \hat{k} , the phase parameter, s_0 , and the full period length of the elastica, $\tilde{L} = 4K(k)/\sqrt{\lambda}$. Here \tilde{L} replaces the co-state parameter λ , since the stable cable shapes described in Section IV are associated with cable lengths $L < \tilde{L}$ and $L = \tilde{L}$.

The three elastica parameters vary in a manner that ensures stable non self-intersecting cable shapes. The modulus paramstate non-set-intersecting cable shapes. The modulus param-eter varies in the interval $0 \le k \le k_{max}$, where k = 0 is a straight-line shape while $k \le k_{max}$ ensures that the cable is not self-intersecting (Section III). The phase parameter s_0 varies in the interval [L/4, 3L/4]. This interval ensures full coverage of the endpoints (X_L, Y_L) associated with the stable cable shapes. The parameter \tilde{L} varies in the interval $[L, L/\rho]$, where $0 < \rho < 1$ is a maximal flattening parameter (Section IV).

The computation of (X_L, Y_L) is summarized as Algorithm 3. The algorithm uses $n_{\rm k}, n_{s_0}$ and $n_{\rm \tilde{L}}$ discrete values of the elastica parameters to compute (X_L, Y_L) over four planar cells embedded in the space (k, s_0, \tilde{L}) . Two cells correspond to stable cable shapes satisfying $L = \tilde{L}$ (horizontal cells 1 and 2 in Fig. 9(a)), the other two cells correspond to stable cable shapes satisfying $L < \hat{L}$ (diagonal cells 3 and 4 in Fig. 9(a)).



Figure 9. The relative endpoint positions (X_L, Y_L) are computed by Algorithm 3 over four cells of the elastica parameters (k, s_0, \tilde{L}) . Cells 1 and 2 parametrize stable non self-intersecting cable shapes satisfying $L = \tilde{L}$. Cells 3 and 4 parametrize stable non self-intersecting cable shapes satisfying L < L.

For each value of (k, s_0, L) , the cable relative endpoint position is computed according to Eq. (8)

$$\begin{pmatrix} X_L(\mathbf{k}, s_0, \tilde{L}) \\ Y_L(\mathbf{k}, s_0, \tilde{L}) \end{pmatrix} = \frac{1}{\lambda} \begin{bmatrix} \cos \phi_0 & \sin \phi_0 \\ \sin \phi_0 & -\cos \phi_0 \end{bmatrix} \begin{pmatrix} \int_0^L \frac{1}{2} \kappa^2(s) ds + \lambda \sigma \cdot L \\ \kappa(L) - \kappa(0) \end{pmatrix}$$
(21)

where ϕ_0 is specified in Eq. (14), $\sigma = 1 - 2k^2$, $\lambda = \lambda_r / EI$, and the cable curvatures $\kappa(0)$ and $\kappa(L)$ are specified in Eq. (9).

Algorithm 3 Relative Endpoint Positions

Input: cable length L; elastica parameters (k, s_0, \tilde{L}) discretized into $(n_k, n_{s_0}, n_{\tilde{L}})$ values in $[0, k_{max}]$, $[\frac{L}{4}, \frac{3L}{4}]$ and $[L, \frac{L}{\rho}]$.

Data structures: EndPoint array of (X_L, Y_L) , each storing elastica parameter triplets $(k, s_{0,1}, \tilde{L})$ and $(k, s_{0,2}, \tilde{L})$. **Initialize:** $EndPoint \leftarrow [0]$.

/*full period cable shapes (cells 1,2 in Fig. 9)*/

Set L = Lfor i = 1 to n_k do for j = 1 to n_{s_0} do Compute $X_L(\mathbf{k}(i), s_0(j), \tilde{L}), Y_L(\mathbf{k}(i), s_0(j), \tilde{L})$ $s_{0,1} = s_0(j)$ $\begin{array}{l} s_{0,1} - s_{0(J)} \\ \text{if } 0 \le s_{0,1} \le \frac{L}{2} \text{ set } s_{0,2} = \frac{L}{2} - s_{0,1} \text{ else } s_{0,2} = \frac{3L}{2} - s_{0,1} \\ EndPoint[X_L, Y_L] \leftarrow \left(k(i), s_{0,1}, \tilde{L}\right), \left(k(i), s_{0,2}, \tilde{L}\right) \end{array}$ end for

end for

/*less than full period cable shapes (cells 3,4 in Fig. 9)*/ for i = 1 to n_k do

for j=1 to $n_{\tilde{L}}$ do

Set $s_{0,1} = \frac{\tilde{J}\tilde{L}(j) - 2L}{4}$, $s_{0,2} = \frac{\tilde{J}\tilde{L}(j) - 2L}{4}$ Compute $X_L(\mathbf{k}(i), s_{0,1}, \tilde{L}(j)), \tilde{Y}_L(\mathbf{k}(i), s_{0,1}, \tilde{L}(j))$ $EndPoint[X_L, Y_L] \leftarrow (k(i), s_{0,1}, \tilde{L}(j))$ Compute $X_L(k(i), s_{0,2}, \tilde{L}(j)), Y_L(k(i), s_{0,2}, \tilde{L}(j))$ $EndPoint[X_L, Y_L] \leftarrow (k(i), s_{0,2}, \tilde{L}(j))$ end for end for

Output: EndPoint array of (X_L, Y_L) .

Example: The relative endpoint positions, (X_L, Y_L) , computed by Algorithm 3 using Eq. (21) are shown in Fig. 10(a). These endpoints were computed over the cells shown in Fig. 9 using elastica parameters (k, s_0, \tilde{L}) discretized into $n_{\rm k} = 160, n_{s_0} = 200$ and $n_{\tilde{L}} = 100$ values, thus giving $n_{\rm k} n_{s_0} + 2n_{\rm k} n_{\tilde{L}} = 64,000$ relative endpoint positions. These endpoint positions are used to initialize the flexible cable 5-D configuration space grid as next described.

Initialization of cable configuration space grid: The flexible cable 5-D configuration space grid, CSpace, consists of $(x(0), y(0), \phi(0))$ and (X_L, Y_L) . The cable base frame position, (x(0), y(0)), varies in a rectangular environment discretized into $n \times n$ cells while the cable base frame orientation, $\phi(0)$, is discretized into m cells. The CSpace grid is



Figure 10. (a) The relative endpoint positions (X_L, Y_L) computed by Algorithm 3 over the elastica parameter cells shown in Fig. 9. (b) The relative endpoint positions lumped into an $N \times N$ array whose inner black cells represent stable non self-intersecting cable shapes. These cells store the elastica parameters that determine the corresponding cable shape.

initialized in two steps. In the first step the relative endpoint positions stored in EndPoint are lumped into an $N \times N$ array, EndPointGrid, shown as a 50 × 50 grid in Fig. 10(b). The inner black cells represent stable non self-intersecting cable shapes. Each of these cells stores two elastica triplets that represent two cable shapes in cells 1 and 2 of Fig 9(a), and a single cable shape in cells 3 and 4 of Fig 9(a). For each inner black cell of EndPointGrid, all cells of CSpace having this (X_L, Y_L) coordinate are marked as *feasible* in CSpace. These cells correspond to stable and non self-intersecting cable shapes and their elastica parameters are kept in the underlying EndPointGrid. All cells of CSpace that project to the outer red cells in Fig. 10(b) are marked as *infeasible*.

Algorithm 4 Flexible Cable Steering Scheme

Input: cable length L; cable CSpace grid; start S and target T specified as feasible cells of *CSpace*. Polygonal obstacles $\mathcal{B}_1, \ldots, \mathcal{B}_k$. Data structures: Open list \mathcal{O} , closed list \mathcal{C} . Initialize: $\mathcal{O} = \{S\}, \mathcal{C} = \emptyset$. /*Search for shortest CSpace path from start to target*/ while $\mathcal{O} \neq \emptyset$ do Select $z^* \in \mathcal{O}$ according to A^* search criterion. if $z^* = T$ then move to output stage. Move z^* from \mathcal{O} to \mathcal{C} . For each feasible neighbor z of z^* in CSpace s.t. $z \notin C$ do Extract cable base frame $(x(0), y(0), \phi(0))$ of z. Extract cable elastica triplets $(k, s_{0,1}, \tilde{L})$ and $(k, s_{0,2}, \tilde{L})$ of z. if $L < \tilde{L}$ then set $s_0 = s_{0,1} / *s_{0,1} = s_{0,2}$ in this case*/ else set $s_0 = s_{0,1}$ when endpoint curvatures are positive and set $s_0 = s_{0,2}$ when endpoint curvatures are negative. $P(t) \leftarrow BezierPolynomial(\mathbf{k}, s_0, \tilde{L})$ $Q(t) \leftarrow P(t)$ positioned at $(x(0), y(0), \phi(0))$. if $Collision(Q(t), \mathcal{B}_1, \ldots, \mathcal{B}_k) = \text{FALSE}$ then add z to \mathcal{O} . end while **Output:** CSpace path from S to T, when such a path exists.

Motion planning in 5-D configuration space: The flexible cable steering scheme is summarized as Algorithm 4. The algorithm is given feasible start and target cells in CSpace and a description of polygonal obstacles in the environment. The main loop of Algorithm 4 selects the current best node in the open list, $z^* \in O$, as detailed below. For each *feasible* neighbor $z \in CSpace$ of z^* , the elastica parameters of z are extracted and fed into Algorithm 3 that computes the Bézier polynomial P(t) for the cable shape. The cable base frame position extracted from z is used to place the Bézier polynomial in the physical environment as Q(t), then collision of Q(t) with the polygonal



Figure 11. Flexible cable steering around a single obstacle. (a) Flexible cable position and shape at the start and target. (b)-(c) Cable folds inward until reaching self-intersection limit while rotating away from the obstacle. (d)-(e) Cable moves to the right along obstacle bottom edge while rotating into horizontal position. (f) Cable stretches outward while circumnavigating the obstacle until its distal endpoint reaches the endpoint target position.

obstacles is efficiently checked by $Collision(Q(t), \mathcal{B}_1, \ldots, \mathcal{B}_k)$. All collision free neighboring cells of z^* are added to the open list, \mathcal{O} , and the main loop of Algorithm 4 resumes. Eventually the target becomes the best node in \mathcal{O} or the open list becomes empty. In the first case the path stored in the closed list, \mathcal{C} , provides the shortest CSpace path from S to T. In the latter case a feasible CSpace path from S to T does not exist.

VII. Representative Examples

This section describes execution examples of the steering scheme described in Section VI. The scheme was implemented on MATLAB using elliptic functions library [2].³ In all examples the flexible cable maximal flattening parameter is set to $\rho = 0.5$, so that \tilde{L} is at most twice the physical cable length.

Example 1—single obstacle: The example shown in Fig. 11 steers a unit length flexible cable in the presence of a single obstacle. The cable starts at the base frame position $(x(0), y(0), \phi(0)) = (0.12, 0.12, -135^{\circ})$ with elastica parameters $(k, s_0, \tilde{L}) = (0.671, 0, L)$. The start shape forms full period of the elastica with co-axial endpoint tangents (Fig. 11(a)). The cable target base frame position is $(x(0), y(0), \phi(0)) = (0, 0, 180^{\circ})$ with elastica parameters $(k, s_0, \tilde{L}) = (0.707, 0.9L, 1.12L)$. The target shape forms 1/1.12 of the elastica full period with equal endpoint tangents (Fig. 11(a)).

Ålgorithm 4 computed the steering path shown in Fig. 11 in 138 seconds (see video clip). The cable first folds inward until reaching self-intersection limit while rotating away from the obstacle (Fig. 11(b)-(c)). The cable now slides with small clearance along the obstacle bottom edge while rotating into horizontal position (Fig. 11(d)). When the cable distal endpoint reaches the obstacle bottom right corner (Fig. 11(e)), the cable stretches outward by increasing \tilde{L} and decreasing k until it reaches the endpoint target position (Fig. 11(f)). Note that equal endpoint tangents are maintained during cable steering \circ

³All simulations run MATLAB-22B on DELL OptiPlex 7080, with Intel I7-10700 CPU running at 2.90 GHz and 16 GB main memory.



Figure 12. Flexible cable steering through an opening between two obstacles. (a) Start and target have the same base frame position (see text for distance to target estimates). (b) Cable folds inward while its mid-section slides under left-obstacle bottom edge. (c) Cable reaches the right obstacle. (d)-(e) Cable moves away from both obstacles while stretching. (f) Cable moves between obstacles by further stretching until it reaches the distal endpoint position.

Example 2—two obstacles: The example shown in Fig. 12 steers a unit length flexible cable between two obstacles. The cable start and target share the same base frame position at $(x(0), y(0), \phi(0)) = (0.26, 0, 180^\circ)$. The cable elastica parameters for the start shape are $(k, s_0, \tilde{L}) = (0.5, 0, L)$. The start shape forms full period of the elastica with coaxial endpoint tangents (Fig. 12(a)). The cable elastica parameters for the target shape are $(k, s_0, \tilde{L}) = (0.707, 1.15L, 1.32L)$. The target shape forms 1/1.32 of the elastica full period with equal endpoint tangents (Fig. 12(a)).

Algorithm 4 computed the steering path shown in Fig. 12 in 40 seconds (see video clip). The cable first folds inward while its mid-section slides with small clearance along the leftobstacle bottom edge (Fig. 12(b)). When the cable mid-section reaches the right obstacle (Fig. 12(c)), it moves away from both obstacles while increasing \tilde{L} in order to stretch and reduce height with respect to its elastica axis (Fig. 12(d)-(e)). The cable distal endpoint now moves between the two obstacles by further increasing \tilde{L} while decreasing k in order to bring the cable endpoint to its target position (Fig. 12(f)).

Practical A^* path planning: Algorithm 4 searches the feasible cells of CSpace using the open list nodes, $z \in O$, sorted by *trip length estimate* from S to T through z. Trip length is measured as the sum l(S, z)+l(z, T), where l(S, z) measures the c-space path length traveled from S to z while l(z,T) estimates the c-space path length yet to be travelled from z to T. The simplest choice for l(z,T) would be Euclidean distance to the target computed in CSpace

$$l(z,T) = \left((x_z(0) - x_T(0))^2 + (x_z(0) - x_T(0))^2 + a \cdot (\phi_z(0) - \phi_T(0))^2 + (X_{L,z} - X_{L,T})^2 + (Y_{L,z} - Y_{L,T})^2 \right)^{1/2}$$

where $(x_z(0), y_z(0), \phi_z(0), X_{L,z}, Y_{L,z})$ are the c-space coordinates of z, $(x_T(0), y_T(0), \phi_T(0), X_{L,T}, Y_{L,T})$ are the c-space coordinates of T and a > 0 is a scaling constant. Using the Euclidean distance estimate, Algorithm 4 took 168 seconds to compute a steering path for Example 2. When the start and target were switched in Example 2, Algorithm 4 took significantly longer time of 816 seconds to compute a steering



Figure 13. Flexible cable steering in a confined environment containing three obstacles. (a) Flexible cable position and shape at the start and target. (b) Cable folds inward until reaching self-intersection limit while rotating inplace. (c) Cable slides in maximally compressed shape through narrow opening between left obstacles. (d) Cable rotates into vertical position. (e)-(f) Cable stretches outward until both endpoints reach their target positions.

path. However, one expects *shorter* runtime when the cable starts within the opening between the two obstacles.

A practical speedup that also gives shorter computation time when the start and target are switched works when the cable's start-and-target base frames are located close to each other. In these situations one can compute the *shortest collision free path* for the cable distal endpoint from start to target (Fig. 12(a)). The shortest collision free path is piecewise linear with vertices located at convex obstacle vertices. Each vertex of the shortest collision free path defines intermediate target position for the cable distal endpoint. The cable is now steered using the Euclidean distance estimate for each intermediate target. In Example 2, three intermediate endpoint targets allowed Algorithm 4 to compute a steering path from start to target in 40 seconds and in shorter time of 37 seconds for the switched start and target in this example.

Example 3—multiple obstacles: The example shown in Fig. 13 steers a unit length flexible cable in a confined environment having unit x and y dimensions and containing three obstacles. The cable starts at the base frame position $(x(0), y(0), \phi(0)) = (0.03, 0.33, 0)$ with elastica parameters $(k, s_0, \tilde{L}) = (0.675, 0.45L, L)$. The start shape forms full period of the elastica with equal endpoint tangents (Fig. 13(a)). The cable target is located at the base frame position $(x(0), y(0), \phi(0)) = (0.21, 0.12, 0)$ with elastica parameters $(k, s_0, \tilde{L}) = (0.55, 0.5L, 1.37L)$. The target shape forms 1/1.37 of the elastica full period with equal endpoint tangents (Fig. 13(a)).

Ålgorithm 4 computed the steering path shown in Fig. 13 in 180 seconds (see video clip). The cable first folds inward until reaching self-intersection limit while rotating in-place into horizontal position (Fig. 13(b)). The cable next slides in maximally compressed shape through the narrow opening



Figure 14. Flexible cable steering through an opening between two obstacles. (a) The gap $d_1 = 0.29$ allows cable steering through the opening. (b) The gap $d_2 = 0.23$ barely allows the cable to move through the opening in a self-folded shape. (c) The gap $d_3 = 0.15$ disconnects the start and target when the flexible cable is not allowed to deform against obstacles.

between the left obstacles (Fig. 13(c)). When the cable reaches the open area beyond the narrow opening it rotates into vertical position (Fig. 13(d)). The cable now stretches outward at both endpoints by increasing \tilde{L} and decreasing k (Fig. 13(e)), until both endpoints reach their target positions (Fig. 13(f)).

The environment depicted in Fig. 13 highlights the steering scheme limitation to sparsely spaced obstacles. Consider the confined environment of Fig. 14 which has unit x and y dimensions. In Fig. 14(a), the gap $d_1 = 0.29$ allows cable steering through the opening (Example 3). In Fig. 14(b), the gap $d_2 = 0.23$ barely allows the cable to move through the opening in a self-folded shape, roughly confined to a rectangle of dimensions $0.15L \times 0.4L$ (Fig. 4). When the gap reduces to $d_3 = 0.15$, Algorithm 4 reports that a feasible steering path no longer exists between start and target.

VIII. Conclusion

The paper considered flexible cable steering by two robot hands that impose endpoint positions and tangents in twodimensions. The robot hands steer the flexible cable while maintaining equal endpoint tangents, thus reducing the planning problem into five configuration variables. The paper described the Euler's elastica solutions for the flexible cable equilibrium shapes. The elastica solutions were then used to develop several tools that were incorporated into a flexible cable steering scheme among sparsely spaced obstacles.

The paper first developed analytic equations that determine the cable elastica parameters in terms of the endpoint positions and tangents imposed by the robot hands. The paper next described the range of the elastica modulus parameter that ensures non self-intersection. Using the notion of conjugate point, the paper established a criterion for the flexible cable stability: all cable shapes that form less than full period of the elastica (midpoint inflection point) or full period of the elastica (two internal inflection points) are automatically stable. Last, the paper described an approximation of the flexible cable equilibrium shapes by convex quadratic arcs that allow efficient collision check against obstacles during steering.

The new tools were incorporated into a steering scheme for flexible cables in two-dimensions by two robot hands. The steering scheme has been implemented and execution examples demonstrated the flexible cable motion between start and target while avoiding self-intersection and collision with sparsely placed obstacles in the environment.

Future research will extend this paper in two important ways. The first extension will consider flexible cable steering by two robot hands under gravity in two-dimensions. The flexible cable equilibrium shapes now minimize the cable elastic and gravitational energies

$$\mathcal{E} = \int_0^L \left(\frac{1}{2}EI \cdot \kappa^2(s) + \rho g \cdot y(s)\right) ds$$

where $\kappa(s)$ is the cable curvature, y(s) is the cable vertical coordinate and L is the cable length. The cable stiffness, EI, and the cable mass density, ρ , are known parameters such that

 $m = \rho L$ is the cable mass. When ρ is small relative to EI, the elastica solutions characterize the cable equilibrium shapes. When ρ is large relative to EI, the cable behaves like a chain that attains *catenary* equilibrium shapes under gravity. A promising approach would be to blend the two analytic solutions into reasonably accurate approximation of the true equilibrium shape. The blending technique will then be augmented with the tools developed in this paper into flexible cable steering scheme under gravity.

A more open ended extension will allow the flexible cable to deform against obstacles during steering from start to target. When friction is sufficiently high at the cable's contacts with obstacles, the flexible cable will exhibit rolling-like behavior with full segments of the cable contacting obstacles. A promising approach would be to allow the flexible cable to deform against a single wall when steered by two robot hands, while avoiding all other obstacles. Predicting the cable equilibrium shapes will require extension of this paper optimal control formulation to include *pure state constraints* that capture contacts with obstacles, then use the elastica solutions to model the contact free portions of the cable with endpoints now imposed by the robot hands and the environment. The flexible cable steering scheme will likely require extra state variables that will measure the cable contacts against the environment.

The extensions will eventually allow steering *flexible strips* by two robot hands in 3-D under the influence of gravity. Suitably designed robot grippers can impose *line contacts* at the flexible strip opposing ends. By maintaining parallel line contacts during 3-D manipulation, flexible strip steering by two robot hands would become a natural generalization of the steering scheme considered in this paper.

Acknowledgment

Prof. Segev from Ben-Gurion University provided highly appreciated input during the preparation of this paper.

APPENDIX: ELLIPTIC FUNCTION DETAILS

This appendix verifies the formulas for the flexible cable curvature and tangent given in Section II. Let us first verify that the flexible cable curvature

$$\kappa(s) = -2\sqrt{\lambda}\mathbf{k} \cdot cn(\sqrt{\lambda}(s_0 + s), \mathbf{k}) \tag{22}$$

solves the elastic energy extremum conditions of Eq. (3)-(4). The two extremum conditions are equivalent to the single condition $H(s) = H^*$ for $s \in [0, L]$, that can be written as

 $\frac{1}{2}EI \cdot \kappa^2(s) + H^* = \lambda_r \cdot \cos(\phi(s) - \phi_0) \quad s \in [0, L].$ (23) Eq. (23) is next convected into an equivalent condition that involves only the cable curvature, $\kappa(s)$. Taking the derivative of Eq. (23) with respect to s gives

$$EI \cdot \frac{d}{ds} \kappa(s) = -\lambda_r \cdot \sin(\phi(s) - \phi_0) \quad s \in [0, L].$$
(24)

where we used the chain rule and then canceled the common factor $\kappa(s) = \frac{d}{ds}\phi(s)$. Eqs (23)-(24) combine into a single implicit differential equation in $\kappa(s)$

$$\left(\frac{1}{2}EI \cdot \kappa^2(s) + H^*\right)^2 + \left(EI \cdot \frac{d}{ds}\kappa(s)\right)^2 = \lambda_r^2.$$
(25)

From Section II, $H^* = \lambda_r \cdot (1 - 2k^2)$. Substituting for H^* in Eq. (25) gives

$$\left(\frac{1}{2}EI \cdot \kappa^2(s) + \lambda_r \cdot (1-2k^2)\right)^2 + \left(EI \cdot \frac{d}{ds}\kappa(s)\right)^2 = \lambda_r^2.$$
(26)

The derivative of $cn(u, \mathbf{k})$ is given by the rule: $\frac{a}{du}cn(u, \mathbf{k}) = -sn(u, \mathbf{k}) \cdot dn(u, k)$, where $sn(u, \mathbf{k})$ is the elliptic sine function and $dn(u, \mathbf{k})$ is the *elliptic delta amplitude* [21]. Applying this derivative rule to $\kappa(s)$ in Eq. (22) gives

$$\frac{d}{ds}\kappa(s) = 2\lambda \cdot sn(\sqrt{\lambda}(s_0+s),\mathbf{k}) \cdot dn(\sqrt{\lambda}\cdot s,\mathbf{k}).$$
(27)

where we used the chain rule. Substituting for $\kappa(s)$ and $\frac{d}{ds}\kappa(s)$ according to Eqs. (22) and (27) in Eq. (26) gives the equation

$$(2k^2 \cdot cn^2(\sqrt{\lambda}(s_0+s), k) + (1-2k^2))^2 + 4k^2 \cdot sn^2(\sqrt{\lambda}(s_0+s), k) \cdot dn^2(\sqrt{\lambda}(s_0+s), k) = 1$$
 (28)

where we substituted $\lambda = \lambda_r/EI$ then canceled the resulting common factor λ_r^2 . The first summand in Eq. (28) can be simplified as $(1-2k^2sn^2(\sqrt{\lambda}(s_0+s),k))^2$. The function dn(u,k)satisfies the relation $dn^2(u,k) = 1-k^2 \cdot sn^2(u,k)$. Substituting for $dn^2(u,k)$ in Eq. (28) and using the simplified summand gives the relation

$$1 - 4k^2 \cdot sn^2(\sqrt{\lambda}(s_0+s),k)) \left(1 - k^2 sn^2(\sqrt{\lambda}(s_0+s),k)\right) + 4k^2 \cdot sn^2(\sqrt{\lambda}(s_0+s),k) \left(1 - k^2 sn^2(\sqrt{\lambda}(s_0+s),k)\right) = 0$$

 $+4k^2 \cdot sn^2(\sqrt{\lambda(s_0+s)}, k)(1-k^2sn^2(\sqrt{\lambda(s_0+s)}, k)) = 1$ which validates the formula for the flexible cable curvature.

Let us next verify the formula for the flexible cable tangent $\left(\int_{-\infty}^{\infty} f(x) dx \right) = \int_{-\infty}^{\infty} f(x) dx$

 $\sin\left(\frac{1}{2}(\phi(s) - \phi_0)\right) = -\mathbf{k} \cdot sn(\sqrt{\lambda} \cdot (s_0 + s), \mathbf{k}).$ (29) Taking the derivative of both sides of Eq. (29) with respect to *s* using the derivative rule $\frac{d}{du}sn(u, \mathbf{k}) = cn(u, \mathbf{k}) \cdot dn(u, k)$ [21] gives

$$\frac{1}{2}\cos(\frac{1}{2}(\phi(s)-\phi_0))\cdot\frac{d}{ds}\phi(s) = -\sqrt{\lambda}\mathbf{k}\cdot cn(\sqrt{\lambda}\cdot(s_0+s),\mathbf{k})\cdot dn(\sqrt{\lambda}\cdot(s_0+s),\mathbf{k}).$$
(30)

where we used the chain rule. Since $\kappa(s) = \frac{d}{ds}\phi(s)$ on the left and $\kappa(s) = -2\sqrt{\lambda}\mathbf{k}\cdot cn(\sqrt{\lambda}(s_0+s),\mathbf{k})$ on the right of Eq. (30), it suffices to validate the relation

$$\cos\left(\frac{1}{2}(\phi(s) - \phi_0)\right) = dn\left(\sqrt{\lambda} \cdot (s_0 + s), \mathbf{k}\right)$$

or equivalently the relation

 $\cos^2\left(\frac{1}{2}\left(\phi(s) - \phi_0\right)\right) = dn^2\left(\sqrt{\lambda} \cdot (s_0 + s), \mathbf{k}\right).$

Using the identity $dn^2(u, \mathbf{k}) + \mathbf{k}^2 s n^2(u, \mathbf{k}) = 1$ [21], it suffices to verify the relation

 $\cos^{2}(\frac{1}{2}(\phi(s)-\phi_{0})) = 1 - k^{2} \cdot sn^{2}(\sqrt{\lambda} \cdot (s_{0}+s), k).$ (31) The sum of $\sin^{2}(\frac{1}{2}(\phi(s)-\phi_{0}))$ according to Eq. (29) and $\cos^{2}(\frac{1}{2}(\phi(s)-\phi_{0}))$ according to Eq. (31) becomes

 $\sin^{2}\left(\frac{1}{2}(\phi(s)-\phi_{0})\right) + \cos^{2}\left(\frac{1}{2}(\phi(s)-\phi_{0})\right) = k^{2} \cdot sn^{2}\left(\sqrt{\lambda} \cdot (s_{0}+s), k\right) + \left(1-k^{2} \cdot sn^{2}\left(\sqrt{\lambda} \cdot (s_{0}+s), k\right)\right) = 1$ which validates the formula for the flexible cable tangent.

REFERENCES

- [1] O. Aghajanzadeh et al. "Adaptive Deformation Control for Elastic Linear Objects". In: *Frontiers in Robotics and AI* 9 (Article 868459, 2022), pp. 1–13.
- [2] M. Batista. "Elfun18 A collection of MATLAB functions for the computation of elliptic integrals and Jacobian elliptic functions of real arguments". In: *SoftwareX*, http://www.sciencedirect.com/journal/softwarex 10 (2019), pp. 1–10.
- [3] M. Batista. "On Stability of Elastic Rod Planar Equilibrium Configurations". In: *Int. J. of Solids and Structures* 72 (2015), pp. 144–152.
- [4] J. Z. Ben-Asher. Optimal Control Theory with Aerospace Applications. Reston, Virginia: AIAA Inc., 2010.
- [5] P. E. Bézier and S. Sioussio. "Semi-Automatic System for Defining Free-Form Curves and Surfaces". In: *Computer Aided Design* 5.2 (1983), pp. 65–72.
- [6] D. Brander et al. "Bézier curves that are close to elastica". In: *Science Direct* 104 (2017), pp. 36–44.

- [7] T. Bretl and Z. McCarthy. "Quasi-Static Manipulation of a Kirchhoff Elastic Rod Based on Geometric Analysis of Equilibrium Configurations". In: *The Int, J. of Robotics Research* 33.1 (2014), pp. 48–68.
- [8] I. M. Gelfand and S. V. Fomin. *Calculus of Variations*. NY: Moscow State University, published in english by Prentice-Hall then by Dover, 1963.
- [9] V. G. A. Goss. "Snap Buckling, Writhing and Loop Formation in Twisted Rods". PhD thesis. Center for Nonlinear Dynamics, University College of London, 2003.
- [10] R. F. Hartl, S. P. Sethi, and R. G. Vickson. "A Survey of the Maximum Principles for Optimal Control Problems with State Constraints". In: *SIAM Review* 37.2 (1995), pp. 181–218.
- [11] R. C. Jackson and M. C. Cavusoglu. "Needle Path Planning for Autonomous Robotic Surgical Suturing". In: *IEEE Int. Conf. on Robotics and Automation*. 2013, pp. 1669–1675.
- [12] S. Javdani et al. "Modeling and Perception of Deformable One-Dimensional Objects". In: *IEEE Int. Conf. on Robotics and Automation*. 2011, pp. 1607– 1614.
- [13] X. Jiang et al. "Robotized Assembly of a Wire Harness in a Car Production Line". In: *Advanced Robotics* 25.3-4 (2011), pp. 473–489.
- [14] R. Lagneau, A. Krupa, and M. Marchal. "Automatic Shape Control of Deformable Wires based on Model-Free Visual Servoing". In: *IEEE Robotics and Automation Letters*, 5.4 (2020), pp. 5252–5259.
- [15] S.V. Levyakov. "Stability Analysis of Curvilinear Configurations of an Inextensible Elastic Rod with Clamped Ends". In: *Mechanics Research Communications* 36.5 (2009), pp. 612–617.
- [16] S.V. Levyakov and V. V. Kuznetsov. "Stability Analysis of Planar Equilibrium Configurations of Elastic Rods Subjected to End Loads". In: *Acta Mech* 211 (2010), pp. 73–87.
- [17] A. Love. *The Mathematical Theory of Elasticity*. Dover, New York, 1944.
- [18] M. Moll and L. E. Kavraki. "Path Planning for Deformable Linear Objects". In: *IEEE Transactions on Robotics* 22.4 (2006), pp. 625–636.
- [19] M. Mukadam, A. Borum, and T. Bretl. "IEEE/RSJ Int. Conf. on Intelligent Robots and Systems". In: *Quasi-Static Manipulation of a Planar Elastic Rod Using Multiple Robotic Grippers*. 2014, pp. 55–60.
- [20] L. S. Pontryagin et al. *The Mathematical Theory of Optimal Processes*. Interscience Publishers John Wiley & Sons, New York-London, 1962.
- [21] V. Prasolov and Y. Solovyev. *Elliptic Functions and Elliptic Integrals*. AMS, Providence, RI, 1997.
- [22] Y. L. Sachkov. "Conjugate Points in Euler's Elastic Problem". In: J. of Dynamical and Control Systems 14 (2008), pp. 409–439.

- [23] Y. L. Sachkov. "Maxwell Strata in the Euler Elastic Problem". In: J. of Dynamical and Control Systems 14 (2008), pp. 169–234.
- [24] Y. L. Sachkov and S. V. Levyakov. "Stability of Inflectional Elastica Centered at Vertices or Inflection Points". In: *Proceedings of the Steklov Institute of Mathematics* 271 (2011), pp. 177–192.
- [25] A. Sintov et al. "Motion Planning for Dual-Arm Manipulation of Elastic Rods". In: *IEEE Robotics and Automation Letters* 5.4 (2020), pp. 6065–6072.
- [26] J. Till and D. Rucker. "Elastic Stability of Cosserat Rods and Parallel Continuum Robots". In: *IEEE Transactions* on Robotics 33.3 (2017), pp. 1–16.
- [27] S. P. Timoshenko and J. N. Goodier. *Theory of Elastic-ity*. 3rd. New York: McGraw-Hill, 1969.
- [28] V. Viswanath et al. "Autonomously Untangling Long Cables". In: *Robotics: Science and Systems,* DOI:10.15607/RSS.2022.XVIII.034. 2022.
- [29] H. Wakamatsu, E. Arai, and S. Hirai. "Knotting/Unknotting Manipulation of Deformable Linear Objects". In: *The Int. J. of Robotics Research* 25.4 (2006), pp. 371–395.
- [30] W. Wang, M. Bell, and D. Balkcom. "Towards Arranging and Tightening Knots and Unknots With Fixtures". In: *IEEE Trans. on Automation Science and Engineering* 12 (2015), pp. 1318–1331.
- [31] Z. Wang, S. Hirai, and S. Kawamura. "Challenges and Opportunities in Robotic Food Handling: A Review". In: *Frontiers in Robotics and AI* 8 (Article 789107, 2022), pp. 1–12.
- [32] J. Zhu et al. "Challenges and Outlook in Robotic Manipulation of Deformable Objects". In: *IEEE Robotics Automation Magazine* (Early Access, 2022), pp. 2–12.
- [33] J. Zhu et al. "Dual-Arm Robotic Manipulation of Flexible Cables". In: 2018 IEEE/RSJ Int. Conf. on Intelligent Robots and Systems. 2018, pp. 479–484.