A Point Process Model for Optimizing Repeated Personalized Action Delivery to Users

Alexander Merkov and David Rohde

January 7, 2025

1 Introduction

This paper provides a formalism for an important class of causal inference problems and then goes on to propose solutions to some interesting special cases. The problem of interest is that we have observations of I users interacting with some system, e.g. people interacting with an advertising system. The causal aspect of the problem occurs because the system will have an opportunity to intervene on each users possibly multiple times. Additionally the system is able to personalize the actions being delivered to the users, there will be an initial observation of how the users behaves before any action has been delivered, in addition between each system actions there will be additional observations that may be used to further personalize the delivery of future actions.

In section 2 we describe a very general idea of the proposed approach, too general to be implemented without further specification. In section 3 we show one of possible ways to specify the data accurately enough to give to this idea an exact formulation. In section 4 we show one of possible classical technologies applicable to implement this approach in simple cases.

2 General Idea

Let u identify a user, and let \mathcal{H}_0^u be the information observed on user u at the time the system has its first opportunity to act. The action delivered is then denoted a_1^u . After this action is delivered some more behavior of the user is observed, the information observed after the first action is delivered, and before the second request to act is denoted \mathcal{H}_1^u , this is then followed by the second action a_2^u , and this sequence continues until some criterion is met and we have made $S^u + 1$ observations, and delivered S^u actions. Imagine that we have a set of logs

 $\mathcal{D} = \{\mathcal{H}^u_{0:S^u}, a^u_{1:S^u}\}^I_{u=1} = \left(\{\mathcal{H}^u_{0:S^u}\}^I_{u=1}, \{a^u_{1:S^u}\}^I_{u=1}\right) =: (H(\mathcal{D}), A(\mathcal{D}))^1$

¹By $X_{i:j}$ we denote the sequence $X_i, X_{i+1}, \ldots, X_j$, possibly empty if j < i.

produced by I independent stationary random processes with common probability distributions $P(\mathcal{H}_k|\mathcal{H}_{0:k-1}, a_{1:k-1}; \theta)$ (i.e. the probability of the observation² given its pre-history and the parameter) parameterized by θ of some parameter space Θ . Then we can write the likelihood of the observations in this dataset given the actions there and this parameter:

$$P(H(\mathcal{D})|A(\mathcal{D}),\theta) = \prod_{i}^{I} P(\mathcal{H}_{S^{u}}^{u}|\mathcal{H}_{0:S^{u}-1}^{u}, a_{1:S^{u}}^{u}, \theta) \times \dots \times P(\mathcal{H}_{1}^{u}|\mathcal{H}_{0}^{u}, a_{1}^{u}, \theta) P(\mathcal{H}_{0}^{u}|\theta)$$

$$(1)$$

where the same rather abstract parameter θ parameterizes a series of distributions on the uncertain space of "observations" conditioned on sequences of any length of "observations" separated with "actions". Similarly, given some prior distribution $P(\theta)$, the posterior can be written:

$$P(\theta|\mathcal{D}) \propto P(\theta)P(H(\mathcal{D})|A(\mathcal{D}),\theta)$$
(2)

up to proportionality.

This model makes few assumptions other than stationarity, and arrow of time assumptions, i.e. actions only impact observations after they were delivered, and the assumption that actions delivered to a users do not affect another users (an assumption sometimes called SUTVA [14]). This formulation is useful for determining how strongly past data supports or contradicts different values of the parameters, but it is inherently tied to the actions actually delivered. Usually in practice we are interested in the strategy, algorithm or to deliver (personalized) actions. We will adopt the convention of calling this algorithm a *policy* and will write it as a probability distribution i.e. $\pi_{\xi}(a_s|a_{1:s-1}, \mathcal{H}_{0:s-1})$ which denotes the probability of the *s*-th action personalized on the basis of s-1previous actions and observations within a family of distributions parameterized by some parameter ξ within some parameter space Ξ . It should be noted that the policy is set by the system and is not something that should be predicted. The predictive distribution for a policy $\pi_x i$ with parameters ξ now becomes:

$$P(\mathcal{H}_{0:S}, a_{1:S}|\xi, \mathcal{D}) = \left(\prod_{s=1}^{S} P(\mathcal{H}_s|\mathcal{H}_{0:s-1}, a_{1:s}, \mathcal{D})\pi_{\xi}(a_s|a_{1:s-1}, \mathcal{H}_{0:s-1})\right) P(\mathcal{H}_0|\mathcal{D})$$

where S + 1 is the number of observations, S is the number of opportunities to act,

$$P(\mathcal{H}_s|\mathcal{H}_{0:s-1}, a_{1:s}, \mathcal{D}) = \int P(\mathcal{H}_s|\mathcal{H}_{0:s-1}, a_{1:s}, \theta) P(\theta|\mathcal{D}) d\theta.$$

 $^{^2 \}rm We$ have defined neither the space of observations, nor a probabilistic measure on it yet. It will be done in the next sections.

 $P(\mathcal{H}_0|\mathcal{D}) = \int P(\mathcal{H}_0|\theta) P(\theta|\mathcal{D}) d\theta$

are known up to proportionality.

To define optimization of the policy we need to define what and under what condition to optimize. We choose some real-valued utility function U defined on sequences of observations and actions $(\mathcal{H}_{0:S}, a_{1:S})$ of any length S, the larger utility, the better. And we need to define some criterion how to start and stop the sequence to compute *its utility* we are interested in.

Example. For a toy criterion of fixed length S of the sequence $(\mathcal{H}_{0:S}, a_{1:S})$ we can specify the *expected utility* under the predictive distribution θ of the policy π_{ξ} for sequences of length S using:

$$\mathcal{U}(\pi_{\xi};\theta,S) = \mathbf{E}_{(\mathcal{H}_{0:S},a_{1:S})\sim P(\mathcal{H}_{0:S},a_{1:S}|\xi,\theta)} U(\mathcal{H}_{0:S},a_{1:S})$$
(3)

or alternatively

$$\mathcal{U}(\xi; \mathcal{D}, S) = \mathbf{E}_{(\mathcal{H}_{0:S}, a_{1:S}) \sim P(\mathcal{H}_{0:S}, a_{1:S} | \xi, \mathcal{D})} U(\mathcal{H}_{0:S}, a_{1:S})$$
(4)

One way to maximize the expected utility is inspired by the Reinforce algorithm [20] namely, stochastic gradient maximization of $\mathcal{U}(\xi; \mathcal{D}, C)$ with respect to ξ for some end-of-sequence criterion C using an approximation of the expected utility as the mean utility on the data sampled from the distribution learnt from available dataset \mathcal{D} . See rather informal algorithm 1.

and

Algorithm 1 stochastic gradient maximization of the expected utility # Convergence and "End of Session" conditions should be specified. # Gradient step parameter λ should be described.

```
\# to be specified
initialize \xi
while Not Converged do
       \theta \sim P(\theta|\mathcal{D})
                                  \# sampling from the distribution known only up to
proportionality requires some explanation
     \mathcal{H}_0 \sim P(\mathcal{H}_0|\theta)
     s \leftarrow 1
     while True do
          a_s \sim \pi_{\xi}(a_s | a_{1:s-1}, \mathcal{H}_{0:s-1})
          \mathcal{H}_s \sim P(\mathcal{H}_s | \mathcal{H}_{0:s-1}, a_{1:s}, \theta)
          if End of Session Condition Met then
               S = s: break
          end if
          s \leftarrow s + 1
     end while
    \xi \leftarrow \xi + \lambda \ U(\mathcal{H}_{0:S}, a_{1:S}) \left( \sum_{s=1}^{S} \nabla_{\xi} \log \pi_{\xi}(a_s | \mathcal{H}_{0:s-1}, a_{1:s-1}) \right)
            # the gradient step size \lambda > 0 should be defined somehow
end while
return \xi
```

This formulation is simply Bayesian decision theory [3] applied to a specific causal problem involving multiple opportunities to personalize treatment to multiple users under stationarity and SUTVA assumptions. It could also be viewed as a Bayesian application of reinforcement learning. In other respects we will also focus on a problem that also falls a little outside the traditional remit of reinforcement learning where both information we learn about the users and opportunities to act upon the users arise asynchronously.

We will also assume that there is no unobserved confounding. While this might seem like a strong assumption it is often absolutely satisfied, as it only requires that the actions are delivered using some policy $\pi_{\xi}(a_s|\mathcal{H}_{0:s-1})$, independent of anything not available in the logs within \mathcal{D} . Obviously by construction online interactive systems will not suffer from unobserved confounding³. We disagree with the impression given in [19, 7, 4] that unobserved confounding is an unavoidable problem in interactive systems such as recommender systems, or computational advertising, and there is no need to use statistical methods to deal with confounding.

Furthermore, there is no use of any formalized *causal inference* such as the do-calculus [8]. This is because *causal inference is just inference* [5, 11]. Similarly there is no need to use the propensity score [13] either as a balancing score to remove confounding [13] (for reasons already explained) nor as a means to compute the expected utility of the policy using the (non-Bayesian) Horvitz-

³Poor practices such as having hierarchies of models accessing different features can and do cause such systems to be susceptible to unobserved confounding, see [12] for more discussion.

Thompson estimator [2]. From a Bayesian perspective the propensity score should not be used, and indeed violates the likelihood principle [1], although it's noteworth that this estimator is at the center of one of the most intense debates in statistics in recent times [10, 18, 9].

The model we have developed so far is extremely generic and no attention has been given to what type of information is observed in \mathcal{H}_s^u , and what type of action is denoted in a_s^u . The rest of this document will develop models for cases inspired by interactive systems such as real time bidding and recommender systems, inspired in part by [6]. An important aspect of these problems is that the observations are sequences of time-stamped events and some of the events cause actions. In order to handle this situation we will adopt the framework of neural temporal point processes [17], and we will discuss suitable models that simultaneously satisfy a) being a good model for a real system; b) have a tractable likelihood; and c) can be efficiently simulated from (enabling policy optimization).

3 Temporal Point Processes for Repeated Action Personalization

We haven't yet specified what information is contained in \mathcal{H}_s^u , we will remedy this situation now, focusing on our problem class where both information and opportunities to act are synchronized in a specific way. Our primary purpose is to formalize the timing and causation of what happens.

Observations \mathcal{H}_s^u are time-ordered sequences of events e_k^u . Observation on the user u begins at time t_0^u , either pre-defined or when a special event e_0^u 'the user appeared' happens, and goes on until time $t_0^u + t_{\max}$. What happens to user u after t_0^u is a finite sequence of B^u events $e_1^u, \ldots, e_{B^u}^u$ of different types initiated by the user and actions made by the "decision maker"⁴. Each action is necessarily caused by an event of certain type and happens immediately after it⁵. So the actions will be considered as additional features of events of certain type(s) say, 'request for action' or 'request to display an ad'. For events of the types which cannot cause actions these additional features get some fixed value, say, 0.

Each event e is featured with its timestamp t (real), type v (categorical), feature vector x whose structure depends on the type: e = (t, v, x), and it can be augmented with additional feature vector of the caused action: $\bar{e} = (t, v, x, f)$. For terminological compatibility with marked temporal point processes (MTPP) the pair m = (v, x) of the type and the features of and event will be called its mark. Type v which can take values like 'click an ad', 'view an item', etc. featured with the ad- or item-dependent features, and a distinguished value 'request for action' featured with the action happened.

⁴E.g. an advertising system.

 $^{^5{\}rm E.g.}$ the user opens a web page of certain publisher and the advertiser decides to display (and displays!) some ads on its margins.

Let $B_0^u = 0$, $B_1^u < \cdots < B_{S^u}^u$ be the indexes of all events e^u of type 'request for action', and $B_{S^u+1}^u = B^u$ be the index of the last event. They split the sequence $e_{1:B^u}^u$ of all such events into $S^u + 1$ segments $e_{(B_{s-1}^u+1):B_s^u}^u$, all of which, except possibly the last $(S^u + 1)$ -th one, end with an event caused an action. These history segments consist of the "information" \mathcal{H}_s^u mentioned in section 1. Segments of augmented events $\bar{e}_{(B_{s-1}^u+1):B_s^u}^u$ contain also the knowledge of the action a_s^u followed, and they also explicitly contain the information on the timing.

This notation lets us write $\mathcal{H}_{0:S^u}^u = e_{1:B^u}^u = (t, m)_{1:B^u}^u = (t, v, x)_{1:B^u}^u$ and $(\mathcal{H}_{0:S^u}^u, a_{1:S^u}^u) = \bar{e}_{1:B^u}^u = (t, m, f)_{1:B^u}^u = (t, v, x, f)_{1:B^u}^u$, whichever detailization level we prefer.

Now we can refine formula (1), algorithm 1 and, for instance, turn the "sampling $\mathcal{H}_s \sim P(\mathcal{H}_s | \mathcal{H}_{0:s-1}, a_{1:s}, \theta)$ " from a good wish in unspecified huge-dimensional space to somewhat modest-dimensional and implementable.

3.1 Marked Temporal Point Process: a probabilistic model

Instead of rather abstract distributions $P(\mathcal{H}_{s}^{u}|\mathcal{H}_{1:s-1}^{u}, a_{1:s}^{u}, \theta)$ of section 1 we can describe much simpler (but still rather complex) distributions of individual events $P(e_{k}|e_{1:k-1}, \theta)$ conditioned on the preceding ones. For simplicity we suppose in this section that the space of features x is finite so there are finitely many possible "marks" m = (v, x).

To reflect the supposed independence of the distributions of the users and stationarity of the process, we remove the users from notation and provide either real or fictitious event e_0 of special type 'start of observations' at time t_0 . For each subsequent event its probability will be written not in terms of its absolute time t_k but of its delay $\tau_k = t_k - t_{k-1}$ with respect to the previous event, though in conditions we keep absolute times⁶.

$$P(e|\bar{e}_{0:k},\theta) = P((\tau,m)|(t,m,f)_{0:k},\theta)$$
(5)

Strictly speaking this formula (5) does not define a probability measure because the next event might never happen with positive probability. To fix it we add the 'no-event' $e_{\infty} = (\tau_{\infty}, m_{\infty}) = (\infty, \infty)$ to the event space. But we will never include this 'no-event' into an event sequence.

Now the probability of the users's history seemingly can be written as the product of much simpler low-dimensional distributions

$$P(\mathcal{H}_{0:S^{u}}^{u}|a_{1:S^{u}}^{u},\theta) = P(e_{1:B^{u}}^{u}|a_{1:S^{u}}^{u},\theta) = \prod_{k=1}^{B^{u}} P(e_{k}^{u}|\bar{e}_{0:k-1}^{u},\theta)$$
$$= \prod_{k=1}^{B^{u}} P((\tau,m)_{k}^{u}|(t,m,f)_{0:k-1}^{u},\theta) \quad (6)$$

 $^6\mathrm{The}$ distribution might depend on the day of week

But this is not all the truth. Why had the sequence of events ended at $e_{B^u}^u$? Because the number B^u was predefined, because 'no-event' e_{∞} appeared, or just because the observation time exceeded some predefined limit $t_0^u + t_{\max}$? In the latter case the probability depends also on t_{\max} :

$$P(e_{1:B}^{u}|t_{\max},\theta) = \prod_{k=1}^{B^{u}} P((\tau_{k},m_{k})^{u}|(t,m,f)_{0:k-1}^{u},\theta)$$
(7)

$$\times \mathbf{1}_{[t_{B^{u}} \le t_{0}^{u}+t_{\max}]}$$
(7)

$$\times P(\tau > t_{0}^{u}+t_{\max}-t_{B^{u}}^{u}|(t,m,f)_{0:B^{u}}^{u},\theta)$$

We postpone considering still huge set of conditions $(t, m, f)_{0:k-1}$ and θ of the distribution $P((\tau_k, m_k)^u | (t, m, f)_{0:k-1}^u, \theta)$ until section 4 and first discuss the rather manageable space of distributions of pairs (time delay, mark) (τ, m) .

Provided the mark m belongs to some finite set $\{1, \ldots, M\} \cup \infty$, the probability of the event can be factorized as $P(e|\ldots) = P((\tau, m)|\ldots) = P(\tau|m, \ldots)Q(m|\ldots)$. The space of (M + 1)-valued multinomial distributions is M-dimensional, so if we choose a D-dimensional family of distributions on \mathbb{R}_+ for τ (for $m < \infty$), we get the (D + 1)M-dimensional space Φ of distributions $P_{\phi}, \phi \in \Phi$ of pairs (τ, m) .

For probability distributions from the space Φ all the factors of formula 7 should be easily computable, they should better be easily differentiable in parameters to learn θ if needed, and they should allow easy sampling for future policy optimization (like in algorithm 1). All this assertion are trivial for multinomial distribution $Q_{\phi}(m|\ldots)$ and might be non-trivial for time distributions $p_{\phi}(\tau|m,\ldots)$. Usually such classic few-parametric families of distribution as lognormal (two-dimensional), Erlang(a series of one-dimensional), gamma (twodimensional) are tried for time distributions $p_{\phi}(\tau|m,\ldots)$ of marked temporal point processes. In [16] it was shown that several-dozen-dimensional mixture of log-normal distribution gives better results. It was also conjectured in [16], that the reason why the mixture is better is that all the base distributions have light tails, no heavier than exponential, while in real world the delay times are heavy-tailed.

Example. We can suggest a non-standard three-dimensional family of heavy-tailed distributions on \mathbb{R}_+ which allow both easy computation and sampling from. Each distribution of this family is unimodal and parameterized by its maximum point τ^* , maximum value p^* and the power speeds α and β of decay approaching 0 and ∞ ; of these 4 parameters only 3 are independent. Its density is

$$p(\tau|\dots) = \begin{cases} \left(\frac{\tau}{\tau^*}\right)^{\alpha} p^* & \text{when } 0 \le \tau \le \tau^* \\ \left(\frac{\tau}{\tau^*}\right)^{-\beta} p^* & \text{when } \tau \ge \tau^* \end{cases}$$
(8)

where $\tau^* > 0, \alpha > 0, \beta > 1, p^* > 0$ and

$$\int_0^\infty p(\tau|\dots)d\tau = \left(\frac{1}{\alpha+1} + \frac{1}{\beta-1}\right)p^*\tau^* = 1$$
(9)

We can express, say p^* via the other parameter using (9) and plug it into (8); this gives us

$$p(\tau|\alpha,\beta,\tau^*) = \begin{cases} \frac{(\alpha+1)(\beta-1)}{(\alpha+\beta)\tau^*} \left(\frac{\tau}{\tau^*}\right)^{\alpha} & \text{when } 0 \le \tau \le \tau^* \\ \frac{(\alpha+1)(\beta-1)}{(\alpha+\beta)\tau^*} \left(\frac{\tau}{\tau^*}\right)^{-\beta} & \text{when } \tau \ge \tau^* \end{cases}$$
(10)

For such a density both the CDF

$$P(\tau|\alpha,\beta,\tau^*) = \begin{cases} \frac{\beta-1}{\alpha+\beta} \left(\frac{\tau}{\tau^*}\right)^{\alpha+1} & \text{when } 0 \le \tau \le \tau^* \\ 1 - \frac{\alpha+1}{\alpha+\beta} \left(\frac{\tau}{\tau^*}\right)^{1-\beta} & \text{when } \tau \ge \tau^* \end{cases}$$
(11)

and its inverse can also be expressed in elementary functions and computed fast, so computations of likelihoods and sampling are easy and maximization of the likelihood is $possible^7$.

4 Neural Temporal Marked Point Processes

After a family Φ of distributions P_{ϕ} , $\phi \in \Phi$ on the space of events is chosen, to model the probability $P(e|\bar{e}_{0:k}, t_{\max}, \theta)$ of an event given the previous events one can consider the parameter θ as a mapping from the space of finite time-ordered sequences $\bar{e}_{0:k}$ of events augmented with consequent actions to Φ . The set Θ of these mappings θ can be rather wide, and either an appropriate mapping $\theta^* \in \Theta$ or a posterior distribution on Θ can be learnt using some training datasets \mathcal{D} and a likelihood-based method. Such an intention was declared in formulas (1) and (2). Now we try to implement it.

As the space Θ we suggest recurrent neural networks (RNNs) in a broad sense: RNN, GRU, LSTM, Transformer, or whatever else. This approach is very popular (see survey [17]) because of sequential nature of conditioning on $\bar{e}_{0:k}$ in $P(e|\bar{e}_{0:k}, t_{\max}, \theta)$. A neural network is defined by its particular structure (the number of neurons and layers, connections between them, activation functions), which should be chosen to define the space Θ , and trainable weights which define a particular network $\theta \in \Theta$. We will not discuss the technically complicated but already classic problems of building and training of RNNs, and focus on the specifics of their application to the marked temporal point processes we are interested in.

Let us remind the general structure and usage of recurrent neural networks. Each RNN is a chain of identical subnetworks $\mathcal{R}(\theta)$ (briefly, \mathcal{R}), one for each element of the sequence to be processed, passing to each other some state vectors $\sigma_j \in \mathbb{R}^d$ where d is a structural parameter of the RNN, taking the previous augmented event \bar{e}_{j-1} and computing the parameter $\phi_j(\theta)$ (briefly ϕ_j) of the distribution P_{ϕ_j} of the current event e_j :

$$\sigma_0 = 0 \tag{12}$$

$$\phi_j = (\mathcal{R}.\phi)(\sigma_{j-1}, \bar{e}_{j-1}) \qquad j = 1, 2, \dots$$
 (13)

$$\sigma_j = (\mathcal{R}_{\cdot}\sigma)(\sigma_{j-1}, \bar{e}_{j-1}) \qquad j = 1, 2, \dots$$
(14)

⁷though with such inconveniences as non-smoothness and non-convexity

Algorithm 2 shows the current simplified approach to computation of the likelihood of the sequence of observed events within the specified time interval. If, say, $p(e|\phi) = p((\tau, m)|\phi) = p(\tau|m, \phi)Q(m|\phi)$ for some multinomial distributions $Q(\cdot|\phi)$ and $p(\cdot|\cdot)$ from the family (10), then the cumulative distribution $P(\tau|\phi)$ of all events is the mixture of the distributions $P(\tau|m, \phi)$ of shape (11) and can be computed easily.

Algorithm 2 Computation of the likelihood of the sequence of events within the specified observation time interval

Input: function $p(e|\phi)$ computing the probability density of the event Input: function $P(\tau|\phi)$ computing the cumulative probability of any event in the time interval $(0, \tau)$

Input: trained RNN $\mathcal{R}(\theta)$ computing parameter ϕ of the distribution Input: the sequence e of B time-ordered augmented events, $e_k = (t, m, f)_k$ Input: $t_0 \in \mathbb{R}, t_{\max} \in \mathbb{R}_+$ the start and the duration of the observation Output: the conditional probability $P(e|t_0, t_{\max}, \theta)$

if $((e_1).t < t_0)$ or $((e_B).t > t_0 + t_{max})$ then

return(0) # the sequence does not fit into the observation interval end if

 $k \leftarrow 0; \sigma \leftarrow 0$ # the current event number and the RNN state $e_0 \leftarrow (t_0, \text{'start'}, 0)$ # the initial (zeroth) pseudo-event r = 1# the probability to be returned while $k \leq B$ do $(\phi, \sigma) \leftarrow \mathcal{R}(\theta)(\sigma, e_k) \quad \# \text{ compute the distribution and the next state}$ $k \leftarrow k + 1$ # the next event number if $k \leq B$ then $r \leftarrow r * p((t_k - t_{k-1}, m_k)|\phi)$ else $r \leftarrow r * (1 - P(t_0 + t_{\max} - t_{k-1} | \phi))$ # no next event observed end if end while return(r)

Then the likelihood of the dataset \mathcal{D} as a result of observation of the set of I users within the time segments $[t_0^u, t_0^u + t_{\max}]^8$ given the actions $A(\mathcal{D})$ happened respectively is:

$$P(\mathcal{D}|A(\mathcal{D}), t_{\max}, \theta) = \prod_{u=1}^{I} \left(\prod_{k=1}^{B^{u}} P_{\phi_{k}^{u}(\theta)}\left((\tau, v)_{k}^{u}\right) \mathbf{1}_{\left[t_{B^{u}}^{u} \le t_{0}^{u} + t_{\max}\right]} P_{\phi_{B^{u}+1}^{u}(\theta)}\left(\tau > t_{\max} - t_{B^{u}}^{u}\right) \right)$$
(15)

⁸The time segment lengths t_{\max}^u might be set to each user individually as well, but then they had to be given explicitly. They cannot be computed just as the maximal differences between the timestamps of events of the user available in the log.

(cf. motivational formula (1) and its refinement (7); the details of computation of each of the I top level factors are presented in algorithm 2).

Remind that θ is the vector of weights of a recurrent neural network which has independent on θ and already fixed structure, so either θ can be learnt⁹ or the posterior on the set of these RNNs $\mathcal{R}(\theta)$ can be defined using $P(\mathcal{D}|\theta)$ as in formula (2). Finally, since all the distributions P_{ϕ} belong to a simple distribution class like (10)¹⁰, sampling each next event (τ, m) is easy, see algorithm 3.

Algorithm 3 Sample an event from a distribution $P((\tau, m)) = p(\tau|m)Q(m)$ for multinomial $Q(\cdot)$ and $p(\cdot|\cdot)$ from the family (10)-(11)

```
Input: M, Q = (q_1, \ldots, q_M), \sum_{m=1}^{M} q_m \le 1
Input: \alpha_m, \beta_m, \tau_m^*, m = 1, \ldots, M see (10)
 Output: the sampled event e = (\tau, m)
 ########## sample m from multinomial Q(m):
 \eta \sim U([0,1])
                                         # uniform sampling
 m \leftarrow 0, s \leftarrow 0;
 while s \leq \eta do
       if m = M then
              \operatorname{return}(\infty,\infty)
                                                 \# no more events
       end if
       m \leftarrow m + 1, s \leftarrow s + q_m;
 end while
                             # sampling in O(\log M) time is also possible<sup>11</sup>
 ########### sample \tau from P(\tau|m), namely from (11):
  \begin{aligned} \eta &\sim U([0,1]) & \text{ $\#$ uniform sampling$} \\ \text{if } \eta &< \frac{\beta_m - 1}{\alpha_m + \beta_m} \text{ then} & \text{ $\#$ compute the inverse } \left(P^{-1}(\tau | m)\right)(\eta) \end{aligned} 
\tau = \tau_m^* \left(\frac{\eta(\alpha_m + \beta_m)}{\beta_m - 1}\right)^{\frac{1}{\alpha_m + 1}}else
      \tau = \tau_m^* \left( \frac{(1-\eta)(\alpha_m + \beta_m)}{\alpha_m + 1} \right)^{-\frac{1}{\beta_m - 1}}
 end if
 \operatorname{return}(\tau,m)
```

Now, after the RNN model $\mathcal{R}(\theta)$ and training its parameter θ are more or less described and sampling an event from it is shown explicitly, we can show how to sample the event sequences and learn the policy (as announced in algorithm

⁹Very roughly speaking, learning θ , or equivalently, training the neural network $\mathcal{R}(\theta)$ given some dataset \mathcal{D} is based upon maximization of the likelihood (15) or something like that. We are not ready to discuss training of RNNs of unspecified structure in details here. See, e.g. a textbook [15]

¹⁰More exactly, to class (10) belong type-conditioned time distributions $p(\tau|m,...)$ while the overall time distribution $p(\tau|...)$ is a mixture of such distributions.

¹¹ but useless in this algorithm because is used only once for the given Q

1 rather informally). See algorithms 4 and 5.

Algorithm 4 Sample a sequence of augmented events of the desired time duration

Input: a RNN \mathcal{R} Input: function sampleNext(ϕ) (algorithm 3) Input: $t_0 \in \mathbb{R}, t_{\max} \in \mathbb{R}_+$ the start and the duration of the sampling Input: policy π_{ξ} to be applied to events of type 'request for action' Output: the length B and the sampled sequence $e_{1:B} = (t, m)_{1:B}$ # the current time and the length of the event sequence $t \leftarrow t_0; B \leftarrow 0;$ $\sigma \leftarrow 0; e_B \leftarrow (t_0, \text{'start'}, 0)$ # the RNN state and the current event while $t < t_0 + t_{\max} \operatorname{do}$ $(\phi, \sigma) \leftarrow \mathcal{R}(\sigma, e_B)$ # compute the distribution and the next state $(\tau, m) \leftarrow \text{SampleNext}(\phi)$ # sample the next event from the distribution $t \leftarrow t + \tau$ # the event absolute time if $t > t_0 + t_{\max}$ then break; # the time is over end if $B \leftarrow B + 1$ $e_B \leftarrow (t, m, 0)$ # store the new event with no action if m = 'request for action' then # sample the requested action from the policy $a \sim \pi_{\xi}(e_{0:B})$ $(e_B).f \leftarrow a$ # and store it as caused by this event end if end while

 $\operatorname{return}(B, e_{1:B})$

Algorithm 5 Stochastic gradient maximization of the policy utility

Input: trained RNN \mathcal{R} Input: function sampleEvents($\mathcal{R}, t_0, t_{\max}, \pi$) (algorithm 4) Input: $t_0 \in \mathbb{R}, t_{\max} \in \mathbb{R}_+$ the start and the duration of the sampling¹² Input: initial policy π_{ξ_0} Input: utility function U defined on the event sequences $e_{1:B}$ Input: gradient step parameter $\lambda > 0$ Input: a StopOptimization(...) criterion Output: the parameter ξ of the optimized policy π_{ξ}

 $\xi \leftarrow \xi_0$

while not StopOptimization(...) do

 $(B, e) \leftarrow \text{sampleEvents}(\mathcal{R}, t_0, t_{\max}, \pi_{\xi}) \\ \# \text{ sample an event and action sequence } \bar{e}_{1:B} \\ \xi \leftarrow \xi + \lambda U(e) \left(\sum_{k=1}^{B} \mathbf{1}_{[m_k=\text{'request for action'}]} \nabla_{\xi} \log \pi_{\xi}(f_k | e_{1:k-1}) \right) \\ \# \text{ a gradient step in the policy parameter space}$

end while

 $\operatorname{return}(\xi)$

References

- James O Berger and Robert L Wolpert. The likelihood principle. IMS, 1988.
- [2] Léon Bottou, Jonas Peters, Joaquin Quiñonero-Candela, Denis X. Charles, D. Max Chickering, Elon Portugaly, Dipankar Ray, Patrice Simard, and Ed Snelson. Counterfactual reasoning and learning systems: The example of computational advertising. *Journal of Machine Learning Research*, 14(101):3207–3260, 2013.
- [3] B. de Finetti. Foresight: its logical laws, its subjective sources. In Breakthroughs in Statistics: Foundations and Basic Theory, pages 127–133. Springer, 1992.
- [4] Ciarán Gilligan-Lee. Some applications of causal inference in the real world. YouTube, 2024.
- [5] Finnian Lattimore and David Rohde. Replacing the do-calculus with Bayes rule. arXiv preprint arXiv:1906.07125, 2019.
- [6] Randall Lewis and Jeffrey Wong. Incrementality bidding and attribution. arXiv preprint arXiv:2208.12809, 2022.

 $^{^{12}\}mathrm{In}$ fact, they have no need to be fixed and might be changed on the run.

- [7] Huishi Luo, Fuzhen Zhuang, Ruobing Xie, Hengshu Zhu, Deqing Wang, Zhulin An, and Yongjun Xu. A survey on causal inference for recommendation. *The Innovation*, 2024.
- [8] Judea Pearl. Causal diagrams for empirical research. Biometrika, 82(4):669–688, 1995.
- [9] James Robins. Robins and Wasserman respond to a nobel prize winner, 2012.
- [10] James M Robins and Ya'acov Ritov. Toward a curse of dimensionality appropriate (coda) asymptotic theory for semi-parametric models. *Statistics in medicine*, 16(3):285–319, 1997.
- [11] David Rohde. Causal inference, is just inference: A beautifully simple idea that not everyone accepts. In I (Still) Can't Believe It's Not Better! Workshop at NeurIPS 2021, pages 75–79. PMLR, 2022.
- [12] David Rohde. Position paper: Why the shooting in the dark method dominates recommender systems practice; a call to abandon anti-utopian thinking. arXiv preprint arXiv:2402.02152, 2024.
- [13] Paul R Rosenbaum and Donald B Rubin. The central role of the propensity score in observational studies for causal effects. *Biometrika*, 70(1):41–55, 1983.
- [14] Donald B Rubin. Comment: Which ifs have causal answers. Journal of the American statistical association, 81(396):961–962, 1986.
- [15] Fathi M. Salem. Recurrent Neural Networks. Springer, 2022.
- [16] Oleksandr Shchur, Marin Biloš, and Stephan Günnemann. Intensity-free learning of temporal point processes. arXiv preprint arXiv:1909.12127, 2019.
- [17] Oleksandr Shchur, Ali Caner Türkmen, Tim Januschowski, and Stephan Günnemann. Neural temporal point processes: A review. arXiv preprint arXiv:2104.03528, 2021.
- [18] Christopher Sims. On an example of Larry Wasserman. online manuscript, available from Link, 2(10), 2006.
- [19] Yixin Wang, Dawen Liang, Laurent Charlin, and David M Blei. Causal inference for recommender systems. In Proceedings of the 14th ACM Conference on Recommender Systems, pages 426–431, 2020.
- [20] Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8:229–256, 1992.