Piano Transcription by Hierarchical Language Modeling with Pretrained Roll-based Encoders

Dichucheng Li

DSP Lab, Electrical Engineering Dept. The Chinese University of Hong Kong Hong Kong SAR, China dccli21@m.fudan.edu.cn Yongyi Zang Independent Researcher Seattle, WA, USA zyy0116@gmail.com Qiuqiang Kong[†] DSP Lab, Electrical Engineering Dept. The Chinese University of Hong Kong Hong Kong SAR, China qqkong@ee.cuhk.edu.hk

Abstract—Automatic Music Transcription (AMT), aiming to get musical notes from raw audio, typically uses frame-level systems with piano-roll outputs or language model (LM)-based systems with note-level predictions. However, frame-level systems require manual thresholding, while the LM-based systems struggle with long sequences. In this paper, we propose a hybrid method combining pre-trained roll-based encoders with an LM decoder to leverage the strengths of both methods. Besides, our approach employs a hierarchical prediction strategy, first predicting onset and pitch, then velocity, and finally offset. The hierarchical prediction strategy reduces computational costs by breaking down long sequences into different hierarchies. Evaluated on two benchmark rollbased encoders, our method outperforms traditional piano-roll outputs 0.01 and 0.022 in onset-offset-velocity F1 score, demonstrating its potential as a performance-enhancing plug-in for arbitrary roll-based music transcription encoder.

Index Terms—Automatic Music Transcription, Music Information Retrieval

I. INTRODUCTION

Automatic music transcription (AMT) is a task of converting audio recordings into symbolic representations [1]. As a key topic in music information retrieval (MIR), AMT bridges audio-based and symbolicbased music understanding. AMT systems enable applications such as score following [2] and audio-score alignment [3].

Piano transcription, an instrument-specific subtask of AMT, is a challenging task due to the high polyphony of piano music. Numerous methods have been utilized for piano transcription in recent decades, including Factorization-based models [4], adaptive estimation of harmonic spectra [5], and SVM-HMM structure [6]. With deep learning's rise, models like CNN [7] and CRNN [8] have been effectively applied in AMT. Onsets & Frames system [9] significantly improved note-level metrics by integrating onset and pitch detection. Kong et al. [10] further enhance the AMT system by proposing a high-resolution AMT system trained by regressing precise onset and offset times of piano notes. To minimize model size, studies [11], [12] have used prior knowledge of harmonic structures in audio representations to develop Dilated Convolutional networks. Transformer is a revolutionary model with a encoderdecoder architecture, the self-attention mechanism of which can extract global features and catch long-term relationships. Toyama et al. [13] proposed a two-level hierarchical frequency-time Transformer to catch long-term spectral and temporal dependencies to determine the precise onset and offset for each note. The above methods use piano rolls as output, which has a frame-level resolution and requires a threshold and a post-processing stage to decode it into a note sequence. Hawthorne et al. [14] revolutionize the AMT framework by treating it as a sequence-to-sequence task, where the the output is directly a sequence of note-event tokens, eliminating the need for extensive threshold-based post-processing

Frame-level and language model (LM)-based systems have traditionally been viewed as distinct approaches in AMT. Frame-level systems utilize a compact piano-roll objective but require complex post-processing, while LM-based systems directly output note-level predictions. However, LM-based systems face challenges due to the lengthy sequences created by flattening note events that contain tokens of onset, offset, pitch, and velocity, resulting in resourceintensive training and inference processes. Furthermore, audio encoder selection has been explored in related domains such as audio captioning [15]–[19] and multimodal large language models [20]– [23], yet its impact on AMT remains unexplored. This gap in research presents an opportunity to bridge the divide between frame-level and LM-based approaches.

In this paper, we introduce a novel approach that leverages the strengths of both roll-based systems and note-based language models for music representation. Our proposed method employs pre-trained roll-based systems as encoders and a language model as a decoder, effectively combining their respective advantages. To enhance prediction efficiency, we implement a hierarchical prediction strategy: first predicting onset and pitch, followed by velocity, and finally offset. To achieve the hierarchical prediction strategy, we trained three models with the same model architecture to predict onset and pitch, velocity, and offset, respectively. This approach significantly reduces the prediction sequence length compared to a flattened note event sequence, resulting in improved performance. We empirically evaluate the impact of different roll-based encoders and language model decoder size. Our findings reveal that the choice of encoder has a much more substantial effect on overall performance than the size of the language model. Notably, we observe that increasing the language model size does not reflect as improved model performance, corroborating observations reported in [14]. We further found that velocity modeling is more prone to overfitting compared to onsetpitch and offset. Our findings highlight the importance of encoder selection in AMT tasks, calling for further research in improving the scalability of language-model-based AMT systems.

This paper is structured as follows: Section II provides a detailed description of both the piano roll-based and LM-based systems. In Section III, we compare the traditional flattened token construction method with our proposed hierarchical approach. Our experimental design is outlined in Section IV, followed by Section V, which presents our findings, including results, ablation studies, and related discussions. Finally, Section VI offers concluding remarks.

II. ROLL-BASED AND LM-BASED AMT SYSTEMS

A. Roll-based AMT Systems

In roll-based AMT, a waveform x is firstly transformed to an feature in time-frequency domain $X \in \mathbb{R}^{T \times F}$, where T is time

† Corresponding author



Fig. 1: Proposed system architecture. (a) Pre-training stage trains the roll-based encoder with frame-level objectives. (b) LM-training stage connects it to a LM decoder, training with note-level objectives.

frames and F is frequency bins, using short-time Fourier transform (STFT). Then, the feature is transformed to predict a piano roll $Y \in \{0, 1\}^{T \times K}$, where K is 88 possible pitches, and 0 or 1 encodes absence or presence of each pitch. The neural network model $f_{\theta}(X)$ predicts $\hat{Y} \in [0, 1]^{T \times K}$, representing predicted pitch probabilities. Training typically uses binary cross-entropy loss:

$$\mathcal{L}_{\text{BCE}} = -\frac{1}{TK} \sum_{t=1}^{T} \sum_{k=1}^{K} [Y_{t,k} \log(\hat{Y}_{t,k}) + (1 - Y_{t,k}) \log(1 - \hat{Y}_{t,k})].$$
(1)

At inference time, the continuous predictions $\hat{Y}_{t,k}$ are typically thresholded to obtain binary predictions, which are then postprocessed to extract note events with onset and offset times. While roll-based systems have shown good performance, the need for postprocessing limits their use cases, and have motivated the development of LM-based systems.

B. LM-based AMT Systems

Language Model (LM)-based AMT systems treat music transcription as a sequence generation task. In these systems, the input audio $X \in \mathbb{R}^{T \times F}$ is typically first encoded into a sequence of hidden representations $H \in \mathbb{R}^{T' \times D}$, where T' is the number of encoded time steps and D is the dimension of the hidden representation. The system then generates a sequence of note events $Y = (y_1, ..., y_N)$, where each y_i represents a note event typically consisting of onset time, pitch, duration, and velocity. The neural network model in an LM-based system can be represented as a conditional language model $p_{\theta}(Y|X)$, where θ are the learnable parameters. This model generates the probability distribution of the next note event given the previous events and the input audio:

$$p_{\theta}(Y|X) = \prod_{i=1}^{N} p_{\theta}(y_i|y_{< i}, X).$$
(2)

Therefore, the training objective for LM-based systems typically uses the negative log-likelihood loss:

$$\mathcal{L}_{\text{NLL}} = -\frac{1}{N} \sum_{i=1}^{N} \log p_{\theta}(y_i | y_{\leq i}, X).$$
(3)

At inference time, the model generates note events autoregressively, often using beam search or other decoding strategies to improve



Fig. 2: Flattened and hierarchical token sequence. o_n, p_n, v_n and d_n represents a note event with onset time o_n , pitch p_n , velocity v_n , and offset d_n . Flattened approach (a) forms one sequence, while the hierarchical approach $(b_1, b_2 \text{ and } b_3)$ forms three sequences. Two lines on o and p tokens denote that they are fixed from b_1 during b_2 and b_3 . Best viewed in color. See Sec. III for details.

the quality of the generated sequence. This approach allows for direct generation of note-level predictions without the need for post-processing, potentially capturing long-term dependencies in the music. While LM-based systems offer the advantage of direct notelevel prediction, they are often computationally expensive due to the need for flattening of note event sequence.

III. FLATTENED AND HIERARCHICAL TOKEN STRUCTURE

Our system is composed of an encoder f_{enc} and a LM-based decoder f_{dec} , as illustrated in Figure 1. The encoders f_{enc} are pre-trained on piano roll objectives, and transforms the input audio $X \in \mathbb{R}^{T \times F}$ into a sequence of hidden representations $H = f_{enc}(X) \in \mathbb{R}^{T' \times D}$, where the LM decoder f_{dec} is designed to predict note-level output $Y = (y_1, ..., y_N)$ from the frame-level feature H extracted by the encoder. We propose a hierarchical prediction strategy for note events, where f_{dec} predicts note pitch, velocity, and offset sequentially, controlled by task-specific query tokens $q \in \{q_p, q_v, q_f\}$ with a vocabulary size of three. The probability of generating a note event y_i can be expressed as:

$$p_{\theta}(y_i|y_{< i}, X, q) = f_{\text{dec}}(y_{< i}, H, q), \tag{4}$$

where θ represents the learnable parameters of both the encoder and decoder. In this section, we detail how we construct the token sequence used to train our system.

Let $H = (x_{1:T'})$ be the hidden representations extracted from the input audio sequence, and $Y = y_{1:N}$ be the sequence of note events, where each $y_n = (o_n, p_n, v_n, d_n)$ represents a note event with onset time o_n , pitch p_n , velocity v_n , and offset f_n . For $p_{\text{onset-pitch}}$, p_{velocity} , and d_{offset} , we add < sos > to the sequence and append task-specific query tokens q_p , q_v , or q_d . Notes are organized by onset time (first to last), then pitch (low to high). We use < eos > to end sequences and < pad > for batching. For flattened sequences, we follow [14], organizing note onset, pitch, velocity, and offset similarly.

Differently than [14], which employs an encoder-decoder language model T5 [24], we use LLaMA [25], a decoder-only language model architecture. The primary difference between these architectures lies in how they process the input sequence to generate the output sequence. The encoder-decoder architecture processes the previously generated tokens $y_{1:n-1}$ using an encoder into a sequence of hidden representations H_{enc} , which is used to predict the next token y_n , i.e. $p(y_n) = p(y_n | H_{\text{enc}})$. In contrast, a decoder-only architecture generates the output sequence by directly conditioning on the previous tokens without needing an explicit encoder step. The model autoregressively predicts the next token from the preceding tokens in the sequence, i.e. $p(y_n) = p(y_n|x_1, y_{1:n-1})$.

A critical aspect of the model is its ability to encode positional information, as the Transformer architecture itself is agnostic to the order of tokens. To address this, we use two types of positional encodings: absolute positional encodings for audio embeddings and rotary position embeddings (RoPE) [26] for note event tokens.

Absolute positional encodings introduce explicit position information to the input tokens by adding a fixed positional vector to each token embedding. The positional vector is calculated using sine and cosine functions of varying wavelengths, which ensure that each position in the sequence has a unique encoding. Formally, for a position pos and dimension i, the positional encoding is defined as:

$$PE(pos, 2i) = \sin\left(\frac{pos}{10000^{\frac{2i}{d}}}\right),$$

$$PE(pos, 2i+1) = \cos\left(\frac{pos}{10000^{\frac{2i}{d}}}\right),$$
(5)

where d is the dimensionality of the embeddings. This encoding is added directly to the token embeddings, allowing the model to differentiate between tokens based on their positions in the sequence.

In contrast, Rotary Position Embeddings (RoPE) [26] offer a more flexible and efficient way of encoding positional information, especially for tasks involving long-range dependencies. RoPE modifies the query (Q) and key (K) vectors by applying a rotation in the embedding space. This introduces a relative positioning between tokens while preserving the inner-product structure of the attention mechanism. The rotary transformation is applied as follows:

$$Q'_{i} = Q_{i} \cos(\theta) + Q_{i+1} \sin(\theta),$$

$$K'_{i} = K_{i} \cos(\theta) + K_{i+1} \sin(\theta),$$
(6)

where θ is a position-dependent angle. Recall the probability of generating the entire sequence Y is given by:

$$p(Y) = \prod_{n=1}^{N} p(y_n | x_1, y_{1:n-1}).$$
(7)

In our hierarchical model, we extend this with task-specific query tokens q. The probability of generating each note y_n is now factorized into subcomponents, each handled by a separate language model:

$$p(y_n) = p(o_n, p_n | x_1, y_{1:n-1}, q_p) \times p(v_n | x_1, y_{1:n-1}, o_n, p_n, q_v) \times p(d_n | x_1, y_{1:n-1}, o_n, p_n, v_n, q_f).$$
(8)

Here, $p_{\text{onset-pitch}}$, p_{velocity} , and p_{offset} represent distinct language models for onset-pitch, velocity, and offset predictions, respectively. These models utilize the attention mechanism described earlier, where the query, key, and value matrices are computed from the input sequence and prior predictions. The use of separate language models for each aspect of the musical event sequence reduces interference between tasks and enables more focused learning. Each language model follows the same Transformer-based structure, where W_p is a learnable linear projection matrix:

$$p_{\text{model}}(\cdot) = \text{softmax}(W_p \cdot \text{FFN}(\text{MultiHead}(Q, K, V))).$$
(9)

Here, FFN represents Feed Forward Network. This formulation allows each submodel to specialize in a specific attribute of the musical sequence while maintaining a consistent underlying architecture. The model benefits from this hierarchical structure, as predictions for onset-pitch, velocity, and offset are made sequentially, with each prediction conditioned on the previous ones.

The efficiency of this hierarchical approach is reflected in its time complexity. For each language model, the time complexity remains $O((T + N)^2 D)$, where T is the length of the input sequence, N is the length of the note sequence, and D is the hidden dimension. However, the overall complexity is reduced to $O(3(T + N)^2 D)$ by splitting the task across three separate models. This is a significant improvement over the $O((T + 3N)^2 D)$ complexity that would result from using a single model for all tasks. Given that $T \ll N$, this leads to an almost threefold reduction in time complexity, greatly improving the model's efficiency while maintaining high accuracy.

IV. EXPERIMENT DESIGN

A. Encoders

For a comprehensive evaluation, we employ two benchmark rollbased systems, and adapt them as encoder. Specifically, we use CRNN [10] and HPPNet [11]. CRNN is comprised of convolutional layers, followed by bi-directional GRU layers and a linear readout layer. Two models of the same architecture are designed to perform note and pedal predictions. We take the embedding before the final readout layer, with 768 dimensions, and concatenate both to form a 1536-dim embedding as the representation H into the LM decoder. HPPNet combines convolutional and recurrent elements, introducing "harmonic dilated convolution" (HD-Conv) layers to exploit harmonic characteristics of the input constant-Q transform.

B. Token Dictionary

The size of our token dictionary is 1265. Beyond task-specific query tokens and special tokens (<sos> for start of sentence, <eos> for end of sentence, <pad> for padding and <unk> for unknown), we encode time at 10ms resolution, yielding 1001 unique tokens for 10-second segments. Following [14], we use 128 tokens each for pitch and velocity. We also introduce a note-sustain" token, used when a note extends beyond the boundary of a training segment, and either its beginning or ending falls outside the current training area.

C. Dataset

We employ the Maestro dataset [27], which contains about 200 hours of paired piano recordings and MIDI score, sourced from the International Piano-e-Competition. The score is directly captured from the Yamaha Disklaviers piano, and have been aligned to have an error margin of within 3 milliseconds against the recordings. The dataset is then segmented into individual musical pieces. We utilize the official train/validation/test split provided by the Maestro dataset, where the number of recordings and total duration in hours are 962/137/177 songs and 159.2/19.4/20.0 hours, respectively.

D. Training and Evaluation Setup

The original CRNN model is trained on 10-second long audio segments, while the HPPNet model is trained on 20-second long ones. For a fair comparison, we retrain HPPNet on 10-second long segments and achieves comparable performance of reported in [11]. For the LM decoder, we use 6 transformer layers with 16 attention heads, and an embedding dimension of 1024. After the models are re-trained, we connect their output to the LM decoder through a linear layer, then train end-to-end using the AdamW optimizer with a learning rate of 1e-5, a batch size of 5, and a maximum step count of 1 million. All experiments are conducted on NVIDIA RTX 4090s. We train all settings until convergence is observed.

TABLE I: Experimental results. Best performing setting for each metric is shown in **bold**.

Models	Params	On F_1	On Off F_1	On Off Vel F_1
Hawthorne et al. [14]	54M	0.960	0.839	0.826
Hawthorne et al. [14]	213M	0.956	0.828	0.814
CRNN Roll	200M	0.967	0.825	0.809
CRNN Flatten	200M	0.943	0.393	0.386
CRNN Hierarchy	200M	0.962	0.845	0.819
HPPNet Roll	181M	0.971	0.822	0.810
HPPNet Flatten	181M	0.950	0.390	0.382
HPPNet Hierarchy	181M	0.971	0.852	0.832

TABLE II: Different LM Decoder Settings.

Setting	# Layer	# Head	# Embed Dim	Batch Size
Tiny	4	8	512	64
Small	6	12	768	56
Base	6	16	1024	40
Large	12	32	1024	24

E. Metrics

We follow the default settings in mir_eval to determine if a predicted note is correct. Compared to a ground-truth note, a correctly predicted note should have an onset within a window of ± 50 milliseconds, a pitch within a window of ± 50 cents, a velocity within a window of 0.1 after normalizing to the interval [0,1], and an offset within ± 50 milliseconds or 20% of the note's duration, whichever is larger. Following previous literature [10], [11], [14], we primarily use an F_1 score that takes into account 'pitches, onsets, offsets, and velocities (On Off Vel F_1)'. We also include results for F_1 scores that consider 'pitches and onsets (On F_1)' or 'pitches, onsets and offsets (On Off F_1)'.

V. RESULTS AND DISCUSSIONS

Results are shown in Tab. I. Comparing between the three settings, we can see that the flattened sequence is slightly worse at modeling onset behavior, but drastically worse at predicting note offset; whereas the hierarchical setting consistently reports comparable or better performance. It is worth noting that the "Roll" approach requires setting a threshold to gate notes as posterior information, whereas the "Hierarchy" approach do not. We have also achieved new state-of-the-art result of the LM-based piano transcription model with the HPPNet setting on all three F_1 scores.

Comparing between our results and results from [14], which also applies a flattened sequence during training, we see that their results are much closer to the "Roll" approach. We believe this is primarily due to the influence of sequence length. In [14], each segment is 4.088 seconds, while in ours, the segment length is 10 seconds. This resulted in more notes per sequence, and with the flattened approach, sequence length grows quickly with note events, which may have hindered model performance. Also, [14] used an encoder-decoder language modeling architecture, while we use a decoder-only language model. We hypothesize that the non-autoregressive nature of the encoderdecoder architecture helped it better encode information that would be especially lost in the long, flattened sequence [28], therefore increased its performance compared to our flattened setting.

Language models have been observed to show a "scaling law" where large models with more parameters exhibit better performance [29]. However, on the piano transcription task, [14] observed that larger model overfits rather than generalize better. To better

TABLE III: Results for scaling experiments. Best results are shown in **bold**.

Models	Params	On F ₁	On Off F_1	On Off Vel F_1
HPPNet tiny HPPNet small HPPNet base HPPNet large	41M 105M 181M 335M	0.938 0.963 0.971 0.967	0.807 0.805 0.852 0.777	0.745 0.763 0.832 0.740
8 - Dotted: Val 6 - stor 7 4 - 2 -	ing idation			Onset Offset Velocity

0 50000 100000 150000 200000 250000 300000 350000 400000 Steps

Fig. 3: Onset-pitch, velocity and offset loss on the training set (solid lines) and validation set (dotted lines). Best viewed in color.

examine this phenomenon, we conduct three scaling experiments by training hierarchical token sequence models on three settings, dubbed as "tiny", "small" and "large", as shown in Table II. We conduct these scaling experiments on 8 NVIDIA RTX 4090s.

Results for the scaling experiments are shown in Table III. We observe that compared to the original setting, no significant change in any metric is observed, while all settings slightly under-perform the "base" setting. To examine the training process, we plot the training and validations sets' loss at different timesteps in Figure 3. We observe that while onset-pitch and offset language models quickly plateaus during training, the velocity training show over-fitting at only about 100k steps, similar to the phenomenon described in [14]. This suggests that the scaling behavior for different token types are different, and further merits our hierarchical approach.

VI. CONCLUSIONS

In this paper, we propose a hybrid method that combines pretrained roll-based encoders with an LM decoder. Besides, our approach employs a hierarchical prediction strategy, first predicting onset and pitch, then velocity, and finally offset. The hierarchical prediction strategy reduces computational costs by breaking down long sequences. Evaluated on two benchmark roll-based encoders, our method outperforms traditional piano-roll outputs 0.01 and 0.022 in onset-offset-velocity F1 score, demonstrating its potential as a performance-enhancing plug-in for any roll-based encoder. Results show that encoder choice significantly impacts performance more than LM size, highlighting the importance of encoder selection in AMT. This study calls for further investigation into improving the scalability of LM-based AMT systems.

VII. ACKNOWLEDGEMENT

This research is supported by IdeaBooster funding from the Chinese University of Hong Kong with project code of IDBF24ENG07.

References

- E. Benetos, S. Dixon, Z. Duan, and S. Ewert, "Automatic music transcription: An overview," *IEEE Signal Processing Magazine*, vol. 36, no. 1, pp. 20–30, 2018.
- [2] B. Li and Z. Duan, "An approach to score following for piano performances with the sustained effect," *IEEE/ACM Transactions on Audio*, *Speech, and Language Processing*, vol. 24, no. 12, pp. 2425–2438, 2016.
- [3] B. Niedermayer and G. Widmer, "A multi-pass algorithm for accurate audio-to-score alignment." in *Proceedings of the 11th International Society for Music Information Retrieval Conference, ISMIR*, 2010, pp. 417–422.
- [4] A. Khlif and V. Sethu, "An iterative multi range non-negative matrix factorization algorithm for polyphonic music transcription." in *Proceedings of the 16th International Society for Music Information Retrieval Conference, ISMIR*, 2015, pp. 330–335.
- [5] E. Vincent, N. Bertin, and R. Badeau, "Adaptive harmonic spectral decomposition for multiple pitch estimation," *IEEE Transactions on Audio, Speech, and Language Processing*, vol. 18, no. 3, pp. 528–537, 2009.
- [6] J. Nam, J. Ngiam, H. Lee, M. Slaney *et al.*, "A classification-based polyphonic piano transcription approach using learned feature representations." in *Proceedings of the 12th International Society for Music Information Retrieval Conference, ISMIR*, 2011, pp. 175–180.
- [7] R. Kelz, M. Dorfer, F. Korzeniowski, S. Böck, A. Arzt, and G. Widmer, "On the potential of simple framewise approaches to piano transcription," in *Proceedings of the 17th International Society for Music Information Retrieval Conference, ISMIR*, 2016.
- [8] S. Sigtia, E. Benetos, and S. Dixon, "An end-to-end neural network for polyphonic piano music transcription," *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, vol. 24, no. 5, pp. 927–939, 2016.
- [9] C. Hawthorne, E. Elsen, J. Song, A. Roberts, I. Simon, C. Raffel, J. Engel, S. Oore, and D. Eck, "Onsets and frames: Dual-objective piano transcription," in *Proceedings of the 19th International Society for Music Information Retrieval Conference, ISMIR*, 2018, pp. 50–57.
- [10] Q. Kong, B. Li, X. Song, Y. Wan, and Y. Wang, "High-resolution piano transcription with pedals by regressing onset and offset times," *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, vol. 29, pp. 3707–3717, 2021.
- [11] W. Wei, P. Li, Y. Yu, and W. Li, "Hppnet: Modeling the harmonic structure and pitch invariance in piano transcription," in *Proceedings of the* 23th International Society for Music Information Retrieval Conference, ISMIR, 2022.
- [12] M. P. Fernandez, H. Kirchhoff, X. Serra et al., "Triad: Capturing harmonics with 3d convolutions," in Proceedings of the 24th International Society for Music Information Retrieval Conference, ISMIR, 2023.
- [13] K. Toyama, T. Akama, Y. Ikemiya, Y. Takida, W.-H. Liao, and Y. Mitsufuji, "Automatic piano transcription with hierarchical frequency-time transformer," in *Proceedings of the 24th International Society for Music Information Retrieval Conference, ISMIR*, 2023.
- [14] C. Hawthorne, I. Simon, R. Swavely, E. Manilow, and J. Engel, "Sequence-to-sequence piano transcription with transformers," in *Proceedings of the 22nd International Society for Music Information Retrieval Conference, ISMIR*, 2021.
- [15] X. Mei, X. Liu, Q. Huang, M. D. Plumbley, and W. Wang, "Audio captioning transformer," arXiv preprint arXiv:2107.09817, 2021.
- [16] X. Mei, C. Meng, H. Liu, Q. Kong, T. Ko, C. Zhao, M. D. Plumbley, Y. Zou, and W. Wang, "Wavcaps: A chatgpt-assisted weakly-labelled audio captioning dataset for audio-language multimodal research," *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 2024.
- [17] G. Zhu and Z. Duan, "Cacophony: An improved contrastive audio-text model," arXiv preprint arXiv:2402.06986, 2024.
- [18] J. Kim, J. Jung, J. Lee, and S. H. Woo, "Enclap: Combining neural audio codec and audio-text joint embedding for automated audio captioning," in *IEEE International Conference on Acoustics, Speech and Signal Processing, ICASSP.* IEEE, 2024, pp. 6735–6739.
- [19] X. Xu, H. Liu, M. Wu, W. Wang, and M. D. Plumbley, "Efficient audio captioning with encoder-level knowledge distillation," *arXiv preprint* arXiv:2407.14329, 2024.
- [20] Z. Chen, J. Wu, W. Wang, W. Su, G. Chen, S. Xing, M. Zhong, Q. Zhang, X. Zhu, L. Lu *et al.*, "Internvl: Scaling up vision foundation models and aligning for generic visual-linguistic tasks," in *Proceedings of the*

IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2024, pp. 24185–24198.

- [21] Y. Chu, J. Xu, X. Zhou, Q. Yang, S. Zhang, Z. Yan, C. Zhou, and J. Zhou, "Qwen-audio: Advancing universal audio understanding via unified large-scale audio-language models," arXiv preprint arXiv:2311.07919, 2023.
- [22] S. Liu, A. S. Hussain, C. Sun, and Y. Shan, "Music understanding llama: Advancing text-to-music generation with question answering and captioning," in *IEEE International Conference on Acoustics, Speech and Signal Processing, ICASSP.* IEEE, 2024, pp. 286–290.
- [23] Z. Deng, Y. Ma, Y. Liu, R. Guo, G. Zhang, W. Chen, W. Huang, and E. Benetos, "Musilingo: Bridging music and text with pre-trained language models for music captioning and query response," *arXiv* preprint arXiv:2309.08730, 2023.
- [24] C. Raffel, N. Shazeer, A. Roberts, K. Lee, S. Narang, M. Matena, Y. Zhou, W. Li, and P. J. Liu, "Exploring the limits of transfer learning with a unified text-to-text transformer," *Journal of machine learning research*, vol. 21, no. 140, pp. 1–67, 2020.
- [25] H. Touvron, L. Martin, K. Stone, P. Albert, A. Almahairi, Y. Babaei, N. Bashlykov, S. Batra, P. Bhargava, S. Bhosale *et al.*, "Llama 2: Open foundation and fine-tuned chat models," *arXiv preprint arXiv:2307.09288*, 2023.
- [26] J. Su, M. Ahmed, Y. Lu, S. Pan, W. Bo, and Y. Liu, "Roformer: Enhanced transformer with rotary position embedding," *Neurocomputing*, vol. 568, p. 127063, 2024.
- [27] C. Hawthorne, A. Stasyuk, A. Roberts, I. Simon, C.-Z. A. Huang, S. Dieleman, E. Elsen, J. Engel, and D. Eck, "Enabling factorized piano music modeling and generation with the maestro dataset," in *International Conference on Learning Representations, ICLR.*
- [28] Z. Fu, W. Lam, Q. Yu, A. M.-C. So, S. Hu, Z. Liu, and N. Collier, "Decoder-only or encoder-decoder? interpreting language model as a regularized encoder-decoder," arXiv preprint arXiv:2304.04052, 2023.
- [29] J. Kaplan, S. McCandlish, T. Henighan, T. B. Brown, B. Chess, R. Child, S. Gray, A. Radford, J. Wu, and D. Amodei, "Scaling laws for neural language models," *arXiv preprint arXiv:2001.08361*, 2020.