WAPTS: A Weighted Allocation Probability Adjusted Thompson Sampling Algorithm for High-Dimensional and Sparse Experiment Settings

Haochen Song 1 , Ilya Musabirov 1 , Ananya Bhattacharjee 1 , Audrey Durand 2 , Meredith Franklin 1 , Anna Rafferty³, Joseph Jay Williams¹ (¹University of Toronto, ²Laval University, ³Carleton University)

ABSTRACT

Aiming for more effective experiment design, such as in video content advertising where different content options compete for user engagement, these scenarios can be modeled as multi-arm bandit problems. In cases where limited interactions are available due to external factors, such as the cost of conducting experiments, recommenders often face constraints due to the small number of user interactions. In addition, there is a trade-off between selecting the best treatment and the ability to personalize and contextualize based on individual factors. A popular solution to this dilemma is the Contextual Bandit framework. It aims to maximize outcomes while incorporating personalization (contextual) factors, customizing treatments such as a user's profile to individual preferences. Despite their advantages, Contextual Bandit algorithms face challenges like measurement bias and the 'curse of dimensionality.' These issues complicate the management of numerous interventions and often lead to data sparsity through participant segmentation. To address these problems, we introduce the Weighted Allocation Probability Adjusted Thompson Sampling (WAPTS) algorithm. WAPTS builds on the contextual Thompson Sampling method by using a dynamic weighting parameter. This improves the allocation process for interventions and enables rapid optimization in data-sparse environments. We demonstrate the performance of our approach on different numbers of arms and effect sizes.

ACM Reference Format:

Haochen Song¹, Ilya Musabirov¹, Ananya Bhattacharjee¹, Audrey Durand², Meredith Franklin¹, Anna Rafferty³, Joseph Jay Williams¹ (¹University of Toronto, ²Laval University, ³Carleton University) . 2024. WAPTS: A Weighted Allocation Probability Adjusted Thompson Sampling Algorithm for High-Dimensional and Sparse Experiment Settings. In 2024 Conference on Digital Experimentation @ MIT (CODE @ MIT). ACM, New York, NY, USA, [3](#page-2-0) pages.<https://doi.org/XXXXXXX.XXXXXXX>

1 INTRODUCTION

Given the past use of adaptively conducted trials in customizing digital experiences and interventions in domains such as education [\[5\]](#page-2-1), conversational recommenders [\[3\]](#page-2-2), and eHealth systems [\[6\]](#page-2-3), the

<https://doi.org/XXXXXXX.XXXXXXX>

central to this search is the contextual Bandit framework, which effectively personalizes sequential decisions adapting to varying expected rewards (outcomes) based on contextual information. This work is further guided by ongoing projects within our team, where we intervene on a large combination of factors that could affect people's learning outcome. Contextual Thompson Sampling (CTS) is notable for its theoretical potential to maximize expected outcomes in each subcategory of the population [\[1\]](#page-2-4). However, its practical application faces the "curse of dimensionality," often tackled by subgroup clustering and model simplification. Although this approach reduces complexity, it introduces challenges related to data sparsity, particularly in scenarios that require fine-grained decision making [\[4\]](#page-2-5).

In this rapidly evolving field, further accelerated by advances in large-language models, where treatments in experiment designs could be added simultaneously as the experiment is being conducted, traditional experimental designs with fixed-arm structures are proving to be insufficient. Our approach aims to address the challenges posed by limited data availability and the need for dynamic, adaptable experimental designs. To this end, we introduce a restructured contextual bandit algorithm, Weighted Allocation Probability-adjusted Thompson Sampling (WAPTS). WAPTS builds on the core updating properties of CTS while introducing a dynamic weighting parameter. This parameter automatically adjusts the allocation probabilities for each intervention and enables faster convergence to the optimal arm even when data is scarce. The algorithm offers a more responsive system that can 'reward' and 'punish' arms faster than the traditional approach, thus tackling issues such as data sparsity and segmentation.

2 PROBLEM SETTING

We would like to expand on the potential use case of the method in a digital learning environment. Consider the following scenario:

In an introductory statistics course, K students with varying motivation profiles and previous achievements participate in online discussion forums, creating their own explanations for others' questions. This activity results in a collection of answers, one or more from each student. The evaluation metric involves each student assessing the helpfulness of n answers.

Traditionally, determining the most helpful answer would require relying on an external evaluation process. If this process is constrained by limited resources, an alternative to a traditional A/B experiment is a multi-arm bandit experimental setup. However, it suffers from the following dilemma:

Selection of 'Good' Explanations for Students: In bandit framework, we want students to benefit from our experiment as

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

CODE@MIT, Oct 19-20, 2024, MIT

[©] 2024 Copyright held by the owner/author(s). Publication rights licensed to ACM. ACM ISBN 978-1-4503-XXXX-X/18/06. . . \$15.00

much as possible. Given that students with similar background knowledge (like those in the aforementioned statistics course) will produce many explanations, it is important to select good explanations quickly. This allows students to have the best learning experience with the concept. However, this requires balancing a trade-off: confidently selecting the 'best' explanation while also choosing explanations that seem 'good' early on.

Learning of 'Good' arms with the Bandit Machine: From the perspective of the bandit algorithm, adaptive algorithms need enough exploration to eliminate bad or sub-optimal treatments using a Bayesian update process. To confidently rule out a treatment, sufficient exploration is needed. This challenge worsens when contextual variables, such as students' profiles, are considered. These variables create an even more sparse environment, making it harder for the algorithm to learn.

Given the above dilemma, the traditional bandit framework, which aims to maximize outcomes (rewards) or, in other words, minimize any potential losses (regret) [\[1\]](#page-2-4), suffers from two key issues: regret fails as a complexity measure, and regret-minimizing algorithms tend to over-explore.

Therefore, we propose the following Weighted Allocation Probabil adjusted Thompson Sampling (WAPTS) method, guided by the following questions:

Guiding Question (GQ) 1: How can we ensure the selection of a 'good' arm in the experiment when we know resources (such as the number of samples) are constrained? In other words, how do we choose treatments that minimize significant losses for students?

Guiding Question (GQ) 2: How can we trade off bad-performing arms more quickly than traditional contextual Thompson sampling, which tends to over-explore in sparse data scenarios?

3 METHOD

Let us generalize from the aforementioned statistics class on-line forum example:

- The total number of treatments (arms) is the number of explanations we are examining, denoted by K .
- The sample size of the entire experiment is $N = K \cdot n$, where K is the number of arms (explanations) and n is the number of answers each student evaluates.
- The profile (contextual factor) of the student during the t -th evaluation of an explanation is represented by a continuous or binary ordinal variable, x_t .
- The usefulness (reward) of the t -th explanation shown to the student is a binary response, denoted by r_t . Here, $r_t = 1$ means the explanation is useful, while $r_t = 0$ means it is not.

The WAPTS update procedure follows a Bayesian Monte Carlo procedure $[2]$, where each arm k has a time-independent success $\mathbf{rate}\ p_{k}$. Bayesian logistic regression, including the interaction effect between x_t and \tilde{w}_k , is used to estimate $\hat{p_{k,t}}$, which is the **posterior belief** of likelihood for a useful explanation of arm k at time t. \tilde{w}_k is a weight parameter sampled from its posterior Multivariate Gaussian distribution, defined by μ_k and Σ_k .

The key to our approach is dynamically adjusting each arm's posterior belief (which essentially changes the allocation prob**ability of arms**) based on its success (k_s) and failure (k_f) counts. The success and failure counts for each arm indicate its success rates so far. We apply the **adjustment factor** $(1 + \text{success rate}) \times$ (success rate) to each posterior probability $p_{k,t}^2$, tuning the posterior probability of arm selection to quickly discard seemingly 'bad' arms. This setting, while detailed for the aforementioned classroom context, is adaptable for various algorithms and experimental setups, such as the traditional Beta-Bernoulli Thompson Sampling or a continuous-reward setting. The algorithm is further generalized in the pseudo-code presented in Algorithm [1](#page-1-0).

Algorithm 1 Weighted Allocation Probability adjusted Thompson Sampling (WAPTS) pseudo-code

		1: Procedure: WAPTS (μ, Σ)
		2: for $t = 1, 2, $ do
	3:	$x_t = get_context()$
	4:	$y_t = \emptyset$ is the reward acquired at time t
	5:	for $k = 1, \ldots, K$ do
	6:	Get Posterior: $(\mu_k, \Sigma_k, k_s, k_f)$
	7:	$\tilde{w_k} \sim N(\mu_k, \Sigma_k)$
ity-	8:	$\hat{p}_{k,t} = \frac{1}{1 + \exp(-(x_t \cdot \hat{w}_k + \hat{w}_k))}$
	9:	success_rate = $\frac{k_s}{k_s + k_f + 1}$ -- Success rates for each arm
	10:	$weight_k = (1 + success_rate) \cdot (success_rate)$
	11:	$\hat{p_{k,t}} = max(\hat{p_{k,t}} * weight_k, 1)$ -- Update posterior for
		each arm, capped at 1 to allow for multiple selections
	12:	end for
	13:	$k = argmax_k(\hat{p}_{k,t})$ the chosen arm
		14: $u_t = \text{take_action(k)}$
		15: if $y_t = 1$ then
	16:	$k_{s} = k_{s} + 1$
	17:	else
	18:	$k_f = k_f + 1$
	19:	end if
	20:	Update Posterior(μ_k , Σ_k , x_t , y_t)
		$21:$ end for

4 COMPARISON BETWEEN WAPTS AND CTS

In the forthcoming analysis and comparisons, we will introduce one binary contextual variable that positively influences intervention success (or specific arm allocation). For consistency across experiments, the success rate for suboptimal treatments is maintained at 0.5 (representing the baseline success rate), subject to minor fluctuations to simulate real-world conditions. The effect size is quantified as the difference between the optimal arm's success rate and the baseline.

We compare the performance of two algorithms (CTS and WAPTS) in a medium sample size of 300, across varying numbers of arms and effect sizes. This sample size is chosen to highlight scenarios where different arms become progressively less explored as the number of arms increases, leading to greater data sparsity. This contrasts with a small sample size, where all arms may remain under-explored, and a large sample size, which allows full exploration of most arms.

Figure 1: Reward and Regret Comparison between CTS and WAPTS across four classes of effect sizes: no effect (0), small (0.1), medium (0.25), and large (0.4). The top panel illustrates reward outcomes, while the bottom panel focuses on regret, demonstrating the algorithms' performance under varying conditions. Note: The vertical axis of the plot is displayed with different scales to clearly capture the large/small trend.

Consider the following scenarios that occur during the experiment; we will illustrate how WAPTS will react to each case:

- A Faster Drop of a Poorly Performing Arm: Suppose a specific arm k has a success rate of 20% at time t . Our adjustment factor in this case will be $(1 + 0.2) \cdot 0.2 = 0.24$. Applying this to the posterior belief $\hat{p}_{k,t}$ means we will further reduce the allocation probability of this arm. For an even lower success rate of 0%, the arm would be permanently dropped from selection.
- A Rewarding Allocation for 'Good' Arms: Similarly, if a specific arm k has a higher success rate of 80% at time t , the adjustment factor will be $(1+0.8) \cdot 0.8 = 1.44$, This results in an even higher allocation likelihood for the arm, especially if other arms are not performing as well.

Figure [1](#page-2-7) shows the scenario where the total sample size at 300 and vary the number of arms and effect sizes in the experiment. A larger number of arms in the experiment means that less exploration can be applied to each arm. Furthermore, as the number

of arms increases, the average reward for both algorithms generally decreases, while the regret correspondingly increases. This observation aligns with expectations since a larger number of interventions (arms) requires more exploration to identify the optimal arm, thereby prolonging the convergence to the 'good' arm by the algorithms.

As mentioned above, regret, which quantifies potential loss, tends to fail in data-sparse settings. The 'good' arm identified by either algorithm (WAPTS or CTS) may not be the true best arm due to the small effect sizes, which led the algorithm to select a seemingly optimal but actually sub-optimal arm. When the effect size is relatively small, regret remains fairly consistent over time. However, this consistency does not hold as the effect size increases.

Notably, under conditions of larger effect sizes (indicating a scenario more conducive to adaptive selection) or a higher number of arms (resulting in increased data sparsity), WAPTS consistently outperforms CTS in terms of both average reward and regret across 10,000 simulations. This superior performance of WAPTS can potentially be attributed to its re-weighting scheme for rapidly excluding poorly performing arms based on failure rates, thereby shortening the process of identifying and focusing on arms with higher success rates.

5 LIMITATIONS AND DISCUSSIONS

The graph comparison above shows a general trend of the two algorithms (WAPTS and CTS), specifically the average reward/regret trend over numerous simulations. However, this does not highlight cases of 'bad luck', where WAPTS may quickly eliminate the optimal arm due to initial failures. As a future step, we plan to enable the algorithm to re-explore early-stage eliminated arms at a fixed ratio consistently.

Another important consideration is that we currently adjust the allocation probability of treatments at the posterior sample level. Although this allows the algorithm to maintain a proper Bayesian update process, it complicates the analysis of its convergence behavior. In our upcoming submission, we plan to propose methods for directly adjusting the posterior distribution parameters. In addition, our goal is to clarify the rationale behind the algorithm design by comparing its performance between different algorithms in a fixed sample size-to-arm number ratio.

REFERENCES

- [1] Shipra Agrawal and Navin Goyal. 2012. Further Optimal Regret Bounds for Thompson Sampling. arXiv[:1209.3353](https://arxiv.org/abs/1209.3353) [cs.LG]
- [2] Shipra Agrawal and Navin Goyal. 2014. Thompson Sampling for Contextual Bandits with Linear Payoffs. arXiv[:1209.3352](https://arxiv.org/abs/1209.3352) [cs.LG]
- [3] Allen Lin, Ziwei Zhu, Jianling Wang, and James Caverlee. 2023. Enhancing User Personalization in Conversational Recommenders. arXiv[:2302.06656](https://arxiv.org/abs/2302.06656) [cs.IR]
- [4] Cosimo Palmisano, Alexander Tuzhilin, and Michele Gorgoglione. 2008. Using Context to Improve Predictive Modeling of Customers in Personalization Applications. IEEE Transactions on Knowledge and Data Engineering 20, 11 (2008), 1535–1549.<https://doi.org/10.1109/TKDE.2008.110>
- [5] Mohi Reza, Juho Kim, Ananya Bhattacharjee, Anna N. Rafferty, and Joseph Jay Williams. 2021. The MOOClet Framework: Unifying Experimentation, Dynamic Improvement, and Personalization in Online Courses. In Proceedings of the Eighth ACM Conference on Learning @ Scale (Virtual Event, Germany) (L@S '21). Association for Computing Machinery, New York, NY, USA, 15–26. <https://doi.org/10.1145/3430895.3460128>
- [6] Qihua Wang and Hongxia Jin. 2010. Exploring online social activities for adaptive search personalization. In Proceedings of the 19th ACM international conference on Information and knowledge management. 999–1008.