Large Language Models Share Representations of Latent Grammatical Concepts Across Typologically Diverse Languages

Jannik Brinkmann^{1,2} Chris Wendler³ Christian Bartelt¹ Aaron Mueller^{2,4} ¹University of Mannheim ²Northeastern University ³EPFL ⁴Technion – IIT

Abstract

Human bilinguals often use similar brain regions to process multiple languages, depending on when they learned their second language and their proficiency. In large language models (LLMs), how are multiple languages learned and encoded? In this work, we explore the extent to which LLMs share representations of morphsyntactic concepts such as grammatical number, gender, and tense across languages. We train sparse autoencoders on Llama-3-8B and Aya-23-8B, and demonstrate that abstract grammatical concepts are often encoded in feature directions shared across many languages. We use causal interventions to verify the multilingual nature of these representations; specifically, we show that ablating only multilingual features decreases classifier performance to near-chance across languages. We then use these features to precisely modify model behavior in a machine translation task; this demonstrates both the generality and selectivity of these feature's roles in the network. Our findings suggest that even models trained predominantly on English data can develop robust, cross-lingual abstractions of morphosyntactic concepts.

github.com/jannik-brinkmann/ multilingual-features

1 Introduction

In the brains of human bilinguals, syntax processing may occur in similar regions for their first and second language, depending on factors like when the second language was learned (Cargnelutti et al., 2019), language proficiency (Połczyńska and Bookheimer, 2021), among many other factors (Sulpizio et al., 2020; Costa and Sebastián-Gallés, 2014). In multilingual language models (LMs; Shannon, 1948), how apt is the analogy of shared processing to human bilinguals? If we desire parameter-efficiency, we might want multilingual



Figure 1: Using sparse autoencoders, we find that language models share representations of grammatical concepts across languages. By intervening on these multilingual representations, we can change the model behavior given inputs in different languages. For example, we can make the model predict plural verbs in *different* languages by activating the *same* plural feature.

representations of concepts such as grammatical number, rather than many language-specific representations of the same concept.

Past work has emphasized language-balanced pretraining corpora (e.g., Conneau et al., 2020; Xue et al., 2021; Mohammadshahi et al., 2022), such that an LM could be said to have many primary languages. However, many of the best-performing multilingual LMs are now primarily English models, trained on over 90% English text (e.g., Dubey et al., 2024). Why do these models perform so well in non-English languages? We hypothesize that these models learn generalizable abstractions that enable more efficient learning of new languages. In other words, being able to deeply characterize a smaller distribution could allow models to acquire more robust abstractions that may generalize more effectively to a wider distribution post-hoc; in contrast, more balanced corpora (wider distributions) could encourage the model to start by learning language-specific abstractions, which are potentially never merged into higher-level languageinvariant concepts. For small models, on a synthetic language pair (English and a token-level duplication of it), Schäfer et al. (2024) show that imbalanced datasets lead to higher sample efficiency and higher overall performance in both languages in the low-data regime.¹

In large language models, multilinguality has both practical and theoretical scientific value. High performance on natural language processing tasks across many languages increases the impact and inclusivity of language technologies, and in a more compute-efficient manner than would be possible by training a large series of monolingual models. Moreover, multilingual models are hypothesized to be able to outperform monolingual models in low-resource languages: past work has emphasized the importance of cross-lingual transfer, where knowledge in one language is shared with another language whose corpora did not contain the information of interest. More abstractly, the extent to which abstract concepts are shared across languages addresses a key question: what kinds of multi-lingual processing mechanisms are acquirable from exposure to large-scale text distributions? It would be more parameter-efficient to learn generalizable abstractions that apply across languages, as opposed to redundantly learning the same grammatical feature for each language separately. Moreover, the existence of generalizable abstractions informs debates on memorization versus generalization: cross-linguistic generalization suggests a more sophisticated and broad application of particular concepts.

Past work has largely investigated multilingual language models using behavioral/benchmarking analyses (Gupta and Srikumar, 2021; Raganato et al., 2020, inter alia) or neuron-level mechanistic analyses (Stanczak et al., 2022). Stanczak et al. observe that masked language models often shared neurons across languages for a particular concept, but causally verifying this is difficult, as counterfactual interventions to neurons often affect the processing of irrelevant concepts (see §2). To overcome this challenge, we make our units of causal analysis sparse autoencoder features, which have been shown to be more monosemantic, and therefore more human-interpretable (Cunningham et al., 2024; Bricken et al., 2023; Rajamanoharan et al., 2024). This enables more precise causal interventions (Marks et al., 2024; Mueller et al., 2024), and allows us to qualitatively verify that features of interest are truly sensitive to the hypothesized feature, rather than a spurious but close-enough feature.

In this work, we train a set of sparse autoencoders on the intermediate activations of Llama-3-8B (Dubey et al., 2024) and Aya-3-8B (Aryabumi et al., 2024) and locate massively multilingual features for various morphosyntactic concepts. We design experiments to quantify the degree to which these concepts are shared across languages, and validate the their role in the models generations. Our results reveal that language models share morphosyntactic concept representations across typologically diverse languages, and that the internal *lingua franca* of large language models may not be English words *per se*, but rather concepts.²

2 Background

Feature disentanglement using sparse autoencoders. The features underlying model computation are not guaranteed to be aligned to neuron bases; they may instead be represented in a distributed manner, such that there is a many-to-many relationship between neurons and concepts (Hinton et al., 1986; Smolensky, 1986). In practice, single neurons³ are often *polysemantic*; in other words, they activate on a range of seemingly unrelated concepts (Bolukbasi et al., 2021; Elhage et al., 2022b). For example, Bricken et al. (2023) observe that a single neuron in a small LM responds to a mixture of academic citations, English dialogue, HTTP requests, and Korean text. To address this, Cunningham et al. (2024); Bricken et al. (2023) propose sparse autoencoders (SAEs) as a scalable technique for unsupervised discovery of interpretable feature directions in neural networks. Given an input activation $\mathbf{x} \in \mathbb{R}^{d_{\text{model}}}$, the autoencoder computes a decomposition

$$\mathbf{x} = \hat{\mathbf{x}} + \boldsymbol{\epsilon}(x) = \mathbf{b} + \sum_{i} f_i(\mathbf{x}) \mathbf{d}_i + \boldsymbol{\epsilon}(x)$$
 (1)

into an approximate reconstruction $\hat{\mathbf{x}}$ as a linear combination of features \mathbf{d}_i . The features $\mathbf{d}_i \in \mathbb{R}^{d_{\text{model}}}$ are unit vectors, the feature activations $f_i(\mathbf{x}) \in \mathbb{R}$ are a sparse set of coefficients, $\mathbf{b} \in \mathbf{c}$

¹For real languages, we expect that features will be shared across languages to a much greater extent.

²Though we note that these concepts are likely to be biased toward English-like representations, as discussed in Wendler et al. (2024).

³We use "neuron" to refer to a single dimension of any hidden representation vector in a model.

 $\mathbb{R}^{d_{\text{model}}}$ is a bias term, and $\boldsymbol{\epsilon}(x) \in \mathbb{R}^{d_{\text{model}}}$ is the approximation error.

Bricken et al. (2023) train SAEs by minimizing an L2 reconstruction error and an L1 regularization term to promote sparsity. However, the L1 regularization term introduces biases that can harm the accuracy of the reconstruction, as the loss can be decreased by trading-off reconstruction for lower L1. Therefore, we use the Gated SAE architecture (Rajamanoharan et al., 2024), which separates the functionality of selecting the features to use and estimating the activation magnitude of those directions. We provide additional details about Gated SAEs and their training in App. D.

A key idea underlying SAE-based interpretability is that one can reinterpret the language model's (LM) internal computations in terms of the SAE features. By applying the decomposition in equation 1 to hidden states x in the LM and folding the SAEs into the forward pass,⁴ we can express model representations as a combination of SAE feature activations f_i and reconstruction errors ϵ . This reframing enables attribution patching techniques (Syed et al., 2024) to identify which SAE features have causal influence on particular aspects of model behaviors.

Finding causally relevant features using attribution patching. Causal interpretability methods aim to locate components in neural networks (such as attention heads or neurons) responsible for particular behaviors (Mueller et al., 2024). This requires constructing a distribution \mathcal{D} over pairs of inputs $(x_{\text{clean}}, x_{\text{patch}})$, where x_{clean} is a prompt on which the behaviour occurs, and x_{patch} is a reference prompt on which the behaviour does not occur. Then, we can quantify the importance of components using a target metric $\mathcal{L} : \mathbb{R}^V \to \mathbb{R}$, e.g., the difference in log-probabilities between a correct token continuation and minimally differing incorrect token continuation. In other words, we quantify the importance of a component on the model behaviour as the expected change in \mathcal{L} when replacing the components's activation on the clean prompt with its value on the patch prompt. This is known as the indirect effect (IE; Pearl, 2001).

An exact but compute-intensive method for causal analysis is activation patching (Meng et al., 2022), where we observe the change in model behaviour when performing a counterfactual intervention to a component. However, this requires a separate forward pass for each component. Therefore, we use attribution patching (AtP; Kramar et al., 2024) to estimate \hat{IE} , a linear approximation of the IE computed as a first-order Taylor expansion:

$$\begin{aligned} \mathrm{IE}_{\mathrm{atp}}(m;\mathbf{a};x_{\mathrm{clean}},x_{\mathrm{patch}}) &= \\ \nabla_{\mathbf{a}}m|_{\mathbf{a}=\mathbf{a}_{\mathrm{clean}}}\left(\mathbf{a}_{\mathrm{patch}}-\mathbf{a}_{\mathrm{clean}}\right) \end{aligned} \tag{2}$$

Here, m is the target metric, usually defined as the logit difference between a correct and minimally differing incorrect token completion given context x_{clean} , \mathbf{a}_{clean} is the activation of component a given x_{clean} , and x_{patch} is a minimally differing context that changes the correct answer. Thus, the intuition is that we can approximate the causal contribution of \mathbf{a} to m by taking the slope of m with respect to \mathbf{a} (where this is approximated as the gradient of m at \mathbf{a}^5) and multiplying this by the change in activations in \mathbf{a} .

AtP requires two forward passes and one backward pass to compute an estimate score for *all* components in parallel. In practice, we employ a more expensive but more accurate approximation based on integrated gradients (Sundararajan et al., 2017). For details, please see App. C.

Probing classifiers. Linear probes have frequently been used to locate representations of morphosyntactic features (e.g., Hewitt and Manning, 2019; Giulianelli et al., 2018; Chi et al., 2020). Given labeled classification data, we may train logistic regressions to map from the activations of frozen intermediate layers of pre-trained models (Belinkov, 2022) to the task labels. We similarly train classifiers to predict morphosyntactic concepts. We then quantify the extent of crosslingual feature sharing for morphosyntactic concepts, and later evaluate the selectivity of targeted morphosyntactic concept interventions.

3 Multilingual Features

In this section, we investigate the extent to which morphosyntactic concepts are shared (or redundantly encoded) across languages. We first measure the overlap between the most causally influential sparse features for a given concept across languages. Then, we investigate whether ablating the multilingual features leads to a consistent decrease in classifier performance across languages.

⁴As described in detail in Marks et al. (2024).

⁵The gradient can be viewed as a local estimate of how much the metric we backpropagate from would be affected by changing the activation of the component.



Figure 2: Proportion of features shared across languages (intersection over union) among the top 32 features for each morphosyntactic concept. A significant fraction of the morphosyntactic concept representations are shared across languages in both Llama-3-8B and Aya-23-8B.

3.1 Experimental Setup

Models. We consider Llama-3-8B (Dubey et al., 2024) and Aya-23-8B (Aryabumi et al., 2024). While Llama 3 was trained primarily on English data, Aya was explicitly developed to support 23 typologically diverse and resource-diverse languages.

Data. We select 23 languages from Universal Dependencies 2.1 (UD; Nivre et al., 2017), a multilingual treebank containing dependency-parsed sentences. This corresponds to the 23 languages that Aya-23 was trained on (see Appendix B). Each word in each sentence in UD is annotated with its part of speech and morphosyntactic features, as defined in the UniMorph schema (Kirov et al., 2018).

Training probing classifiers. We train a probing classifier for each combination of morphosyntactic concept (e.g., gender) and language (e.g., English). We filter for morphosyntactic concepts that are annotated in at least six languages. During training, the inputs to the classifiers are residual stream activations from the end of the model's middle layer (L = 16), as this layer is expected to capture abstract, high-level and human-interpretable features (Elhage et al., 2022a; Lad et al., 2024). Following Marks et al. (2024), we pool non-padding token activations by summing them; then, we fit a logistic regression to the pooled representations.

Training sparse autoencoders. We train Gated SAEs (Rajamanoharan et al., 2024) for both Llama-3-8B and Aya-23-8B. We collect activations over 250 million tokens of The Pile (Gao et al., 2020) extracted from the residual stream at the same layer at which we train the probing classifiers. To verify the quality of the SAEs, we measure the proportion of loss recovered when replacing the model activations with SAE reconstructions thereof. While the training dataset is primarily composed of English texts, we verify that it also reconstructs other language effectively using the mC4 dataset (Xue et al., 2021; see App. D).

3.2 Results

Representations of morphosynthactic concepts are shared across languages. First, we measure the extent of overlap across languages for the top features encoding a morphosyntactic category. For this, we perform attribution patching (§2), where the target metric is the logit of the probing classifiers we trained in §2. This identifies the set of causally relevant features that are most influential on the probe's logits. We observe that a small fraction of features dominate the causal effect, with a long tail of features that have a small effect. Therefore, for each language and concept, we select the top-32 most informative features per probe and compute the overlap across languages within a concept. We present the results in Figure 2.

We observe significant overlap of up to 50 % in the features identified for the same grammatical concepts across typologically diverse languages. For example, feature 22860 is among the most influential features across *all* 15 languages that inflect for grammatical gender. The overlap is greater for morphosyntactic concepts present in a larger number of languages, such as grammatical number. We also find that the extent of overlap is largely consistent across Llama-3-8B and Aya-23-8B, with only a small number of exceptions (e.g. negative polarity). Thus, despite the lack of one-to-one mapping of grammatical concepts across languages, there exist highly multilingual representations of abstract morphosyntactic concepts.



Figure 3: Examples of the activation patterns of selected features that correspond to cross-lingual representations of grammatical concepts. For example, we locate features that indicate the presence of plural nouns across languages or features that indicate past tense.



Figure 4: Performance of the probing classifiers before and after ablating multilingual features. Specifically, we test ablating (a) all multilingual features, and (b) the upper quartile of the *most multilingual* features. We find that the classifiers crucially rely on multilingual features to predict the presence of morphosyntactic features.

Effect of causal interventions on multilingual features are consistent across languages. How important are multilingual features compared to monolingual features? We evaluate the importance of multilingual features by measuring the impact of ablating the multilingual features on the performance of the probing classifiers. We define multilingual features as those in the top feature set across at least two languages. The results (Figure 4) suggest that the classifiers crucially rely on multilingual features to predict the presence of morphosyntactic concepts. This suggests that large language models-including those trained primarily on English-learn to rely on shared representations to detect particular concepts, rather than relying on language-specific representations.

We also observe that while many features are shared across at least two languages, there is a small set of features shared across a large number of languages (App. E Therefore, we investigate ablating only *massively multilingual* features. Specifically, we order features by the number of languages for which they are causally relevant, and the average strength of their causal effect. Then, we select the upper quartile of features in this ranking—i.e., the most multilingual features—and only ablate those. For Llama 3, the performance after ablating only massively multilingual features drops to 67% on average. Notably, when ablating all multilingual features, the performance drops to 61% a difference of only 6% percent, despite ablating four times as many features. This suggests that massively multilingual features explain most of the probes' behavior.

Feature overlap across concepts. We now investigate the extent of feature overlap across grammatical concepts. This provides insights into the specificity of the functional roles of features. Specifically, we analyze the overlap in the sets of multilingual features associated with different conceptvalue pairs (e.g., masculine gender and singular number).⁶ For each pair, we measure the fraction of multilingual features shared, and compute the mean overlap across all pairs.

We find that the mean overlap across concepts is 13.9% (\pm 10.7%). This relatively low (but significant) overlap is expected, as some linguistic concepts are jointly morphologically realized. For instance, singular number and masculine gender share 40.6% of their features; this is intuitive, given the frequent joint inflection of adjectives and pronouns for both number and gender. For example, in French and Hebrew, "il" and "Ti" are masculine singular pronouns, where changing either number *or* gender alters the form. Similarly, adjectives in these languages have distinct forms for combinations of grammatical gender and number.

⁶We use *concept* to refer to the variable—e.g., gender or number—and *concept-value* to refer to specific values that the variable can take—e.g., masculine gender or singular number.

Multilingual features are human-interpretable.

One benefit of sparse features over neurons is their interpretability. This provides a qualitative way to verify that the features are truly relevant to the target concept, rather than related solely in some spurious correlational manner. Thus, we manually inspect a subset of the identified features, finding that many of them are intuitively meaningful and interpretable across different languages. We present the most multilingual features for two common concepts and a selection of their activation patterns across typologically diverse languages in Figure 3.

4 Demonstrating Functional Selectivity: A Case Study in Machine Translation

Another benefit of sparse features is the level of fine-grained control they provide over language model behaviors (Templeton et al., 2024). Indeed, feature-based interventions tend to be more effective then neuron-based methods at precisely modifying how language models generalize without destroying task performance (Marks et al., 2024). We leverage this property in a machine translation setting to (i) demonstrate the functional selectivity of the discovered morphosyntactic features (i.e., to show that intervening with them has few side effects on other concepts), and (ii) provide additional evidence that their causal role is highly general (i.e., that it is effective in this MT setting and not just on the probes). To evaluate (i) and (ii), we use feature steering (Templeton et al., 2024), where we clamp features of interest to counterfactual activations. These activations can be either significantly higher or lower than the values observed in practice. This approach is similar to prior work on understanding the functional role of individual neurons in image models (Bau et al., 2019).

As translation is a difficult task that does not always have a single clear answer, we restrict to a smaller subsample of concepts and languages such that we can manually verify the baseline quality of translations, and then the efficacy of the interventions. We restrict our analysis to tense (Past vs. Present), gender (Masc. vs. Fem.), and number (Sing. vs. Plural), as these concepts are shared across most languages we consider, and narrow to three languages: English, German, and French. We provide details on the prompt format and translation performance in Appendix F.

4.1 Experimental Setup

Data. We design datasets consisting of minimal pairs of inputs that differ only with respect to the presence of a grammatical concept (see Table 3 in App. G). For example, we generate counterfactual pairs that elicit singular or plural verbs based on the grammatical number of the subject:

- a. The **parents** near the cars \rightarrow were
- b. The **parent** near the cars \rightarrow **was**

This is an adaptation and translation of data from Arora et al. (2024). Then, we check whether the probability of the grammatical sequence is higher for each pair. In our experiments, we only consider sentences where Llama-3-8B is indeed capable of making grammatically correct predictions.

Feature intervention. In our setting, we follow Templeton et al. (2024) and intervene in the model by scaling a single SAE feature to a multiple of its maximum activation value observed in the dataset.⁷ More formally, for a given grammatical concept, we select one feature from the set of multilingual features identified in §3 and scale it to a multiple of the observed activation value. We implement feature steering by decomposing the residual stream activations x into the sum of two components, the SAE reconstruction and the reconstruction error (see Equation 1). Then, we replace the SAE term with a modified SAE reconstruction in which we set the activation value of a specific feature in the SAE to a counterfactual value, but leave the error term unchanged. We then run the forward pass on the network using this modified residual stream. We only apply the intervention to the last token position of each generation step to prevent degenerate outputs. Thus, for a given morphosyntactic concept, similar to Templeton et al. (2024), we explore different multiples and choose the one that works best empirically.

We consider activating features in contexts where they would not be active otherwise. We observe that intervening on multiple features at the same time is very sensitive to the combination of features and their activation value. Therefore, we follow Templeton et al. (2024) in intervening on only a single feature at a time. To select the feature, we manually inspect the features and select one feature per concept where the activation values are most interpretable.

⁷For this purpose, we record the maximum activations of features across 20 M tokens.



Figure 5: Efficacy in flipping the model behavior on our counterfactual dataset when translating between languages and intervening on a *single* multilingual feature per concept. For each concept, we translate a sentence from some source language (e.g. German) where some concept (e.g. present tense) to another language (e.g. English) and measure the number of times the model starts to predict some alternative concept value (e.g. past tense). In each of these settings, we intervene on a single feature and measure the success rate over 64 examples.



Figure 6: Fraction of times an intervention on a grammatical concept exclusively impacts that concept, indicating the degree of cross-concept interference. We observe that interference is generally very rare.

4.2 Quantitative Results

Efficacy. We define the efficacy of the intervention as the proportion of examples where the probe's label flips after the intervention. To measure this, we generate a translation with and without the intervention. Then, in new forward passes with no interventions, we give the model these translations, pool their representations, and measure whether the probe's (from §2) labels differ between the two translations. We find that intervening on a single feature is often sufficient to change the models prediction towards the indended concept (e.g., a masculine instead of feminine pronoun; see Figure 5). However, we also observe that, for some concepts, intervening on a single feature is often sufficient.

Selectivity. We also evaluate the selectivity of the interventions. Specifically, we want interventions to *only* flip the labels on the concept that we intervene on, and not others. We operationalise this using the probing classifiers trained in §2. As before, we generate two translations: one with and without feature interventions to a given concept.

Then, we compute selectivity as the proportion of translation pairs for which none of the other concept probes changed their predictions. Our results (Figure 6) suggest that the interventions are generally selective to the concept.

4.3 Qualitative Results

The quantitative results provide insights into the generalisation of the identified features to a different distribution, and allow us to quantify the success rate of the interventions. However, the dataset is neither naturalistic nor diverse. Therefore, we perform the same interventions on the Flores-101 dataset, which provides aligned translations across 101 languages (Goyal et al., 2021). We present a selection of qualitative examples in Figure 7.

However, we acknowledge that the intervention was not successful in some cases, and sometimes led to degenerate generations. Concept-specific tuning over the number of features and activation values used was also required. These limitations highlight common problems with feature steering methods: activations often must be scaled to significantly larger values than would naturally be observed in practice (Templeton et al., 2024). This, combined with intervening on multiple features simultaeously, can result in unexpected or degenerate outputs (Shabalin et al., 2023).

5 Related Work

Multilingual language modeling. Multilingual language models are trained on multiple languages simultaneously, typically with an explicitly designed balance between languages in the pretraining corpus. For example, XLM-R (Conneau et al., 2020), M2M (Mohammadshahi et al., 2022),

Turkish	English
Televizyon haberleri santralden→ yükselen beyaz dumanı gösteriyor.	The TV news is showing the white smoke rising from the chimney of the plant.
¹ → ↑ Past Tense	A television news program showed a cloud of white smoke from the reactor.
English	German
He was greeted by Singapore's Deputy Prime → Minister Wong Kan Seng and discussed trade and terrorism issues with the Singapore Prime Minister Lee Hsien Loong.	Er wurde von Wong Kan Seng, dem stellvertret enden Premierminister Singapurs, begrüßt und sprach mit Lee Hsien Loong, dem Premierminister Singapurs, über Handels- und Terrorismus- angelegenheiten. Sie wurde von der stellvertretenden Premier- ministerin Wong Kan Seng in Empfang genommen und unterhielt sich mit der singapurischen Premierministerin Lee Hsien Loong über Handels- und Terrorismus-Themen.
French	Spanish
Peu de gens les considèrent comme des→ dinosaures étant donne qu'ils ont des ailes et peuvent voler.	Pocos los consideran dinosaurios porque tienen alas y pueden volar.
'→ ↑ Singular	Pocos lo consideran como un dinosaurio , ya que tiene alas y puede volar.

Figure 7: Comparison of translations with (highlighted in red) and without intervening on multilingual features encoding a morphosyntactic concept. The words indicating that the model flipped its behavior are highlighted in bold. The input texts are sampled from the Flores-101 dataset.

mT5 (Xue et al., 2021), and Aya (Aryabumi et al., 2024) are trained with corpora balanced across many languages. In contrast, Llama 3 (Dubey et al., 2024) is trained on a much more English-centric distribution: over 90% of the corpus is English text. Generally, the motivation behind balanced corpora during multilingual pretraining is to encourage cross-lingual transfer. We find that this balance may not be necessary for multilingual representations when the corpora are sufficiently large.

Interpreting multilingual language models. A central question in multilingual language modeling is whether language models develop a universal concept representation, disentangled from specific languages. Huang et al. (2023) studied different forms of cross-lingual transfer using a variety of models and probing tasks. Wendler et al. (2024) found that languages models trained on unbalanced, English-dominated corpora operate in a concept space that lies closer to English than to other languages. Ferrando (2024) studies the specific mechanism of subject-verb agreement and finds that these mechanisms are consistent across languages. Dumas et al. (2024) observed that concepts (e.g. "car") are encoded disentangled from specific languages and can be transferred between them. Similarly, Stanczak et al. (2022) found that probes trained on different languages read the same concepts from the same neurons in smaller-scale masked language models such as mBERT (Devlin et al., 2019) and XLM-R (Conneau et al., 2020), while Feng et al. (2024) observed that their propositional probes generalise to Spanish. De Varda and Marelli (2023) extended this study by investigating the cross-lingual consistency of individual neurons responding to syntactic phenomena. Our work extends these findings to large-scale models not explicitly intended to be multilingual, and shows stronger causal evidence for the functional selectivity of these conceptual representations.

6 Discussion and Conclusion

Language models trained primarily on English data perform surprisingly well in other languages. Prior work has emphasized the importance of balanced pretraining corpora, so as to not overfit to a single language (Conneau et al., 2020; Mohammadshahi et al., 2022); however, more recent studies suggest that the size of the pretraining corpusnot balance-may be more important for crosslingual generalization (Jiang et al., 2023; Dubey et al., 2024; Schäfer et al., 2024). Why is this effective? Our results provide evidence that largescale pretraining, even with imbalanced corpora, induces equally cross-lingualistcally generalizable grammatical abstracts as pretraining with balanced corpora. This is evidence in favor of a hypothesis discussed in Wendler et al. (2024): the internal lingua franca of large language models may not be English words per se, but rather concepts. That said, it is still reasonable to assume these concepts are likely biased toward how English handles them in models pre-trained on imbalanced corpora.

How generalizable should grammatical concept representations be? While it is more parameterefficient to share representations across languages, this may lead to biases if two languages assign different social or semantic connotations to-or simply distribute differently-the same grammatical concepts. Indeed, there is not a one-to-one relationship between concepts across languages: different languages may have differing numbers of values for the same concept (e.g., Finnish has many more grammatical cases than German), and may use the same categories in different ways (e.g., the same nouns often have different genders in different languages, even within language families). More language-specific features could lead to less bias, but would require more parameters to represent. It is not clear what the optimal point between these two ends of generalization are.

More practically, the extent to which concepts are shared across languages has implications for multilingual downstream NLP tasks. For example, it helps explain the phenomenon that preference tuning for toxicity mitigation in a single language generalizes to other languages (Li et al., 2024). Thus, we might reasonably expect various types of interventions and model editing approaches to generalize from a single language to other languages.

Limitations

Non-linear features. Sparse autoencoders are a method for unsupervised search for features. However, they will only recover a feature if it is *linearly encoded*. Thus, if a concept is encoded in a nonlinear manner, then sparse features may struggle to recover the full range of that variable. Thus, sparse features are generally best-suited to encoding binary relations, whereas some features may be encoded in more complex arrangements such as circular shapes (cf. Engels et al. 2024).

Feature interventions. We use SAE features to intervene on the models internal state. Similar to Templeton et al. (2024), we find that this typically requires clamping the feature activations to values outside their observed range over the training dataset. However, clamping feature activations to extreme values often causes the model to produce nonsensical generations, e.g., repeating the same token indefinitely. Thus, while our results demonstrate that the identified features can be causally responsible for model behavior, optimally intervening on groups of features, is an open problem that future work should address.

Distinction between model understanding and generation. In our experiments, the linear probes measure whether it is possible to linearly separate grammatical concepts in the model's representations, whereas the machine translation experiments measure the effect of feature directions on model generation. Past work (Meng et al., 2022; Orgad et al., 2024; Gottesman and Geva, 2024) has observed a distinction between a model encoding a concept versus being able to use that concept during generation (i.e., a "knowing vs. saying" distinction). Anecdotally, we observed that some features with a high causal effect on the linear probe do not necessarily have a similar effect on the model's generation. We hypothesize that this is due to an intrinsic distinction between concept understanding/representation and concept generation.

Human biases in feature interpretation. One must be cautious in applying human concepts to language model representations. It is probable that language models deploy distinct concept spaces from humans; thus, human explanations of neurons or features are likely to be biased in ways that can result in suboptimal predictions of when the neuron or feature will activate (cf. Huang et al., 2023).

References

- Aryaman Arora, Dan Jurafsky, and Christopher Potts. 2024. CausalGym: Benchmarking causal interpretability methods on linguistic tasks. In Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 14638–14663, Bangkok, Thailand. Association for Computational Linguistics.
- Viraat Aryabumi, John Dang, Dwarak Talupuru, Saurabh Dash, David Cairuz, Hangyu Lin, Bharat Venkitesh, Madeline Smith, Kelly Marchisio, Sebastian Ruder, Acyr Locatelli, Julia Kreutzer, Nick Frosst, Phil Blunsom, Marzieh Fadaee, Ahmet Üstün, and Sara Hooker. 2024. Aya 23: Open weight releases to further multilingual progress. *Preprint*, arXiv:2405.15032.
- David Bau, Jun-Yan Zhu, Hendrik Strobelt, Bolei Zhou, Joshua B. Tenenbaum, William T. Freeman, and Antonio Torralba. 2019. GAN dissection: Visualizing and understanding generative adversarial networks. In *International Conference on Learning Representations*.
- Yonatan Belinkov. 2022. Probing classifiers: Promises, shortcomings, and advances. *Computational Linguistics*, 48(1):207–219.
- Tolga Bolukbasi, Adam Pearce, Ann Yuan, Andy Coenen, Emily Reif, Fernanda Viégas, and Martin Wattenberg. 2021. An interpretability illusion for BERT. *Preprint*, arXiv:2104.07143.
- Trenton Bricken, Adly Templeton, Joshua Batson, Brian Chen, Adam Jermyn, Tom Conerly, Nick Turner, Cem Anil, Carson Denison, Amanda Askell, Robert Lasenby, Yifan Wu, Shauna Kravec, Nicholas Schiefer, Tim Maxwell, Nicholas Joseph, Zac Hatfield-Dodds, Alex Tamkin, Karina Nguyen, Brayden McLean, Josiah E Burke, Tristan Hume, Shan Carter, Tom Henighan, and Christopher Olah. 2023. Towards monosemanticity: Decomposing language models with dictionary learning. *Transformer Circuits Thread*.
- Elisa Cargnelutti, Barbara Tomasino, and Franco Fabbro. 2019. Language brain representation in bilinguals with different age of appropriation and proficiency of the second language: A meta-analysis of functional imaging studies. *Frontiers in human neuroscience*, 13:445658.
- Ethan A. Chi, John Hewitt, and Christopher D. Manning. 2020. Finding universal grammatical relations in multilingual BERT. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 5564–5577, Online. Association for Computational Linguistics.
- Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. 2020. Unsupervised

cross-lingual representation learning at scale. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 8440–8451, Online. Association for Computational Linguistics.

- Albert Costa and Núria Sebastián-Gallés. 2014. How does the bilingual experience sculpt the brain? *Nature Reviews Neuroscience*, 15(5):336–345. Research Support, Non-U.S. Gov't; Review.
- Hoagy Cunningham, Aidan Ewart, Logan Riggs Smith, Robert Huben, and Lee Sharkey. 2024. Sparse autoencoders find highly interpretable features in language models. In *The Twelfth International Conference on Learning Representations*.
- Andrea Gregor De Varda and Marco Marelli. 2023. Data-driven cross-lingual syntax: An agreement study with massively multilingual models. *Computational Linguistics*, 49(2):261–299.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.
- Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, Arun Rao, Aston Zhang, Aurelien Rodriguez, Austen Gregerson, Ava Spataru, Baptiste Roziere, Bethany Biron, Binh Tang, Bobbie Chern, Charlotte Caucheteux, Chaya Nayak, Chloe Bi, Chris Marra, Chris McConnell, Christian Keller, Christophe Touret, Chunyang Wu, Corinne Wong, Cristian Canton Ferrer, Cyrus Nikolaidis, Damien Allonsius, Daniel Song, Danielle Pintz, Danny Livshits, David Esiobu, Dhruv Choudhary, Dhruv Mahajan, Diego Garcia-Olano, Diego Perino, Dieuwke Hupkes, Egor Lakomkin, Ehab AlBadawy, Elina Lobanova, Emily Dinan, Eric Michael Smith, Filip Radenovic, Frank Zhang, Gabriel Synnaeve, Gabrielle Lee, Georgia Lewis Anderson, Graeme Nail, Gregoire Mialon, Guan Pang, Guillem Cucurell, Hailey Nguyen, Hannah Korevaar, Hu Xu, Hugo Touvron, Iliyan Zarov, Imanol Arrieta Ibarra, Isabel Kloumann, Ishan Misra, Ivan Evtimov, Jade Copet, Jaewon Lee, Jan Geffert, Jana Vranes, Jason Park, Jay Mahadeokar, Jeet Shah, Jelmer van der Linde, Jennifer Billock, Jenny Hong, Jenya Lee, Jeremy Fu, Jianfeng Chi, Jianyu Huang, Jiawen Liu, Jie Wang, Jiecao Yu, Joanna Bitton, Joe Spisak, Jongsoo Park, Joseph Rocca, Joshua Johnstun, Joshua Saxe, Junteng Jia, Kalyan Vasuden Alwala, Kartikeya Upasani, Kate Plawiak, Ke Li, Kenneth Heafield, Kevin Stone, Khalid El-Arini, Krithika Iyer, Kshitiz Malik, Kuenley Chiu, Kunal Bhalla, Lauren Rantala-Yeary, Lau-

rens van der Maaten, Lawrence Chen, Liang Tan, Liz Jenkins, Louis Martin, Lovish Madaan, Lubo Malo, Lukas Blecher, Lukas Landzaat, Luke de Oliveira, Madeline Muzzi, Mahesh Pasupuleti, Mannat Singh, Manohar Paluri, Marcin Kardas, Mathew Oldham, Mathieu Rita, Maya Pavlova, Melanie Kambadur, Mike Lewis, Min Si, Mitesh Kumar Singh, Mona Hassan, Naman Goyal, Narjes Torabi, Nikolay Bashlykov, Nikolay Bogoychev, Niladri Chatterji, Olivier Duchenne, Onur Çelebi, Patrick Alrassy, Pengchuan Zhang, Pengwei Li, Petar Vasic, Peter Weng, Prajjwal Bhargava, Pratik Dubal, Praveen Krishnan, Punit Singh Koura, Puxin Xu, Qing He, Qingxiao Dong, Ragavan Srinivasan, Raj Ganapathy, Ramon Calderer, Ricardo Silveira Cabral, Robert Stojnic, Roberta Raileanu, Rohit Girdhar, Rohit Patel, Romain Sauvestre, Ronnie Polidoro, Roshan Sumbaly, Ross Taylor, Ruan Silva, Rui Hou, Rui Wang, Saghar Hosseini, Sahana Chennabasappa, Sanjay Singh, Sean Bell, Seohyun Sonia Kim, Sergey Edunov, Shaoliang Nie, Sharan Narang, Sharath Raparthy, Sheng Shen, Shengye Wan, Shruti Bhosale, Shun Zhang, Simon Vandenhende, Soumya Batra, Spencer Whitman, Sten Sootla, Stephane Collot, Suchin Gururangan, Sydney Borodinsky, Tamar Herman, Tara Fowler, Tarek Sheasha, Thomas Georgiou, Thomas Scialom, Tobias Speckbacher, Todor Mihaylov, Tong Xiao, Ujjwal Karn, Vedanuj Goswami, Vibhor Gupta, Vignesh Ramanathan, Viktor Kerkez, Vincent Gonguet, Virginie Do, Vish Vogeti, Vladan Petrovic, Weiwei Chu, Wenhan Xiong, Wenyin Fu, Whitney Meers, Xavier Martinet, Xiaodong Wang, Xiaoqing Ellen Tan, Xinfeng Xie, Xuchao Jia, Xuewei Wang, Yaelle Goldschlag, Yashesh Gaur, Yasmine Babaei, Yi Wen, Yiwen Song, Yuchen Zhang, Yue Li, Yuning Mao, Zacharie Delpierre Coudert, Zheng Yan, Zhengxing Chen, Zoe Papakipos, Aaditya Singh, Aaron Grattafiori, Abha Jain, Adam Kelsey, Adam Shajnfeld, Adithya Gangidi, Adolfo Victoria, Ahuva Goldstand, Ajay Menon, Ajay Sharma, Alex Boesenberg, Alex Vaughan, Alexei Baevski, Allie Feinstein, Amanda Kallet, Amit Sangani, Anam Yunus, Andrei Lupu, Andres Alvarado, Andrew Caples, Andrew Gu, Andrew Ho, Andrew Poulton, Andrew Ryan, Ankit Ramchandani, Annie Franco, Aparajita Saraf, Arkabandhu Chowdhury, Ashley Gabriel, Ashwin Bharambe, Assaf Eisenman, Azadeh Yazdan, Beau James, Ben Maurer, Benjamin Leonhardi, Bernie Huang, Beth Loyd, Beto De Paola, Bhargavi Paranjape, Bing Liu, Bo Wu, Boyu Ni, Braden Hancock, Bram Wasti, Brandon Spence, Brani Stojkovic, Brian Gamido, Britt Montalvo, Carl Parker, Carly Burton, Catalina Mejia, Changhan Wang, Changkyu Kim, Chao Zhou, Chester Hu, Ching-Hsiang Chu, Chris Cai, Chris Tindal, Christoph Feichtenhofer, Damon Civin, Dana Beaty, Daniel Kreymer, Daniel Li, Danny Wyatt, David Adkins, David Xu, Davide Testuggine, Delia David, Devi Parikh, Diana Liskovich, Didem Foss, Dingkang Wang, Duc Le, Dustin Holland, Edward Dowling, Eissa Jamil, Elaine Montgomery, Eleonora Presani, Emily Hahn, Emily Wood, Erik Brinkman, Esteban Arcaute, Evan Dunbar, Evan Smothers, Fei Sun, Felix Kreuk, Feng Tian, Firat Ozgenel, Francesco Caggioni, Francisco Guzmán,

Frank Kanayet, Frank Seide, Gabriela Medina Florez, Gabriella Schwarz, Gada Badeer, Georgia Swee, Gil Halpern, Govind Thattai, Grant Herman, Grigory Sizov, Guangyi, Zhang, Guna Lakshminarayanan, Hamid Shojanazeri, Han Zou, Hannah Wang, Hanwen Zha, Haroun Habeeb, Harrison Rudolph, Helen Suk, Henry Aspegren, Hunter Goldman, Ibrahim Damlaj, Igor Molybog, Igor Tufanov, Irina-Elena Veliche, Itai Gat, Jake Weissman, James Geboski, James Kohli, Japhet Asher, Jean-Baptiste Gaya, Jeff Marcus, Jeff Tang, Jennifer Chan, Jenny Zhen, Jeremy Reizenstein, Jeremy Teboul, Jessica Zhong, Jian Jin, Jingyi Yang, Joe Cummings, Jon Carvill, Jon Shepard, Jonathan McPhie, Jonathan Torres, Josh Ginsburg, Junjie Wang, Kai Wu, Kam Hou U, Karan Saxena, Karthik Prasad, Kartikay Khandelwal, Katayoun Zand, Kathy Matosich, Kaushik Veeraraghavan, Kelly Michelena, Keqian Li, Kun Huang, Kunal Chawla, Kushal Lakhotia, Kyle Huang, Lailin Chen, Lakshya Garg, Lavender A, Leandro Silva, Lee Bell, Lei Zhang, Liangpeng Guo, Licheng Yu, Liron Moshkovich, Luca Wehrstedt, Madian Khabsa, Manav Avalani, Manish Bhatt, Maria Tsimpoukelli, Martynas Mankus, Matan Hasson, Matthew Lennie, Matthias Reso, Maxim Groshev, Maxim Naumov, Maya Lathi, Meghan Keneally, Michael L. Seltzer, Michal Valko, Michelle Restrepo, Mihir Patel, Mik Vyatskov, Mikayel Samvelyan, Mike Clark, Mike Macey, Mike Wang, Miquel Jubert Hermoso, Mo Metanat, Mohammad Rastegari, Munish Bansal, Nandhini Santhanam, Natascha Parks, Natasha White, Navyata Bawa, Nayan Singhal, Nick Egebo, Nicolas Usunier, Nikolay Pavlovich Laptev, Ning Dong, Ning Zhang, Norman Cheng, Oleg Chernoguz, Olivia Hart, Omkar Salpekar, Ozlem Kalinli, Parkin Kent, Parth Parekh, Paul Saab, Pavan Balaji, Pedro Rittner, Philip Bontrager, Pierre Roux, Piotr Dollar, Polina Zvyagina, Prashant Ratanchandani, Pritish Yuvraj, Qian Liang, Rachad Alao, Rachel Rodriguez, Rafi Ayub, Raghotham Murthy, Raghu Nayani, Rahul Mitra, Raymond Li, Rebekkah Hogan, Robin Battey, Rocky Wang, Rohan Maheswari, Russ Howes, Ruty Rinott, Sai Jayesh Bondu, Samyak Datta, Sara Chugh, Sara Hunt, Sargun Dhillon, Sasha Sidorov, Satadru Pan, Saurabh Verma, Seiji Yamamoto, Sharadh Ramaswamy, Shaun Lindsay, Shaun Lindsay, Sheng Feng, Shenghao Lin, Shengxin Cindy Zha, Shiva Shankar, Shuqiang Zhang, Shuqiang Zhang, Sinong Wang, Sneha Agarwal, Soji Sajuyigbe, Soumith Chintala, Stephanie Max, Stephen Chen, Steve Kehoe, Steve Satterfield, Sudarshan Govindaprasad, Sumit Gupta, Sungmin Cho, Sunny Virk, Suraj Subramanian, Sy Choudhury, Sydney Goldman, Tal Remez, Tamar Glaser, Tamara Best, Thilo Kohler, Thomas Robinson, Tianhe Li, Tianjun Zhang, Tim Matthews, Timothy Chou, Tzook Shaked, Varun Vontimitta, Victoria Ajayi, Victoria Montanez, Vijai Mohan, Vinay Satish Kumar, Vishal Mangla, Vítor Albiero, Vlad Ionescu, Vlad Poenaru, Vlad Tiberiu Mihailescu, Vladimir Ivanov, Wei Li, Wenchen Wang, Wenwen Jiang, Wes Bouaziz, Will Constable, Xiaocheng Tang, Xiaofang Wang, Xiaojian Wu, Xiaolan Wang, Xide Xia, Xilun Wu, Xinbo Gao, Yanjun Chen, Ye Hu, Ye Jia, Ye Qi, Yenda Li,

Yilin Zhang, Ying Zhang, Yossi Adi, Youngjin Nam, Yu, Wang, Yuchen Hao, Yundi Qian, Yuzi He, Zach Rait, Zachary DeVito, Zef Rosnbrick, Zhaoduo Wen, Zhenyu Yang, and Zhiwei Zhao. 2024. The Llama 3 herd of models. *Preprint*, arXiv:2407.21783.

- Clément Dumas, Veniamin Veselovsky, Giovanni Monea, Robert West, and Chris Wendler. 2024. How do Llamas process multilingual text? A latent exploration through the patchscope. In *ICML 2024 Workshop on Mechanistic Interpretability*.
- Nelson Elhage, Tristan Hume, Catherine Olsson, Neel Nanda, Tom Henighan, Scott Johnston, Sheer ElShowk, Nicholas Joseph, Nova DasSarma, Ben Mann, Danny Hernandez, Amanda Askell, Kamal Ndousse, Andy Jones, Dawn Drain, Anna Chen, Yuntao Bai, Deep Ganguli, Liane Lovitt, Zac Hatfield-Dodds, Jackson Kernion, Tom Conerly, Shauna Kravec, Stanislav Fort, Saurav Kadavath, Josh Jacobson, Eli Tran-Johnson, Jared Kaplan, Jack Clark, Tom Brown, Sam McCandlish, Dario Amodei, and Christopher Olah. 2022a. Softmax linear units. *Transformer Circuits Thread*.
- Nelson Elhage, Tristan Hume, Catherine Olsson, Nicholas Schiefer, Tom Henighan, Shauna Kravec, Zac Hatfield-Dodds, Robert Lasenby, Dawn Drain, Carol Chen, Roger Grosse, Sam McCandlish, Jared Kaplan, Dario Amodei, Martin Wattenberg, and Christopher Olah. 2022b. Toy models of superposition. *Transformer Circuits Thread*.
- Joshua Engels, Isaac Liao, Eric J. Michaud, Wes Gurnee, and Max Tegmark. 2024. Not all language model features are linear. *Computing Research Repository*, arXiv:2405.14860.
- Jiahai Feng, Stuart Russell, and Jacob Steinhardt. 2024. Monitoring latent world states in language models with propositional probes. *arXiv preprint arXiv:2406.19501*.
- Javier Ferrando. 2024. On the similarity of circuits across languages: a case study on the subject-verb agreement task. In *ICML 2024 Workshop on Mechanistic Interpretability*.
- Jaden Fiotto-Kaufman, Alexander R. Loftus, Eric Todd, Jannik Brinkmann, Koyena Pal, Dmitrii Troitskii, Michael Ripa, Adam Belfki, Can Rager, Caden Juang, Aaron Mueller, Samuel Marks, Arnab Sen Sharma, Francesca Lucchetti, Nikhil Prakash, Carla Brodley, Arjun Guha, Jonathan Bell, Byron C. Wallace, and David Bau. 2024. Nnsight and ndif: Democratizing access to open-weight foundation model internals. *Preprint*, arXiv:2407.14561.
- Leo Gao, Stella Biderman, Sid Black, Laurence Golding, Travis Hoppe, Charles Foster, Jason Phang, Horace He, Anish Thite, Noa Nabeshima, Shawn Presser, and Connor Leahy. 2020. The Pile: An 800GB dataset of diverse text for language modeling. *Preprint*, arXiv:2101.00027.

- Mario Giulianelli, Jack Harding, Florian Mohnert, Dieuwke Hupkes, and Willem Zuidema. 2018. Under the hood: Using diagnostic classifiers to investigate and improve how language models track agreement information. In *Proceedings of the 2018 EMNLP Workshop BlackboxNLP: Analyzing and Interpreting Neural Networks for NLP*, pages 240–248, Brussels, Belgium. Association for Computational Linguistics.
- Daniela Gottesman and Mor Geva. 2024. Estimating knowledge in large language models without generating a single token. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 3994–4019, Miami, Florida, USA. Association for Computational Linguistics.
- Naman Goyal, Cynthia Gao, Vishrav Chaudhary, Peng-Jen Chen, Guillaume Wenzek, Da Ju, Sanjana Krishnan, Marc'Aurelio Ranzato, Francisco Guzmán, and Angela Fan. 2021. The flores-101 evaluation benchmark for low-resource and multilingual machine translation.
- Ashim Gupta and Vivek Srikumar. 2021. X-fact: A new benchmark dataset for multilingual fact checking. In Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 2: Short Papers), pages 675–682, Online. Association for Computational Linguistics.
- John Hewitt and Christopher D. Manning. 2019. A structural probe for finding syntax in word representations. In Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), pages 4129–4138, Minneapolis, Minnesota. Association for Computational Linguistics.
- G. E. Hinton, J. L. McClelland, and D. E. Rumelhart. 1986. *Distributed representations*, page 77–109. MIT Press, Cambridge, MA, USA.
- Jing Huang, Atticus Geiger, Karel D'Oosterlinck, Zhengxuan Wu, and Christopher Potts. 2023. Rigorously assessing natural language explanations of neurons. In Proceedings of the 6th BlackboxNLP Workshop: Analyzing and Interpreting Neural Networks for NLP, pages 317–331, Singapore. Association for Computational Linguistics.
- Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Lélio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. 2023. Mistral 7b.
- Adam Karvonen, Benjamin Wright, Can Rager, Rico Angell, Jannik Brinkmann, Logan Riggs Smith, Claudio Mayrink Verdun, David Bau, and Samuel Marks. 2024. Measuring progress in dictionary learning for language model interpretability with board game

models. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*.

- Christo Kirov, Ryan Cotterell, John Sylak-Glassman, Géraldine Walther, Ekaterina Vylomova, Patrick Xia, Manaal Faruqui, Sabrina J. Mielke, Arya McCarthy, Sandra Kübler, David Yarowsky, Jason Eisner, and Mans Hulden. 2018. UniMorph 2.0: Universal Morphology. In Proceedings of the Eleventh International Conference on Language Resources and Evaluation (LREC 2018), Miyazaki, Japan. European Language Resources Association (ELRA).
- Janos Kramar, Tom Lieberum, Rohin Shah, and Neel Nanda. 2024. AtP*: An efficient and scalable method for localizing LLM behaviour to components. *Preprint*, arXiv:2403.00745.
- Vedang Lad, Wes Gurnee, and Max Tegmark. 2024. The remarkable robustness of LLMs: Stages of inference? In *ICML 2024 Workshop on Mechanistic Interpretability*.
- Xiaochen Li, Zheng-Xin Yong, and Stephen H. Bach. 2024. Preference tuning for toxicity mitigation generalizes across languages. *Preprint*, arXiv:2406.16235.
- Aleksandar Makelov, Georg Lange, and Neel Nanda. 2024. Towards principled evaluations of sparse autoencoders for interpretability and control. In *ICLR* 2024 Workshop on Secure and Trustworthy Large Language Models.
- Sam Marks and Aaron Mueller. 2024. Dictionary learning. https://github.com/saprmarks/ dictionary_learning/tree/main.
- Samuel Marks, Can Rager, Eric J. Michaud, Yonatan Belinkov, David Bau, and Aaron Mueller. 2024. Sparse feature circuits: Discovering and editing interpretable causal graphs in language models. *Preprint*, arXiv:2403.19647.
- Kevin Meng, David Bau, Alex J Andonian, and Yonatan Belinkov. 2022. Locating and editing factual associations in GPT. In *Advances in Neural Information Processing Systems*.
- Alireza Mohammadshahi, Vassilina Nikoulina, Alexandre Berard, Caroline Brun, James Henderson, and Laurent Besacier. 2022. SMaLL-100: Introducing shallow multilingual machine translation model for low-resource languages. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 8348–8359, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.
- Aaron Mueller, Jannik Brinkmann, Millicent Li, Samuel Marks, Koyena Pal, Nikhil Prakash, Can Rager, Aruna Sankaranarayanan, Arnab Sen Sharma, Jiuding Sun, Eric Todd, David Bau, and Yonatan Belinkov. 2024. The quest for the right mediator: A history, survey, and theoretical grounding of causal interpretability. *Preprint*, arXiv:2408.01416.
- Joakim Nivre, Željko Agić, Lars Ahrenberg, Lene Antonsen, Maria Jesus Aranzabe, Masayuki Asahara, Luma Ateyah, Mohammed Attia, Aitziber Atutxa, Liesbeth Augustinus, Elena Badmaeva, Miguel Ballesteros, Esha Banerjee, Sebastian Bank, Verginica Barbu Mititelu, John Bauer, Kepa Bengoetxea, Riyaz Ahmad Bhat, Eckhard Bick, Victoria Bobicev, Carl Börstell, Cristina Bosco, Gosse Bouma, Sam Bowman, Aljoscha Burchardt, Marie Candito, Gauthier Caron, Gülşen Cebiroğlu Eryiğit, Giuseppe G. A. Celano, Savas Cetin, Fabricio Chalub, Jinho Choi, Silvie Cinková, Çağrı Çöltekin, Miriam Connor, Elizabeth Davidson, Marie-Catherine de Marneffe, Valeria de Paiva, Arantza Diaz de Ilarraza, Peter Dirix, Kaja Dobrovoljc, Timothy Dozat, Kira Droganova, Puneet Dwivedi, Marhaba Eli, Ali Elkahky, Tomaž Erjavec, Richárd Farkas, Hector Fernandez Alcalde, Jennifer Foster, Cláudia Freitas, Katarína Gajdošová, Daniel Galbraith, Marcos Garcia, Moa Gärdenfors, Kim Gerdes, Filip Ginter, Iakes Goenaga, Koldo Gojenola, Memduh Gökırmak, Yoav Goldberg, Xavier Gómez Guinovart, Berta Gonzáles Saavedra, Matias Grioni, Normunds Grūzītis, Bruno Guillaume, Nizar Habash, Jan Hajič, Jan Hajič jr., Linh Hà Mỹ, Kim Harris, Dag Haug, Barbora Hladká, Jaroslava Hlaváčová, Florinel Hociung, Petter Hohle, Radu Ion, Elena Irimia, Tomáš Jelínek, Anders Johannsen, Fredrik Jørgensen, Hüner Kaşıkara, Hiroshi Kanayama, Jenna Kanerva, Tolga Kayadelen, Václava Kettnerová, Jesse Kirchner, Natalia Kotsyba, Simon Krek, Veronika Laippala, Lorenzo Lambertino, Tatiana Lando, John Lee, Phương Lê Hồng, Alessandro Lenci, Saran Lertpradit, Herman Leung, Cheuk Ying Li, Josie Li, Keying Li, Nikola Ljubešić, Olga Loginova, Olga Lyashevskaya, Teresa Lynn, Vivien Macketanz, Aibek Makazhanov, Michael Mandl, Christopher Manning, Cătălina Mărănduc, David Mareček, Katrin Marheinecke, Héctor Martínez Alonso, André Martins, Jan Mašek, Yuji Matsumoto, Ryan McDonald, Gustavo Mendonça, Niko Miekka, Anna Missilä, Cătălin Mititelu, Yusuke Miyao, Simonetta Montemagni, Amir More, Laura Moreno Romero, Shinsuke Mori, Bohdan Moskalevskyi, Kadri Muischnek, Kaili Müürisep, Pinkey Nainwani, Anna Nedoluzhko, Gunta Nešpore-Bērzkalne, Lương Nguyễn Thị, Huyền Nguyễn Thị Minh, Vitaly Nikolaev, Hanna Nurmi, Stina Ojala, Petya Osenova, Robert Östling, Lilja Øvrelid, Elena Pascual, Marco Passarotti, Cenel-Augusto Perez, Guy Perrier, Slav Petrov, Jussi Piitulainen, Emily Pitler, Barbara Plank, Martin Popel, Lauma Pretkalnina, Prokopis Prokopidis, Tiina Puolakainen, Sampo Pyysalo, Alexandre Rademaker, Loganathan Ramasamy, Taraka Rama, Vinit Ravishankar, Livy Real, Siva Reddy, Georg Rehm, Larissa Rinaldi, Laura Rituma, Mykhailo Romanenko, Rudolf Rosa, Davide Rovati, Benoît Sagot, Shadi Saleh, Tanja Samardžić, Manuela Sanguinetti, Baiba Saulīte, Sebastian Schuster, Djamé Seddah, Wolfgang Seeker, Mojgan Seraji, Mo Shen, Atsuko Shimada, Dmitry Sichinava, Natalia Silveira, Maria Simi, Radu Simionescu, Katalin Simkó, Mária Šimková, Kiril Simov, Aaron Smith, Antonio Stella,

Milan Straka, Jana Strnadová, Alane Suhr, Umut Sulubacak, Zsolt Szántó, Dima Taji, Takaaki Tanaka, Trond Trosterud, Anna Trukhina, Reut Tsarfaty, Francis Tyers, Sumire Uematsu, Zdeňka Urešová, Larraitz Uria, Hans Uszkoreit, Sowmya Vajjala, Daniel van Niekerk, Gertjan van Noord, Viktor Varga, Eric Villemonte de la Clergerie, Veronika Vincze, Lars Wallin, Jonathan North Washington, Mats Wirén, Tak-sum Wong, Zhuoran Yu, Zdeněk Žabokrtský, Amir Zeldes, Daniel Zeman, and Hanzhi Zhu. 2017. Universal dependencies 2.1. LINDAT/CLARIAH-CZ digital library at the Institute of Formal and Applied Linguistics (ÚFAL), Faculty of Mathematics and Physics, Charles University.

- Hadas Orgad, Michael Toker, Zorik Gekhman, Roi Reichart, Idan Szpektor, Hadas Kotek, and Yonatan Belinkov. 2024. Llms know more than they show: On the intrinsic representation of llm hallucinations. *Preprint*, arXiv:2410.02707.
- Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the* 40th Annual Meeting of the Association for Computational Linguistics, pages 311–318, Philadelphia, Pennsylvania, USA. Association for Computational Linguistics.
- Judea Pearl. 2001. Direct and indirect effects. In Proceedings of the Seventeenth Conference on Uncertainty in Artificial Intelligence, UAI'01, page 411–420, San Francisco, CA, USA. Morgan Kaufmann Publishers Inc.
- F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. 2011. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830.
- Monika M. Połczyńska and Susan Y. Bookheimer. 2021. General principles governing the amount of neuroanatomical overlap between languages in bilinguals. *Neuroscience and Biobehavioral Reviews*, 130:1–14.
- Matt Post. 2018. A call for clarity in reporting BLEU scores. In Proceedings of the Third Conference on Machine Translation: Research Papers, pages 186– 191, Brussels, Belgium. Association for Computational Linguistics.
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. 2020. Exploring the limits of transfer learning with a unified text-to-text transformer. *J. Mach. Learn. Res.*, 21(1).
- Alessandro Raganato, Tommaso Pasini, Jose Camacho-Collados, and Mohammad Taher Pilehvar. 2020. XL-WiC: A multilingual benchmark for evaluating semantic contextualization. In *Proceedings of the 2020*

Conference on Empirical Methods in Natural Language Processing (EMNLP), pages 7193–7206, Online. Association for Computational Linguistics.

- Senthooran Rajamanoharan, Arthur Conmy, Lewis Smith, Tom Lieberum, Vikrant Varma, János Kramár, Rohin Shah, and Neel Nanda. 2024. Improving dictionary learning with gated sparse autoencoders. *Preprint*, arXiv:2404.16014.
- Anton Schäfer, Shauli Ravfogel, Thomas Hofmann, Tiago Pimentel, and Imanol Schlag. 2024. Language imbalance can boost cross-lingual generalisation. *arXiv preprint arXiv:2404.07982*.
- Stepan Shabalin, Dmitrii Kharlapenko, Arthur Conmy, and Neel Nanda. 2023. SAE features for refusal and sycophancy steering vectors. LessWrong.
- Claude Elwood Shannon. 1948. A mathematical theory of communication. *The Bell System Technical Journal*, 27:379–423.
- P. Smolensky. 1986. Neural and conceptual interpretation of PDP models, page 390–431. MIT Press, Cambridge, MA, USA.
- Karolina Stanczak, Edoardo Ponti, Lucas Torroba Hennigen, Ryan Cotterell, and Isabelle Augenstein. 2022. Same neurons, different languages: Probing morphosyntax in multilingual pre-trained models. In Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, pages 1589–1598, Seattle, United States. Association for Computational Linguistics.
- Simone Sulpizio, Nicola Del Maschio, Davide Fedeli, and Jubin Abutalebi. 2020. Bilingual language processing: A meta-analysis of functional neuroimaging studies. *Neuroscience and Biobehavioral Reviews*, 108:834–853.
- Mukund Sundararajan, Ankur Taly, and Qiqi Yan. 2017. Axiomatic attribution for deep networks. In *Proceedings of the 34th International Conference on Machine Learning - Volume 70*, ICML'17, page 3319–3328. JMLR.org.
- Aaquib Syed, Can Rager, and Arthur Conmy. 2024. Attribution patching outperforms automated circuit discovery. In *The 7th BlackboxNLP Workshop*.
- Adly Templeton, Tom Conerly, Jonathan Marcus, Jack Lindsey, Trenton Bricken, Brian Chen, Adam Pearce, Craig Citro, Emmanuel Ameisen, Andy Jones, Hoagy Cunningham, Nicholas L Turner, Callum McDougall, Monte MacDiarmid, C. Daniel Freeman, Theodore R. Sumers, Edward Rees, Joshua Batson, Adam Jermyn, Shan Carter, Chris Olah, and Tom Henighan. 2024. Scaling monosemanticity: Extracting interpretable features from Claude 3 Sonnet. *Transformer Circuits Thread*.

- Chris Wendler, Veniamin Veselovsky, Giovanni Monea, and Robert West. 2024. Do llamas work in English? on the latent language of multilingual transformers. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15366–15394, Bangkok, Thailand. Association for Computational Linguistics.
- Benjamin Wright and Lee Sharkey. 2024. Addressing feature suppression in sparse autoencoders. Less-Wrong post.
- Linting Xue, Noah Constant, Adam Roberts, Mihir Kale, Rami Al-Rfou, Aditya Siddhant, Aditya Barua, and Colin Raffel. 2021. mT5: A massively multilingual pre-trained text-to-text transformer. In *Proceedings* of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, pages 483–498, Online. Association for Computational Linguistics.

A Implementation Details

A.1 Infrastructure

The experiments were run on a single server with 8 NVIDIA RTX A6000 48 GB GPUs with CUDA Version 12.4 and an AMD EPYC 7413 24-Core Processor. The total runtime for training the probes and autoencoders was less than a week.

A.2 Libraries

To extract activations and intervene on the model, we use nnsight (Fiotto-Kaufman et al., 2024). For training the linear probes, we use scikit-learn (Pedregosa et al., 2011). For training the SAEs, we use dictionary-learning (Marks and Mueller, 2024).

B Languages

In our experiments, we consider the set of languages which Aya-23 (Aryabumi et al., 2024) was trained on. This includes: Arabic, Chinese, Czech, Dutch, English, French, German, Greek, Hebrew, Hindi, Indonesian, Italian, Japanese, Korean, Persian, Polish, Portuguese, Romanian, Russian, Spanish, Turkish, Ukrainian, and Vietnamese.

C Attribution Patching

Here, we elaborate on activation patching, attribution patching, and the modified attribution patching approach we use in our experiments.

Activation patching is a method for quantifying the causal importance of a model component on a model behavior. It involves replacing the activation of some component in the model during one model forward pass with the activations of the same component from a different forward pass. This requires constructing a distribution \mathcal{D} over pairs of inputs (x_{clean}, x_{patch}), where x_{clean} is a prompt on which the behaviour occurs, and x_{patch} is a reference prompt on which the behaviour does not occur. For example, to study subject-verb agreement one could construct a datasets of pairs such as:

- a. The **dog** \rightarrow **barks**
- b. The **dogs** \rightarrow **bark**

Then, we can define the contribution of a node $n \in N$, where N is the number of components in the model, to the model's behaviour as the counterfactual expected impact of replacing that node on the clean prompt with its value on the patch prompt (Meng et al., 2022). In practice, performing activation patching for all components requires O(N) forward passes, which does not scale efficiently (Mueller et al., 2024). Therefore, we use a faster linear approximation of the contribution of a node; this is *attribution patching*, which computes a first-order Taylor expansion of this metric as described in §2.

In our experiments, we use the attribution patching approach proposed by Marks et al. (2024) which employs a more expensive but more accurate approximation based on integrated gradients:

$$\begin{split} \hat{\mathrm{IE}}_{\mathrm{ig}}(m;\mathbf{a};x_{\mathrm{clean}},x_{\mathrm{patch}}) = \\ \sum_{\alpha} \nabla_{\mathbf{a}} m \big|_{\alpha \mathbf{a}_{\mathrm{clean}} + (1-\alpha) \mathbf{a}_{\mathrm{patch}}} \right) (\mathbf{a}_{\mathrm{patch}} - \mathbf{a}_{\mathrm{clean}}) \end{split}$$

where the sum ranges over K = 10 equallyequally spaced $\alpha \in \{0, \frac{1}{K}, \dots, \frac{K-1}{K}\}$. While this cannot be done in parallel for two nodes when one is downstream of another, it can be done in parallel for arbitrarily many nodes which do not depend on each other. Thus the additional cost of computing $\hat{\mathbf{IE}}_{ig}$ over $\hat{\mathbf{IE}}_{atp}$ scales linearly in K.

D Sparse Autoencoders

D.1 Gated Sparse Autoencoders

The SAE architecture, as introduced in Bricken et al. (2023) is defined by encoder weights $W_e \in \mathbb{R}^{m \times n}$, decoder weights $W_d \in \mathbb{R}^{n \times m}$ with columns constrained to have a L_2 -norm of 1, and biases $b_e \in \mathbb{R}^m$, $b_d \in \mathbb{R}^n$. Given an input $\mathbf{x} \in \mathbb{R}^n$, the SAE computes

$$\mathbf{f}(\mathbf{x}) = \operatorname{ReLU}(W_e(\mathbf{x} - \mathbf{b}_d) + \mathbf{b}_e) \qquad (3)$$

$$\hat{\mathbf{x}} = W_d \, \mathbf{f}(\mathbf{x}) + \mathbf{b}_d \tag{4}$$

where f(x) is the vector of feature activations, and \hat{x} is the reconstruction. This model is trained using the following loss term:

$$\mathcal{L}_{\text{standard}} = \mathbb{E}_{\mathbf{x} \sim \mathcal{D}_{\text{train}}} \Big[\|\mathbf{x} - \hat{\mathbf{x}}\|_2 + \lambda \|\mathbf{f}(\mathbf{x})\|_1 \Big].$$
(5)

for some hyperparameter $\lambda > 0$ controlling sparsity.

The L_1 penalty introduces biases that can harm the accuracy of the reconstruction, as the loss can be decreased by trading-off reconstruction for lower L1 (Wright and Sharkey, 2024). To address this, Rajamanoharan et al. (2024) introduced a architectural modification that separates (i) the selection of dictionary elements to use in a reconstruction, and (ii) estimating the coefficients of these elements. This results in the following gated architecture:

$$\begin{aligned} \pi_{\text{gate}}(\mathbf{x}) &:= W_{\text{gate}}(\mathbf{x} - \mathbf{b}_d) + \mathbf{b}_{\text{gate}} \\ \mathbf{\tilde{f}}(\mathbf{x}) &:= \mathbb{I} \left[\pi_{\text{gate}}(\mathbf{x}) > 0 \right] \odot \\ \text{ReLU}(W_{\text{mag}}(\mathbf{x} - \mathbf{b}_d) + \mathbf{b}_{\text{mag}}) \\ \hat{x}(\mathbf{\tilde{f}}(\mathbf{x})) &= W_d \mathbf{\tilde{f}}(\mathbf{x}) + \mathbf{b}_d \end{aligned}$$

where $\mathbb{I}[\cdot > 0]$ is the Heaviside step function and \odot denotes elementwise multiplication. Then, the loss function uses \hat{x}_{frozen} , a frozen copy of the decoder:

$$\mathcal{L}_{\text{gated}} := \mathbb{E}_{\mathbf{x} \sim \mathcal{D}_{\text{train}}} \Big[\|\mathbf{x} - \hat{x}(\tilde{\mathbf{f}}(\mathbf{x}))\|_{2}^{2} \\ + \lambda \|\text{ReLU}(\pi_{\text{gate}}(\mathbf{x}))\|_{1}$$
(6)
$$+ \|\mathbf{x} - \hat{x}_{\text{frozen}}(\text{ReLU}(\pi_{\text{gate}}(\mathbf{x})))\|_{2}^{2} \Big]$$

D.2 Training Parameters

Parameter	Value
Optimiser	Adam
Learning Rate	0.001
L1 Coefficient	0.505
Expansion Factor	8
Number of Token	250 Million
Batch Size	512
Warmup Steps	1,000

Table 1: Training parameters of our sparse autoencoders for both Llama-3-8B and Aya-23-8B.

D.3 Performance Across Languages

We evaluate the performance of the sparse autoencoder trained on Llama-3-8B using the multilingual C4 (mC4) dataset (Xue et al., 2021), itself a multilingual extension of the C4 dataset (Raffel et al., 2020). Table 2 presents the *loss recovered* when replacing the residual stream activations with the sparse autoencoder reconstructions across a range of languages. For this purpose, we compute the loss recovered as

$$L_{recovered} = \frac{L_{reconstructed} - L_{zero}}{L_{original} - L_{zero}}$$
(7)

where $L_{original}$ is the cross entropy (CE) loss of the language model without intervention, L_{zero} is the CE loss of the model when zero ablating the activations, and $L_{reconstructed}$ is the loss when replacing the activations with the sparse autoencoder reconstructions. This is a standard extrinsic metric to measure autoencoder quality (Mueller et al., 2024). However, it does not measure the intrinsic interpretability of the SAE features, which is not possible to measure in the absence of ground truth features (Karvonen et al., 2024; Makelov et al., 2024).

Language	Loss Recovered	
Chinese	0.8122	
Dutch	0.9004	
English	0.9257	
Finnish	0.8582	
French	0.9285	
German	0.9026	
Indonesian	0.9205	
Japanese	0.8759	
Turkish	0.8522	

Table 2: Evaluation of the sparse autoencoder trained on Llama-3-8B across different subsets on the AllenAI C4 dataset. The table shows the fraction of loss recovered when replacing residual stream activations with sparse autoencoders reconstructions across nine languages.

E Features Across Languages

We measured the number of languages for which the top-32 features for each concept were strongly influential. Across grammatical concepts, the number of languages that a feature is influential for roughly follows a power law distribution. Below, we present the distributions for a selection of common concepts (see Figures 8, 9, 10). We find that for most concepts, there are multiple features that are shared across nearly all languages. Note that the maximum number of languages varies across concepts, as not all languages inflect for a given concept nor are annotated for it in Universal Dependencies.



Figure 8: Distribution of the number of languages across which a given feature associated with masculine gender is shared (Llama 3).



Figure 9: Distribution of the number of languages across which a given feature associated with past tense is shared (Llama 3).



Figure 10: Distribution of the number of languages across which a given feature associated with accusative case is shared (Llama 3).

F Machine Translation

F.1 Prompt Format

The following is an example of our 2-shot translation prompt:



Figure 11: Distribution of the number of languages across which a given feature associated with masculine gender is shared (Aya-23).



Figure 12: Distribution of the number of languages across which a given feature associated with past tense is shared (Aya-23).



Figure 13: Distribution of the number of languages across which a given feature associated with accusative case is shared (Aya-23).

F.2 Translation Performance

We evaluate the ability of Llama-3-8B and Aya-23-8B to translate languages in-context using the Flores-101 dataset (Goyal et al., 2021). Specifically, we measure the BLEU score (Papineni et al., 2002) using the SacreBLEU implementation (Post, 2018). We prompt models with 2 ground-truth exemplar translations, and then give it the test sentence in the source language (see Figure 14). Results are presented in Figure 15 and 16. The governor's office said nineteen of the injured were police officers. \\ Das Gouverneursamt erklärte, dass von den Verletzten neun Polizisten waren.

He produced over 1,000 stamps for Sweden and 28 other countries. \\ Er produzierte über 1.000 Briefmarken für Schweden und 28 weitere Länder.

The truck driver, who is aged 64, was not injured in the crash. $\$

Figure 14: Example 2-shot translation prompt between English and German. Note that the double backslashes are *literals*, not newlines. We found this prompt format to work best empirically in 2-shot settings in initial experiments.



Figure 15: SacreBLEU scores of Llama-3-8B.



Figure 16: SacreBLEU scores of Aya-23-8B.

G Counterfactual Dataset

Our counterfactual dataset considers three concepts (gender, number, tense) and three languages (English, French, German). The dataset format is inspired by CausalGym (Arora et al., 2024) and the templates are in part taken from that dataset. We present example counterfactuals in Table 3.

Morphosyntactic Concept	Language	Example Input	Example Output
Gender (Masc. vs. Fem.)	English	When Sam was at the park	he
		When Sarah was at the park	she
	French	Louis a accepté, parce	qu'il
		Charlotte a accepté, parce	qu'elle
	German	Lukas lachte, weil	er
		Hannah lachte, weil	sie
Number (Sing. vs. Plur.)	English	The scientist	discovers
		The scientists	discover
	French	Le docteur	est
		Les docteurs	sont
	German	Der Schauspieler	ist
		Die Schauspieler	sind
Tense (Pres. vs. Past)	English	When Mary is in the bed, she	sleeps
		When Mary was in the bed, she	slept
	French	Louis marche parce qu'il	est
		Louis marchait parce qu'il	était
	German	Lukas geht, weil er	ist
		Lukas ging, weil er	war

Table 3: Examples from our counterfactual dataset.