Derivation of Output Correlation Inferences for Multi-Output (aka Multi-Task) Gaussian Process

Shuhei Watanabe

Preferred Networks Inc. shuheiwatanabe@preferred.jp

Abstract Gaussian process (GP) is arguably one of the most widely used machine learning algorithms in practice. One of its prominent applications is Bayesian optimization (BO). Although the vanilla GP itself is already a powerful tool for BO, it is often beneficial to be able to consider the dependencies of multiple outputs. To do so, Multi-task GP (MTGP) is formulated, but it is not trivial to fully understand the derivations of its formulations and their gradients from the previous literature. This paper serves friendly derivations of the MTGP formulations and their gradients.

1 Introduction

Gaussian process (GP) is one of the most important machine learning algorithms in practice and often plays a key role in Bayesian optimization (BO) (Brochu et al., 2010; Shahriari et al., 2016; Garnett, 2022)¹ because GP shows good predictive accuracy even with a small amount of data. While the vanilla GP models only one output, multi-output modeling by GP (Bonilla et al., 2007), aka multi-task GP (MTGP), often brings benefits as represented by Swersky et al. (2013); Daulton et al. (2020, 2022). Although they demonstrated that MTGP is effective for multi-objective optimization, constrained optimization, multi-fidelity optimization, and meta-learning, many works still do not rely on MTGP, e.g., multi-objective optimization by Yang et al. (2019), constrained optimization by Gardner et al. (2014); Gelbart et al. (2014); Eriksson and Poloczek (2021), multi-fidelity optimization by Kandasamy et al. (2017); Song et al. (2019); Kandasamy et al. (2019); Wistuba et al. (2022), and meta-learning by Feurer et al. (2018). That is partially because the original paper (Bonilla et al., 2007) unfortunately lacks their derivation details, making it challenging to fully understand. To this end, we remove this barrier in this paper by giving more detailed and friendly derivations of the formulations and the gradients of the formulations with respect to kernel hyperparameters. By doing so, we would like more researchers to work on the aforementioned problem setups using MTGP, potentially leading to further enhancements in existing hyperparameter optimization frameworks that use MTGP such as BoTorch (Balandat et al., 2020).

2 Related Work

In this paper, we focus only on MTGP formulated in Bonilla et al. (2007) simply because this model is used in BoTorch ², which is the most widely used GP-based BO framework we are aware of. Bonilla et al. (2007) formulated MTGP as a linear combination of latent GPs with fixed coefficients as explained later. This formulation is relatively simple and a large body of existing work tackled to capture more complex structures. For example, Wilson et al. (2011) modeled the coefficients dependent on input variables, Alvarez and Lawrence (2008) employed convolved process, and Titsias (2009); Nguyen et al. (2014) used variational inference to approximate the posterior of the latent processes.

¹BO is not necessarily dependent on GP. For example, TPE (Bergstra et al., 2011; Watanabe, 2023) uses kernel density estimation and SMAC (Lindauer et al., 2022) uses random forest.

²See the documentation string of MultiTaskGP in https://botorch.org/api/_modules/botorch/models/multitask.html.

3 Preliminaries

3.1 Notations

In this paper, we use the following notations:

- 1. $\mathcal{N}(\boldsymbol{\mu}, \boldsymbol{\Sigma})$, the Gaussian distribution with the mean $\boldsymbol{\mu}$ and the covariance matrix $\boldsymbol{\Sigma}$,
- 2. $\mathcal{N}(\boldsymbol{z}|\boldsymbol{\mu},\boldsymbol{\Sigma})$, the probability density function of the Gaussian distribution with the mean $\boldsymbol{\mu}$ and the covariance matrix $\boldsymbol{\Sigma}$,
- 3. $x \in \mathcal{X} \subseteq \mathbb{R}^{D}$, an input vector x defined on a D-dimensional domain \mathcal{X} ,
- 4. $f_m : \mathcal{X} \to \mathbb{R}$, the unobservable output mean function of the *m*-th output,
- 5. $M \in \mathbb{Z}_+$, the number of outputs given an input vector,
- 6. $y_{n,m} \sim \mathcal{N}(f_m(\mathbf{x}_n), \sigma_m^2)$, the observed *m*-th output value of the *n*-th input vector \mathbf{x}_n ,
- 7. $\Sigma := \text{diag}[\sigma_1^2, \dots, \sigma_M^2] \in \mathbb{R}^{M \times M}$, a diagonal matrix with the (m, m)-th element σ_m^2 ,
- 8. $\mathbf{0}_N \in \mathbb{R}^N$, a zero vector with the size N,
- 9. $I_N \in \mathbb{R}^{N \times N}$, an identity matrix with the shape of $N \times N$,
- 10. $S := I_N \otimes \Sigma \in \mathbb{R}^{NM \times NM}$, the Kronecker product of I_N and Σ ,
- 11. $y_n := [y_{n,1}, y_{n,2}, \dots, y_{n,m}] \in \mathbb{R}^M$, the observed output vector given the *n*-th input vector,
- 12. $Y \in \mathbb{R}^{N \times M}$, the observed output matrix with the (i, j)-th element $y_{i,j}$,
- 13. $f_n := [f_{n,1}, \ldots, f_{n,m}] := [f_1(\mathbf{x}_n), f_2(\mathbf{x}_n), \ldots, f_m(\mathbf{x}_n)] \in \mathbb{R}^M$, the output mean vector given the *n*-th input vector,
- 14. $F \in \mathbb{R}^{N \times M}$, the output mean matrix with the (i, j)-th element $f_{i,j}$,
- 15. $\boldsymbol{y}_{1:N} \coloneqq \operatorname{vec}(Y) = [\boldsymbol{y}_1^{\top}, \dots, \boldsymbol{y}_N^{\top}]^{\top} \in \mathbb{R}^{NM}$, the flattened observed output vector,
- 16. $f_{1:N} \coloneqq \text{vec}(F) = [f_1^\top, \dots, f_N^\top]^\top \in \mathbb{R}^{NM}$, the flattened output mean vector,
- 17. $k_{\theta} : \mathcal{X} \times \mathcal{X} \to \mathbb{R}$, a kernel function given its hyperparameters θ ,
- 18. $K_x \in \mathbb{R}^{N \times N}$, a kernel matrix for the input vectors with the (i, j)-th element $k_{\theta}(x_i, x_j)$,
- 19. $K_f \in \mathbb{R}^{M \times M}$, a kernel matrix for outputs,
- 20. $K_{xf} := K_x \otimes K_f \in \mathbb{R}^{NM \times NM}$, the Kronecker product of K_x and K_f , and
- 21. $A_{i,j} \in \mathbb{R}$, the (i, j)-th element of the matrix A.

Note that we assume that kernel matrices are positive definite and symmetric, meaning that they are invertible, and the output function $f : \{1, ..., M\} \times \mathcal{X} \to \mathbb{R}$ follows the Gaussian process, i.e., $f \sim \mathcal{GP}(\mu, k_{\theta}k_f)$ where $k_f(i, j) = (K_f)_{i,j}$ is an index kernel for the output correlation, and vec : $\mathbb{R}^{N \times M} \to \mathbb{R}^{NM}$ is the vectorization operation:

$$\operatorname{vec}(C) = \operatorname{vec}\left(\begin{bmatrix} C_{1,1} & \cdots & C_{1,M} \\ \vdots & \ddots & \vdots \\ C_{N,1} & \cdots & C_{N,M} \end{bmatrix}\right) = \begin{bmatrix} C_{1,1}, \dots, C_{1,M}, C_{2,1}, \dots, C_{2,M}, \dots, C_{N,1}, \dots, C_{N,M} \end{bmatrix}^{\top}.$$
(1)

Furthermore, we define the Kronecker product \otimes as follows:

$$A \otimes B = \begin{bmatrix} A_{1,1}B & \cdots & A_{1,N}B \\ \vdots & \ddots & \vdots \\ A_{N,1}B & \cdots & A_{N,N}B \end{bmatrix} \in \mathbb{R}^{NM \times NM}$$
(2)

where $A \in \mathbb{R}^{N \times N}$ and $B \in \mathbb{R}^{M \times M}$.

3.2 Basic Theorems in Linear Algebra

In this section, we consistently assume that $A \in \mathbb{R}^{N \times N}$, $B \in \mathbb{R}^{M \times M}$, $C \in \mathbb{R}^{N \times M}$, and $D \in \mathbb{R}^{M \times N}$.

Theorem 1 $\operatorname{vec}(C)^{\top}(A \otimes B)\operatorname{vec}(C) = \operatorname{tr}(ACB^{\top}C^{\top})$ holds.

The proof is available in Appendix A.1.

Theorem 2 tr(CD) = tr(DC) holds.

This property is known as cyclic property and the proof is available in Appendix A.2.

4 Output Correlation Inference for Multi-Task Gaussian Process

Bonilla et al. (2007) proposed to model the interaction effects between each output by assuming $\mathcal{N}(f_{1:N}|\mathbf{0}_{NM}, K_{xf})$ as the prior and $\mathcal{N}(\boldsymbol{y}|\boldsymbol{f}, \boldsymbol{\Sigma})$ as the likelihood. Importantly, we need to estimate the kernel matrix K_f for outputs and Bonilla et al. (2007) introduced the EM algorithm (McLachlan and Krishnan, 2008) update for this and the gradient approach. However, the paper unfortunately lacks their derivation details. This section provides the derivation details to fill the gap in the original paper. Note that the approach used in BoTorch is the gradient approach explained in Section 4.2.

4.1 EM Algorithm Update for Multi-Task Gaussian Process

We first provide a friendly derivation of the EM algorithm update for MTGP.

4.1.1 Complete-Data Log-Likelihood. Since MTGP requires the approximation of the output correlation K_f , the hyperparameter optimization of the kernel function is indispensable. To estimate K_f , Bonilla et al. (2007) used the EM algorithm that repeats E step where we estimate the expectation over the distribution $p(f_{1:N}|\boldsymbol{y}_{1:N}, \boldsymbol{\theta}, K_f, \Sigma)$ of the missing data, i.e. $f_{1:N}$ in our case, and M step where we maximize the complete-data log-likelihood $L_{\text{comp}} \coloneqq p(\boldsymbol{y}_{1:N}, f_{1:N})$, which we derive in this section. Using the Bayes' theorem $p(\boldsymbol{y}_{1:N}, f_{1:N}) = p(\boldsymbol{y}_{1:N}|f_{1:N})p(f_{1:N})$, the complete-data log-likelihood is computed as follows:

$$L_{\text{comp}} = \log \mathcal{N}(\boldsymbol{y}_{1:N}|\boldsymbol{f}_{1:N}, S) \mathcal{N}(\boldsymbol{f}_{1:N}|\boldsymbol{0}_{NM}, K_{xf}) \text{ (Defs. } S = I_N \otimes \Sigma, K_{xf} = K_x \otimes K_f)$$

$$= \log \frac{1}{(2\pi)^{NM} |S|^{1/2} |K_{xf}|^{1/2}} \exp\left(-\frac{(\boldsymbol{y}_{1:N} - \boldsymbol{f}_{1:N})^\top S^{-1}(\boldsymbol{y}_{1:N} - \boldsymbol{f}_{1:N})}{2} - \frac{\boldsymbol{f}_{1:N}^\top K_{xf}^{-1} \boldsymbol{f}_{1:N}}{2}\right)$$

$$= -NM \log 2\pi - \frac{1}{2} \log |S| - \frac{(\boldsymbol{y}_{1:N} - \boldsymbol{f}_{1:N})^\top S^{-1}(\boldsymbol{y}_{1:N} - \boldsymbol{f}_{1:N})}{2} - \frac{1}{2} \log |K_{xf}| - \frac{\boldsymbol{f}_{1:N}^\top K_{xf}^{-1} \boldsymbol{f}_{1:N}}{2}.$$
(3)

Since $|A \otimes B| = |A|^M |B|^N$ holds for $A \in \mathbb{R}^{N \times N}$ and $B \in \mathbb{R}^{M \times M}$, we can further transform as follows:

$$L_{\text{comp}} = -\frac{M}{2} \underbrace{\log |I_N|}_{=0} -\frac{N}{2} \underbrace{\log |\Sigma|}_{=\Sigma_{m=1}^M \log \sigma_m^2} - \frac{M}{2} \log |K_x| - \frac{N}{2} \log |K_f| - \underbrace{(\mathbf{y}_{1:N} - f_{1:N})^\top (I_N \otimes \Sigma)^{-1} (\mathbf{y}_{1:N} - f_{1:N})}_{=\frac{1}{2} \sum_{n=1}^N (\mathbf{y}_n - f_n)^\top \Sigma^{-1} (\mathbf{y}_n - f_n)} - \frac{f_{1:N}^\top K_{xf}^{-1} f_{1:N}}{2} + \text{const.}$$

$$= -\frac{N}{2} \sum_{m=1}^M \log \sigma_m^2 - \frac{M}{2} \log |K_x| - \frac{N}{2} \log |K_f| - \frac{1}{2} \sum_{n=1}^N (\mathbf{y}_n - f_n)^\top \Sigma^{-1} (\mathbf{y}_n - f_n) - \frac{f_{1:N}^\top K_{xf}^{-1} f_{1:N}}{2} + \text{const.}$$
(4)

We will finally transform the last term of Eq. (4) using $(A \otimes B)^{-1} = A^{-1} \otimes B^{-1}$, Theorem 1, and Theorem 2. Without loss of generality, we can ignore the coefficient -1/2 and then we can transform the last term as follows:

$$f_{1:N}^{\top} K_{xf}^{-1} f_{1:N} = f_{1:N}^{\top} (K_x \otimes K_f)^{-1} f_{1:N} = \operatorname{vec}(F)^{\top} (K_x^{-1} \otimes K_f^{-1}) \operatorname{vec}(F)$$

= $\operatorname{tr}(K_x^{-1} F K_f^{-1} F^{\top})$ (\because Theorem 1, $K_x = K_x^{\top}, K_f = K_f^{\top}$) (5)
= $\operatorname{tr}(F^{\top} K_x^{-1} F K_f^{-1})$ (\because Theorem 2)

By plugging it back in, we obtain the complete-data log-likelihood:

$$L_{\text{comp}} = -N \sum_{m=1}^{M} \log \sigma_m - \frac{M}{2} \log |K_x| - \frac{N}{2} \log |K_f| - \sum_{n=1}^{N} \sum_{m=1}^{M} \frac{(y_{n,m} - f_{n,m})^2}{2\sigma_m^2} - \frac{1}{2} \text{tr}(F^{\mathsf{T}} K_x^{-1} F K_f^{-1}) + \text{const}$$
(6)

4.1.2 Maximum Likelihood Estimation in M Step. In the M step, we maximize the complete-data loglikelihood L_{comp} with respect to θ , Σ , and K_f . Conventionally, we simply take hyperparameters at the stationary point. We first estimate $\hat{\sigma}_i$:

$$\frac{\partial L_{\text{comp}}}{\partial \sigma_i} = -N \sum_{m=1}^M \frac{\partial \log \sigma_m}{\partial \sigma_i} - \sum_{n=1}^N \sum_{m=1}^M \frac{\partial 1/\sigma_m^2}{\partial \sigma_i} \frac{(y_{n,m} - f_{n,m})^2}{2} = -\frac{N}{\sigma_i} + \frac{1}{\sigma_i^3} \sum_{n=1}^N (y_{n,i} - f_{n,i})^2.$$
(7)

By taking the derivative of zero, we obtain:

$$\frac{\partial L_{\text{comp}}}{\partial \sigma_i} = -\frac{N}{\sigma_i} + \frac{1}{\sigma_i^3} \sum_{n=1}^N (y_{n,i} - f_{n,i})^2 = 0 \Longrightarrow \hat{\sigma}_i^2 = \frac{1}{N} \sum_{n=1}^N (y_{n,i} - f_{n,i})^2. \tag{8}$$

Then we consider K_f . For simplicity, we take the derivative with respect to $Q = K_f^{-1}$:

$$\frac{\partial L_{\text{comp}}}{\partial Q} = -\frac{N}{2} \frac{\partial \log |Q^{-1}|}{\partial Q} - \frac{1}{2} \frac{\partial \text{tr}(F^{\top}K_x^{-1}FQ)}{\partial Q} = \frac{N}{2} \frac{\partial \log |Q|}{\partial Q} - \frac{1}{2}(F^{\top}K_x^{-1}F)^{\top} = \frac{N}{2}Q^{-1} - \frac{1}{2}F^{\top}K_x^{-1}F.$$
(9)

Note that we used the fact that $F^{\top}K_x^{-1}F$ and Q^{-1} are symmetric for the last transformation. By taking the derivative of zero, the following is obtained:

$$\hat{K}_f = \frac{F^\top K_x^{-1} F}{N} \tag{10}$$

 $^{{}^{3}}A$ and *B* must be a squared regular matrix.

Finally, we consider θ . Since we jointly optimize θ and K_f , we can plug in the optimal K_f in Eq. (9) to Eq. (6) and obtain the following:

$$L_{\text{comp}} = -\frac{M}{2} \log |K_x| - \frac{N}{2} \log |K_f| - \frac{1}{2} \text{tr}(F^{\top} K_x^{-1} F K_f^{-1}) + \text{const.}$$

$$= -\frac{M}{2} \log |K_x| - \frac{N}{2} \log \left| \frac{F^{\top} K_x^{-1} F}{N} \right| - \frac{1}{2} \text{tr}(NI_M) + \text{const.}$$

$$= -\frac{M}{2} \log |K_x| - \frac{N}{2} \log |F^{\top} K_x^{-1} F| |N^{-M}| + \text{const.}$$

$$= -\frac{M}{2} \log |K_x| - \frac{N}{2} \log |F^{\top} K_x^{-1} F| + \text{const.}$$
 (11)

Therefore, we need to optimize the following to yield the optimal θ :

$$\hat{\theta} = \underset{\theta}{\operatorname{argmax}} L_{\operatorname{comp}} = \underset{\theta}{\operatorname{argmin}} -2L_{\operatorname{comp}} = \underset{\theta}{\operatorname{argmin}} (M \log |K_x| + N \log |F^{\top} K_x^{-1} F|).$$
(12)

Note that this optimization must be performed numerically by using, for example, L-BFGS as analytical solutions for θ are not available.

- **4.1.3 Overview of EM Algorithm.** Although we derived the update equations for the EM algorithm in the previous section, we cannot directly obtain the solutions due to the missing data, i.e. $f_{1:N}$. Bonilla et al. (2007) proposed to take the expectation of each hyperparameter over $p(f_{1:N}|\boldsymbol{y}_{1:N}, \boldsymbol{\theta}, K_f, \boldsymbol{\Sigma}) = \mathcal{N}(f_{1:N}|K_{xf}(K_{xf} + S)^{-1}\boldsymbol{y}_{1:N}, K_{xf} K_{xf}(K_{xf} + S)^{-1}K_{xf})$. To summarize, we perform the following in the EM algorithm:
 - 1. Sample $\{\tilde{f}_{1:N}^{(k)}\}_{k=1}^{K}$ from $p(f_{1:N}|\boldsymbol{y}_{1:N}, \hat{\boldsymbol{\theta}}^{\text{old}}, \hat{K_f}^{\text{old}}, \hat{\Sigma}^{\text{old}}),$
 - 2. Optimize $\hat{\theta}^{\text{new}} = \operatorname{argmin}_{\theta}(M \log |K_x| + N \log \frac{1}{K} \sum_{k=1}^{K} |(\tilde{F}^{(k)})^\top K_x^{-1} \tilde{F}^{(k)}|)$ where $\tilde{f}_{1:N}^{(k)} = \operatorname{vec}(\tilde{F}^{(k)})$,
 - 3. Resample $\{\tilde{f}_{1:N}^{(k)}\}_{k=1}^{K}$ from $p(f_{1:N}|\boldsymbol{y}_{1:N}, \hat{\boldsymbol{\theta}}^{\text{new}}, \hat{K}_{f}^{\text{old}}, \hat{\Sigma}^{\text{old}}),$
 - 4. Calculate $(\hat{\sigma}_m^{\text{new}})^2 = \frac{1}{NK} \sum_{k=1}^K \sum_{n=1}^N (y_{n,m} f_{n,m}^{(k)})^2$ and $\hat{K}_f^{\text{new}} = \sum_{k=1}^K \frac{(\tilde{F}^{(k)})^\top (K_x^{\text{new}})^{-1} \tilde{F}^{(k)}}{NK}$,
 - 5. Update the hyperparameters $\hat{\theta}^{\text{old}} \leftarrow \hat{\theta}^{\text{new}}, \hat{K_f}^{\text{old}} \leftarrow \hat{K_f}^{\text{new}}, \hat{\Sigma}^{\text{old}} \leftarrow \hat{\Sigma}^{\text{new}}$ and go back to 1.

4.2 Gradient Approach for Multi-Task Gaussian Process

In the previous section, we discussed the EM algorithm for MTGP, which was reported to poorly perform in terms of both the quality of solutions and the convergence speed (Bonilla et al., 2007). This motivated another approach — the approximation of K_f by a gradient-based method. Since this approach can be extended to the case where some outputs are not evaluated at some input vectors, we show the gradients for both cases, but the solutions are, in principle, identical in both cases as both of them are the maximization of the marginal log-likelihood.

4.2.1 Case I: All Outputs Are Evaluated for Every Input Vector (Kronecker Structure). In this case, we maximize the marginal log-likelihood $\mathcal{N}(\boldsymbol{y}_{1:N}|\boldsymbol{0}_{NM}, K_{xf} + S)$ with respect to $\boldsymbol{\theta}, \boldsymbol{\Sigma}$, and K_f . Bonilla et al. (2007) proposed to optimize each element in a lower-triangle matrix $L \in \mathbb{R}^{M \times M}$ so that $K_f = LL^{\top}$ maximizes the marginal log-likelihood.

$$L_{\text{mll}} = \log \mathcal{N}(\boldsymbol{y}_{1:N}|\boldsymbol{0}_{NM}, K_{xf} + S) = \log \frac{1}{(2\pi)^{NM/2} |K_{xf} + S|^{1/2}} \exp\left(-\frac{\boldsymbol{y}_{1:N}^{\top}(K_{xf} + S)^{-1} \boldsymbol{y}_{1:N}}{2}\right)$$

$$= -\frac{1}{2} \log |K_{xf} + S| - \frac{\boldsymbol{y}_{1:N}^{\top}(K_{xf} + S)^{-1} \boldsymbol{y}_{1:N}}{2} + \text{const.}$$
(13)

We now calculate the derivative of the marginal log-likelihood with respect to a parameter $z \in \mathbb{R}$ and then this result generalizes to any other parameters such as θ , *L*, and Σ . The derivative of the first term can be calculated as follows using $\frac{\partial \log |A|}{\partial z} = \operatorname{tr}(A^{-1}\frac{\partial A}{\partial z})$:

$$\frac{\partial \log |K_{xf} + S|}{\partial z} = \operatorname{tr}\left((K_{xf} + S)^{-1} \frac{\partial K_{xf} + S}{\partial z}\right).$$
(14)

The derivative of the second term can be computed using $\frac{\partial \boldsymbol{y}^{\mathsf{T}} A \boldsymbol{y}}{\partial z} = \boldsymbol{y}^{\mathsf{T}} \frac{\partial A}{\partial z} \boldsymbol{y}$ and $\frac{\partial A^{-1}}{\partial z} = -A^{-1} \frac{\partial A}{\partial z} A^{-1}$:

$$\frac{\partial \boldsymbol{y}_{1:N}^{\mathsf{T}}(K_{xf}+S)^{-1}\boldsymbol{y}_{1:N}}{\partial z} = \boldsymbol{y}_{1:N}^{\mathsf{T}} \frac{\partial (K_{xf}+S)^{-1}}{\partial z} \boldsymbol{y}_{1:N} = \boldsymbol{y}_{1:N}^{\mathsf{T}}(K_{xf}+S)^{-1} \frac{\partial K_{xf}+S}{\partial z} (K_{xf}+S)^{-1} \boldsymbol{y}_{1:N}.$$
(15)

Therefore, if we define $G = \frac{\partial K_{xf} + S}{\partial z}$ and $Q = (K_{xf} + S)^{-1}$, the derivative is computed as:

$$\frac{\partial L_{\text{mll}}}{\partial z} = -\frac{1}{2} (\text{tr}(QG) + \boldsymbol{y}_{1:N}^{\top} QGQ \boldsymbol{y}_{1:N}).$$
(16)

Note that the derivatives of each parameter are computed as follows:

$$\frac{\partial K_{xf} + S}{\partial \theta_i} = \frac{\partial K_x}{\partial \theta_i} \otimes I_M,$$

$$\frac{\partial K_{xf} + S}{\partial \sigma_m^2} = I_N \otimes \text{diag}[0, \dots, \underbrace{1}_{m-\text{th element}}, \dots, 0],$$

$$\frac{\partial K_{xf} + S}{\partial L_{i,j}} = I_N \otimes (E_{i,j}L^\top + LE_{j,i}),$$
(17)

where $E_{i,j} \in \mathbb{R}^{M \times M}$ is a matrix that has 0 except at the (i, j)-th element where the element is 1. Note that the derivative with respect to the Cholesky decomposition is calculated as $\frac{\partial K_f}{\partial L_{i,j}} = \frac{\partial LL^{\top}}{\partial L_{i,j}} = \frac{\partial L}{\partial L_{i,j}}L^{\top} + L\frac{\partial L^{\top}}{\partial L_{i,j}} = E_{i,j}L^{\top} + LE_{j,i}$. Although we listed the analytical forms of each derivative, since we can use automatic differentiation provided by PyTorch (Paszke et al., 2019), we do not have to use them explicitly.

4.2.2 Case II: Some Outputs Are Missing for Some Input Vectors. This scenario is inspired by the linear coregionalization model (LCM) (Wackernagel, 2003) and Bonilla et al. (2007) did not discuss the extension, but we can surely extend the gradient-based approach to this setup as well. In this setup, a set of observations on which Gaussian process is trained is different from the previous setups. We are given a set of observations $\{\{(x_n, y_{n,m})\}_{n=1+\sum_{i=1}^{m-1}N_i}^{N_m}\}_{m=1}^M$ and Gaussian process is trained on this dataset where N_m is the number of observations for the *m*-th output. Simply put, some outputs may not be evaluated at some input vectors. Even in this case, the gradient calculation is possible. Let us define $s_m \coloneqq \sum_{i=1}^{m-1} N_i$ where $s_1 = 0$, the (i, j)-th block kernel matrix as:

$$K_{x}^{(i,j)} \coloneqq \begin{bmatrix} k_{\theta}(\boldsymbol{x}_{s_{i}+1}, \boldsymbol{x}_{s_{j}+1}) & \cdots & k_{\theta}(\boldsymbol{x}_{s_{i}+1}, \boldsymbol{x}_{s_{j}+N_{j}}) \\ \vdots & \ddots & \vdots \\ k_{\theta}(\boldsymbol{x}_{s_{i}+N_{i}}, \boldsymbol{x}_{s_{j}+1}) & \cdots & k_{\theta}(\boldsymbol{x}_{s_{i}+N_{i}}, \boldsymbol{x}_{s_{j}+N_{j}}) \end{bmatrix} \in \mathbb{R}^{N_{i} \times N_{j}}.$$
(18)

Then the kernel matrix for the input vectors is defined as:

$$K_{x} := \begin{bmatrix} K_{x}^{(1,1)} & \dots & K_{x}^{(1,M)} \\ \vdots & \ddots & \vdots \\ K_{x}^{(M,1)} & \dots & K_{x}^{(M,M)} \end{bmatrix} \in \mathbb{R}^{s_{M} \times s_{M}}.$$
 (19)

Using Khatri-Rao product, the covariance matrix of the prior is computed as:

$$K_{x} * K_{f} + I_{s_{M}} * \Sigma = \begin{bmatrix} \sigma_{1}^{2} I_{N_{1}} + K_{x}^{(1,1)} (K_{f})_{1,1} & \cdots & K_{x}^{(1,M)} (K_{f})_{1,M} \\ \vdots & \ddots & \vdots \\ K_{x}^{(M,1)} (K_{f})_{M,1} & \cdots & \sigma_{M}^{2} I_{N_{M}} + K_{x}^{(M,M)} (K_{f})_{M,M} \end{bmatrix} \in \mathbb{R}^{s_{M} \times s_{M}}$$
(20)

where I_{s_M} is partitioned in the same submatrix sizes as K_x , $K_x * K_f = (K_x^{(i,j)} \otimes (K_f)_{i,j})_{i,j}$ is Khatri-Rao product. Note that Eq. (20) can also be expressed as follows:

$$K_x * K_f + I_{s_M} * \Sigma = P^\top (K_{xf} + S)P$$
(21)

where $P \in \mathbb{R}^{N \times s_M}$ is a matrix that is created from an identity matrix I_N by removing the columns where $\mathbf{y}_{1:N}$ does not exist. In the NumPy style, we could write it as P = np.eye(N * M)[:, ~np.isnan(Y.flatten())] where missing values in Y are assumed to be padded by np.nan. By doing so, the mathematical form of the gradient becomes very straightforward using Eq. (17) because the following holds:

$$\frac{\partial K_x * K_f + I_{s_M} * \Sigma}{\partial z} = \frac{\partial P^\top (K_{xf} + S)P}{\partial z} = P^\top \frac{\partial K_{xf} + S}{\partial z}P.$$
(22)

As mentioned by Lin et al. (2024), the matrix multiplication with P is simply a slicing operation and we do not actually have to explicitly instantiate P.

5 Practical Consideration

As mentioned by Bonilla et al. (2007), the gradient approach, cf. Section 4.2, is practical in terms of both convergence speed and predictive accuracy, especially because automatic differentiation is accessible thanks to PyTorch (Paszke et al., 2019) and the gradients do not have to be calculated explicitly. Talking about the time complexity, a naïve implementation for optimizing the marginal log-likelihood in Eq. (13) with respect to kernel hyperparameters has the time complexity of $O(N^3M^3)$ and the memory complexity of $O(N^2M^2)$ due to the inverse calculation of K_{xf} + S. On the other hand, Stegle et al. (2011), cf. Section 2.1, demonstrated that the time complexity and the memory complexity can be improved to $O(N^3 + M^3)$ and $(N^2 + M^2)$ by exploiting the Kronecker structure discussed in Section 4.2.1 and the eigenvalue decompositions of K_x and K_f separately. Lin et al. (2024) further extended this improvement to the case for non-Kronecker structure discussed in Section 4.2.2. If additional speedup is necessary, we can use the Nyström approximation (Williams and Seeger, 2000), which uses $K \simeq K_{\mathcal{I},\mathcal{I}} K_{\mathcal{I},\mathcal{I}}^{-1} K_{\mathcal{I},\cdot}$ where $\mathcal{I} \subseteq \{1, \ldots, N\}$ is a subset of indices ⁴, and PPCA (Tipping and Bishop, 1999), which uses $K \simeq U\Lambda U^{\top} + s^2 I_N$ where $U\Lambda U^{\top}$ is the eigendecomposition of K and s² can be analytically determined from the eigenvalues according to Tipping and Bishop (1999). Note that BoTorch (Balandat et al., 2020) uses $K_f \simeq \tilde{L}\tilde{L}^{\top} + \text{diag}[v_1, \dots, v_M]$ where \tilde{L} is a low-rank approximation of the Cholesky decomposition and both $\tilde{L} \in \mathbb{R}^{M \times M'}(M' \leq M)$ and $[v_1, \ldots, v_M]$ are learned via the gradient approach ⁵.

We now discuss more specific applications. For Multi-objective optimization and constrained optimization, we can typically assume that the training dataset has the Kronecker structure, so the gradient approach from Section 4.2.1 can be simply applied. For multi-fidelity optimization, although many missing data points are expected due to early stopping, many data points are still evaluated at the same input vectors. That is why the gradient approach from Section 4.2.2 would be beneficial. Additionally, Swersky et al. (2013) optimized each element of the Cholesky decomposition in the log space and then exponentiated back after the optimization. This trick benefitted

⁴Typically, the subset is randomly chosen.

⁵By default, BoTorch uses no approximation, i.e. M' = M.

them because it is reasonable to assume a positive correlation between the outputs in multi-fidelity optimization. For meta-learning, since it is not uncommon to have no shared input vectors among each task, it would be helpful to use approximation methods such as the Nyström approximation.

With that being said, if many evaluations are expected during an optimization, we should consider using a light-weight BO method such as TPE extensions instead of GPBO such as MOTPE (Ozaki et al., 2020, 2022) for multi-objective optimization, (Watanabe and Hutter, 2022, 2023) for constrained optimization, (Falkner et al., 2018) for multi-fidelity optimization, (Watanabe et al., 2022, 2023) for meta-learning.

6 Conclusion

In this paper, we showed the detailed derivations of the intermediate processes for MTGP. We hope that our derivations help practitioners verify their codes and will be a helpful reference for researchers in the future.

References

- Alvarez, M. and Lawrence, N. (2008). Sparse convolved Gaussian processes for multi-output regression. Advances in Neural Information Processing Systems.
- Balandat, M., Karrer, B., Jiang, D., Daulton, S., Letham, B., Wilson, A., and Bakshy, E. (2020). BoTorch: A Framework for Efficient Monte-Carlo Bayesian Optimization. In Advances in Neural Information Processing Systems.
- Bergstra, J., Bardenet, R., Bengio, Y., and Kégl, B. (2011). Algorithms for hyper-parameter optimization. Advances in Neural Information Processing Systems.
- Bonilla, E., Chai, K., and Williams, C. (2007). Multi-task Gaussian process prediction. Advances in neural information processing systems.
- Brochu, E., Cora, V., and de Freitas, N. (2010). A tutorial on Bayesian optimization of expensive cost functions, with application to active user modeling and hierarchical reinforcement learning. *arXiv*:1012.2599.
- Daulton, S., Balandat, M., and Bakshy, E. (2020). Differentiable expected hypervolume improvement for parallel multi-objective Bayesian optimization. *Advances in Neural Information Processing Systems*.
- Daulton, S., Eriksson, D., Balandat, M., and Bakshy, E. (2022). Multi-objective Bayesian optimization over high-dimensional search spaces. In *Uncertainty in Artificial Intelligence*.
- Eriksson, D. and Poloczek, M. (2021). Scalable constrained Bayesian optimization. In *International Conference on Artificial Intelligence and Statistics*.
- Falkner, S., Klein, A., and Hutter, F. (2018). BOHB: Robust and efficient hyperparameter optimization at scale. In *International Conference on Machine Learning*.
- Feurer, M., Letham, B., Hutter, F., and Bakshy, E. (2018). Practical transfer learning for Bayesian optimization. *arXiv:1802.02219*.
- Gardner, J., Kusner, M., Xu, Z., Weinberger, K., and Cunningham, J. (2014). Bayesian optimization with inequality constraints. In *International Conference on Machine Learning*.
- Garnett, R. (2022). Bayesian Optimization. Cambridge University Press.
- Gelbart, M., Snoek, J., and Adams, R. (2014). Bayesian optimization with unknown constraints. *arXiv:1403.5607*.
- Kandasamy, K., Dasarathy, G., Oliva, J., Schneider, J., and Poczos, B. (2019). Multi-fidelity Gaussian process bandit optimisation. *Journal of Artificial Intelligence Research*, 66.
- Kandasamy, K., Dasarathy, G., Schneider, J., and Póczos, B. (2017). Multi-fidelity Bayesian optimisation with continuous approximations. In *International Conference on Machine Learning*.
- Lin, J., Ament, S., Balandat, M., and Bakshy, E. (2024). Scaling Gaussian processes for learning curve prediction via latent Kronecker structure. *arXiv:2410.09239*.
- Lindauer, M., Eggensperger, K., Feurer, M., Biedenkapp, A., Deng, D., Benjamins, C., Ruhkopf, T., Sass, R., and Hutter, F. (2022). SMAC3: A versatile Bayesian optimization package for hyperparameter optimization. *Journal of Machine Learning Research*, 23.

McLachlan, J. and Krishnan, T. (2008). The EM algorithm and extensions. John Wiley & Sons.

- Nguyen, T., Bonilla, E., et al. (2014). Collaborative multi-output Gaussian processes. In *Uncertainty in Artificial Intelligence*.
- Ozaki, Y., Tanigaki, Y., Watanabe, S., Nomura, M., and Onishi, M. (2022). Multiobjective treestructured Parzen estimator. *Journal of Artificial Intelligence Research*, 73.
- Ozaki, Y., Tanigaki, Y., Watanabe, S., and Onishi, M. (2020). Multiobjective tree-structured Parzen estimator for computationally expensive optimization problems. In *Genetic and Evolutionary Computation Conference*.
- Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z., Gimelshein, N., Antiga, L., et al. (2019). PyTorch: An imperative style, high-performance deep learning library. Advances in neural information processing systems.
- Shahriari, B., Swersky, K., Wang, Z., Adams, R., and de Freitas, N. (2016). Taking the human out of the loop: A review of Bayesian optimization. *Proceedings of the IEEE*, 104.
- Song, J., Chen, Y., and Yue, Y. (2019). A general framework for multi-fidelity Bayesian optimization with Gaussian processes. In *International Conference on Artificial Intelligence and Statistics*.
- Stegle, O., Lippert, C., Mooij, J., Lawrence, N., and Borgwardt, K. (2011). Efficient inference in matrix-variate Gaussian models with iid observation noise. Advances in Neural Information Processing Systems.
- Swersky, K., Snoek, J., and Adams, R. (2013). Multi-task Bayesian optimization. In Advances in Neural Information Processing Systems.
- Tipping, M. and Bishop, C. (1999). Probabilistic principal component analysis. *Journal of the Royal Statistical Society Series B: Statistical Methodology*, 61.
- Titsias, M. (2009). Variational learning of inducing variables in sparse Gaussian processes. In *Artificial Intelligence and Statistics*.
- Wackernagel, H. (2003). *Multivariate geostatistics: an introduction with applications*. Springer Science & Business Media.
- Watanabe, S. (2023). Tree-structured Parzen estimator: Understanding its algorithm components and their roles for better empirical performance. *arXiv:2304.11127*.
- Watanabe, S., Awad, N., Onishi, M., and Hutter, F. (2022). Multi-objective tree-structured Parzen estimator meets meta-learning. arXiv:2212.06751.
- Watanabe, S., Awad, N., Onishi, M., and Hutter, F. (2023). Speeding up multi-objective hyperparameter optimization by task similarity-based meta-learning for the tree-structured Parzen estimator. *arXiv:2212.06751*.
- Watanabe, S. and Hutter, F. (2022). c-TPE: Generalizing tree-structured Parzen estimator with inequality constraints for continuous and categorical hyperparameter optimization. *arXiv:2211.14411*.
- Watanabe, S. and Hutter, F. (2023). c-TPE: Tree-structured Parzen estimator with inequality constraints for expensive hyperparameter optimization. *arXiv:2211.14411*.

- Williams, C. and Seeger, M. (2000). Using the Nyström method to speed up kernel machines. *Advances in Neural Information Processing Systems*.
- Wilson, A., Knowles, D., and Ghahramani, Z. (2011). Gaussian process regression networks. *arXiv:1110.4411*.
- Wistuba, M., Kadra, A., and Grabocka, J. (2022). Supervising the multi-fidelity race of hyperparameter configurations. *Advances in Neural Information Processing Systems*.
- Yang, K., Emmerich, M., Deutz, A., and Bäck, T. (2019). Multi-objective Bayesian global optimization using expected hypervolume improvement gradient. *Swarm and evolutionary computation*, 44.

A Proofs

A.1 Proof of Theorem 1

Proof 1 We first calculate the right hand side. The matrix multiplication can be easily computed as follows:

$$(AC)_{i,j} = \sum_{k=1}^{N} A_{i,k} C_{k,j} \in \mathbb{R}^{N \times M}, (B^{\top} C^{\top})_{i,j} = \sum_{k=1}^{M} B_{k,i} C_{j,k} \in \mathbb{R}^{M \times N}.$$
 (23)

Therefore, we yield:

$$(ACB^{\top}C^{\top})_{i,j} = \sum_{k=1}^{M} (AC)_{i,k} (B^{\top}C^{\top})_{k,j} = \sum_{p=1}^{M} \sum_{q=1}^{N} \sum_{r=1}^{M} A_{i,q}C_{q,p}B_{r,p}C_{j,r},$$

$$RHS = tr(ACB^{\top}C^{\top}) = \sum_{k=1}^{N} (ACB^{\top}C^{\top})_{k,k} = \sum_{k=1}^{N} \sum_{p=1}^{M} \sum_{q=1}^{N} \sum_{r=1}^{M} A_{k,q}C_{q,p}B_{r,p}C_{k,r}.$$
(24)

We now consider the (i, j)-th block of $A \otimes B$ in the left hand side, i.e. $A_{i,j}B[C_{j,1}, \ldots, C_{j,M}]^{\top}$. Then we obtain $\sum_{p=1}^{M} A_{i,j}B_{r,p}C_{j,p}$ at the r-th row. Since we are taking the inner product, we need to sum up the r-th row elements in the (i, j)-th blocks for $j \in \{1, \ldots, N\}$, leading to $\sum_{j=1}^{N} \sum_{p=1}^{M} A_{i,j}B_{r,p}C_{j,p}$. By considering the summation over the rows $(r \in \{1, \ldots, M\})$ in the i-th blocks of $\sum_{j=1}^{N} \sum_{p=1}^{M} A_{i,j}B_{r,p}C_{j,p}$ and vec(C), we yield $\sum_{j=1}^{N} \sum_{p=1}^{M} \sum_{r=1}^{M} C_{i,r}A_{i,j}B_{r,p}C_{j,p}$ at the i-th block. By adding up from i = 1 to N, we obtain:

$$RHS = \sum_{i=1}^{N} \sum_{j=1}^{N} \sum_{p=1}^{M} \sum_{r=1}^{M} C_{i,r} A_{i,j} B_{r,p} C_{j,p}$$
$$= \sum_{k=1}^{N} \sum_{q=1}^{N} \sum_{p=1}^{M} \sum_{r=1}^{M} A_{k,q} C_{q,p} B_{r,p} C_{k,r} = LHS.$$
(25)

This completes the proof.

A.2 Proof of Theorem 2

Proof 2 We calculate both hand sides, respectively:

LHS =
$$\sum_{n=1}^{N} \sum_{m=1}^{M} C_{n,m} D_{m,n}$$
, RHS = $\sum_{m=1}^{M} \sum_{n=1}^{N} D_{m,n} C_{n,m}$ (26)

Since the results of the left and right hand sides match, this completes the proof.