

# A note on the construction of augmented designs in square arrays

E.R. WILLIAMS<sup>1</sup> and H-P. PIEPHO<sup>2</sup>

<sup>1</sup>Statistical Support Network, Australian National University, Canberra, Australia

<sup>2</sup>Biostatistics Unit, Institute of Crop Science, University of Hohenheim, Stuttgart, Germany

## Abstract

An augmented design in a square array can be derived from a smaller row-column design (the contraction). Such a contraction has also previously been used to generate a two-replicate resolvable incomplete block design. We demonstrate a parallel between these two uses of the contraction and thereby establish a recently proposed conjecture by linking the average efficiency factor of the augmented design with that of its contraction.

**Key Words:** augmented design; average efficiency factor; contraction; square array design; two-replicate resolvable design

**Author for correspondence:** Emlyn Williams, E-mail: [emlyn@alphastat.net](mailto:emlyn@alphastat.net).

## 1. INTRODUCTION

In plant breeding programs, a large number of entries usually need to be tested in early generations. Typically, the amount of seed available per entry is sufficient for only a single plot. In this situation, estimating an error variance and allowing for local adjustments by blocking can be accommodated by allocating a certain fraction of plots to check varieties (Kempton, 1984). One way to generate a design with unreplicated entries and replicated checks is to employ a blocked design for the replicated check varieties and augment these blocks with unreplicated test lines. Such designs were first proposed by Federer (1956, 1961) under the label augmented designs. Randomizing entries and checks within each augmented block provides a valid estimate of the error variance and permits adjustments for block effects based on a linear model.

More recently Piepho and Williams (2016) and Vo-Thanh and Piepho (2020) provided methods for the construction of augmented designs in a two-way arrangement of plots and gave references to earlier work. In order to allow for the prospect of both row and column adjustment, it is important that there are adequate numbers of replicated checks to provide

error degrees of freedom for the comparison of entries. This can require around 15 – 20% of plots being assigned to checks. An alternative is to replicate some of the entries to generate error degrees of freedom; such designs are called partially replicated (p-rep) designs (Cullis *et al.*, 2006). It is then usual to still include a smaller number of replicated checks in the p-rep design; this can have the advantage of allowing a comparison of new material with established checks (Williams *et al.*, 2024, section 7.7).

Recently Bailey and Haines (2024) investigated the construction of augmented designs in square arrays from smaller auxiliary designs (contractions). They conjecture a link between the average pairwise variance of the augmented design and its contraction. Here we establish this link using results from Patterson and Williams (1976). It follows from this link that to obtain an optimal square array augmented design, one should use an optimal contraction.

## 2. CONSTRUCTION

We start with a row-column design for  $v$  treatments in  $v$  columns and  $k$  rows. This design is denoted as the contraction, from which an augmented design will be generated. Federer and Raghavarao (1975) explain how by switching the roles of the  $k$  rows and  $v$  treatments in the contraction we can generate the positions of  $k$  check varieties in the  $v \times v$  augmented design. The remaining  $v(v - k)$  cells can be filled with unreplicated test entries.

**Example 1.** Suppose for  $v = 5$  and  $k = 3$ , the contraction is given by the row-column design:

		Column				
		1	2	3	4	5
Row	A	2	4	5	1	3
	B	5	3	2	4	1
	C	1	2	3	5	4

Switching the roles of the  $k$  rows and  $v$  treatments means that the row labels A, B and C in the contraction become the labels for the checks in the augmented design, and the treatment labels in the contraction become the row positions of the checks. This conversion is applied separately for each column of the contraction, leading to the following location of the check varieties A, B and C in the augmented design, which by construction has the same number of columns as the contraction:

		Column				
		1	2	3	4	5
Row	1	C			A	B
	2	A	C	B		
	3		B	C		A
	4		A		B	C
	5	B		A	C	

The blank spaces are then randomly filled with the single replicates of 10 test entries to complete the augmented design.

Patterson and Williams (1976) used methodology to demonstrate how a  $k \times v$  contraction can be used to construct a two-replicate resolvable incomplete block design for  $vk$  treatments with  $v$  blocks of size  $k$  in each replicate. They showed that there is a link between the average efficiency factor of the contraction ( $E_{con}$ ) and that for the resolvable design, where the average efficiency factor of an incomplete block design is defined as the harmonic mean of the canonical efficiency factors (John and Williams, 1995, section 2.3). In particular, Patterson and Williams (1976) derived the relationship

$$E_{res} = \frac{(vk - 1)}{(vk - 2v + 1) + 4(v - 1)/E_{con}} \quad (1)$$

where  $E_{res}$  is the average efficiency factor of the resolvable design. John and Williams (1995, section 4.7) provided more detail on the construction process. Note that although the contraction for both the resolvable and augmented designs has been specified as a row-column design, the rows comprise a complete replicate of the treatments and hence the average efficiency factor of the row-column contraction is the same as that just considering the columns as incomplete blocks.

In a similar vein the Patterson and Williams (1976) theory can also be used to derive the following link between the average efficiency factor for the augmented design ( $E_{aug}$ ) and that for the contraction:

$$E_{aug} = \frac{(v^* - 1)}{(v^* - 2v + 1) + 2v(v - 1)/(kE_{con})} \quad (2)$$

where  $v^* = v \times v - k \times (v - 1)$  is the total number of treatments in the augmented design. A derivation of (2) is provided in the Appendix.

Expression (2) defines the average efficiency factor for the whole design, including the check varieties. But because these are orthogonal to both rows and columns in the augmented

design with average efficiency factor of one, we can simply subtract the quantity  $k$  from numerator and denominator to obtain the average efficiency factor ( $E_{test}$ ) of the test entries, i.e.

$$E_{test} = \frac{(v^* - 1) - k}{(v^* - 2v + 1) - k + 2v(v - 1)/(kE_{con})}$$

Furthermore the average pairwise variance for the singly-replicated test entries ( $A_{test}$ ) is given by  $A_{test} = 2/E_{test}$ , e.g. see Williams and Piepho (2015) equation (3). Hence this establishes the Conjecture of Bailey and Haines (2024).

**Example 2.** Bailey and Haines (2024, Example 5.1) discuss a contraction for 12 treatments in 12 incomplete blocks of size 3. This is an optimal incomplete block design with  $E_{con} = 0.68006$  thus giving  $A_{test} = 4.0075$ , which agrees with the result in their Table 7.

### 3. DISCUSSION

An important consequence of (2) is that the best augmented design in a square array will be obtained from the best available contraction. In some cases, optimal contractions can be obtained from existing construction methods, for example cyclic designs, as discussed by Bailey and Haines (2024). But for many combinations of  $v$  and  $k$ , this is not the case, e.g. Example 2. There are, of course, a wide range of different construction methods available for the production of optimal contractions. But in addition, it is often worthwhile to use computer design generation packages such as CycDesigN (VSNi, 2024), especially as the contractions of practical interest for the generation of such augmented designs are likely to be quite small. Hence the powerful computers and algorithms of today can often produce optimal designs very quickly, as can be indicated by tight upper bounds on the average efficiency factor (John and Williams, 1995, section 2.8).

Finally, a topic of further research could be an investigation of whether the idea of contractions can also be used for augmented designs in rectangular arrays of plots; and even whether the construction of efficient p-rep designs including check varieties can also be produced.

## REFERENCES

- Bailey, R. A. and Haines, L. M. (2024) The square array design.  
<https://doi.org/10.48550/arXiv.2412.09166>
- Cullis, B. R., Smith, A. and Coombes, N. (2006) On the design of early generation variety trials with correlated data. *Journal of Agricultural, Biological and Environmental Statistics* **11**, 381-393.
- Federer, W. T. (1956) Augmented (or hoonuiaku) designs. *Hawaiian Sugar Planters Record* **55** (2), 191-208.
- Federer, W. T. (1961) Augmented designs with one-way elimination of heterogeneity. *Biometrics* **17**, 447-473.
- Federer, W. T. and Raghavarao, D. (1975) On augmented designs. *Biometrics* **31**, 29-35
- John, J. A. and Williams, E. R. (1995) *Cyclic and computer generated designs* (2nd ed.). London, UK: Chapman and Hall.
- Kempton, R. A. (1984) The design and analysis of unreplicated field trials. *Vorträge für Pflanzenzüchtung* **7**, 219-242.
- Patterson, H. D. and Williams, E. R. (1976) Some theoretical results on general block designs. *Proceedings of the 5<sup>th</sup> Combinatorial Conference. Congressus Numerantium* **XV** 489-496.
- Piepho, H. P. and Williams, E. R. (2016) Augmented row-column designs for a small number of checks. *Agronomy Journal* **108**, 2256-62.
- Vo-Thanh, N. and Piepho, H. P. (2020) Augmented quasi-sudoku designs in field trials. *Computational Statistics and Data Analysis* **150**, 106988.
- VSNI (2024) CycDesigN, Version 8.0, <http://www.vsni.co.uk/software/cycdesign/>
- Williams, E. R., Harwood, C. E. and Matheson, A. C. (2024) *Experimental design and analysis for tree improvement* (3<sup>rd</sup> ed.) CSIRO Publishing, Collingwood.
- Williams, E. R. and Piepho, H. P. (2015) Optimality and contrasts in block designs with unequal treatment replication. *Australian and New Zealand Journal of Statistics* **57**, 203-209.

## APPENDIX

### Derivation of equation (2)

We approach the derivation by using Example 1 to demonstrate a link between the two-replicate resolvable design and the augmented design, both of which are developed from the

associated contraction. We can then use the theory in Patterson and Williams (1976) to derive the result.

For the contraction in Example 1, the corresponding two-replicate resolvable design for 15 treatments with 5 incomplete blocks of size 3 in each replicate, is given by:

Replicate 1				
1	2	3	4	5
1	2	3	4	5
6	7	8	9	10
11	12	13	14	15

Replicate 2				
1	2	3	4	5
2	4	5	1	3
10	8	7	9	6
11	12	13	15	14

with treatment by block incidence matrices of

	1	2	3	4	5
1	1				
2		1			
3			1		
4				1	
5					1
6	1				
7		1			
8			1		
9				1	
10					1
11	1				
12		1			
13			1		
14				1	
15					1

$N_1$

	1	2	3	4	5
1				1	
2	1				
3					1
4		1			
5			1		
6					1
7			1		
8		1			
9				1	
10	1				
11	1				
12		1			
13			1		
14					1
15				1	

$N_2$

respectively for the two replicates. Thus we have  $N_1'N_2$  as

1			1	1
1	1	1		
	1	1		1
	1		1	1
1		1	1	

which is the incidence matrix for the contraction, thus leading to equation (1) for the average efficiency factor for the two-replicate resolvable design (Patterson and Williams, 1976, section 7).

In a similar vein after switching the roles of treatments and rows in the contraction we can derive matrices relating to the augmented design as

	1	2	3	4	5
1	A				
2		A			
3			A		
4				A	
5					A
6	B				
7		B			
8			B		
9				B	
10					B
11	C				
12		C			
13			C		
14				C	
15					C

$M_1$

	1	2	3	4	5
1				A	
2	A				
3					A
4		A			
5			A		
6					B
7			B		
8		B			
9				B	
10	B				
11	C				
12		C			
13			C		
14					C
15				C	

$M_2$

so suggesting  $M_1' M_2$  as

C			A	B
A	C	B		
	B	C		A
	A		B	C
B		A	C	

which is then the augmented design. Thus it follows that we can use the theory in Patterson and Williams (1976) and substitute  $N_1' N_2$  into their equation 7.2 which then provides the link between the eigenvalues of the contraction and the non-unit eigen-values of the augmented design. In particular, the  $(v - 1)$  non-zero eigenvalues of the contraction provide  $(v - 1)$  pairs of eigenvalues for the augmented design. Then by adding in the  $v^* - 2v + 1$  unit eigenvalues (linked to the test entries) and scaling  $E_{con}$  by  $v/k$  resulting from switching the roles of treatments and rows in the contraction, we obtain the result.