

# Chain-of-Reasoning: Towards Unified Mathematical Reasoning in Large Language Models via a Multi-Paradigm Perspective

Yiyao Yu<sup>1\*</sup> Yuxiang Zhang<sup>1\*</sup> Dongdong Zhang<sup>2†</sup> Xiao Liang<sup>1</sup> **Xingxing Zhang**<sup>2</sup> Ziyi Yang<sup>2</sup> Mahmoud Khademi<sup>2</sup> Hengyuan Zhang<sup>1</sup> Hany Awadalla<sup>2</sup> Junjie Wang<sup>1†</sup> Yujiu Yang<sup>1†</sup> Furu Wei<sup>2</sup> <sup>2</sup>Microsoft <sup>1</sup>Tsinghua University yuyy23@mails.tsinghua.edu.cn, joel1070408@gmail.com

{dozhang,xizhang,ziyiyang,mkhademi,hanyh,fuwei}@microsoft.com

### Abstract

Large Language Models (LLMs) have made notable progress in mathematical reasoning, yet they often rely on single-paradigm reasoning that limits their effectiveness across diverse tasks. In this paper, we introduce Chain-of-Reasoning (CoR), a novel unified framework that integrates multiple reasoning paradigms—Natural Language Reasoning (NLR), Algorithmic Reasoning (AR), and Symbolic Reasoning (SR)—to enable synergistic collaboration. CoR generates multiple potential answers using different reasoning paradigms and synthesizes them into a coherent final solution. We propose a Progressive Paradigm Training (PPT) strategy that allows models to progressively master these paradigms, culminating in the development of CoR-Math-7B. Experimental results demonstrate that CoR-Math-7B significantly outperforms current SOTA models, achieving up to a 41.0% absolute improvement over GPT-4 in theorem proving tasks and a 7.9% improvement over RL-based methods in arithmetic tasks. These results showcase the enhanced mathematical comprehensive ability of our model, achieving significant performance gains on specific tasks and enabling zero-shot generalization across tasks.



Figure 1: A comprehensive comparative analysis of CoR-Math-7B and baseline models across challenging mathematical tasks. (a) demonstrates the effectiveness of CoR-Math-7B (zero-shot) in theorem proving tasks, specifically emphasizing its advantage over baseline and their fine-tuned variants over SFT and RL. (b) shows a resource-efficiency analysis for arithmetic computation tasks, plotting model performance vs. SFT data size, in which CoR-Math-7B attains the optimal resource efficiency, achieving near-optimal zero-shot performance.

<sup>\*</sup>Equal contribution. Yiyao Yu did this work during the internship at Microsoft Research. Yuxiang Zhang did this work as a research assistant at Tsinghua University.

<sup>&</sup>lt;sup>†</sup>Corresponding Author.



Figure 2: The reasoning process under different paradigms: (a) In single-paradigm reasoning, each reasoning step relies on the same knowledge medium, such as Natural Language (NL), algorithms, or symbols. (b) In tool-integrated single-paradigm, NL is used for reasoning, while code assists in solving specific sub-problems. After obtaining the execution results, the reasoning continues using NL. (c) The proposed CoR reasoning framework, along with several examples, shows that multi-paradigm reasoning allows for varying reasoning depths to address different types of problems.

# 1 Introduction

While LLMs have demonstrated strong performance in solving mathematical tasks [Feigenbaum et al., 1963, Hosseini et al., 2014], advanced open-source reasoners still struggle with solving comprehensive mathematical problems, including both arithmetic computation and theorem proving.

Existing works [Xin et al., 2024, Yang et al., 2024, Wu et al., 2024] are often trained on specific tasks, aiming to enhance their ability to independently derive answer based on specific structured knowledge representation. This representation is known as the reasoning paradigm, involving Natural Language Reasoning (NLR), Algorithmic Reasoning (AR), and Symbolic Reasoning (SR), as illustrated in Figure 2 (a). Specifically, NLR leverages natural language text for reasoning based on human common sense and semantic context, with explicit step-by-step natural language explanations [Wei et al., 2022]. AR leverages code to focus on the computer's operations and execution process, performing inference on the final target, such as the generation of Python code for compilation [Chen et al., 2023, Gao et al., 2023] to obtain the final answer. SR utilizes logical symbols and axiomatic systems as the fundamental tools for rigorously formalized reasoning, with current methods [Xin et al., 2024, Huang et al., 2024, Wu et al., 2024] considering numerous symbolic trajectories through a tree-based search process for theorem proving. However, these methods focus on improving single-paradigm reasoning and overlook the potential of collaboration among multiple paradigms, which restricts their single-task performance and hinders their cross-task generalization.

Researchers have explored various strategies to tackle these challenges. To improve the single-task performance, some works have explored integrating tools to overcome the limitations of single-paradigm reasoning [Gou et al., 2024, LI et al., 2024], as shown in Figure 2 (b). These methods combine natural language with code-based algorithms (tools) to enable interleaved reasoning and generate a final answer. Although these methods acknowledge the potential benefits of integrating different reasoning paradigms, they often rely on a single paradigm to complete the reasoning process. They overlook the possibility that the second paradigm could independently complete the reasoning, thereby constraining its overall potential. Besides, in an effort to overcome the challenge of achieving cross-task generalization, several studies [Shao et al., 2024, Huang et al., 2024] incorporate data samples from diverse task types into large-scale training datasets, such as those drawn from theorem proving tasks that focus exclusively on SR solutions, or from arithmetic problems that emphasize NLR solutions. Although models trained on such data are capable of cross-task reasoning, they still rely on demonstrations for effective transfer.

To address these limitations, we propose a novel unified reasoning framework, Chain-of-Reasoning (CoR), which chains NLR, AR, and SR together to generate synergistic benefits. As illustrated in Figure 2 (c), CoR enables multi-paradigm reasoning for a given problem, which applies different

reasoning paradigms to derive multiple potential answers and are then summarized into a final answer. The framework allows the model to continue reasoning using additional paradigms based on previously generated ones, facilitating collaboration among paradigms to enhance individual task performance. Moreover, CoR implements unified multi-paradigm reasoning across different tasks to obtain the required answers, thereby achieving zero-shot reasoning across tasks. In detail, by adjusting the prompts, the depth of reasoning can be varied, which improves the model's adaptability to diverse tasks. By constructing such multi-paradigm reasoning paths, we create a training dataset named MPM, comprising 167k reasoning paths. Furthermore, we propose a novel Progressive Paradigm Training (PPT) approach, which enables models to progressively master multiple reasoning paradigms, resulting in CoR-Math-7B.

We evaluated CoR-Math-7B on three representative and challenging mathematical reasoning benchmarks that effectively demonstrate comprehensive reasoning capabilities, encompassing both arithmetic computation and theorem proving. These benchmarks include MATH [Hendrycks et al., 2021], GSM8k [Cobbe et al., 2021], and MiniF2F [Zheng et al., 2022]. Our results show that LLMs equipped with CoR significantly outperform current SOTA baselines. In the theorem proving task as shown in Figure 1 (a), CoR-Math-7B surpasses GPT-4o's [Hurst et al., 2024] zero-shot performance by a remarkable absolute 41.0% and outperforms all other few-shot reasoners. In arithmetic tasks, our CoR-Math-7B first performs NLR and SR as a rehearsal, which enhances the accuracy of AR and demonstrates the effectiveness of synergy. For example, CoR-Math-7B achieves an absolute improvement of 7.9% over Reinforcement Learning (RL) methods [Shao et al., 2024] that utilize the same base model on the MATH dataset. Furthermore, as shown in Figure 1 (b), CoR-Math-7B efficiently utilizes resources to surpass the optimal performance curve of single-paradigm approaches. Compared to mainstream methods that perform extensive searches within a single paradigm, our CoR framework achieves better results by extending test-time inference across multiple paradigm spaces. These results show that our method achieves comprehensive mathematical problem solving abilities though multi-paradigm reasoning, requiring fewer training data and reducing reasoning costs.

### 2 Related Work

**Reasoning Paradigms in LLMs.** Recent advancements in LLMs have primarily concentrated on enhancing single-paradigm reasoning, where each paradigm serves as a distinct medium for knowledge representation and logical inference. NLR utilizes human-readable language to solve commonsense reasoning and step-by-step deductions [Wei et al., 2022, Yao et al., 2023, Zhou et al., 2023, Besta et al., 2024, Sel et al., 2024]. For precise numerical computations, AR is to generate executable code, such as Python scripts, to perform accurate calculations through execution [Chen et al., 2023, Rozière et al., 2023]. In the realm of theorem proving, SR leverages logical symbols and axiomatic systems to ensure rigorous and verifiable proofs [Xin et al., 2024]. Furthermore, some approaches leverage external tools within the single-paradigm to enhance reasoning capabilities [Gou et al., 2024], such as using calculators or code interpreters, while maintaining the core reasoning process within a single paradigm. While these paradigms excel within their specific areas, they often struggle with cross-domain generalization and dynamic environments. To address these issues, the CoR framework facilitates collaboration between various reasoning paradigms to enable zero-shot multitasking generalization.

**Mathematical Problem Solving with LLMs.** Advanced research demonstrates the significant potential of LLMs in solving mathematical problems [Zhu et al., 2023]. Several studies have developed unified mathematical solvers by synthesizing mathematical data, capable of addressing various challenges such as arithmetic calculations and theorem proving [Huang et al., 2024, Shao et al., 2024]. However, recent research tends to focus on optimizing single paradigms. For instance, in the field of arithmetic computation, there is a tendency to incorporate programming tools to aid natural language mathematical reasoning [Gou et al., 2024]. In theorem proving, researchers not only utilize specialized annotated data, including pre-training data and reinforcement learning reward data, but also employ tree-based search methods to generate numerous possible solutions [Ying et al., 2024b, Xin et al., 2024]. These methods either fail to fully consider the importance of complete reasoning or rely heavily on large-scale search within the solution space to fully explore the performance improvement potential of a single paradigm. To address these issues, we introduce the MPM dataset and present the CoR-Math-7B model, trained on it, which leverages the synergistic effects of multiparadigm reasoning to navigate towards the optimal solution within the expanded multi-paradigm solution space.



Figure 3: An overview of (a) the Multi-Paradigm Math (MPM) dataset construction process, involving reconstruction, extension, and theorem prover verification, and (b) the Progressive Paradigm Training (PPT) method, where the model is trained with increasing reasoning paradigms in stages.

### **3** Chain-of-Reasoning Framework

### 3.1 Overview

Our CoR framework aims to enable LLMs to perform a series of multi-paradigm reasoning on any type of mathematical problem, ultimately arriving at a solution. Specifically, given a mathematical problem x, LLMs ( $\mathbb{P}$ ) can infer the result y by following multiple reasoning paradigms, where each reasoning paradigm  $\tau$  includes n reasoning paths  $\{rp_1, ..., rp_n\}$ . To formally represent this single-paradigm scenario, we can formulate it as  $y \sim \mathbb{P}(y|x, \tau)$ . To simplify the process for each reasoning paradigm, we set n = 1 as default (Details in Section 6).

Inspired by recent works [Wei et al., 2022] in encouraging step-by-step reasoning, we introduce CoR, which extends from a single paradigm to three paradigms  $\Gamma = (\tau_1, \tau_2, \tau_3)$ . For generating multiple chained reasoning paradigms for a given problem, CoR follows the steps outlined below. The reasoning process begins with the initialization of the problem x and the first reasoning paradigm  $\tau_1$ . Subsequently, each paradigm  $\tau_i$  in the sequence  $\Gamma$  is generated based on the problem x and the previously established paradigms  $\tau_1, ..., \tau_{i-1}$ , as represented by  $\tau_i \sim \mathbb{P}(\tau_i | x, \tau_1, ..., \tau_{i-1})$ . Finally, the outcomes from all reasoning paradigms are aggregated to derive the final result y, expressed as  $y \sim \mathbb{P}(y | x, \tau_{\text{NLR}}, \tau_{\text{SR}}, \tau_{\text{AR}})$ , considering three paradigms: NLR, SR, and AR. In detail,  $\tau_{\text{SR}}$  and  $\tau_{\text{AR}}$ include both the complete reasoning paths and the interaction processes with tool outputs. In our experiments,  $\tau_{\text{SR}}$  utilizes the Lean prover, and  $\tau_{\text{AR}}$  leverages a Python compiler as the algorithmic interactive tool. CoR possesses the capacity for broad application in complex reasoning scenarios. In the context of mathematical reasoning, it manifests as CoR-Math, with potential for future adaptations such as CoR-Code.

According to this framework, as shown in Figure 3, the training pipeline consists of three key phases: (a) collecting a Multi-Paradigm Mathematical (MPM) dataset, with deep reasoning paths based on multiple reasoning paradigms; (b) introducing a Progressive Paradigm Training (PPT) strategy to shape the model's reasoning behavior, gradually mastering more reasoning paradigms; and (c) leveraging the trained LLM for zero-shot inference, allows multi-paradigm reasoning with adaptable depth, and uses Sequential Multi-Paradigm Sampling (SMPS) to explore a diverse solution space.

### **3.2** Collecting Dataset

To enable CoR training, we extend the traditional single-paradigm training datasets to incorporate multiple reasoning paradigms, represented as < x, NLR, SR, AR, y >. As presented in Figure 3 (a), the training data collection process involves two stages: (a.1) Reconstructing and Extending, and (a.2) Revising. In the first stage, we reconstruct existing high-quality open-source mathematical data as seed samples and synthesize additional reasoning paradigms to create the MPM-raw dataset. In the second stage, a theorem prover examines the MPM-raw samples, and a mathematical reasoner revises those that do not pass, ultimately compiling all completed data into the MPM dataset.

**Stage 1: Reconstructing and Extending**. We introduce a universal text template designed for multiparadigm reasoning (Details in Appendix A.1). This template standardizes the positioning of distinct reasoning paradigms and defines the relationships between them. It accommodates various reasoning depths and supports flexible combinations of different reasoning paradigms. As shown in Figure 2 (c), Problem 1 demonstrates an instance incorporating both NLR and SR paradigms, while Problem 2 showcases an instance that integrates three reasoning paradigms. To ensure data integrity and prevent potential biases, we pre-process the Numina-TIR [LI et al., 2024] and Lean-Workbook [Ying et al., 2024a] datasets through a two-step process. First, samples without corresponding solutions are removed. Second, we further reconstruct and extend these datasets by leveraging powerful LLMs  $\mathcal{G}$ , such as GPT-40 [Hurst et al., 2024]. These models generate missing reasoning paradigms  $\tau_g$  and refine existing ones  $\tau'$ , ensuring comprehensive coverage and logical consistency. To effectively guide the processes of augmentation and refinement, we develop tailored prompts  $p_s$  for each seed dataset. Examples of these prompts are detailed in Appendix A.2. The procedure can be described in:

$$\tau_g \sim \mathbb{P}_{\mathcal{G}}(\tau_g \mid p_s \oplus x \oplus y \oplus \tau'), \tau' \in \{\tau_{\mathrm{NLR}}, \tau_{\mathrm{SR}}, \tau_{\mathrm{AR}}\},\tag{1}$$

where  $\oplus$  means concatenation. After that, we conduct a manual review of all samples. Given that alternative approaches are readily verified through external tools, we focus on the accuracy of the NLR and AR. This approach considerably lowers the requisite skill level of annotators. Furthermore, to avoid data leakage, we calculate the Levenshtein distance [Miller et al., 2009] between problems in the training and test samples, while details are provided in the Appendix **B.1**. As a result, this phase yields the MPM-raw dataset, comprising approximately 285,000 synthetic samples.

**Stage 2: Revising.** The MPM-raw dataset interacts with the Lean prover to verify proof steps, guiding the filtering and modification of reasoning paths. The process submits the proof  $\tau_{SR}$  to the prover. Once the prover successfully completes the proof without returning any errors, the entire multi-paradigm reasoning path is collected to the MPM dataset. Otherwise, the error information  $\varepsilon$  returned by the prover is fed into a revising model  $\mathbb{P}_R$ . Furthermore, this model generates a revised proof  $\tilde{\tau}_{SR}$  based on a prompt  $p_{\varepsilon}$ . The relationship can be expressed as:

$$\tilde{\tau}_{\mathbf{SR}} \sim \mathbb{P}_R(\tilde{\tau}_{\mathbf{SR}} \mid p_{\varepsilon} \oplus x \oplus y \oplus \tau_{\mathbf{SR}}),$$
(2)

where the revised proof  $\tilde{\tau}_{SR}$  is then resubmitted to the Lean prover for verification. This iterative process continues for a maximum of 64 iterations or until the prover verifies  $\tilde{\tau}_{SR}$  as correct. In detail, we utilize DeepSeek-Prover-V1.5 [Xin et al., 2024] as the revising model.

As a result, the MPM dataset comprises 82,770 problems and 167,412 multi-paradigm reasoning solutions.

#### 3.3 Training

Inspired by recent advances [LI et al., 2024], we introduce the Progressive Paradigm Training (PPT) strategy, which enables LLMs to gradually master an increasing variety of reasoning paradigms. As shown in Figure 3 (b), this training framework enables the model to progressively expand its reasoning capability by introducing different types of reasoning data in stages. Each training stage uses a different combination of reasoning paradigms. In the stage ①, given the dominance of NL in the pre-training data of language models [Dubey et al., 2024], we create Numina-CoT\* as an initialized teaching stage. This is done by modifying the original Numina-CoT dataset [LI et al., 2024] according to our universal text template, which enables the model to learn to use NL to solve complex mathematical problems. Based on the question x, the model performs reasoning  $\tau_{NLR}$  and generates the answer y. The generated sequence is  $z = [x]\tau_{NLR}y$ , where [x] represents the tokens of the inputs. For simplicity, we first consider the loss function for a single sample:

$$\mathcal{L}_{\text{sample}} = -\sum_{t=1}^{|z|} \log \mathbb{P}_{\theta}(z_t \mid z_{< t}), \tag{3}$$

where  $\theta$  represents the model parameters,  $z_t$  is the *t*-th token in the generated sequence, and  $z_{<t}$  indicates all tokens before the *t*-th token in the generated sequence. In stage @, considering a certain proportion of code corpora in the pre-training data, we expand the training dataset to include two paradigms: NLR and AR. Similar to Numina-CoT\*, we modify the original Numina-TIR to create Numina-TIR\*. With this modified dataset, the generated sequence is  $z = [x]\tau_{\text{NLR}}\tau_{\text{AR}}y$ . After this stage, the model can handle problems that require precise answers. Finally, in the stage ③, we further expand the training data to three reasoning paradigms by utilizing the MPM dataset, where z is  $[x]\tau_{\text{NLR}}\tau_{\text{AR}}\tau_{\text{SR}}y$ . After full PPT stages, the trained CoR-Math-7B model not only masters NLR and AR but also can perform rigorous logical SR.

#### 3.4 Inference

We introduce an inference method that combines variable reasoning depth and sequential multiparadigm sampling to solve comprehensive mathematical tasks, enabling the model to adapt its reasoning process based on task-specific requirements.

**Prompts with variable reasoning depth.** In the zero-shot inference phase, the CoR-Math-7B exhibits proficiency in multi-paradigm reasoning. This proficiency allows for the implementation of multi-paradigm reasoning with adaptable reasoning depths, achieved by adjusting prompts according to the specific demands of a given task. Initially, the model is prompted to conduct NLR, thereby activating a wide range of knowledge patterns associated with natural language from the pre-training corpus. Subsequently, the inference method is tailored to the specific problem type. For instance, in the context of theorem proving, the model transitions to SR, which is better suited for formal deduction. Given that the output of the model during SR is structured in Lean 4, the relevant proof segment can be extracted as the final solution. In cases of arithmetic computation, the model first performs NLR, followed by SR to strengthen logical coherence, and ultimately employs AR for precise calculations. A summary box is utilized to present the final results. This adaptable paradigm effectively captures the distinct reasoning patterns inherent in different paradigms and demonstrates flexibility in accommodating a variety of scenarios.

Sequential Multi-Paradigm Sampling (SMPS). Instead of token-level sampling based on tree structures [Qiu et al., 2024, Xiong et al., 2024] within single-paradigm reasoning paths, we purpose sequential paradigm-level sampling method, named SMPS. This approach allows the model to generate outputs by sequentially sampling across different paradigms. For instance, in a two-paradigm reasoning scenario, the model first instantiates J distinct paths for the initial reasoning paradigm  $\tau_1$ .

$$\tau_{1j} \sim \mathbb{P}(\tau_{1j} \mid x), \quad \forall j \in 1, \dots, J$$
(4)

Subsequently, for each of these  $\tau_1$  paths, the model instantiates K possible paths for the secondary reasoning paradigm  $\tau_2$ 

$$\tau_{2k} \sim \mathbb{P}(\tau_{2k} \mid x, \tau_{1j}), \quad \forall k \in 1, \dots, K, \forall j$$
(5)

This hierarchical sampling process yields a total of  $J \times K$  potential responses, denoted as y.

$$y_{jk} \sim \mathbb{P}(y_{jk} \mid x, \tau_{1j}, \tau_{2k}), \quad \forall j, k$$
(6)

In summary, the SMPS method leverages the combinatorial expansion of reasoning paths to explore a diverse paradigm-based solution space comprehensively. This structured approach enhances the robustness and depth of the reasoning results.

### 4 Experimental Settings

#### 4.1 Evaluation Setup

**Datasets.** To evaluate our model's mathematical reasoning capabilities comprehensively, we utilize a suite of widely recognized and representative benchmark datasets. These datasets encompass a diverse range of mathematical reasoning tasks, including arithmetic computation and theorem proving. The arithmetic computation ability is evaluated on the GSM8K [Cobbe et al., 2021] and MATH [Hendrycks et al., 2021] datasets. These datasets span a spectrum of difficulty levels, from elementary arithmetic to mathematical competitions. Theorem proving ability is evaluated on the MiniF2F test set [Zheng et al., 2022], which features mathematical problems of Olympiad difficulty.

**Metrics.** Accuracy serves as the primary metric for performance evaluation across all datasets. In detail, we follow the widely-used CoT settings [Wei et al., 2022] to obtain solutions for arithmetic problem tasks, with numerical answers rounded to the nearest integer. The SymPy library<sup>1</sup> is utilized for parsing and evaluating mathematical expressions. To address potential variations in numerical representation, the model is instructed to explicitly state the final answer in the conclusion, following the approach in Numina models [LI et al., 2024]. For theorem proving datasets, we follow the recent advances [Xin et al., 2024] to adapt the publicly available MiniF2F benchmark for the Lean 3 theorem proving environment to the Lean 4 environment<sup>2</sup>. These adjustments ensure the use of

<sup>&</sup>lt;sup>1</sup>https://www.sympy.org/

<sup>&</sup>lt;sup>2</sup>https://github.com/rahul13613/miniF2F-lean4

the most up-to-date formal verification tools. The pass@N metric evaluates the capacity of the model to generate correct proofs within N attempts. Specifically, our CoR-Math-7B employs SMPS, which operates by performing NLR followed by SR. Therefore, the sample budget N is  $N_{\text{NLR}} \times N_{\text{SR}}$ . Detailed settings of all models are provided in Appendix A.5.

### 4.2 Implementation Details

We fine-tuned widely-used DeepSeek-Math-Base 7B [Shao et al., 2024] and Llama-3.1 8B [Dubey et al., 2024] models, employing our PPT method on MPM dataset. Unless otherwise specified, CoR-Math-7B model is based on DeepSeek-Math-Base 7B. The details are available in Appendix A.3.

### 4.3 Baselines

This study examines three categories of baseline models, with results reported using CoT prompting.

**General-purpose mathematical models:** Considering the general applicability of our CoR-Math-7B model, we present the SOTA general-purpose mathematical models, including Mustard [Huang et al., 2024], DeepSeek-Math [Shao et al., 2024], InternLM-Math [Ying et al., 2024b], Llama-3.1 [Dubey et al., 2024], Mistral [Jiang et al., 2023], and Llemma [Azerbayev et al., 2024].

**Task-specific mathematical models:** We consider several expert models on mathematical optimization for specific tasks. For expert models on arithmetic computation, we include several models that undergo specialized reinforcement in arithmetic computation to achieve enhanced performance, such as more data and tool invocation. These models encompass Qwen2.5-Math [Yang et al., 2024], WizardMath [Luo et al., 2023], MetaMath [Yu et al., 2024], DART-Math [Tong et al., 2024], InternLM-Math [Ying et al., 2024b], , DeepSeek-Math-Instruct / RL [Shao et al., 2024], Xwin-Math [Li et al., 2024], ToRA [Gou et al., 2024], and NuminaMath [LI et al., 2024]. For expert models on theorem proving, we consider several SOTA models with substantial improvements, including reinforcement learning and Monte Carlo search. We include LLM-Step [Welleck and Saha, 2023], GPT-f [Polu and Sutskever, 2020], Lean-STaR [Lin et al., 2024], Hypertree Proof Search [Lample et al., 2022], DeepSeek-Prover [Xin et al., 2024], and InternLM2.5-StepProver [Wu et al., 2024].

**Foundation models and proprietary models:** We introduce current advanced open-source foundational models, which are Llama-3.1 [Dubey et al., 2024], Mistral [Jiang et al., 2023], and Mixtral [Jiang et al., 2024]. We also introduce proprietary models, which are GPT-4 [OpenAI, 2023], GPT-40 [Hurst et al., 2024] and o1-mini [OpenAI, 2024], as robust competitors.

# 5 Results and Analysis

### 5.1 Main Results

This section presents a comprehensive evaluation of CoR-Math-7B's capabilities in diverse mathematical reasoning tasks. We systematically assess its performance against SOTA models and expert models on specific domains using a zero-shot evaluation setting. Our objective is to demonstrate how multi-paradigm approach enables CoR-Math-7B to achieve superior general mathematical reasoning abilities and computational efficiency, compared to methods based on a single reasoning paradigm.

### 5.1.1 Comparisons with General-purpose Mathematical Models

To explore the versatility of CoR-Math-7B and assess its comprehensive mathematical reasoning capabilities, we compare it with widely-used models and SOTA general mathematical models. As shown in Table 1, CoR-Math-7B achieves the best performance across three challenging benchmarks in a zero-shot setting. These results collectively highlight the strong comprehensive mathematical reasoning abilities of our model. The findings are detailed below: (1) arithmetic computation task: our CoR-Math-7B achieves optimal results across all arithmetic computation benchmarks. For example, it exceeds InterLM2-Math-Plus-7B by a 13.7% absolute improvement on the MATH dataset. (2) theorem proving task: our CoR-Math-7B achieves the best zero-shot result on MiniF2F, even surpassing the proprietary GPT-40 model by a 41% absolute increase in few-shot setting. (3) zero-shot vs few-shot: The zero-shot performance of CoR-Math-7B demonstrates a 14.0% absolute improvement over the few-shot performance of DeepSeek-math-7B-Base on the MiniF2F

Table 1: A overall comparison of CoR-Math-7B with three types of general mathematical reasoners (proprietary, foundational, and general-purpose mathematical models (GMM)) on three mathematical benchmarks. Results are shown for zero-shot (denoted by  $\emptyset$ ) or few-shot settings by default. For the MiniF2F benchmark, we report the best results from the relevant literature with a specified sample budget. **Bolded** scores are the best performance among all models except for the proprietary one.

Model	Model Types	MATH Pass@1	GSM8k Pass@1	miniF2F-test Sample Budget (N)	miniF2F-test Pass@N
o1-mini	Proprietary	$90.0^{\emptyset}$	94.8 <sup>Ø</sup>	1	13.2
GPT-4	Proprietary	42.5 <sup>Ø</sup>	$87.1^{\emptyset}$	128	24.6
GPT-40	Proprietary	$76.6^{\emptyset}$	90.5 <sup>ø</sup>	128	25.0
Llama-3.1-8B	Foundation	$4.2^{\emptyset}$	$6.2^{\emptyset}$	128	25.8
Llama-3.1-8B-Instruct	Foundation	47.2 <sup>Ø</sup>	$76.6^{\emptyset}$	128	23.4
Mistral-7B	Foundation	14.3	40.3	$1 \times 32 \times 100$	22.1
Mixtral-8x7B	Foundation	28.4	74.4	$1 \times 32 \times 100$	23.4
MUSTARD	GMM	13.8 <sup>Ø</sup>	$27.9^{\emptyset}$	1	7.8
Llemma-7B	GMM	18.6	41.0	$1 \times 32 \times 100$	26.2
DeepSeek-Math-7B-Base	GMM	$11.8^{\emptyset}$	$22.2^{\emptyset}$	$1 \times 32 \times 100$	28.3
InternLM2-Math-7B-Base	GMM	21.5	49.2	$1 \times 32 \times 100$	30.3
InternLM2-Math-Plus-7B	GMM	53.0 <sup>Ø</sup>	$85.8^{\emptyset}$	$1 \times 32 \times 100$	43.3
				128×1	52.9 <sup>Ø</sup>
CoR-Math-7B	GMM	<b>66.7</b> <sup>Ø</sup>	<b>88.7</b> <sup>Ø</sup>	32×100	59.4 <sup>Ø</sup>
				128×128	<b>66.0</b> <sup>∅</sup>

dataset. When testing on the MiniF2f dataset revealed limited proficiency in Qwen2.5-Math [Yang et al., 2024] in Lean 4, indicating a focus on arithmetic computation over theorem proving. Therefore, we classify Qwen2.5-Math as an arithmetic computation model rather than a general mathematical model and compare it in Section 5.1.3. These findings indicate the strong generalization capability and comprehensive mathematical reasoning ability of the CoR framework. This suggests NLR descriptions and SR verification rehearse precise mathematical reasoning for AR. In summary, the results indicate that the CoR framework can handle a diverse range of complex reasoning challenges, and leveraging the synergy between different paradigms can enhance general reasoning capabilities.

### 5.1.2 Comparisons with Expert Models on Theorem Proving

Table 2 shows CoR-Math-7B's exceptional zero-shot performance on the MiniF2F, achieving 66.0% accuracy without demonstrations while competing methods require few-shot examples. Its zero-shot performance is particularly noteworthy when considering computational efficiency.

Table 2: The zero-shot ( $\emptyset$ ) performance of CoR-Math-7B and the few-shot performance of optimized models on the MiniF2F benchmark. These models incorporate optimizations related to theorem proving. The highest scores are in **bold**.

Model	Sample Budget $N$	MiniF2F
LLMStep	$1 \times 32 \times 100$	27.9
GPT-f	64×8×512	36.6
Hypertree Proof Search	64×5000	41.0
Lean-STaR	64×1×50	46.3
DeepSeek-Prover-V1.5-Base	6400	42.2
DeepSeek-Prover-V1.5-SFT + RMaxTS	4×6400	56.3
DeepSeek-Prover-V1.5-SFT + RMaxTS	32×6400	60.2
DeepSeek-Prover-V1.5-RL + RMaxTS	4×6400	59.6
DeepSeek-Prover-V1.5-RL + RMaxTS	32×6400	63.5
InternLM2.5-StepProver	64×32×100	54.5
InternLM2.5-StepProver-BF	$1 \times 32 \times 600$	47.3
InternLM2.5-StepProver-BF	256×32×600	59.4
InternLM2.5-StepProver-BF+CG	$2 \times 32 \times 600$	50.7
InternLM2.5-StepProver-BF+CG	256×32×600	65.9
CoR-Math-7B	128×128	66.0 <sup>0</sup>

For instance, under similar computational constraints, our CoR-Math-7B surpasses DeepSeek-Prover-V1.5-RL + RMaxTS by 6.4% absolute points (66.0% vs 59.6% with  $128 \times 128$  vs  $4 \times 6400$ ) and InternLM2.5-StepProver-BF+CG by 15.3% absolute points (66.0% vs 50.7% with  $128 \times 128$  vs  $2 \times 32 \times 600$ ). Compared to significantly larger sample sizes, CoR-Math-7B retains its competitive edge. For example, zero-shot CoR-Math-7B outperforms few-shot InternLM2.5-StepProver-BF+CG by 0.1% in absolute score, despite considering approximately 300 times more potential solutions. These results highlight the effectiveness of multi-paradigm reasoning and demonstrate how CoR efficiently searches paradigm-based solution spaces.

#### 5.1.3 Comparisons with Expert Models on Arithmetic Computation

Table 3 shows the significant competitiveness of our CoR-Math-7B when compared to expert models on arithmetic computation. Compared to methods like ToRA and NuminaMath that use code as a tool without full reasoning, our CoR-Math-7B with multi-paradigm reasoning outperforms them on all benchmarks. For instance, on the competition-level MATH dataset, CoR-Math-7B achieves an 11.4% absolute improvement over the tool-integrated NuminaMath-7B-TIR. This reinforces the effectiveness of complete code-based reasoning compared to the fragmented interleaving of natural language and Python code.

To further explore the relationship between resource utilization (training sample size) and performance, we fit a quadratic function to the current SOTA models and conduct a Pareto frontier analysis [Branke et al., 2008]. Based on Table 3, we generate the fitting Pareto curve shown in Figure 1 (b), which is based on all reasoning methods. Our CoR-Math-7B achieves superior performance compared to the optimal performance of single-paradigm reasoning methods with similar data volume. This suggests the existence of a new optimal curve based on multi-paradigm reasoning methods, which outperforms the curve of single-paradigm approaches.

Model	SET Data Siza (k)	MATH GSM8k	Augrago		
Model	ZS Pass@1		ZS Pass@1	Average	
WizardMath	868	10.7	54.9	32.8	
MetaMath-7B	2,790	19.8	66.5	43.2	
MetaMath-Llemma-7B	2,790	30.0	69.2	49.6	
MetaMath-Mistral-7B	2,790	28.2	77.7	53.0	
ToRA	85	40.1	68.8	54.5	
ToRA-CODE	85	44.6	72.6	58.6	
NuminaMath-7B-CoT	859	$54.4^{\dagger}$	$66.6^{\dagger}$	60.5	
Xwin-Math-7B	1,440	40.6	82.6	61.6	
NuminaMath-7B-TIR	931	$55.3^{\dagger}$	$73.6^\dagger$	64.5	
DART-Math-7B	1,175	53.6	86.6	70.1	
Qwen2.5-Math-7B-Instruct	3,026	83.6	95.2	89.4	
CoR-Math-7B	1,098	66.7	88.7	77.7	

Table 3: Zero-shot (ZS) performance on the MATH and GSM8K benchmarks for the arithmetic task, with data size in the Supervised Fine-Tuning (SFT) stage. † denotes our reported results with the open-sourced model weights. The best results are in **bold**, and the second-best results are <u>underlined</u>.

#### 5.2 Ablation Study

We conduct a series of ablation studies, providing insights into the key factors that drive the performance of our multi-paradigm reasoning framework.

#### 5.2.1 Impact of Stages in PPT Method

To evaluate the effectiveness of PPT methods, we employ two base models, Llama-3.1-8B [Dubey et al., 2024] and Deepseek-Math-7B-Base [Shao et al., 2024]. We present the results of the PPT method across different stages on these two models for the MATH and GSM8K benchmarks. As shown in Figure 4, the vanilla models exhibit limited performance on both benchmarks. After stage ①, the performance of all models improves significantly. For instance, Llama-3.1-Base achieves absolute gains of 47.9% on MATH and 61.0% on GSM8K. This demonstrates the necessity of understanding



Figure 4: An evaluation of the effectiveness of the PPT strategy on mathematical reasoning tasks. We present the zero-shot Pass@1 results on the MATH and GSM8k benchmarks, across three cumulative stages of the PPT strategy based on the DeepSeek-Math and Llama-3.1 models. The results highlight the cumulative effectiveness of the PPT strategy, showing increased performance for both models across all benchmark datasets with each progressive stage. These results indicate that the PPT strategy is a viable method to enhance mathematical reasoning capabilities.

mathematical concepts and warming up the models. Subsequently, we conduct stage <sup>(2)</sup> training, which utilizes data with NLR and AR. The limited performance gains are potential because the pre-training data already includes code and natural language corpus. Both stage <sup>(1)</sup> and stage <sup>(2)</sup> primarily reactivate the base models in the mathematical domain, and stage <sup>(1)</sup> already incorporates NLR training. In the final stage <sup>(3)</sup>, we consider training with three paradigms, and all models experience performance enhancements. This suggests that introducing rare or unseen paradigms helps to improve the reasoning ability of learned paradigms.

#### 5.2.2 Impact of Reasoning Paradigms Order

We investigated the impact of varying the sequence of reasoning paradigms employed by CoR-Math-7B during zero-shot inference for arithmetic computation tasks. Our experiments involved modifying only the prompt structure to enforce different paradigm orders. Given that NLR closely aligns with the pre-training of LLMs, it was consistently positioned as the initial paradigm in our experiments. Table 4 presents the accuracy for the MATH and GSM8K benchmarks under two different paradigm orders. The results indicate that performing SR before AR achieves the best performance. Specifically, on the MATH benchmark, this order achieves an accuracy of 66.7%, an improvement over the 49.9% attained by the sequence that AR before SR. A possible explanation for this observation lies in the synergistic effect of the ordered paradigms. SR plays a crucial role in decomposing the problem into manageable sub-steps, thereby providing a structured foundation for subsequent AR. By placing SR before AR, we hypothesize that the model is better equipped to perform accurate calculations, leveraging the intermediate reasoning steps generated by SR. Furthermore, positioning AR immediately preceding the Summary phase may facilitate a more coherent integration of the computational outcome into the final answer.

Table 4: Zero-shot Pass@1 results for varying paradigm orders on the MATH and GSM8k benchmarks. The best results are in **bold**.

Benchmark	$\begin{array}{l} \text{NLR} \rightarrow \textbf{SR} \rightarrow \\ \textbf{AR} \rightarrow \text{Summary} \end{array}$	$\begin{array}{l} \text{NLR} \rightarrow \textbf{AR} \rightarrow \\ \textbf{SR} \rightarrow \text{Summary} \end{array}$
MATH	66.7	49.9
GSM8K	88.7	84.2

#### 5.2.3 Impact of Scaling Model Size

Table 5 investigates the performance of various base models with different parameters under the CoR framework. We employ the Qwen2.5-Math models [Yang et al., 2024] with 1.5 billion and 7 billion parameters as the base model. Results demonstrate that our CoR framework achieves superior performance with increasing parameter scale. Specifically, when comparing a model with 7 billion

Table 5: Zero-shot Pass@1 results on the MATH and GSM8k benchmarks across different model scales. The best scores are in **bold**.

Model	MATH	GSM8k
Qwen2.5-Math-1.5B (CoR)	57.6	84.5
Qwen2.5-Math-7B (CoR)	<b>64.7</b>	<b>90.0</b>

parameters to one with 1.5 billion parameters, the former attained an absolute increase of 7.1% on the MATH benchmark and 5.5% on the GSM8K benchmark. This evidence supports the claim that CoR exhibits scalability with respect to model parameter scaling.

### 6 Discussion on Reasoning Hierarchy: Paradigms, Paths, and Steps

This section attempts to explore the essence of reasoning, contrasts CoR with current methods, examines the factors contributing to its effectiveness, and provides a new perspective for future research.



Figure 5: An overview of the reasoning hierarchical structure. (a) A single reasoning paradigm depicts multiple distinct reasoning paths. (b) An example of single-paradigm reasoning includes one reasoning path, which contains several reasoning steps. (c) Multi-paradigm reasoning includes several distinct reasoning paradigms.

As shown in Figure 5, this paper posits that reasoning texts generated by LLMs exhibit a reasoning hierarchical structure, which consists of three levels: reasoning paradigms, reasoning paths, and reasoning steps.

- **Reasoning steps** represent the fundamental units, each comprising one or more tokens and encompassing an incomplete stage of the solution process.
- **Reasoning paths** consist of several reasoning steps, forming a complete line of reasoning that typically includes a final answer and the solution process.
- **Reasoning paradigms** comprise one or more reasoning paths. They often contain multiple potential final answers, thus necessitating a summarization method, such as a summary module, to extract the ultimate answer. Furthermore, a reasoning paradigm utilizes a single knowledge media, such as natural language.



Figure 6: A comparison of reasoning paradigms in advanced studies. (a) deep reasoning, characterized by serial concatenation of reasoning paths. (b) interleaved reasoning, which integrates secondary methods for guidance within a dominant paradigm. (c) multi-paradigm reasoning (Our proposed CoR), a framework designed to harness the synergistic effects between different reasoning paradigms.

Furthermore, current studies can be categorized based on their focus. As shown in Figure 5 (a), contemporary work concentrates within a single paradigm, optimizing along two dimensions: depth (the number of reasoning steps) and width (the number of reasoning paths). For instance, regarding reasoning depth, the CoT method [Wei et al., 2022] employs prompts to increase intermediate steps within one reasoning path to achieve higher performance. Concerning reasoning width, some approaches [Wang et al., 2023] involve altering sampling techniques to generate multiple distinct reasoning paths. Random sampling exemplifies this. Other studies [Zhu et al., 2023] employ scoring mechanisms for reasoning steps, guiding LLMs to generate several more desirable reasoning paths. Monte Carlo search illustrates this. Building upon these generated reasoning paths, existing work proposes various integration strategies to obtain the final answer, such as Best-of-N and Self-consistency [Wang et al., 2023]. Specifically, as shown in Figure 6 (a), recent advanced studies introduce the deep reasoning method, which focuses on generating serial concatenation of reasoning paths followed by summarization (like OpenAI o1). Since these methods are based on different optimization dimensions, we can combine them feasibly in applications.

Specifically, some approaches prioritize a dominant paradigm for reasoning yet hope to integrate other paradigms for guidance. For instance, as shown in Figure 6 (b), the reasoning process of ToRA [Gou et al., 2024] presents an interleaved reasoning method with different knowledge media. It involves initial natural language generation, which is followed by code generation. Subsequently, the process awaits the results of code execution before generating further natural language. InternLM2.5-StepProver [Wu et al., 2024] exhibits a similar pattern. It incorporates natural language annotations to support symbolic reasoning steps. However, these interleaved reasoning approaches do not constitute true multi-paradigm reasoning. The primary paradigm can independently achieve the final answer without the supplementary paradigms. Consequently, these methods imply a single-paradigm reasoning approach enhanced by other paradigms, rather than genuine multi-paradigm reasoning.

Current methods often *overlook the synergistic effects between paradigms and underestimate the importance of complete reasoning for achieving accurate results.* To address this challenge, as shown in Figure 5 (c) and Figure 6 (c), we introduce Chain-of-Reasoning (CoR), a unified reasoning framework capable of multi-paradigm reasoning. This framework embodies the following potential advantages:

**Sequential reasoning dependency**. As a type of multi-paradigm reasoning, CoR is not a mere accumulation of isolated steps; instead, it represents a coherent, interconnected process. The output from an earlier paradigm functions not only as input for a subsequent paradigm but also informs the foundational information for its reasoning. For instance, knowledge derived from a natural language paradigm guides subsequent algorithmic paradigms, thereby enhancing the efficiency and accuracy of code generation based on detailed natural language reasoning. This mechanism also provides substantial context from prior paradigms to later paradigms and operates as a form of preliminary rehearsal where subsequent paradigms can follow correct reasoning steps or rectify incorrect ones.

A novel direction for test-time scaling emerges. We observe that the achievable improvements of single-paradigm reasoning are increasingly constrained by various search methods applied to the solution space. For instance, DeepSeek-Prover-V1.5-RL + RMaxTS requires  $32 \times 6400$  reasoning paths to achieve 63.5% few-shot accuracy on the miniF2F benchmark. While extending the number of candidate solution paths seems a natural way to enhance the hit rate for ground truth solutions, the substantial computational effort involved underscores the inherent limitations of single-paradigm reasoning. This observation suggests that scaling up reasoning within a single paradigm during test time is inadequate for addressing complex tasks, such as mathematical problem solving. From a broader perspective, our CoR framework reexamines this challenge by shifting the focus of scaling efforts from reasoning paths to reasoning paradigms, thereby proposing a novel avenue for advancement.

**Expanding the solution space**. In multi-paradigm reasoning, the solution space is expanded by considering potential orthogonal relationships between reasoning paradigms. This allows generated solutions to be searched within different paradigms. Moreover, diverse solutions across paradigms can leverage chain relationships in reasoning to mutually inform each other. Therefore, our CoR framework enhances both intra-paradigm and inter-paradigm search capabilities within a large solution space. This diversity increases the likelihood of discovering optimal solutions.

**Journey-based reasoning learning**. CoR enhances models' learning trajectory, allowing them to perform deep reasoning both within specific paradigms and across multiple paradigms. This approach

expands the "journey" by introducing the ability to navigate and collaborate across diverse reasoning paradigms.

**Compatibility with existing methods**. Since most current approaches are fundamentally based on a single paradigm, CoR can seamlessly integrate these methods within its specified paradigms, enabling them to work synergistically and leverage their strengths. For example, CoT can be incorporated as a specific implementation of the NLR paradigm in CoR. This implies that CoR serves as a platform that facilitates continuous integration and collaboration.

### 7 Conclusions

This paper introduces Chain-of-Reasoning (CoR), a novel unified reasoning framework that synergistically combines natural language, algorithmic, and symbolic reasoning to solve mathematical problems. Our approach demonstrates the potential of integrating diverse reasoning paradigms in the reasoning process, enabling language models to tackle complex mathematical challenges effectively. CoR achieves significant performance gains on challenging mathematical reasoning tasks, substantially outperforming existing single-paradigm approaches on benchmarks like MATH and MiniF2F. In addition, CoR introduces a new, orthogonal perspective to traditional test-time scaling by leveraging multi-paradigm reasoning paths to enhance computational efficiency and performance. Furthermore, our proposed CoR framework offers valuable insights for future research, contributing to the development of more robust and versatile reasoning agents capable of leveraging the strengths of multiple reasoning modalities.

### References

- Zhangir Azerbayev, Hailey Schoelkopf, Keiran Paster, Marco Dos Santos, Stephen Marcus McAleer, Albert Q. Jiang, Jia Deng, Stella Biderman, and Sean Welleck. Llemma: An open language model for mathematics. In *ICLR*. OpenReview.net, 2024.
- Maciej Besta, Nils Blach, Ales Kubicek, Robert Gerstenberger, Michal Podstawski, Lukas Gianinazzi, Joanna Gajda, Tomasz Lehmann, Hubert Niewiadomski, Piotr Nyczyk, and Torsten Hoefler. Graph of thoughts: Solving elaborate problems with large language models. In *AAAI*, pages 17682–17690. AAAI Press, 2024.
- Jürgen Branke, Kalyanmoy Deb, Kaisa Miettinen, and Roman Slowinski, editors. *Multiobjective Optimization, Interactive and Evolutionary Approaches [outcome of Dagstuhl seminars]*, volume 5252 of Lecture Notes in Computer Science, 2008. Springer.
- Wenhu Chen, Xueguang Ma, Xinyi Wang, and William W. Cohen. Program of thoughts prompting: Disentangling computation from reasoning for numerical reasoning tasks. *Trans. Mach. Learn. Res.*, 2023, 2023.
- Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. Training verifiers to solve math word problems. *CoRR*, abs/2110.14168, 2021.
- Tri Dao. Flashattention-2: Faster attention with better parallelism and work partitioning. In *ICLR*. OpenReview.net, 2024.
- Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, Arun Rao, Aston Zhang, Aurélien Rodriguez, Austen Gregerson, Ava Spataru, Baptiste Rozière, Bethany Biron, Binh Tang, Bobbie Chern, Charlotte Caucheteux, Chaya Nayak, Chloe Bi, Chris Marra, Chris McConnell, Christian Keller, Christophe Touret, Chunyang Wu, Corinne Wong, Cristian Canton Ferrer, Cyrus Nikolaidis, Damien Allonsius, Daniel Song, Danielle Pintz, Danny Livshits, David Esiobu, Dhruv Choudhary, Dhruv Mahajan, Diego Garcia-Olano, Diego Perino, Dieuwke Hupkes, Egor Lakomkin, Ehab AlBadawy, Elina Lobanova, Emily Dinan, Eric Michael Smith, Filip Radenovic, Frank Zhang, Gabriel Synnaeve, Gabrielle Lee, Georgia Lewis Anderson, Graeme Nail, Grégoire Mialon, Guan Pang, Guillem Cucurell, Hailey Nguyen, Hannah Korevaar, Hu Xu, Hugo Touvron, Iliyan Zarov, Imanol Arrieta Ibarra, Isabel M. Kloumann, Ishan Misra, Ivan

Evtimov, Jade Copet, Jaewon Lee, Jan Geffert, Jana Vranes, Jason Park, Jay Mahadeokar, Jeet Shah, Jelmer van der Linde, Jennifer Billock, Jenny Hong, Jenya Lee, Jeremy Fu, Jianfeng Chi, Jianyu Huang, Jiawen Liu, Jie Wang, Jiecao Yu, Joanna Bitton, Joe Spisak, Jongsoo Park, Joseph Rocca, Joshua Johnstun, Joshua Saxe, Junteng Jia, Kalyan Vasuden Alwala, Kartikeya Upasani, Kate Plawiak, Ke Li, Kenneth Heafield, Kevin Stone, and et al. The Ilama 3 herd of models. *CoRR*, abs/2407.21783, 2024.

- Edward A Feigenbaum, Julian Feldman, et al. *Computers and thought*, volume 37. New York McGraw-Hill, 1963.
- Luyu Gao, Aman Madaan, Shuyan Zhou, Uri Alon, Pengfei Liu, Yiming Yang, Jamie Callan, and Graham Neubig. PAL: program-aided language models. In *ICML*, volume 202 of *Proceedings of Machine Learning Research*, pages 10764–10799. PMLR, 2023.
- Zhibin Gou, Zhihong Shao, Yeyun Gong, Yelong Shen, Yujiu Yang, Minlie Huang, Nan Duan, and Weizhu Chen. Tora: A tool-integrated reasoning agent for mathematical problem solving. In *ICLR*. OpenReview.net, 2024.
- Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. Measuring mathematical problem solving with the MATH dataset. In *NeurIPS Datasets and Benchmarks*, 2021.
- Mohammad Javad Hosseini, Hannaneh Hajishirzi, Oren Etzioni, and Nate Kushman. Learning to solve arithmetic word problems with verb categorization. In *EMNLP*, pages 523–533. ACL, 2014.
- Yinya Huang, Xiaohan Lin, Zhengying Liu, Qingxing Cao, Huajian Xin, Haiming Wang, Zhenguo Li, Linqi Song, and Xiaodan Liang. MUSTARD: mastering uniform synthesis of theorem and proof data. In *ICLR*. OpenReview.net, 2024.
- Aaron Hurst, Adam Lerer, Adam P. Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, Aleksander Madry, Alex Baker-Whitcomb, Alex Beutel, Alex Borzunov, Alex Carney, Alex Chow, Alex Kirillov, Alex Nichol, Alex Paino, Alex Renzin, Alex Tachard Passos, Alexander Kirillov, Alexi Christakis, Alexis Conneau, Ali Kamali, Allan Jabri, Allison Moyer, Allison Tam, Amadou Crookes, Amin Tootoonchian, Ananya Kumar, Andrea Vallone, Andrej Karpathy, Andrew Braunstein, Andrew Cann, Andrew Codispoti, Andrew Galu, Andrew Kondrich, Andrew Tulloch, Andrey Mishchenko, Angela Baek, Angela Jiang, Antoine Pelisse, Antonia Woodford, Anuj Gosalia, Arka Dhar, Ashley Pantuliano, Avi Nayak, Avital Oliver, Barret Zoph, Behrooz Ghorbani, Ben Leimberger, Ben Rossen, Ben Sokolowsky, Ben Wang, Benjamin Zweig, Beth Hoover, Blake Samic, Bob McGrew, Bobby Spero, Bogo Giertler, Bowen Cheng, Brad Lightcap, Brandon Walkin, Brendan Quinn, Brian Guarraci, Brian Hsu, Bright Kellogg, Brydon Eastman, Camillo Lugaresi, Carroll L. Wainwright, Cary Bassin, Cary Hudson, Casey Chu, Chad Nelson, Chak Li, Chan Jun Shern, Channing Conger, Charlotte Barette, Chelsea Voss, Chen Ding, Cheng Lu, Chong Zhang, Chris Beaumont, Chris Hallacy, Chris Koch, Christian Gibson, Christina Kim, Christine Choi, Christine McLeavey, Christopher Hesse, Claudia Fischer, Clemens Winter, Coley Czarnecki, Colin Jarvis, Colin Wei, Constantin Koumouzelis, and Dane Sherburn. Gpt-4o system card. CoRR, abs/2410.21276, 2024.
- Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de Las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Lélio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. Mistral 7b. *CoRR*, abs/2310.06825, 2023.
- Albert Q. Jiang, Alexandre Sablayrolles, Antoine Roux, Arthur Mensch, Blanche Savary, Chris Bamford, Devendra Singh Chaplot, Diego de Las Casas, Emma Bou Hanna, Florian Bressand, Gianna Lengyel, Guillaume Bour, Guillaume Lample, Lélio Renard Lavaud, Lucile Saulnier, Marie-Anne Lachaux, Pierre Stock, Sandeep Subramanian, Sophia Yang, Szymon Antoniak, Teven Le Scao, Théophile Gervet, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. Mixtral of experts. *CoRR*, abs/2401.04088, 2024.
- Guillaume Lample, Timothée Lacroix, Marie-Anne Lachaux, Aurélien Rodriguez, Amaury Hayat, Thibaut Lavril, Gabriel Ebner, and Xavier Martinet. Hypertree proof search for neural theorem proving. In *NeurIPS*, 2022.

- Chen Li, Weiqi Wang, Jingcheng Hu, Yixuan Wei, Nanning Zheng, Han Hu, Zheng Zhang, and Houwen Peng. Common 7b language models already possess strong math capabilities. *CoRR*, abs/2403.04706, 2024.
- Jia LI, Edward Beeching, Lewis Tunstall, Ben Lipkin, Roman Soletskyi, Shengyi Costa Huang, Kashif Rasul, Longhui Yu, Albert Jiang, Ziju Shen, Zihan Qin, Bin Dong, Li Zhou, Yann Fleureau, Guillaume Lample, and Stanislas Polu. Numinamath. https://github.com/project-numina/ aimo-progress-prize, 2024.
- Haohan Lin, Zhiqing Sun, Yiming Yang, and Sean Welleck. Lean-star: Learning to interleave thinking and proving. CoRR, abs/2407.10040, 2024.
- Haipeng Luo, Qingfeng Sun, Can Xu, Pu Zhao, Jianguang Lou, Chongyang Tao, Xiubo Geng, Qingwei Lin, Shifeng Chen, and Dongmei Zhang. Wizardmath: Empowering mathematical reasoning for large language models via reinforced evol-instruct. *CoRR*, abs/2308.09583, 2023.
- Frederic P. Miller, Agnes F. Vandome, and John McBrewster. Levenshtein Distance: Information theory, Computer science, String (computer science), String metric, Damerau?Levenshtein distance, Spell checker, Hamming distance. Alpha Press, 2009. ISBN 6130216904.
- OpenAI. GPT-4 technical report. CoRR, abs/2303.08774, 2023.
- OpenAI. Openai o1 system card, 2024. URL https://arxiv.org/abs/2412.16720.
- Stanislas Polu and Ilya Sutskever. Generative language modeling for automated theorem proving. *CoRR*, abs/2009.03393, 2020.
- Jiahao Qiu, Yifu Lu, Yifan Zeng, Jiacheng Guo, Jiayi Geng, Huazheng Wang, Kaixuan Huang, Yue Wu, and Mengdi Wang. Treebon: Enhancing inference-time alignment with speculative tree-search and best-of-n sampling. *CoRR*, abs/2410.16033, 2024.
- Samyam Rajbhandari, Jeff Rasley, Olatunji Ruwase, and Yuxiong He. Zero: memory optimizations toward training trillion parameter models. In SC, page 20. IEEE/ACM, 2020.
- Baptiste Rozière, Jonas Gehring, Fabian Gloeckle, Sten Sootla, Itai Gat, Xiaoqing Ellen Tan, Yossi Adi, Jingyu Liu, Tal Remez, Jérémy Rapin, Artyom Kozhevnikov, Ivan Evtimov, Joanna Bitton, Manish Bhatt, Cristian Canton-Ferrer, Aaron Grattafiori, Wenhan Xiong, Alexandre Défossez, Jade Copet, Faisal Azhar, Hugo Touvron, Louis Martin, Nicolas Usunier, Thomas Scialom, and Gabriel Synnaeve. Code Ilama: Open foundation models for code. *CoRR*, abs/2308.12950, 2023.
- Bilgehan Sel, Ahmad Al-Tawaha, Vanshaj Khattar, Ruoxi Jia, and Ming Jin. Algorithm of thoughts: Enhancing exploration of ideas in large language models. In *ICML*. OpenReview.net, 2024.
- Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *CoRR*, abs/2402.03300, 2024.
- Yuxuan Tong, Xiwen Zhang, Rui Wang, Ruidong Wu, and Junxian He. Dart-math: Difficulty-aware rejection tuning for mathematical problem-solving. *CoRR*, abs/2407.13690, 2024.
- Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc V. Le, Ed H. Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. In *ICLR*. OpenReview.net, 2023.
- Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed H. Chi, Quoc V. Le, and Denny Zhou. Chain-of-thought prompting elicits reasoning in large language models. In *NeurIPS*, 2022.
- Sean Welleck and Rahul Saha. LLMSTEP: LLM proofstep suggestions in lean. *CoRR*, abs/2310.18457, 2023.
- Zijian Wu, Suozhi Huang, Zhejian Zhou, Huaiyuan Ying, Jiayu Wang, Dahua Lin, and Kai Chen. Internlm2.5-stepprover: Advancing automated theorem proving via expert iteration on large-scale LEAN problems. *CoRR*, abs/2410.15700, 2024.

- Huajian Xin, Z. Z. Ren, Junxiao Song, Zhihong Shao, Wanjia Zhao, Haocheng Wang, Bo Liu, Liyue Zhang, Xuan Lu, Qiushi Du, Wenjun Gao, Qihao Zhu, Dejian Yang, Zhibin Gou, Z. F. Wu, Fuli Luo, and Chong Ruan. Deepseek-prover-v1.5: Harnessing proof assistant feedback for reinforcement learning and monte-carlo tree search. *CoRR*, abs/2408.08152, 2024.
- Yunfan Xiong, Ruoyu Zhang, Yanzeng Li, Tianhao Wu, and Lei Zou. Dyspec: Faster speculative decoding with dynamic token tree structure. *CoRR*, abs/2410.11744, 2024.
- An Yang, Beichen Zhang, Binyuan Hui, Bofei Gao, Bowen Yu, Chengpeng Li, Dayiheng Liu, Jianhong Tu, Jingren Zhou, Junyang Lin, Keming Lu, Mingfeng Xue, Runji Lin, Tianyu Liu, Xingzhang Ren, and Zhenru Zhang. Qwen2.5-math technical report: Toward mathematical expert model via self-improvement. *CoRR*, abs/2409.12122, 2024.
- Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Tom Griffiths, Yuan Cao, and Karthik Narasimhan. Tree of thoughts: Deliberate problem solving with large language models. In *NeurIPS*, 2023.
- Huaiyuan Ying, Zijian Wu, Yihan Geng, Jiayu Wang, Dahua Lin, and Kai Chen. Lean workbook: A large-scale lean problem set formalized from natural language math problems. *CoRR*, abs/2406.03847, 2024a.
- Huaiyuan Ying, Shuo Zhang, Linyang Li, Zhejian Zhou, Yunfan Shao, Zhaoye Fei, Yichuan Ma, Jiawei Hong, Kuikun Liu, Ziyi Wang, Yudong Wang, Zijian Wu, Shuaibin Li, Fengzhe Zhou, Hongwei Liu, Songyang Zhang, Wenwei Zhang, Hang Yan, Xipeng Qiu, Jiayu Wang, Kai Chen, and Dahua Lin. InternIm-math: Open math large language models toward verifiable reasoning, 2024b.
- Longhui Yu, Weisen Jiang, Han Shi, Jincheng Yu, Zhengying Liu, Yu Zhang, James T. Kwok, Zhenguo Li, Adrian Weller, and Weiyang Liu. Metamath: Bootstrap your own mathematical questions for large language models. In *ICLR*. OpenReview.net, 2024.
- Kunhao Zheng, Jesse Michael Han, and Stanislas Polu. minif2f: a cross-system benchmark for formal olympiad-level mathematics. In *ICLR*. OpenReview.net, 2022.
- Denny Zhou, Nathanael Schärli, Le Hou, Jason Wei, Nathan Scales, Xuezhi Wang, Dale Schuurmans, Claire Cui, Olivier Bousquet, Quoc V. Le, and Ed H. Chi. Least-to-most prompting enables complex reasoning in large language models. In *ICLR*. OpenReview.net, 2023.
- Xinyu Zhu, Junjie Wang, Lin Zhang, Yuxiang Zhang, Yongfeng Huang, Ruyi Gan, Jiaxing Zhang, and Yujiu Yang. Solving math word problems via cooperative reasoning induced language models. In *ACL* (1), pages 4471–4485. Association for Computational Linguistics, 2023.

# Appendix

### **A** Experiment Details

### A.1 The detail of the Universal Text Template

Universal Template Designed for Multi-paradigm Reasoning.			
### Problem:			
[Statement of the problem]			
-			
Let's go through this step-by-step:			
1. [Step 1 description]			
2.[Step 2 description]			
3. [Step 3 description]			
$\checkmark$ [Verification or conclusion of the step-by-step reasoning]			
Let's write the corresponding formal proof in Lean 4 to prove th ### Formal proof in Lean 4	is:		
[Lean 4 code for formal proof]			
	[Lean 4 Output]		
Let's use Python to perform these calculations: ### Code in Python			
[Python code for calculation]			
	[Python Output]		
[Summary of the solution and key takeaways]			

Figure 7: The universal text template designed for multi-paradigm reasoning. The contents for each paradigm have been omitted.

As shown in Figure 7, we apply the designed universal text template on all training samples.

### A.2 Example Prompts for Dataset Enhancement

To guide LLMs in generating and refining reasoning paradigms during dataset enhancement, we developed specific prompts  $(p_s)$  tailored to each seed dataset. These prompts provide structured instructions for the models to follow, ensuring the generation of high-quality and logically consistent reasoning paradigms.

Figure 9 and Figure 8 provide examples of such prompts designed for augmenting and refining formal proofs within the Lean 4 theorem prover for the Numina-TIR and Lean-Workbook datasets,

**Example Prompts for TIR Dataset Enhancement** 

#### **System Prompt:**

You are an expert in Lean 4. Please respond to a math problem by translating the provided informal proof into Lean 4 code. Follow the format provided in the prompt. Please note that the informal proof and the formal proof need to be identical. Follow the format provided in the prompt. **User Input:** 

Now please translate the formal solution in Lean 4 following the instructions below. Please write the corresponding solution in Lean 4 (indicated by "Formal proof in Lean 4: ") given the "# Problem: " and "# Informal proof: ", filling in the "# Formal proof in Lean 4: " section.

You must respond in the following format: # Problem: ... # Informal proof: ... # Formal proof in Lean 4: ```lean4 (lean 4 code for proving) ... Here are examples you may refer to: N few-shot examples # Problem: {problem}

# Informal proof: {informal\_proof}
# Formal proof in Lean 4:

```lean4 ...

Figure 8: Example prompts for Numina-TIR dataset enhancement. The few-shot examples provided for the LLM have been omitted.

respectively. The prompt specifies the input and output format and includes placeholders for the problem statement, informal proof, and corresponding formal proof in Lean 4. It also incorporates  $N_{\text{shot}}$  few-shot examples to further guide the model. In our experiments, consistent with the common settings employed in [Jiang et al., 2023, Yang et al., 2024], we use  $N_{\text{shot}} = 8$ . This structured approach and setting are adapted and applied to all datasets to ensure comprehensive coverage and logical consistency across the enhanced dataset.

#### A.3 Details of Training Settings

In all stages of the PPT method, a learning rate of 2e - 5 and a warm-up ratio of 1% are implemented. To enhance computational efficiency, the training process is conducted using distributed optimization with DeepSpeed ZeRO Stage 3 [Rajbhandari et al., 2020] and is combined with Flash-Attention [Dao, 2024]. Stage ① comprises 3 epochs, whereas the satge ② and ③ are conducted over 4 epochs. A sequence length of 2, 048 tokens is used in Stages ① and ②, which is increased to 4, 096 tokens in Stage ③ to support more complex reasoning tasks. Furthermore, we employ an annealing strategy at the end of Stage ③ with high-quality MPM samples, with the aim of further enhancing model accuracy in complex reasoning tasks.

#### A.4 Benchmarks

We report the statistics of the evaluation datasets in Table 6.

#### Example Prompts for Lean-Workbook Dataset Enhancement

#### System Prompt:

You are an expert in Lean 4 and formal mathematics. Your task is to explain how to construct formal proofs using Lean 4 syntax and tactics. Focus on the Lean 4 approach to theorem proving, rather than traditional mathematical reasoning.

### **User Input:**

Please follow the instructions below to convert the Lean 4 code (indicated by "Formal proof in Lean 4: ") into its informal proof, using the informal problem (indicated by "Problem: ") as a guide. Please write the corresponding informal solution in natural language (indicated by "Informal proof: ") given the "# Problem: " and "# Formal proof in Lean 4: ", filling in the "# Informal proof: " section. <Instruction>

Analyze the given mathematical theorem and the corresponding Lean 4 code. Provide a detailed explanation of the proof process, adhering to the following guidelines:

1. Theorem structure: Clearly state the theorem, including its assumptions and conclusion.

2. Proof strategy: Explain the overall strategy employed in the proof, focusing on logical reasoning and mathematical deduction rather than calculation.

3. Step-by-step reasoning: Provide a detailed, step-by-step explanation of the proof process, ensuring that each step corresponds to an element in the Lean 4 code.

4. Logical deduction: Emphasize how each step of the proof follows logically from the previous steps or from the given assumptions.

5. Mathematical concepts: Discuss any specific mathematical concepts, notations, or definitions used in the proof, such as divisibility or exponentiation.

6. Abstraction: Present the proof in a general, abstract form that could be applied to similar problems, rather than focusing on specific numerical calculations.

7. Correspondence to code: Ensure that the logical flow of your proof explanation aligns with the structure and tactics used in the Lean 4 code, without explicitly mentioning Lean-specific terminology. Avoid using syntax or terminology specific to formal proof systems. Instead, focus on presenting a rigorous mathematical argument using general logical principles and mathematical language. The proof should follow the reasoning path implied by the Lean 4 code but be accessible to readers unfamiliar with formal proof assistants.

</Instruction>

You must respond in the following format: # Problem: ...

# Tags: ...

# Formal proof in Lean 4:

```lean4
(lean 4 code for proving)

. . .

# Informal proof: (Informal reasoning path for proving the problem) Here are examples you may refer to:

#### N few-shot examples

# Problem: {problem}

# Tags: {tag}
# Formal proof in Lean 4:

```lean4

{lean\_workbook code}

• • •

# Informal proof: ...

Figure 9: Example pompts for Lean-Workbook dataset enhancement. The few-shot examples provided for the LLM have been omitted.

| Dataset       | # of Test set  | Avg. Length  |
|---------------|----------------|--------------|
| MATH<br>GSM8K | 5,000<br>1,319 | 30.7<br>46.3 |
| MiniF2f       | 244            | 30.5         |

Table 6: The statistics of the evaluation datasets.

### A.5 Details of Metrics

This study employs the pass@N metric on the MiniF2F benchmark, with the evaluation grounded in a sample budget of N. To ensure a fair comparison of computational cost across different generation schemes, this paper defines the sample budget according to the following rules.

- For single-pass sampling methods, we define the sample budget N as the total number of proofs generated, with large values of N factorized for ease of comparison to tree search methods.
- For best-first-search methods, following the notation in Llemma [Azerbayev et al., 2024], we present  $N = N_{\text{att}} \times N_{\text{tact}} \times N_{\text{iter}}$  where  $N_{\text{att}}$  denotes the number of best-first-search attempts,  $N_{\text{tact}}$  denotes the number of tactics generated for each expansion, and  $N_{\text{iter}}$  denotes the number of expansion iterations.
- For tree-based search methods, e.g., RMaxTS [Xin et al., 2024] and HTPS [Lample et al., 2022], we present  $N = N_{\text{att}} \times N_{\text{ex}}$ , where  $N_{\text{att}}$  denotes the number of tree search attempts, and  $N_{\text{ex}}$  denotes the number of model generations invoked in tree expansions.
- For our SMPS, we define the sample budget as  $N = N_{\rm NLR} \times N_{\rm SR}$ , where  $N_{\rm NLR}$  denotes the number of initial semantic reasoning paths, and  $N_{\rm SR}$  denotes the number of symbolic reasoning paths extended for each other reasoning paradigm.

## **B** Additional Analysis

### **B.1** The Risk of Data Leakage

We measure the Levenshtein distance [Miller et al., 2009] between problems in the training dataset and those in the test dataset to mitigate the risk of data leakage. During the experiments, we set a similarity threshold of 0.7 and excluded cases from the training dataset that exceeded this threshold. As a result, approximately 1,000 cases, accounting for less than 0.6% of our training dataset, were removed to prevent potential leakage.

### **B.2** Different Evaluation Strategies on Arithmetic Benchmarks

Table 7: Zero-shot results of different evaluation strategies across MATH and GSM8k benchmarks.

| Model                                 | MA             | TH             | GSM8k          |                |
|---------------------------------------|----------------|----------------|----------------|----------------|
|                                       | Pass@1         | Maj@8          | Pass@1         | Maj@8          |
| Llama-3.1-8B<br>DeepSeek-Math-Base-7B | 58.18<br>66.74 | 59.46<br>71.70 | 84.00<br>88.70 | 87.26<br>91.43 |

Table 7 explores the impact of various evaluation strategies on the CoR framework. The majority vote strategy benefits the CoR framework. Specifically, a majority vote strategy with 8 candidate samples on GSM8K can exceed GPT-4o's Pass@1 performance (90.5%).