# Code Readability in the Age of Large Language Models: An Industrial Case Study from Atlassian

Wannita Takerngsaksiri Monash University Melbourne, Australia

> Jirat Pasuksmit Atlassian Australia

Micheal Fu The University of Melbourne Melbourne, Australia

> Kun Chen Atlassian United States

Chakkrit Tantithamthavorn Monash University Melbourne, Australia

> Ming Wu Atlassian United States

facilitates better comprehension of its functionality [19] but also

els have demonstrated remarkable results across various software

development tasks [42] (e.g., code completion [37, 38], test case gen-

eration [2, 35], code review automation [17, 20, 30, 40], vulnerability

detection and repair [10–12]). Recently, there has been a growing

interest in integrating LLMs into modern Integrated Development

Environments (IDEs) (e.g., GitHub Copilot [13]) to assist software

engineers in implementing new features, improving code quality,

fixing bugs, and resolving software development tasks.

In the age of large language models (LLMs) for code, these mod-

significantly reduces software maintenance costs.

# ABSTRACT

Programmers spend a significant amount of time reading code during the software development process. This trend is amplified by the emergence of large language models (LLMs) that automatically generate code. However, little is known about the readability of the LLM-generated code and whether it is still important from practitioners' perspectives in this new era. In this paper, we conduct a survey to explore the practitioners' perspectives on code readability in the age of LLMs and investigate the readability of our LLM-based software development agents framework, *HULA*, by comparing its generated code with human-written code in real-world scenarios. Overall, the findings underscore that (1) readability remains a critical aspect of software development; (2) the readability of our LLM-generated code is comparable to human-written code, fostering the establishment of appropriate trust and driving the broad adoption of our LLM-powered software development platform.

## **KEYWORDS**

Code Readability, Large Language Models, Practitioner's Perceptions

#### **ACM Reference Format:**

Wannita Takerngsaksiri, Micheal Fu, Chakkrit Tantithamthavorn, Jirat Pasuksmit, Kun Chen, and Ming Wu. 2025. Code Readability in the Age of Large Language Models: An Industrial Case Study from Atlassian. In *Companion Proceedings of the 33rd ACM Symposium on the Foundations of Software Engineering (FSE '25), June 23–27, 2025, Trondheim, Norway.* ACM, New York, NY, USA, 6 pages. https://doi.org/10.1145/nnnnnn.nnnnnn

## **1 INTRODUCTION**

Code readability has long been a key focus in software engineering research [3, 8, 9, 19, 24, 39]. For example, Minelli *et al.* found that programmers dedicate approximately 70% of their time to reading and understanding source code [26]. Similarly, as Guido Van Rossum, the creator of Python, has noted: *"Code is read more of-ten than it is written"*[15]. Thus, writing readable code not only

FSE '25, June 2025, Trondheim, Norway

https://doi.org/10.1145/nnnnnnnnnnnn

At Atlassian, code readability has always been a cornerstone of software development, as it plays a critical role in facilitating software evolution and maintenance. In the age of large language models (LLMs), like those integrated into Jira (a task management platform) [4], the importance of code readability is amplified. Readable code ensures that teams can efficiently collaborate, debug, and enhance their software, reducing technical debt and long-term costs. Recently, we introduced HULA, a human-in-the-loop software development agents framework powered by large language models [36]. While HULA aims to streamline development tasks, a crucial question arises: does readability retain its value in this LLMassisted paradigm, and if so, why? Additionally, how readable is the code it generates compared to human-written code? Understanding and ensuring code readability in LLM-generated code is vital for Atlassian, since it directly impacts the productivity and satisfaction

In this paper, we aim to investigate the practitioners' perceptions on the importance, the challenges, and the state of practice of code readability, and investigate the readability of LLM-generated code and human-written code in the context of enterprise software development tasks. Thus, we address the following two RQs.

of software development teams, enabling teams to work efficiently.

# RQ1) How and why code readability is important in the age of large language models for code?

Through an online survey of 118 practitioners, we found that 81% of practitioners agreed that code readability is important. The key motivation is to reduce maintenance costs in the long term, while the key challenging factor is time constraints. Although code readability is currently improved via code review comments, 72% of practitioners agreed to consider adopting LLMs as an alternative. 39% of practitioners perceived that LLM-generated code is more readable than human-written code, followed by 34% perceived that the readability of both LLM-generated and human-written code

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

<sup>@</sup> 2025 Copyright held by the owner/author(s). Publication rights licensed to ACM. ACM ISBN 978-x-xxxx-x/YY/MM

is similar. These findings suggest that code readability is still critically important in the age of large language models.

# RQ2) How readable is the LLM-generated code compared to human-written code?

Through an examination of the readability of code generated by our LLM-powered code generation (HULA [36], powered by GPT-4 [28]) and human-written code using our 144 internal Jira software development tasks, we found that the readability of LLM-generated code is comparable to humanwritten code (with a negligible to small effect size difference) based on various measurements (e.g., lines of code, code complexity, comment to code ratio). These findings demonstrate that the LLM-generated code can closely resemble human-written code in terms of readability.

**Paper Organization.** Section 2 presents the motivation and related work. Section 3 and Section 4 present the approach and results of RQ1 and RQ2, respectively. Section 5 discloses the threats to the validity of our study, while Section 6 draws the conclusion.

### 2 MOTIVATION AND RELATED WORKS

In this section, we discuss motivation and related work to formulate the research questions.

*Motivation*. Code readability is a cornerstone of software development at Atlassian, particularly as we integrate LLMs into Jira and other platforms [4, 36]. With the adoption of LLM-powered tools, the size and complexity of codebases are expected to grow rapidly as the majority of the codebase could be generated by LLMs [14]. This paradigm shift raises concerns among Atlassian software engineers and customers regarding the readability of LLM-generated code, which may increase technical debts, incur maintenance costs, and negatively affect enterprise coding standards. Therefore, it is of utmost importance to understand whether readability retains its value in this LLM-assisted paradigm, and if so, why? And, how readable is LLM-generated code compared to human-written code?

**Related Works**. Code readability is a property that influences how easily a given piece of code can be read and understood [5]. Over the past 20 years [3, 8, 9, 19, 24, 39], prior studies have focused on investigating factors influencing code readability and developing metrics, models, and tools to quantify code readability. For example, Buse and Weimer [5, 6] found that the average lines of code and average number of identifiers per line are closely associated with code readability. Similarly, Posnett *et al.* [31] identified associations between readability and metrics such as the number of lines, Halstead Volume, and character entropy. Furthermore, Scalabrino *et al.* [32, 33] emphasized that readability is influenced not only by code structure but also by textual features such as code comments. Moreover, Alawad *et al.* [3] observed a negative correlation between readability and code complexity, reporting that higher complexity is often associated with lower readability.

In the age of large language models (LLMs), studying code readability is more crucial than ever. While LLMs have now been seamlessly integrated into software development tools, workflows, and platforms like GitHub Copilot [13], IntelliJ IDEA [18], Chat-GPT [28], and Atlassian's Jira AI [4, 36], they also introduce new challenges. Practitioners often raised concerns about the quality of LLM-generated code. For example, Liu *et al.* [21] found that 47% of ChatGPT-generated code snippets suffer from maintainability issues. Majdinasab *et al.* [22] discovered that 27% of code suggested by GitHub Copilot contains code vulnerabilities. Similarly, Perry *et al.* [29] found that users who had access to an AI assistant wrote significantly less secure code than those without access. Such concerns often lead to a lack of trust in the adoption of LLM-powered software development tools.

While many studies flag issues on LLM-generated code in the security aspect, it is still unclear on the readability aspect of how readable is LLM-generated code compared to human-written code. Recently, Madi [1] found that code generated by GitHub Copilot is comparable in complexity and readability to code written by human pair programmers in the live coding of a controlled environment. However, little is known about the code readability of LLM-generated code on production in real-world scenarios and how the practitioners perceived code readability in the age of large language models. The importance of code readability and the gap in literature lead us to formulate the following research questions: **(RQ1)** *How and why code readability is important in the age of large language models for code?* and **(RQ2)** *How readable is the LLM-generated code compared to human-written code?* 

# 3 (RQ1) HOW AND WHY CODE READABILITY IS IMPORTANT IN THE AGE OF LARGE LANGUAGE MODELS FOR CODE?

#### 3.1 Approach

The practitioners' survey aims to explore four main topics of code readability: the importance, the challenges, the state of practice and the readability of LLM-generated code. In this section, we describe the design of our survey study and the participant selection process.

**Survey.** We design the 15-minute Google Form with four main sections: the importance of code readability, the challenges of code readability, the state of code readability, and the readability of LLM-generated code. The themes for the Likert scales of agreement questions (e.g., motivations for code readability) are derived from the literature review. Specifically, we categorized factors identified in the literature into themes, which formed the design of our survey questions (i.e., Q1.3, Q2.2, Q3.1). The full list of our survey questions and themes can be found on our GitHub repository [34]. Lastly, the survey obtained Ethical Permission from the Monash University Human Research Ethics Committee (MUHREC, Project ID 42299) before conducting the research.

**Participant.** We recruit participants through advertisements within Atlassian and public channels, including social media platforms like programming-related Facebook groups and personal LinkedIn networks. The participants can opt-in to win one of three gift cards of \$20 as a token of appreciation. Finally, during 3 weeks of advertisement in June 2024, we received 118 survey responses with diverse backgrounds. We summarize the attributes of our participants' demographic in Figure 1.

## 3.2 Results

Table 1 to 4 show the results of this research question, covering four themes of code readability based on 118 practitioners' responses.

Code Readability in the Age of Large Language Models: An Industrial Case Study from Atlassian



Figure 1: The Demographic of Participants in RQ1 (n=118).

*The Importance:* 81% of practitioners agree that code readability is important and the top motivation to improve code readability is to reduce maintenance cost and effort in the long term. Table 1 shows that 56% of practitioners answered spending more than half of their time reading code in their professional practice, while 81% of them were aware of the importance of code readability. Particularly, the top three motivations to prioritize code readability are to reduce maintenance costs, to help the debugging process, and to improve code comprehension.

*The Challenges:* 79% of practitioners agree that the top challenging factor preventing them from prioritizing code readability is time constraints due to project deadlines. Table 2 shows that 70% of practitioners answered they always or often prioritize code readability in their professional practice. However, the top three factors that prevent them from prioritizing the improvement of code readability are the time constraints of project deadlines, the complexity of the codebase or legacy code, and the focus on code functionality over code readability.

The State of Practice: While manually improving code readability is still a dominant method with 68% of practitioners selection, 72% of practitioners agree to consider adopting LLMs to improve code readability. Table 3 shows that the most popular method for improving code readability in professional practice is still done manually by either peer review (41%) or selfimprovement (27%). However, 17% of the practitioners have started to adopt LLMs to improve the code readability. The majority of them indicated that they used ChatGPT (n=12) as a tool. In fact, 72% of the practitioners are open to adopting LLMs to improve code. Additionally, the top three factors that practitioners consider when improving code readability are the descriptive naming variables and functions, the comments and documentation, and the complexity of functions or files.

The Readability of LLM-generated Code: 39% of practitioners answer they perceive the LLM-generated code as more readable than the human-written code. Table 4 shows that 54% of practitioners answered using LLMs to generate or complete code more than half of their time in professional practice, indicating the current trend of high usage in LLM-generated code. Meanwhile, 39% of practitioners answered they perceive the LLM-generated code as more readable than the human-written code, followed by 34% of them answered both are similarly readable. The top justifications from the follow-up open-text question are logic complexity (n=25), code length (n=15), a number of loop conditions (n=12) and code structure/format (n=12). Specifically, a practitioner who voted LLM-generated code as more readable indicated that "Human code has too many logic conditions to check". On the other hand, a practitioner who voted Human code as more readable indicates that "I find it easier to follow along." Interestingly, some practitioners reason that "Actually, Human code is easier to understand in terms of solution, but having a lot of nested loop and conditions makes it harder to read and debug.", indicates that understanding code and reading code can be as well on the different scales of decision.

# 4 (RQ2) HOW READABLE IS THE LLM-GENERATED CODE COMPARED TO HUMAN-WRITTEN CODE?

### 4.1 Approach

The empirical study aims to understand code readability via static code analysis. In this section, we describe the design of our case study on HULA [36] over our internal dataset.

Large Language Model. We evaluate the code readability using our Human-in-the-loop Software Development Agents framework, *HULA* [36]. HULA is Atlassian's LLM-based agents framework for software development available internally in Jira Software. Specifically, the framework is used to generate a code patch given a code repository and a description of the Jira issue to be resolved. In this version, HULA uses GPT-4 [28] as a based LLM and the framework is evaluated without additional human feedback.

**Datasets.** We evaluate HULA via the *internal dataset* [36], which includes a set of completed software development tasks (i.e., Jira issues, repositories and corresponding pull requests from BitBucket) at Atlassian. The dataset consists of 144 Jira issues with 250 coding files spanning six programming languages: TypeScript, Java, Kotlin, Python, Go and Scala.

**Code Readability Measurement.** Following the recent study on code readability [1], we cautiously select the following eight static analysis metrics that are language-agnostic (i.e., can be used in multilingual) via the Multimetric library[41].

First, we use *Line of Code* to evaluate the total number of lines of code in the file and *Comment Ratio* to evaluate the percentage of the lines of comment to code. Then, *Cyclomatic Complexity* [25] is used to evaluate the number of decision paths of the code, expressing the code complexity. Next, *Maintainability Index* [27] is used to measure how maintainable the code is. Lastly, we utilize *Halstead Metrics* [16], a set of metrics designed to quantify various aspects of code. These metrics are employed to evaluate key attributes, including *Difficulty* (the difficulty of the program to write or understand), *Vocabulary* (the number of unique operators and unique operands

Wannita Takerngsaksiri, Micheal Fu, Chakkrit Tantithamthavorn, Jirat Pasuksmit, Kun Chen, and Ming Wu

## Table 1: (RQ1) The Importance of Code Readability from Practitioners' Perspective.

	The Importance of Code Readability		
Q1.1	How much of your time is devoted to reading code in your professional practice?	65%	%
	Always (>75%) Often (50-75%) Sometimes (25-50)	0%) Rarely (<25%) Never (0%)	
Q1.2	How important is code readability in your opinion?	81% 7%	70
Q1.3	What motivates you to prioritize code readability		
	improvement in your professional practice?		
A.	Improve code comprehension for oneself and others.	85%	6
B.	Reduce maintenance cost and effort in the long term.	90% 5%	7 0
C.	Facilitate reusable and scalable development process.	76% 9%	7 0
D.	Enhance productivity and collaboration in the team.	81% 5%	70
Е.	Reflect professionalism, aesthetic and industrial standard.	72%	70
F.	Help debugging and troubleshooting process.	87% 6%	6
			-

Strongly Agree Agree Neutral Disagree Strongly Disagree

# Table 2: (RQ1) The Challenges of Code Readability from Practitioners' Perspective.

	The Challenges of Code Readability			
Q2.1	How often do you prioritize code readability in your pro-	70%		4%
	fessional practice?			
	Always (>75%) Often (50-75%) Sometimes (25-509	%) 📕 Rai	rely (<25%) Never (0%)	
		,		
Q2.2	What factors prevent you from prioritizing the improve-			
	ment of code readability in your professional practice?			
А.	Time constraints due to project deadlines.	79%		9%
В.	Focus on code functionality over code readability.	65%		16%
C.	Focus on other performance metrics (e.g., speed and efficiency).	58%		17%
D.	Complexity of the codebase or legacy code makes the code	70%		17%
	readability improvement challenging.			
Е.	Resistance from team members or stakeholders.	61%		22%
F.	Limited resource or support on standards or best practices on	63%		20%
	code readability improvement.			

Strongly Agree Agree Neutral Disagree Strongly Disagree

## Table 3: (RQ1) The State of Code Readability from Practitioners' Perspective.

	The State of Code Readability		
Q3.1	What are the factors you consider when improving the		
	code readability?		
A.	Code length (e.g., length of identifier, line, function, file, etc.)	71%	11%
В.	Code structure/format (e.g., indentation, use of brackets, etc.)	77%	7%
C.	Code style/standard (e.g., PEP8, ESLint, Linter, etc.)	74%	11%
D.	Comment and documentation	84%	4%
Е.	Descriptive naming variable/function	86%	4%
F.	Function/file complexity	82%	5%
Q3.2	Would you consider adopting LLMs to improve code read-	72%	8%
	ability?		
	Strongly Agree Agree Neutral Disagree	Strongly Disagree	
Q3.3	How do you improve your code readability in your pro-	68%	29%

fessional practice?

Manually by peer review comments Manually self-improve code Mixed Static tools AI-based tools

#### Table 4: (RQ1) The Readability of LLM-generated Code from Practitioners' Perspective.

	The Readability of LLM-generated Code		
Q4.1	How often do you use LLMs for code genera-	54%	25%
	tion/completion in your professional practice?		
	Always (>75%) Often (50-75%) Sometimes (25-50	%) Rarely (<25%) Never (0%)	
Q4.2	To what extent do you think LLM-generated code is read-	27%	39%
	able compared to human code in professional practice?		

Human-written code is more readable
Both are similar
LLM-generated code is more readable

Table 5: (RQ2) The mean significance from Mann-Whitney U Test [23] and Effect Size measured by the Cliff's Delta [7] based on the comparison of HULA and Human code.

Metric	P-Value	Effect Size
Line of Code	< 0.001	0.230 (small)
Comment Ratio	0.005	0.124
Cyclomatic Complexity	0.622	0.015
Maintainability Index	< 0.001	-0.225 (small)
Halstead Difficulty	< 0.001	0.201 (small)
Halstead Vocabulary	< 0.001	0.202 (small)
Halstead Volume	< 0.001	0.208 (small)
Halstead Time	< 0.001	0.205 (small)

occurrence), *Volume* (the program length and vocabulary size), and *Time Required* (the estimated time for implementation).

### 4.2 Results

Figure 2 shows the results of this research question, covering the case study of HULA on our internal dataset. Table 5 shows the statistical significance and the effect size of the result.

Our case study on the HULA framework reveals that the generated code is comparable to the human-written code, with only minor differences. Figure 2 shows that HULA, with a GPT-4 based model, generates code that is highly similar to humans with only a slightly longer code but with no statistically significant difference in Cyclomatic Complexity and comment ratio. On Halstead's metrics, our LLM-generated code has marginally higher values on difficulty, vocabulary, volume, and time required. These results indicate that the HULA framework can produce code that closely resembles human-written code in terms of code readability, indicating the promising performance of LLM in production.

## **5 THREAT TO VALIDITY**

*Threats to internal validity.* We use an online survey to study practitioners' perceptions of code readability. We design the questions based on literature reviews to mitigate the hallucination on factors related to code readability. However, we acknowledge the limitations that the justifications might be beyond the literature review which we sourced from.

*Threats to external validity.* Our survey was derived from the perceptions of 118 practitioners with different backgrounds and work experiences in coding (see Figure 1). Nonetheless, we



Figure 2: (RQ2) The Scores of Code Readability Measures between HULA-generated and Human-written Code.

acknowledge that the results may differ when surveying different population groups. Additionally, the empirical study is a case study of our HULA framework, we acknowledge that the results may differ when experimenting with different models and datasets.

*Threat to construct validity.* We use an empirical study with static code analysis as a proxy for code readability measurement between LLM-generated and Human code. We cautiously follow the existing work on selecting the metrics representing code readability. However, we acknowledge the limitations that the metrics might not completely represent the code readability from all perspectives.

## 6 CONCLUSION AND IMPLICATIONS

In this paper, we investigate the practitioners' perceptions on the importance, the challenges, and the state of practice of code readability, and investigate the readability of LLM-generated code and human-written code in the context of enterprise software development tasks. Our findings underscore that readability remains a critical aspect of software development, even in the age of large language models (LLMs). Moreover, the code generated by our LLM-powered framework, HULA, is shown to be comparable in readability to human-written code. This supports the establishment of appropriate trust and drives the broad adoption of our LLM-powered software development platform. Practitioners can confidently integrate LLMs into their workflows, knowing that code readability will not be compromised. This fosters more effective teamwork, simplifies maintenance tasks, and ensures the long-term success of software projects. FSE '25, June 2025, Trondheim, Norway

## REFERENCES

- Naser Al Madi. 2022. How readable is model-generated code? examining readability and visual inspection of github copilot. In *Proceedings of the 37th IEEE/ACM International Conference on Automated Software Engineering*. 1–5.
- [2] Saranya Alagarsamy, Chakkrit Tantithamthavorn, and Aldeida Aleti. 2024. A3Test: Assertion-augmented automated test case generation. *Information and Software Technology* 176 (2024), 107565.
- [3] Duaa Alawad, Manisha Panta, Minhaz Zibran, and Md Rakibul Islam. 2019. An empirical study of the relationships between code readability and software complexity. arXiv preprint arXiv:1909.01760 (2019).
- [4] Atlassian. 2024. AI-Powered. Developer-Led. https://www.atlassian.com/solutions/ devops/ai-innovation
- [5] Raymond PL Buse and Westley R Weimer. 2008. A metric for software readability. In Proceedings of the 2008 international symposium on Software testing and analysis. 121–130.
- [6] Raymond PL Buse and Westley R Weimer. 2009. Learning a metric for code readability. IEEE Transactions on software engineering 36, 4 (2009), 546–558.
- [7] Norman Cliff. 1993. Dominance statistics: Ordinal analyses to answer ordinal questions. *Psychological bulletin* 114, 3 (1993), 494.
- [8] Ron Coleman. 2018. Aesthetics versus readability of source code. International Journal of Advanced Computer Science and Applications 9, 9 (2018).
- [9] Sarah Fakhoury, Yuzhan Ma, Venera Arnaoudova, and Olusola Adesope. 2018. The effect of poor source code lexicon and readability on developers' cognitive load. In Proceedings of the 26th conference on program comprehension. 286–296.
- [10] Michael Fu and Chakkrit Tantithamthavorn. 2022. Linevul: A transformer-based line-level vulnerability prediction. In Proceedings of the 19th International Conference on Mining Software Repositories. 608–620.
- [11] Michael Fu, Chakkrit Tantithamthavorn, Trung Le, Yuki Kume, Van Nguyen, Dinh Phung, and John Grundy. 2024. AIBugHunter: A Practical tool for predicting, classifying and repairing software vulnerabilities. *Empirical Software Engineering* (2024). https://doi.org/10.1007/s10664-023-10346-3
- [12] Michael Fu, Chakkrit Tantithamthavorn, Trung Le, Van Nguyen, and Dinh Phung. 2022. VulRepair: a T5-based automated software vulnerability repair. In Proceedings of the 30th ACM joint european software engineering conference and symposium on the foundations of software engineering. 935–947.
- [13] GitHub. 2021. Your AI pair programmer. https://github.com/features/copilot
- [14] Adam Gospodarczyk. 2024. Up to 90% of my code is now generated by AI. https: //www.techsistence.com/p/up-to-90-of-my-code-is-now-generated
- [15] Alyssa Coghlan <ncoghlan at gmail.com> Guido van Rossum <guido at python.org>, Barry Warsaw <barry at python.org>. 2001. PEP 8 - Style Guide for Python Code. https://peps.python.org/pep-0008/
- [16] Maurice H Halstead. 1977. Elements of Software Science (Operating and programming systems series). Elsevier Science Inc.
- [17] Yang Hong, Chakkrit Tantithamthavorn, Patanamon Thongtanunam, and Aldeida Aleti. 2022. Commentfinder: a simpler, faster, more accurate code review comments recommendation. In Proceedings of the 30th ACM joint European software engineering conference and symposium on the foundations of software engineering. 507–519.
- [18] Jetbrains. 2024. The Leading Java and Kotlin IDE. https://www.jetbrains.com/idea/
- [19] John Johnson, Sergio Lubo, Nishitha Yedla, Jairo Aponte, and Bonita Sharif. 2019. An empirical study assessing source code readability in comprehension. In 2019 IEEE International conference on software maintenance and evolution (ICSME). IEEE, 513–523.
- [20] Zhiyu Li, Shuai Lu, Daya Guo, Nan Duan, Shailesh Jannu, Grant Jenks, Deep Majumder, Jared Green, Alexey Svyatkovskiy, Shengyu Fu, et al. 2022. CodeReviewer: Pre-training for automating code review activities. arXiv preprint arXiv:2203.09095 (2022).
- [21] Yue Liu, Thanh Le-Cong, Ratnadira Widyasari, Chakkrit Tantithamthavorn, Li Li, Xuan-Bach D Le, and David Lo. 2024. Refining chatgpt-generated code: Characterizing and mitigating code quality issues. ACM Transactions on Software Engineering and Methodology 33, 5 (2024), 1–26.
- [22] Vahid Majdinasab, Michael Joshua Bishop, Shawn Rasheed, Arghavan Moradidakhel, Amjed Tahir, and Foutse Khomh. 2024. Assessing the Security of GitHub

Copilot's Generated Code-A Targeted Replication Study. In 2024 IEEE International Conference on Software Analysis, Evolution and Reengineering (SANER). IEEE, 435-444.

- [23] Henry B Mann and Donald R Whitney. 1947. On a test of whether one of two random variables is stochastically larger than the other. *The annals of mathematical statistics* (1947), 50–60.
- [24] Umme Ayda Mannan, İftekhar Ahmed, and Anita Sarma. 2018. Towards understanding code readability and its impact on design quality. In Proceedings of the 4th ACM SIGSOFT International Workshop on NLP for Software Engineering. 18–21.
- [25] Thomas J McCabe. 1976. A complexity measure. IEEE Transactions on software Engineering 4 (1976), 308–320.
- [26] Roberto Minelli, Andrea Mocci, and Michele Lanza. 2015. I Know What You Did Last Summer - An Investigation of How Developers Spend Their Time. In 2015 IEEE 23rd International Conference on Program Comprehension. 25–35. https://doi.org/10.1109/ICPC.2015.12
- [27] P. Oman and J. Hagemeister. 1992. Metrics for assessing a software system's maintainability. In Proceedings Conference on Software Maintenance 1992. 337–344. https://doi.org/10.1109/ICSM.1992.242525
- [28] OpenAI. 2023. GPT-4 Technical Report. arXiv:2303.08774 [cs.CL]
- [29] Neil Perry, Megha Srivastava, Deepak Kumar, and Dan Boneh. 2023. Do users write more insecure code with AI assistants?. In Proceedings of the 2023 ACM SIGSAC Conference on Computer and Communications Security. 2785–2799.
- [30] Chanathip Pornprasit and Chakkrit Tantithamthavorn. 2024. Fine-Tuning and Prompt Engineering for Large Language Models-based Code Review Automation. Information and Software Technology (2024).
- [31] Daryl Posnett, Abram Hindle, and Premkumar Devanbu. 2011. A simpler model of software readability. In Proceedings of the 8th working conference on mining software repositories. 73–82.
- [32] Simone Scalabrino, Mario Linares-Vásquez, Rocco Oliveto, and Denys Poshyvanyk. 2018. A comprehensive model for code readability. *Journal of Software: Evolution and Process* 30, 6 (2018), e1958.
- [33] Simone Scalabrino, Mario Linares-Vasquez, Denys Poshyvanyk, and Rocco Oliveto. 2016. Improving code readability models with textual features. In 2016 IEEE 24th International Conference on Program Comprehension (ICPC). IEEE, 1–10.
- [34] Wannita Takerngsaksiri. 2025. awsm-research/CodeReadability-GenAI. https: //github.com/awsm-research/CodeReadability-GenAI
- [35] Wannita Takerngsaksiri, Rujikorn Charakorn, Chakkrit Tantithamthavorn, and Yuan-Fang Li. 2024. PyTester: Deep Reinforcement Learning for Text-to-Testcase Generation. arXiv preprint arXiv:2401.07576 (2024).
- [36] Wannita Takerngsaksiri, Jirat Pasuksmit, Patanamon Thongtanunam, Chakkrit Tantithamthavorn, Ruixiong Zhang, Fan Jiang, Jing Li, Evan Cook, Kun Chen, and Ming Wu. 2025. Human-In-the-Loop Software Development Agents. *ICSE SEIP* (2025).
- [37] Wannita Takerngsaksiri, Chakkrit Tantithamthavorn, and Yuan-Fang Li. 2024. Syntax-aware on-the-fly code completion. *Information and Software Technology* 165 (2024), 107336.
- [38] Wannita Takerngsaksiri, Cleshan Warusavitarne, Christian Yaacoub, Matthew Hee Keng Hou, and Chakkrit Tantithamthavorn. 2024. Students' Perspectives on AI Code Completion: Benefits and Challenges. In 2024 IEEE 48th Annual Computers, Software, and Applications Conference (COMPSAC). 1606–1611. https://doi.org/10.1109/COMPSAC61105.2024.00252
- [39] Yahya Tashtoush, Zeinab Odat, Izzat M Alsmadi, and Maryan Yatim. 2013. Impact of programming features on code readability. (2013).
- [40] Patanamon Thongtanunam, Chanathip Pornprasit, and Chakkrit Tantithamthavorn. 2022. Autotransform: Automated code transformation to support modern code review process. In Proceedings of the 44th international conference on software engineering. 237–248.
- [41] Konrad Weihmann. 2024. priv-kweihmann/multimetric. https://github.com/privkweihmann/multimetric
- [42] Wayne Xin Zhao, Kun Zhou, Junyi Li, Tianyi Tang, Xiaolei Wang, Yupeng Hou, Yingqian Min, Beichen Zhang, Junjie Zhang, Zican Dong, et al. 2023. A survey of large language models. arXiv preprint arXiv:2303.18223 (2023).