# TAD-Bench: A Comprehensive Benchmark for Embedding-Based Text Anomaly Detection

Yang Cao<sup>1,2</sup>, Sikun Yang<sup>1,2</sup>, Chen Li<sup>3</sup>, Haolong Xiang<sup>4</sup>, Lianyong Qi<sup>5</sup>, Bo Liu<sup>6</sup>, Rongsheng Li<sup>7</sup>, Ming Liu<sup>8</sup>,

<sup>1</sup>School of Computing and Information Technology, Great Bay University, China

<sup>2</sup>Great Bay Institute for Advanced Study, Great Bay University, China

<sup>3</sup>Graduate School of Informatics, Nagoya University, Japan

<sup>4</sup>School of Software, Nanjing University of Information Science and Technology, China

<sup>5</sup>College of Computer Science and Technology China University of Petroleum (East China), China

<sup>6</sup>College of Cyberspace Security, Zhengzhou University, China

<sup>7</sup>School of Computer, Harbin Engineering University, China

<sup>8</sup>School of IT, Deakin University, Australia

## Abstract

Text anomaly detection is crucial for identifying spam, misinformation, and offensive language in natural language processing tasks. Despite the growing adoption of embedding-based methods, their effectiveness and generalizability across diverse application scenarios remain under-explored. To address this, we present TAD-Bench, a comprehensive benchmark designed to systematically evaluate embeddingbased approaches for text anomaly detection. TAD-Bench integrates multiple datasets spanning different domains, combining state-ofthe-art embeddings from large language models with a variety of anomaly detection algorithms. Through extensive experiments, we analyze the interplay between embeddings and detection methods, uncovering their strengths, weaknesses, and applicability to different tasks. These findings offer new perspectives on building more robust, efficient, and generalizable anomaly detection systems for real-world applications.

## 1 Introduction

Anomaly detection is a critical task in machine learning, with applications ranging from fraud detection and content moderation to user behavior analysis (Pang et al., 2021). Within natural language processing (NLP), anomaly detection has become increasingly relevant for identifying outliers such as harmful content, phishing attempts, and spam reviews. However, while AD tasks in structured data (e.g., tabular, time series, graphs) (Steinbuss and Böhm, 2021; Blázquez-García et al., 2021; Qiao et al., 2024) have achieved significant maturity, anomaly detection in the unstructured and high-dimensional domain of text remains underexplored. The complexity of textual data-driven by its diverse syntactic, semantic, and pragmatic structures-presents unique challenges for robust

anomaly detection.

The rise of deep learning and transformer-based models has revolutionized natural language processing (NLP), enabling the development of contextualized embeddings that encode rich semantic and syntactic information. Techniques such as BERT (Devlin et al., 2019) and OpenAI's text-embedding models (OpenAI, 2024) have demonstrated remarkable success across a wide range of NLP tasks, offering dense, high-dimensional representations that effectively capture linguistic nuances. These embeddings have become a cornerstone for many downstream tasks, providing powerful tools for applications such as text classification (da Costa et al., 2023) and retrieval (Zhu et al., 2023). Their ability to generalize across tasks and domains has positioned them as a promising foundation for more complex challenges, including anomaly detection.

In recent years, embedding-based methods have gained significant attention in anomaly detection tasks, particularly for capturing deviations in textual data. While promising, several challenges remain unaddressed. Existing studies often lack systematic evaluations of how different embeddings perform across diverse anomaly types, raising questions about their generalization capabilities in complex, real-world scenarios such as multilingual settings or domain-specific anomalies. Recent efforts, such as AD-NLP (Bejan et al., 2023) and NLP-ADBench (Li et al., 2024), have significantly advanced anomaly detection in NLP. AD-NLP provides valuable insights into different types of anomalies, while NLP-ADBench expands evaluations to a wide range of algorithms and datasets. However, AD-NLP evaluates few detection algorithms while NLP-ADBench considers only a few embedding methods, respectively. Our work aims to move beyond simply filling these gaps, by systematically exploring the following questions:

- What types of tasks are LLM embeddings paired with anomaly detectors most suitable for, and where do they face limitations?
- Which embedding methods consistently excel across different anomaly detection tasks?
- Which anomaly detection algorithms perform robustly across various embeddings and tasks?

In this work, we introduce TAD-Bench, a benchmark for text anomaly detection. Our goal is to provide a more comprehensive evaluation of latest embeddings, anomaly detectors, and their combinations, offering actionable insights for diverse NLP scenarios. By incorporating a broader selection of embedding models and evaluating an extensive array of anomaly detection methods, our benchmark enables a thorough understanding of their performance on static datasets, with a focus on robustness and generalizability.

The main contributions of this work are summarized as follows:

- Proposes TAD-Bench, a benchmark integrating diverse datasets for text anomaly detection across domains such as spam, fake news, and offensive language.
- Conducts a systematic evaluation of LLMbased embeddings and anomaly detection algorithms, revealing their relative strengths and weaknesses.
- Provides insights into effective embeddingdetector configurations for improving robustness and generalizability in NLP anomaly detection tasks.

## **2 Problem Definitions**

In the context of NLP, an anomaly refers to a text instance that exhibits characteristics or patterns that are significantly different from the majority of the dataset. Such anomalies can manifest in various ways, including rare topics, unusual syntax or semantics, domain-specific jargon, or even intentionally manipulated language, such as spam, fake news, or offensive content. Detecting these anomalies is critical for numerous applications, such as content moderation, fraud detection, and identifying novel or emerging patterns in large text corpora.

Formally, let  $\mathcal{D} = \{x_1, x_2, \dots, x_N\}$  represent a corpus of N textual instances, where each instance  $x_i \in \mathcal{X}$  is a sequence of tokens:

 $x_i = [t_1, t_2, \dots, t_{L_i}]$ , and  $L_i$  denotes the sequence length. The goal of NLP-AD is to identify a subset of instances  $\mathcal{D}_{anomaly} \subset \mathcal{D}$ , such that  $\mathcal{D}_{anomaly}$ contains samples that deviate significantly from the majority of the dataset  $\mathcal{D}_{normal} = \mathcal{D} \setminus \mathcal{D}_{anomaly}$ .

To achieve this, an anomaly detection algorithm  $g : \mathbb{R}^d \to \mathbb{R}$  is applied to the representations of the textual instances. (1) Each text instance  $x_i$  is first mapped to a fixed-dimensional vector  $\mathbf{z}_i \in \mathbb{R}^d$  using an embedding model  $\phi : \mathcal{X} \to \mathbb{R}^d$ , such that  $\mathbf{z}_i = \phi(x_i)$ . (2) The anomaly detection algorithm then assigns an anomaly score  $s_i = g(\mathbf{z}_i)$  to each instance. Based on a predefined threshold  $\tau$ , an instance  $x_i$  is classified as anomalous if:

$$x_i \in \mathcal{D}_{\text{anomaly}} \iff s_i \ge \tau.$$

The objective of NLP-AD is to ensure that g effectively distinguishes between normal and anomalous instances, even in the absence of labeled data, while being robust to the inherent variability and high dimensionality of textual data.

## **3** Related Work

Embedding-based text anomaly detection typically involves two stages: extracting representations from text using pre-trained language models and detecting anomalies using dedicated algorithms. In this section, we review prior work on these two aspects to provide context for our benchmark.

### 3.1 Text representations

The development of text representations extraction techniques has been fundamental to progress in natural language processing (NLP). Early methods like TF-IDF (Term Frequency-Inverse Document Frequency) (Salton and Buckley, 1988) represented text in sparse vector spaces by measuring word importance relative to a corpus. While interpretable and computationally efficient, TF-IDF could not capture semantic relationships between words. Later, dense embeddings such as Word2Vec (Mikolov, 2013) and GloVe (Pennington et al., 2014) addressed this limitation by mapping words into continuous vector spaces based on their cooccurrence patterns in large corpora. However, these embeddings were static, assigning the same vector to a word regardless of its context.

To overcome the limitations of static embeddings, contextualized embeddings were introduced, with models like ELMo (Embeddings from Language Models) (Peters et al., 2018) producing word representations that vary based on context. This innovation was further advanced by transformerbased models like BERT (Bidirectional Encoder Representations from Transformers) (Devlin et al., 2019), which used bidirectional attention mechanisms to simultaneously capture left and right context. BERT set new benchmarks in NLP and inspired numerous improvements, including RoBERTa (Zhuang et al., 2021) and ALBERT (Lan et al., 2020).

More recently, large language models such as GPT (Generative Pre-trained Transformer (Brown et al., 2020) have pushed the boundaries of embedding methods. These models, trained on massive datasets, produce versatile embeddings that capture both semantic and generative properties of text. LLMs have demonstrated unprecedented performance across a wide range of NLP tasks, establishing them as dominant tools for text representation in various applications, including anomaly detection.

## 3.2 Anomaly Detection

Existing anomaly detection methods can be broadly categorized into 6 classes: distance, density, isolation, statistical, projection and deep learning-based approaches. Each category offers distinct advantages and is suited for different types of data distributions and anomaly patterns.

Distance-based methods, such as k-Nearest Neighbors (kNN) (Ramaswamy et al., 2000), identify anomalies by measuring the distance of a given data point to its nearest neighbors. Points that are far from their neighbors are considered anomalous. These methods are intuitive and straightforward but suffer from the curse of dimensionality in highdimensional spaces, where distances lose their discriminative power, reducing their effectiveness.

Density-based methods identify points with significantly lower local density compared to their surroundings as anomaly. Local Outlier Factor (LOF) (Breunig et al., 2000) measures the local density of a point relative to its neighbors. Histogram-Based Outlier Score (HBOS) (Goldstein and Dengel, 2012) estimates densities using histograms for individual features.

Isolation-based methods assume anomalies are rare and different, Isolation Forest (iForest) (Liu et al., 2008, 2012), detect anomalies by recursively partitioning the feature space where anomalies require fewer partitions than normal points. Improved techniques, such as iNNE (Isolation-based

Table 1: Dataset description. Nor. and Ano. stand for Normal and Anomaly.

Dataset	# Samples	# Nor.	# Ano.	% Ano.
Email Spam	3578	3432	146	4.0805
SMS Spam	4969	4825	144	2.8980
COVID-Fake	1173	1120	53	4.5183
LIAR2	2130	2068	62	2.9108
OLID	641	620	21	3.2761
Hate Speech	4287	4163	124	2.8925

Nearest Neighbor Ensembles) (Bandaragoda et al., 2018), use hypersphere to partition data space and assigns larger hyperspheres to anomalies, improving robustness in detecting local anomalies.

Probabilistic and statistical methods identify anomalies based on deviations from the data distribution. ECOD (Li et al., 2022) uses cumulative distribution functions for efficient anomaly scoring, while COPOD (Li et al., 2020) leverages copulas to model feature dependencies, handling multivariate data effectively. Projection-based methods, such as One-Class SVM (OCSVM) (Schölkopf et al., 2001), separate normal and anomalous data by learning a decision boundary in a high-dimensional feature space. While effective for complex distributions.

Deep learning-based methods train on normal data to learn representations, identifying anomalies as deviations. Approaches like Deep SVDD (Ruff et al., 2018) and LUNAR (Goodge et al., 2022) capture nonlinear patterns but require substantial data and computational resources.

## **4** Benchmark Settings

#### 4.1 Datasets

The limited availability of purpose-built datasets constrains the development and evaluation of effective methods in NLP-AD. To address this gap, we curated and transformed 6 existing classification datasets from three common NLP domains: spam detection, fake news detection, and offensive language detection. By selecting datasets from diverse domains, we aim to explore the applicability of embedding-based anomaly detection methods across different NLP scenarios.

Anomalies, as defined in our problem, are inherently rare. However, due to the lack of dedicated datasets for text anomaly detection, we adapted classification datasets by designating specific classes as anomalies and down-sampling them to simulate realistic anomaly rates. For each dataset, the anomaly rate was set to approximately 3%, reflecting the typical rarity of anomalies in real-world scenarios.

Unlike traditional text classification tasks, no additional preprocessing was applied to the source text, as any token, word, or symbol could potentially carry critical information indicative of an anomaly. By preserving the original text in its raw form, we aim to retain all features that may contribute to the detection of anomalous patterns. Table 1 shows the statistics of the 6 pre-processed datasets used in this benchmark and their description are shown as follows:

**Email-Spam** (Metsis et al., 2006) contains 5,171 emails labeled as spam or ham, with spam treated as the anomaly class. We utilized the preprocessed version provided in (Li et al., 2024).

**SMS-Spam** (Almeida et al., 2011) comprises 5,574 SMS messages originally labeled as spam or ham. Spam messages are designated as the anomaly.

**COVID-Fake** (Das et al., 2021) comprises posts collected from social media platforms and fact-checking websites. Real news items were sourced from verified outlets providing accurate COVID-19 information, while fake news was gathered from tweets, posts, and articles containing misinformation about COVID-19. Fake news is treated as the anomaly class.

**LIAR2** (Xu and Kechadi, 2024) consists of approximately 23,000 statements manually labeled by professional fact-checkers for fake news detection tasks. The "True" class, representing accurate statements, is considered the normal class, while the "Pants on Fire" class, representing highly misleading statements, is treated as the anomaly.

**OLID** contains 14,200 annotated English tweets, categorized using a three-level annotation model. For this benchmark, only the Level A (Offensive Language Detection) annotations are used, where tweets labeled as offensive are considered as anomalies, and non-offensive tweets are considered as normal.

**Hate-Speech** (Davidson et al., 2017) contains tweets annotated by CrowdFlower users. The tweet content is used as data, with "hate speech" treated as anomalies.

## 4.2 Embedding Models

Table 2 summarizes the embedding models employed in this paper. To extract high-quality embeddings from the datasets, 8 embedding models were utilized. These include **BERT** (*bert-base-uncased*), MiniLM (all-MiniLM-L6-v2), LLAMA (Llama-3.2-1B), stella (stella\_en\_400M\_v5), and Qwen (Qwen2.5-1.5B) from the HuggingFace platform, as well as OpenAI-provided models: O-ada (textembedding-ada-002), O-small (text-embedding-3small), and **O-large** (text-embedding-3-large). All these models are based on the Transformer architecture, which has become the standard for representation learning in NLP tasks. The OpenAI models (O-ada, O-small, O-large) are specifically designed for embedding generation, offering embeddings with varying levels of granularity. On the other hand, LLAMA and Qwen are primarily auto-regressive language models optimized for text generation. In this paper, we repurposed these models for embedding extraction by computing the attention-weighted mean of their last hidden states, ensuring that only valid tokens contribute to the final sentence embeddings.

Notably, LLAMA and Qwen were constrained to a maximum token length of 512 tokens, same as BERT, due to computational resource limitations. Other models, such as MiniLM, Stella, and the OpenAI embeddings, utilized automatic truncation to process longer input sequences. This limitation may restrict LLAMA and Qwen's ability to fully leverage their extended context capabilities, particularly for datasets with longer text instances, such as LIAR2 and Hate-Speech. However, this unified token length ensures a fair comparison of runtime efficiency across models under consistent experimental conditions. It also highlights the trade-offs between computational cost and embedding quality, particularly when resource constraints are a factor in model deployment.

#### 4.3 Anomaly Detectors

The embeddings derived from these models were subsequently used as input features for anomaly detection algorithms. To identify anomalous instances, we employed 8 state-of-the-art anomaly detection methods sourced from the *PyOD* library<sup>1</sup> (Zhao et al., 2019). These algorithms include **KNN**, **LOF**, **OCSVM**, **iForest**, **INNE**, **ECOD**, **HBOS** and **COPOD**. These algorithms were selected to capture diverse anomaly detection paradigms, ensuring robust detection across varying dataset characteristics.

<sup>&</sup>lt;sup>1</sup>PyOD: https://pyod.readthedocs.io/en/latest/ index.html

Models	Max Tokens	# Dimensions	# Parameters	
BERT	512	768	110 M	
MINILM	512	384	22.7 M	
O-ada	8191	1536	350 M	
O-small	8191	1536	125 M	
O-large	8191	3072	1.3 B	
LLAMA	4096	2048	1 B	
stella	2048	1024	400 M	
Qwen	8192	1536	1.5 B	

Table 2: Embedding Models Overview. M and B are for million and billion, respectively.

For reproducibility and consistency, the default hyperparameter settings provided in the respective algorithm implementations and original papers were adopted. This approach minimizes user bias and allows for a fair comparison of algorithm performance when applied to the embeddings generated by the different models. The combination of diverse embedding models and anomaly detection algorithms ensures a comprehensive evaluation of text anomaly detection in terms of both computational efficiency and detection effectiveness.

#### 4.4 Evaluation Criteria and Trials

Performance was evaluated using the Area Under the Receiver Operating Characteristic Curve (AU-ROC), which is a widely used criteria in anomaly detection tasks. Each experiment was conducted 5 times, and the average AUROC was reported to ensure result reliability.

The entire pipeline, including embedding extraction and anomaly detection, was implemented in PyTorch. Experiments were executed on a computational setup equipped with a Ryzen 9 5900X 12-core CPU for data preprocessing and model orchestration, and an Nvidia RTX 3060 GPU with 12GB of memory for model inference and embedding generation.

### **5** Experiments

## 5.1 Applicability of LLM Embeddings with Anomaly Detectors

Table 1 summarizes the performance of various anomaly detectors combined with LLM-derived embeddings across different datasets, while Figure 1 highlights their strong performance in specific tasks, particularly spam detection. In both the email spam and SMS spam detection tasks (Figure 1a and Figure 1d, many embedding-detector combinations achieve high AUC scores, with several exceeding 0.8. This strong performance can be attributed to the explicit nature of spam-related features, such as the presence of URLs, nonsensical text, or repetitive patterns. An example from the Email Spam dataset is shown below:

Subject: oxycconttin no script needeeed your place to ggo too for all ur prreexxxiscrlpt 10 n pi sx , paaaaain killerzxss noeoo presscippt http : // hyyydroccodeeeine vicccodinne / vic geeet reeeliefff noowee http : // offfmeebabyy

These features are effectively represented in the semantic spaces created by general-purpose embeddings, enabling anomaly detectors to distinguish spam messages from legitimate ones. Additionally, the relatively small variance in detection performance across embeddings suggests that spam detection relies on surface-level linguistic patterns that are well captured by the embeddings used in this study.

For fake news detection, the results indicate a more mixed performance across datasets. On the Covid Fake News dataset (Figure 1b, multiple embedding-detector combinations achieve AUC scores close to or exceeding 0.8, suggesting that these methods are capable of identifying subtle stylistic and linguistic differences between fake and real news. These differences may include deviations in tone, phrasing, or structural composition of the text. However, on the LIAR2 dataset (Figure 1e, the AUC scores exhibit much greater variability across different combinations of embeddings and detectors. This variability likely stems from the greater factual complexity of the LIAR2 dataset, where detecting anomalies may require external knowledge or sophisticated reasoning that is not inherently encoded within the embeddings. Despite this variability, the relatively strong performance on the Covid Fake News dataset underscores the potential of embedding-based approaches for fake news detection, particularly when the anomalies are stylistic or linguistic in nature.

In contrast, the performance on hate speech and offensive language detection tasks (Figure 1c and Figure 1f) is consistently weaker, with AUC scores rarely exceeding 0.6 across embedding-detector combinations. This suggests that the embeddings struggle to capture the nuanced and contextdependent features necessary for these tasks. For

Embeddings	Detectors	Email-Spam	SMS-Spam	<b>COVID-Fake</b>	LIAR2	Hate-Speech	OLID	Average
8	kNN	0.7625	0.4484	0.8467	0.6594	0.5033	0.5137	0.6223
	OCSVM	0.7362	0.6323	0.7867	0.6237	0.4866	0.4866	0.6254
	IForest	0.7152	0.6323	0.7701	0.6051	0.4925	0.4783	0.6129
BERT	LOF	0.6786	0.3230	0.8713	0.6717	0.4632	0.4703	0.5841
DERI	FCOD	0.7309	0.6235	0.7722	0.6175	0.4889	0.4973	0.6211
	INNE	0.730	0.6295	0.8012	0.6362	0.4850	0.4740	0.6366
	HROS	0.7145	0.6251	0.7698	0.6100	0.4035	0.4740	0.5317
	COPOD	0.6454	0.5020	0.7098	0.6242	0.4933	0.5002	0.5317
		0.0434	0.3727	0.7714	0.0242	0.4971	0.5063	0.5214
	OCSVM	0.9414	0.5180	0.7843	0.7449	0.3004	0.3003	0.6406
	IForest	0.0078	0.5915	0.7645	0.0470	0.4607	0.4520	0.6105
MINII M	LOF	0.9078	0.5472	0.7433	0.3930	0.4097	0.4331	0.0193
IVIIINILIVI	LOF	0.5587	0.5024	0.7433	0.0804	0.3078	0.3422	0.3891
	LCOD	0.9525	0.5954	0.7381	0.0332	0.3780	0.4208	0.6201
	INNE	0.9320	0.5757	0.8033	0.0001	0.4223	0.4624	0.0491
	HBUS	0.9478	0.0137	0.7441	0.6447	0.3888	0.4310	0.5387
		0.9453	0.0317	0.7410	0.0095	0.3710	0.4037	0.5375
		0.8865	0.3212	0.9094	0.7921	0.6341	0.5243	0.6779
	UCSVM	0.9310	0.8221	0.8143	0./169	0.4807	0.5048	0./116
<u> </u>	IForest	0.8872	0.7376	0.7432	0.6421	0.4632	0.4891	0.6604
O-ada	LOF	0.3808	0.5033	0.7316	0.7541	0.4328	0.5376	0.5567
	ECOD	0.9380	0.8822	0.8150	0.7200	0.4610	0.4986	0.7191
	INNE	0.8507	0.8031	0.8533	0.7378	0.4820	0.5102	0.7062
	HBOS	0.9433	0.8813	0.8164	0.7186	0.4583	0.5098	0.6182
	COPOD	0.9502	0.8759	0.8153	0.7201	0.4513	0.4811	0.6134
	kNN	0.8921	0.2290	0.9400	0.7756	0.6416	0.5587	0.6728
	OCSVM	0.9475	0.5755	0.8932	0.7024	0.4577	0.5547	0.6885
O-small	IForest	0.9058	0.6177	0.8085	0.5973	0.5025	0.5580	0.6650
	LOF	0.3863	0.5257	0.7809	0.7489	0.4139	0.5581	0.5690
	ECOD	0.9481	0.6301	0.8808	0.7022	0.4249	0.5295	0.6859
	INNE	0.8673	0.6080	0.9185	0.7198	0.4491	0.5382	0.6835
	HBOS	0.9522	0.6273	0.8719	0.7008	0.4245	0.5157	0.5846
	COPOD	0.9605	0.5722	0.8664	0.6974	0.4017	0.4963	0.5706
	kNN	0.8292	0.1698	0.9537	0.7687	0.6291	0.5497	0.6500
	OCSVM	0.9403	0.5630	0.8924	0.6621	0.4260	0.4971	0.6635
	IForest	0.8999	0.5297	0.8041	0.5687	0.4516	0.5068	0.6268
O-large	LOF	0.4048	0.4719	0.8233	0.7356	0.3833	0.5167	0.5559
	ECOD	0.9487	0.6422	0.8875	0.6540	0.3959	0.4967	0.6708
	INNE	0.8230	0.5970	0.9261	0.6876	0.4197	0.5170	0.6617
	HBOS	0.9538	0.6525	0.8849	0.6404	0.3835	0.4989	0.5734
	COPOD	0.9639	0.6798	0.8854	0.6536	0.3537	0.4980	0.5763
	kNN	0.8715	0.3655	0.8668	0.7229	0.4991	0.4081	0.6223
	OCSVM	0.9023	0.7379	0.8132	0.6892	0.4774	0.4057	0.6710
	IForest	0.8962	0.7275	0.7833	0.6860	0.4647	0.4082	0.6610
Llama	LOF	0.6056	0.4053	0.8673	0.7274	0.4376	0.3972	0.5734
	ECOD	0.8844	0.7573	0.7819	0.6989	0.4643	0.3998	0.6644
	INNE	0.9122	0.7065	0.8160	0.6935	0.4702	0.3917	0.6650
	HBOS	0.9017	0.7895	0.7758	0.7064	0.4580	0.3898	0.5745
	COPOD	0.9153	0.8163	0.7584	0.7291	0.4435	0.3526	0.5736
	kNN	0.8654	0.3212	0.9034	0.6884	0.4746	0.5016	0.6258
stella	OCSVM	0.8922	0.7165	0.8063	0.5103	0.3729	0.4439	0.6237
	IForest	0.8862	0.7377	0.7738	0.4999	0.3545	0.4325	0.6141
	LOF	0.3931	0.4733	0.7129	0.6549	0.4036	0.5285	0.5277
	ECOD	0.9075	0.7894	0.8115	0.5023	0.3421	0.4395	0.6321
	INNE	0.8271	0.6926	0.8366	0.5330	0.3325	0.4532	0.6125
	HBOS	0.9178	0.8017	0.8086	0.4952	0.3355	0.4252	0.5406
	COPOD	0.9300	0.8589	0.8167	0.4936	0.3018	0.3797	0.5401
	kNN	0.8618	0.2110	0.8438	0.6626	0.5163	0.4602	0.5926
Qwen	OCSVM	0.8804	0.6229	0.7868	0.6216	0.4916	0.4882	0.6486
	IForest	0.8829	0.6195	0.7686	0.6155	0.4825	0.4869	0.6427
	LOF	0.6043	0.3600	0.8555	0.6894	0.4600	0.4518	0.5702
	ECOD	0.8678	0.6648	0.7680	0.6172	0.4852	0.4773	0.6467
	INNE	0.8839	0.5940	0.7833	0.6339	0.4902	0.4693	0.6424
	HBOS	0.8854	0.6877	0.7638	0.6170	0.4847	0.4685	0.5582
	COPOD	0.9044	0.7393	0.7463	0.6291	0.4794	0.4336	0.5617

Table 3: Evaluation across 6 datasets in terms of ROC-AUC.



Figure 1: Boxplot of AUCROC scores for anomaly detectors on different embeddings across six datasets.

example, hate speech often involves implicit cues such as sarcasm, cultural references, or indirect hostility, which may not be adequately represented in the embeddings. Similarly, offensive language detection, as seen in the OLID dataset, requires distinguishing fine-grained differences in tone or intent, such as the distinction between neutral, offensive, or subjective language. These distinctions often depend on broader contextual information, such as the discourse or dialogue in which the language appears. These distinctions often depend on broader contextual information, such as the discourse or dialogue in which the language appears. For example, without additional context, such as the speaker's intent or the conversational background, the following statement from OLID dataset remains ambiguous whether this statement qualifies as hate speech:

@USER #metoo are all racist!

## 5.2 Comparative Effectiveness of Embeddings in Anomaly Detection

The results in Table 3 demonstrate the remarkable capabilities of the OpenAI family of embeddings (O-ada, O-small, and O-large), consistently outperforming other embeddings across a variety of anomaly detection tasks. Specifically, O-ada achieves the highest average AUC scores with the ECOD detector (0.8822) on the SMS Spam dataset and with kNN (0.7921) on the LIAR2 dataset. Similarly, O-small demonstrates outstanding performance, achieving the highest AUC scores with kNN on the Hate Speech (0.6416) and OLID (0.5587) datasets. Additionally, O-large secures top AUC scores with COPOD (0.9639) on the Email Spam dataset and with kNN (0.9537) on the COVID Fake News dataset.

In comparison, other embeddings, such as MINILM, exhibit strong performance in specific tasks but lack consistency across more complex datasets. For instance, MINILM achieves exceptional AUC scores of 0.9526 and 0.9626 on the Email Spam datasets, respectively, when used with INNE and OCSVM. However, its performance drops significantly on datasets like OLID and LIAR2, indicating limitations in handling tasks where deeper contextual or domain-specific cues are required. Similarly, embeddings such as stella and Qwen show moderate performance, excelling in a limited subset of tasks but failing to achieve the same level of versatility as the OpenAI embeddings.

These observations suggest that the OpenAI embeddings, particularly O-small and O-large, provide the most robust and consistent performance across a wide range of tasks. Their ability to effectively represent both explicit textual features (e.g., spam detection tasks) and subtle contextual variations (e.g., Covid Fake News and OLID) underscores their suitability for anomaly detection scenarios that require both surface-level semantic



Figure 2: Average rank (lower the better) of 3 differernt OpenAI embeddings-based methods on AUCROC across 6 datasets

extraction and deeper linguistic understanding.

Moreover, the collective performance of the OpenAI family emphasizes the adaptability and efficacy of transformer-based embeddings in addressing anomaly detection challenges across datasets with diverse linguistic and semantic complexities. OpenAI embeddings consistently emerge as dominant and versatile solutions in various scenarios, making them highly effective for a wide range of applications.

## 5.3 Performance Across Anomaly Detectors

To evaluate the robustness of anomaly detection algorithms across various embeddings and tasks, we analyze their average rankings using OpenAI embeddings (O-ada, O-small, and O-large) as representative examples (Figure 2). These embeddings were selected based on their strong and consistent performance across datasets, as demonstrated in Section 5.2. The rankings provide insight into which detection algorithms perform reliably regardless of the embedding or task.

Across all three embeddings, kNN and INNE consistently rank as the top-performing algorithms. This indicates their robustness and adaptability to the semantic structures of LLM-derived embeddings. kNN, in particular, excels due to its ability to effectively model local density variations in feature space, making it well-suited for both explicitpattern tasks like spam detection and nuanced tasks like fake news and hate speech detection. INNE, with its efficiency and strong generalization capabilities, complements kNN as a reliable alternative in diverse anomaly detection scenarios.

ECOD also ranks highly, consistently appearing among the top three detectors across embeddings. Its lightweight design and ability to estimate density-based anomalies make it a strong candidate for scenarios where computational efficiency is critical. On the other hand, methods like LOF, COPOD, and iForest consistently rank lower, highlighting their limitations in high-dimensional and semantically complex embedding spaces. These methods struggle with noise, data sparsity, and the nuanced patterns encoded in LLM embeddings, which limits their effectiveness across diverse tasks.

Overall, kNN, INNE, and ECOD demonstrate robust and consistent performance across embeddings and tasks, making them well-suited for general-purpose anomaly detection pipelines. In contrast, methods like LOF, COPOD, and iForest show weaker adaptability, likely due to their limitations in handling high-dimensional and semantically rich embeddings.

## 6 Conclusion

In this work, we present a comprehensive benchmark for embedding-based anomaly detection in natural language processing, evaluating the interplay between large language model (LLM) embeddings and classical anomaly detection algorithms across three diverse domains: spam detection, fake news detection, and offensive language detection. Our results reveal both the strengths and limitations of LLM embeddings, demonstrating their effectiveness in tasks with explicit patterns but highlighting challenges in capturing implicit, context-dependent anomalies.

### **Limitations and Future Works**

TAD-Bench evaluates anomaly detection across three domains: spam detection, fake news detection, and offensive language detection. While these tasks provide diverse and relevant benchmarks, they do not fully capture the complexity of realworld applications. Strong performance in spam detection highlights the ability of LLM embeddings to capture explicit patterns, while mixed results in fake news detection and poor performance in offensive language detection reveal their limitations in modeling implicit, context-sensitive cues. Expanding to domains like medical, financial, or legal texts that involve unique challenges, and exploring datasets with more implicit anomalies, could better evaluate the adaptability and robustness of these methods.

In addition, our work uses pre-trained LLM embeddings and default hyperparameters for anomaly detectors, ensuring consistency but potentially underestimating their best-case performance. Finetuning LLMs on domain-specific data could improve embedding quality, while systematic hyperparameter optimization might unlock the full potential of anomaly detectors. Future research should explore these directions, leveraging techniques like AutoML to streamline both embedding fine-tuning and parameter tuning, thereby achieving more competitive performance.

Moreover, TAD-Bench focuses solely on embedding-based methods, excluding end-to-end approaches that directly process raw text. While embeddings offer modularity and efficiency, end-toend models like autoencoders or transformer-based systems may capture richer contextual information and handle more complex anomalies. Future work should incorporate end-to-end models and explore hybrid approaches that combine the strengths of both paradigms, providing a more comprehensive evaluation of anomaly detection methods in NLP.

## **Ethic Statement**

All the data and information in this paper are from public source.

## References

- Tiago A Almeida, José María G Hidalgo, and Akebo Yamakami. 2011. Contributions to the study of sms spam filtering: new collection and results. In *Proceedings of the 11th ACM symposium on Document engineering*, pages 259–262.
- Tharindu R Bandaragoda, Kai Ming Ting, David Albrecht, Fei Tony Liu, Ye Zhu, and Jonathan R Wells. 2018. Isolation-based anomaly detection using nearest-neighbor ensembles. *Computational Intelligence*, 34(4):968–998.
- Matei Bejan, Andrei Manolache, and Marius Popescu. 2023. Ad-nlp: A benchmark for anomaly detection in natural language processing. In *Proceedings of the* 2023 Conference on Empirical Methods in Natural Language Processing, pages 10766–10778.
- Ane Blázquez-García, Angel Conde, Usue Mori, and Jose A Lozano. 2021. A review on outlier/anomaly detection in time series data. *ACM computing surveys* (*CSUR*), 54(3):1–33.

- Markus M Breunig, Hans-Peter Kriegel, Raymond T Ng, and Jörg Sander. 2000. Lof: identifying densitybased local outliers. In *Proceedings of the 2000 ACM SIGMOD international conference on Management of data*, pages 93–104.
- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.
- Liliane Soares da Costa, Italo L Oliveira, and Renato Fileto. 2023. Text classification using embeddings: a survey. *Knowledge and Information Systems*, 65(7):2761–2803.
- Sourya Dipta Das, Ayan Basak, and Saikat Dutta. 2021. A heuristic-driven ensemble framework for covid-19 fake news detection. In *Combating Online Hostile Posts in Regional Languages during Emergency Situation: First International Workshop, CONSTRAINT* 2021, Collocated with AAAI 2021, Virtual Event, February 8, 2021, Revised Selected Papers 1, pages 164–176. Springer.
- Thomas Davidson, Dana Warmsley, Michael Macy, and Ingmar Weber. 2017. Automated hate speech detection and the problem of offensive language. In *Proceedings of the international AAAI conference on web and social media*, volume 11, pages 512–515.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.
- Markus Goldstein and Andreas Dengel. 2012. Histogram-based outlier score (hbos): A fast unsupervised anomaly detection algorithm. *KI-2012: poster and demo track*, 1:59–63.
- Adam Goodge, Bryan Hooi, See-Kiong Ng, and Wee Siong Ng. 2022. Lunar: Unifying local outlier detection methods via graph neural networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pages 6737–6745.
- Zhenzhong Lan, Mingda Chen, Sebastian Goodman, Kevin Gimpel, Piyush Sharma, and Radu Soricut. 2020. Albert: A lite bert for self-supervised learning of language representations. *Preprint*, arXiv:1909.11942.
- Yuangang Li, Jiaqi Li, Zhuo Xiao, Tiankai Yang, Yi Nian, Xiyang Hu, and Yue Zhao. 2024. Nlpadbench: Nlp anomaly detection benchmark. *arXiv preprint arXiv:2412.04784*.

- Zheng Li, Yue Zhao, Nicola Botta, Cezar Ionescu, and Xiyang Hu. 2020. Copod: copula-based outlier detection. In 2020 IEEE international conference on data mining (ICDM), pages 1118–1123. IEEE.
- Zheng Li, Yue Zhao, Xiyang Hu, Nicola Botta, Cezar Ionescu, and George H Chen. 2022. Ecod: Unsupervised outlier detection using empirical cumulative distribution functions. *IEEE Transactions on Knowledge and Data Engineering*, 35(12):12181–12193.
- Fei Tony Liu, Kai Ming Ting, and Zhi-Hua Zhou. 2008. Isolation forest. In 2008 eighth ieee international conference on data mining, pages 413–422. IEEE.
- Fei Tony Liu, Kai Ming Ting, and Zhi-Hua Zhou. 2012. Isolation-based anomaly detection. ACM Transactions on Knowledge Discovery from Data (TKDD), 6(1):1–39.
- Vangelis Metsis, Ion Androutsopoulos, and Georgios Paliouras. 2006. Spam filtering with naive bayeswhich naive bayes? In *CEAS*, volume 17, pages 28–69. Mountain View, CA.
- Tomas Mikolov. 2013. Efficient estimation of word representations in vector space. *arXiv preprint arXiv:1301.3781*, 3781.
- OpenAI. 2024. New embedding models and api updates.
- Guansong Pang, Chunhua Shen, Longbing Cao, and Anton Van Den Hengel. 2021. Deep learning for anomaly detection: A review. *ACM computing surveys (CSUR)*, 54(2):1–38.
- Jeffrey Pennington, Richard Socher, and Christopher D Manning. 2014. Glove: Global vectors for word representation. In *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)*, pages 1532–1543.
- Matthew E. Peters, Mark Neumann, Mohit Iyyer, Matt Gardner, Christopher Clark, Kenton Lee, and Luke Zettlemoyer. 2018. Deep contextualized word representations. In Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers), pages 2227–2237, New Orleans, Louisiana. Association for Computational Linguistics.
- Hezhe Qiao, Hanghang Tong, Bo An, Irwin King, Charu Aggarwal, and Guansong Pang. 2024. Deep graph anomaly detection: A survey and new perspectives. *arXiv preprint arXiv:2409.09957*.
- Sridhar Ramaswamy, Rajeev Rastogi, and Kyuseok Shim. 2000. Efficient algorithms for mining outliers from large data sets. In *Proceedings of the 2000 ACM SIGMOD international conference on Management of data*, pages 427–438.

- Lukas Ruff, Robert Vandermeulen, Nico Goernitz, Lucas Deecke, Shoaib Ahmed Siddiqui, Alexander Binder, Emmanuel Müller, and Marius Kloft. 2018. Deep one-class classification. In *International conference on machine learning*, pages 4393–4402. PMLR.
- Gerard Salton and Christopher Buckley. 1988. Termweighting approaches in automatic text retrieval. *Information processing & management*, 24(5):513– 523.
- Bernhard Schölkopf, John C Platt, John Shawe-Taylor, Alex J Smola, and Robert C Williamson. 2001. Estimating the support of a high-dimensional distribution. *Neural computation*, 13(7):1443–1471.
- Georg Steinbuss and Klemens Böhm. 2021. Benchmarking unsupervised outlier detection with realistic synthetic data. ACM Transactions on Knowledge Discovery from Data (TKDD), 15(4):1–20.
- Cheng Xu and M-Tahar Kechadi. 2024. An enhanced fake news detection system with fuzzy deep learning. *IEEE Access*, 12:88006–88021.
- Yue Zhao, Zain Nasrullah, and Zheng Li. 2019. Pyod: A python toolbox for scalable outlier detection. *Journal of Machine Learning Research*, 20(96):1–7.
- Yutao Zhu, Huaying Yuan, Shuting Wang, Jiongnan Liu, Wenhan Liu, Chenlong Deng, Haonan Chen, Zheng Liu, Zhicheng Dou, and Ji-Rong Wen. 2023. Large language models for information retrieval: A survey. *arXiv preprint arXiv:2308.07107*.
- Liu Zhuang, Lin Wayne, Shi Ya, and Zhao Jun. 2021. A robustly optimized BERT pre-training approach with post-training. In *Proceedings of the 20th Chinese National Conference on Computational Linguistics*, pages 1218–1227, Huhhot, China. Chinese Information Processing Society of China.