Multi-terminal Strong Coordination over Noisy Channels with Encoder Cooperation

Viswanathan Ramachandran, Tobias J. Oechtering and Mikael Skoglund Division of Information Science and Engineering KTH Royal Institute of Technology, Stockholm, Sweden {visra,oech,skoglund}@kth.se

Abstract—We investigate the problem of strong coordination over a multiple-access channel (MAC) with cribbing encoders. In this configuration, two encoders observe independent and identically distributed (i.i.d.) samples of a source random variable each and encode the inputs to the MAC. The decoder which observes the output of the MAC together with side-information, must generate approximately i.i.d. samples of another random variable which is jointly distributed with the two sources and the side information. We also allow for possible encoder cooperation, where one of the encoders can non-causally crib from the other encoder's input. Independent pairwise shared randomness is assumed between each encoder and the decoder at limited rates. Firstly, in the presence of cribbing, we derive an achievable region based on joint source-channel coding. We also prove that in the absence of cribbing, our inner bound is tight for the special case when the MAC is composed of deterministic links, and the sources are conditionally independent given the side information. We then explicitly compute the regions for an example both with and without cribbing between the encoders, and demonstrate that cribbing strictly improves upon the achievable region.

I. INTRODUCTION

The framework of *coordination* [1] explores the minimal communication necessary to establish a desired joint distribution of actions among all nodes in a network. In light of the explosion of device-to-device communications as part of the Internet of Things (IoT), this architecture is useful in such scenarios where decentralized cooperation is desired amongst distributed agents. We focus on the notion of *strong coordination*, where the distribution of the sequence of actions must be close in total variation to a target distribution.

Complete characterizations for strong coordination in multiterminal networks are comparatively rare. Building upon the the point-to-point network, a cascade network with secrecy constraints was investigated in [2], for which the optimal tradeoff between communication and common randomness rates was determined. In [3]–[5], strong coordination was investigated over a multiple-access network of noiseless links. Along with a tight characterization for independent sources, the role of shared randomness amongst the encoders in reducing the communication requirements for simulation was established.

Simulation of a channel using another channel as a resource, rather than noiseless communication links as in [6], was investigated by [7], [8]. Inner and outer bounds on the ratecoordination region were proposed in the context of singleuser as well as broadcast channel simulation therein. The same scenario was studied with an additional constraint of



Fig. 1. Strong coordination over a MAC with cribbing encoders

coordinating the channel input and output signals in [9]. The current paper extends channel simulation from noisy channels [8] to a three-terminal scenario with possible encoder cooperation [10]–[12]. Our setting can also be viewed as an extension of the multi-terminal noiseless network coordination problem [3] to the case of noisy resource channels.

Main Contributions. When the switch S in Fig. 1 is closed, we derive an achievable region (Theorem 1) based on joint source-channel coding. When the switch S in Fig. 1 is open, we give a tight characterization for the special case when the MAC is composed of deterministic links, and the sources are conditionally independent given the side information (Theorem 2). The non-trivial part lies in leveraging the deterministic channel and independent sources assumptions to obtain a single-letterization matching the inner bound, which is known to be difficult for distributed source coding settings [13]. We then explicitly compute the regions for an example both with and without encoder cribbing and demonstrate that cribbing strictly improves upon the achievable region (see Section IV).

II. SYSTEM MODEL

The setup comprises two encoders, with Encoder $j \in \{1, 2\}$ observing an input given by X_j^n , and a decoder which observes a side information sequence W^n . For $j \in \{1, 2\}$, Encoder j and the decoder can harness pairwise shared randomness K_j , assumed to be uniformly distributed on $[1 : 2^{nR_{0j}}]$. When the switch S in Fig. 1 is closed, Encoder 2 (which observes X_2^n and has access to K_2) first generates the channel input sequence X_2^n . Then, Encoder 1 (which observes X_1^n and has access to K_1 as well as X_2^n) creates the channel input sequence X_1^n . A discrete-memoryless multipleaccess channel specified by $p(\tilde{y}|\tilde{x}_1, \tilde{x}_2)$ maps the channel input sequences into an observation Y^n at the receiver. The sources (X_{1i}, X_{2i}, W_i) , $i = 1, 2, \ldots, n$, are assumed to be i.i.d. with joint distribution specified by nature as $q_{X_1X_2W}$. The random variables $X_1, X_2, W, \tilde{X}_1, \tilde{X}_2, \tilde{Y}$ assume values in finite alphabets $\mathcal{X}_1, \mathcal{X}_2, \mathcal{W}, \tilde{\mathcal{X}}_1, \tilde{\mathcal{X}}_2, \tilde{\mathcal{Y}}$, respectively. The shared randomness indices K_1 and K_2 are assumed to be independent of each other and of (X_1^n, X_2^n, W^n) . The decoder obtains $(K_1, K_2, W^n, \tilde{Y}^n)$ and simulates an output sequence Y^n (where Y_i , i = 1, ..., n, assumes values in a finite alphabet \mathcal{Y}) which along with the input sources and side information must be approximately i.i.d. according to the joint distribution $q_{X_1X_2WY}^{(n)}(x_1^n, x_2^n, w^n, y^n) := \prod_{i=1}^n q_{X_1X_2WY}(x_{1i}, x_{2i}, w_i, y_i)$ (refer Figure 1).

Definition 1. A $(2^{nR_{01}}, 2^{nR_{02}}, n)$ code comprises two randomized encoders $p^{\text{Enc}_2}(\tilde{x}_2^n|x_2^n, k_2)$ and $p^{\text{Enc}_1}(\tilde{x}_1^n|x_1^n, k_1, \tilde{x}_2^n)$ and a randomized decoder $p^{\text{Dec}}(y^n|k_1, k_2, w^n, \tilde{y}^n)$, where $k_j \in [1: 2^{nR_{0j}}], j \in \{1, 2\}.$

The induced joint distribution of all the random variables and the resulting induced marginal distribution on (X_1^n, X_2^n, W^n, Y^n) are respectively given by

$$\begin{split} p(x_1^n, x_2^n, w^n, k_1, k_2, \tilde{x}_1^n, \tilde{x}_2^n, \tilde{y}^n, y^n) \\ &= \frac{1}{2^{n(R_{01}+R_{02})}} q(x_1^n, x_2^n, w^n) p^{\text{Enc}_2}(\tilde{x}_2^n | x_2^n, k_2) \\ &\times p^{\text{Enc}_1}(\tilde{x}_1^n | x_1^n, k_1, \tilde{x}_2^n) p(\tilde{y}^n | \tilde{x}_1^n, \tilde{x}_2^n) p^{\text{Dec}}(y^n | k_1, k_2, w^n, \tilde{y}^n) \end{split}$$

and

$$p^{\text{ind}}(x_1^n, x_2^n, w^n, y^n) = \sum_{k_1, k_2, \tilde{x}_1^n, \tilde{x}_2^n, \tilde{y}^n} p(x_1^n, x_2^n, w^n, k_1, k_2, \tilde{x}_1^n, \tilde{x}_2^n, \tilde{y}^n, y^n).$$

Definition 2. A rate pair (R_{01}, R_{02}) is said to be achievable for a target joint distribution $q_{X_1X_2WY}$ with cribbing provided there exists a sequence of $(2^{nR_{01}}, 2^{nR_{02}}, n)$ codes such that

$$\lim_{n \to \infty} ||p_{X_1^n, X_2^n, W^n, Y^n}^{\text{ind}} - q_{X_1 X_2 W Y}^{(n)}||_1 = 0,$$
(1)

where $q_{X_1X_2WY}^{(n)}$ is the target i.i.d. product distribution

$$q_{X_1X_2WY}^{(n)}(x_1^n, x_2^n, w^n, y^n) := \prod_{i=1}^n q_{X_1X_2WY}(x_{1i}, x_{2i}, w_i, y_i).$$

Definition 3. The rate region $\mathcal{R}_{\text{noisy-coord}}^{\text{MAC, crib}}$ is the closure of the set of all achievable rate pairs (R_{01}, R_{02}) .

We also separately consider the case when the switch S in Fig. 1 is open. A code, an achievable rate pair, and the rate region can be defined analogously. In particular, the code and an achievable rate pair can be defined similar to

Definitions 1 and 2 by changing the map at Encoder 1 to simply $p^{\text{Enc}_1}(\tilde{x}_1^n | x_1^n, k_1)$. The rate region $\mathcal{R}_{\text{noisy-coord}}^{\text{MAC}}$ is the closure of the set of all achievable rate tuples (R_{01}, R_{02}) when the switch S in Fig.1 is open. Let $\mathcal{R}_{\text{noisy-coord}, R_{02} \to \infty}^{\text{MAC}}$ be the region when the pairwise shared randomness K_2 is unlimited:

$$\mathcal{R}_{\text{noisy-coord, } R_{02} \to \infty}^{\text{MAC}} = \{R_{01} : \exists R_{02} \\ \text{s.t.} (R_{01}, R_{02}) \in \mathcal{R}_{\text{noisy-coord}}^{\text{MAC}} \}.$$
(2)

III. MAIN RESULTS

We first present our results in the context where one of the encoders is allowed to crib [10, Situation 4] from the other encoder's input non-causally (the switch S in Figure 1 is closed). This will facilitate cooperation between the encoders, in that Enc 1 can build its codebooks conditioned on the knowledge of the input codeword from Enc 2. We have the following inner bound to the rate region $\mathcal{R}_{noisy-coord}^{MAC, crib}$. In the theorem below, the auxiliary random variables U_1 , U_2 are used in the joint source-channel coding scheme to send source descriptions of X_1 , X_2 respectively, while T is a timesharing random variable. The decoder then recovers the source descriptions and locally simulates Y.

Theorem 1 (Achievable Rate Region with Cribbing amongst the Encoders). Given a target joint p.m.f. $q_{X_1X_2WY}$, the rate pair (R_{01}, R_{02}) is in $\mathcal{R}_{\text{noisy-coord}}^{\text{MAC}, \text{ crib}}$ provided

$$I(U_1; U_2, W, \tilde{Y}|T) \ge I(U_1; X_1, \tilde{X}_2|T)$$
 (3a)

$$I(U_2; U_1, W, Y|T) \ge I(U_2; X_2|T)$$
 (3b)

$$I(U_1, U_2; W, \tilde{Y}|T) \ge I(U_1; X_1, \tilde{X}_2|T) + I(U_2; X_2|T) - I(U_1; U_2|T)$$
(3c)

$$R_{01} \ge I(U_1; X_1, X_2, W, Y|T)$$

$$-I(U_1; U_2, W, Y|T)$$
(3d)
$$R_{02} \ge I(U_2; X_1, X_2, W, Y|T)$$

$$-I(U_2; U_1, W, \tilde{Y}|T)$$
 (3e)

$$\begin{aligned} R_{01} &\geq I(U_1; X_1, X_2, W, Y | T) - I(U_1; W, \tilde{Y} | T) \\ &+ I(U_2; X_2 | T) - I(U_2; U_1, W, \tilde{Y} | T) \end{aligned}$$

$$R_{02} \ge I(U_2; X_1, X_2, W, Y | T) - I(U_2; W, Y | T) + I(U_1; X_1, \tilde{X}_2 | T) - I(U_1; U_2, W, \tilde{Y} | T)$$

$$(3g)$$

$$R_{02} \ge I(U_1, U_2; X_1, X_2, W Y | T)$$

$$\begin{split} R_{01} + R_{02} &\geq I(U_1, U_2; X_1, X_2, W, Y | T) \\ &\quad - I(U_1, U_2; W, \tilde{Y} | T), \end{split} \tag{3h}$$

for some p.m.f.

$$p(x_1, x_2, w, t, u_1, u_2, \tilde{x}_1, \tilde{x}_2, \tilde{y}, y) = p(x_1, x_2, w)p(t)p(u_2, \tilde{x}_2 | x_2, t)p(u_1, \tilde{x}_1 | x_1, \tilde{x}_2, t) \times p(\tilde{y} | \tilde{x}_1, \tilde{x}_2)p(y | u_1, u_2, w, \tilde{y}, t)$$
(4)

such that

$$\sum_{u_1, u_2, \tilde{x}_1, \tilde{x}_2, \tilde{y}} p(x_1, x_2, w, u_1, u_2, \tilde{x}_1, \tilde{x}_2, \tilde{y}, y|t) = q(x_1, x_2, w, y) \ \forall \ t$$

We note that constraints (3a)–(3c) ensure that the source descriptions can be successfully recovered at the decoder, while constraints (3d)–(3h) are the minimum rates of shared randomness needed for channel simulation. In particular, note that the right-hand sides of the inequalities (3a), (3c) and (3g) featuring mutual information terms with U_1 can depend upon \tilde{X}_2 . For a detailed proof, please refer to Section V.

Now consider the case when the switch S in Figure 1 is open, i.e., no cribbing is admissible. Then we can derive a tight characterization if the channel $p(\tilde{y}|\tilde{x}_1, \tilde{x}_2)$ is composed of deterministic links, i.e., $\tilde{Y} = (f_1(\tilde{X}_1), f_2(\tilde{X}_2))$ for deterministic maps $f_1(\cdot)$ and $f_2(\cdot)$, and $I(X_1; X_2|W) = 0$.

Theorem 2 (Tight Characterization without Encoder Cribbing). Consider a target p.m.f. $q_{X_1X_2WY}$ such that $I(X_1; X_2|W) = 0$, and also assume that the MAC is composed of deterministic links, i.e. $\tilde{Y} = (f_1(\tilde{X}_1), f_2(\tilde{X}_2)) \triangleq (\tilde{Y}_1, \tilde{Y}_2)$. Then the rate region $\mathcal{R}_{\text{noisy-coord, } R_{02} \to \infty}$ is characterized by the set of rates R_{01} such that

 $H(\tilde{Y}_{1}|T) \ge I(U_{1}, \tilde{Y}_{1}; X_{1}|W, T)$ (5a)

 $H(\tilde{Y}_2|T) \ge I(U_2, \tilde{Y}_2; X_2|W, T)$ (5b)

$$R_{01} \ge I(U_1, \tilde{Y}_1; X_1, Y | X_2, W, T) - H(\tilde{Y}_1 | T),$$
 (5c)

for some p.m.f.

$$p(x_{1},x_{2},w,t,u_{1},u_{2},\tilde{x}_{1},\tilde{x}_{2},\tilde{y},y) = p(w)p(x_{1}|w)p(x_{2}|w)p(t)\prod_{j=1}^{2}p(u_{j}|x_{j},t)p(\tilde{x}_{j}|u_{j},x_{j},t) \times p(\tilde{y}|\tilde{x}_{1},\tilde{x}_{2})p(y|u_{1},u_{2},w,\tilde{y},t)$$
(6)

such that

$$\sum_{u_1, u_2, \tilde{x}_1, \tilde{x}_2, \tilde{y}} p(x_1, x_2, w, u_1, u_2, \tilde{x}_1, \tilde{x}_2, \tilde{y}, y | t) = q(x_1, x_2, w, y) \,\forall \, t$$

with the auxiliary cardinalities bounded as
$$|\mathcal{U}_1| \leq |\mathcal{X}_1||\mathcal{X}_2||\mathcal{W}||\tilde{\mathcal{X}}_1||\tilde{\mathcal{X}}_2||\tilde{\mathcal{Y}}||\mathcal{Y}|, \quad |\mathcal{U}_2| \leq |\mathcal{U}_1||\mathcal{X}_1||\mathcal{X}_2||\mathcal{W}||\tilde{\mathcal{X}}_1||\tilde{\mathcal{X}}_2||\tilde{\mathcal{Y}}||\mathcal{Y}| \text{ and } |\mathcal{T}| \leq 3.$$

The achievability largely follows from [7, Theorem 3], by also accounting for the decoder side information and enforcing the conditional independence $p(x_1, x_2, w) =$ $p(w)p(x_1|w)p(x_2|w)$ along with $\tilde{Y} = (f_1(\tilde{X}_1), f_2(\tilde{X}_2))$. A detailed proof of the converse is given in Section VI.

IV. EXAMPLE: CRIBBING HELPS FOR CHANNEL SIMULATION

In this section, we show with the help of an example that in the presence of cribbing between the encoders, the achievable region can be improved upon. Our illustration will be in the context of Theorem 2. Accordingly, we first compute the region of Theorem 2 without encoder cribbing for this example, and then show that the region is improved in the presence of encoder cribbing.

Example 1. Let $X_1 = (X_{11}, X_{12})$, where X_{11} and X_{12} are independent and uniform binary random variables. Let $X_2 = B$, where B is uniformly distributed on $\{1, 2\}$ and

independent of X_1 . Suppose the channel to be simulated $q_{Y|X_1,X_2}$ is such that $Y = X_{1B}$. For the sake of simplicity, we let $W = \emptyset$ and assume a perfect resource channel $\tilde{Y} = (\tilde{X}_1, \tilde{X}_2)$, i.e., the maps $f_1(\cdot)$ and $f_2(\cdot)$ in Theorem 2 are identities. We focus on the requisite values of $H(\tilde{X}_1)$ and $H(\tilde{X}_2)$ for channel simulation in the presence of unlimited shared randomness rates, with and without encoder cribbing.

In the absence of cribbing between the encoders, from Theorem 2, the region $\mathcal{R}_{\text{noisy-coord}}^{\text{MAC}}$ for unlimited shared randomness rates R_{01}, R_{02} and a perfect channel $\tilde{Y}_j = \tilde{X}_j$ for $j \in \{1, 2\}$ is simply characterized by the feasibility constraints

$$H(X_1|T) \ge I(U_1, X_1; X_1|T) H(\tilde{X}_2|T) \ge I(U_2, \tilde{X}_2; X_2|T),$$

for some p.m.f.

$$p(x_1, x_2, t, u_1, u_2, \tilde{x}_1, \tilde{x}_2, y) =$$

$$p(x_1)p(x_2)p(t) \prod_{j=1}^2 p(u_j, \tilde{x}_j | x_j, t)p(y | u_1, u_2, \tilde{x}_1, \tilde{x}_2, t)$$

such that $\sum_{\substack{u_1,u_2,\tilde{x}_1,\tilde{x}_2\\ y \in \mathcal{X}}} p(x_1,x_2,u_1,u_2,\tilde{x}_1,\tilde{x}_2,y|t) = q(x_1,x_2,y), \text{ for all } t. \text{ The following proposition explicitly}$

 $q(x_1, x_2, y)$, for an *i*. The following proposition explicitly characterizes the optimal region (of feasibility constraints) for the given $q_{X_1X_2Y}$.

Proposition 1. For the target distribution $q_{X_1X_2Y}$ in Example 1, channel simulation is feasible if and only if $H(\tilde{X}_1) \ge 2$ and $H(\tilde{X}_2) \ge 1$ (thus $H(\tilde{X}_1, \tilde{X}_2) \ge 3$).

Proof. For the achievability, it suffices to prove that there exists a p.m.f.

$$p(x_1, x_2, u_1, u_2, \tilde{x}_1, \tilde{x}_2, y) =$$

$$p(x_1)p(x_2) \prod_{j=1}^2 p(u_j, \tilde{x}_j | x_j) p(y | u_1, u_2, \tilde{x}_1, \tilde{x}_2)$$

such that $\sum_{u_1,u_2,\tilde{x}_1,\tilde{x}_2} p(x_1, x_2, u_1, u_2, \tilde{x}_1, \tilde{x}_2, y) = q(x_1, x_2, y),$ $I(U_1, \tilde{X}_1; X_1) = 2$ and $I(U_2, \tilde{X}_2; X_2) = 1$. By choosing $U_1 = X_1$ and $U_2 = X_2$, it is clear that the conditions on the joint p.m.f. $p(x_1, x_2, u_1, u_2, \tilde{x}_1, \tilde{x}_2, y)$ are satisfied and $I(U_1, \tilde{X}_1; X_1) = H(X_1) = 2, I(U_2, \tilde{X}_2; X_2) = H(B) = 1.$ The interesting part is the converse, in Appendix A.

We next prove that with cribbing, it is possible to achieve channel simulation with smaller values of $H(\tilde{X}_1)$ and $H(\tilde{X}_2)$ compared to the optimal region without cribbing. To see this, we choose $\tilde{X}_2 = X_2$ which in the presence of cribbing makes $X_2 = B$ available to Enc 1. Then Enc 1 can afford to send only $\tilde{X}_1 = X_{1B}$ (instead of the entire (X_{11}, X_{12}) necessitated in the absence of cribbing). More formally, the region $\mathcal{R}_{\text{noisy-coord}}^{\text{MAC}, \text{ crib}}$ in Theorem 1 specializes for independent sources, perfect channel and unlimited shared randomness to the set of feasibility constraints

$$H(\tilde{X}_1|T) \ge I(U_1, \tilde{X}_1; X_1, \tilde{X}_2|T) - I(U_1; U_2, \tilde{X}_2|\tilde{X}_1, T)$$

$$H(\tilde{X}_{2}|T) \geq I(U_{2}, \tilde{X}_{2}; X_{2}|T) - I(U_{2}; U_{1}, \tilde{X}_{1}|\tilde{X}_{2}, T)$$

$$H(\tilde{X}_{1}, \tilde{X}_{2}|T) \geq I(U_{2}, \tilde{X}_{2}; X_{2}|T) - I(U_{2}, \tilde{X}_{2}; U_{1}, \tilde{X}_{1}|T)$$

$$+ I(U_{1}, \tilde{X}_{1}; X_{1}, \tilde{X}_{2}|T),$$

for some p.m.f.

$$p(x_1, x_2, t, u_1, u_2, x_1, x_2, y) = p(x_1)p(x_2)p(t)p(u_2, \tilde{x}_2|x_2, t)p(u_1, \tilde{x}_1|x_1, \tilde{x}_2, t) \times p(y|u_1, u_2, \tilde{x}_1, \tilde{x}_2, t)$$
(7)

such that

$$\sum_{i_1, u_2, \tilde{x}_1, \tilde{x}_2} p(x_1, x_2, u_1, u_2, \tilde{x}_1, \tilde{x}_2, y|t) = q(x_1, x_2, y),$$

for all t. Now we can choose $U_1 = X_{1B}$ and $U_2 = B$ to obtain that channel simulation is feasible if $H(\tilde{X}_1) \ge 1$, $H(\tilde{X}_2) \ge 1$ and $H(\tilde{X}_1, \tilde{X}_2) \ge 2$. This strictly improves upon the (optimal region of) feasibility constraints without cribbing, which were $H(\tilde{X}_1) \ge 2$, $H(\tilde{X}_2) \ge 1$ and $H(\tilde{X}_1, \tilde{X}_2) \ge 3$.

V. PROOF OF THEOREM 1

The proof makes use of the Output Statistics of Random Binning (OSRB) framework [14]. In the following discussion, we adopt the convention of using capital letters (such as P_X) to represent random p.m.f.'s, as in [6], [14]. We establish achievability with $|\mathcal{T}| = 1$, for simplicity.

Random Binning Protocol: Let the random variables $\overline{(U_1^n, U_2^n, X_1^n, X_2^n, W^n, \tilde{X}_1^n, \tilde{X}_2^n, \tilde{Y}^n, Y^n)}$ be drawn i.i.d. according to the joint distribution

$$p(x_1, x_2, w, u_1, u_2, \tilde{x}_1, \tilde{x}_2, \tilde{y}, y)$$

$$= p(x_1, x_2, w) p(u_2 | x_2) p(\tilde{x}_2 | u_2, x_2) p(u_1 | x_1, \tilde{x}_2)$$

$$\times p(\tilde{x}_1 | u_1, x_1, \tilde{x}_2) p(\tilde{y} | \tilde{x}_1, \tilde{x}_2) p(y | u_1, u_2, w, \tilde{y})$$
(8)

such that the marginal $p(x_1, x_2, w, y) = q(x_1, x_2, w, y)$. The following random binning is then applied: independently generate two uniform bin indices (K_j, F_j) of U_j^n , where $K_j = \phi_{j1}(U_j^n) \in [1 : 2^{nR_{0j}}]$ and $F_j = \phi_{j2}(U_j^n) \in [1 : 2^{n\tilde{R}_j}]$. The receiver estimates $(\hat{u}_1^n, \hat{u}_2^n)$ from its observations $(k_1, f_1, k_2, f_2, w^n, \tilde{y}^n)$ using a Slepian-Wolf decoder. The random p.m.f. induced by this binning scheme is given by:

$$\begin{split} &P(x_1^n, x_2^n, w^n, y^n, u_1^n, u_2^n, \tilde{x}_1^n, \tilde{x}_2^n, \tilde{y}^n, k_1, f_1, k_2, f_2, \hat{u}_1^n, \hat{u}_2^n) \\ &= p(x_1^n, x_2^n, w^n) p(u_2^n | x_2^n) p(\tilde{x}_2^n | u_2^n, x_2^n) p(u_1^n | x_1^n, \tilde{x}_2^n) \\ &\times p(\tilde{x}_1^n | u_1^n, x_1^n, \tilde{x}_2^n) p(\tilde{y}^n | \tilde{x}_1^n, \tilde{x}_2^n) p(y^n | u_1^n, u_2^n, w^n, \tilde{y}^n) \\ &\times P(k_1, f_1 | u_1^n) P(k_2, f_2 | u_2^n) \\ &\times P^{SW}(\hat{u}_1^n, \hat{u}_2^n | k_1, f_1, k_2, f_2, w^n, \tilde{y}^n) \\ &= p(x_1^n, x_2^n, w^n) P(k_2, f_2, u_2^n | x_2^n) p(\tilde{x}_2^n | u_2^n, x_2^n) \\ &\times P^{SW}(\hat{u}_1^n, \hat{u}_2^n | k_1, f_1, k_2, f_2, w^n, \tilde{y}^n) p(y^n | \tilde{x}_1^n, \tilde{x}_2^n) \\ &\times P^{SW}(\hat{u}_1^n, \hat{u}_2^n | k_1, f_1, k_2, f_2, w^n, \tilde{y}^n) p(y^n | u_1^n, u_2^n, w^n, \tilde{y}^n) \\ &= p(x_1^n, x_2^n, w^n) P(k_2, f_2 | x_2^n) P(u_2^n | k_2, f_2, x_2^n) \\ &\times P(\tilde{x}_1^n | u_2^n, x_2^n) P(k_1, f_1 | x_1^n, \tilde{x}_2^n) \\ &\times P(u_1^n | k_1, f_1, x_1^n, \tilde{x}_2^n) p(\tilde{x}_1^n | u_1^n, x_1^n, \tilde{x}_2^n) p(\tilde{y}^n | \tilde{x}_1^n, \tilde{x}_2^n) \\ &\times P^{SW}(\hat{u}_1^n, \hat{u}_2^n | k_1, f_1, k_2, f_2, w^n, \tilde{y}^n) p(y^n | u_1^n, u_2^n, w^n, \tilde{y}^n). \end{split}$$

Random Coding Protocol: In this scheme, we assume the presence of additional shared randomness F_j of rate $R_j, j \in$ $\{1,2\}$ between the respective encoders and the decoder in the original problem. Encoder 2 observes (k_2, f_2, x_2^n) , and generates u_2^n according to the p.m.f. $P(u_2^n|k_2, f_2, x_2^n)$ from the protocol above. Further, encoder 2 draws \tilde{x}_2^n according to the p.m.f. $p(\tilde{x}_2^n|u_{2j}^n, x_2^n)$. Encoder 1 observes $(k_1, f_1, x_1^n, \tilde{x}_2^n)$, and generates u_1^n according to the p.m.f. $P(u_1^n|k_1, f_1, x_1^n, \tilde{x}_2^n)$ from the protocol above. Further, encoder 1 draws \tilde{x}_1^n according to the p.m.f. $p(\tilde{x}_1^n|u_1^n, x_1^n, \tilde{x}_2^n)$. The receiver first estimates $(\hat{u}_1^n, \hat{u}_2^n)$ from its observations $(k_1,k_2,f_1,f_2,w^n, ilde y^n)$ using the Slepian-Wolf decoder from the binning protocol, i.e. $P^{SW}(\hat{u}_{1}^{n}, \hat{u}_{2}^{n} | k_{1}, f_{1}, k_{2}, f_{2}, w^{n}, \tilde{y}^{n})$. Then it generates the output y^n according to the distribution $p_{Y^{n}|U_{1}^{n},U_{2}^{n},W^{n},\tilde{Y}^{n}}(y^{n}|\hat{u}_{1}^{n},\hat{u}_{2}^{n},w^{n},\tilde{y}^{n})$. The induced random p.m.f. from the random coding scheme is

$$\begin{split} \hat{P}(x_1^n, x_2^n, w^n, y^n, u_1^n, u_2^n, \tilde{x}_1^n, \tilde{x}_2^n, \tilde{y}^n, k_1, f_1, k_2, f_2, \hat{u}_1^n, \hat{u}_2^n) \\ &= p^{\mathrm{U}}(k_1) p^{\mathrm{U}}(f_1) p^{\mathrm{U}}(k_2) p^{\mathrm{U}}(f_2) p(x_1^n, x_2^n, w^n) \\ &\times P(u_2^n | k_2, f_2, x_2^n) p(\tilde{x}_2^n | u_2^n, x_2^n) \\ &\times P(u_1^n | k_1, f_1, x_1^n, \tilde{x}_2^n) p(\tilde{x}_1^n | u_1^n, x_1^n, \tilde{x}_2^n) p(\tilde{y}^n | \tilde{x}_1^n, \tilde{x}_2^n) \\ &\times P^{SW}(\hat{u}_1^n, \hat{u}_2^n | k_1, f_1, k_2, f_2, w^n, \tilde{y}^n) p(y^n | \hat{u}_1^n, \hat{u}_2^n, w^n, \tilde{y}^n) \end{split}$$

Analysis of Rate Constraints:

Using the fact that (k_j, f_j) are bin indices of u_j^n for $j \in \{1, 2\}$, we impose the conditions

$$R_{01} + R_1 \le H(U_1 | X_1, X_2), \tag{9}$$

$$R_{02} + R_2 \le H(U_2|X_2), \tag{10}$$

that ensure, by invoking [14, Theorem 1]

$$P(x_1^n, x_2^n, w^n, u_1^n, u_2^n, \tilde{x}_1^n, \tilde{x}_2^n, \tilde{y}^n, k_1, f_1, k_2, f_2, \hat{u}_1^n, \hat{u}_2^n) \approx \hat{P}(x_1^n, x_2^n, w^n, u_1^n, u_2^n, \tilde{x}_1^n, \tilde{x}_2^n, \tilde{y}^n, k_1, f_1, k_2, f_2, \hat{u}_1^n, \hat{u}_2^n).$$
(11)

We next impose the following constraints for the success of the (Slepian-Wolf) decoder by Slepian-Wolf theorem [15]

$$R_{01} + R_1 \ge H(U_1|U_2, W, Y),$$
 (12)

$$R_{02} + \hat{R}_2 \ge H(U_2|U_1, W, \hat{Y}),$$
 (13)

$$R_{01} + \tilde{R}_1 + R_{02} + \tilde{R}_2 \ge H(U_1, U_2 | W, \tilde{Y}), \qquad (14)$$

Expressions (12)-(14) suffice to obtain

$$P(x_1^n, x_2^n, w^n, u_1^n, u_2^n, \tilde{x}_1^n, \tilde{x}_2^n, \tilde{y}^n, k_1, f_1, k_2, f_2, \hat{u}_1^n, \hat{u}_2^n) \approx P(x_1^n, x_2^n, w^n, u_1^n, u_2^n, \tilde{x}_1^n, \tilde{x}_2^n, \tilde{y}^n, k_1, f_1, k_2, f_2) \times \mathbb{1}\{\hat{u}_1^n = u_1^n, \hat{u}_2^n = u_2^n\}.$$
(15)

Using (15) and (11) in conjunction with the first and third parts of [14, Lemma 4], we obtain

$$\begin{split} \hat{P}(x_1^n, x_2^n, w^n, u_1^n, u_2^n, \tilde{x}_1^n, \tilde{x}_2^n, \tilde{y}^n, k_1, f_1, k_2, f_2, \hat{u}_1^n, \hat{u}_2^n, y^n) \\ &= \hat{P}(x_1^n, x_2^n, w^n, u_1^n, u_2^n, \tilde{x}_1^n, \tilde{x}_2^n, \tilde{y}^n, k_1, f_1, k_2, f_2, \hat{u}_1^n, \hat{u}_2^n) \\ &\times p(y^n | \hat{u}_1^n, \hat{u}_2^n, w^n, \tilde{y}^n) \\ &\approx P(x_1^n, x_2^n, w^n, u_1^n, u_2^n, \tilde{x}_1^n, \tilde{x}_2^n, \tilde{y}^n, k_1, f_1, k_2, f_2) \\ &\times \mathbb{1}\{\hat{u}_1^n = u_1^n, \hat{u}_2^n = u_2^n\} p(y^n | \hat{u}_1^n, \hat{u}_2^n, w^n, \tilde{y}^n) \end{split}$$

$$= P(x_1^n, x_2^n, w^n, u_1^n, u_2^n, \tilde{x}_1^n, \tilde{x}_2^n, \tilde{y}^n, k_1, f_1, k_2, f_2, y^n) \\ \times \mathbb{1}\{\hat{u}_1^n = u_1^n, \hat{u}_2^n = u_2^n\}.$$
(16)

This implies, by the first part of [14, Lemma 4]

$$\hat{P}(x_1^n, x_2^n, w^n, y^n, f_1, f_2) \approx P(x_1^n, x_2^n, w^n, y^n, f_1, f_2).$$
(17)

We further require (X_1^n, X_2^n, W^n, Y^n) to be nearly independent of (F_1, F_2) , so that the latter can be eliminated. This is realized by imposing the following conditions:

$$\hat{R}_1 \le H(U_1|X_1, X_2, W, Y),$$
(18)

$$\tilde{R}_2 \le H(U_2|X_1, X_2, W, Y), \tag{19}$$

$$\tilde{R}_1 + \tilde{R}_2 \le H(U_1, U_2 | X_1, X_2, W, Y).$$
(20)

By [14, Theorem 1], this suffices to obtain

$$P(x_1^n, x_2^n, w^n, y^n, f_1, f_2) \approx p^{\mathsf{U}}(f_1)p^{\mathsf{U}}(f_2)p(x_1^n, x_2^n, w^n, y^n),$$

which implies that

$$\hat{P}(x_1^n, x_2^n, w^n, y^n, f_1, f_2) \approx p^{\mathrm{U}}(f_1) p^{\mathrm{U}}(f_2) p(x_1^n, x_2^n, w^n, y^n),$$
(21)

by invoking (17) and the triangle inequality. Hence there exists a fixed binning with corresponding pmf \tilde{p} such that if we replace P by \tilde{p} in (21) and denote the resulting pmf by \hat{p} ,

$$\hat{p}(x_1^n, x_2^n, w^n, y^n, f_1, f_2) \approx p^{\mathrm{U}}(f_1)p^{\mathrm{U}}(f_2)p(x_1^n, x_2^n, w^n, y^n).$$

Now the second part of [14, Lemma 4] allows us to conclude that there exist instances $F_1 = f_1^*, F_2 = f_2^*$ such that

$$\hat{p}(x_1^n, x_2^n, w^n, y^n | f_1^*, f_2^*) \approx p(x_1^n, x_2^n, w^n, y^n).$$
(22)

Finally on eliminating $(\tilde{R}_1, \tilde{R}_2)$ from equations (9) – (10), (12) – (14) and (18) – (20) by the FME procedure, we obtain the rate constraints in Theorem 1.

VI. CONVERSE PROOF OF THEOREM 2

Consider a coding scheme that induces a joint distribution on (X_1^n, X_2^n, W^n, Y^n) which satisfies the constraint

$$\|p_{X_1^n, X_2^n, W^n, Y^n} - q_{X_1 X_2 W Y}^{(n)}\|_1 \le \epsilon.$$
(23)

Lemma 1. [9, Lemma 6] Let p_{S^n} be such that $||p_{S^n} - q_S^{(n)}||_1 \le \epsilon$, where $q_S^{(n)}(s^n) = \prod_{i=1}^n q_S(s_i)$, then

$$\sum_{i=1}^{n} I_p(S_i; S_{\sim i}) \le ng(\epsilon), \tag{24}$$

where $g(\epsilon) = 2\sqrt{\epsilon} \left(H(S) + \log |\mathcal{S}| + \log \frac{1}{\sqrt{\epsilon}} \right) \to 0 \text{ as } \epsilon \to 0.$

Let us now prove the first inequality in Theorem 2. Recall that $\tilde{Y} = (f_1(\tilde{X}_1), f_2(\tilde{X}_2)) \triangleq (\tilde{Y}_1, \tilde{Y}_2).$

$$0 \leq H(\tilde{Y}_{1}^{n}) - I(\tilde{Y}_{1}^{n}; K_{1}, X_{1}^{n}, W^{n})$$

$$\leq H(\tilde{Y}_{1}^{n}) - I(\tilde{Y}_{1}^{n}; X_{1}^{n} | K_{1}, W^{n})$$

$$\leq \sum_{i=1}^{n} H(\tilde{Y}_{1i}) - \sum_{i=1}^{n} I(\tilde{Y}_{1}^{n}; X_{1i} | K_{1}, X_{1,i+1}^{n}, W_{\sim i}, W_{i})$$

$$\stackrel{(a)}{=} \sum_{i=1}^{n} H(\tilde{Y}_{1i}) - \sum_{i=1}^{n} I(K_{1}, \tilde{Y}_{1}^{n}, X_{1,i+1}^{n}, W_{\sim i}; X_{1i} | W_{i})$$

$$\leq \sum_{i=1}^{n} H(\tilde{Y}_{1i}) - \sum_{i=1}^{n} I(K_{1}, \tilde{Y}_{1\sim i}, W_{\sim i}, \tilde{Y}_{1i}; X_{1i} | W_{i})$$

$$\stackrel{(b)}{=} \sum_{i=1}^{n} H(\tilde{Y}_{1i}) - \sum_{i=1}^{n} I(U_{1i}, \tilde{Y}_{1i}; X_{1i} | W_{i})$$

$$= nH(\tilde{Y}_{1T} | T) - nI(U_{1T}, \tilde{Y}_{1T}; X_{1T} | W_{T}, T)$$

$$= nH(\tilde{Y}_{1} | T) - nI(U_{1}, \tilde{Y}_{1}; X_{1} | W, T), \qquad (25)$$

where (a) follows from the joint i.i.d. nature of $(X_{1i}, W_i), i = 1, \ldots, n$ and the independence of K_1 from (X_1^n, W^n) , while (b) follows from an auxiliary random variable identification $U_{1i} = (K_1, \tilde{Y}_{1\sim i}, W_{\sim i})$. The inequality $H(\tilde{Y}_2|T) \ge I(U_2, \tilde{Y}_2; X_2|W, T)$ follows analogously, with an auxiliary random variable choice given by $U_{2i} = (K_2, \tilde{Y}_{2\sim i})$.

The constraint on the shared randomness rate R_{01} is proved next. Consider the sequence of inequalities below:

-- (- -)

$$\begin{split} nR_{01} &= H(K_{1}) \\ &= H(K_{1}, \tilde{Y}_{1}^{n}) - H(\tilde{Y}_{1}^{n}|K_{1}) \\ &\geq H(K_{1}, \tilde{Y}_{1}^{n}|X_{2}^{n}, W^{n}) - H(\tilde{Y}_{1}^{n}) \\ &\geq I(K_{1}, \tilde{Y}_{1}^{n}; X_{1}^{n}, Y^{n}|X_{2}^{n}, W^{n}) - H(\tilde{Y}_{1}^{n}) \\ &\geq \sum_{i=1}^{n} I(K_{1}, \tilde{Y}_{1}^{n}; X_{1i}, Y_{i}|X_{1,i+1}^{n}, Y_{i+1}^{n}, X_{2}^{n}, W^{n}) - \sum_{i=1}^{n} H(\tilde{Y}_{1i}) \\ &= \sum_{i=1}^{n} I(K_{1}, \tilde{Y}_{1}^{n}, X_{1,i+1}^{n}, Y_{i+1}^{n}, X_{2\sim i}, W_{\sim i}; X_{1i}, Y_{i}|X_{2i}, W_{i}) \\ &\quad - \sum_{i=1}^{n} I(X_{1,i+1}^{n}, Y_{i+1}^{n}, X_{2\sim i}, W_{\sim i}; X_{1i}, Y_{i}|X_{2i}, W_{i}) \\ &\quad - \sum_{i=1}^{n} H(\tilde{Y}_{1i}) \\ \begin{pmatrix} a \\ \geq \\ \\ \sum_{i=1}^{n} I(K_{1}, \tilde{Y}_{1\sim i}, W_{\sim i}, \tilde{Y}_{1i}; X_{1i}, Y_{i}|X_{2i}, W_{i}) - ng(\epsilon) \\ &\quad - \sum_{i=1}^{n} H(\tilde{Y}_{1i}) \\ &= \sum_{i=1}^{n} I(U_{1i}, \tilde{Y}_{1i}; X_{1i}, Y_{i}|X_{2i}, W_{i}) - \sum_{i=1}^{n} H(\tilde{Y}_{1i}) - ng(\epsilon) \\ &= nI(U_{1T}, \tilde{Y}_{1T}; X_{1T}, Y_{T}|X_{2T}, W_{T}, T) - nH(\tilde{Y}_{1T}|T) - ng(\epsilon) \\ &= nI(U_{1}, \tilde{Y}_{1}; X_{1}, Y|X_{2}, W, T) - nH(\tilde{Y}_{1}|T) - ng(\epsilon), \end{split}$$

where (a) follows by (23) and Lemma 1.

The proof of Theorem 2 is completed by showing the continuity of the derived converse bound at $\epsilon = 0$ (note that g(0) := 0 through continuous extension of the function $g(\epsilon)$). This continuity follows from cardinality bounds on the auxiliary random variables (U_1, U_2) to ensure the compactness of the simplex, as outlined in [6, Lemma VI.5]. The cardinalities of U_1 and U_2 can be restricted as mentioned following the perturbation method of [16], similar to [17]. Finally, by invoking the continuity properties of total variation distance and mutual information in the probability simplex, the converse for Theorem 2 is complete.

REFERENCES

- P. Cuff, H. Permuter, and T. Cover, "Coordination capacity," *IEEE Transactions on Information Theory*, vol. 56, no. 9, pp. 4181–4206, 2010.
- [2] S. Satpathy and P. Cuff, "Secure cascade channel synthesis," *IEEE Transactions on Information Theory*, vol. 62, no. 11, pp. 6081–6094, 2016.
- [3] G. R. Kurri, V. Ramachandran, S. R. B. Pillai, and V. M. Prabhakaran, "Multiple access channel simulation," *IEEE Transactions on Information Theory*, vol. 68, no. 11, pp. 7575–7603, 2022.
- [4] V. Ramachandran, S. R. B. Pillai, and V. M. Prabhakaran, "Strong coordination with side information," in 2020 IEEE International Symposium on Information Theory (ISIT), 2020, pp. 1564–1569.
- [5] V. Ramachandran, T. J. Oechtering, and M. Skoglund, "Multi-terminal strong coordination over noiseless networks with secrecy constraints," in 2024 International Zurich Seminar on Information and Communication (IZS). ETH Zurich Library, 2024.
- [6] P. Cuff, "Distributed channel synthesis," *IEEE Transactions on Informa*tion Theory, vol. 59, no. 11, pp. 7071–7096, 2013.
- [7] F. Haddadpour, M. H. Yassaee, M. R. Aref, and A. Gohari, "When is it possible to simulate a DMC channel from another?" in *IEEE Information Theory Workshop*, 2013, pp. 1–5.
- [8] F. Haddadpour, M. H. Yassaee, S. Beigi, A. Gohari, and M. R. Aref, "Simulation of a channel with another channel," *IEEE Transactions on Information Theory*, vol. 63, no. 5, pp. 2659–2677, 2017.
- [9] G. Cervia, L. Luzzi, M. Le Treust, and M. R. Bloch, "Strong coordination of signals and actions over noisy channels with two-sided state information," *IEEE Transactions on Information Theory*, vol. 66, no. 8, pp. 4681–4708, 2020.

- [10] F. Willems and E. Van der Meulen, "The discrete memoryless multipleaccess channel with cribbing encoders," *IEEE Transactions on Information Theory*, vol. 31, no. 3, pp. 313–327, 1985.
- [11] H. Asnani and H. H. Permuter, "Multiple-access channel with partial and controlled cribbing encoders," *IEEE Transactions on Information Theory*, vol. 59, no. 4, pp. 2252–2266, 2012.
- [12] W. Huleihel and Y. Steinberg, "Multiple access channel with unreliable cribbing," in 2016 IEEE International Symposium on Information Theory (ISIT). IEEE, 2016, pp. 1491–1495.
- [13] T. Berger, "Multiterminal source coding," *The information theory approach to communications*, vol. 229, pp. 171–231, 1977.
- [14] M. Yassaee, M. Aref, and A. Gohari, "Achievability proof via output statistics of random binning," *IEEE Transactions on Information Theory*, vol. 60, no. 11, pp. 6760–6786, 2014.
- [15] D. Slepian and J. Wolf, "Noiseless coding of correlated information sources," *IEEE Transactions on information Theory*, vol. 19, no. 4, pp. 471–480, 1973.
- [16] A. A. Gohari and V. Anantharam, "Evaluation of Marton's inner bound for the general broadcast channel," *IEEE Transactions on Information Theory*, vol. 58, no. 2, pp. 608–619, 2012.
- [17] V. Ramachandran, T. J. Oechtering, and M. Skoglund, "Multi-terminal strong coordination over noisy channels with secrecy constraints," in 2024 IEEE International Symposium on Information Theory (ISIT), 2024.
- [18] V. Ramachandran and S. R. B. Pillai, "Feedback-capacity of degraded gaussian vector bc using directed information and concave envelopes," in 2017 Twenty-third National Conference on Communications (NCC). IEEE, 2017, pp. 1–6.

APPENDIX A Converse Proof of Proposition 1

For the converse, we need to prove that for any p.m.f.

$$\begin{split} p(x_1, x_2, u_1, u_2, \tilde{x}_1, \tilde{x}_2, y) = \\ p(x_1) p(x_2) p(u_1, \tilde{x}_1 | x_1) p(u_2, \tilde{x}_2 | x_2) p(y | u_1, u_2, \tilde{x}_1, \tilde{x}_2) \end{split}$$

such that

$$\sum_{\mu_1, u_2, \tilde{x}_1, \tilde{x}_2} p(x_1, x_2, u_1, u_2, \tilde{x}_1, \tilde{x}_2, y) = q(x_1, x_2, y)$$

we have $I(U_1, \tilde{X}_1; X_1) \geq 2$ and $I(U_2, \tilde{X}_2; X_2) \geq 1$. The independence between X_1 and X_2 along with the long Markov chain $(U_1, \tilde{X}_1) \rightarrow X_1 \rightarrow X_2 \rightarrow (U_2, \tilde{X}_2)$ ensures that (U_1, \tilde{X}_1, X_1) is independent of (U_2, \tilde{X}_2, X_2) . We also have the output Markov chain $Y \rightarrow (U_1, \tilde{X}_1, U_2, \tilde{X}_2) \rightarrow (X_1, X_2)$. Clearly, if $H(X_1|U_1, \tilde{X}_1) = H(X_2|U_2, \tilde{X}_2) = 0$, it follows that $I(U_1, \tilde{X}_1; X_1) = H(X_1) = 2$ and $I(U_2, \tilde{X}_2; X_2) =$ $H(X_2) = 1$. We now prove that if either $H(X_1|U_1, \tilde{X}_1) > 0$ or $H(X_2|U_2, \tilde{X}_2) \geq 0$, a contradiction arises.

Let $H(X_2|U_2, \tilde{X}_2) > 0$ (which means $I(U_2, X_2; X_2) = H(X_2) - H(X_2|U_2, \tilde{X}_2) = 1 - H(X_2|U_2, \tilde{X}_2) < 1$) for the sake of contradiction. Hence there exist (u_2, \tilde{x}_2) with $P(U_2 = u_2, \tilde{X}_2 = \tilde{x}_2) > 0$ such that $p_{X_2|U_2=u_2, \tilde{X}_2=\tilde{x}_2}$ is supported on $\{1,2\}$. We note that the Markov chain $Y \to (X_1, U_2, \tilde{X}_2) \to X_2$ holds because

$$I(Y; X_2|X_1, U_2, \tilde{X}_2) \leq I(Y, U_1, \tilde{X}_1; X_2|X_1, U_2, \tilde{X}_2)$$

= $I(U_1, \tilde{X}_1; X_2|X_1, U_2, \tilde{X}_2) + I(Y; X_2|U_1, \tilde{X}_1, U_2, \tilde{X}_2, X_1)$
 $\leq I(U_1, \tilde{X}_1, X_1; U_2, \tilde{X}_2, X_2) + I(Y; X_1, X_2|U_1, \tilde{X}_1, U_2, \tilde{X}_2)$
= 0, (27)

where the last equality follows because (U_1, \tilde{X}_1, X_1) is independent of (U_2, \tilde{X}_2, X_2) and the Markov chain $Y \rightarrow (U_1, \tilde{X}_1, U_2, \tilde{X}_2) \rightarrow (X_1, X_2)$ holds.

Let us consider the induced distribution given by $p_{Y|X_1=(0,1),U_2=u_2,\tilde{X}_2=\tilde{x}_2}$. This is well-defined because $P(X_1=(0,1),U_2=u_2,\tilde{X}_2=\tilde{x}_2)>0$ as X_1 is independent of (U_2,\tilde{X}_2) and $P(X_1=(0,1))>0$, $P(U_2=u_2,\tilde{X}_2=\tilde{x}_2)>0$. The fact that

$$P(X_2 = 2 | X_1 = (0, 1), U_2 = u_2, X_2 = \tilde{x}_2)$$

= $P(X_2 = 2 | U_2 = u_2, \tilde{X}_2 = \tilde{x}_2) > 0$

along with the Markov chain $Y \to (X_1, U_2, \tilde{X}_2) \to X_2$ imply

$$P(Y = 0|X_1 = (0, 1), U_2 = u_2, X_2 = \tilde{x}_2)$$

= $P(Y = 0|X_1 = (0, 1), U_2 = u_2, \tilde{X}_2 = \tilde{x}_2, X_2 = 2) = 0.$ (28)

Likewise, the fact that

$$P(X_2 = 1 | X_1 = (0, 1), U_2 = u_2, \tilde{X}_2 = \tilde{x}_2)$$

= $P(X_2 = 1 | U_2 = u_2, \tilde{X}_2 = \tilde{x}_2) > 0$

along with the Markov chain $Y \to (X_1, U_2, \tilde{X}_2) \to X_2$ imply $P(Y = 1 | X_1 = (0, 1), U_2 = u_2, \tilde{X}_2 = \tilde{x}_2)$

$$= P(Y = 1 | X_1 = (0, 1), U_2 = u_2, \tilde{X}_2 = \tilde{x}_2, X_2 = 1) = 0.$$
(29)

From (28) and (29), we are led to a contradiction since $p_{Y|X_1=(0,1),U_2=u_2,\tilde{X}_2=\tilde{x}_2}$ has to be a probability distribution.

Similarly, let $H(X_1|U_1, \tilde{X}_1) > 0$ (which means $I(U_1, \tilde{X}_1; X_1) = H(X_1) - H(X_1|U_1, \tilde{X}_1) = 2 - H(X_1|U_1, \tilde{X}_1) < 2$) for the sake of contradiction. Hence there exist (u_1, \tilde{x}_1) with $P(U_1 = u_1, \tilde{X}_1 = \tilde{x}_1) > 0$ such that $p_{X_1|U_1=u_1, \tilde{X}_1=\tilde{x}_1}$ has a support whose size is larger than 1. This means that the support can be a superset of $\{(0,0), (0,1)\}, \{(0,0), (1,0)\}, \{(0,0), (1,1)\}, \{(0,1), (1,0)\}, \{(0,1), (1,1)\}$ or $\{(1,0), (1,1)\}$ - these are considered in turn next. We note that the Markov chain $Y \to (X_2, U_1, \tilde{X}_1) \to X_1$ holds via similar reasoning as (27).

Suppose that the support of $p_{X_1|U_1=u_1,\tilde{X}_1=\tilde{x}_1}$ is a superset of $\{(0,0), (0,1)\}$. Let us consider the induced distribution given by $p_{Y|X_2=2,U_1=u_1,\tilde{X}_1=\tilde{x}_1}$. This is well-defined because $P(X_2 = 2, U_1 = u_1, \tilde{X}_1 = \tilde{x}_1) > 0$ as X_2 is independent of (U_1, \tilde{X}_1) and $P(X_2 = 2) > 0, P(U_1 = u_1, \tilde{X}_1 = \tilde{x}_1) > 0$. The fact that $P(X_1 = (0, 1)|X_2 = 2, U_1 = u_1, \tilde{X}_1 = \tilde{x}_1) > 0$ along with the Markov chain $Y \to (X_2, U_1, \tilde{X}_1) \to X_1$ imply

$$P(Y = 0 | X_2 = 2, U_1 = u_1, X_1 = \tilde{x}_1)$$

= $P(Y = 0 | X_2 = 2, U_1 = u_1, \tilde{X}_1 = \tilde{x}_1, X_1 = (0, 1)) = 0.$

Likewise, the fact that $P(X_1 = (0,0)|X_2 = 2, U_1 = u_1, \tilde{X}_1 = \tilde{x}_1) > 0$ along with the Markov chain $Y \to (X_2, U_1, \tilde{X}_1) \to X_1$ imply

$$P(Y = 1 | X_2 = 2, U_1 = u_1, \tilde{X}_1 = \tilde{x}_1)$$

= $P(Y = 1 | X_2 = 2, U_1 = u_1, \tilde{X}_1 = \tilde{x}_1, X_1 = (0, 0)) = 0.$

We are led to a contradiction since $p_{Y|X_2=2,U_1=u_1,\tilde{X}_1=\tilde{x}_1}$ has to be a probability distribution.

Next suppose that the support of $p_{X_1|U_1=u_1,\tilde{X}_1=\tilde{x}_1}$ is a superset of $\{(0,0),(1,0)\}$. We consider the well-defined distribution $p_{Y|X_2=1,U_1=u_1,\tilde{X}_1=\tilde{x}_1}$. The fact that $P(X_1 = (1,0)|X_2 = 1, U_1 = u_1, \tilde{X}_1 = \tilde{x}_1) > 0$ along with the Markov chain $Y \to (X_2, U_1, \tilde{X}_1) \to X_1$ imply

$$P(Y = 0 | X_2 = 1, U_1 = u_1, X_1 = \tilde{x}_1)$$

= $P(Y = 0 | X_2 = 1, U_1 = u_1, \tilde{X}_1 = \tilde{x}_1, X_1 = (1, 0)) = 0.$

Likewise, the fact that $P(X_1 = (0,0)|X_2 = 1, U_1 = u_1, \tilde{X}_1 = \tilde{x}_1) > 0$ along with the Markov chain $Y \to (X_2, U_1, \tilde{X}_1) \to X_1$ imply

$$P(Y = 1 | X_2 = 1, U_1 = u_1, \tilde{X}_1 = \tilde{x}_1)$$

= $P(Y = 1 | X_2 = 1, U_1 = u_1, \tilde{X}_1 = \tilde{x}_1, X_1 = (0, 0)) = 0.$

We are led to a contradiction since $p_{Y|X_2=1,U_1=u_1,\tilde{X}_1=\tilde{x}_1}$ has to be a probability distribution. The other supports $\{(0,0),(1,1)\}$, $\{(0,1),(1,0)\}$, $\{(0,1),(1,1)\}$ and $\{(1,0),(1,1)\}$ can be analyzed in a similar manner to arrive at a contradiction.