Multi-Objective Hyperparameter Selection via Hypothesis Testing on Reliability Graphs

Amirmohammad Farzaneh¹ Osvaldo Simeone¹

Abstract

In sensitive application domains, multi-objective hyperparameter selection can ensure the reliability of AI models prior to deployment, while optimizing auxiliary performance metrics. The state-of-the-art Pareto Testing (PT) method guarantees statistical reliability constraints by adopting a multiple hypothesis testing framework. In PT, hyperparameters are validated one at a time, following a data-driven order determined by expected reliability levels. This paper introduces a novel framework for multi-objective hyperparameter selection that captures the interdependencies among the reliability levels of different hyperparameter configurations using a directed acyclic graph (DAG), which is termed the reliability graph (RG). The RG is constructed based on prior information and data by using the Bradley-Terry model. The proposed approach, RG-based PT (RG-PT), leverages the RG to enable the efficient, parallel testing of multiple hyperparameters at the same reliability level. By integrating False Discovery Rate (FDR) control, RG-PT ensures robust statistical reliability guarantees and is shown via experiments across diverse domains to consistently yield superior solutions for multi-objective calibration problems.

1. Introduction

1.1. Context and Motivation

Hyperparameter optimization is an essential element of the machine learning pipeline, particularly in sensitive domains such as healthcare, finance, and engineering [\(Bischl et al.,](#page-8-0) [2023;](#page-8-0) [Yang & Shami,](#page-10-0) [2020\)](#page-10-0). Hyperparameters to be set prior to deployment include *training parameters* such as

Figure 1. Comparison of Pareto Testing (PT) [\(Laufer-Goldshtein](#page-9-0) [et al.,](#page-9-0) [2023\)](#page-9-0) and reliability graph-based PT (RG-PT) proposed in this work. (a) PT first estimates the Pareto front in the space of risk functions to be controlled (horizontal axis) and optimized (vertical axis), with the red dashed line indicating the reliability constraint. (b) PT then tests the reliability of hyperparameters λ sequentially, in the order of estimated reliability. (c) RG-PT first estimates interdependencies among the reliability levels of different hyperparameter configurations using a directed acyclic graph (DAG), which is termed the reliability graph (RG). This enables efficient parallel testing of multiple hyperparameters, potentially discovering more effective hyperparameter configurations (see Fig. [2\)](#page-1-0).

learning rates, regularization constants, and reward priorities in reinforcement learning systems [\(Eimer et al.,](#page-8-1) [2023\)](#page-8-1), *inference parameters*, such as decision thresholds [\(Hancock](#page-8-2) [et al.,](#page-8-2) [2022\)](#page-8-2), and *complexity settings* determining numerical accuracy and computational efficiency [\(Hu et al.,](#page-9-1) [2021\)](#page-9-1). Hyperparameter selection typically targets multiple performance objectives, such as classification accuracy, calibration, fairness, and domain-specific criteria, such as tracking precision [\(Dong et al.,](#page-8-3) [2018\)](#page-8-3), perplexity [\(Rahnama et al.,](#page-9-2) [2018\)](#page-9-2), and transmission rates [\(Chen et al.,](#page-8-4) [2020\)](#page-8-4).

Validation can be costly. Notably, determining training or fine-tuning parameters in large language models (LLMs) requires running expensive optimization procedures, and many engineering problems require interaction with the real world [\(Polese et al.,](#page-9-3) [2023\)](#page-9-3). Thus, in modern settings, it is common to limit the search to a pre-selected discrete set of configurations for the hyperparameters [\(Bergstra & Bengio,](#page-8-5) [2012\)](#page-8-5).

Most existing hyperparameter selection strategies make a

¹Centre for Intelligent Information Processing Systems, Department of Engineering, King's College London, London, United Kingdom. Correspondence to: Amirmohammad Farzaneh <amirmohammad.farzaneh@kcl.ac.uk>.

best-effort attempt at addressing multi-objective problems. This is done by estimating functions of the Pareto front for the performance criteria of interest [\(Deb et al.,](#page-8-6) [2002;](#page-8-6) Hernández-Lobato et al., [2016;](#page-8-7) [Paria et al.,](#page-9-4) [2020;](#page-9-4) [Li et al.,](#page-9-5) [2020\)](#page-9-5). An important, recent, exception is Pareto Testing (PT) [\(Laufer-Goldshtein et al.,](#page-9-0) [2023\)](#page-9-0). PT builds on Learn-Then-Test (LTT) [\(Angelopoulos et al.,](#page-8-8) [2021\)](#page-8-8), which pioneered the use of multiple hypothesis testing (MHT) to ensure the statistical validity of hyperparameter selection.

As illustrated in Fig. [1,](#page-0-0) PT carries out a preliminary besteffort optimization step to estimate the Pareto front in the space of the objectives of interest. These encompass risk functions that must be controlled, encoding reliability constraint, as well as auxiliary risk functions to be optimized. PT proceeds by testing the candidate hyperparameters according to the linear order determined by the increasing value of the estimated reliability risk functions (see Fig. [1\(](#page-0-0)b)).

This paper is motivated by the observation that, especially in engineering applications, the hyperparameter space is often highly structured, and not all configurations can be neatly ordered by their reliability levels. To account for this, we introduce a novel *multi-objective hyperparameter selection* method that operates on a directed acyclic graph (DAG), termed the *reliability graph* (RG). In an RG, nodes represent candidate hyperparameter configurations and an edge directed from one hyperparameter to another indicates that the reliability of the first hyperparameter is predictive of the reliability level of the second hyperparameter (see Fig. $1(c)$ $1(c)$).

The proposed hyperparameter selection method, referred to as *RG-based Pareto Testing* (RG-PT), constructs an RG based on prior knowledge and limited validation data. Prior knowledge may include properties such as the reduction in reliability that may result from an increased sparsity at the levels of model parameters [\(Zhou et al.,](#page-10-1) [2021\)](#page-10-1) or activations [\(Chen et al.,](#page-8-9) [2023\)](#page-8-9). By incorporating MHT mechanisms operating on a DAG [\(Ramdas et al.,](#page-9-6) [2019\)](#page-9-6) within the PT framework, RG-PT allows for a more efficient testing that can discover more effective hyperparameter configurations, while offering reliability guarantees (see Fig. [2\)](#page-1-0).

1.2. Further Related Work

Hyperparameter Selection: Traditional methods for hyperparameter optimization like grid search and random search [\(Bergstra & Bengio,](#page-8-5) [2012\)](#page-8-5) are widely used but they can be inefficient. In contrast, more advanced techniques such as Bayesian optimization [\(Snoek et al.,](#page-10-2) [2012\)](#page-10-2) and bandit-based methods, such as Hyperband [\(Li et al.,](#page-9-7) [2018\)](#page-9-7) and gradientbased optimization [\(Maclaurin et al.,](#page-9-8) [2015\)](#page-9-8), can enhance computational efficiency via resource allocation, but they lack statistical guarantees. This gap addressed is by the

Figure 2. Illustration of the benefits of the proposed RG-PT hyperparameter selection scheme over the state-of-the-art LTT and PT for an object detection application [\(Angelopoulos et al.,](#page-8-8) [2021\)](#page-8-8). The red arrows mark the objects not detected by an object recognition model calibrated using LTT or PT that are instead detected by the same model calibrated via RG-PT (see Sec. [5.2](#page-7-0) for details).

mentioned frameworks incorporating MHT [\(Angelopoulos](#page-8-8) [et al.,](#page-8-8) [2021;](#page-8-8) [Laufer-Goldshtein et al.,](#page-9-0) [2023\)](#page-9-0).

Multi-Objective Optimization: Modern AI applications often require optimizing multiple objectives such as accuracy and efficiency. This can be formally done through Pareto optimization to identify all the feasible trade-off points among different objectives [\(Deb et al.,](#page-8-6) [2002\)](#page-8-6). PT [\(Laufer-Goldshtein et al.,](#page-9-0) [2023\)](#page-9-0) applies MHT to provide statistical reliability while balancing multiple objectives.

Conformal Prediction and LTT: Conformal prediction constructs statistically valid prediction intervals using calibration data [\(Shafer & Vovk,](#page-9-9) [2008;](#page-9-9) [Romano et al.,](#page-9-10) [2019\)](#page-9-10). Drawing inspiration from conformal prediction, LTT [\(Angelopou](#page-8-8)[los et al.,](#page-8-8) [2021\)](#page-8-8) frames hyperparameter selection as an MHT problem. While [\(Angelopoulos et al.,](#page-8-8) [2021\)](#page-8-8) mentions the possible use of graph-based approaches, these are limited to fixed user-defined graphs or linear directed graphs (chains). Other extensions of LTT include quantile control [\(Farzaneh](#page-8-10) [et al.,](#page-8-10) [2024\)](#page-8-10), applications to information theory [\(Farzaneh &](#page-8-11) [Simeone,](#page-8-11) [2024\)](#page-8-11), and adaptive testing mechanisms [\(Zecchin](#page-10-3) [& Simeone,](#page-10-3) [2024\)](#page-10-3).

1.3. Main Contributions

The main contributions of this paper are as follows.

Methodology: We propose RG-PT, a novel multi-objective hyperparameter selection framework that systematically utilizes interdependencies among the reliability levels of candidate hyperparameter configurations. RG-PT infers precedence relationships among the reliability levels of hyperparameters from prior information and data by constructing an RG via the Bradley-Terry (BT) ranking model [\(Hunter,](#page-9-11) [2004\)](#page-9-11). Then, it applies MHT-based hyperparameter selection on the RG by following the graphical testing method in [\(Ramdas et al.,](#page-9-6) [2019\)](#page-9-6).

Applications: We demonstrate the effectiveness of RG-PT through experiments in various scenarios, including language model calibration [\(Peters & Martins,](#page-9-12) [2021\)](#page-9-12), object detection [\(Angelopoulos et al.,](#page-8-8) [2021\)](#page-8-8), image classification [\(Franceschi et al.,](#page-8-12) [2024\)](#page-8-12), and telecommunications engineering [\(Valcarce,](#page-10-4) [2020\)](#page-10-4), highlighting its advantages over conventional methods.

The rest of this paper is organized as follows. In Sec. [2,](#page-2-0) we define the multi-objective hyperparameter selection problem. Sec. [3](#page-2-1) provides an overview of PT, and Sec. [4](#page-3-0) details the proposed RG-PT framework. Experimental results are presented in Sec. [5.](#page-6-0) We conclude the paper in Sec. [6.](#page-7-1)

2. Multi-Objective Hyperparameter Selection

In this section, we define the problem of multi-objective hyperparameter selection, and we show how this problem can be formulated via MHT by following references [\(An](#page-8-8)[gelopoulos et al.,](#page-8-8) [2021;](#page-8-8) [Laufer-Goldshtein et al.,](#page-9-0) [2023\)](#page-9-0).

2.1. Problem Definition

Consider a predefined discrete and finite set Λ of hyperparameters λ , which govern the performance of a machine learning model (see, e.g., [\(Bergstra & Bengio,](#page-8-5) [2012\)](#page-8-5)). Hyperparameter selection aims at obtaining a hyperparameter $\lambda \in \Lambda$ by considering its performance via L risk functions. Specifically, when tested on a data point Z , a hyperparameter λ attains risk values $r_l(Z, \lambda)$ for $l = 1, \ldots, L$. The risk functions $r_l(Z, \lambda)$ are negatively oriented, meaning that lower risk values correspond to better-performing hyperparameters. The risks are normalized within the range $0 \leq r_l(Z,\lambda) \leq 1.$

For each performance criterion $l = 1, \ldots, L$, the *average risk function* is defined as

$$
R_l(\lambda) = \mathbb{E}_Z \left[r_l(Z, \lambda) \right],\tag{1}
$$

where the expectation is taken over the distribution P_Z of the data Z.

We partition the set of L risk functions into the following two groups:

1. *Reliability risk functions:* The first set of risk functions ${R_l(\lambda)}_{l=1}^{L_c}$ must be controlled via the choice of the hyperparameter λ . In particular, a hyperparameter configuration λ is said to be *reliable* if it guarantees the constraints

$$
R_l(\lambda) \le \alpha_l \quad \text{for all} \quad l = 1, \dots, L_c. \tag{2}
$$

2. *Auxiliary risk functions:* The second set of performance

measures $\{R_l(\lambda)\}_{l=L_c+1}^L$ are unconstrained, and they are ideally optimized via the selection of the hyperparameter λ .

Accordingly, the goal of hyperparameter selection is defined as the *multi-objective problem*

$$
\min_{\lambda \in \Lambda} \{ R_{L_c+1}(\lambda), R_{L_c+2}(\lambda), \dots, R_L(\lambda) \}
$$
\nsubject to $R_l(\lambda) < \alpha_l$ for all $1 \leq l \leq L_c$,\n\n(3)

which targets the minimization of the auxiliary risk functions $\{R_l(\lambda)\}_{l=L_c+1}^L$ under constraints on the reliability risk functions $\{R_l(\lambda)\}_{l=1}^{L_c}$. Solving a multi-objective optimization problem such as [\(3\)](#page-2-2) may entail identifying the entire Pareto front of dominant solutions $\lambda \in \Lambda$, or obtaining specific solutions corresponding to scalar criteria [\(Deb et al.,](#page-8-13) [2016;](#page-8-13) [Jamieson & Talwalkar,](#page-9-13) [2016\)](#page-9-13).

The problem [\(3\)](#page-2-2) cannot be directly addressed since the data distribution P_Z is unknown. However, we assume to have access to i.i.d. data $\mathcal{Z} = \{Z_j\}_{j=1}^n$ drawn from the unknown data distribution P_Z . For any subset $\widetilde{\mathcal{Z}} \subseteq \mathcal{Z}$, we write as

$$
\hat{R}_l(\lambda|\widetilde{\mathcal{Z}}) = \frac{1}{|\widetilde{\mathcal{Z}}|} \sum_{Z \in \widetilde{\mathcal{Z}}} r_l(Z, \lambda) \tag{4}
$$

the corresponding empirical estimate of risk function $R_l(\lambda)$.

2.2. Hyperparameter Selection as Multiple Hypothesis Testing

As proposed in [\(Angelopoulos et al.,](#page-8-8) [2021\)](#page-8-8), hyperparameter selection can be formally addressed as an MHT problem. Accordingly, for each hyperparameter $\lambda \in \Lambda$, we define the null hypothesis \mathcal{H}_{λ} that hyperparameter λ is not reliable, violating the constraints [\(2\)](#page-2-3), i.e.,

$$
\mathcal{H}_{\lambda}: \text{ there exists } l \in \{1, \ldots, L_{c}\} \text{ such that } R_{l}(\lambda) > \alpha_{l}.
$$
\n
$$
(5)
$$

Thus, rejecting the null hypothesis \mathcal{H}_{λ} implies that hyperparameter λ is reliable, meeting all the constraints in [\(2\)](#page-2-3). A rejection is also referred to as a *discovery*. A discovery is *false* if the selected hyperparameter λ is actually unreliable, satisfying the null hypothesis \mathcal{H}_{λ} .

As discussed in the next section, by formulating hyperparameter selection as an MHT problem, we can leverage statistical tools that guarantee *false discovery rate* (FDR) requirements [\(Casella & Berger,](#page-8-14) [2024\)](#page-8-14), ensuring that any selected configuration satisfies the risk constraints in [\(3\)](#page-2-2) with a prescribed probability.

3. Background: Pareto Testing

In this section, we review PT [\(Laufer-Goldshtein et al.,](#page-9-0) [2023\)](#page-9-0), a state-of-the-art MHT-based multi-objective hyperparameter selection method.

3.1. Statistical Reliability Constraints

Problem [\(3\)](#page-2-2) cannot be directly solved since we only assume access to the empirical estimates. Following LTT [\(Angelopoulos et al.,](#page-8-8) [2021\)](#page-8-8), using the data set Z , PT finds a subset $\widehat{\Lambda}_{\mathcal{Z}} \subseteq \Lambda$ of hyperparameters that satisfies the statistical constraint |
|
|is
d
es $\frac{1}{2}$ ve
ov

ˆI^DOPT

Pr^Z -Rl(λ) ≤ α^l for all l = 1, . . . , Lc, and for all ^λ [∈] Λˆ ^Z ≥ 1 − δ, (6) two disjoint subsets ^DOPT and ^DMHT ○² Approximating the Pareto frontier using the estimates ^ˆI^DOPT (T; ^Y) and ^ˆI^DOPT (X; T) to form ⇤OPT ○3 Applying sequential FWER-controlling algorithm 1 Introduction

where $0 \le \delta \le 1$ is a user-specified probability of failure, and the probability is evaluated over the calibration data Z. The condition [\(6\)](#page-3-1), known as *family-wise error rate* (FWER) control, ensures that all the hyperparameters λ in the selected set Λ_z are reliable with probability at least $1 - \delta$.

3.2. Pareto Testing

PT [\(Laufer-Goldshtein et al.,](#page-9-0) [2023\)](#page-9-0) leverages held-out data to select the testing order for addressing problems of the form [\(3\)](#page-2-2). The procedure is summarized in Fig. [3,](#page-3-2) and it consists of the following steps:

⃝1 *Estimating the Pareto front for all risk measures:* PT divides the calibration dataset Z into two disjoint subsets, Z_{OPT} and Z_{MHT} . Using the data set Z_{OPT} , it identifies the subset $\Lambda_{\text{OPT}} \subseteq \Lambda$ of hyperparameters that are on the Pareto front of the space of estimated risk measures $\{\hat{R}_l(\lambda | \mathcal{Z}_{\text{OPT}})\}_{l=1}^L$. This is done by addressing the multi-objective optimization problem [\(3\)](#page-2-2) with the estimates $\{\hat{R}_l(\lambda | \mathcal{Z}_{\text{OPT}})\}_{l=1}^L$ in lieu of the true risks $\{R_l(\lambda | \mathcal{Z}_{\text{OPT}})\}_{l=1}^L$ by using any existing algorithm [\(Laufer-Goldshtein et al.,](#page-9-0) [2023\)](#page-9-0).

⃝2 *Ordering the hyperparameters:* PT creates a global linear ordering on the hyperparameters in the set Λ_{OPT} by using the estimates $\{\hat{R}_l(\lambda|\mathcal{Z}_{\text{OPT}})\}_{l=1}^{L_c}$ of the reliability risk functions.

 $\textcircled{3}$ *FWER-controlling MHT:* Using the data set \mathcal{Z}_{MHT} , FWER-controlling MHT is carried out via fixed sequence testing (FST) [\(Maurer,](#page-9-14) [1995\)](#page-9-14) by following the order found in the previous step. This results in the subset $\Lambda_{\mathcal{Z}}$ of reliable hyperparameters that are guaranteed to satisfy the condition [\(6\)](#page-3-1).

⃝4 *Addressing the multi-objective optimization problem:* Given the subset $\Lambda_{\mathcal{Z}}$, PT addresses the problem

$$
\min_{\lambda \in \hat{\Lambda}_{\mathcal{Z}}} \{ \hat{R}_{L_c+1}(\lambda | \mathcal{Z}_{\text{OPT}}), \dots, \hat{R}_{L}(\lambda | \mathcal{Z}_{\text{OPT}}) \},\tag{7}
$$

where the auxiliary risk functions $R_l(\lambda)$ in [\(3\)](#page-2-2) are replaced with the corresponding empirical estimates [\(4\)](#page-2-4) obtained with data set \mathcal{Z}_{OPT} .

To elaborate on steps (2) - (3) , for each null hypothesis \mathcal{H}_{λ} in

tier using the estimates $\hat{R}_1(\lambda | \mathcal{Z}_{\text{OPT}})$ and $\hat{R}_2(\lambda | \mathcal{Z}_{\text{OPT}})$ to form the while minimizing the risk $R_2(\lambda)$: ① Approximate the Pareto fronand for all $\lambda \in \hat{\Lambda}_z$ $\geq 1 - \delta$, (0) Figure 3. Illustration of the operation of PT [\(Laufer-Goldshtein](#page-9-0) jective is to control the risk $R_1(\lambda)$ to be below the threshold α , subset of hyperparameters Λ_{OPT} ; $\textcircled{2}$ - $\textcircled{4}$ Apply a sequential FDR[et al.,](#page-9-0) [2023\)](#page-9-0) for two risk functions $R_1(\lambda)$ and $R_2(\lambda)$. The obcontrolling algorithm on the hyperparameters in Λ_{OPT} to obtain the subset $\hat{\Lambda}_z$, and select the hyperparameter λ^* that minimizes $\ddot{R}_2(\lambda | \mathcal{Z}_{\text{OPT}}).$

[\(5\)](#page-2-5), given a data set $\widetilde{\mathcal{Z}} \subseteq \mathcal{Z}$, define the p-value [\(Rice,](#page-9-15) [2006\)](#page-9-15)

$$
p_{\lambda,l}(\widetilde{\mathcal{Z}}) = e^{-2|\widetilde{\mathcal{Z}}|(\alpha_l - \hat{R}_l(\lambda|\widetilde{\mathcal{Z}}))^2_+}
$$
(8)

for $l = 1, \ldots, L_c$, and the combined p-value

$$
p_{\lambda}(\widetilde{\mathcal{Z}}) = \max_{1 \le l \le L_c} p_{\lambda,l}(\widetilde{\mathcal{Z}}). \tag{9}
$$

rameters according to data Z_{OPT} . FST, a sequential MHT In step (2) , hyperparameters in set Λ_{OPT} are ordered from low to high based on the combined p-value $p_{\lambda}(\mathcal{Z}_{\text{OPT}})$, reflecting an ordering from most to least reliable hyperpaalgorithm (see Appendix [A\)](#page-11-0), is then applied by using the combined *p*-values $p_{\lambda}(\mathcal{Z}_{\text{MHT}})$.

4. Reliability Graph-Based Pareto Testing

In this section, we introduce RG-PT, a novel hyperparameter selection strategy based on MHT that adopts a testing schedule based on the novel concept of RG.

4.1. Overview

The general principle underlying RG-PT is that the reliability of some hyperparameters can be highly predictive of the reliability of other hyperparameters. This structure is encoded in an RG by leveraging prior information and data via the BT model [\(Hunter,](#page-9-11) [2004\)](#page-9-11). By testing on a DAG, RG-PT supports a more flexible and efficient testing procedure that allows for the testing of multiple hyperparameters in parallel.

Using a partition $\{Z_{\text{OPT}}, Z_{\text{MHT}}\}$ of the data set Z, at a high level, RG-PT consists of the following steps, which are illustrated in Fig. [4:](#page-4-0)

⃝1 *Estimating the Pareto front for all risk measures:* Using the data set \mathcal{Z}_{OPT} , RG-PT identifies the the subset $\Lambda_{\text{OPT}} \subseteq \Lambda$

Ξ ۰

DOPT

DMHT

 $\overline{}$

amirfar76

ˆ

September 2024

over the selected hyperparameters; 3 Apply an FDR-controlling hyperparameters Λo_{PT} lying on the Pareto front; ② Build the RG Figure 4. Illustration of the main steps of RG-PT: $\circled{1}$ Estimate the MHT procedure, DAGGER, to the RG.

of hyperparameters that are estimated to lie on the Pareto front in the same manner as PT (see previous section).

⃝2 *Learning the reliability graph:* Rather than ordering the hyperparameters globally and sequentially as done by PT, RG-PT creates an RG, with nodes given by the hyperparameters in subset Λ_{OPT} . This is done by following the principle that hyperparameters $\lambda \in \Lambda_{\text{OPT}}$ whose reliability levels are predictive of the reliability levels of other hyperparameters $\Lambda' \subset \Lambda_{\text{OPT}}$ should be tested before the hyperparameters Λ' . Details are provided in Sec. [4.2.](#page-4-1)

1 1 ⃝3 *FDR-controlling MHT:* FDR-controlling MHT is carried out by following the order encoded by the RG. As explained in Sec. [4.2,](#page-4-1) this is done by using DAGGER [\(Ramdas et al.,](#page-9-6) [2019\)](#page-9-6), targeting FDR requirements.

⃝4 *Addressing the multi-objective optimization problem*: Using the estimated subset $\Lambda_{\mathcal{Z}}$ of reliable hyperparameters, the multi-objective optimization problem [\(7\)](#page-3-3) is addressed in the same manner as PT (see previous section).

4.2. Learning the Reliability Graph

expectation that parent nodes are predictive of the reliability After obtaining the estimated Pareto front Λ_{OPT} , RG-PT constructs an RG to encode the expected relationships between the reliability levels attained by the candidate hyperparameters in the set Λ_{OPT} . The RG is a DAG, in which each node represents a hyperparameter, and edges are directed to describe a reliability hierarchy. Specifically, edges encode the of their child nodes.

Starting from the nodes with no parents and following the direction of the edges in the RG, one encounters hyperparameters that are estimated to be increasingly unreliable. Generalizing the linear ordering assumed by PT, the DAG structure adopted by RG-PT can assign the same expected reliability ranking to multiple hyperparameters. Specifically, all the hyperparameters at the same depth in the DAG are deemed to have the same relative reliability level.

In order to learn the RG, RG-PT leverages the data set \mathcal{Z}_{OPT} ,

reliability of pairs of hyperparameters. This is done by \mathbf{u} \mathbf{v} following two steps: as well as, possibly, prior information about the relative

For matriple hyperparameters to be ranked equally. This effectively assigns a depth level d in the DAG to each hyperrepin assi \circ Learn the RG \circ \circ \circ Apply FDR-
for multiple hyperparameters to be ranked equally. This the same depth level. This step is explained in Sec. [4.2.1.](#page-4-2) 1. *Depth assignment:* The hyperparameters in set Λ_{OPT} are $\frac{1}{\hat{R}_1(\lambda | Z_{\text{OPT}})}$ $\mathcal G$ ranked in terms of their expected reliability, while allowing parameter, with multiple hyperparameters possibly sharing

> λ at some depth d, RG-PT selects a subset of hyperparam-2. *Learning the directed edges:* Given any hyperparameter eters at the previous depth level $d - 1$ to serve as parents of the hyperparameter λ . This is done by choosing the hyperparameters at depth $d-1$ that are most predictive of the reliability level of hyperparameter λ . This step is explained in Sec. [4.2.2.](#page-5-0)

4.2.1. DEPTH ASSIGNMENT

 $1 < D < |\Lambda_{\text{OPT}}|$, which is assumed from now on. Fix a number $D \leq |\Lambda_{\text{OPT}}|$ of levels for the DAG. With $D = |\Lambda_{\text{OPT}}|$, one can assign each hyperparameter $\lambda \in \Lambda_{\text{OPT}}$ a distinct level, yielding a global ordering and recovering PT. Conversely, with $D = 1$, all hyperparameters $\lambda \in \Lambda_{\text{OPT}}$ are assigned to the same level. The setting of interest is thus

 Z_{OPT} , and then partitioning the set Λ_{OPT} into D clusters Depth assignment is carried out by first obtaining a score s(λ) for all hyperparameters $\lambda \in \Lambda_{\text{OPT}}$ using the data set according to the obtained scores.

To compute the scores $s(\lambda)$ for hyperparameters $\lambda \in \Lambda_{\text{OPT}}$, we use the BT model [\(Hunter,](#page-9-11) [2004\)](#page-9-11). The BT model converts pairwise counts w_{ij} for all pairs of hyperparameters λ_i and λ_i in subset Λ_{OPT} into per-hyperparameter scores $s(\lambda)$ for all $\lambda \in \Lambda_{\text{OPT}}$. The pairwise counts measure the number of times that hyperparameter λ_i was found to be more reliable than hyperparameter λ_j . In RG-PT, we propose to evaluate the pairwise counts w_{ij} by leveraging two sources of information:

• *Prior information:* Prior information is encoded by pairwise probabilities $0 \leq \eta_{ij} \leq 1$ for each pair of hyperparameters $\lambda_i, \lambda_j \in \Lambda_{\text{OPT}}$. This probability reflects the expected rate at which hyperparameter λ_i is observed to be more reliable than hyperparameter λ_i . Note that we have $\eta_{ji} = 1 - \eta_{ij}$. The strength of the prior information is determined via a pseudocount variable n_p as in the standard categorical-Dirichlet model [\(Bishop & Nasrabadi,](#page-8-15) [2006\)](#page-8-15). A larger pseudocount n_p indicates a stronger trust in the prior information. Importantly, the statistical guarantees of RG-PT do not depend on the choice of the prior probabilities ${n_p}$ and pseudocount n_p , which can, however, improve the capacity of RG-PT to optimize the auxiliary risk functions. Note that in the absence of prior information, one can

set $n_p = 0$.

• *Data:* Using the *p*-values $p_{\lambda_i}(\mathcal{Z}_{\text{OPT}})$ and $p_{\lambda_j}(\mathcal{Z}_{\text{OPT}})$ in [\(9\)](#page-3-4), we evaluate the data-driven probability

$$
p_{ij}(\mathcal{Z}_{\text{OPT}}) = \frac{p_{\lambda_i}(\mathcal{Z}_{\text{OPT}})}{p_{\lambda_i}(\mathcal{Z}_{\text{OPT}}) + p_{\lambda_j}(\mathcal{Z}_{\text{OPT}})}\tag{10}
$$

that hyperparameter λ_i is more reliable than hyperparameter λ_j . Note that we have $p_{ij}(\mathcal{Z}_{\text{OPT}}) = 1 - p_{ji}(\mathcal{Z}_{\text{OPT}})$.

Overall, the pair-wise probability w_{ij} is obtained by combining prior information and data as

$$
w_{ij} = |\mathcal{Z}_{\text{OPT}}| p_{ij}(\mathcal{Z}_{\text{OPT}}) + n_p \eta_{ij}, \tag{11}
$$

so that the strength of the prior depends on the ratio $n_p/|\mathcal{Z}_{\text{OPT}}|$ between the pseudocount n_p and the number of data points $|\mathcal{Z}_{\text{OPT}}|$.

Using the BT model, the scores $s(\lambda_i)$ for all hyperparameters $\lambda_i \in \Lambda_{\text{OPT}}$ are obtained by maximizing the loglikelihood [\(Hunter,](#page-9-11) [2004\)](#page-9-11)

$$
\sum_{i=1}^{|\Lambda_{\text{OPT}}|} \sum_{j=1}^{|\Lambda_{\text{OPT}}|} \left(w_{ij} \ln \left(\frac{s(\lambda_i)}{s(\lambda_i) + s(\lambda_j)} \right) \right), \quad (12)
$$

with $w_{ii} = 0$ for all $1 \le i \le |\Lambda_{\text{OPT}}|$. With this design, in the absence of prior information ($n_p = 0$), the BT model reduces to assigning scores directly proportional to the pvalues $p_{\lambda}(\mathcal{Z}_{\text{OPT}})$, as is done in PT [\(Laufer-Goldshtein et al.,](#page-9-0) [2023\)](#page-9-0). Therefore, the proposed approach ensures a seamless integration of prior information into the score assignment, while maintaining consistency with PT when prior information is unavailable.

After obtaining the scores $s(\lambda_i)$ for all $1 \leq i \leq |\Lambda_{\text{OPT}}|$, depth assignment is done via clustering, producing disjoint subsets $\Lambda_1, \ldots, \Lambda_D$. The cluster $\Lambda_1 \subseteq \Lambda_{\text{OPT}}$ contains the hyperparameters with the highest expected reliability, and the remaining clusters $\Lambda_2, \ldots, \Lambda_D$ are sorted in descending order of expected reliability. All hyperparameters in cluster Λ_d are assigned depth level d.

Clustering can be implemented by using methods such as K means or hierarchical clustering. We recommend to use agglomerative hierarchical clustering, which begins with each hyperparameter in its own cluster and iteratively merges clusters [\(Jain & Dubes,](#page-9-16) [1988\)](#page-9-16).

4.2.2. LEARNING THE DIRECTED EDGES

Having obtained the clusters $\Lambda_1, \ldots, \Lambda_D$, the RG is constructed by: (*i*) including one node for each hyperparameter $\lambda \in \Lambda_{\text{OPT}}$; and *(ii)* selecting for each hyperparameter $\lambda \in \Lambda_d$ at depth level d a subset of hyperparameters in cluster Λ_{d-1} to serve as parents of λ for all depth levels $2 \leq d \leq K$. The resulting directed edges are intended to represent inferred reliability dependencies.

To this end, we implement feature selection via the *nonnegative Lasso* [\(Tibshirani,](#page-10-5) [1996\)](#page-10-5). Specifically, given hyperparameter $\lambda \in \Lambda_d$, we consider the problem of predicting the risks $\{r_l(Z,\lambda)\}_{l=1}^L$ from the risks $\{r_l(Z,\lambda')\}_{l=1}^L$ attained by the hyperparameters $\lambda \in \Lambda_{d-1}$ at the previous depth level. The use of non-negative Lasso regression ensures that only positive correlations are represented in the DAG, preserving hierarchical reliability relationships between parent and child nodes.

Formally, using the data set \mathcal{Z}_{OPT} , for each hyperparameter $\lambda \in \Lambda_d$ we address the problem

$$
\min_{\beta \geq 0} \sum_{Z \in \mathcal{Z}_{\text{OPT}}} ||r(Z, \lambda) - \sum_{\lambda' \in \Lambda_{d-1}} \beta_{\lambda'} r(Z, \lambda')||_2^2
$$

+ $\tau \sum_{\lambda' \in \Lambda_{d-1}} \beta_{\lambda'},$ (13)

where $\beta = {\beta_{\lambda'}}_{\lambda' \in \Lambda_{d-1}}$ is the vector of non-negative regression coefficients corresponding to each potential parent node $\lambda' \in \Lambda_{d-1}$; $r(Z, \lambda)$ is the vector containing the values $\{r_l(Z,\lambda)\}_{l=1}^{L_c};$ $\|\cdot\|_2$ represents the ℓ_2 norm; and $\tau > 0$ is a regularization parameter that controls the degree of sparsity in the solution. As for the variables $(n_p, \{\eta_{ij}\})$ in the BT likelihood [\(12\)](#page-5-1), the choice of the parameter τ does not affect the validity properties of RG-PT. After solving the convex problem [\(13\)](#page-5-2), only the hyperparameters $\lambda' \in \Lambda_{j-1}$ for which the corresponding coefficient $\beta_{\lambda'}$ are positive are selected as parent nodes of hyperparameter λ .

4.3. FDR-Controlling Multiple Hypothesis Testing

Given the obtained RG, RG-PT performs MHT via DAG-GER [\(Ramdas et al.,](#page-9-6) [2019\)](#page-9-6), an FDR-controlling algorithm that operates on DAGs. Next, we first outline the reasons behind using FDR, and then explain the testing procedure.

The requirement [\(6\)](#page-3-1) guaranteed by FWER-controlling algorithms often comes at the cost of limiting the number of hyperparameters retained in the subset $\Lambda_{\mathcal{Z}}$. This, in turn, constrains the quality of the solutions to problem [\(7\)](#page-3-3). Instead of constraining the probability of having *any* unreliable hyperparameter in set Λ _{\mathcal{Z}}, one can control the *proportion* of unreliable hyperparameters in set $\Lambda_{\mathcal{Z}}$.

Accordingly, the FDR is defined as the expected proportion of unreliable hyperparameters in set $\Lambda_{\mathcal{Z}}$. Controlling the FDR amounts to finding a subset $\Lambda_{\mathcal{Z}} \subseteq \Lambda$ that satisfies the inequality

$$
\mathbb{E}_Z\left[\frac{\sum_{\lambda \in \hat{\Lambda}_Z} \mathbf{1}\{R_l(\lambda) > \alpha_l \text{ for any } l = 1, \dots, L_c\}}{\max(|\hat{\Lambda}_Z|, 1)}\right] \le \delta,
$$
\n(14)

where $1\{\cdot\}$ is the indicator function, and the expectation is taken over the unknown data distribution P_Z . The FDR constraint [\(14\)](#page-5-3) contrasts with the FWER requirement [\(6\)](#page-3-1), which aims to limit the probability of any unreliable hyperparameter in the selected set $\Lambda_{\mathcal{Z}}$.

DAGGER is an FDR-controlling procedure that operates on a DAG. DAGGER begins testing at the root nodes of the RG, i.e., at the hyperparameters in cluster Λ_1 , and proceeds with the clusters $\Lambda_2, \Lambda_3, \ldots, \Lambda_D$, guided by the outcomes of prior tests. If a hyperparameter is deemed unreliable, none of its descendants are tested.

Using the data set \mathcal{Z}_{MHT} , the p-values used for MHT are given by $p_{\lambda}(\mathcal{Z}_{\text{MHT}})$ in [\(9\)](#page-3-4) for each hyperparameter $\lambda \in \Lambda_{\text{OPT}}$. The testing level δ_i for each hyperparameter λ_i , detecting λ_i as reliable if $p_{\lambda_i} \leq \delta_i$, is determined based on several factors. These include the overall target FDR level δ in constraint [\(14\)](#page-5-3), the number of reliable hyperparameters identified among those tested prior to λ_i , and the structure of the graph rooted at λ_i . We refer the reader to Appendix [B](#page-11-1) and to [\(Ramdas et al.,](#page-9-6) [2019\)](#page-9-6) for details.

5. Experiments

In this section, we evaluate the proposed RG-PT hyperparameter selection strategy on two problems: a sequence-tosequence translation problem [\(Peters & Martins,](#page-9-12) [2021\)](#page-9-12), and an object detection task [\(Angelopoulos et al.,](#page-8-8) [2021\)](#page-8-8). Two additional experiments addressing a classical small-scale machine learning benchmark [\(Franceschi et al.,](#page-8-12) [2024\)](#page-8-12) and an engineering application in the domain of telecommunica-tions [\(Valcarce,](#page-10-4) [2020\)](#page-10-4) can be found in Appendix C^1 C^1 C^1 .

Throughout, we adopt as benchmarks LTT [\(Angelopou](#page-8-8)[los et al.,](#page-8-8) [2021\)](#page-8-8) and PT [\(Laufer-Goldshtein et al.,](#page-9-0) [2023\)](#page-9-0). LTT is implemented by applying Benjamini-Hochberg (BH) [\(Benjamini & Hochberg,](#page-8-16) [1995\)](#page-8-16) as the FDR-controlling algorithm, while PT follows Sec. [3](#page-2-1) with the caveat that FDRcontrolling FST [\(Lynch et al.,](#page-9-17) [2017\)](#page-9-17) is used in lieu of an FWER-controlling scheme. LTT uses the entire calibration data set $\mathcal Z$ to evaluate the p-values used in BH, while PT and RG-PT partition \mathcal{Z} into data sets \mathcal{Z}_{OPT} and \mathcal{Z}_{MHT} . To the best of our knowledge, LTT and PT are the only existing hyperparameter selection methods that guarantee statistical validity in the sense of the FWER requirement [\(6\)](#page-3-1) or the FDR constraint [\(14\)](#page-5-3).

5.1. Sequence-to-Sequence Language Translation

We consider a sequence-to-sequence language translation task on the WMT16 Romanian-English dataset [\(Bojar et al.,](#page-8-17) [2016\)](#page-8-17), using BLEU [\(Papineni et al.,](#page-9-18) [2002\)](#page-9-18) and ROUGE-L [\(Lin,](#page-9-19) [2004\)](#page-9-19) as the objectives. Following [\(Peters & Mar](#page-9-12)[tins,](#page-9-12) [2021\)](#page-9-12), the dataset is preprocessed with SentencePiece

tokenization [\(Kudo,](#page-9-20) [2018\)](#page-9-20), and an LSTM-based encoderdecoder is trained. Two key hyperparameters are considered:

1. The hyperparameter ρ controls the sparsity of the output distribution using Entmax [\(Peters et al.,](#page-9-21) [2019\)](#page-9-21), transitioning between a dense output with softmax ($\rho = 1$) and sparsemax $(\rho = 2)$ [\(Martins & Astudillo,](#page-9-22) [2016\)](#page-9-22).

2. The *Fenchel-Young label smoothing strength* ϵ is a training regularization hyperparameter that determines the extent to which one-hot targets are mixed with uniform noise based on Fenchel-Young losses [\(Peters & Martins,](#page-9-12) [2021\)](#page-9-12). Accordingly, the original one-hot targets are assigned weight $1 - \epsilon$, while the uniform distribution over all possible classes is assigned the weight ϵ .

To create the initial candidate set Λ , we selected hyperparameters over a grid of 32 combinations, using 8 logarithmically spaced values in the interval [1, 2] for ρ , and values in the set $\{0.0, 0.01, 0.05, 0.1\}$ for ϵ . This selection is in line with [\(Peters & Martins,](#page-9-12) [2021\)](#page-9-12).

To set up RG-PT, we leveraged the prior knowledge that less sparse settings may be more reliable than their sparser counterparts. Specifically, for any two hyperparameters $\lambda_i = (\rho_i, \epsilon_i)$ and $\lambda_j = (\rho_j, \epsilon_j)$ where $\rho_i < \rho_j$, we assigned a prior probability $\eta_{ij} = 1$, reflecting this prior reliability assumption. Furthermore, the pseudocount parameter n_p , which determines the weight of prior information, was set to be equal to $|\mathcal{Z}_{\text{OPT}}|$.

Denote as $R_{\text{BLEU}}(\lambda)$ and $R_{\text{ROUGE}}(\lambda)$ the average BLEU and ROUGE-L scores, respectively, obtained for a given hyperparameter configuration $\lambda = (\rho, \epsilon)$. The goal is to guarantee the BLEU score to be above a threshold α , while maximizing the ROUGE-L score. This amounts to an instance of problem [\(3\)](#page-2-2), with $L = 2$, $L_c = 1$, $R_1(\lambda) = -R_{BLEU}(\lambda)$, $R_2(\lambda) = -R_{\text{ROUGE}}(\lambda)$, and $\delta = 0.1$. After MHT, all the schemes choose the hyperparameter $\lambda \in \hat{\Lambda}_{\mathcal{Z}}$ with the maximum estimated value $R_{\text{ROUGE}}(\lambda)$, i.e., minimum $\hat{R}_2(\lambda | \mathcal{Z})$ for LTT, and minimum $\hat{R}_2(\lambda | \mathcal{Z}_{\text{OPT}})$ for PT and RG-PT. The data set sizes are $|\mathcal{Z}| = 400$, $|\mathcal{Z}_{\text{OPT}}| = 200$, and $|\mathcal{Z}_{\text{MHT}}| = 200.$

Fig. [5](#page-7-2) illustrates the ROUGE-L score achieved on the test data by each calibration method, plotted against the target value for the BLEU score. The results demonstrate that RG-PT consistently maintains higher ROUGE-L scores, even under stricter requirements for the BLEU score. This highlights RG-PT's advantage in effectively exploring the hyperparameter space, enabling a more efficient testing procedure and identifying superior hyperparameter configurations that still statistically satisfy the desired conditions on the risk functions.

The codes for the experiments can be found at $https://$ github.com/kclip/RG-PT.

Figure 5. Test ROUGE-L scores achieved by LTT, PT, and RG-PT methods as a function of the target reliability value for the BLEU score.

5.2. Image Segmentation for Object Detection

We now evaluate the proposed RG-PT framework on a multi-objective image segmentation task for object detection, leveraging the MS-COCO dataset [\(Lin et al.,](#page-9-23) [2014\)](#page-9-23) and a pretrained detector from Detectron2 [\(Wu et al.,](#page-10-6) [2019\)](#page-10-6) as done in [\(Angelopoulos et al.,](#page-8-8) [2021\)](#page-8-8). The task involves three distinct objectives: (*i*) detecting objects within an image (object detection); (*ii*) delineating object boundaries (image segmentation); and (*iii*) assigning correct labels to detected objects (object classification). These tasks are measured using recall, intersection-over-union (IoU), and classification accuracy, respectively. The goal is to control classification errors while optimizing recall and segmentation quality, addressing the trade-offs among these objectives.

The performance of the detection is determined by three hyperparameters:

1. The *object recall threshold* (λ_1) controls the threshold for selecting objects based on confidence scores. Reducing the value of λ_1 lowers the confidence threshold, which allows more objects to be selected at the cost of, potentially, increasing false positives.

2. The *mask size threshold* (λ_2) tunes the size of the bounding masks used to segment objects, impacting the IoU score.

3. The *classification certainty level* (λ_3) controls the certainty level required for object classification, adjusting the tolerance for inclusion in the set of labels assigned to each detected object.

Denote as $R_1(\lambda)$, $R_2(\lambda)$, and $R_3(\lambda)$ the risks associated with recall, IOU, and coverage, respectively, for hyperparameter $\lambda = (\lambda_1, \lambda_2, \lambda_3)$. Controlling these risks in the context of problem [\(3\)](#page-2-2) is equivalent to having $L = 3$ and $L_c = 3$. Additionally, as in [\(Angelopoulos et al.,](#page-8-8) [2021\)](#page-8-8), we set the targets as $\alpha_1 = 0.5$, $\alpha_2 = 0.5$, and $\alpha_3 = 0.75$ with $\delta = 0.1$. Within the set $\Lambda_{\mathcal{Z}}$ of reliable hyperparameters returned by the algorithm of choice, we choose the hyperparameter in subset $\hat{\Lambda}_z$ with the lowest value of λ_1 in order to increase the number of detected objects as much as possible.

and RG-PT methods. The box plots show the range (denoted by Figure 6. Example of of hyperparameter distributions for LTT, PT, the horizontal black whiskers), median (represented by the thick black vertical lines), and interquartile range (depicted by the boxes) of the object recall threshold hyperparameter λ_1 .

No prior knowledge was leveraged in creating the RG in this experiment by setting $n_p = 0$.

We compare the distribution of the hyperparameters returned by LTT, PT, and RG-PT. The distribution is obtained by running 200 trials for each algorithm over different splits of calibration data \mathcal{Z} into subsets \mathcal{Z}_{OPT} and \mathcal{Z}_{MHT} with $|\mathcal{Z}_{\text{OPT}}| = 1500$ and $|\mathcal{Z}_{\text{MHT}}| = 1500$. As shown in Fig. [6,](#page-7-3) the results demonstrate that RG-PT tends to return lower values for λ_1 than both LTT and PT. In particular, both the mean and dispersion for RG-PT are lower than those for LTT and PT. A lower threshold λ_1 allows the detector to select more objects, which directly enhances object recall, while still maintaining controlled levels of segmentation and classification accuracy (see also Fig. [2\)](#page-1-0).

6. Conclusion

In this paper, we have introduced RG-PT, a novel framework for multi-objective hyperparameter selection that integrates MHT with the concept of RGs to capture interdependencies among candidate hyperparameters. By leveraging a DAG structure informed by prior knowledge and data, RG-PT enables a more powerful parallel testing of hyperparameters compared to the state-of-the-art methods LTT and PT. RG-PT provides statistical guarantees through FDR control, while expanding the space of reliable hyperparameter configurations, leading to a superior optimization of auxiliary objectives.

Future work may investigate the use of synthetic data for the derivation of an RG, as well as the integration with sequential testing methods based on e-processes [\(Zecchin &](#page-10-3) [Simeone,](#page-10-3) [2024\)](#page-10-3).

Acknowledgements

This work was supported by the European Union's Horizon Europe project CENTRIC (101096379), by the Open Fellowships of the EPSRC (EP/W024101/1), and by the EPSRC project (EP/X011852/1).

References

- Angelopoulos, A. N., Bates, S., Candes, E. J., Jordan, ` M. I., and Lei, L. Learn then test: Calibrating predictive algorithms to achieve risk control. *arXiv preprint arXiv:2110.01052*, 2021.
- Benjamini, Y. and Hochberg, Y. Controlling the false discovery rate: a practical and powerful approach to multiple testing. *Journal of the Royal statistical society: series B (Methodological)*, 57(1):289–300, 1995.
- Benjamini, Y. and Yekutieli, D. The control of the false discovery rate in multiple testing under dependency. *Annals of statistics*, pp. 1165–1188, 2001.
- Bergstra, J. and Bengio, Y. Random search for hyperparameter optimization. *Journal of machine learning research*, 13(2), 2012.
- Bischl, B., Binder, M., Lang, M., Pielok, T., Richter, J., Coors, S., Thomas, J., Ullmann, T., Becker, M., Boulesteix, A.-L., et al. Hyperparameter optimization: Foundations, algorithms, best practices, and open challenges. *Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery*, 13(2):e1484, 2023.
- Bishop, C. M. and Nasrabadi, N. M. *Pattern recognition and machine learning*, volume 4. Springer, 2006.
- Bojar, O., Chatterjee, R., Federmann, C., Graham, Y., Haddow, B., Huck, M., Jimeno Yepes, A., Koehn, P., Logacheva, V., Monz, C., Negri, M., Névéol, A., Neves, M., Popel, M., Post, M., Rubino, R., Scarton, C., Specia, L., Turchi, M., Verspoor, K., and Zampieri, M. Findings of the 2016 conference on machine translation. In Bojar, O., Buck, C., Chatterjee, R., Federmann, C., Guillou, L., Haddow, B., Huck, M., Yepes, A. J., Névéol, A., Neves, M., Pecina, P., Popel, M., Koehn, P., Monz, C., Negri, M., Post, M., Specia, L., Verspoor, K., Tiedemann, J., and Turchi, M. (eds.), *Proceedings of the First Conference on Machine Translation: Volume 2, Shared Task Papers*, pp. 131–198, Berlin, Germany, August 2016. Association for Computational Linguistics. doi: 10.18653/v1/W16-2301. URL <https://aclanthology.org/W16-2301/>.
- Casella, G. and Berger, R. *Statistical inference*. CRC press, 2024.
- Chen, X., Cheng, J., Zhang, Z., Wu, L., Dang, J., and Wang, J. Data-rate driven transmission strategies for deep

learning-based communication systems. *IEEE Transactions on Communications*, 68(4):2129–2142, 2020.

- Chen, X., Liu, Z., Tang, H., Yi, L., Zhao, H., and Han, S. Sparsevit: Revisiting activation sparsity for efficient high-resolution vision transformer. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 2061–2070, 2023.
- de Sant Ana, P. M. and Marchenko, N. Radio Access Scheduling using CMA-ES for optimized QoS in wireless networks. In *2020 IEEE Globecom Workshops (GC Wkshps)*, pp. 1–6. IEEE, 2020.
- Deb, K., Pratap, A., Agarwal, S., and Meyarivan, T. A fast and elitist multiobjective genetic algorithm: NSGA-II. *IEEE transactions on evolutionary computation*, 6(2): 182–197, 2002.
- Deb, K., Sindhya, K., and Hakanen, J. Multi-objective optimization. In *Decision sciences*, pp. 161–200. CRC Press, 2016.
- Dong, X., Shen, J., Wang, W., Liu, Y., Shao, L., and Porikli, F. Hyperparameter optimization for tracking with continuous deep Q-learning. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 518–527, 2018.
- Eimer, T., Lindauer, M., and Raileanu, R. Hyperparameters in reinforcement learning and how to tune them. In *International Conference on Machine Learning*, pp. 9104–9149. PMLR, 2023.
- Farzaneh, A. and Simeone, O. Statistically valid information bottleneck via multiple hypothesis testing. *arXiv preprint arXiv:2409.07325*, 2024.
- Farzaneh, A., Park, S., and Simeone, O. Quantile learnthen-test: Quantile-based risk control for hyperparameter optimization. *IEEE Signal Processing Letters*, 2024.
- Franceschi, L., Donini, M., Perrone, V., Klein, A., Archambeau, C., Seeger, M., Pontil, M., and Frasconi, P. Hyperparameter optimization in machine learning. *arXiv preprint arXiv:2410.22854*, 2024.
- Hancock, J., Johnson, J. M., and Khoshgoftaar, T. M. A comparative approach to threshold optimization for classifying imbalanced data. In *2022 IEEE 8th International Conference on Collaboration and Internet Computing (CIC)*, pp. 135–142. IEEE, 2022.
- Hernández-Lobato, D., Hernandez-Lobato, J., Shah, A., and Adams, R. Predictive entropy search for multi-objective bayesian optimization. In *International conference on machine learning*, pp. 1492–1501. PMLR, 2016.
- Hu, X., Chu, L., Pei, J., Liu, W., and Bian, J. Model complexity of deep learning: A survey. *Knowledge and Information Systems*, 63:2585–2619, 2021.
- Hunter, D. R. Mm algorithms for generalized bradley-terry models. *The annals of statistics*, 32(1):384–406, 2004.
- Jain, A. K. and Dubes, R. C. *Algorithms for clustering data*. Prentice-Hall, Inc., 1988.
- Jamieson, K. and Talwalkar, A. Non-stochastic best arm identification and hyperparameter optimization. In *Artificial intelligence and statistics*, pp. 240–248. PMLR, 2016.
- Kudo, T. Subword regularization: Improving neural network translation models with multiple subword candidates. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 66–75, 2018.
- Laufer-Goldshtein, B., Fisch, A., Barzilay, R., and Jaakkola, T. S. Efficiently controlling multiple risks with Pareto testing. In *Proc. International Conference on Learning Representations*, 2023.
- Li, L., Jamieson, K., DeSalvo, G., Rostamizadeh, A., and Talwalkar, A. Hyperband: A novel bandit-based approach to hyperparameter optimization. *Journal of Machine Learning Research*, 18(185):1–52, 2018.
- Li, T., Sanjabi, M., Beirami, A., and Smith, V. Fair resource allocation in federated learning. In *International Conference on Learning Representations*, 2020.
- Lin, C.-Y. Rouge: A package for automatic evaluation of summaries. In *Text summarization branches out*, pp. 74–81, 2004.
- Lin, T.-Y., Maire, M., Belongie, S., Hays, J., Perona, P., Ramanan, D., Dollár, P., and Zitnick, C. L. Microsoft COCO: Common objects in context. In *Computer Vision– ECCV 2014: 13th European Conference, Zurich, Switzerland, September 6-12, 2014, Proceedings, Part V 13*, pp. 740–755. Springer, 2014.
- Lynch, G., Guo, W., Sarkar, S. K., and Finner, H. The control of the false discovery rate in fixed sequence multiple testing. *Electronic Journal of Statistics*, 11(2):4649 – 4673, 2017. doi: 10.1214/17-EJS1359.
- Maclaurin, D., Duvenaud, D., and Adams, R. Gradientbased hyperparameter optimization through reversible learning. In *International conference on machine learning*, pp. 2113–2122. PMLR, 2015.
- Martins, A. and Astudillo, R. From softmax to sparsemax: A sparse model of attention and multi-label classification. In *International conference on machine learning*, pp. 1614– 1623. PMLR, 2016.
- Maurer, W. Multiple comparisons in drug clinical trials and preclinical assays: a-priori ordered hypothesis. *Biomed. Chem.-Pharm. Ind.*, 6:3–18, 1995.
- Papineni, K., Roukos, S., Ward, T., and Zhu, W.-J. BLEU: a method for automatic evaluation of machine translation. In *Proceedings of the 40th annual meeting of the Association for Computational Linguistics*, pp. 311–318, 2002.
- Paria, B., Kandasamy, K., and Póczos, B. A flexible framework for multi-objective bayesian optimization using random scalarizations. In *Uncertainty in Artificial Intelligence*, pp. 766–776. PMLR, 2020.
- Peters, B. and Martins, A. F. Smoothing and shrinking the sparse seq2seq search space. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 2642–2654, 2021.
- Peters, B., Niculae, V., and Martins, A. F. Sparse sequenceto-sequence models. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 1504–1519, 2019.
- Polese, M., Bonati, L., D'oro, S., Basagni, S., and Melodia, T. Understanding o-ran: Architecture, interfaces, algorithms, security, and research challenges. *IEEE Communications Surveys & Tutorials*, 25(2):1376–1411, 2023.
- Powers, D. Evaluation: from precision, recall and f-measure to roc, informedness, markedness & correlation. *Journal of Machine Learning Technologies*, 2:37, 2011.
- Rahnama, A. H. A., Toloo, M., and Zaidenberg, N. J. An lpbased hyperparameter optimization model for language modeling. *The Journal of Supercomputing*, 74:2151– 2160, 2018.
- Ramdas, A., Chen, J., Wainwright, M. J., and Jordan, M. I. A sequential algorithm for false discovery rate control on directed acyclic graphs. *Biometrika*, 106(1):69–86, 2019.
- Rice, J. A. *Mathematical Statistics and Data Analysis.* Belmont, CA: Duxbury Press., third edition, 2006.
- Romano, Y., Patterson, E., and Candes, E. Conformalized quantile regression. *Advances in neural information processing systems*, 32, 2019.
- Shafer, G. and Vovk, V. A tutorial on conformal prediction. *Journal of Machine Learning Research*, 9(3), 2008.
- Snoek, J., Larochelle, H., and Adams, R. P. Practical bayesian optimization of machine learning algorithms. *Advances in neural information processing systems*, 25, 2012.
- Tibshirani, R. Regression shrinkage and selection via the lasso. *Journal of the Royal Statistical Society Series B: Statistical Methodology*, 58(1):267–288, 1996.
- Valcarce, A. Wireless Suite: A collection of problems in wireless telecommunications. *https://github.com/nokia/wireless-suite*, 2020.
- Wu, Y., Kirillov, A., Massa, F., Lo, W.-Y., and Girshick, R. Detectron2. [https://github.com/](https://github.com/facebookresearch/detectron2) [facebookresearch/detectron2](https://github.com/facebookresearch/detectron2), 2019. Accessed: 2024-11-19.
- Yang, L. and Shami, A. On hyperparameter optimization of machine learning algorithms: Theory and practice. *Neurocomputing*, 415:295–316, 2020.
- Yogatama, D., Kong, L., and Smith, N. A. Bayesian optimization of text representations. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, 2015.
- Zecchin, M. and Simeone, O. Adaptive learn-then-test: Statistically valid and efficient hyperparameter selection. *arXiv preprint arXiv:2409.15844*, 2024.
- Zhou, X., Zhang, W., Xu, H., and Zhang, T. Effective sparsification of neural networks with global sparsity constraint. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3599–3608, 2021.

A. Fixed Sequence Testing

In this section, we provide a brief overview of FST for controlling the FDR, which we used in our simulations for PT. While PT, as outlined in [\(Laufer-Goldshtein et al.,](#page-9-0) [2023\)](#page-9-0), is designed to support control of the FWER, our focus in this paper is on FDR control.

MHT methods such as the Bonferroni correction for FWER control [\(Rice,](#page-9-15) [2006\)](#page-9-15) and the Benjamini-Yekutieli (BY) procedure for FDR control [\(Benjamini & Yekutieli,](#page-8-18) [2001\)](#page-8-18) do not leverage any side information about the relative reliability of the hyperparameters. When such information is available during calibration, FST can be used to test hyperparameters in order of expected reliability. When the ordering information is accurate, FST can be beneficial to reduce the FDR [\(Lynch et al.,](#page-9-17) [2017\)](#page-9-17). In this section, we briefly describe the FST procedure for FDR control.

With FST, the candidate hyperparameters are ordered as $\lambda_{(1)}, \ldots, \lambda_{(|\Lambda|)}$ using side information. The ordering ideally lists the hyperparameters from the most to the least likely to meet the reliability criterion [\(2\)](#page-2-3).

Starting with $i = 1$, each hyperparameter $\lambda_{(i)}$ is tested sequentially based on its p-value $p_{\lambda_{(i)}}$ against an adjusted critical value δ_i that decreases with the index $i = 1, 2, ..., |\Lambda|$. At each step i, the hyperparameter $\lambda_{(i)}$ is deemed to be reliable if $p_{\lambda(i)} \leq \delta_i$. Testing continues until k hyperparameters are deemed to be unreliable, at which point testing stops. The choice of the integer k is typically set as a small proportion, often around 5-10%, of the total number of hypotheses, $|\Lambda|$.

The critical values δ_i are adapted to account for the position of each hypothesis in the testing sequence. These values are specifically designed to control the FDR under various dependency structures among the p -values. For the case of interest here, which is arbitrary dependence of the *p*-values, the critical levels can be set as [\(Lynch et al.,](#page-9-17) [2017\)](#page-9-17)

$$
\delta_i = \begin{cases} \frac{\delta}{k} & \text{if } i \le k \\ \frac{(\vert \Lambda \vert - k + 1)\delta}{(\vert \Lambda \vert - i + 1)k} & \text{if } i > k, \end{cases} \tag{15}
$$

where δ is the target FDR level and k is the number of unreliable hyperparameters allowed before testing stops.

The final set of reliable hyperparameters is $\hat{\Lambda}_{z} = {\lambda_{(1)}, \ldots, \lambda_{(j)}}$, where j corresponds to the index of the last hyperparameter tested before stopping. This ensures that the FDR is rigorously maintained below level δ .

B. Summary of DAGGER

This section outlines the step-up procedure used in DAGGER [\(Ramdas et al.,](#page-9-6) [2019\)](#page-9-6) to dynamically adjust the testing thresholds. DAGGER determines the testing thresholds adaptively based on the structure of the DAG and on the outcomes of previously tested hypotheses. At each depth level of the DAG, thresholds are updated dynamically to control the FDR, while respecting the hierarchical dependencies encoded by the DAG.

At each depth d, only the hyperparameters with no unreliable parents are considered for testing. If any parent of a hyperparameter λ is deemed unreliable by DAGGER, all of its descendants are also automatically deemed unreliable. The threshold for testing the i -th hypothesis at depth d is given by

$$
\delta_i(r) = \frac{v_i}{V} \cdot \frac{\delta}{\beta(m_i + r + R_{1:d-1} - 1)},\tag{16}
$$

where $r \in [1, |\Lambda_d|]$ is a parameter set as detailed below; v_i is the effective number of leaves in the subgraph rooted at the current node; V is the total number of leaves in the DAG; m_i is the effective number of nodes in the subgraph rooted at the current node; $R_{1:d-1}$ is the total number of rejections at depths 1 through $d-1$; and $\beta(\cdot)$ is a reshaping function, such as the Benjamini-Yekutieli [\(Benjamini & Yekutieli,](#page-8-18) [2001\)](#page-8-18) function $\beta_{BY}(x) = x \sum_{k=1}^{V} 1/k$, which is designed to ensure FDR control under arbitrary dependence.

The effective number of leaves v_i and the effective number of nodes m_i for node i are calculated as follows. If i is a leaf, then we have $v_i = m_i = 1$. Otherwise, the values v_i and m_i are calculated recursively from leaves to roots as

$$
v_i = \sum_{j \in \text{children}(i)} \frac{v_j}{|\text{parents}(j)|},\tag{17}
$$

and

$$
m_i = 1 + \sum_{j \in \text{children}(i)} \frac{m_j}{|\text{parents}(j)|},\tag{18}
$$

Figure 7. Inustration of the DAGGER algorithm s operation to control the FDR at $\delta = 0.1$. At each step, a hyperparameter is tested, starting
from the root nodes and progressing level by level through the DAG. The testi DMHT using the step-up procedure in [\(16\)](#page-11-2) and [\(19\)](#page-12-1), using the identity function as $\beta(\cdot)$. The p-value of each hyperparameter is compared against its respective threshold δ_i to assess the reliability of λ_i .

where children(i) and parents(i) denote the sets of the children and the parents of node i, respectively.

needs to be determined before testing can begin. To The parameter r at depth d needs to be determined before testing can begin. To maximize the number of rejections while ensuring FDR control, DAGGER calculates the value

$$
R = \arg\max_{r=1,\dots,|\Lambda_d|} \left[\sum_{\lambda_i \in \Lambda_d} \mathbf{1}\{p_{\lambda_i}(\mathcal{Z}_{\text{MHT}}) \le \delta_i(r)\} \ge r \right]. \tag{19}
$$

The threshold $\delta_i(R)$ is then used to perform the testing for hyperparameter λ_i .

The step-up procedure [\(16\)](#page-11-2) ensures that thresholds are increasingly relaxed, i.e., increased, as we move further down the DAG. The overall algorithm is described in Algorithm [1,](#page-13-0) and an example illustrating DAGGER's operation is shown in Fig. [7.](#page-12-2) The figure highlights how thresholds are updated and decisions propagated through the DAG. For simplicity, the figure assumes the reshaping function $\beta(\cdot)$ to be the identity function $\beta(x) = x$. First, the values for the effective number of leaves v_i and the effective number of nodes m_i are calculated for each hyperparameter λ_i . Next, going level by level, the thresholds $\delta_i(R)$ are calculated using [\(16\)](#page-11-2) and [\(19\)](#page-12-1), and each hyperparameter λ_i is tested by comparing $p_{\lambda_i}(\mathcal{Z}_{\text{MHT}})$ with $\delta_i(R)$.

C. Additional Experiments

C.1. Image Classification

In this experiment, following [\(Franceschi et al.,](#page-8-12) [2024\)](#page-8-12), we consider the problem of hyperparameter selection for a support vector machine (SVM) model used to classify images from the Fashion MNIST dataset. The Fashion MNIST is a widely used benchmark for image classification, consisting of 70,000 grayscale images of 10 different clothing categories.

classification error $R_{\text{err}}(\lambda)$ measures the proportion of incorrectly classified images out of the total number of samples. The We consider two risk functions ($L = 2$) in problem [\(3\)](#page-2-2), namely the classification error $R_{\text{err}}(\lambda)$ and the recall, $R_{\text{rec}}(\lambda)$. The

Input: DAG structure, *p*-values $\{p_{\lambda}(\mathcal{Z}_{\text{MHT}})\}\$, target FDR level δ **Output:** Set of reliable hyperparameters $\hat{\Lambda}_z$ for depth $d = 1, \ldots, D$ do for each hyperparameter λ_i in cluster Λ_d do if all parent hyperparameters of λ_i are deemed as reliable then Evaluate threshold $\delta_i(R)$ using [\(16\)](#page-11-2) and [\(19\)](#page-12-1) if $p_{\lambda_i}(\mathcal{Z}_{\text{MHT}}) \leq \delta_i(R)$ then Detect λ_i as reliable else Detect λ_i as unreliable end if end if end for Update Λ _z with all the hyperparameters detected as reliable at depth d end for return $\Lambda_{\mathcal{Z}}$

recall measures the ability of a model to correctly identify all the relevant instances of each class. Accordingly, for each class, the recall is computed as the ratio of correctly identified instances of that class to the total number of actual instances of the same class in the dataset. The recall $R_{\text{rec}}(\lambda)$ represents the average of the recall values across all classes.

With reference to problem [\(3\)](#page-2-2), we aim at minimizing recall, i.e. $R_2(\lambda) = R_{\text{rec}}(\lambda)$, while keeping the classification error rate below 0.3, i.e. $R_1(\lambda) = R_{\text{acc}}(\lambda)$, $L_c = 1$, and $\alpha_1 = 0.3$. The goal is therefore defined as

$$
\min_{\lambda \in \Lambda} R_{\text{rec}}(\lambda) \quad \text{subject to} \quad R_{\text{acc}}(\lambda) < 0.3. \tag{20}
$$

This is a non-trivial problem since the accuracy maximizing model may not also optimize the recall [\(Powers,](#page-9-24) [2011\)](#page-9-24).

The SVM model requires the selection of two hyperparameters [\(Franceschi et al.,](#page-8-12) [2024\)](#page-8-12). The regularization parameter, C , controls the desired trade-off between maximizing the margin and minimizing the classification error. Lower values of C allow for a softer margin that can overlook some misclassification errors, while higher values enforce stricter classification error requirements. The kernel coefficient, γ , determines the impact of a single training example on the decision boundary, with higher values capturing finer details in the data set but risking overfitting. To create the initial candidate set Λ , we selected hyperparameters over a grid of 25 combinations, using five logarithmically spaced values in the intervals [−3, 3] and $[-4, 1]$ for C and γ , respectively. This selection is in line with approaches such as [\(Yogatama et al.,](#page-10-7) [2015\)](#page-10-7) for SVM hyperparameter selection.

We used 5,000 data points for training the SVM, and used an additional 5,000 data points as calibration data Z . The calibration data set Z was in turn divided into two groups of size 2,500, for the data sets Z_{OPT} and Z_{MHT} , respectively.

Fig. [8](#page-14-0) illustrates the testing procedures of LTT [\(Angelopoulos et al.,](#page-8-8) [2021\)](#page-8-8), PT [\(Laufer-Goldshtein et al.,](#page-9-0) [2023\)](#page-9-0), and RG-PT. The x- and y-axes represent the logarithmic scales of the two hyperparameters C and γ , while the contours indicate levels of recall $R_{\text{rec}}(\lambda)$, evaluated on the test data set, as a function of the hyperparameters $\lambda = (c, \gamma)$. The numbers illustrate the testing order for each testing method. Note that than LTT, which uses BY, does not follow any inferred order on the hyperparameters, and thus does not have the order labels in the figures. Furthermore, while LTT and PT test hyperparameters one by one, following a linear trajectory, RG-PT proceeds along a DAG, testing at the same time all hyperparameters at the same depth in the DAG.

LTT and PT are seen to stop at the sixth tested hyperparameter, yielding the set of reliable hyperparameters Λ_z marked as green dots. In contrast, RG-PT returns a much larger set Λ _Z of reliable hyperparameters, also marked as green dots. Choosing within these sets the hyperparameter that minimizes the estimated recall as per problem [\(20\)](#page-13-1) yields the solutions indicated as green stars, corresponding to a test recall of 0.727 for LTT and PT, and 0.332 for RG-PT.

It is important to note that all three methods yield test accuracies below the 0.3 threshold in [\(20\)](#page-13-1). Specifically, the hyperparameters selected by LTT and PT result in a test accuracy error of 0.267, while those chosen by RG-PT achieve a

Figure 8. Illustration of the hyperparameter selection procedure followed by LTT (a), PT (b), and RG-PT (c) for the setting studied in Sec. [C.1.](#page-12-3) Each node represents a hyperparameter $\lambda = (C, \gamma)$, with the numbers representing the testing order. Green nodes show the hyperparameters included in the reliable set Λ_z , and the star node shows the hyperparameter in set Λ_z with the lowest recall rate.

slightly higher accuracy error of 0.286. Although the accuracy of RG-PT is closer to the threshold, it remains consistent with the statistical guarantee outlined in [\(20\)](#page-13-1). In fact, RG-PT achieves a lower recall while maintaining the desired accuracy constraint, whereas LTT and PT follow a more conservative approach, leading to a reliable hyperparameter with higher recall.

C.2. Radio Access Scheduling

In this section, we study a telecommunications engineering problem, namely the optimization of a radio access scheduler [\(Valcarce,](#page-10-4) [2020\)](#page-10-4). In this setup, each user equipment (UE) belongs to one of four quality-of-service (QoS) classes, assigned at random, each with its own delay and bit rate requirements [\(de Sant Ana & Marchenko,](#page-8-19) [2020\)](#page-8-19). The goal is to control the delay of UEs in a given QoS class, while simultaneously minimizing the delays for UEs in the other three QoS classes.

Accordingly, in the context of problem [\(3\)](#page-2-2), we choose $L = 4$ and $L_c = 1$, and we set the risk $R_i(\lambda)$ to be equal to the average delay of QoS class i for $1 \le i \le 4$. We aim to keep $R_2(\lambda)$ below 15 ms, while minimizing $R_1(\lambda)$, $R_3(\lambda)$, and $R_4(\lambda)$. Formally, the problem is stated as

$$
\min_{\lambda \in \Lambda} \{ R_1(\lambda), R_3(\lambda), R_4(\lambda) \} \text{ subject to } R_2(\lambda) < 15 \text{ ms.} \tag{21}
$$

The scheduling algorithm at the base station allocates spectral resources to the UEs. As in [\(Valcarce,](#page-10-4) [2020\)](#page-10-4), the UEs are randomly distributed within a 1 km^2 area containing a centrally located base station. Each UE has an initial buffer of

Figure 9. Distribution of the average delay for the four QoS classes using hyperparameters optimized by PT (left column) and RG-PT (right column). The dashed red line indicates the target threshold for the average delay in QoS class 2.

100 packets, and moves at random speeds and directions. Resource allocation is carried out in intervals of 1 ms, called transmission time intervals (TTIs), over 10,000 TTIs per episode.

The resource allocation algorithm is controlled by a set of hyperparameters $\lambda = (\lambda_1, \lambda_2, \lambda_3, \lambda_4) \in \Lambda$, where each λ_i adjusts a specific criterion in the reward model as detailed in [\(Valcarce,](#page-10-4) [2020\)](#page-10-4). Hyperparameters λ_1 , λ_2 , λ_3 , and λ_4 determine respectively the channel quality for each UE, the total queue sizes at the UEs, the age of the oldest packet in each UE's buffer, and the fairness in resource block allocation among UEs.

Calibration and test data were generated using the Nokia wireless suite [\(Valcarce,](#page-10-4) [2020\)](#page-10-4). For each run, we used 100 episodes for calibration and 100 episodes for testing.

The candidate hyperparameter set Λ was generated by keeping λ_1 and λ_2 at the values λ_1^* and λ_2^* recommended by [\(de Sant Ana & Marchenko,](#page-8-19) [2020\)](#page-8-19), and linearly sweeping hyperparameters λ_3 and λ_4 in [0.02, 0.2] and [-0.1, 0.1], respectively, with 10 steps each, resulting in a total of 100 combinations.

Fig. [9](#page-15-0) presents the results of using PT and RG-PT to optimize the hyperparameter $\lambda = (\lambda_1, \lambda_2, \lambda_3, \lambda_4)$. Both methods successfully meet the statistical guarantee of $R_2(\lambda) < 15$ ms for class 2. However, RG-PT demonstrates a greater ability to explore the hyperparameter space Λ , identifying configurations that more effectively minimize the average delay across the other three classes.