Hybrid Cooperative Co-Evolution Algorithm for Deadlock-prone Distributed Assembly Flowshop Scheduling with Limited buffers Using Petri nets

Siyi Wang, Yanxiang Feng, Xiaoling Li, Guanghui Zhang, Yikang Yang

Abstract—The distributed assembly flowshop scheduling problem (DAFSP) can be applied to immense manufacturing environments. In DAFSP, jobs are first processed in distributed flowshops, and then assembled into final products by an assembly machine, which usually has *limited* buffers in practical application. This limited capacity can lead to deadlocks, halting job completion and blocking the entire manufacturing process. However, existing scheduling methods fail to address these deadlocks in DAFSP effectively. As such, we develop a hybrid cooperative co-evolution (HCCE) algorithm for solving the deadlock-prone DAFSP by minimizing the makespan. For the first time, we use Petri nets to analyze the deadlocks in DAFSP and propose a Petri net-based deadlock amending method (IDAM), which is further integrated into HCCE to ensure the feasibility (i.e., deadlock-freeness) of solutions. Importantly, HCCE contains an elite archive (EAR) and two subpopulations. It uses the problem-specific operators for heuristic initialization and global-search. To enhance the quality and diversity of solutions, an information transfer mechanism (ITM) is developed among subpopulation and EAR, and four local-search operators are performed sequentially on each individual in EAR. Finally, comprehensive experiments demonstrate the effectiveness and superiority of the proposed HCCE algorithm.

Index Terms—Distributed assembly flowshop scheduling; deadlock-free scheduling; Petri nets; cooperative co-evolution

I. INTRODUCTION

During the past decades, the assembly scheduling problem (ASP) has been widely used in practical manufacturing processes such as automobiles [1] and semi-conductor devices [2]. These ASPs usually comprise two stages: *manufacturing* and *assembly*. Jobs are first processed in the manufacturing stage, which could be a flowshop, jobshop, single factory, or multi-factories, etc. Then, in the assembly stage, the finished

jobs will be assembled into products on a single assembly machine or parallel machines.

Due to economic globalization, enterprises have transitioned from traditional centralized production to distributed production [3]. Correspondingly, the research on the distributed ASP (DASP) attracts the attentions of many researchers worldwide. It is usually assumed that the manufacturing stage of DASP consists of distributed multi-factories and the assembly stage is a single machine. To date, many algorithms have been proposed to solve DASPs, including Genetic algorithm (GA) [4], Estimation of Distribution algorithm (EDA) [5], Iterated Greedy algorithm (IGA) [6], Variable Neighborhood Descent algorithm (VNDA) [1], etc. Their objectives are varying, such as minimizing the makespan, total completion time, or maximum lateness (one or multiple of them). Significantly, these existing literature on DASP often assume that the size of assembly buffers in the second stage is infinite [6], [7], [8]. But in real manufacturing environments, such as semiconductor manufacturing and food processing production, the capacity of assembly buffers is either nonexistent or of limited size.

The primary challenge incurred by the limited assembly buffers for DASP is the undesirable deadlock [9]. Precisely, if the limited assembly buffer is full of jobs but none of them can be assembled into a product, then no job can be advanced into the assembly machine and the whole system is blocked. According to [10], the deadlock of DASP is closely related to the order of finished jobs entering into the assembly buffer. To characterize and control deadlock, the whole DASP can be decoupled as two subpopulations: job-scheduling and factory-scheduling. The former determines the jobs' order entering assembly buffer, while the latter assigns each job to a specific factory. Correspondingly, the key for solving deadlock in DASP lies in the first subproblem-find a deadlock-free job order entering assembler buffer. Moreover, Petri net, an effective tool to model discrete event systems, have been widely used to characterize and control deadlocks [11], [12], [13], but do date no one use Petri net to analyze the deadlocks in DASP.

This paper studies a kind of deadlock-prone DASP, namely distributed assembly flowshop scheduling problem (DAFSP), with limited assembly buffers, where the manufacturing stage is a distributed *blocking flowshop* and the assembly stage is a single assembly machine. The objective is to minimize the system makespan. We develop a hybrid cooperative

This work was supported in part by the National Natural Science Foundation of China under Grant 62103062; in part by the Hebei Natural Science Foundation under Grant F2024204007; in part by the State Key Laboratory for Manufacturing Systems Engineering of Xi'an Jiaotong University under Grant sklms 2023002.

Siyi Wang, Yanxiang Feng and Yikang Yang are with the School of Automation Science and Engineering, Xi'an Jiaotong University, Xi'an 710049, China (e-mail: wangsiyi@stu.xjtu.edu.cn; fengyanxiang@xjtu.edu.cn; yangyk74@mail.xjtu.edu.cn).

Xiaoling Li is with the School of Electronics and Control Engineering, Chang'an University, Xi'an 710064, China (e-mail: xiaolingli@chd.edu.cn).

Guanghui Zhang is with the School of Information Science and Technology, Hebei Agricultural University, Baoding 071001, China, (e-mail: ghzhang@hebau.edu.cn).

Symbol	Definition
и	Number of jobs.
f	Number of factories.
т	Number of machines.
l	Number of products.
i	Index for jobs, $i \in \{1, 2,, u\}$.
с	Index for factories, $c \in \{1, 2, \ldots, f\}$.
k	Index for machines, $k \in \{1, 2, \ldots, m\}$.
q	Index for products, $q \in \{1, 2, \ldots, l\}$.
Ψ	The capacity of assembly buffers.
AP	The job-to-product plan.
CM _{max}	The makespan of the manufacturing stage.
CA _{max}	The system makespan.
$S_{i,k}$	The start time of job <i>i</i> on machine <i>k</i> .
$C_{i,k}$	The completion time of job <i>i</i> on machine <i>k</i> .
CA.	The start time of product q on assemble machine
SAq	M_A .
CA	The completion time of product q on assemble
CAq	machine M_A .
$\Delta = \{\lambda, \mu\}$	An individual of HCCE.
π	A solution for DAFSP.

Nomenclature

co-evolution (HCCE) algorithm to solve these deadlock-prone DAFSPs. First, an *assembly procedure Petri net* (APP) is established to model the entering of jobs into the assembly buffer. Based on banker's algorithm (BA), a Petri net-based deadlock amending method (IDAM) is proposed to ensure the feasibility or deadlock-freeness of the jobs' order. Then, IDAM is embeded into HCCE to coordinate deadlock control and scheduling. Importantly, HCCE employs the modified cooperative co-evolution algorithm (mCCEA) framework, including two subpopulations and an elite archive (EAR). These subpopulations primarily consist of job-permutations and factory-permutations, respectively, corresponding to the subpopulations of job-scheduling and factory-scheduling. The main contributions are summarized as follows.

- 1. For the first time we use Petri nets for analyzing deadlocks in DAFSP and a strategy IDAM with polynomial complexity is proposed.
- 2. We incorporate IDAM into HCCE to ensure the feasibility or deadlock-freeness of the solution of DAFSP, and the makespan of a solution is calculated by a novel backward method which maintains the deadlock-freeness of solution.
- 3. Two problem-specific heuristic operators are constructed for initialization and global evolution of proposed HCCE algorithm.
- 4. To improve the quality and diversity of individuals, an ITM is used to exchange information among subpopulations and EAR. Meanwhile, four local search operators are applied sequentially for each individual in EAR, enhancing the searchability of the algorithm.

To evaluate the performance of HCCE in solving the DAFSP, three variants of HCCE and three state-of-the-art metaheuristic algorithms HHMA [7], EDMBO [8], and PBIGA [6] are selected for comparison. The experimental

results demonstrate that: 1) HCCE outperforms its three variants in solving various instances, verifying the effectiveness of the specially designed components of HCCE. 2) HCCE outperforms the three compared metaheuristic algorithms, verifying the effectiveness of HCCE in solving deadlock-prone DAFSP.

The rest of this article is organized as follows. Section II reviews the related literature. Section III describes the DAFSP and the methods to check and amend the deadlock. Section IV presents the HCCE algorithm. Section V presents the results of computational experiments. Finally, Section VI summarizes our work and suggests directions for future research.

II. LITERATURE REVIEW

Extensive and systematic studies have been conducted on ASP [14]. Lee *et al.* [15] first consider the three-machine assembly flowshop scheduling problem to minimize makespan, where two machines are used in the first stage and the other in the assembly stage. The work [16] considers multiple parallel machines at the job processing stage and develops a heuristic algorithm with a worst-case ratio bound to minimize the makespan. Furthermore, the ASP with multiple non-identical assembly machines is studied in [16], where a hybrid algorithm is presented combining the variable neighborhood search with a heuristic.

The DASP has been investigated in recent years. This problem involves a manufacturing stage comprising several identical production factories. Hatami et al. [17] study this DASP to minimize the makespan by presenting a mixed integer linear programming model and a VND. Several meta-heuristic algorithms are developed to improve the scheduling efficiency [14]. For example, an effective Hyper Heuristic-based Memetic Algorithm (HHMA) [7] and an Estimation of Distribution Algorithm-based Memetic Algorithm (EDAMA) [5] are presented for DAPFSP for minimizing makespan. An IGA is used in [6] and [18] based on groupthink to minimize the total flow time. Considering the blocking constraint in the manufacturing stage, an effective Water Wave Optimization Algorithm with problem-specific knowledge (KWWO) is presented for solving the distributed assembly blocking flow-shop scheduling problem (DABFSP). The above articles all focus on minimizing a single objective. However, He et al. [19] minimize makespan, total flow time, and total energy consumption simultaneously by a Greedy Co-Evolutionary Cooperative Algorithm (CCEA). Additionally, Wang and Wang [20] minimize the total tardiness and energy consumption simultaneously by a cooperative memetic algorithm with feedback.

The CCEA is first presented by Potter and De Jong [21]. It has been used to solve many optimization problems, including power systems [22], [23], vehicle routing problems [24], [25], satellite-module layout [26], etc. Recently, a CCEA with a new cooperation mechanism, known as reference sharing, is proposed for function optimization problems [27]. Lei [28] provides a co-evolutionary genetic algorithm (CGA) for a fuzzy flexible job shop scheduling problem. Zheng and Wang [29] propose a CCEA for a resource-constrained unrelated parallel machine green scheduling problem for minimizing the



Fig. 1. The diagram of a DAFSP.

makespan and the total carbon emission. Besides, Pan [30] develops a co-evolutionary artificial bee colony (CCABC) algorithm for a steelmaking-continuous casting scheduling problem to minimize the makespan and charge waiting times.

Although deadlocks are a crucial aspect of manufacturing system evolution, as far as we know, there is no literature resolving the deadlock issue in DAFSP. The recent studies for solving deadlocks mainly focus on automated manufacturing systems (AMSs). Petri net is an important tool to model and characterize deadlocks [31]. Liu et al. [32] develop a transition cover-based design of Petri net deadlock controllers for AMSs. The robust deadlock control problem for AMSs with unreliable resources is studied in [33], [34] where Petri nets model the unreliable systems. Feng et al. [35] focus on the robust deadlock prevention problem for AMSs with a type of unreliable resources. Considering the assembly operation, Wu et al. [36] study the deadlock problem and model this system using resource-oriented Petri nets. Hu and Zhou [37] use a mathematical programming method to derive each deadlock in an iterative way, and synthesize a live controlled net.

III. DEADLOCK-PRONE DAFSP

A. Problem description and modeling

As shown in Fig. 1, the studied DAFSP has f identical factories $F = \{c_1, c_2, ..., c_f\}$ and an assembly machine M_A . It aims to produce l products $L = \{q_1, q_2, ..., q_l\}$ by scheduling u jobs $U = \{i_1, i_2, ..., i_u\}$. Each factory is a flow shop with m machines $M = \{k_1, k_2, ..., k_m\}$. The whole DAFSP consists of two stages: manufacturing and assembly. In the first manufacturing stage, all factories process jobs simultaneously, the finished jobs will be removed into the assembly buffers B_A with the capacity Ψ . The finished jobs in B_A will be assembled into products by machine M_A according to the job-to-product plan $AP = \{AP_q \mid q = 1, 2, ..., l\}$, where product $q \in L$ is assembled by $|AP_q|$ jobs in AP_q . Only after all jobs in AP_q are removed into B_A , the assembling of product q starts.

The *makespan* of the manufacturing (resp. assembly) stage is denoted by CM_{max} (resp. CA_{max}), which equals to the maximum completion time of all jobs (resp. products). Their calculation is given in Section III.D. Herein, CA_{max} is also called *system makespan*, and the objective of this paper is to minimize CA_{max} . We make the following assumptions for DAFSP: (1) All jobs and machines are available at time zero. The processing time of job *i* on machine *k* is predefined as $p_{i,k}$, and the assembly time of product *q* on machine M_A is set as pA_q .

(2) In each factory, all jobs have to follow the same path on every machine, and each job must path through all the machines within its assigned factory.

(3) A job can only be processed on a single machine at any time, and each machine can process one job at a time.

(4) The setup time is included in the processing time and transportation time of jobs are disregarded.

(5) Each job can only belong to one product plan, and the finished job will be removed into B_A immediately if B_A is available.

(6) Each job can be processed at any time after its previous job is finished, without the necessity of immediate processing.

Moreover, we introduce the following variables to describe DAFSP.

- $S_{i,k}$: start time of job *i* on machine *k*;
- *C_{i,k}*: completion time of job *i* on machine *k*;
- SA_q : start time of product q on assembly machine M_A ;
- CA_q: completion time of product q on assembly machine M_A;

The completion time of job *i* on the last machine-*m* is represented by $C_{i,m}$. Since only after all jobs in AP_q are manufactured, product *q* can be assembled, the following inequality holds.

$$SA_q \ge \max_{i \in APq} \{ C_{i,m} \}$$
⁽¹⁾

B. Solution coding and deadlock

The whole DAFSP can be divided into two subproblems: *job scheduling* and *factory scheduling*. The former subproblem determines the processing order of jobs entering into buffer B_A . The latter subproblem determines the assignment of jobs to factories. Thus, an individual for DAFSP is coded as $\Delta = \{\lambda, \mu\}$, which consists of two permutations $\lambda = (\lambda[1], \lambda[2], ..., \lambda[u])$ and $\mu = (\mu[1], \mu[2], ..., \mu[u])$ denoting the permutations of jobs and factories, respectively. Note that each job appears exactly once in λ .

For a coding $\Delta = \{\lambda, \mu\}$, after allocating job *i* to the factory $\mu[i]$, and sorting all jobs assigned to each factory according to their order in λ , we obtain a unique *solution* $\pi = \{\pi_c \mid c \in F\}$ of DAFSP. For example, as illustrated by Fig.2, for $\Delta = \{\lambda, \mu\}$



 q_1

Fig. 3. The example of deadlock.

where $\lambda = (i_1, i_4, i_3, i_2, i_5)$ and $\mu = (c_2, c_2, c_1, c_1, c_2)$, the solution extracted from Δ is $\pi = \{\pi_1, \pi_2\}$, where $\pi_1 = \{i_4, i_3\}$ and $\pi_2 = \{i_1, i_2, i_5\}$.

If B_A is full of jobs but none of them can be removed into M_A for assembling, then a blockage, namely *deadlock*, is resulted.

Example 1: Consider a DAFSP with five jobs i_1-i_5 and two products q_1 and q_2 with $AP_1 = \{i_1, i_3\}$ and $AP_2 = \{i_2, i_4, i_5\}$. The capacity of B_A is $\Psi = 3$. As shown in Fig. 3, according to $\lambda = (i_1, i_4, i_5, i_3, i_2)$, assuming that after i_1 , i_4 , and i_5 complete the processing and enter B_A , the buffer becomes saturated. Due to the lack of job i_3 (resp. i_2), product q_1 (resp. q_2) cannot be produced by assembling jobs in B_A . Thus, jobs i_2 and i_3 cannot be removed into B_A anymore and the system is trapped in *deadlock*.

As illustrated by Example 1, deadlock is closely related to the order of the jobs' arrival at buffer B_A , i.e., the permutation λ . Therefore, it is imperative to convert λ into a deadlock-free one. The next subsection will develop a deadlock-amending method jointly using Petri net model and Banker's algorithm (BA).

C. Deadlock-amending method based on Petri net and BA

1) Petri net model

This subsection develops an *assembly procedure Petri net* (APP) for modeling the entering of jobs into B_A . See Appendix A for the basic definitions of Petri net.

Definition 1: The APP (N, M_0) model of a DAFSP is constructed by the following steps:

Step 1: Establish a path $t_q p_q^e$ for each product $q \in L$, as well as a path $p_i t_i p_i^e$ for each job $i \in AP_q$, and add an arc (p_i^e, t_q) between every p_i^e and t_q .

Step 2: Let p_B be a place representing the buffer B_A . Add arcs (p_B, t_i) (resp. (t_q, p_B)) for each transition t_i (resp. t_q) with weight 1 (resp. $|AP_j|$).

Step 3: Let M_0 be the initial marking where $M_0(p_i) = 1$, $M_0(p_i^e) = 0$, $\forall i \in U$, $M_0(p_B) = \Psi$, and $M_0(p_q^e) = 0$, $\forall q \in L$.

Example 2: Consider the DAFSP in Fig. 3 with five jobs i_1 - i_5 and two products q_1 and q_2 where $AP_1 = \{i_1, i_3\}$ and $AP_2 = \{i_2, i_4, i_5\}$. The capacity of buffer B_A is $\Psi = 3$. Fig. 4(a) illustrates the APP model (N, M_0).

Remark 1: In (N, M_0) , place p_i with a token represents that job *i* is finished on the last machine *m*, the firing of t_i represents the moving of job *i* into B_A , while p_i^e with a token denotes the waiting of job *i* in B_A . The firing of t_q represents the start of the assembly operation of product *q*, and p_q^e denotes the finished product *q*. Buffers in p_B can be used or released by firing transitions t_i or t_q . Initially, M_0 implies that all jobs complete their processing in the first stage and all buffers of B_A are available. When all jobs are assembled and products are produced, each p_q^e is marked. Then APP reaches a *final state* M_E , where $M_E(p_i) = M_E(p_i^e) = 0$, $\forall i \in U, M_0(p_B) =$ Ψ , and $M_E(p_q^e) = 1$, $\forall q \in L$.

Remark 2: We assume that the assembly transition t_q , $q \in L$, is fired under a state M as long as it is enabled, i.e., $\forall p_i^e \in {}^{\bullet}t_q$, M(p) > 0. This is, after all jobs in AP_q are removed into B_A , the assembly of product q starts immediately, releasing the occupied buffers.

Given a permutation λ , by converting each job *i* of λ into transition t_i , we can extract a transition sequence $\alpha(\lambda)$, representing the order of jobs entering buffer B_A . According to the firing sequence of $\alpha(\lambda)$, the system may enter a deadlock.

Example 3: Consider the APP model (N, M_0) in Fig. 4(a). For a permutation $\lambda = (i_1, i_4, i_5, i_3, i_2)$, its corresponding transition sequence is $\alpha(\lambda) = t_{i1}t_{i4}t_{i5}t_{i3}t_{i2}$. However, only firing the first three transitions $t_{i1}t_{i4}t_{i5}$, a deadlock $M = p_{i2} + p_{i4}^e + p_{i5}^e + p_{i1}^e + p_{i3}$ is resulted, shown in Fig. 4(b). Particularly, at M, place p_B is empty, so transition t_{i2} or t_{i3} cannot fire and no token is flowed into p_{i2}^e or p_{i3}^e . Then, transitions t_{q1} and t_{q2} cannot fire and no occupied buffer B_A is released, i.e., p_B cannot be marked forever. Thus, M is a deadlock.

2) Improved BA to check the safeness of a marking

According to the supervisory control theory in DEDS [38], a state M of APP (N, M_0) is *safe* if it can reach the final state M_E . That is, the *safeness* of state M implies that all finished jobs can be assembled into products starting from M. We propose an improved BA (IBA) to determine the safeness of a specific marking.

Algorithm 1 IBA (Improved Bank's Algorithm).						
Input: an	APP model (N, M_0) and a marking M					
Output:	True or False					

 $Flag_w = 0$; /* $Flag_w = 1$ denotes that the safety detection result of the input marking *M* is obtained; otherwise, $Flag_w = 0.*/$

- 1: Let $\Omega = \{q \in L \mid M(p_q^e) = 0\}$
- 2: Let $\Theta = [\Theta_1, \Theta_2, ..., \Theta_l]$ where $\Theta_q = |AP_q| \sum_{i \in APq} M(p_i^e)$;
- 3: Let $M_{cu} = M$;
- 4: While($!Flag_w$)
- 5: **if** $\Omega = \emptyset$

 $Flag_{df}$ = True, $Flag_w$ = 1; /* $Flag_{df}$ = True denotes the input marking is deadlock-free; otherwise, $Flag_{df}$ = False.*/

6: else 7: Let $\Pi = \{q \in L \mid M_{cu}(p_B) \ge \Theta_q\}$ 8: If $\Pi \neq \emptyset$ 9: Select $q \in \Pi$; 10: $\Omega = \Omega \setminus \{q\}$; 11: Let $M_1 = M_{cu}$; 12: Set $M_1(p_q^e) = 1, M_1(p_B) = M_1(p_B) + |AP_q| - \Theta_q$,



(a) Initial marking M_0 in (N, M_0)

(b) Deadlock M in (N, M_0)

(c) Safe state M'in (N, M_0)

Fig. 4. APP model of DAFSP.

	$M_1(p_i^e)$	$=M_1(p_i)=0 \ \forall i \in AP_q;$
13:	Μ	$T_{cu} = M_1.$
14:	else	
15:		$Flag_{df} = $ false, $Flag_w = 1;$
16:	end	
17:	end	
18:	end	
19:	return <i>Flag</i> _{df} ;	

In IBA, first let $\Omega = \{q \in L \mid M(p_q^e) = 0\}$ collect all the non-finished products under M, and a sequence $\Theta = [\Theta_1,$ $\Theta_2, \ldots, \Theta_l$] with $\Theta_q = |AP_q| - \sum_{i \in APq} M(p_i^e)$ denote the number of jobs in AP_q that are not removed into B_A . The currently-analyzing marking M_{cu} is initially set as the input M. Then a loop is executed, which contains two main parts:

i) $\Omega = \emptyset$, all products are assembled, $M_{cu} = M_E$, and hence *M* is safe, True is returned.

ii) $\Omega \neq \emptyset$, we set $\Pi = \{q \in L \mid M_{cu}(p_B) \ge \Theta_q\}$. If $\Pi \neq \emptyset$, we select a product $q \in \Pi$, assemble it under M_{cu} , obtain a new marking M_1 by emptying all places p_i and p_i^e , $\forall i \in AP_q$, and adding a token into p_q^e . Then, update $M_{cu} = M_1$. Otherwise, if $\Pi = \emptyset$, it means there are no adequate buffers to support the assembly of the remaining products, hence False is returned.

Example 4: Consider the APP in Fig. 4 (a) and the state M in Fig. 4 (b). By IBA, we have $\Omega = \{q_1, q_2\}, \Theta = [1, 1], M_{cu}(p_B)$ = 0, $\Omega \neq \emptyset$, and $\Pi = \emptyset$, indicating that products q_1 and q_2 can never be assembled under M. For another state $M' = p_1 + p_2^{e} + p_2^{e}$ $p_3 + p_4 + p_5 + 2p_B$ shown Fig. 4(c), we have $\Omega = \{q_1, q_2\}, \Theta =$ [2, 2], and $M_{cu}(p_B) = 2$. First, select q_1 from Π , since there are adequate buffers to store the jobs for assembling q_1 , i.e., jobs in p_{i1} and p_{i3} , we empty places p_{i1} , p_{i3} , p_{i1}^e and p_{i3}^e , and a token is added into p_{q1}^{e} , resulting a new state $M_1 = p_2^{e} + p_4 + p_5 + p_5 + p_6 + p_6$ $p_{q1}^{e} + 2p_{B}$. Similarly, product q_{2} can be assembled as well under M_1 . Therefore, M' is safe and the output is True.

3) *IBA-based deadlock-amending method*

Given an APP (N, M_0) and a permutation λ , by the aid of Algorithm IBA, we develop a polynomial-complexity algorithm, namely IDAM, to determine whether λ is deadlock-free, and if not, we convert λ into a deadlock-free permutation.

Algorithm 2 IDAM (IBA-based deadlock-amending method). **Input:** an APP model (N, M_0) and a λ -sequence **Output:** a deadlock-free sequence λ' .

Obtain $\alpha(\lambda) = t_1 t_2 \dots t_n$, i.e., the transition sequence 1: corresponding to λ .

2:	Let $M_{cu} = M_0$;
3:	$\gamma = \alpha(\lambda);$
4:	for each $r \in [1, \alpha(\lambda)]$
5:	$Flag_t = 0$;/* $Flag_t = 0$ denotes that safe transition is
	not found; otherwise, $Flag_t = 1$.
6:	while $(!Flag_i)$
7:	Let <i>t</i> be the <i>r</i> -th transition of γ ;
8:	$M_{cu}[t>M;$
9:	if $IBA(M) = True$
10:	$M_{cu} = M;$
11:	$Flag_t = 1;$
12:	else
13:	remove <i>t</i> to the end of γ ;
14:	end
15:	end
16:	end

17: Extract a job permutation λ' from γ ;

18: Output λ' .

Algorithm IDAM first obtains the transition sequence $\alpha(\lambda)$ from λ , and set the currently-analyzing $M_{cu} = M_0$ and $\gamma = \alpha(\lambda)$. Then a loop while (Lines 5–14) is performed $|\alpha(\lambda)|$ times. Specifically, during the *r*-th time of executing the loop, let *t* denote the r-th transition of γ , M be the state after firing t at M_{cu} , i.e., $M_{cu}[t>M, \text{ if IBA}(M) = \text{True}, M \text{ is safe, then let } M_{cu} =$ *M*, and this loop ends; otherwise, remove t to the end of γ and the current loop continues.

Remark 3: In APP model (N, M_0) , each transition is fired exactly once before reaching the final marking M_E . Given a permutation λ and its corresponding transition sequence $\alpha(\lambda)$, algorithm IDAM can find a feasible transition sequence γ , i.e., an updated version of $\alpha(\lambda)$, according to which M_E can be reached from M_0 . That means, all products can be assembled successfully by firing the transitions in γ sequentially. Therefore, the job permutation λ' extracted from γ is deadlock-free.

Computational complexity of Algorithm IDAM: The entire IDAM method repeats $|\alpha(\lambda)| = u$ iterations, where u is the number of jobs. In the r-th iteration, at most (u - r + 1)transitions are checked. Thus, the complexity of IDAM is $O(u^2)$, i.e., IDAM is of polynomial complexity.

Example 5: Consider the APP in Fig. 4(a) and a permutation $\lambda = (i_1, i_4, i_5, i_3, i_2), \alpha(\lambda) = t_{i1}t_{i4}t_{i5}t_{i3}t_{i2}$. The procedure of implementing IDAM on λ is illustrated in Fig. 5. First let $\gamma = \alpha(\lambda)$. Then as shown in Fig. 5(a) (resp. (b)), after firing the first (resp. second) transition t_{i1} (resp. t_{i4}) of γ , the obtained state is determined safe by IBA. However, the



Fig.5. Processing of IDAM. (a) t_{i1} is fired. (b) t_{i4} is fired. (c) t_{i5} is moved to the end of α . (d) t_{i3} is fired. (e) t_{i2} is fired. (f) t_{i5} is fired.

resulted state after firing the third transition t_{i5} is detected as False by IBA. So, t_{i5} needs to be remove to the end of γ , generating a new sequence $\gamma = t_{i1}t_{i4}t_{i3}t_{i2}t_{i5}$ in Fig. 5(c). Subsequently, we continue analyzing the third transition t_{i3} of γ , and the resulting state, shown in Fig. 5(d), is checked safe by IBA. Similarly, by firing the remaining transition t_{i2} and t_{i5} , we can find that the resulted states in Fig. 5(e) and (f) are safe. Thus, the final marking M_E can be reached from M_0 by firing the transition in γ sequentially. That is, the updated sequence γ is feasible, and the corresponding processing sequence $\lambda' = (i_1, i_4, i_3, i_2, i_5)$ is deadlock-free.

D. Makespan calculation

Given a coding $\Delta = \{\lambda, \mu\}$, we first implement algorithm IDAM to amend λ , obtaining a deadlock-free λ' . Then, a deadlock-free solution π can be obtained from $\Delta' = \{\lambda', \mu\}$. The system makespan of π is computed in a backward way, so as to maintain the deadlock-freeness of π .

First let σ be the sequence of assembling products extracted from λ' . The makespans CM_{max} and CA_{max} of $\boldsymbol{\pi} = \{\pi_c \mid c \in F\}$ can be computed based λ' and σ according to equations (2)–(9), where π_c, λ' , and σ can be written as $\pi_c = \{i_{c(1)}, i_{c(2)}, ..., i_{c(|\pi_c|)}\}, \lambda' = (\lambda'(1), \lambda'(2), ..., \lambda'(u))$, and $\sigma = (\sigma(1), \sigma(2), ..., \sigma(l))$ for convenience, respectively.

$$\begin{cases} C_{\lambda'(u),m} = Time \\ S_{\lambda'(u),m} = C_{\lambda'(u),m} - p_{\lambda'(u),m} \end{cases}$$
(2)

$$\begin{cases} C_{\lambda'(h),m} = \begin{cases} S_{\lambda'(h+1),m} & \text{if } \lambda'(h), \lambda'(h+1) \in \pi_c, \\ & \forall h \in U / \{u\}, \forall c \in F \\ C_{\lambda'(h+1),m} - 1 & \text{otherwise} \end{cases}$$
(3)
$$S_{\lambda'(h),m} = C_{\lambda'(h),m} - p_{\lambda'(h),m} \end{cases}$$

$$\begin{cases} C_{i_{c(|\pi_{c}|)},k} = S_{i_{c(|\pi_{c}|)},k+1} \\ S_{i_{c(|\pi_{c}|)},k} = C_{i_{c(|\pi_{c}|)},k} - p_{i_{c(|\pi_{c}|)},k} \end{cases} \quad \forall c \in F, \forall k \in M / \{m\}$$
(4)

$$\begin{cases} C_{i_{c(h)},k} = \min\left(S_{i_{c(h)},k+1}, S_{i_{c(h+1)},k}\right) \\ S_{i_{c(h)},k} = C_{i_{c(h)},k} - p_{i_{c(h)},k} \end{cases}$$
(5)

$$\forall h \in \{1, 2, ..., |\pi_c| - 1\}, \forall c \in F, \forall k \in M / \{m\}$$

$$CM_{\max} = C_{\mathcal{L}(u)} - \min_{i \in U} \left(S_{i,1}\right)$$
(6)

$$\begin{cases} SA_{\sigma(1)} = \max_{i \in AP_{\sigma(1)}} \left\{ C_{i,m} \right\} \\ CA_{\sigma(1)} = SA_{\sigma(1)} + pA_{\sigma(1)} \end{cases}$$
(7)

$$\begin{cases} SA_{\sigma(j)} = \max\left\{CA_{\sigma(j-1)}, \max_{i \in AP_{\sigma(j)}}\left\{C_{i,m}\right\}\right\} \\ CA_{\sigma(j)} = SA_{\sigma(j)} + pA_{\sigma(j)} \end{cases} \quad \forall j \in L / \{1\} \quad (8)$$

$$CA_{max} = \max_{j \in L} CA_{\sigma(j)} - \min_{i \in U} \left(S_{i,1} \right)$$
(9)

Table I THE PROCESSING TIME OF JOBS $i_1 - i_5$ ON MACHINES

	k_1	k_2	k_3				
i_1	5	3	6				
i_2	4	3	5				
<i>i</i> ₃	3	3	4				
i_4	6	4	6				
<i>i</i> ₅ 4 6 4							
Table II							

THE PROCESSING TIME OF PRODUCTS $q_1 - q_2$ ON MACHINES



Fig. 6. Gantt chart of a solution of DAFSP.

In equation (2), let the scheduling time Time be the completion time of the last job $\lambda'(u)$ on the last machine *m* in the manufacturing stage, i.e., $C_{\lambda'(u), m} = Time$, and its start time can be computed. Equation (3) determines $C_{i, m}$ and $S_{i, m}$ for each job $i \in \{\lambda'(1), \lambda'(2), \dots, \lambda'(u-1)\}$ on machine *m*. In particular, if two consecutive jobs $\lambda'(h)$ and $\lambda'(h+1)$ are assigned to the same factory, we set $C_{\lambda'(h), m} = S_{\lambda'(h+1), m}$. Otherwise, to ensure $\lambda'(h)$ is finished before $\lambda'(h+1)$, we set $C_{\lambda'(h), m} = C_{\lambda'(h+1), m} - 1$. Equations (4) and (5) compute the completion time and start time for the last job $i_{c(\pi c)}$ and the remaining jobs of π_c on every machine $k \in M / \{m\}$, respectively. Equation (6) obtains the makespan of the manufacturing stage. Equations (7) and (8) obtain the start time and completion time of the first product $\sigma(1)$ and $\sigma(j)$, j > j1, respectively. Equation (9) computes the system makespan CA_{max} .

Example 6: Reconsider the DAFSP in Example 2, its APP model is shown in Fig. 4(a). The processing time of jobs i_1 – i_5 and the products q_1 and q_2 on various machines are illustrated in Table I and II, respectively. For $\Delta = \{\lambda, \mu\}$, where $\lambda = (i_1, i_4, i_5, i_3, i_2)$ and $\mu = (c_2, c_2, c_1, c_1, c_2)$, first λ is converted into a deadlock-free $\lambda' = (i_1, i_4, i_3, i_2, i_5)$ by Algorithm IDAM. Thus, the solution extracted from $\{\lambda', \mu\}$ is $\boldsymbol{\pi} = \{\pi_1, \pi_2\}$, where $\pi_1 = \{i_4, i_3\}$ and $\pi_2 = \{i_1, i_2, i_5\}$. Meanwhile, $\sigma = (q_1, q_2)$ is obtained from λ' . According to (2)–(9), we obtain $CM_{max} = 25$, $CA_{max} =$

30, and the corresponding Gantt chart is provided in Fig. 6, where the scheduling time *Time* is denoted as symbol "T" for brevity

IV. HCCE ALGORITHM FOR DAFSP

The proposed Hybrid Cooperative Co-Evolution (HCCE) algorithm for DAFSP is introduced in this section. The *individual* of HCCE is referred to the double-permutation coding $\Delta = \{\lambda, \mu\}$. The main components of HCCE are: *m*CCEA framework, initialization method, global search, information transfer mechanism (ITM), local search methods, and reinitialization strategy.

A. mCCEA framework

The proposed HCCE includes two subpopulations, namely Π_1 and Π_2 , which are composed of λ permutations and μ permutations. Let Π_1 and Π_2 have the same size, denoted as *PS*.

Similar to the work [40], each entity in Π_1 is represented by $\langle \lambda^n, col_1[n] \rangle$, where n = 1, 2, ..., PS. The integer $col_1[n]$, ranging from 1 to *PS*, is called *collaborator* of λ^n , which indicates that λ^n is associated with the $col_1[n]$ -th permutation $\mu^{col1[n]}$ in Π_2 . Then, λ^n and its collaborator constitute an individual $\{\lambda^n, \mu^{coll[n]}\}$. Similarly, each entity in Π_2 is represented by $\langle \mu^n, col_2[n] \rangle$, where $col_2[n]$ is an integer from 1 to *PS*, representing the collaborator index in Π_1 .

At most $2 \times PS$ individuals can be obtained by combining the λ permutations and μ permutations with their collaborators. We use EAR, denoted by Φ , to store the superior *ep*% individuals, i.e., $AS = ep\% \times PS$ is the size of Φ .

For example, consider the *m*CCEA population shown in Fig. 7, where *PS* = 3 and *AS* = 1. The entity $\langle \lambda^1, 3 \rangle$ in Π_1 indicates that the collaborator of λ^1 is μ^3 , and a new individual $\Delta^1 = \{\lambda^1, \mu^3\}$ can be obtained. Similarly, for the entity $\langle \mu^1, 1 \rangle \in \Pi_2$, the collaborator of μ^1 is λ^1 , and the corresponding individual is $\Delta^2 = \{\lambda^1, \mu^1\}$. Following this scheme, another four individuals $\Delta^3 = \{\lambda^2, \mu^1\}, \Delta^4 = \{\lambda^2, \mu^2\}, \Delta^5 = \{\lambda^3, \mu^2\}, \text{ and } \Delta^6 = \{\lambda^3, \mu^3\}$ are obtained. Among them, assuming that Δ^1 is the best individual, therefore, it can be used to constitute the EAR Φ .

B. Initialization

1) Heuristic initialization methods

Let $\vartheta_i = \sum_{k=1}^{m} p_{i,k}$ be the sum of processing time for a job *i*, and $\sum_{i \in AP_q} \vartheta_i$ be the sum of processing time of jobs that are used for assembling product *q*. We first present two problem-specific heuristic operators H_1 and H_2 .

*H*₁: Given a job permutation $\lambda = (\lambda[1], \lambda[2], ..., \lambda[u])$, we assign each job $i_n = \lambda[n], n \in \{1, 2, ..., u\}$, to all possible factories and calculate the corresponding makespan CM_{max} , and the factory with the lowest CM_{max} is selected to process job i_n . Finally, a complete factory permutation μ is obtained.

*H*₂: Given a factory permutation μ , generate a job permutation $\gamma = (\gamma[1], \gamma[2], ..., \gamma[u])$ by sorting all jobs in descending order of the sum of processing time. Let the job permutation λ be an empty sequence initially. For each job $i_n = \gamma[n], n \in \{1, 2, ..., u\}$, we test it at all possible positions of λ ,



Fig. 7. *m*CCEA framework where PS = 3 and AS = 1.



Fig. 8. An example of the evolution process for λ sequence.

and insert i_n at the position of λ resulting in the lowest CM_{max} . Finally, a complete job permutation λ is obtained.

Based on operators H_1 and H_2 , we propose four initialization methods $L_1 - L_4$.

 L_1 : Generate a job permutation λ by sorting all jobs in descending order based on the sum of their processing time. Then, take λ as the input for H_1 , obtain a factory permutation μ and an initial individual $\Delta = \{\lambda, \mu\}$.

*L*₂: Generate a permutation σ by sorting all products in descending order of the sum of their processing time. For each product $q \in \sigma$, sort jobs in AP_q in descending order of the sum of their processing time, and obtain a sequence S_q . Finally, a job permutation λ is generated by sorting sequences S_q according to σ . Taking λ as the input for H_1 , we obtain a factory permutation μ and an individual $\Delta = \{\lambda, \mu\}$.

*L*₃: Take a random job permutation λ as the input for *H*₁, obtain a factory permutation μ and an initial individual $\Delta = \{\lambda, \mu\}$.

*L*₄: Take a random factory permutation μ as the input for *H*₂, obtain a job permutation λ and an initial individual $\Delta = {\lambda, \mu}$.

2) Initialization for Π_1 , Π_2 and Φ

We generate the first four individuals using the four heuristic methods L_1-L_4 . The remaining *PS*-4 individuals are generated randomly. Algorithm IDAM is used to ensure the deadlock-freeness of all job permutations. The obtained individuals are denoted by $\Delta^n = {\lambda^n, \mu^n}, n \in {1, 2, ..., PS}$.

Initially, for each n = 1, 2, ..., PS, let $col_1[n] = col_2[n] = n$. Then Π_1 and Π_2 store all $\langle \lambda^n, col_1[n] \rangle$ and $\langle \mu^n, col_2[n] \rangle$, respectively. The top $AS = ep\% \times PS$ individuals with the shortest system makespan are selected to construct EAR.

C. Global evolution for HCCE

Note that Π_1 and Π_2 evolve with different problem-specific global explorers.

For each $\langle \lambda^n, col_1[n] \rangle$ in Π_1 , n = 1, 2, ..., PS, let r be a random integer between 1 and *PS*. We obtain a new permutation λ by taking μ^r in Π_2 as the input of operator H_2 . By Algorithm IDAM, we convert λ to deadlock-free λ' . If the individual $\{\lambda', \mu^r\}$ is better than $\{\lambda^n, \mu^{col1[n]}\}$, or $\mu^{col1[n]}$ in Π_2 has been changed, we set $\lambda^n = \lambda'$ and $col_1[n] = r$. Meanwhile, if $\{\lambda', \mu^r\}$ is better than $\{\lambda^{col2[r]}, \mu^r\}$, we set $col_2[r] = n$. An example of above evolution process is illustrated in Fig. 8.

Similarly, for each entity $\langle \mu^n, col_2[n] \rangle \in \Pi_2$, let *r* be a random integer between 1 and *PS*. A new permutation μ is generated by taking λ^r in Π_1 as the input for operator H_1 . If the new individual $\{\lambda^r, \mu\}$ is better than $\{\lambda^{col_2[n]}, \mu^n\}$, or $\lambda^{col_2[n]}$ in Π_1 has been changed, we set $\mu^n = \mu$ and $col_2[n] = r$. Also, if $\{\lambda^r, \mu\}$ is better than $\{\lambda^r, \mu^{col_1[r]}\}$, we set $col_1[r] = n$.

D. Information transfer mechanism

To improve the diversity and the quality of individuals, we propose an information transfer mechanism (ITM), transferring the superior coding among subpopulations Π_1 , Π_2 , and EAR Φ .

Denote $\langle \lambda^b, col_1[b] \rangle$ and $\langle \lambda^w, col_1[w] \rangle$ as the *best* and *worst* entities in Π_1 with the shortest and largest system makespan, respectively. Similarly, the best and worst entities in Π_2 is denoted by $\langle \mu^b, col_2[b] \rangle$ and $\langle \mu^w, col_2[w] \rangle$, respectively.

First, let r_1 and r_2 be two random integers between 1 and *PS*. Then for entities $\langle \lambda^{r_1}, col_1[r_1] \rangle \in \Pi_1$ and $\langle \mu^{r_2}, col_2[r_2] \rangle \in \Pi_2$, we replace λ^{r_1} with $\lambda^{col_2[b]}$ and replace μ^{r_2} with $\mu^{col_1[b]}$.

Next, let r_3 and r_4 be two random integers between 1 and AS. The elite individuals $\Delta_{e}^{r3} = \{\lambda_e^{r3}, \mu_e^{r3}\}$ and $\Delta_e^{r4} = \{\lambda_e^{r4}, \mu_e^{r4}\}$ are replaced with $\{\lambda^b, \mu^{col1[b]}\}$ and $\{\lambda^{col2[b]}, \mu^b\}$, respectively. On the other hand, the permutations λ^w and μ^w in the worst entities are replaced by λ_e^{r3} and μ_e^{r4} , respectively.

E. Local search performed on EAR

To increase the convergence ability of HCCE, four local search operators LS_1-LS_4 are executed sequentially on each elite individual $\Delta_{e^n} = {\lambda_{e^n}, \mu_{e^n}}$ in EAR Φ , where n = 1, 2, ..., AS. Their details are as follows.

LS₁: Let $\lambda = \lambda_e^n$. For a product q, remove all jobs of AP_q from λ and denote the remaining sequence as λ_q . Then we insert jobs of AP_q sequentially into λ_q , leading to the lowest system makespan. Meanwhile, assign all jobs in AP_q to the factory with the lowest system makespan. Continue this process for all products. If the generated new individual Δ is better than the original Δ_e^n , replace it with Δ .

Remark 4: Identify q_t as the last product that is not assembled continuously, and the factory assigned to the last processing job of, is called *critical-factory*. Meanwhile, the factory with the maximum start time for its first processing job is called *min-factory*. For example, consider the scheduling result in Fig. 6, the last product that is not assembled continuously is q_1 , thus, $q_t = q_1$. The last processing job for q_1

is i_3 , which is assigned to factory c_1 . Thus, the *critical-factory* is c_1 . Additionally, the *min-factory* is c_2 .

 LS_2 : Let Γ be the set of jobs processed in the critical-factory. Remove all jobs in Γ from λ_e^n , and denote the remaining permutation as λ_q . Insert each job of Γ into the certain position of λ_q that leads to the lowest system makespan. Finally, obtain a complete job permutation λ . Use Algorithm IDAM to convert λ to a deadlock-free λ' . If the generated new individual $\Delta = \{\lambda', \mu_e^n\}$ is better than Δ_e^n , replace it with Δ .

*LS*₃: For each job processed by the critical-factory, we change its assigned factory to min-factory, and obtain a new factory permutation μ . If the generated new individual $\Delta = \{\lambda_e^n, \mu\}$ is better than Δ_e^n , replace it with Δ .

*LS*₄: Denote $\Delta_{best} = \{\lambda_{best}, \mu_{best}\}$ as the best individual in Φ . We first randomly remove $d = u \times cd\%$ jobs from λ_e^n , and let Γ collect all these removed jobs. Then, a new job sequence λ is generated from λ_e^n by arranging the jobs of Γ according to their order in λ_{best} . The assigned factory for each job in Γ is changed according to μ_{best} , we obtain a new factory sequence μ from μ_e^n . Use Algorithm IDAM to convert λ to deadlock-free λ' . If the generated new individual $\Delta = \{\lambda', \mu\}$ is better than the original one, replace it with Δ .

F. Restart

To avoid the local optimum, we propose an reinitialization strategy to restart the populations for remaining the diversity. Specifically, if the best individual $\Delta_{best} = \{\lambda_{best}, \mu_{best}\}$ of EAR Φ has not been improved in a predetermined number α of consecutive generations, we restart the subpopulations Π_1 and Π_2 according to the initialization method proposed in section IV. B.

G. Overall HCCE algorithm for DAFSP

The overall HCCE algorithm for DAFSP is outlined as follows.

 Set parameters <i>AS</i>, <i>PS</i>, and α. Construct APP model for DAFSP. Initialization for Π₁, Π₂ and Φ. While termination is not satisfied do.
 Construct APP model for DAFSP. Initialization for Π₁, Π₂ and Φ. While termination is not satisfied do
3: Initialization for Π_1 , Π_2 and Φ . 4: While termination is not satisfied do
4. While termination is not satisfied do
+. White termination is not satisfied do
5: Perform global evolution for each entity in Π_1 .
6: Perform global evolution for each entity in Π_2 .
7: Exchange information among Π_1 , Π_2 , and Φ through ITM model.
8: Perform local search for each individual in Φ .
9: If the best individual $\Delta_{best} \in \Phi$ is not improved in α consecutive generations
10: Initialization for Π_1 and Π_2 .
11: end
12: end
13: Output the Δ_{best} .

V. COMPUTATION EXPERIMENTS

In this section, we conduct extensive experiments to evaluate the performance of proposed HCCE algorithm in solving various deadlock-prone DAFSPs. First, the parameter

 Table III

 PARAMETER SIZES FOR EACH INSTANCE TYPE

Instance type	и	f	т	l	$u \times f \times m \times l$
Small	10, 16, 24	2, 3	2, 4, 6	2, 4	$3 \times 2 \times 3 \times 2 = 36$
Medium	30, 40, 50	4, 6	8, 10, 12	6, 8	$3 \times 2 \times 3 \times 2 = 36$
Large	80, 100, 120	8, 10	16, 18, 20	10, 16	$3 \times 2 \times 3 \times 2 = 36$

Table IV

Trial	F	actor	Leve	1	Response Value			
Inai	PS	ер	α	cd	Small	Medium	Large	
1	1	1	1	1	445.5	1175.5	1769.7	
2	1	2	2	2	449.1	1175.9	1775.4	
3	1	3	3	3	445.7	1172.3	1777.2	
4	1	4	4	4	444.1	1173.9	1773.9	
5	2	1	2	3	441.4	1172.2	1775.1	
6	2	2	1	4	446.4	1172.4	1776.5	
7	2	3	4	1	446.6	1167.1	1784.3	
8	2	4	3	2	445.6	1168.9	1779.7	
9	3	1	3	4	444	1171.3	1775	
10	3	2	4	3	445.6	1172.4	1771.8	
11	3	3	1	2	448.4	1173.7	1774.7	
12	3	4	2	1	442.4	1174.2	1775.8	
13	4	1	4	2	443.9	1172.2	1774.7	
14	4	2	3	1	442	1167.8	1775.7	
15	4	3	2	4	446.1	446.1 1169.2 17		
16	4	4	1	3	446.4	46.4 1172.2 1775		

values of HCCE are calibrated via a design of experiment method. The components of HCCE are validated by three of its variant algorithms. Finally, we compare HCCE with three other state-of-the-art algorithms. The experiments are run on a Windows 10 operating system with an Intel Core i9-10900K CPU @ 3.70 GHz and 64.0 GB of RAM by using MATLAB programming language.

A. Experimental settings

Since the DAFSP has not been dealt with before, according to the benchmark design idea [1], we generate three types of testing instances: *small*, *medium*, and *large*. The scale parameters u, f, m, and l for each instance type are listed in Table III, where u, f, m, and l are the numbers of jobs, factories, machines, and products, respectively. There are a total of 108 combinations of $u \times f \times m \times l$. For each combination, three cases are presented in which the processing times for jobs and products are randomly generated within [1, 99] and [1, 50], respectively, following a uniform distribution. Therefore, we consider $324 = 108 \times 3$ instances.

Table V
STATISTICAL ANALYSIS AND SELECTED PARAMETER VALUE

 Table VI

 RESULTS OF HCCE AND COMPARED ALGORITHMS

Factor level		PS	ер	α	cd	
	1	446.1	443.7	446.675	444.125	
	2	445	445.775	444.75	446.75	
	3	445.1	446.7	444.325	444.775	
Small	4	444.6	444.625	445.05	445.15	
	Delta	1.5	3	2.35	2.625	
	Rank	4	1	3	2	
	SPV	50	0.2	21	0.1	
	1	1174.4	1172.8	1173.45	1171.15	
	2	1170.15	1172.125	1172.875	1172.675	
	3	1172.9	1170.575	1170.075	1172.275	
Medium	4	1170.35	1172.3	1171.4	1171.7	
	Delta	4.25	2.225	3.375	1.525	
	Rank	1	3	2	4	
	SPV	35	0.5	21	0.1	
	1	1774.05	1773.625	1774.15	1776.375	
	2	1778.9	1774.85	1775.6	1776.125	
	3	1774.325	1778.075	1776.9	1774.95	
Large	4	1775.55	1776.275	1776.175	1775.375	
	Delta	4.85	4.45	2.75	1.425	
	Rank	1	2	3	4	
	SPV	25	0.2	3	0.7	

For each instance, the assembly plan AP_q for each product $q \in L$ is randomly generated. The capacity Ψ of buffer B_A is randomly generated with ranges of [b, 1.5b] where $b = \max\{|AP_q|, q \in L\}$. The termination time for all algorithms is defined as $Time \times u \times f \times m \times l$ milliseconds, where Time takes three values 20, 50, 120 for large, medium, and small instances, respectively.

B. Parameter calibration

Four relevant parameters {*PS*, *ep*, *cd*, α } in the HCCE algorithm require calibration, where *PS* denotes the number of individuals, *ep* represents the proportion of selected superior individuals in EAR Φ , *cd* is the proportion of jobs removed in the *destruction* process of *LS*₄, and α indicates the number of largest consecutive generations in the restart strategy.

The above parameter calibration is performed by following two steps: i) experimentally selecting different values for each parameter as its factor levels, and ii) determining the most suitable parameter values for different instance types using the traditional Taguchi design of experiment (DOE) method [39]. Each instance is tested ten times independently, and the average system makespan CA_{max} serves as the performance metric. This process is illustrated as follows:

First, we test ten values for each parameter on a medium-type instance with $u \times f \times m \times l = 30 \times 4 \times 10 \times 6$, while the other parameters are fixed. Four values that lead to the minimum average CA_{max} are selected as the factor levels.

			HC	CE ₁	HC	CE_2	HC	CE ₃	HC	CE
Ins	stance g	group	bRPD	aRPD	bRPD	aRPD	bRPD	aRPD	bRPD	aRPD
		10	0.0175	0.0425	0.0166	0.0426	0.0054	0.0072	0.0000	0.0044
	и	16	0.0327	0.0797	0.0354	0.0763	0.0041	0.0161	0.0016	0.0137
		24	0.0413	0.0723	0.0382	0.0702	0.0064	0.0215	0.0013	0.0173
		2	0.0255	0.0513	0.0227	0.0526	0.0057	0.0133	0.0014	0.0099
	J	3	0.0354	0.0784	0.0374	0.0735	0.0048	0.0165	0.0005	0.0137
s		2	0.0231	0.053	0.0212	0.0541	0.0030	0.0106	0.0007	0.0088
	т	4	0.0332	0.0759	0.0385	0.0702	0.0083	0.0199	0.0000	0.0135
		6	0.0352	0.0656	0.0305	0.0648	0.0046	0.0143	0.0021	0.0131
	,	2	0.0294	0.0642	0.0294	0.0602	0.0042	0.0154	0.0014	0.0139
	ı	4	0.0315	0.0655	0.0307	0.0659	0.0063	0.0144	0.0005	0.0098
	A	Avg	0.0305	0.0648	0.0301	0.0630	0.0053	0.0149	0.0010	0.0118
		30	0.0491	0.075	0.0500	0.0725	0.0096	0.0239	0.0002	0.0135
	и	40	0.0481	0.0725	0.0467	0.0712	0.0085	0.0211	0.0015	0.0134
		50	0.047	0.0681	0.0456	0.0674	0.0120	0.0252	0.0006	0.0163
	f	4	0.045	0.0683	0.0484	0.0701	0.0113	0.0253	0.0005	0.0131
		6	0.0511	0.0754	0.0465	0.0706	0.0087	0.0215	0.0010	0.0156
М	m	8	0.0508	0.0758	0.0491	0.0720	0.0140	0.0254	0.0002	0.0150
		10	0.0453	0.0731	0.0478	0.0725	0.0091	0.0240	0.0009	0.0164
		12	0.0481	0.0666	0.0455	0.0666	0.0068	0.0208	0.0012	0.0117
	,	6	0.0458	0.0702	0.0458	0.0692	0.0098	0.0231	0.0009	0.0140
	ı	8	0.0504	0.0735	0.0491	0.0716	0.0102	0.0237	0.0006	0.0147
	Avg		0.0481	0.0719	0.0475	0.0704	0.0100	0.0234	0.0008	0.0144
		80	0.0436	0.0648	0.0354	0.0592	0.0088	0.0161	0.0000	0.0106
	и	100	0.0352	0.0495	0.0301	0.0469	0.0046	0.0136	0.0007	0.0126
		120	0.0277	0.0449	0.0282	0.0430	0.0060	0.0114	0.0000	0.0097
	£	8	0.0338	0.0512	0.0299	0.0481	0.0051	0.0128	0.0003	0.0102
	5	10	0.0371	0.0549	0.0325	0.0512	0.0079	0.0146	0.0001	0.0117
L		16	0.0409	0.0598	0.0381	0.0567	0.0082	0.0162	0.0003	0.0123
	т	18	0.0353	0.0516	0.0326	0.0507	0.0078	0.0153	0.0003	0.0132
		20	0.0302	0.0478	0.0230	0.0416	0.0034	0.0096	0.0001	0.0074
	,	10	0.0338	0.0509	0.0300	0.0490	0.0059	0.0128	0.0004	0.0108
	ı	16	0.0372	0.0552	0.0324	0.0504	0.0070	0.0146	0.0001	0.0111
	A	Avg	0.0355	0.0531	0.0312	0.0497	0.0065	0.0137	0.0002	0.0110

Specifically, the four levels chosen for *PS* are $\{25, 35, 40, 50\}$; for *ep*, $\{0.2, 0.3, 0.5, 0.6\}$; for α , $\{3, 6, 21, 24\}$; and for *cd*, $\{0.1, 0.4, 0.7, 0.8\}$.

Second, an orthogonal array $L_{16}(4^4)$ is established based on the different factor levels in Table IV. Since three instance types are designed for the DAFSP, DOE is performed three times for instances with $u \times f \times m \times l = 16 \times 3 \times 4 \times 4$, $40 \times 4 \times 10 \times 8$, and $80 \times 8 \times 18 \times 10$, respectively. During DOE execution, there are 16 parameter combinations, and HCCE is independently conducted 10 times for each combination. The average system makespan is used as the response value.



Fig. 9. Variation trend for compared algorithms.

Table VII RESULTS OF THE FREIDMAN TEST

		Instance		Averag	Chi-	Davalara		
		group	HCCE1	HCCE ₂	HCCE ₃	HCCE	Square	P-value
	bRPD	S	3.65	3.35	2	1	27.545	0.0
		М	3.65	3.35	2	1	27.545	0.0
		L	3.90	3.10	2	1	28.920	0.0
	aRPD	S	3.60	3.40	2	1	27.120	0.0
		М	3.85	3.15	2	1	28.758	0.0
		L	4	3	2	1	30.000	0.0

Table V presents a statistical analysis of the obtained results. In small-scale instances, *ep* is the most important factor, followed by *cd*, α , and *PS*. In medium-scale instances, *PS* is the most important factor, followed by α , *ep*, and *cd*. In large-scale instances, *PS* ranks as the most important factor, followed by *ep*, α , and *cd*. Therefore, the recommended parameter sets {*PS*, *ep*, α , *cd*} for small-scale, medium-scale, and large-scale instances are {50, 0.2, 21, 0.1}, {35, 0.5, 21, 0.1}, and {25, 0.2, 3, 0.7}, respectively.

C. Effectiveness of HCCE special components

To ascertain the effectiveness of HCCE's components, we developed three variants of HCCE, denoted as $HCCE_1-HCCE_3$. $HCCE_1$ employs the basic CCEA-RS algorithm [40] with random initialization of individuals. $HCCE_2$ is $HCCE_1$ adding heuristic initialization. $HCCE_3$ is $HCCE_2$ incorporating the mCCEA framework. Finally, HCCE is $HCCE_3$ plus the local search method.

Table VIII RESULTS OF HCCE AND COMPARED ALGORITHMS

Instance group			НН	MA	EDM	4BO	PBIGA		HCCE	
Instance group			bRPD	aRPD	bRPD	aRPD	bRPD	aRPD	bRPD	aRPD
		10	0.0875	0.1035	0.0375	0.0877	0.0304	0.0431	0.0010	0.0081
	и	16	0.1172	0.1299	0.0480	0.0922	0.0374	0.0524	0.0003	0.0102
		24	0.1338	0.1552	0.0330	0.0687	0.0490	0.0641	0.0007	0.0160
	£	2	0.1091	0.1261	0.0290	0.0660	0.0338	0.0453	0.0005	0.0096
	,	3	0.1166	0.1330	0.0500	0.0998	0.0440	0.0612	0.0008	0.0132
s	m	2	0.1142	0.1276	0.0351	0.0781	0.0339	0.0490	0.0007	0.0116
		4	0.1185	0.1400	0.0423	0.0868	0.0385	0.0513	0.0011	0.0123
		6	0.1058	0.1210	0.0412	0.0837	0.0443	0.0593	0.0002	0.0104
	ı	2	0.1305	0.1439	0.0323	0.0693	0.0418	0.0566	0.0009	0.0113
		4	0.0952	0.1152	0.0468	0.0983	0.0360	0.0498	0.0005	0.0115
	Avg		0.1128	0.1295	0.0395	0.0831	0.0389	0.0532	0.0007	0.0114
		30	0.0413	0.0573	0.0609	0.1271	0.0186	0.0320	0.0006	0.0152
	и	40	0.0462	0.0621	0.0487	0.1054	0.0191	0.0305	0.0003	0.0146
		50	0.0429	0.0564	0.0461	0.0998	0.0144	0.0250	0.0017	0.0156
	£	4	0.0494	0.0655	0.0445	0.1006	0.0205	0.0325	0.0008	0.0150
	J	6	0.0376	0.0517	0.0594	0.1210	0.0143	0.0258	0.0010	0.0153
М	m	8	0.0477	0.0630	0.0546	0.1166	0.0211	0.0339	0.0012	0.0161
		10	0.0424	0.0579	0.0473	0.1060	0.0141	0.0270	0.0012	0.0150
		12	0.0404	0.0549	0.0539	0.1097	0.0169	0.0266	0.0002	0.0144
	,	6	0.0421	0.0565	0.0483	0.1040	0.0196	0.0310	0.0006	0.0154
	ı	8	0.0449	0.0607	0.0555	0.1178	0.0152	0.0273	0.0012	0.0149
	Avg		0.0435	0.0586	0.0519	0.1108	0.0174	0.0292	0.0009	0.0152
	и	80	0.0275	0.0422	0.0635	0.1278	0.0065	0.0135	0.0004	0.0102
		100	0.0244	0.0366	0.0489	0.0949	0.0063	0.0120	0.0012	0.0109
		120	0.0281	0.0399	0.0603	0.0985	0.0111	0.0163	0.0015	0.0109
	f	8	0.0259	0.0394	0.0488	0.0949	0.0069	0.0132	0.0008	0.0105
		10	0.0274	0.0398	0.0663	0.1192	0.0090	0.0147	0.0013	0.0108
L	m	16	0.0254	0.0390	0.0612	0.1130	0.0071	0.0135	0.0019	0.0123
		18	0.0244	0.0368	0.0549	0.1025	0.0062	0.0118	0.0007	0.0095
		20	0.0302	0.0429	0.0566	0.1056	0.0106	0.0166	0.0005	0.0102
	I	10	0.0224	0.0343	0.0547	0.0985	0.0074	0.0141	0.0011	0.0102
		16	0.0310	0.0448	0.0604	0.1153	0.0086	0.0138	0.0010	0.0112
	Avg		0.0267	0.0396	0.0576	0 1070	0.0080	0.0140	0.0010	0.0107

We compare HCCE with $\text{HCCE}_1\text{-}\text{HCCE}_3$ based on the merit called relative percentage deviation (*RPD*), which is defined as follows:

$$RPD = (CA_{max} - CA_{max}^{best}) / CA_{max}^{best}$$
(10)

where CA_{max} is the system makespan of the current algorithm for a test instance, and CA_{max}^{best} is the lowest system makespan obtained by all algorithms for the same instance. To reduce randomness, after running each algorithm 10 times independently, we record the best *RPD* (*bRPD*) and average *RPD* (*aRPD*).



Fig. 10. Variation trend for compared algorithms.

Table IX RESULTS OF THE FREIDMAN TEST

	Instance		Chi-	D volue			
	group	HHMA	EDMBO	PBIGA	HCCE	Square	1 -value
	s	4	2.6	2.4	1	27.120	0.0
bRPD	М	3.1	3.9	2.0	1	28.920	0.0
	L	3	4	2	1	30.000	0.0
	S	4	3	2	1	30.000	0.0
aRPD	М	3	4	2	1	30.000	0.0
	L	4	3	2	1	30.000	0.0

Comparison results are summarized in Table VI by four levels of the number of jobs, factories, machines, and products. The best results for each category are marked in bold. The HCCE algorithm outperforms other variants in all categories. Fig. 9 plots the trend variations of *bRPD* and *aRPD* for HCCE₁–HCCE₃, and HCCE under each instance type. It is observed that: 1) HCCE₁ has the worst performance in all instances, 2) HCCE₂ shows slight improvement over HCCE₁, suggesting that the initialization strategy moderately enhances algorithm performance, 3) HCCE₃ significantly outperforms HCCE₂, 4) HCCE is better than HCCE₃, indicating the effectiveness of the local search method, and 5) the most substantial improvement is observed with the transition from HCCE₂ to HCCE₃. That means the mCCEA framework plays a vital role in enhancing HCCE performance.

To enhance the credibility of our results, a statistical analysis is performed to validate the comparison algorithms within a 95% confidence interval and to detect significant differences, utilizing the Friedman test [41]. The results of the Freidman test are summarized in Table VII by instance size, showing all *P*-values are 0 and the HCCE algorithm consistently achieved the lowest average rank, indicating the HCCE algorithm outperforms other variants in all instances.

D. Comparison with state-of-the-art algorithms

To evaluate the effectiveness of the HCCE algorithm, we compare it with three state-of-the-art algorithms: Hyper Heuristic-based Memetic Algorithm (HHMA) [7], Effective Discrete Monarch Butterfly Optimization (EDMBO) algorithm [8], and Population-Based Iterated Greedy Algorithm (PBIGA) [6]. These algorithms and HCCE are applied to the model and experimental settings in this article. The instances are run 10 times independently and the corresponding *bRPD* and *aRPD* are obtained.

Comparison results are summarized in Table VIII by three different instance types. The best results in each type are marked in bold. The HCCE algorithm outperforms other compared algorithms for all instance types. Fig. 10 illustrates the trend variations of *bRPD* and *aRPD* for all algorithms. It shows that: 1) in small-type instances, HCCE significantly outperforms the other algorithms, while HMMA exhibits the worst performance, and EDMBO and PBIGA show similar performance, 2) in other instance types, HCCE continues to perform best, but EDMBO is the worst, and the performance of PBIGA gradually approaches that of HCCE, particularly in large-type instances.

A statistical analysis is conducted to verify the comparison results with a 95% confidence interval, identifying significant differences among comparison algorithms. The Freidman test results are summarized in Table IX by instance size, showing all *P*-values are 0 and HCCE has the lowest average rank among all algorithms. Experimental results confirm that the HCCE algorithm outperforms the other comparison algorithms in all instances.

VI. CONCLUSION

Deadlock is a crucial problem for DAFSP with limited buffers, and to date no one has well resolved this issue. For the first time, this paper utilizes Petri nets to model deadlocks in DAFSP and proposes an amending method, namely IDAM, to ensure the feasibility or deadlock-freeness of the solutions for DAFSP. This method is integrated into the proposed HCCE algorithm, which has several special designs. First, an mCCEA framework that includes two subpopulations and EAR is proposed. To improve the quality and diversity of individuals, an ITM is used to exchange information among subpopulations, and two problem-specific operators are introduced for initialization and global search. Further, four local search operators are sequentially applied to each individual in the EAR to improve the searchability. Finally, the effectiveness of the components of HCCE is validated by comparing it with its three variants. The results demonstrate that HCCE outperforms the variants and the mCCEA framework is most key factor for enhancing the performance. Meanwhile, the experiment results show that HCCE

outperforms three state-of-the-art comparison algorithms, including HHMA [7], EDMBO [8], and PBIGA [6].

Future work should explore DAFSP with multiple assembly factories and dynamic scheduling scenarios, such as urgent product insertions. Additionally, more strategies such as reinforcement learning and acceleration method should be considered.

APPENDIX

A PN is a three-tuple N = (P, T, F), where *P* and *T* are finite and disjoint sets. $P = \{p_1, p_2, ..., p_r\}$ is the set of places, where *r* is the number of places. $T = \{t_1, t_2, ..., t_d\}$ is the set of transitions, where *d* is the number of transitions. $F \subseteq (P \times T) \cup (T \times P)$ is the set of directed arcs, where $P \times T$ denotes the directed arcs from *P* to *T* and $T \times P$ denotes the directed arcs from *T* to *P*. Places, transitions, and directed arcs constitute a directed graph, where $P \cup T$ is the set of vertices and *F* is the set of arcs of the directed graph. *P*, *T*, and *F* are represented by circles, rectangles, and arcs with arrows respectively.

Given a node $x \in P \cup T$, the preset of x is defined as ${}^{\bullet}x = \{y \in P \cup T \mid (y, x) \in F\}$, and the postset of x is defined as $x^{\bullet} = \{y \in P \cup T \mid (x, y) \in F\}$. These notations can be extended to a set, for example, let $X \in P \cup T$ and then ${}^{\bullet}X = \bigcup_{x \in X} {}^{\bullet}x$ and $X^{\bullet} = \bigcup_{x \in X} x^{\bullet}$.

A marking or state of *N* is a mapping $M : P \rightarrow \mathbb{Z}$, where $\mathbb{Z} = \{0,1,2,...\}$. Given a place $p \in P$ and a marking *M*, M(p) denotes the number of tokens in *p* at *M*. Let $S \subseteq P$ be a set of places; the sum of tokens in all places of *S* at *M* is denoted by M(S), i.e., $M(S) = \sum_{p \in S} M(p)$. A PN *N* with an initial marking M_0 is called a marked PN, denoted as (N, M_0) .

A transition $t \in T$ is enabled at a marking M, denoted by M[t >, if $\forall p \in {}^{\bullet}t$, M(p) > 0. An enabled transition t at M can result in a new reachable marking M', denoted by M [t > M', where M'(p) = M(p) - 1, $\forall p \in {}^{\bullet}t \setminus t^{\bullet}$, M'(p) = M(p) + 1, $\forall p \in t^{\bullet} \setminus {}^{\bullet}t$, otherwise, M'(p) = M(p). A sequence of transitions $\alpha =$ $t_1t_2...t_k$ is *feasible* from a marking M if there exists $M_i[t_i > M_{i+1}, i = 1, 2, ..., k$, where $M_1 = M$. We state that M_i is a reachable marking from M.

REFERENCES

- S. Hatami, R. Ruiz, and C. Andrés-Romano, "The Distributed Assembly Permutation Flowshop Scheduling Problem," Int. J. Prod. Res., vol. 51, no. 17, pp. 5292–5308, Sep. 2013, doi: 10.1080/00207543.2013.807955.
- [2] X. Wu, X. Liu, and N. Zhao, "An improved differential evolution algorithm for solving a distributed assembly flexible job shop scheduling problem," Memetic Comput., vol. 11, no. 4, pp. 335–355, Dec. 2019, doi: 10.1007/s12293-018-00278-7.
- [3] C. Lu, L. Gao, J. Yi, and X. Li, "Energy-Efficient Scheduling of Distributed Flow Shop With Heterogeneous Factories: A Real-World Case From Automobile Industry in China," IEEE Trans. Ind. Inform., vol. 17, no. 10, pp. 6687–6696, Oct. 2021, doi: 10.1109/TII.2020.3043734.
- [4] X. Li, X. Zhang, M. Yin, and J. Wang, "A genetic algorithm for the distributed assembly permutation flowshop scheduling problem," in 2015 IEEE Congress on Evolutionary Computation (CEC), Sendai, Japan: IEEE, May 2015, pp. 3096–3101. doi: 10.1109/CEC.2015.7257275.
- [5] S.-Y. Wang and L. Wang, "An Estimation of Distribution Algorithm-Based Memetic Algorithm for the Distributed Assembly Permutation Flow-Shop Scheduling Problem," IEEE Trans. Syst. Man Cybern. Syst., vol. 46, no. 1, pp. 139–149, Jan. 2016, doi: 10.1109/TSMC.2015.2416127.

- [6] F. Zhao, Z. Xu, L. Wang, N. Zhu, T. Xu, and J. Jonrinaldi, "A Population-Based Iterated Greedy Algorithm for Distributed Assembly No-Wait Flow-Shop Scheduling Problem," IEEE Trans. Ind. Inform., vol. 19, no. 5, pp. 6692–6705, May 2023, doi: 10.1109/TII.2022.3192881.
- [7] H.-B. Song, Y.-H. Yang, J. Lin, and J.-X. Ye, "An effective hyper heuristic-based memetic algorithm for the distributed assembly permutation flow-shop scheduling problem," Appl. Soft Comput., vol. 135, p. 110022, Mar. 2023, doi: 10.1016/j.asoc.2023.110022.
- [8] S. Du, W. Zhou, D. Wu, and M. Fei, "An effective discrete monarch butterfly optimization algorithm for distributed blocking flow shop scheduling with an assembly machine," Expert Syst. Appl., vol. 225, p. 120113, Sep. 2023, doi: 10.1016/j.eswa.2023.120113.
- [9] KeYi Xing, LiBin Han, MengChu Zhou, and Feng Wang, "Deadlock-Free Genetic Scheduling Algorithm for Automated Manufacturing Systems Based on Deadlock Control Policy," IEEE Trans. Syst. Man Cybern. Part B Cybern., vol. 42, no. 3, pp. 603–615, Jun. 2012, doi: 10.1109/TSMCB.2011.2170678.
- [10] F. Cao, Y. Feng, K. Xing, and G. Zhang, "Deadlock Control and Hybrid Social Spider Scheduling Algorithm for Two-stage Assembly Permutation Flowshop with Limited Buffers".
- [11] O. T. Baruwa, M. A. Piera, and A. Guasch, "Deadlock-Free Scheduling Method for Flexible Manufacturing Systems Based on Timed Colored Petri Nets and Anytime Heuristic Search," IEEE Trans. Syst. Man Cybern. Syst., vol. 45, no. 5, pp. 831–846, May 2015, doi: 10.1109/TSMC.2014.2376471.
- [12] JianChao Luo, KeYi Xing, MengChu Zhou, XiaoLing Li, and XinNian Wang, "Deadlock-Free Scheduling of Automated Manufacturing Systems Using Petri Nets and Hybrid Heuristic Search," IEEE Trans. Syst. Man Cybern. Syst., vol. 45, no. 3, pp. 530–541, Mar. 2015, doi: 10.1109/TSMC.2014.2351375.
- [13] B. Huang, R. Jiang, and G. Zhang, "Search strategy for scheduling flexible manufacturing systems simultaneously using admissible heuristic functions and nonadmissible heuristic functions," Comput. Ind. Eng., vol. 71, pp. 21–26, May 2014, doi: 10.1016/j.cie.2014.02.010.
- [14] G. M. Komaki, S. Sheikh, and B. Malakooti, "Flow shop scheduling problems with assembly operations: a review and new trends," Int. J. Prod. Res., vol. 57, no. 10, pp. 2926–2955, May 2019, doi: 10.1080/00207543.2018.1550269.
- [15] C.-Y. Lee, T. C. E. Cheng, and B. M. T. Lin, "Minimizing the Makespan in the 3-Machine Assembly-Type Flowshop Scheduling Problem," Manag. Sci., vol. 39, no. 5, pp. 616–625, May 1993, doi: 10.1287/mnsc.39.5.616.
- [16] A. Mozdgir, S. M. T. Fatemi Ghomi, F. Jolai, and J. Navaei, "Two-stage assembly flow-shop scheduling problem with non-identical assembly machines considering setup times," Int. J. Prod. Res., vol. 51, no. 12, pp. 3625–3642, Jun. 2013, doi: 10.1080/00207543.2012.756151.
- [17] Hatami S, Ruiz R, Andres-Romano C. The distributed assembly permutation flowshop scheduling problem[J]. International Journal of Production Research, 2013, 51(17): 5292-5308.
- [18] Y.-Y. Huang, Q.-K. Pan, J.-P. Huang, P. Suganthan, and L. Gao, "An improved iterated greedy algorithm for the distributed assembly permutation flowshop scheduling problem," Comput. Ind. Eng., vol. 152, p. 107021, Feb. 2021, doi: 10.1016/j.cie.2020.107021.
- [19] X. He, Q.-K. Pan, L. Gao, L. Wang, and P. N. Suganthan, "A Greedy Cooperative Co-Evolutionary Algorithm With Problem-Specific Knowledge for Multiobjective Flowshop Group Scheduling Problems," IEEE Trans. Evol. Comput., vol. 27, no. 3, pp. 430–444, Jun. 2023, doi: 10.1109/TEVC.2021.3115795.
- [20] J. Wang and L. Wang, "A cooperative memetic algorithm with feedback for the energy-aware distributed flow-shops with flexible assembly scheduling," Comput. Ind. Eng., vol. 168, p. 108126, Jun. 2022, doi: 10.1016/j.cie.2022.108126.
- [21] M. A. Potter and K. A. Jong, "A cooperative coevolutionary approach to function optimization," in Parallel Problem Solving from Nature — PPSN III, vol. 866, Y. Davidor, H.-P. Schwefel, and R. Männer, Eds., in Lecture Notes in Computer Science, vol. 866. , Berlin, Heidelberg: Springer Berlin Heidelberg, 1994, pp. 249–257. doi: 10.1007/3-540-58484-6_269.
- [22] C. H. Liang, C. Y. Chung, K. P. Wong, and X. Z. Duan, "Parallel Optimal Reactive Power Flow Based on Cooperative Co-Evolutionary Differential Evolution and Power System Decomposition," IEEE Trans. Power Syst., vol. 22, no. 1, pp. 249–257, Feb. 2007, doi: 10.1109/TPWRS.2006.887889.
- [23] Y. S. Son and R. Baldick, "Hybrid Coevolutionary Programming for Nash Equilibrium Search in Games With Local Optima," IEEE Trans. Evol. Comput., vol. 8, no. 4, pp. 305–315, Aug. 2004, doi: 10.1109/TEVC.2004.832862.
- [24] Y. Mei, X. Li, and X. Yao, "Cooperative Coevolution With Route Distance Grouping for Large-Scale Capacitated Arc Routing Problems," IEEE Trans. Evol. Comput., vol. 18, no. 3, pp. 435–449, Jun. 2014, doi: 10.1109/TEVC.2013.2281503.
- [25] F. B. De Oliveira, R. Enayatifar, H. J. Sadaei, F. G. Guimarães, and J.-Y. Potvin, "A cooperative coevolutionary algorithm for the Multi-Depot Vehicle

Routing Problem," Expert Syst. Appl., vol. 43, pp. 117–130, Jan. 2016, doi: 10.1016/j.eswa.2015.08.030.

- [26] Hong-fei Teng, Yu Chen, Wei Zeng, Yan-jun Shi, and Qing-hua Hu, "A Dual-System Variable-Grain Cooperative Coevolutionary Algorithm: Satellite-Module Layout Design," IEEE Trans. Evol. Comput., vol. 14, no. 3, pp. 438–455, Jun. 2010, doi: 10.1109/TEVC.2009.2033585.
- [27] M. Shi and S. Gao, "Reference sharing: a new collaboration model for cooperative coevolution," J. Heuristics, vol. 23, no. 1, pp. 1–30, Feb. 2017, doi: 10.1007/s10732-016-9322-9.
- [28] D. Lei, "Co-evolutionary genetic algorithm for fuzzy flexible job shop scheduling," Appl. Soft Comput., vol. 12, no. 8, pp. 2237–2245, Aug. 2012, doi: 10.1016/j.asoc.2012.03.025.
- [29] X.-L. Zheng and L. Wang, "A collaborative multiobjective fruit fly optimization algorithm for the resource constrained unrelated parallel machine green scheduling problem," IEEE Trans. Syst. Man Cybern. Syst., vol. 48, no. 5, pp. 790–800, 2016.
- [30] Q.-K. Pan, "An effective co-evolutionary artificial bee colony algorithm for steelmaking-continuous casting scheduling," Eur. J. Oper. Res., vol. 250, no. 3, pp. 702–714, May 2016, doi: 10.1016/j.ejor.2015.10.007.
- [31] N. Wu, M. Zhou, and G. Hu, "One-Step Look-Ahead Maximally Permissive Deadlock Control of AMS by Using Petri Nets," ACM Trans. Embed. Comput. Syst., vol. 12, no. 1, pp. 1–23, Jan. 2013, doi: 10.1145/2406336.2406346.
- [32] H. Liu, K. Xing, M. Zhou, L. Han, and F. Wang, "Transition Cover-Based Design of Petri Net Controllers for Automated Manufacturing Systems," IEEE Trans. Syst. Man Cybern. Syst., vol. 44, no. 2, pp. 196–208, Feb. 2014, doi: 10.1109/TSMC.2013.2238923.
- [33] Y. Wu, K. Xing, J. Luo, and Y. Feng, "Robust deadlock control for automated manufacturing systems with an unreliable resource," Inf. Sci., vol. 346–347, pp. 17–28, Jun. 2016, doi: 10.1016/j.ins.2016.01.049.
- [34] F. Wang, K.-Y. Xing, M.-C. Zhou, X.-P. Xu, and L.-B. Han, "A robust deadlock prevention control for automated manufacturing systems with unreliable resources," Inf. Sci., vol. 345, pp. 243–256, Jun. 2016, doi: 10.1016/j.ins.2016.01.057.
- [35] Y. Feng, K. Xing, Z. Gao, and Y. Wu, "Transition Cover-Based Robust Petri Net Controllers for Automated Manufacturing Systems With a Type of Unreliable Resources," IEEE Trans. Syst. Man Cybern. Syst., vol. 47, no. 11, pp. 3019–3029, Nov. 2017, doi: 10.1109/TSMC.2016.2558106.
- [36] Naiqi Wu, MengChu Zhou, and ZhiWu Li, "Resource-Oriented Petri Net for Deadlock Avoidance in Flexible Assembly Systems," IEEE Trans. Syst. Man Cybern. - Part Syst. Hum., vol. 38, no. 1, pp. 56–69, Jan. 2008, doi: 10.1109/TSMCA.2007.909542.
- [37] H. Hu and M. Zhou, "A Petri Net-Based Discrete-Event Control of Automated Manufacturing Systems With Assembly Operations," IEEE Trans. Control Syst. Technol., vol. 23, no. 2, pp. 513–524, Mar. 2015, doi: 10.1109/TCST.2014.2342664.
- [38] F. Charbonnier, H. Alla, and R. David, "The supervised control of discrete event dynamic systems: a new approach," in Proceedings of 1995 34th IEEE Conference on Decision and Control, New Orleans, LA, USA: IEEE, 1995, pp. 913–920. doi: 10.1109/CDC.1995.479101.
- [39] D. C. Montgomery, Design and analysis of experiments, 8. ed. Hoboken, NJ: Wiley, 2013.
- [40] Q.-K. Pan, L. Gao, and L. Wang, "An Effective Cooperative Co-Evolutionary Algorithm for Distributed Flowshop Group Scheduling Problems," IEEE Trans. Cybern., vol. 52, no. 7, pp. 5999–6012, Jul. 2022, doi: 10.1109/TCYB.2020.3041494.
- [41] S. García, D. Molina, M. Lozano, and F. Herrera, "A study on the use of non-parametric tests for analyzing the evolutionary algorithms' behaviour: a case study on the CEC'2005 Special Session on Real Parameter Optimization," J. Heuristics, vol. 15, no. 6, pp. 617–644, Dec. 2009, doi: 10.1007/s10732-008-9080-4.