# The Imitation Game According To Turing

Sharon Temtsin, The University of Canterbury, New Zealand, sharon.temstin@pg.canterbury.ac.nz, ORCID: 0000-0002-2819-6821

Diane Proudfoot, The University of Canterbury, New Zealand, ORCID: 0000-0002-9736-4489 David Kaber, Oregon State University, USA, ORCID: 0000-0003-3413-1503 Christoph Bartneck, The University of Canterbury, New Zealand, ORCID: 0000-0003-4566-4815

# Abstract

The current cycle of hype and anxiety concerning the benefits and risks to human society of Artificial Intelligence is fuelled, not only by the increasing use of generative AI and other AI tools by the general public, but also by claims made on behalf of such technology by popularizers and scientists. In particular, recent studies have claimed that Large Language Models (LLMs) can pass the Turing Test—a goal for AI since the 1950s—and therefore can "think". Large-scale impacts on society have been predicted as a result. Upon detailed examination, however, none of these studies has faithfully applied Turing's original instructions. Consequently, we conducted a rigorous Turing Test with GPT-4-Turbo that adhered closely to Turing's instructions for a three-player imitation game. We followed established scientific standards where Turing's instructions were ambiguous or missing. For example, we performed a Computer-Imitates-Human Game (CIHG) without constraining the time duration and conducted a Man-Imitates-Woman Game (MIWG) as a benchmark. All but one participant correctly identified the LLM, showing that one of today's most advanced LLMs is unable to pass a rigorous Turing Test. We conclude that recent extravagant claims for such models are unsupported, and do not warrant either optimism or concern about the social impact of thinking machines.

Keywords Turing Test, the imitation game, LLM, GPT-4, rigorous experiment, game duration constraint

**Acknowledgments** We would like to acknowledge Jack Copeland for his contribution to the origin, development and interpretation of this study.

**Statement and Declarations** The authors have no relevant financial or non-financial interests to disclose.

# 1 Introduction

In 1950, Alan Turing described an "imitation game' that, he proposed, provided a "criterion for 'thinking'": if an imaginable digital computer does well in this game, it can think (Turing 1950). Since Turing introduced the imitation game, there have been numerous efforts to build machines that could pass the test, as well as several Turing-style test methodologies. Interest in the imitation game has extended beyond the scientific community; events and reports of machines attempting to pass the test have captured the general public's interest. Recently, several studies have been released claiming to show that some Large Language Models (LLM) can pass Turing's test—and therefore are intelligent. This has been widely reported in news and magazine articles (CNN, 2014; Veselov, 2014; Boyle, 2016; Oremus, 2022; Oremus, 2023; Cuthbertson, 2023; Toews, 2024). However, although many researchers claim to have conducted Turing's Test, to the best of our knowledge, no

one thus far has rigorously followed his original instructions (Copeland, 2000). In this research, we focus on Turing's original work to conduct an experiment that rigorously follows his instructions for the imitation game.

### 1.1 Which imitation game?

Turing described three different versions of the imitation game (Copeland, 2000). He first introduced a restricted chess-playing version in his 1948 report (Turing, 1948). In 1950, Turing introduced a second version, the three-player imitation game (Turing, 1950). This is the game that is commonly referred to when talking about the Turing test. According to Turing, the three players include: A, B, and C. For clarity, we designate A and B as *Contestants* and C as an *Interrogator*. The Interrogator is situated in a separate room with no means of interaction with the Contestants except through textbased communication. During the game, the Interrogator addresses messages to Contestants, labeled X and Y, simultaneously. The objective of each role is as follows: A's goal is to convince the Interrogator to make an incorrect identification, while B aims to help the Interrogator make the correct identification. The game ends when the Interrogator decides on the identity of the Contestants: the Interrogator's objective is to match the Contestants to the labels X and Y: "at the end of the game he says either 'X is A and Y is B' or 'X is B and Y is A'." (Turing, 1950, p. 433).

Turing introduced the game using the example of a Man-Imitates-Woman Game (MIWG) (Turing, 1950). In this scenario, A is a man and B is a woman. The Interrogator can be of either sex. The man is labeled X and the woman is labeled Y, unbeknown to the Interrogator. The objective of the man is to convince the Interrogator that he is a woman, while the woman aims to assist the Interrogator in his/her task. The objective of the Interrogator is to correctly match the labels with the corresponding sexes, by stating either "X is a man and Y is a woman" (correct identification) or "X is a woman and Y is a man" (incorrect identification).

Extending the imitation game, Turing transformed the question "Can machines think?" into an unambiguous formulation consisting of two questions: "What will happen when a machine takes the part of A in this game?" and "Will the Interrogator decide wrongly as often when the game is played like this as he does when the game is played between a man and a woman?" (Turing, 1950, p. 434). These questions suggest playing a Machine-Imitates-Human Game (MIHG) using a machine in the role of A and a human in the role of B. The machine's success is determined by the results of both the MIHG and the MIWG (Turing, 1950). Here we follow the Copeland interpretation of the protocol for scoring the imitation game (Copeland, 2000, 2023). Each game ends with a score for the performance of the Interrogator. The machine passes the test if the performance of the Interrogator in the MIHG is no better than the performance of the Interrogator in the MIWG. Turing predicted that a digital computer could succeed in the game (Turing, 1950) at some point in the future. It is important to note that Turing changed from using the term "machine" to the term "digital computer". Today, we are unlikely to consider a machine that is not a computer for this task, and hence we will refer to the MIHG as the Computer-Imitates-Human Game (CIHG) (there is no requirement that the computer be digital).

In 1952, Turing proposed a third version of the test, a two-player imitation game (Turing et al., 1952). He suggested replacing the Interrogator with a jury. In the two-player imitation game, there is only a single Contestant, which is either a computer or a human. The jury communicates with the Contestant by text-based communication, aiming to determine the Contestant's identity. Unfortunately, Turing did not provide further details of this version of the test, leaving the benchmark for this game unidentified.

### 1.2 Context

Efforts to develop a text-based conversational agent began in 1966, starting with ELIZA, a program capable of conducting text-based psychotherapy-type conversations with humans (Weizenbaum, 1966). In 1972, Parry, a "paranoid" conversational agent, was the first chatbot to participate in a Turing-like test, where physicians were asked to determine whether a transcript was of a conversation with a human or with a chatbot—a task they found difficult (Colby et al., 1972).

In 1991, Hugh Loebner inspired conversational agent developers by establishing an annual competition known as the Loebner Prize Competition (Epstein, 1992). Initially, the contest adopted the format of the two-player imitation game. The competition awarded a bronze medal and a cash prize of a few thousand dollars for the best human imitation skills demonstrated by a computer. The jury was restricted to challenging the conversational partner solely on one topic, which was chosen by the partner. Moreover, each juror had to rank the respondents based on their human imitation skills instead of simply identifying them. A grand prize of \$100,000 was to be awarded for passing the two-player test (Epstein, 1992). Since 1994, in addition to the bronze medal, competitors have competed for silver and gold medals (Powers, 1998; Loebner, 2009). The silver medal carries a prize of \$25,000 and is awarded to a computer that manages to convince 50% of a jury that it was chatting with a human. The machine that can pass a version of the "Total Turing Test" (TTT) receives a gold medal and a prize of \$100,000. The organizers changed the requirement for winning the grand prize (gold medal) from passing the Turing Test to passing the TTT because some chatbots participating in the contest showed considerable progress in the game without demonstrating any actual capacity for thinking (Epstein, 1992; Powers, 1998). Moreover, the organizers believed that, to do well in the imitation game, a computer should have sensory experience of the world (Powers, 1998). The TTT requires robotic embodiment, on the assumption that a thinking machine cannot exist without a body (Harnad, 1989). The Truly Total Turing Test (TTTT) (Schweizer, 1998) extends the TTT with a further requirement: the machine must develop human capabilities autonomously. We are not aware of any current state-of-the-art technology that can pass any of these tests. Since 2004, the Loebner Prize competition has adopted the three-player imitation game format. The last competition was held in 2019 (Jones and Bergen, 2024a).

In 2014, the University of Reading organized a Turing Test competition to commemorate the 60<sup>th</sup> anniversary of Turing's death. In the end, the organizers announced that the "Eugene Goostman" chatbot finally "passed" the Turing Test (Warwick and Shah, 2015). This announcement was based on Turing's prediction that "in about fifty years time ... an average Interrogator will not have more than a 70% chance of making the correct identification after 5 minutes of questioning" (Turing, 1950, p. 442). However, this was a misinterpretation of Turing's prediction as the protocol for scoring the game (Copeland, 2014). The developers also modeled the chatbot based on a 13-year-old Ukrainian boy. This characterization may have elicited a greater tolerance among the jury regarding the chatbot's limited communication capabilities (Copeland, 2014).

The next notable attempt to conduct the two-player imitation game occurred online in October 2023 (Jones and Bergen, 2024a). This study compared the performance of different LLMs from a family of GPT algorithms, such as GPT-4 and GPT-3.5. The study explored different prompts and LLM parameters. The authors criticized the 70% benchmark, expressing doubts regarding Turing's prediction and his intention to utilize it as a standard benchmark. Nevertheless, they retained the 5-minute test duration. A single GPT-4 chatbot out of 12 chatbots (8 GPT-4 and 4 GPT-3.5) and ELIZA were correctly identified nearly 50% (50.3%) and 59% of the time, respectively. Based on the GPT-4 result, Jones and Bergen (2024a) suggested that "successful deception and impersonation of humans is already possible" (Jones and Bergen, 2024a, p. 9). ELIZA performed better than all 4 GPT-3.5 chatbots and 3 out of 8 GPT-4 chatbots. Various media platforms, such as The Independent

(Cuthbertson, 2023) and Yahoo (Evanson, 2023), highlighted the unsatisfactory performance of GPT-3.5.

Follow-up research was conducted in May 2024 (Jones and Bergen, 2024b). Three chatbots, GPT3.5, GPT-4 and ELIZA, participated in the 5-minute two-player imitation game. The GPT-driven chatbots shared the same prompt. The prompt was engineered as "the persona of a young person who was very concise, didn't take the game very seriously, used slang, and made occasional spelling errors" (Jones and Bergen, 2024b, p. 3). The authors adopted the 50% benchmark for the computer to pass the test. ELIZA, GPT-3.5, GPT-4, and the human Contestant were correctly identified 78%, 50%, 46%, and 67% of the time respectively. As a result, the authors claimed that GPT-4 passed the test. We notice a strong resemblance between the characteristics of the "Eugene Goostman" chatbot and the prompt for this experiment. This suggests that the reason for passing the test could be the social engineering of the prompt.

In summary, most implementations of the imitation game have not followed Turing's instructions rigorously. Often, these tests limited the game duration even though Turing did not specify this. The three-player imitation game, in which the Interrogator is conversing with both a computer and a human, appears to be the better option, since Turing provided a benchmark for it. In addition, it has been suggested that, while the two-player game could be biased by anthropomorphism, an Interrogator's anthropomorphizing is controlled in the three-player game (Proudfoot, 2011, 2013).

### 1.3 Our study

Our goal is to execute Turing's three-player imitation game as closely as possible to Turing's original description (Turing, 1950). We used a state-of-the-art LLM, GPT-4-Turbo, while acknowledging that rapid developments in the field will require regular re-testing in the future. We also aim to establish guidelines for executing Turing's instructions, to support future testing. This requires careful attention to ambiguous aspects of the imitation game. Can GPT-4-Turbo, one of today's most advanced LLMs, pass Turing's test? We wonder if the previous claims of LLMs' passing Turing's test can be substantiated when following Turing's original instructions.

Other research questions explored in this research relate to playing imitation games with the duration unconstrained: Is the CIHG significantly longer than the MIWG? Are the CIHG or MIWG significantly longer than 5 minutes? Does the game duration affect the correctness of identification?

We also note that, in addition to providing Turing's criterion of intelligence or thinking in machines, the imitation game may serve other purposes, such as a "red flag" that the machine is capable of deceiving people (Oremus, 2022). The game could be a valuable method for monitoring the progress of generative AI systems such as GPT-4 (Achiam et al., 2023), which is known for producing human-like text and responses (Jones and Bergen, 2024b). While such AI systems are commonly used for online applications, such as customer assistance (Soni, 2023), their deception capabilities could be utilized for malicious purposes, such as fraud and political influence (Park et al., 2024; Lebrun et al., 2024). Currently, there are no mature methods to evaluate AI capabilities to deceive (Park et al., 2024). Determining protocols for running the imitation game may therefore be of relevance in minimizing online deception, with the resulting damaging social impact.

#### 2 Methods

We preregistered the study on AsPredicted with reference number 148990.

#### 2.1 Participants

We recruited participants from the University of Canterbury community, with 210 people initially involved in 42 CIHG and 42 MIWG trials. After excluding 2 trials due to OpenAI server issues and 8 due to participants' misunderstandings of their roles, 185 participants remained across 37 trials of each type of game.

Following Turing's instructions, the Interrogator role was taken by a human (Turing, 1950). Here it is also important to note that in his 1952 paper, Turing specified that the Interrogator "should not be expert" about machines (Turing, 1952, p. 495). We infer that participants were required to have no prior knowledge of the imitation game or AI expertise. Consequently, people in the computer science and philosophy departments were excluded from participating in the CIHG.

For the CIHG, participants were between 18 and 52 years old, with an average age of 22 years. An imbalanced gender representation has the potential to provide a biased result regarding the Interrogator's performance, which is an essential component in both three-player imitation games. Consequently, trials were distributed as follows: 9 female Interrogators-female Contestants, 8 female-male, 8 male-female, 9 male-male, and 3 non-binary human Contestants. Regarding fields of study, 42% of the 74 participants studied Psychology, 32% studied Engineering, 10% studied Law, and the rest studied Arts, Management, Geography, and Speech and Language.

We applied a similar restriction on experts to both the CIHG and MIWG, disallowing psychology experts from participating in the MIWG. In the MIWG, non-binary Contestants were disallowed as Turing explicitly instructed that one Contestant must be a man, and another Contestant must be a woman. The average age of participants was 27 years, ranging from 18 to 52 years old. To maintain gender balance, we recruited 19 male and 18 female Interrogators. Regarding fields of study, 55% of the 111 participants studied computer and data science, 17% studied Engineering, and the rest studied Philosophy, Biology, Arts, Finance, Management, Geography, and Education.

#### 2.2 A computer player

We looked for reliable and affordable technology that could integrate smoothly with our imitation game application. In addition, the chatbot had to be able to hold an unconstrained conversation with the Interrogator. To identify chatbots capable of playing the imitation game, we asked each chatbot two questions: "Are you a bot?" and "Are you a man or a woman?". These questions were posed to chatbots already tuned for playing the imitation game. For example, the tuning could be done via prompts designed to simulate Turing's test. A positive response to the first question disqualified the system, as did any avoidance of specifying gender in response to the second. A short conversation consisting of ten exchanges was used as a sanity check to confirm the system's capability to imitate a human consistently throughout a conversation. We found the GPT-4 family of chatbots to be the most suitable for the computer role in the CIHG. The GPT-4-Turbo model was chosen due to a lower subscription cost compared to GPT-4. We used the OpenAI API to integrate the LLM into our application.

The GPT-4-Turbo parameters were set to a temperature of 0.75, a max\_tokens limit of 1000, and a frequency\_penalty of 0.0. The prompt was: "You are a human. You are not a bot or an assistant. Do not act like an assistant. You know only English. You are a student at the University of Canterbury in Christchurch, New Zealand. Choose unisex first and family names. You can choose other personality properties by yourself and stick to these choices. Please answer in formal language for up to two sentences. Please answer questions strictly and seldom end a response with a question of your own. Have a chit-chat conversation but do not show it explicitly. Make a time delay before an answer to simulate human thinking and typing time. Answer greetings with an answer style: 'Hi'. If you are asked about being a robot, deny that by using only one sentence. Do not stick to one topic

for too long. Frequently, make human-style grammatical errors and omit needless punctuation.". Regarding the instruction to use a unisex name, our aim was that the chatbot would respond as a generic human as long as possible.

### 2.3 Setup

Turing did not specify the total number of rooms to be used in the game or whether contestants can be in contact during the game. We utilized two separate rooms, one for Contestants and one for the Interrogator. The only connection between the rooms was computer-mediated communication through the university network.

Each participant was assigned an experiment station consisting of a chair, desk, monitor setup, and "play" setup (Fig. 1). The monitor setup included a laptop and a chess piece for interaction with the experimenter via Zoom. To avoid influencing the game, the experimenter waited outside the room, monitoring participants through pre-assigned Zoom breakout rooms with the experimenter's camera and audio disabled. Participant Zoom windows were minimized to prevent distraction. Participants were instructed not to operate the Zoom computer under any circumstances and were informed about the Zoom camera, which was used for live streaming only, and the intended purpose.

The game play setup served as a system to guide the participant through the experiment along with playing the imitation game. The human Contestant's play setup consisted of a single laptop, while the Interrogator's setup required two laptops for chatting with the two different Contestants (Fig. 1). We labeled the Interrogator's devices as "PlayerA" and "PlayerB" to correspond to the X and Y labels in Turing's game description.

Each participant interacted with three web applications through a play setup: a Qualtrics experiment guide, a warmup web application introducing the chat interface, and a game web application enabling communication between the Interrogator and the Contestant. The Interrogator simultaneously interacted with two computers (bottom image in Fig. 1), each hosting the warmup and game web applications. One computer also ran a third application that guided the Interrogator through the experiment. The warmup web application enabled interaction between each participant and a dummy chatbot, RandomBot.

The chat interface was identical for both the warmup and imitation game stages. The main chat screen (Fig. 2) included an "Add Message" text field, "System Notifications" field, "Send" button, and "Messages" window. The "Messages" window displays the chat history, and participants could scroll to view past messages. The Interrogator managed two interfaces simultaneously, with labels "PlayerA" and "PlayerB" appearing in the "Messages" window to distinguish between conversations. The labels corresponded to physical labels on the play setup computers. The non-interactive "System Notifications" field informed users of available actions.

To prevent interaction between human participants before meeting the experimenter, designated waiting areas were identified. Ideally, participants only saw each other for the first time during the debriefing stage.

The sticky notes on the Interrogator's desk (Fig. 3) served as a decision tool, allowing the Interrogator to state their identification decision. They placed each note on a different computer in the play setup.

The MIWG setup was as described above but added an extra participant, resulting in the Contestants' room being divided into two spaces with a temporary cubicle wall. Each Contestant was assigned a personal experiment station, and separate waiting areas were created to prevent interaction upon their arrival. The Contestants were prohibited from interacting until the debriefing stage. The identities on the Interrogator's sticky notes were also changed to "Man" and "Woman".

## 2.4 Procedure

The booking system lacked the means to prevent participants from scheduling the same timeslot as their friends. This scenario could introduce unfairness and bias to the game, if participants in the imitation game are already familiar with each other. Therefore, 10 minutes before the experiment, the experimenter moved between waiting areas to manage unexpected situations, such as participants who knew each other or met by chance on their way to the experiment. The experimenter welcomed each participant and inquired whether the participant knew the other persons scheduled for that trial. If confirmed, the trial was excluded from the experiment and the participants were encouraged to join a different trial. Otherwise, the experimenter asked them to wait until all players were present, and then escorted them to their designated stations in the experiment rooms. In fact, for only one trial did participants who came together complete the entire imitation game. Their acquaintance was discovered during the debriefing stage and the trial was excluded.

All participants provided written informed consent before taking part in the experiment. They were informed that they could withdraw at any time for any reason without negative consequences—for example, if they felt uncomfortable or offended during the unconstrained conversation. The experimenter introduced the monitor and play setup to each participant. Since the experimenter was not present during the imitation game, participants were instructed to summon the experimenter by moving the chess piece into the Zoom camera's view at a designated spot on the desk.

Next, the Qualtrics Guide was presented to explain the imitation game rules, the participant's role, and a brief experiment overview, without revealing the Turing Test's final goal. At the end of the introduction page, a validation question was posed ("What is your role in the game?") to ensure participants understood their role. If answered incorrectly, the experimenter clarified the mistake and helped the participant to identify the correct response. A correct answer advanced the participant to the warmup stage.

During the warmup stage, participants familiarized themselves with the chat interface. The Contestants practiced using the interface, while the Interrogator trained on simultaneous chatting across two computers, as well as the decision-making process. The warmup interface functioned similarly to the imitation game chat interface. The participants conversed with RandomBot, which used a small set of unrelated, repetitive responses ('How are you?'', "What is your favorite rugby team?'', and "Are you hungry?''). This method shortened the training time and minimized any learning effect on performance in the imitation game. The warmup stage had no time limits. For the Interrogator's training on the two-computer setup RandomBot's responses were: "I am glad.", "Go All Blacks!", and "I'm very hungry.".

Regarding the Interrogator's final decision, they were advised to end conversations by simply sending no more messages. They then placed the different sticky notes on the two computers, based on their decision. They subsequently summoned the experimenter and exited the room. Once an Interrogator closed the door to the room, their decision was considered final, concluding the game. This process was rehearsed at least twice or until the Interrogator felt comfortable with the game.

Each game started with the Interrogator sending a first message to a Contestant. Conversations followed a "ping-pong" style, where players had to wait for a response before sending another message. The game concluded when the Interrogator made their decision according to instructions. The experimenter then entered the room to record identifications (photograph the sticky notes), while the Interrogator waited outside. The players were subsequently asked to complete the demographic questionnaire and call for the experimenter when finished.

During the debriefing stage, participants gathered in the Contestants' room and met each other for the first time. The experimenter then revealed whether the Interrogator made the correct identification. Participants were informed of the purpose of the experiment, provided a brief introduction to Alan Turing and the imitation game, and participated in a brief discussion of their experiences. The experimenter also invited any questions. Benefits were distributed according to the study protocol with psychology students receiving credit points, while other participants received a 10 NZD voucher.

The CIHG and MIWG followed the same procedure, with the MIWG including an additional human Contestant instead of a computer. The female Contestant met the experimenter in the waiting area near the Contestants' room entrance and entered the experiment room first, as her station was furthest from the entrance. The male Contestant met the Interrogator in the farthest waiting area and entered only after the female Contestant was seated and had given consent. This ensured they did not see each other until the debriefing stage.



**Fig. 1** The CIHG setup. The figure is composed of three parts: top-left, top-right, and bottom. The top-left displays the logo of a chatbot, representing the computer Contestant interface. The top-right shows the human Contestant experiment setup, which consists of two laptops. One laptop, running a play setup, is placed on a desk with a chair for the participant. The other laptop, running a monitor setup, is situated on a separate desk to the left of the participant's workspace. The monitor laptop's camera captures the participant's area and a chess piece. The chess piece is positioned on the corner of the monitor desk between the two laptops. The bottom displays the Interrogator experiment setup. The setup includes a desk space with a chair for the participant. Additionally, it contains three laptops. The laptops on each side of the table constitute the play setup, where each device is used to participate in an unconstrained conversation. There is a chess piece in the center of the desk and the monitor laptop behind it, composing the monitor setup. Also, on the table, there are sticky notes of different colors showing the identities of the Contestants, "COMPUTER" and "HUMAN". The bottom is connected to each other via red and green opposing arrows, representing bidirectional communication flow during the unconstrained conversation sessions

ID Messages		
	Inte	rrogator: Hi
PlayerB: Hi		
	Interrogator: Ho	ow are you?
PlauerB: Good. uourself?		
Add Message		
Write a message here		
B <sub>k</sub> System Notifications		
You have received a response. Please continue conversation by sending your response.	e the	Send

**Fig. 2** A screenshot of the chat interface in the imitation game. The Interrogator chats with PlayerB. The interface includes a message box with a scroll bar to view conversation history. The user typing area is displayed below the chat messages. Below the typing area, there is a notifications window indicating the conversation status. The "Send" button next to the notification window was used to send messages

# 2.5 Measurement

# 2.5.1 Decision timestamp

With no time constraint, the game's duration was defined as the time from the first message received by a Contestant to the Interrogator's decision. We used the last recorded message time as a proxy for decision time.

# 2.5.2 Demographic questionnaire

Participants were asked three questions, including their gender, age, and field of study. The Interrogator had to answer one additional question: "Could you please justify and explain your decisions during the game?" They were permitted a small response window (100<sup>--</sup> words) for this purpose.

# 2.5.3 Data

Three types of data were collected for each imitation game: conversations (and times), demographic questionnaires, and a photo of the identification results. All data were saved on a university protected shared drive, accessible only to research members for safety and backup. During the game, recordings of both conversations were made and stored in a single file in chronological order.

# 2.6 Limitations

Despite the rigorous approach used in conducting this experimental study, there were some aspects of the game that we could not control. Many state-of-the-art LLMs are not available for local installation or they are very expensive to run. Other LLMs, such as models of the GPT family and "Claude", run on cloud technology and are available based on the "software as a service" method. Service providers can update the state of their models over time (Chen et al., 2024). This limitation did not affect the results of the current experiment, as the interrogator performance in the CIHG was

extremely high, but it should be taken into account when performing long-term experiments. Moreover, the robustness of the provider's server running the LLM may affect the game, with chatbot stopping responding during the trial leading to its exclusion.

We also cannot control human participant misunderstanding of their role in the imitation game. We used a validation question to ensure each player had understood. In addition, the Interrogator went through a decision-making process to reinforce their understanding of the Interrogator's role in the game. Despite these steps, some trials were excluded because at least one player misunderstood their role.

#### 3 Results

#### 3.1 The imitation game

Out of 37 Interrogators, 16 (43%) identified the man in MIWG, while 97% identified the computer in CIHG. We conducted a binary logistic regression with Game type (MIWG or CIHG) and Imitation Game Duration (IGD) as independent variables, and identification Correctness as the dependent variable. The model is shown in equation (1). Table 1 shows the estimation of the effects of Game and IGD on Correctness. The analyses highlighted a significant effect of the Game, while the IGD had no significant effect on Correctness.

$$Logit(Correctness) = \beta_0 + \beta_1 \times Game + \beta_2 \times IGD$$
(1)

An analysis of deviance, comparing a binary logistic regression model with and without IGD, did not show a significant difference (p=0.16) and AIC scores were similar (63.8). Consequently, a reduced model with Game as the sole independent variable was adopted. Table 2 presents the results, where the Game effect remained significant with an odds ratio (effect size) of 42.86.

The intercept for the reduced model is an indicator of whether the MIWG score significantly differs from a chance-level benchmark (50%), which represents random identification by an Interrogator. Results revealed the intercept does not significantly differ from zero (Table 2), which corresponds to 50% accuracy in identification.

### 3.2 Game duration comparison

The time duration histograms for both games, CIHG and MIWG, are presented in Fig. 3 and Fig. 4, respectively. The mean duration for CIHG was 821 seconds (~14 minutes) with a standard deviation of 569 seconds (~10 minutes), and a median of 717 seconds (~ 12 minutes). For MIWG, the mean duration was 1439 seconds (~24 minutes) with a standard deviation of 606 seconds (~10 minutes), and a median of 1453 seconds (~24 minutes).

The CIHG duration histogram (Fig. 3) shows a logarithmic distribution shape, supported by a Shapiro-Wilk normality test (p < 0.001). In contrast, the MIWG duration histogram (Fig. 4) exhibits a Gaussian shape with the mean and median around 24 minutes with an insignificant Shapiro-Wilk test (p=0.598). A one-sided Wilcoxon test confirmed that the MIWG duration was significantly longer than CIHG duration (p<0.001).

Given the frequent use of a 5-min duration in previous imitation game implementations (Jones and Bergen, 2024a,b; Warwick and Shah, 2015), we made a comparison with our observed CIHG duration distribution. A one-sided Wilcoxon test revealed the CIHG duration to be significantly longer, (p<0.001). Only 4 out of 74 trials in the current experiment had durations less than or equal to 5 min.

Effect	Estimat	Std. Error	z value	p value
Intercept	-1.409	0.904	-1.559	.119
Game	4.425	1.168	3.789	.000*
IGD	0.001	0.001	1.365	.172

Table 1. The estimation, standard error, z-value, and p-value of the intercept, Game and the Imitation Game Duration.

*Footnotes:* \* indicates that p-value is smaller than .05.

Table 2. The estimation, standard error, z-value, and p-value of the intercept and Game.

Effect	Estimat	Std. Error	z value	p value
Intercept	-0.272	0.332	-0.819	0.413
Game	3.856	1.067	3.614	.000*

*Footnotes:* \* indicates that p-value is smaller than .05.

### 4 Discussion

A comparison between the performance of CIHG and MIWG was conducted, with MIWG serving as a benchmark to determine whether GPT-4-Turbo passed Turing's test. Statistical analysis showed that the type of imitation game significantly affected correctness of an Interrogator's identification, revealing a significant difference in performance between the CIHG (97%) and MIWG (43%). The CIHG Interrogator performed better than the Interrogator in the MIWG, indicating that GPT-4-Turbo did not pass the test. This result contradicts several different claims that the GPT style model passes the test (Warwick and Shah, 2015; Celeste, 2023; Alisa, 2023; Jones and Bergen, 2024b). Moreover, the lack of a significant difference between the performance in the MIWG and the chance level benchmark (50% accuracy) suggests that this benchmark could replace the MIWG performance score (under present experiment conditions) as an indicator of whether the CIHG test has been passed. This approach would save substantial time and effort necessary to perform the MIWG.

Carrying out trials with an unconstrained duration revealed no effect of game duration on an Interrogator's correctness in identifying Contestants, That is, regardless of game type, duration does not predict identification correctness. Moreover, the MIWG duration was significantly longer than the CIHG duration, suggesting that the MIWG is more challenging for Interrogators. In addition, the CIHG's mean duration was about 14 minutes, with only 4 trials lasting 5 min or less. This implies that the 5 min constraint used in previous studies is not only a misinterpretation of Turing's work but also a constraint that substantially limits the interrogators' perceived need to further examine contestants.

Scheduling participants is a necessity, and hence limitations on the game duration are unavoidable. For instance, Prolific, a platform for conducting online studies, enforces study duration constraints. The constraint we recommend would apply to both CIHG and MIWG trials. Applying the two sigma rule to the MIWG duration distribution (Fig. 4), we suggest a constraint of 2651 seconds (~44 minutes). This constraint covers 97% of trials in the current study, making it suitable for representing an almost unconstrained duration. If a shorter constraint is necessary, duration could be reduced by 1 MIWG standard deviation. The new constraint value would then be 2045 seconds (~34 minutes) (Fig. 4), covering 89% (66 out-of 74) of the trials. The MIWG duration

could also be constrained further to its mean value of 1439 seconds ( $\sim$ 24 minutes). This limit would include 69% (51 out-of 74) of all trials, while around half of the MIWG trials (18 out-of 37) fall below this constraint along with 90% (33 out-of 37) of the CIHG trials. This constraint could serve as a lower bound for the MIWG duration.



**Fig. 3** The CIHG histogram. The x-axis represents the imitation game duration. The axis is divided into 300 sec (5 min) steps. The y-axis represents the frequency of each game duration. The red, blue and black dashed vertical lines represent mean (at 821 sec), median (at 717 sec), and mean +/- standard deviation (at 252 sec and 1390 sec) respectively



**Fig. 4** The MIWG histogram. The x-axis represents the imitation game duration. The axis is divided into 300 sec (5 min) steps. The y-axis represents the frequency of each game duration. The red, blue, black, and brown dashed vertical lines represent mean (at 1439 sec), median (at 1453 sec), mean +/- standard deviation (at 833 sec and 2045 sec), and mean +/- 2\*standard deviation (at 227 sec and 2651 sec) respectively

A duration constraint based on the CIHG duration distribution (Fig. 3) would be used if an experimenter decided to test a computer against the chance-level benchmark. The computer passes the test if the performance of the Interrogator in the CIHG is no better than 50% identification

accuracy. Since the distribution of time for this game is not normal, the two sigma rule is not applicable. The upper (time) bound can be set at 1390 seconds ( $\sim$ 23 minutes), covering 90% (33 out-of 37) of CIHG trials, defined by a single standard deviation. The CIHG mean, 821 seconds ( $\sim$ 14 minutes), could be a lower-bound, covering 59% (22 out-of 37) of CIHG trials. Using this benchmark would shorten a single trial by at least 9 minutes. However, the effect of using a different duration constraint for each game type would require further evaluation.

### 5 Conclusion and future work

To address the question "Can GPT-4-Turbo pass the Turing's test?", we conducted a rigorous Turing test based on Turing's guidelines. In the absence of explicit instructions from Turing, we had to fillin gaps with established research standards, such as the "warmup" method. While we cannot be completely certain that this complies with Turing's ideas, we are confident that it at least avoids several misinterpretations plaguing many previous studies and competitions. To the best of our knowledge, this is the closest that a three-player imitation game for the CIHG and the MIWG has ever come to Turing's original instructions. Our results show that GPT-4-Turbo did *not* pass the test, as previous studies claimed (Jones and Bergen, 2024b; Warwick and Shah, 2015).

In addition, the present study revealed that the MIWG lasts significantly longer than the CIHG, suggesting that the MIWG is more challenging for an Interrogator. This is consistent with the intention to make the test difficult for a machine to pass, as would be expected in a test that is, as Turing said, a "criterion for 'thinking'" in machines (Turing, 1950, p. 436). Moreover, the average CIHG duration exceeded 5 min, a duration limit applied in previous studies (Jones and Bergen, 2024a,b; Warwick and Shah, 2015; Shah and Warwick, 2010).

Results also showed no significant difference between the MIWG score and a chance-level benchmark, making the chance level an economical alternative. Although our results support using a chance-level benchmark, by comparison with (Jones and Bergen, 2024a,b), we reached a different conclusion by not limiting the game duration.

In case there is a need to constrain Turing's test, we found that 44 minutes can approximate an "unconstrained" duration. For a more practical constraint, we recommend a range of 24–34 minutes. Applying the chance-level benchmark adjusts the range to be between 14–23 minutes.

We hope that by outlining a rigorous method for Turing's test, the media will be better able to judge the merits of future studies and give credit only where it is due—and that this may have positive social impact, by reducing AI anxiety among the general public. We do not dare to estimate how long it will take for conversational agents to have any chance of passing the test. In 1952 Turing himself said that it would be "at least 100 years" before a machine would pass his test (Turing, 1952, p. 495).

### 6 Ethics statement

The University of Canterbury Human Research Ethics Committee (HREC 2023/98/LR-PS) approved this study.

#### References

Achiam J, Adler S, Agarwal S et al, (2023) Gpt-4 Technical Report. arXiv preprint arXiv:2303.08774. https://doi.org/10.48550/arXiv.2303.08774

Alisa J (2023) ChatGPT has passed the Turing test and if you're freaked out, you're not alone. TechRadar. https://www.techradar.com/opinion/chatgpt-has-passed-the-turing-test-and-if-youre-freaked-out-youre-not-alone

Boyle D (2016) What's the difference between robots and humans? it's my newt. https://www.theguardian.com/commentisfree/2016/sep/22/robots-pass-humans-turing-test-loebner-prize

Celeste B (2023) ChatGPT broke the Turing test — the race is on for new ways to assess AI. Nature. https://www.nature.com/articles/d41586-023-02361-7

Chen L, Zaharia M, Zou J (2024) How Is ChatGPT's Behavior Changing Over Time? Harvard Data Science Review. 6(2). https://doi.org/ 10.1162/99608f92.5317da47

CNN (2014) Passing the Turing test. https://edition.cnn.com/videos/bestoftv/2014/ 06/10/exp-ns-thompson-eugene-goostman.cnn

Colby KM, Hilf FD, Weber S, Kraemer HC (1972) Turing-like indistinguishability tests for the validation of a computer simulation of paranoid processes. Artificial Intelligence. 3:199–221. https://doi.org/10.1016/0004-3702(72)90049-5

Copeland J (2000) The Turing Test<sup>\*</sup>. *Minds and Machine*. 10(4):519–539. https://doi.org/10.1023/A:1011285919106

Copeland J (2014) Why Eugene Goostman Did Not Pass the Turing Test. https://www. huffingtonpost.co.uk/jack-copeland/turing-test-eugene-goostman\_b\_5478112.html

Copeland J (2023) Early AI in Britain: Turing et al. IEEE Annals of the History of Computing. 45(3): 19 – 31. https://doi.org/10.1109/MAHC.2023.33006

Cuthbertson A (2023) ChatGPT beaten by 1960s computer program in Turing test study. https://www.independent.co.uk/tech/chatgpt-turing-test-failed-ai-b2459930.html

Epstein R (1992) The Quest for the Thinking Computer. AI magazine. 13(2):81-81. https://doi.org/10.1609/aimag.v13i2.993

Evanson N (2023) A Chatbot from the 1960s has thoroughly beaten OpenAI's GPT-3.5 in a Turing test, because people thought it was just 'too bad' to be an actual AI. https://www.yahoo.com/tech/chatbot-1960s-thoroughly-beaten-openais-121521464.html

Harnad S (1989) Minds, Machines and Searle. Journal of Experimental & Theoretical Artificial Intelligence. 1(1):5–25. https://doi.org/10.1080/09528138908953691

Jones CR, Bergen BK (2024) Does GPT-4 pass the Turing test? Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers). pages 5183–5210. https://doi.org/10.18653/v1/2024.naaclong.290

Jones CR, Bergen BK (2024) People cannot distinguish GPT-4 from a human in a Turing test. arXiv preprint arXiv:2405.08007. https://doi.org/10.48550/arXiv.2405.08007

Lebrun B, Temtsin S, Vonasch A, Bartneck C (2024) Detecting the corruption of online questionnaires by artificial intelligence. Frontiers in Robotics and AI. 10:1277635. https://doi.org/10.3389/frobt.2023.1277635

Loebner H (2009) How to Hold a Turing Test Contest. In: Epstein R, Roberts G, Beber G (ed) Parsing the Turing test, page 173–179. Springer Dordrecht. http://doi.org/10.1007/978-1-4020-6710-5 12

Oremus W (2022) Google's AI passed a famous test — and showed how the test is broken. https://www.washingtonpost.com/technology/2022/06/17/google-ai-lamda-turing-test/

Oremus W (2023) What is the Turing Test that determines if computers can think? https://abcnews.go.com/US/turing-test-determines-computers/story?id=101486628

Park PS, Goldstein S, O'Gara A, Chen M, Hendrycks D (2024) AI deception: A survey of examples, risks, and potential solutions. Patterns. 5(5). https://doi.org/10.1016/j.patter2024.100988

Powers DMW (1998) The total Turing test and the Loebner prize. In New Methods in Language Processing and Computational Natural Language Learning. pages 279 – 280. Association for Computational Linguistics. https://doi.org/10.3115/1603899.1603947

Proudfoot D (2011) Anthropomorphism and AI: Turing's much misunderstood imitation game. Artificial Intelligence. 175(5-6):950–957. https://doi.org/10.1016/j.artint.2011.01.006

Proudfoot D (2013) Rethinking Turing's Test. The Journal of philosophy. 110(7):391–411. https://www.jstor.org/stable/43820781

Schweizer P (1998) The Truly Total Turing Test \*. Minds and Machines. 8(2):263–272. https://doi.org/10.1023/A:1008229619541

Shah H, Warwick K (2010) Hidden Interlocutor Misidentification in Practical Turing Tests. Minds and Machines. 20(3):441–454. https://doi.org/10.1007/s11023-010-9219-6

Soni V (2023) Large Language Models for Enhancing Customer Lifecycle Management. Journal of Empirical Social Science Studies. 7(1):67–89. https://publications.dlpress. org/index.php/jesss/article/view/58

Toews R (2025) 10 AI Predictions For 2025. https://www.forbes.com/sites/ robtoews/2024/12/22/10-ai-predictions-for-2025/

Turing A (1948) Intelligent Machinery. In: Reproduced in Copeland J (ed) The Essential Turing, National Physical Laboratory Report. pages 395–432. Clarendon Press

Turing A (1950) Computing Machinery and Intelligence. Mind. LIX(236):433–460. https://doi.org/ 10.1093/mind/LIX.236.433 Turing A, Braithwaite R, Jefferson G, Newman M (1952) Can Automatic Calculating Machines Be Said To Think? In: Reproduced in Copeland J (ed) The Essential Turing. BBC Broadcast. page 487–515. Clarendon Press

Veselov V (2014) Computer AI passes Turing test in 'world first'. https://www.bbc. com/news/technology-27762088

Warwick K, Shah H (2015) Can machines think? A Report on Turing Test Experiments at the Royal Society. Journal of Experimental & Theoretical Artificial Intelligence. 28(6):989–1007. https://doi.org/10.1080/0952813X.2015.1055826

Weizenbaum J (1966) Eliza—a computer program for the study of natural language communication between man and machine. Communications of the ACM. 9(1):36–45. https://doi.org/10.1145/365153.365168