Decoder-Only LLMs are Better Controllers for Diffusion Models

Ziyi Dong Sun Yat-sen University GuangZhou, China dongzy6@mail2.sysu.edu.cn

Pengxu Wei* Sun Yat-sen University, Pengcheng Laboratory GuangZhou, China, Shenzhen, China weipx3@mail.sysu.edu.cn

arXiv:2502.04412v1 [cs.CV] 6 Feb 2025

Dalle-3

Ours





Text Prompt: Envision a secluded beach at twilight, where the last golden rays of the sun cast a soft glow on the rugged cliffs. The sky is a tapestry of pink and purple, with the early evening stars just beginning to emerge. Waves gently lap against the shore, where a lone, ancient oak tree stands, its twisted roots spilling out onto the white sand. Nearby, a weathered boat rests in the sand, abandoned, its paint peeling and sails tattered. In the background, a lighthouse perches precariously at the cliff's edge, its beacon flickering to life as the light fades. The scene is one of serene isolation, untouched by the rush of modern life, a timeless testament to nature's quiet majesty.

Yao Xiao Sun Yat-sen University GuangZhou, China xiaoy99@mail2.sysu.edu.cn

Liang Lin Sun Yat-sen University, Pengcheng Laboratory GuangZhou, China, Shenzhen, China linliang@ieee.org

Dalle-3

Ours



Text Prompt: In the room, there is a transparent glass vase filled with beautiful pink roses. Three lemons are placed next to the vase on a table. The table is a next to a green couch. The couch is adorned with two pillows, One is pink and the other has a green and gray pattern. The floor is covered with wooden flooring. The walls are painted with latex paint. The ceiling is made of plaster and has a line-shaped design. The room has a large window, providing ample natural light.

Figure 1: Comparison of our LLMDiff with DALL-E 3 [2]. The pink texts represents the parts that our LLMDiff has understood but DALL-E 3 fails. Diffusion Models based on text encoders, *e.g.*, DALL-E 3, are prone to neglecting details when interpreting complex long texts, and have a limited understanding of entity relationships. Instead, our model employs a decoder-only LLM and can more effectively capture semantic and logical relationships between entities.

Abstract

Groundbreaking advancements in text-to-image generation have recently been achieved with the emergence of diffusion models. These models exhibit a remarkable ability to generate highly artistic and intricately detailed images based on textual prompts. However, obtaining desired generation outcomes often necessitates repetitive trials of manipulating text prompts just like casting spells on a magic mirror, and the reason behind that is the limited capability of semantic understanding inherent in current image generation models. Specifically, existing diffusion models encode the text prompt

MM '24, October 28-November 1, 2024, Melbourne, VIC, Australia

@ 2024 Copyright held by the owner/author(s). Publication rights licensed to ACM. ACM ISBN 979-8-4007-0686-8/24/10 https://doi.org/10.1145/3664647.3680725

input with a pre-trained encoder structure, which is usually trained on a limited number of image-caption pairs. The state-of-the-art large language models (LLMs) based on the decoder-only structure have shown a powerful semantic understanding capability as their architectures are more suitable for training on very large-scale unlabeled data. In this work, we propose to enhance text-to-image diffusion models by borrowing the strength of semantic understanding from large language models, and devise a simple vet effective adapter to allow the diffusion models to be compatible with the decoder-only structure. Meanwhile, we also provide a supporting theoretical analysis with various architectures (e.g., encoder-only, encoder-decoder, and decoder-only), and conduct extensive empirical evaluations to verify its effectiveness. The experimental results show that the enhanced models with our adapter module are superior to the stat-of-the-art models in terms of text-to-image generation quality and reliability.

CCS Concepts

• Computing methodologies → Computer Vision.

^{*}Corresponding Author.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

Keywords

Text-to-Image Generation, Diffusion Models

ACM Reference Format:

Ziyi Dong, Yao Xiao, Pengxu Wei*, and Liang Lin. 2024. Decoder-Only LLMs are Better Controllers for Diffusion Models. In *Proceedings of the 32nd ACM International Conference on Multimedia (MM '24), October 28-November 1, 2024, Melbourne, VIC, Australia.* ACM, New York, NY, USA, 9 pages. https://doi.org/10.1145/3664647.3680725

1 Introduction

Image generative models have progressed explosively in recent years, with the prevalence of Generative Adversarial Networks (GANs) and diffusion models. Text-to-image generation methods such as Stable Diffusion [24, 27], DALL-E 3 [2], and Imagen [28] are capable of synthesizing high-quality images by taking textual descriptions (prompts) as the input. One key step of these models is to understand the user intention and semantic meanings from the text prompts and encode them to text features for further driving image content generation with diffusion models. To this end, most of the existing methods adopt an encoder-based language model structure (e.g., CLIP [25] or T5 [26]), which were pre-trained on a limited number of image-caption pairs or texts pairs due to the expensive data annotation cost, resulted in the unsatisfying performance for the image generation quality and reliability. Thus, obtaining a user-desired image with these methods is not easy. In particular, to generate a complex and detail-rich image, repetitive trials of manipulating the text prompts are very common. For example, as shown in Fig. 1, the state-of-the-art DALL-E 3 fails to comprehend the entities and their relationships described in the complex prompts, resulting in numerous omissions.

On the other hand, we have also witnessed a very fast development of the Large Language Models (LLMs), *e.g.*, GPT-4 [22], PaLM [7] and Llama2 [14], which have shown very incredible power on semantic understanding, reasoning and naturally interacting with human. These LLMs mainly employ the decoder-only structure that can be trained on a massive scale of unlabeled textual data. Unfortunately, bridging the ability of LLMs with the current diffusion-based text-to-image generation framework is unexplored due to the incompatibility of these two model architectures. Some recent attempts have made to borrow the ability of LLMs for enhancing the text-to-image generation performance with the diffusion models [11, 18]. Their approaches proposed to enrich or rewrite the user text prompt through LLMs and still rely on the vanilla text encoders to guide the image generation performance.

To tackle this challenge, we propose a novel and general approach to upgrading various text-to-image diffusion models by borrowing the strength of semantic understanding from large language models (LLMs). In particular, we reveal that a Transformer-based language model (*e.g.* ChatGPT [22]) can be rephrased as the denoising steps in Denoising Diffusion Probabilistic Models (DDPMs) [12]. Viewing LLMs as diffusion models, we have further derived theoretical underpinnings for extracting text encodings from the blocks of LLMs. These findings drive us to attach a simple yet effective network module to the cross-attention part of the denoising U-Net. as shown in Fig. 2. This module enables us to effectively integrate

block-wise representations within the language model for generating the text encoding of the input text prompt, which can accurately capture the semantic meanings and contextual dependency among words due to the power of pre-trained LLMs. We name this module as LLMDiff-Adapter as it can be a plug-and-play component for connecting LLMs with various text-to-image diffusion models and gaining conspicuous improvement. As some examples shown in Fig. 1, the results generated by our model can better preserve the semantic meanings and user intent from the input prompts, *e.g.* well representing the entities and their relationships for image generation.

In the evaluation, we conduct a comparative analysis of different text-to-image models on the same benchmarks. We compared the performance of using our proposed LLMDiff-Adapter against other architectures, *e.g.* simply connecting the output of decoder-only LLMs or adopting encoder structure such as CLIP [25] and T5 [26] through linear layers to the diffusion models. The experimental results show that our model achieves superior performance among the competitions in several aspects, including the quality of generated image details, logical coherence, and comprehensive understanding of the text descriptions. The relevant quantitative results are also presented to underscore the effectiveness of our approach in solving the limitations of current diffusion-based text-to-image generation methods.

2 Related Works

2.1 Text-to-Image Diffusion Models

Recently, diffusion-based image generation models have achieved remarkable success. These models learn to iteratively denoise a noisy image and generate the image progressively [12]. Compared to GAN-based methods, diffusion models are more stable in training and able to generate more diverse images. With the advent of diffusion models incorporating guidance mechanisms [13, 19], there has been a notable advancement in the performance of diffusion models. For the first time, diffusion models beat GANs in conditional generation tasks. Ever since, the focus of research on text-to-image synthesis has gradually shifted from GAN to Diffusion [5, 15, 16, 21]. Some large-scale text-to-image models [2, 10, 27, 31] have achieved highly accurate and fine-grained controllable semantic generation. The recently proposed latent diffusion model (LDM) [27] unprecedentedly makes high-resolution and high-quality text-to-image models become a reality. Based on LDM, DALL-E 3 [2] has ushered the text-to-image models into unprecedented levels, leveraging powerful text encoders and high-quality data.

2.2 Large Language Models

In recent years, large-scale language models with billions of parameters have demonstrated remarkable performance across various natural language understanding and generation tasks. The dominant form of language models shifted from BERT-like models [9, 20] that focus on language understanding to the currently prevalent generative language models with decoder-only architectures [7, 14, 17, 22]. These decoder-only models have successfully unified a wide spectrum of tasks, showing commendable proficiency in dialogue interactions. Even in language comprehension tasks, [4, 8] also shows that CLIP and BERT style text encoders perform



Figure 2: Comparison with other neural network structures employed for computing text encoding in diffusion models. Our proposed LLMDiff, which leverages a decoder-only structure by casting the transformer-based language model as a diffusion model, can predict the text encodings for text-to-image generation by integrating layer-wise representations in the language model. Intuitively, compared with other structures (*e.g.* encoder-decoder) our LLMDiff is more powerful in exploring the semantic meanings and dependency among words from the input text prompt. More details and theoretical derivations are provided in Sec. 3.4.

worse than decoder-only LLMs. Moreover, recent models exhibit the ability of in-context learning [3], enabling them to adaptively leverage contextual information to accomplish downstream tasks.

2.3 LLMs for Text-to-Image Generation

Existing text-to-image diffusion models are primarily based on encoder-structured text models like CLIP and T5. However, there are ongoing efforts of works that seek to explore the potential for transposing the wealth of knowledge inherent in Large Language Models (LLMs) into existing diffusion frameworks. Certain research endeavors, such as [11, 18], have attempted to utilize LLMs to predict the layout of objects, thereby enhancing the logical coherence and overall quality of the images produced by diffusion models. This is achieved by employing LLMs to rewrite the prompts, ensuring a better alignment between the generated images and the input text. Another approach [1] attempts to use LLMs to help users construct better prompts, leveraging the capabilities of LLMs to generate superior images.

While these pioneering efforts are indeed instrumental in integrating the knowledge of LLMs into diffusion models, they predominantly employ indirect methods to bridge the gap between them, and thus, are inherently constrained by the limitations of the inefficient text encoder. In contrast, we propose a novel method that directly integrates the output of the LLM into the existing diffusion model. By completely discarding the text encoder, we aim to liberate the text-to-image diffusion models from the bottleneck of language comprehensibility, which may significantly enhance their performance in controllable image generation.

3 A New Controller for Text-to-Image Generation

In this section, we elucidate the theoretical analysis for extracting text encodings from decoder-only LLMs. Initially, we reveal that Transformer-based LLMs can be rephrased as diffusion models. Within this view, we pinpoint a specific timestep in the decoder component of an encoder-decoder LLM to deduce the encoder's text encoding distribution from its input and output. This deduction is then extended to decoder-only models, leading to the conclusion that text encodings can be estimated from the outputs generated for sentences and words at each timestep.

3.1 Text-to-Image Diffusion Models

Text-to-image diffusion models typically employ an encoder to encode textual inputs *x* with *d*-1 tokens as control conditions $c_{<d}$. Sequentially, those text encodings $c_{<d}$ are decoded for *image generation* through the diffusion model, *i.e.*, $p(z_{t-1}|z_t, c_{<d})$, where z_t is the latent at timestep *t*, or for *text generation* via a text decoder, *i.e.*, $p(x_d|c_{<d})$, where x_d is the *d*-th predicted token.

Typically, the text encoder utilized by diffusion models is derived from pre-trained models such as encoder-only or encoder-decoder LLMs. However, despite their impressive generative performance, decoder-only LLMs are not applicable to text-to-image generation. This is because these models directly generate tokens, making it infeasible to get text features c directly.

3.2 LLMs as Diffusion Models

We revisit the transformer-based LLMs from a probabilistic perspective, to help to derive the formal modeling of text encodings for text-to-image generation. Considering that LLMs in a transformer architecture have a sequence of transformer blocks with the same structure, it is intuitive to model the forward process in a diffusionlike manner. Take an encoder-only LLM, CLIP, for example. Each input token is first fed into an embedding layer. For similarity, the output of the embedding layer for the *d*-th token is taken as the input, denoted as x_d^T . Then, it goes through *T* transformer blocks that perform the causal attention masks in self-attention, which can be represented as $p_{\theta t} (x_d^{t-1} | x_d^t, x_{<d}^t)$ for the *t*-th block parameterized θ_t . This process is akin to the denoising process of DDPM with conditioning. So, the transformer-based LLMs can be viewed as diffusion models. Thus, we can leverage the dynamical properties and theoretical frameworks of diffusion models to analyze various structures of LLMs with a causal mask.

Moreover, the prediction of the model can be formulated as:

$$p_{\theta}(c_d|x_{\leq d}) = p(x_d^T) \prod_{t=1}^{I} p_{\theta^t}(x_d^{t-1}|x_d^t, x_{< d}^t)$$
(1)

3.3 Text Encodings from Encoder-Decoder LLMs

For an encoder-decoder LLM, the encoder model processes contextual text, encoding it into a feature representation, *i.e.*, text encodings $c_{<d}$. Subsequently, the decoder model utilizes these text features to generate words with $p_{\theta^t}(x_d^{t-1}|x_d^t, c_{<d})$. Thus, each block in the decoder utilizes the same condition $c_{<d}$. Using the input x_d^t and output x_d^{t-1} of any block, the encoding $c_{<d}$ from the encoder is estimated through Bayes' theorem:

$$p(c_{(2)$$

3.4 Text Encodings from Decoder-only LLMs

For a decoder-only LLM, it is not directly available for textual features, *i.e.*, text encodings c in encoder-decoder LLMs. Functioning as a generative model, it can be conceptualized as predicting the next token based on conditions from the preceding tokens. Those contextual conditions are changing, not shared like encoder-decoder LLMs. Namely, when predicting the d-th word, the preceding d-1 words collectively serve as its contextual condition,

$$p_{\theta}(x_d | x_{< d}) = p(x_d^T) \prod_{t=1}^T p_{\theta^t}(x_d^{t-1} | x_d^t, x_{< d}^t)$$
(3)

Accordingly, given the input x_d^t and output x_d^{t-1} of transformer blocks, the estimation of $p(x_{< d}^t | x_d^{t-1}, x_d^t)$ can be derived as follows,

$$p_{\theta^{t}}(x_{

$$= \frac{p(x_{d}^{t-1}|x_{\leq d}^{t})p(x_{d}^{t}|x_{

$$\propto \underbrace{p(x_{d}^{t-1}|x_{d}^{t}, x_{$$$$$$

block prediction of sentence block prediction of single words

where $p(x_d^{t-1}|x_d^t, x_{d}^t)$ is the generative LLM's prediction for x_d^t . Most existing LLMs employ a causal mask as the attention mask. Consequently, $p(x_d^{t-1}|x_d^t)$ can be obtained by feeding x_d^t alone into the LLM, *i.e.*, $p(x_d^{t-1}|x_d^t) = p(x_d^{t-1}|x_d^t, \emptyset)$. However, it is still intractable to compute the text encodings c

However, it is still intractable to compute the text encodings c from decoder-only LLMs. Notably, $x_{<d}^t$ is taken as the condition of the next token prediction, playing the similar role of $c_{<d}$ in encoder-decoder LLMs. Thus, there exists a $c_{<d}$ for decoder-only LLMs, which is the unbiased estimator of $x_{<d}$. Given that the decoder-only LLMs, there exists a be viewed as diffusion model, we can estimate the score function of $p(c_{<d}|x_d^{t-1}, x_d^t)$ through $p_{\theta t}(x_{<d}^t|x_d^{t-1}, x_d^t)$, thereby obtaining the text encoding $c_{<d}$. In accordance with Eqn. (4), the score

Ziyi Dong, Yao Xi	ao, Pengxu	Wei, &	Liang	Lin
-------------------	------------	--------	-------	-----

Algorithm 1: Text encoding from decoder-only LLMs				
Input: Text input \boldsymbol{x} with length D , embedding layer ω .				
1 $m{c} = \omega(m{x}) \sim p(m{c}^T)$; // Initial the text diffusion process.				
// denoise steps.				
² for $t = T$ to 1 do				
$\mathbf{s} \qquad \mathbf{for} \ d = 1 \ \mathbf{to} \ D \ \mathbf{do}$				
// estimate $\nabla_x \log p_{\theta^t}(x_d^{t-1} x_d^t, c_{< d})$.				
4 $s_{sentence} \leftarrow g(t)S_{\theta t}(x_d^{t-1}, x_d^t, x_{\leq d}^t);$				
// estimate $\nabla \log p_{\theta^t}(x_d^{t-1} x_d^t)$.				
$ s_{word} \leftarrow g(t)S_{\theta^t}(x_d^{t-1}, x_d^t); $				
$ \nabla \log p_{\theta^t}(c_{< d} x_d^t, x_d^{t-1}) \leftarrow s_{sentence} - s_{word}; $				
7 end				
8 $\epsilon_t \sim \mathcal{N}(0,1);$				
9 $c \leftarrow c + \nabla \log p_{\theta^t}(c_{< d} x_d^t, x_d^{t-1}) + \sqrt{2h(t)} \epsilon_t;$				
10 end				
Output: c				

function of $p_{\theta t}(c_{< d} | x_d^{t-1}, x_d^t)$ can be approximated as follows:

$$\begin{aligned} \nabla_{c} \log p_{\theta^{t}}(c_{

$$(5)$$$$

where g(t) is a scalar function that is dependent on the time step t. Furthermore, from Eqn. (1), by modeling an LLM as a diffusion process, the score function for $p(c_{< d}|x)$ can be approximated as:

$$\begin{aligned} \nabla_{c} \log p_{\theta^{t}}(c_{$$

Taking into account the stochastic nature of generative language models during sampling, we can use this score function to perform Langevin dynamics sampling to obtain the final text encoding for image generation:

$$c_{d}^{t-1} = c_{d}^{t} + \nabla_c \log p_{\theta t} (c_{$$

where h(t) is a learnable function, and $\epsilon_t \sim \mathcal{N}(0, I)$.

4 LLMDiff Adapter

4.1 Decoder-only LLMs as Diffusion Controller

As discussed in Sec. 3, we can derive text encodings suitable for controlling diffusion image generation models from decoder-only LLMs utilizing Langevin dynamics:

$$c_{(8)$$

Leveraging the residual structure of existing transformer blocks and by combining Eqns. (5) and (6), we can transform these transformer blocks to derive the model for predicting scores: $S_{\theta'}(x_d^{t-1}, x_{\leq d}^t) \approx$ $\nabla_x \log p(x_d^{t-1}|x_d^t, x_{< d}^t), S_{\theta'}(x_d^{t-1}, x_d^t) \approx \nabla_x \log p(x_d^{t-1}|x_d^t)$. Accordingly, the estimation of *c* is implemented by Algorithm 1. Based on this text encoding, we can construct an adapter to integrate decoderonly LLMs into existing diffusion models. In contrast to the primary practice of merely employing LLMs for text optimization and encoding optimized texts via a text encoder with inherent performance

MM '24, October 28-November 1, 2024, Melbourne, VIC, Australia



Figure 3: Our LLMDiff-Adapter framework, wherein the parameters of both the LLM and the diffusion U-Net (including the original cross-attention module) are frozen during training. The newly added cross-attention module employs two adaptive-weight parameters to incorporate with the original one, which is dynamically adjusted during training.

limitations, text encodings derived from LLMs to control the generation of diffusion models can be a superior alternative for diffusion model training from scratch or adaption in a pre-trained diffusion model. In the following, we will elaborate an effective adaptor in a pre-trained diffusion model for image generation.

4.2 LLMDiff Adapter: Bridging Decoder-Only LLMs and Pre-trained Diffusion Models

To leverage the pre-trained knowledge of existing diffusion models more effectively, we propose an LLMDiff Adapter incorporating text encoding from generative decoder-only LLMs into a pre-trained text-to-image diffusion model, as illustrated in Fig. 3. The original cross-attention module is aligned with the preceding text encoder, and it is what actually imposes a bottleneck on the comprehension of user prompts. However, it still holds a wealth of knowledge and insights for text-to-image generation, learned during the pretraining phase. Therefore, we keep the original cross-attention module intact and align it with the encoding derived from LLMs through linear layers. This enables effective utilization of the knowledge of large-scale pre-trained models, preserving basic generation capabilities.

Simultaneously, an additional cross-attention module is introduced to learn how to better generate images based on the text encoding derived from LLMs. The outputs of these two modules are combined through a set of learnable weight factors: a_1 , a_2 , b_1 , and b_2 , and the overall computation can be formulated as follows:

$$f = attn(\hat{\tau}_q(q), \hat{\tau}_k(\phi(\mathbf{c})), \hat{\tau}_v(\phi(\mathbf{c})))a_1e^{b_1} + attn(\tau_q(q), \tau_k(\mathbf{c}), \tau_v(\mathbf{c}))a_2e^{b_2},$$
(9)

where $\hat{\tau}$ is the linear layer of the original cross-attention module, τ is that in additional cross-attention module, and ϕ is the linear layer to align the LLMs with the original cross-attention module. For training stability, the initial values of a_1 and b_1 are set to 1 and 0, respectively, while a_2 and b_2 start at 0.

During the model learning, the newly added cross-attention module gradually refines the outputs, effectively adapting the knowledge of generative LLMs to the diffusion model. Our Adapter is trained with the MSE loss for diffusion models:

$$\mathcal{L} = \|\epsilon_{\theta}(z_t, c) - \epsilon\|^2, \tag{10}$$

where ϵ_{θ} is the diffusion U-Net, z_t is the latent feature map at timestep t, and $\epsilon \sim \mathcal{N}(0, I)$.

5 Experiments

5.1 Experimental Settings

Dataset. We utilized a subset of data collected from GRIT [23] and midjourney-v5-202304-clean [30]. Simple filtering was applied to the image resolution and texts, with the total number of data used for training approximating 1 million. To ensure a fair comparison, our model was trained alongside existing text-encoder-based models (including SD1.5 [27], SDXL [24], and T5-based SD1.5 models) using the same dataset and similar Adapters.

Base models. Our experiments are conducted based on pre-trained Stable Diffusion (SD) 1.5 model [27], utilizing two Large Language Models (LLMs), Phi1.5 [17] and Vicuna1.5-7B [6]. The number of parameters of Phi1.5 is close to that of the text encoders of CLIP and T5, thereby ensuring a fair comparison of the performance.

Implementation details. Our LLMDiff Adapter has approximately 45M parameters. We utilize AdamW optimizer with a learning rate of 1e-5 for the Adapter training. The size of input images is 512x512, in conjunction with the Aspect Ratio Bucket, which automatically groups images of different aspect ratios into different batches and seeks to avoid image cropping as much as possible. The weighted coefficients of the two cross attentions are initialized as follows: $a_1 = 1, b_1 = 0, a_2 = 0.1, b_2 = 0$. LLM itself does not require fine-tuning and we use a batch size of 256 for training on 8 NVIDIA A100 GPUs with 40GB VRAM.

Metrics. We assess the models from three dimensions. (1) For *controllability*, we evaluate the degree of matching between the generated images and the given text via the CLIP Score. However, since the SD model itself is based on CLIP, for fairness, we employ the SigLIP-L-384 [32] model to calculate the SigLIP Score:

 $Score(I, L) = 100 \times sigmoid(\alpha cos(f_{img}(I), f_{text}(L)) + \beta),$ (11)

where *I* is the input image, *L* is the input text, f_{img} is the image encoder, and f_{text} is the text encoder. α and β are the learned

Table 1: Quantitative analysis of our LLMDiff Adapter compared with existing methods.

Method	SigLIP Score \uparrow	Quality↑	Complexity↑	Beauty↑
SD1.5	4.6	74.1	23.2	88.9
SDXL	6.2	76.5	23.9	90.6
SD1.5 +(T5-XL)	7.4	74.9	22.5	90.9
Ours (phi1.5)	5.8	76.3	24.9	91.0
Ours (Vicuna-7B)	8.5	78.6	24.7	92.9

parameters from SigLIP model. (2) For *image quality*, we utilize CLIP-IQA [29] to evaluate the quality of the images from the aspects of image details and overall image quality. (3) As for the *logicality* of images, we employ the user study. For each model, we construct 15 prompts from multiple perspectives, including action logic, color matching, and the number of objects, etc. Each prompt generates 10 images, and human evaluators judge whether the core logic of these prompts is reflected in the images.

5.2 Quantitative Analysis

For a quantitative analysis of our method, we use the SigLIP Score to evaluate how well the generated images match the given text. Furthermore, we use CLIP-IQA to analyze the image's Quality, Complexity, and Beauty, thereby assessing whether the overall quality of the generated image is better.

In Tab. 1, our proposed method based on Vicuna-7B achieved a SigLIP Score of 8.5, which is 31% higher than the best existing SDXL model of 6.2. Meanwhile, the model based on phi-1.5 has a 26% improvement compared to the SD1.5 used as our baseline, approaching the level of SDXL. These results suggest that our LLMDiff Adapter can effectively combine the existing LLM and Diffusion models. Allowing the powerful text comprehension capabilities of the LLM to be utilized in the text-to-image diffusion model, thereby generating images with sufficient controllability. The more powerful the LLM, the stronger the controllability it brings.

Regarding the quality of the generated images in Tab. 1, our method surpasses existing methods in multiple aspects such as overall image quality, complexity of details, and aesthetic appeal of the image. The Quality score reached 78.6, improving by 2.7% compared to the currently best SDXL model. In terms of the complexity of the generated image features, the Complexity score reached 24.7, with an improvement of 3.3% compared to SDXL. The aesthetic appeal score of the image also reached 92.9, surpassing the existing SDXL by 2.5%. By controlling the generation process of the Diffusion model through the LLM model, we can not only improve the alignment between the image and the text, but also enhance the quality, detail, and aesthetic appeal of the generated images.

5.3 Qualitative Evaluation

Our model is evaluated qualitatively on its ability to understand actions, entity relationships, spatial structures, and complex descriptions. As shown in Fig. 4, our approach, powered by the robust semantic comprehension of LLMs, delivers more precise and controllable outcomes in depicting multiple entities and their interrelationships. For instance, in the first column of Fig. 4, our method Ziyi Dong, Yao Xiao, Pengxu Wei, & Liang Lin

accurately generates an image of a white rabbit seated on a wooden bench with two blue cats next to it, showcasing a refined understanding of entity quantity and color correspondence. It also correctly comprehend the action where only one cat looks at the rabbit, unlike existing methods that struggle with such inter-entity actions.

The third column highlights our method's ability in accurately generating distinct entities from descriptions without feature confusion. Existing models often focus on keywords and miss the holistic context, failing with overlapping keywords. For instance, with entities like a robot, a robot with a rat head, and a rat, keyword-based approach risks overlooking some entities due to overlaps. Models leveraging text encoders like CLIP or T5 cannot accurately interpret these relationships, resulting in imprecise image generation.

For complex scenes derived from extensive text descriptions, prevailing methods often misinterpret long texts, leading to incomplete scene generation. Our method integrates LLMs into the diffusion model, exploiting LLMs' powerful long-text comprehension capabilities to precisely delineate each scene part and inter-entity relationships. In the last column of Fig. 4, our method precisely renders a complex indoor scene described in extensive text, including the pink rose, three lemons, a sofa with pillows, and interior decoration. In contrast, existing methods typically produce simpler, less detailed scenes.

Moreover, our method excels in generating meaningful detailed features. Based on the SD1.5 model, our LLMDiff Adapter, combined with LLMs' powerful comprehension capabilities, significantly enhances the texture and detail quality of generated images. While SD1.5 often produces fragmented and indistinct features, our approach generates coherent and meaningful local features, especially in complex scenes described by long texts.

5.4 Analysis of Reasoning Ability

Existing text-to-image generation models tend to produce visually highly similar image details with the given texts. They struggle to generate image details that texts do not explicitly indicate but are necessary for commonsense or reasoning. In our experiments, this is also taken into consideration for model evaluation, in Fig. 5.

In the first two columns of Fig. 5, our model can accurately understand the number of entities in the description, which is a great challenge for current diffusion models based on text encoders. With the help of LLM's understanding of quantifiers and entity relationships, we can enable the diffusion model to accurately generate the number of entities given in the description text.

The third column of Fig. 5 illustrates our model's advanced reasoning abilities. Tasked with generating an image from the perspective of a falling cat, our model accurately depicts the scene as seen by the cat, rather than mistakenly showing a falling cat, as would be typical of models focusing on keywords only.

The fourth column illustrates how our model effectively leverages the LLM's capability to infer the physical laws. The task is to generate an image of a glass ball falling from a great height. Our model accurately generates an image of a glass ball shattering upon impact, consistent with real-world physics, unlike existing models that depict an intact glass ball. These are what text-encoder-based diffusion models fail to comprehend, as they lack this reasoning ability. Decoder-Only LLMs are Better Controllers for Diffusion Models

MM '24, October 28-November 1, 2024, Melbourne, VIC, Australia



Figure 4: In comparison with existing approaches, LLMDiff exhibits superior capabilities in both language comprehension and action understanding. Furthermore, it is proficient in generating images with high-quality details.

The last column reveals our model's capacity to utilize LLM's inherent imagination ability and understanding of functions. The goal is to create a pig that can fly, focusing on its inherent ability to fly rather than its state or actions. It is expected that the generated image should depict an animal with a pig's primary features but a body structure adapted for flight. Existing models all generate a pig flying in the sky, and particularly, SD models simply draw a pig floating in the sky, without any imagination about the function of flying. Our model, instead, infers the user's intention from the text and conceptualizes the ability to fly based on LLM's knowledge base. It borrows structure characteristics from common flying animals, like birds, and integrates them into the pig. The pig's ears evolve into larger structures resembling wings, and it reduces to two feet and a smaller size, which are typical bird traits. Our model thus imagines a pig with flying capabilities rooted in real-world logic and pig features, rather than forcibly attaching wings.

Ziyi Dong, Yao Xiao, Pengxu Wei, & Liang Lin





Figure 6: The scale factor of newly added attentions and the original attentions in each cross-attention module of U-Net.

5.5 Analysis of Scaling Factors

According to the results in Fig. 6, which shows the weight distribution across various layers in the new and original cross-attentions, a substantial portion of the original knowledge within the model is preserved. The preservation is less in layers with a higher number of parameters, while layers at both ends, which have fewer parameters, retain more. The newly added rectification module primarily operates in the decoder part of the U-Net.

6 Conclusion and Limitations

In this paper, we have viewed generative LLMs with a transformerbased decoder-only structure as a diffusion model, and thus we can sample implicit text encodings for image generation. We propose an LLMDiff Adapter to incorporate these encodings into a textto-image diffusion model, enhancing the model's controllability and reasoning abilities, logic, and physics. The generated images are more realistic, with improved detail and quality. Moreover, our method outperforms existing text-encoder-based methods in various quantitative metrics.

Limitations. Our method requires the output from each Transformer block of LLM, and thus it is incompatible with closed-source models like GPT-4 and Claude 3.

Decoder-Only LLMs are Better Controllers for Diffusion Models

MM '24, October 28-November 1, 2024, Melbourne, VIC, Australia

Acknowledgments

This work is supported in part by National Natural Science Foundation of China (NSFC) under Grant U21A20470, No.62376292, 62325605, Guangdong Basic and Applied Basic Research Foundation under Grant No.2023A1515011374, and the Science and Technology Program of Guangzhou, China, under Grant 2024A04J6365

References

- Seungho Baek, Hyerin Im, Jiseung Ryu, Juhyeong Park, and Tak Yeon Lee. 2023. PromptCrafter: Crafting Text-to-Image Prompt through Mixed-Initiative Dialogue with LLM. *CoRR* abs/2307.08985 (2023). arXiv:2307.08985
- [2] James Betker, Gabriel Goh, Li Jing, TimBrooks, Jianfeng Wang, Linje Li, LongOuyang, JuntangZhuang, JoyceLee, YufeiGuo, WesamManassra, PrafullaDhariwal, CaseyChu, YunxinJiao, and Aditya Ramesh. [n. d.]. Improving Image Generation with Better Captions. https://cdn.openai.com/papers/dall-e-3.pdf
- [3] Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020. Language Models are Few-Shot Learners. In *NeurIPS 2020*, Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (Eds.).
- [4] Zhihong Chen, Guiming Chen, Shizhe Diao, Xiang Wan, and Benyou Wang. 2023. On the Difference of BERT-style and CLIP-style Text Encoders. In ACL.
- [5] Jun Cheng, Fuxiang Wu, Yanling Tian, Lei Wang, and Dapeng Tao. 2020. RiFeGAN: Rich Feature Generation for Text-to-Image Synthesis From Prior Knowledge. In IEEE/CVF Conference on Computer Vision and Pattern Recognition. 10908–10917.
- [6] Wei-Lin Chiang, Zhuohan Li, Zi Lin, Ying Sheng, Zhanghao Wu, Hao Zhang, Lianmin Zheng, Siyuan Zhuang, Yonghao Zhuang, Joseph E. Gonzalez, Ion Stoica, and Eric P. Xing. 2023. Vicuna: An Open-Source Chatbot Impressing GPT-4 with 90%* ChatGPT Quality. https://lmsys.org/blog/2023-03-30-vicuna/
- [7] Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, Parker Schuh, Kensen Shi, Sasha Tsvyashchenko, Joshua Maynez, Abhishek Rao, Parker Barnes, Yi Tay, Noam Shazeer, Vinodkumar Prabhakaran, Emily Reif, Nan Du, Ben Hutchinson, Reiner Pope, James Bradbury, Jacob Austin, Michael Isard, Guy Gur-Ari, Pengcheng Yin, Toju Duke, Anselm Levskaya, Sanjay Ghemawat, Sunipa Dev, Henryk Michalewski, Xavier Garcia, Vedant Misra, Kevin Robinson, Liam Fedus, Denny Zhou, Daphne Ippolito, David Luan, Hyeontaek Lim, Barret Zoph, Alexander Spiridonov, Ryan Sepassi, David Dohan, Shivani Agrawal, Mark Omernick, Andrew M. Dai, Thanumalayan Sankaranarayana Pillai, Marie Pellat, Aitor Lewkowycz, Erica Moreira, Rewon Child, Oleksandr Polozov, Katherine Lee, Zongwei Zhou, Xuezhi Wang, Brennan Saeta, Mark Diaz, Orhan Firat, Michele Catasta, Jason Wei, Kathy Meier-Hellstern, Douglas Eck, Jeff Dean, Slav Petrov, and Noah Fiedel. 2023. PaLM: Scaling Language Modeling with Pathways. J. Mach. Learn. Res. 24 (2023), 240:1–240:113.
- [8] et.al. Dan Hendrycks. 2021. Measuring Massive Multitask Language Understanding. In *ICLR*.
- [9] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In NAACL-HLT 2019, Jill Burstein, Christy Doran, and Thamar Solorio (Eds.). 4171–4186.
- [10] Ming Ding, Zhuoyi Yang, Wenyi Hong, Wendi Zheng, Chang Zhou, Da Yin, Junyang Lin, Xu Zou, Zhou Shao, Hongxia Yang, and Jie Tang. 2021. CogView: Mastering Text-to-Image Generation via Transformers. In Advances in Neural Information Processing Systems. 19822–19835.
- [11] Hanan Gani, Shariq Farooq Bhat, Muzammal Naseer, Salman H. Khan, and Peter Wonka. 2023. LLM Blueprint: Enabling Text-to-Image Generation with Complex and Detailed Prompts. *CoRR* abs/2310.10640 (2023). arXiv:2310.10640
- [12] Jonathan Ho, Ajay Jain, and Pieter Abbeel. 2020. Denoising Diffusion Probabilistic Models. In Advances in Neural Information Processing Systems.

- [13] Jonathan Ho and Tim Salimans. 2021. Classifier-Free Diffusion Guidance. In NeurIPS 2021 Workshop on Deep Generative Models and Downstream Applications.
- [14] et. al. Hugo Touvron. 2023. Llama 2: Open Foundation and Fine-Tuned Chat Models. CoRR abs/2307.09288 (2023). arXiv:2307.09288
- [15] Ajay Jain, Ben Mildenhall, Jonathan T. Barron, Pieter Abbeel, and Ben Poole. 2022. Zero-Shot Text-Guided Object Generation with Dream Fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*. 857–866.
- [16] Bowen Li, Xiaojuan Qi, Thomas Lukasiewicz, and Philip H. S. Torr. 2019. Controllable Text-to-Image Generation. In *NeurIPS 2019*, Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (Eds.).
- [17] Yuanzhi Li, Sébastien Bubeck, Ronen Eldan, Allie Del Giorno, Suriya Gunasekar, and Yin Tat Lee. 2023. Textbooks Are All You Need II: phi-1.5 technical report. *CoRR* abs/2309.05463 (2023). arXiv:2309.05463
- [18] Long Lian, Boyi Li, Adam Yala, and Trevor Darrell. 2023. LLM-grounded Diffusion: Enhancing Prompt Understanding of Text-to-Image Diffusion Models with Large Language Models. *CoRR* abs/2305.13655 (2023). arXiv:2305.13655
- [19] Xihui Liu, Dong Huk Park, Samaneh Azadi, Gong Zhang, Arman Chopikyan, Yuxiao Hu, Humphrey Shi, Anna Rohrbach, and Trevor Darrell. 2021. More Control for Free! Image Synthesis with Semantic Diffusion Guidance. *CoRR* abs/2112.05744 (2021). arXiv:2112.05744
- [20] Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. RoBERTa: A Robustly Optimized BERT Pretraining Approach. CoRR abs/1907.11692 (2019). arXiv:1907.11692
- [21] Alexander Quinn Nichol, Prafulla Dhariwal, Aditya Ramesh, Pranav Shyam, Pamela Mishkin, Bob McGrew, Ilya Sutskever, and Mark Chen. 2022. GLIDE: Towards Photorealistic Image Generation and Editing with Text-Guided Diffusion Models. In International Conference on Machine Learning. 16784–16804.
- [22] OpenAI. 2023. GPT-4 Technical Report. CoRR abs/2303.08774 (2023). arXiv:2303.08774
- [23] Zhiliang Peng, Wenhui Wang, Li Dong, Yaru Hao, Shaohan Huang, Shuming Ma, and Furu Wei. 2023. Kosmos-2: Grounding Multimodal Large Language Models to the World. ArXiv abs/2306.14824 (2023).
- [24] Dustin Podell, Zion English, Kyle Lacey, Andreas Blattmann, Tim Dockhorn, Jonas Müller, Joe Penna, and Robin Rombach. 2023. SDXL: Improving Latent Diffusion Models for High-Resolution Image Synthesis. *CoRR* abs/2307.01952 (2023). arXiv:2307.01952
- [25] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. 2021. Learning Transferable Visual Models From Natural Language Supervision. In Proceedings of the International Conference on Machine Learning, Vol. 139. 8748–8763.
- [26] Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. 2020. Exploring the Limits of Transfer Learning with a Unified Text-to-Text Transformer. J. Mach. Learn. Res. 21 (2020), 140:1–140:67.
- [27] Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. 2022. High-Resolution Image Synthesis with Latent Diffusion Models. In IEEE/CVF Conference on Computer Vision and Pattern Recognition. 10674–10685.
- [28] Chitwan Saharia, William Chan, Saurabh Saxena, Lala Li, Jay Whang, Emily Denton, Seyed Kamyar Seyed Ghasemipour, Burcu Karagol Ayan, S. Sara Mahdavi, Rapha Gontijo Lopes, Tim Salimans, Jonathan Ho, David J. Fleet, and Mohammad Norouzi. 2022. Photorealistic Text-to-Image Diffusion Models with Deep Language Understanding. CoRR abs/2205.11487 (2022). arXiv:2205.11487
- [29] Jianyi Wang, Kelvin C. K. Chan, and Chen Change Loy. 2023. Exploring CLIP for Assessing the Look and Feel of Images. In AAAI 2023, Brian Williams, Yiling Chen, and Jennifer Neville (Eds.). AAAI Press, 2555–2563.
- [30] wanng. 2023. midjourney-v5-202304-clean. https://huggingface.co/datasets/ wanng/midjourney-v5-202304-clean.
- [31] Jiahui Yu, Yuanzhong Xu, Jing Yu Koh, Thang Luong, Gunjan Baid, Zirui Wang, Vijay Vasudevan, Alexander Ku, Yinfei Yang, Burcu Karagol Ayan, Ben Hutchinson, Wei Han, Zarana Parekh, Xin Li, Han Zhang, Jason Baldridge, and Yonghui Wu. 2022. Scaling Autoregressive Models for Content-Rich Text-to-Image Generation. *CoRR* abs/2206.10789 (2022). arXiv:2206.10789
- [32] Xiaohua Zhai, Basil Mustafa, Alexander Kolesnikov, and Lucas Beyer. 2023. Sigmoid Loss for Language Image Pre-Training. CoRR abs/2303.15343 (2023). arXiv:2303.15343