ShapeLib: Designing a library of procedural 3D shape abstractions with Large Language Models

R. KENNY JONES, Brown University, USA

PAUL GUERRERO, Adobe Research, United Kingdom

NILOY J. MITRA, University College London and Adobe Research, United Kingdom

DANIEL RITCHIE, Brown University, USA



Fig. 1. ShapeLib guides an LLM to design a library of procedural shape functions from a given set of (20) seed shapes and textual descriptions. Using an LLM prior makes the functions semantically interpretable and easy to edit, while aligning them with the seed shapes specializes the functions to a given domain and reduces LLM hallucinations. The library can be used to train a network for visual program induction that generalizes well beyond the seed shapes.

Procedural representations are desirable, versatile, and popular shape encodings. Authoring them, either manually or using data-driven procedures, remains challenging, as a well-designed procedural representation should be compact, intuitive, and easy to manipulate. A long-standing problem in shape analysis studies how to discover a reusable library of procedural functions, with semantically aligned exposed parameters, that can explain an entire shape family. We present ShapeLib as the first method that leverages the priors of frontier LLMs to design a library of 3D shape abstraction functions. Our system accepts two forms of design intent: text descriptions of functions to include in the library and a seed set of exemplar shapes. We discover procedural abstractions that match this design intent by proposing, and then validating, function applications and implementations. The discovered shape functions in the library are not only expressive but also generalize beyond the seed set to a full family of shapes. We train a recognition network that learns to infer shape programs based on our library from different visual modalities (primitives, voxels, point clouds). Our shape functions have parameters that are semantically interpretable and can be modified to produce plausible shape variations. We show that this allows inferred programs to be successfully manipulated by an LLM given a text prompt. We evaluate ShapeLib on different datasets and show clear advantages over existing methods and alternative formulations.

$\label{eq:CCS} \text{Concepts:} \bullet \textbf{Computing methodologies} \to \textbf{Shape modeling}.$

Additional Key Words and Phrases: procedural modeling, shape analysis, shape abstraction, library learning, large language models, LLMs, semantics

1 INTRODUCTION

3D shapes are central to many visual computing problems. A variety of stakeholders, from entertainment and gaming systems to robotics and manufacturing depend on the ability to edit, manipulate, analyze, and synthesize 3D assets. Procedural models, which are structured programs that produce geometry when executed, are an appealing representation for 3D shapes that provide natural support for these operations in contrast with alternative representations such as meshes, point clouds, or voxels. Well-designed procedural models expose (semantic) handles that end-users can interpret and use to easily manipulate output geometry. These programs, however, are expensive to author or acquire.

Expert-designed procedural models [Müller et al. 2006; Pearl et al. 2022; Wonka et al. 2003] are useful because they are often composed of functions from a shape library that exposes the 'right' level of abstraction for a particular domain. Whereas a single procedural model can typically represent a distribution of shapes through parameter variations, a shape function library provides a set of elementary functions that can be *reused* across many procedural model instantiations. For instance, authoring a good procedural model of a building, while maintaining an interpretable interface, might require functions that tile windows over a facade [Wonka et al. 2003], or automatically extrude common types of roofing patterns from a boundary [Müller et al. 2006]. Access to this sort of domain-specific library allows procedural models to realize the many benefits of this representational paradigm. Unfortunately, designing a good library

Authors' addresses: R. Kenny Jones, russell_jones@brown.edu, Brown University, USA; Paul Guerrero, guerrero@adobe.com, Adobe Research, United Kingdom; Niloy J. Mitra, n.mitra@cs.ucl.ac.uk, University College London and Adobe Research, United Kingdom; Daniel Ritchie, daniel_ritchie@brown.edu, Brown University, USA.

of procedural modeling functions is even more difficult compared with authoring a single procedural model.

Despite the difficulty of this problem, some work has investigated how to automatically discover good libraries of procedural shape functions. These methods use data-driven approaches to optimize a compression-based objective. They operate in a 'bottom-up' fashion, starting from a base modeling language with elementary functions, and gradually grow their library, in a greedy manner, by defining new and more domain-specific abstraction functions based on how much they help to compress shapes from a large dataset. While these approaches can successfully optimize their compression objective, they base their library development solely on compressing out common geometric patterns over a large shape dataset, without any semantic 'top-down' guidance. As a result, the functions they produce can only align to shape semantics by chance, making them difficult to interpret and meaningfully manipulate.

As an alternative, we investigate how Large Language Models (LLMs) can help with this procedural language design problem. LLMs have demonstrated remarkable success over a surprisingly diverse range of tasks, from 3D layout synthesis [Hu et al. 2024] to general code generation [Jiang et al. 2024]. There are reasons to believe they might be useful in helping to design procedural models. They have top-down world knowledge about the semantic relationships of parts within shapes and they are proficient at writing code. Despite these properties, LLMs also have limitations that temper their procedural modeling capabilities. As we demonstrate experimentally, latest frontier LLMs still struggle to understand complex geometric layouts and often misinterpret or misattribute constraints and relations between parametric controls. Their mistakes manifest as hallucinations, leading to implausible geometry or structures that cannot represent assets in existing 3D datasets.

We propose ShapeLib, a hybrid system that guides an LLM through the creation of a library of procedural abstraction functions from a specified design intent. An expert user provides this design intent to our system with two modalities: (i) function descriptions in natural language, and (ii) a seed set of exemplar shapes. The two modalities are complementary: the first mode allows the user to specify the kinds of functions they would like to interface with; while the second mode provides geometric references that guide and constrain library development.

ShapeLib breaks the complex library design process into a series of sub-problems. First, we use an LLM to design the library interface with a prompting workflow conditioned on the function descriptions. Next, we task an LLM with proposing applications of these functions to explain shapes from the seed set (from the interface only, without any actual implementations). We then use these proposed applications to automatically formulate input/output examples that guide the LLM to propose implementations of each function. We finalize the library with a validation step that performs a geometric analysis over the proposed function implementations and applications. To apply these functions to represent shapes beyond the seed set, we additionally train a recognition network that learns to map input shapes to output programs written with the library functions. To train this network, we create a synthetic data generator by prompting an LLM with the finalized library implementation and asking it to produce a function that randomly generates

an input shape using the abstraction functions. In this way, even starting from only a small seed set, ShapeLib can find programs that use these abstraction functions to explain a much larger collection of shapes (see Figure 1).

We evaluate ShapeLib by using it to design libraries of procedural functions over multiple shape categories (chair, table, storage, lamp, faucet). We find that our method generates functions that (i) adhere to the top-down semantics provided by the natural language descriptions, and (ii) produce geometric outputs that reflect structures observed from the exemplar shapes. Beyond this, we experimentally validate that our discovered library helps us to realize the benefits of representing shapes procedurally along a number of axes. *Generalization (a):* they are useful for modeling shapes outside of the seed set; *Interpretability (b):* they are aligned with semantics and expose a small number of parameters that produce predictable edits; *Plausibility (c):* they constrain outputs to maintain shape semantics under manipulation.

We compare against alternative problem framings, and find that our dual modality design intent is crucial for our success. When semantic information from (i) is missing, systems like ShapeCoder [Jones et al. 2023] find abstractions that improve compression, but lack interpretability and do not maintain plausibility. When reference geometry from (ii) is missing, LLMs design sensible library interfaces, but produce function implementations that can not generalize across shape distributions.

In summary, our contributions are:

- ShapeLib, a pipeline that guides an LLM through the development of a library of procedural functions while adhering to specified design intent.
- (2) A recognition network that learns to infer programs that use library functions to explain input shapes, trained with a synthetic data sampler authored by an LLM.
- (3) Demonstrations that our library better realizes the benefits of procedural representations over alternative approaches.

We will release code upon publication.

2 RELATED WORK

Library learning. The core goal of our method is to learn a library of functions that can be used to procedurally represent any 3D shape in a given domain. Several prior methods [Bellur et al. 2024; Bowers et al. 2023; Cao et al. 2023; Ellis et al. 2018, 2021] have tackled the library learning problem in a more general setting. These methods take as input a set of simple tasks or programs that use only basic operators and find a library of more abstract functions that can represent the inputs more compactly. Though these approaches have demonstrated impressive generality, their non-specialization limits their usability for 3D shapes. For example, they struggle to handle the complex parametric expressions that describe geometric relations between shape parts. ShapeMOD [Jones et al. 2021] and ShapeCoder [Jones et al. 2023] extend library learning to 3D shapes, using specialized search strategies over parametric expressions.

However, unlike our method, all of the methods above derive the library based only on the input examples, without using any additional priors like our LLM. Typically, their goal is to maximize the compression of input examples when represented with library functions. This limits the *interpretability* of functions learned by these methods, i.e., how well their parameters and the operations they perform align with the semantics of 3D shapes. As a result, programs and their parameters are harder to understand and more difficult to use for both humans and LLMs, as we will demonstrate in our evaluation. Additionally, due to the lack of guidance from a strong prior, these methods require a much larger set of input examples and are more prone to get stuck in local minima, miss relevant functions, or produce duplicate functions.

More recently, Lilo [Grand et al. 2024] also proposes making use of an LLM prior for general (i.e., non-shape-specific) library learning. However, apart from not handling 3D shapes, the LLM is only used to *name* functions that are found by one of the earlier methods [Bowers et al. 2023], and to apply these functions to given input examples. As the functions, along with their parameters, are still found without LLM guidance, the interpretability issue remains.

Shape program inference and generation. Once we have discovered a library of functions, we can use it to infer a program for a given input shape or to directly generate new shape programs. Several methods have tackled this problem of shape program inference and generation. Most methods assume that a low-level shape language is given, for example CAD languages [Li et al. 2024, 2023; Ren et al. 2022; Uy et al. 2022; Willis et al. 2020; Wu et al. 2021; Xu et al. 2021, 2022], CSG operations [Du et al. 2018; Kania et al. 2020; Ren et al. 2021; Yu et al. 2023, 2022], or other languages [Deng et al. 2022; Ganeshan et al. 2023; Jones et al. 2020, 2024; Tian et al. 2019], including more domain-specific languages [Guo et al. 2020; Lee et al. 2023; Plocharski et al. 2024]. Shape programs are generated directly in this language, without learning a domain-specific function library that could be specialized to a given use case, usually by training a neuro-symbolic approach on a large set of examples.

However, both the lack of a domain-specific function library and the lack of a strong semantic prior like an LLM limit the *interpretability* of the resulting programs, making it difficult to produce plausible edits, both manually or via natural language prompts: omitting a domain-specific function library reduces consistency and compositionality of the programs, making them less compact, and harder to interpret and work with. Thus, similar to prior library learning methods, the lack of a strong semantic prior reduces semantic alignment of operations and parameters.

Other methods assume shape programs are available and only focus on generating or inferring parameters for these programs [Michel and Boubekeur 2021; Pearl et al. 2022; Raistrick et al. 2023, 2024]. Results are impressive, but require an expert to craft well-designed shape programs as input. In contrast, we only require high-level design intent as input, in the form of natural language descriptions and a set of seed shapes.

Scene layout generation using LLMs. LLMs have recently been used to directly generate 2D or 3D scene layouts from a natural language prompt [Aguina-Kang et al. 2024; Feng et al. 2023; Hu et al. 2024; Littlefair et al. 2025; Yang et al. 2024; Zhang et al. 2024]. Note that in terms of priors used, this is the opposite of the approaches described in the previous paragraph: only an LLM prior is used, but no prior is obtained from a set of seed examples. This makes it hard to align the generated scene layouts to a target distribution, as examples can describe a target distribution much more efficiently than a text prompt. Additionally, the lack of a domain-specific function library results in the same problems described in the last paragraph: scene representations are not compact and have a large number of parameters, which makes them difficult to edit. In contrast, our approach combines the LLM prior with a prior obtained from a set of examples via our learned function library. Recently, SceneMotifCoder [Tam et al. 2024] also combines a LLM prior with a prior from a small set of 1-3 examples. However, no function library is constructed, and they only produce very simple object layouts (e.g., stacks, rows, or grids).

3 OVERVIEW

ShapeLib guides an LLM through the process of developing a library of procedural functions that matches an input design intent. In our problem framing, we assume that a user has a procedural modeling domain in mind (e.g., a particular category of shapes). The user will communicate their design intent to our system, which is then tasked with producing a fully realized library of abstraction functions that meet our desiderata: (a) they should generalize, (b) they should be interpretable, and (c) they should produce plausible outputs.

Our system receives a number of benefits from the prior knowledge encoded in LLMs. Since LLMs have been trained extensively on human-written code, they are able to author functions with meaningful names and parameters. This exposes an interface that a person can easily work with and understand. However, we also find that LLMs are prone to hallucinate, generating mismatches from 'real' distributions of shapes (e.g., collections of 3D assets).

To overcome this issue, we guide and ground the LLM outputs under the supervision of the user provided design intent, consisting of a textual description and a set of seed shapes. Textual descriptions of desired function properties help constrain the interface design, prompting the semantic prior of the LLM to attune towards a particular modeling task. Each seed set we consider is composed of twenty 3D shapes with part-level semantic segmentations and textured renders. Our system validates the plausibility of its productions by searching for function implementations and applications that can explain sub-structures in these exemplars.

In the following, we explain how ShapeLib solves this problem. In Section 4, we describe how we convert design intent into a fully realized library of abstraction functions. In Section 5, we describe how we can expand the usage of this library beyond the seed set by training a recognition network on synthetic data.

4 LIBRARY DESIGN

ShapeLib converts design intent into a library of functions through a series of steps, which we depict in Figure 2. The interface creation step converts function descriptions into a library interface (Section 4.1). The application proposal step identifies which library functions should model which seed set shapes (Section 4.2). The implementation proposal step generates candidate function implementations (Section 4.3). The library is then finalized with a validation step that checks combinations of proposed function applications and implementations against seed set examples (Section 4.4). 4 . R. Kenny Jones, Paul Guerrero, Niloy J. Mitra, and Daniel Ritchie



Fig. 2. Method overview. We design a function library in four steps, starting from a user intent (light blue) that consists of function descriptions and a set of seed shapes. First, (a) we prompt an LLM to create function interfaces that define parameters and annotate the function's purpose. Then, (b) the LLM is prompted to propose multiple applications of the functions that reconstruct the seed shapes. Next, (c) we use this information to guide the LLM to propose multiple function implementations. The library is finalized with a validation step (d) that searches for pairs of applications and implementations that best reconstruct the seed shapes by guiding the LLM to author a synthetic data generator with the library functions, and using the resulting paired data to train a recognition network for visual program induction.

4.1 Interface Creation

ShapeLib first converts user function descriptions into a library interface (Fig. 2, a). We prompt an LLM to produce a structured interface, where for each function it produces a typed signature and an accompanying doc-string.

We provide the LLM with two default classes: a 'Part' class that creates primitives that abstract detailed geometry and a 'Coord-Frame' class that defines a local bounding volume. Our prompt contains task instructions and in-context expert demonstrations sourced from different categories. By default, we use axis-aligned cuboid primitives, though this design decision could be generalized by modifying prompt instructions and examples.

The LLM produces function signatures that expose parametric handles, e.g. the numbers of bars in a ladder back or the height of base runner. Each function is instructed to take in a special first parameter, *CF*, a 'CoordFrame' that specifies the expected extents of the functions outputs. Functions are typed so that they return a List of 'Part' objects.

Through our in-context examples and instructions, we prompt the doc-string to have a particular structure. First, it defines a *description* field to explain the high-level goals of the function. Then, it defines a *parts* field, that specifies what parts should be produced depending

on the input parameters. Finally, it defines a *parameter* field, that explains how they should affect the output structure. This interface is then used to guide the library development.

4.2 Proposing Function Applications

As LLMs are prone to hallucinate, we do not directly implement each function following the prior step. Instead, we would like to ground each function implementation by referencing structures from the seed set. To find such references, we propose programs that apply library functions that explain exemplar shapes (Fig. 2, b).

This step begins by sampling a shape from the seed set. We ask a VLM to describe the parts that is sees from a render of the shape. We also convert the 3D semantic part annotations into a list of labeled 'Part' objects. We combine these inputs together, and task an LLM with deciding what parts should be explained by which library functions (even though these functions lack implementations). The LLM outputs this decision by authoring a 'program()' function that proposes library function applications (along with parameters). We ask the LLM to use a special 'group_parts' function when constructing this program, that consumes a list of input 'Part' objects and returns a bounding 'CoordFrame' object. In this way, the 'program' provides information about which parts of the input shape should be explained by which library functions.

As we later demonstrate empirically, the accuracy of individual LLM calls has a high variance which makes them hard to trust. Therefore, instead of finding a single program for each shape, we run this procedure K times for each shape in the seed set (K=5).

4.3 Propose Function Implementations

ShapeLib now has the information from the prior steps it needs to author good function implementations: typed signatures, docstring guidance, and input-output examples. These input-output example pairs can be automatically found from the proposed function applications. From this input, we ask the LLM to complete the implementation of each function so that it matches the signature type, meets the doc-string specification, and respects the observed patterns present in the usage examples (Fig. 2, c).

Of note, we find that the LLM predictions in the previous application proposal step do a good job of identifying which functions should explain which parts, but do a much worse job at predicting parameter values. With this in mind, we mask out parameter values with a special token '?' in all input-output examples. We do this for every parameter value, except for the first *CF* 'CoordFrame', as the correct value for this parameter can be found automatically with the 'group_parts' function.

Similar to previous step, we find that some implementations produced by the LLM produce better or worse matches against the input specification. So for each function in our library, we propose K different ways that it could be implemented (K=4).

4.4 Library Validation

At this point we are close to having a fully realized library. From the prior steps we have (a) function doc-strings and signatures, (b) proposals of how the functions should be applied to explain groups of parts in seed-set shapes, and (c) proposals of how the function should be implemented. This validation step is responsible for deciding which of these proposals are 'good', and not just LLM hallucinations (Fig 2, d).

To make this decision, we search over pairs of proposed implementations and parameterizations, and record those that geometrically match structures present in the seed set shapes. For each proposed function implementation from (c) we check which of proposed part groups from (b) this implementation can explain. Specifically, we try executing the function with the proposed parameterizations sourced from (b), calculate the observed error between the target parts and function output, and record the parameterization that achieves the best error. Our error metric compares corner-to-corner distances between sets of geometric primitives, and mark function applications as invalid if the paired structures are not similar enough (see the appendix for details).

At this point, for each group of parts from (b) we know which implementation from (c) best matches the observed part structure. We keep the implementation that achieves the *best* error across the *most* part groups, and remove all others proposals. If this *best* implementation found valid applications across multiple seed set shapes, we update the library interface entry with its implementation logic. Otherwise, we remove the function entry from the interface.

5 USING THE LIBRARY FOR PROGRAM SYNTHESIS

In Section 4, we constructed a library of functions that have meaningful signatures and structured doc-strings. Each function has an implementation that is capable of producing structures that capture patterns observed in the seed set, but a question remains: how can we use these functions to represent new shapes?

In this section, we describe our strategy for expanding library function usage beyond the seed set (Fig. 2, *right*). To begin, we once again make use of the strong prior of LLMs by providing it with our library interface and asking it to design a procedure that uses the abstraction functions to randomly synthesize synthetic shapes. Once we've developed this synthetic data sampler, we can use it to produce paired training data for a recognition network that learns how to solve an inverse task: given an input shape structure, write a program using the library functions that explain its parts.

Generating a synthetic shape sampler. In this step, we design a prompt that describes the library we've developed, including the interface of each function and examples of how to use it (sourced from the validation stage). We give this prompt to an LLM and ask it to write a 'sample shape' function that randomly produces new shapes using the provided abstractions. Interestingly, we find that frontier LLMs are able to provide useful implementations of such a 'sample_shape' function. A shown in Figure 2, some of these random outputs produce good shape abstractions, while other random samples violate class semantics. With this in mind, instead of attempting to get the LLM to perfect its implementation, we treat its output as a synthetic data generator for a recognition network. To broaden the coverage and variety of structures that these 'sample shape' functions produce, we employ an iterative refinement loop that provides automatic feedback to the LLM. This refinement procedure ensures that all functions and parameters in the library get used, and instructs the 'sample_shape' function to produce outputs spanning the observed structures from validation step (see appendix).

Training a recognition network. Once we've improved the 'sample shape' function through rounds of iterative refinement, we can use it to produce training data for a recognition network. This network takes as input a shape represented as a set of unordered primitives (e.g., Cuboid dimensions and positions). It outputs a program that uses library functions to reconstruct this input shape. We implement this network as an autoregressive Transformer decoder [Vaswani et al. 2017] with a causal prefix mask over the input shape representation. We train this network from scratch, streaming random samples from the synthetic data generator: each program we sample becomes a target output and we execute the program to find the corresponding input. Once trained, we can use this network to find library function applications that explain shapes from outside of the starting seed set (Fig. 2, right-bottom). Our inference procedure prompts the network with an input set of unordered primitives and samples a large number of programs according the network's predicted distribution. We try executing each program, and we record its complexity (the number of tokens it uses) and its geometric error against the input set. We choose the program that minimizes an objective that is a simple weighted combination of these two values.

Table 1. We compare how well ShapeLib's library of abstraction functions can generalize from the seed set to held-out validation shapes. We report the objective score achieved by our method compared with alternatives. Obj is a weighted average of the program DoF and the geometric error.

Set	Method	Obj↓	Prog DoF \downarrow	$\mathbf{Error}\downarrow$	# Lib Fns ↓	Dev Time
	Prims	73.0	73.0	0.000	0	0 h
Seed	LLM-Direct	64.0	61.6	0.242	5.6	0.25 h
seea	ShapeCoder	43.8	39.9	0.389	19.2	20.26 h
	ShapeLib	43.5	39.6	0.393	5.6	0.85 h
	Method	Obj↓	Prog DoF \downarrow	Error ↓	# Shape Fns \downarrow	Inf Time ↓
	Prims	71.5	71.5	0.000	17.133	5.137 s
Val	LLM-Direct	65.3	63.5	0.184	14.482	4.792 s
	ShapeCoder	52.1	48.6	0.354	13.485	7.361 s
	ShapeLib	51.5	47.8	0.369	9.592	5.137 s

6 RESULTS AND EVALUATION

We run experiments over multiple categories of 3D shapes (chair, table, storage, lamp, faucet). For each category, an expert user provides design intent as (a) natural language descriptions of functions that would be useful for this category and (b) a set of 20 seed shapes sourced from PartNet [Mo et al. 2019], which has per-part annotations. We obtain corresponding renders of each shape from ShapeNet [Chang et al. 2015]. This input is provided to ShapeLib, which then produces libraries of abstraction functions for each category. Unless otherwise noted, we use OpenAI's o1-mini as the LLM.

We find that ShapeLib discovers libraries that match the design intent, with validated implementations for almost all of the functions specified in natural language (chair 8/8, table 5/6, storage 6/6, faucet 5/5, lamp 4/4). Figure 3 shows examples of these implementations and applications.

We verify that our method is able to help realize the benefits of representing shapes in a procedural fashion with experiments that match our stated desiderata (see Figure 4.). To evaluate generalization, we compare recognition networks that infer programs from structured inputs (Section 6.1) and from unstructured geometry (Section 6.2). We then evaluate how well function applications are aligned with class semantics (Section 6.3). Finally, we show that our interface is interpretable and maintains plausibility under manipulations with a perceptual study that evaluates how well an LLM can edit our shape programs compared to a baseline (Section 6.4)

6.1 Library Function Generalization

We measure how well our library generalizes beyond the patterns in the seed shapes. We compare against three alternatives: *Prims*, *LLM-Direct*, and *ShapeCoder*. *Prims* refers to our representation of input shapes as collection of unordered primitives – it is used as lower performance bound; *LLM-Direct* is an ablated version of our method that only reasons over the natural language descriptions to discover a library of abstraction and does not use seed shapes; while *ShapeCoder* only uses seed shapes. In our evaluations we show that ShapeLib, which uses both forms of design intent, offers clear advantages over these alternatives.

We evaluate the ability of different methods to compress programs in Table 1. We report this over two different shape sets: the

Table 2. We train networks that learn to map unstructured geometry (point clouds or voxels) to shape programs. Learning with ShapeLib functions improves reconstruction Chamfer distance and voxel IoU.

Method	$\mathbf{CD} \downarrow (\textit{Point Clouds})$	$IoU \uparrow (Voxels)$
ShapeCoder	0.0490	0.5708
ShapeLib	0.0467	0.6404

seed set (20 shapes per category) and a held-out validation set (400-1000 shapes per category). For ShapeLib and LLM-Direct, program applications are found for validation shapes using the recognition network that takes as input a shape represented as a collection of unordered primitives (Section 5). ShapeCoder develops and learns such a recognition network during its 'library learning' stage. For both the seed set and the validation set, we report the total compression objective value (Obj). This is a weighted sum of the degrees of freedom the program exposes (Prog DoF, weight 1), and the geometric error of the reconstructions (Error, weight 10). We also report the number of functions used in each library (# Lib fns), the time it took to discover each library (Dev time), the number of functions used per shape (# Shape fns) and the average time it takes to infer a program for a validation shape (Inf Time).

From the results, we note LLM-Direct performs poorly, and its function implementations can't find applications that match well to real geometry (resulting in its limited objective improvement over Prims). ShapeCoder is designed solely to perform well at program compression, but despite this, ShapeLib is able to match or slightly outperform ShapeCoder with respect to the objective. Moreover, we achieve this result much faster, using a smaller collection of library functions, and require less function calls to reconstruct shapes during inference. We find library implementations in under an hour, whereas ShapeCoder's bottom up procedure takes around a day to converge (though our LLM API calls cost \$5-10 per category).

6.2 Shape Programs from Unstructured Geometry

So far, we demonstrated that our recognition network from Section 5 can successfully convert semi-structure geometric inputs into programs, but what about completely unstructured geometry such as point clouds or voxels? To support this application, we train new recognition networks that take either point clouds or voxels as input. We source training data using the original 'structured' recognition network to annotate shapes in PartNet with corresponding programs. Per category, we use 400-4000 shapes for training and re-use the same 400-1000 shapes as described previously for validation. We sample both point clouds and voxels for each of the shapes.

Table 2 compares the reconstruction performance of a recognition network trained with function from ShapeLib to a recognition network trained with functions from ShapeCoder. For point clouds, we track Chamfer distance [Fan et al. 2017] between input point cloud (sampled from mesh geometry) and point cloud sampled from abstracted cuboid outputs. For voxels, we track IoU between input voxelizations and voxelizations of program outputs. We find that functions from ShapeLib enable more accurate reconstructions compared to functions from ShapeCoder. We visualize some qualitative results for some validation shapes in Figure 4. In addition to leading

Table 3. We measure the 'semantic entropy' of library function applications by analyzing the distribution of functions used to reconstruct parts in validation shapes. Lower values indicate more semantically aligned usage.

Method	Chair	Table	Storage	Lamp	Faucet
ShapeCoder	1.67	1.578	2.077	1.732	2.103
ShapeLib	0.484	1.095	0.745	0.684	1.243

Table 4. Fine-grained semantic segmentation performance found by applying functions over validation shapes, and assigning labels with a voting scheme decided by seed-set usage patterns.

Method	Precision \uparrow	Recall ↑	F1 Score ↑
ShapeCoder	0.25	0.30	0.27
LLM-Direct	0.34	0.12	0.18
ShapeLib	0.50	0.30	0.36

Table 5. Results of our perceptual study evaluating edits made by an LLM to programs that use shape abstraction libraries. We report judgments along two axes: shape plausibility and match to edit intent.

	More Plausible(%)	Better Matches Intent (%)
vs. ShapeCoder	75%	73%

to better reconstructions, we also see that the application of our functions are more strongly correlated with class semantics.

6.3 Sematic Consistency of Function Usages

Beyond reconstruction, the *way* in which functions are used also impacts the usefulness of the resulting model. We design an experiment to evaluate the *semantic consistency* of function usages. We track how each function is applied when reconstructing validation shapes, and record the semantic labels of the parts that it matches against. Then, for each semantic label, we analyze the distribution of functions that were used to construct parts of this type. If functions are well-aligned with semantics, i.e. have a consistent usage pattern, then this distribution should have low entropy. We report results of this experiment in Table 3. Compared with ShapeCoder, ShapeLib has a much lower semantic entropy, indicating that its assignment of functions to part structures is more semantically aligned.

Semantic Segmentation. Alternatively, we judge the semantic alignment of these libraries by using them to perform semantic segmentation. We design an experiment to test these capabilities. For each function, we look at validated applications made over the seed set, and record the semantic labels of parts that each function explains. We then aggregate this information by counting the most commonly covered part labels to produce a simple voting function to assign semantic labels when the function is applied. We evaluate the semantic segmentation performance on fine-grained part labels from PartNet over validation shapes, and report results of this experiment in Table 4. ShapeCoder and ShapeLib achieve a similar recall, but ShapeLib is twice as precise in its semantic predictions. LLM-Direct is more precise then ShapeCoder, however without access to seed set exemplars it cannot find many successful function application, resulting in poor recall.

6.4 Editing Shape Programs with LLMs

In this section, we investigate two critical questions concerning our library: is it interpretable and does it help constrain shape plausibility. We consider these questions under the framing of a shape editing study. First, we use the application network from Section 5 to find programs that explain validation shapes, using either functions from ShapeCoder or ShapeLib. We then design a series of shape edit requests, and ask an LLM to edit the text of the shape program to meet the request (i.e. change function parameters and how functions are used, as depicted in Figure 1, for example).

To evaluate performance, we designed a two alternative forced choice perceptual study. We choose 5 shapes from the validation set of each category, and consider 4 edits per shape, giving us a crossproduct of 100 total comparison conditions. We provide o1mini with the fully implemented function library for both ShapeLib and ShapeCoder conditions. For the ShapeCoder condition, we observed that o1mini produced a program that failed on execution for 11/100 editing tasks, so we omit those from the study. o1mini never produced a program that failed on execution for the ShapeLib condition. We recruited 13 participants who made 50 perceptual judgments each. For each comparison, we show the original shape in the middle, and arrange edits made using ShapeCoder/ShapeLib programs on either side, randomizing the left/right order. We then ask each participant to make two judgments: (i) which manipulated shape was more plausible, and (ii) which edit better matched the input edit request.

We report preference rates of ShapeLib over ShapeCoder along these two axes in Table 5. These results support our claim that our library of shape abstraction functions provides an interface that is easy to interpret and maintains strong plausibility under parameter variations. We show qualitative demonstrations of these edits in Figure 4, and observe higher semantic alignment of LLM edits, when these edits are made over ShapeLib programs.

7 CONCLUSION

We have presented ShapeLib as the first method that combines general semantic priors from LLMs with domain-specific information in the form of small seed set of shapes to produce a function library that *generalizes* to a full category of shapes and exposes *interpretable* parameters that produce *plausible* results under manipulation. This addresses the long-standing problem in visual program induction to create programs that are not only compact, but also semantically well-aligned and thus easy to work with for both humans and LLMs.

Several limitations indicate possible directions for future work: our current shape representation does not model precise part orientations. This could be addressed by modifying the prompts and seed set with oriented parts, but would likely increase the number of proposals needed to find good implementations. Our function libraries currently only model a single shape class. More generic functions that apply to multiple classes may be found by providing more examples in longer prompts.

Other interesting directions for future work include (i) guiding the LLM to create a procedural generator that more closely aligns with the semantics of a shape class by refining our synthetic data generator with programs found by our recognition network; (ii) training a

generative module that produces detailed geometry from our coarse structural representation, by learning the correlation between structure and geometry; (iii) making functions differentiable by asking the LLM to use PyTorch, enabling gradient-based parameter fitting during program inference; and (iv) using other modalities to convey design intent, like examples of expert-crafted procedures from Infinigen [Raistrick et al. 2024].

REFERENCES

- Rio Aguina-Kang, Maxim Gumin, Do Heon Han, Stewart Morris, Seung Jean Yoo, Aditya Ganeshan, R Kenny Jones, Qiuhong Anna Wei, Kailiang Fu, and Daniel Ritchie. 2024. Open-Universe Indoor Scene Generation using LLM Program Synthesis and Uncurated Object Databases. arXiv preprint arXiv:2403.09675 (2024).
- Abhiram Bellur, Razan Alghamdi, Kidus Workneh, and Joseph Izraelevitz. 2024. Leroy: Library Learning for Imperative Programming Languages. arXiv preprint arXiv:2410.06438 (2024).
- Matthew Bowers, Theo X. Olausson, Lionel Wong, Gabriel Grand, Joshua B. Tenenbaum, Kevin Ellis, and Armando Solar-Lezama. 2023. Top-Down Synthesis for Library Learning. Proc. ACM Program. Lang. 7, POPL, Article 41 (jan 2023), 32 pages. https: //doi.org/10.1145/3571234
- David Cao, Rose Kunkel, Chandrakana Nandi, Max Willsey, Zachary Tatlock, and Nadia Polikarpova. 2023. Babble: Learning Better Abstractions with E-Graphs and Anti-Unification. Proc. ACM Program. Lang. 7, POPL, Article 14 (jan 2023), 29 pages. https://doi.org/10.1145/3571207
- Angel X. Chang, Thomas Funkhouser, Leonidas Guibas, Pat Hanrahan, Qixing Huang, Zimo Li, Silvio Savarese, Manolis Savva, Shuran Song, Hao Su, Jianxiong Xiao, Li Yi, and Fisher Yu. 2015. ShapeNet: An Information-Rich 3D Model Repository. arXiv:1512.03012 (2015).
- Paolo Cignoni, Marco Callieri, Massimiliano Corsini, Matteo Dellepiane, Fabio Ganovelli, and Guido Ranzuglia. 2008. MeshLab: an Open-Source Mesh Processing Tool. In Eurographics Italian Chapter Conference, Vittorio Scarano, Rosario De Chiara, and Ugo Erra (Eds.). The Eurographics Association. https://doi.org/10. 2312/LocalChapterEvents/ItalChap/ItalianChapConf2008/129-136
- Boyang Deng, Sumith Kulal, Zhengyang Deng, Congyue Deng, Yonglong Tian, and Jiajun Wu. 2022. Unsupervised Learning of Shape Programs with Repeatable Implicit Parts. In Advances in Neural Information Processing Systems.
- Tao Du, Jeevana Priya Inala, Yewen Pu, Andrew Spielberg, Adriana Schulz, Daniela Rus, Armando Solar-Lezama, and Wojciech Matusik. 2018. InverseCSG: automatic conversion of 3D models to CSG trees. In Annual Conference on Computer Graphics and Interactive Techniques Asia (SIGGRAPH Asia). ACM.
- Kevin Ellis, Lucas Morales, Mathias Sablé-Meyer, Armando Solar-Lezama, and Joshua B. Tenenbaum. 2018. Library Learning for Neurally-Guided Bayesian Program Induction. In Advances in Neural Information Processing Systems (NeurIPS).
- Kevin Ellis, Catherine Wong, Maxwell Nye, Mathias Sablé-Meyer, Lucas Morales, Luke Hewitt, Luc Cary, Armando Solar-Lezama, and Joshua B Tenenbaum. 2021. Dreamcoder: Bootstrapping inductive program synthesis with wake-sleep library learning. In Proceedings of the 42nd acm sigplan international conference on programming language design and implementation. 835–850.
- Haoqiang Fan, Hao Su, and Leonidas J Guibas. 2017. A point set generation network for 3d object reconstruction from a single image. In *Proceedings of the IEEE conference* on computer vision and pattern recognition. 605–613.
- Weixi Feng, Wanrong Zhu, Tsu-jui Fu, Varun Jampani, Arjun Akula, Xuehai He, Sugato Basu, Xin Eric Wang, and William Yang Wang. 2023. LayoutGPT: Compositional Visual Planning and Generation with Large Language Models. arXiv preprint arXiv:2305.15393 (2023).
- Aditya Ganeshan, R Kenny Jones, and Daniel Ritchie. 2023. Improving unsupervised visual program inference with code rewriting families. In Proceedings of the IEEE/CVF International Conference on Computer Vision. 15791–15801.
- Gabriel Grand, Lionel Wong, Maddy Bowers, Theo X Olausson, Muxin Liu, Joshua B Tenenbaum, and Jacob Andreas. 2024. Lilo: Learning interpretable libraries by compressing and documenting code. *ICLR* (2024).
- Jianwei Guo, Haiyong Jiang, Bedrich Benes, Oliver Deussen, Xiaopeng Zhang, Dani Lischinski, and Hui Huang. 2020. Inverse procedural modeling of branching structures by inferring L-systems. ACM Transactions on Graphics (TOG) 39, 5 (2020), 1–13.
- Ziniu Hu, Ahmet Iscen, Aashi Jain, Thomas Kipf, Yisong Yue, David A Ross, Cordelia Schmid, and Alireza Fathi. 2024. SceneCraft: An LLM Agent for Synthesizing 3D Scenes as Blender Code. In Forty-first International Conference on Machine Learning.
- Juyong Jiang, Fan Wang, Jiasi Shen, Sungju Kim, and Sunghun Kim. 2024. A Survey on Large Language Models for Code Generation. arXiv preprint arXiv:2406.00515 (2024).
- R. Kenny Jones, Theresa Barton, Xianghao Xu, Kai Wang, Ellen Jiang, Paul Guerrero, Niloy J. Mitra, and Daniel Ritchie. 2020. ShapeAssembly: Learning to Generate

Programs for 3D Shape Structure Synthesis. ACM Transactions on Graphics (TOG), Siggraph Asia 2020 39, 6 (2020), Article 234.

- R. Kenny Jones, David Charatan, Paul Guerrero, Niloy J. Mitra, and Daniel Ritchie. 2021. ShapeMOD: Macro Operation Discovery for 3D Shape Programs. ACM Transactions on Graphics (TOG), Siggraph 2021 40, 4 (2021), Article 153.
- R Kenny Jones, Paul Guerrero, Niloy J Mitra, and Daniel Ritchie. 2023. Shapecoder: Discovering abstractions for visual programs from unstructured primitives. ACM Transactions on Graphics (TOG) 42, 4 (2023), 1–17.
- R. Kenny Jones, Renhao Zhang, Aditya Ganeshan, and Daniel Ritchie. 2024. Learning to Edit Visual Programs with Self-Supervision. In Advances in Neural Information Processing Systems.
- Kacper Kania, Maciej Zieba, and Tomasz Kajdanowicz. 2020. UCSG-NET-unsupervised discovering of constructive solid geometry tree. Advances in neural information processing systems 33 (2020), 8776–8786.
- Diederik P. Kingma and Jimmy Ba. 2014. Adam: A Method for Stochastic Optimization. CoRR abs/1412.6980 (2014).
- Jae Joong Lee, Bosheng Li, and Bedrich Benes. 2023. Latent L-systems: Transformerbased tree generator. ACM Transactions on Graphics 43, 1 (2023), 1–16.
- Pu Li, Jianwei Guo, Huibin Li, Bedrich Benes, and Dong-Ming Yan. 2024. SfmCAD: Unsupervised CAD Reconstruction by Learning Sketch-based Feature Modeling Operations. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. 4671–4680.
- Pu Li, Jianwei Guo, Xiaopeng Zhang, and Dong-Ming Yan. 2023. Secad-net: Selfsupervised cad reconstruction by learning sketch-extrude operations. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. 16816–16826.
- Gabrielle Littlefair, Niladri Shekhar Dutt, and Niloy J Mitra. 2025. FlairGPT: Repurposing LLMs for Interior Designs. arXiv preprint arXiv:2501.04648 (2025).
- Elie Michel and Tamy Boubekeur. 2021. DAG Amendment for Inverse Control of Parametric Shapes. ACM Transactions on Graphics 40, 4 (2021), 173:1–173:14.
- Kaichun Mo, Shilin Zhu, Angel X. Chang, Li Yi, Subarna Tripathi, Leonidas J. Guibas, and Hao Su. 2019. PartNet: A Large-Scale Benchmark for Fine-Grained and Hierarchical Part-Level 3D Object Understanding. In *The IEEE Conference on Computer Vision* and Pattern Recognition (CVPR).
- Pascal Müller, Peter Wonka, Simon Haegler, Andreas Ulmer, and Luc Van Gool. 2006. Procedural modeling of buildings. In ACM SIGGRAPH 2006 Papers. 614–623.
- Adam Paszke, Sam Gross, Soumith Chintala, Gregory Chanan, Edward Yang, Zachary DeVito, Zeming Lin, Alban Desmaison, Luca Antiga, and Adam Lerer. 2017. Automatic differentiation in PyTorch. (2017).
- Ofek Pearl, Itai Lang, Yuhua Hu, Raymond A. Yeh, and Rana Hanocka. 2022. GeoCode: Interpretable Shape Programs. arXiv:2212.11715 [cs.GR]
- Aleksander Plocharski, Jan Swidzinski, Joanna Porter-Sobieraj, and Przemysław Musialski. 2024. FaçAID: A Transformer Model for Neuro-Symbolic Facade Reconstruction. In SIGGRAPH Asia 2024 Conference Papers. 1–11.
- Charles Ruizhongtai Qi, Li Yi, Hao Su, and Leonidas J Guibas. 2017. Pointnet++: Deep hierarchical feature learning on point sets in a metric space. In Advances in neural information processing systems. 5099–5108.
- Alexander Raistrick, Lahav Lipson, Zeyu Ma, Lingjie Mei, Mingzhe Wang, Yiming Zuo, Karhan Kayan, Hongyu Wen, Beining Han, Yihan Wang, Alejandro Newell, Hei Law, Ankit Goyal, Kaiyu Yang, and Jia Deng. 2023. Infinite Photorealistic Worlds Using Procedural Generation. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. 12630–12641.
- Alexander Raistrick, Lingjie Mei, Karhan Kayan, David Yan, Yiming Zuo, Beining Han, Hongyu Wen, Meenal Parakh, Stamatis Alexandropoulos, Lahav Lipson, Zeyu Ma, and Jia Deng. 2024. Infinigen Indoors: Photorealistic Indoor Scenes using Procedural Generation. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR). 21783–21794.
- Daxuan Ren, Jianmin Zheng, Jianfei Cai, Jiatong Li, Haiyong Jiang, Zhongang Cai, Junzhe Zhang, Liang Pan, Mingyuan Zhang, Haiyu Zhao, et al. 2021. Csg-stump: A learning friendly csg-like representation for interpretable shape parsing. In Proceedings of the IEEE/CVF international conference on computer vision. 12478–12487.
- Daxuan Ren, Jianmin Zheng, Jianfei Cai, Jiatong Li, and Junzhe Zhang. 2022. Extrudenet: Unsupervised inverse sketch-and-extrude for shape parsing. In *European Conference* on Computer Vision. Springer, 482–498.
- Hou In Ivan Tam, Hou In Derek Pun, Austin T Wang, Angel X Chang, and Manolis Savva. 2024. SceneMotifCoder: Example-driven visual program learning for generating 3D object arrangements. arXiv preprint arXiv:2408.02211 (2024).
- Yonglong Tian, Andrew Luo, Xingyuan Sun, Kevin Ellis, William T. Freeman, Joshua B. Tenenbaum, and Jiajun Wu. 2019. Learning to Infer and Execute 3D Shape Programs. In International Conference on Learning Representations (ICLR).
- Mikaela Angelina Uy, Yen-Yu Chang, Minhyuk Sung, Purvi Goel, Joseph G Lambourne, Tolga Birdal, and Leonidas J Guibas. 2022. Point2cyl: Reverse engineering 3d objects from point clouds to extrusion cylinders. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. 11850–11860.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. 2017. Attention is All you Need. In Advances in Neural Information Processing Systems, I. Guyon, U. Von Luxburg,

S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (Eds.), Vol. 30. Curran Associates, Inc. https://proceedings.neurips.cc/paper_files/paper/2017/file/ 3f5ee243547dee91fbd053c1c4a845aa-Paper.pdf

- Karl D. D. Willis, Yewen Pu, Jieliang Luo, Hang Chu, Tao Du, Joseph G. Lambourne, Armando Solar-Lezama, and Wojciech Matusik. 2020. Fusion 360 Gallery: A Dataset and Environment for Programmatic CAD Reconstruction. arXiv preprint arXiv:2010.02392 (2020).
- Peter Wonka, Michael Wimmer, François Sillion, and William Ribarsky. 2003. Instant architecture. ACM Transactions on Graphics (TOG) 22, 3 (2003), 669–677.
- Rundi Wu, Chang Xiao, and Changxi Zheng. 2021. Deepcad: A deep generative network for computer-aided design models. In Proceedings of the IEEE/CVF International Conference on Computer Vision. 6772–6782.
- Xianghao Xu, Wenzhe Peng, Chin-Yi Cheng, Karl DD Willis, and Daniel Ritchie. 2021. Inferring cad modeling sequences using zone graphs. In Proceedings of the IEEE/CVF conference on computer vision and pattern recognition. 6062–6070.
- Xiang Xu, Karl DD Willis, Joseph G Lambourne, Chin-Yi Cheng, Pradeep Kumar Jayaraman, and Yasutaka Furukawa. 2022. SkexGen: Autoregressive Generation of CAD Construction Sequences with Disentangled Codebooks. In International Conference on Machine Learning. PMLR, 24698–24724.
- Yue Yang, Fan-Yun Sun, Luca Weihs, Eli VanderBilt, Alvaro Herrasti, Winson Han, Jiajun Wu, Nick Haber, Ranjay Krishna, Lingjie Liu, et al. 2024. Holodeck: Language guided generation of 3d embodied ai environments. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. 16227–16237.
- Fenggen Yu, Qimin Chen, Maham Tanveer, Ali Mahdavi Amiri, and Hao Zhang. 2023. D²CSG: Unsupervised learning of compact CSG trees with dual complements and dropouts. Advances in Neural Information Processing Systems 36 (2023), 22807–22819.
- Fenggen Yu, Zhiqin Chen, Manyi Li, Aditya Sanghi, Hooman Shayani, Ali Mahdavi-Amiri, and Hao Zhang. 2022. Capri-net: Learning compact cad shapes with adaptive primitive assembly. In Proceedings of the IEEE/CVF conference on computer vision and pattern recognition. 11768–11778.
- Yunzhi Zhang, Zizhang Li, Matt Zhou, Shangzhe Wu, and Jiajun Wu. 2024. The scene language: Representing scenes with programs, words, and embeddings. arXiv preprint arXiv:2410.16770 (2024).

A ADDITIONAL METHOD DETAILS

A.1 Objective Function

When searching for programs that explain shapes, we need an objective function to guide the search. We take inspiration from prior approaches such as [Jones et al. 2023], and formulated an objective function as a weighted average of two terms. One of these terms counts up the number of degrees of freedom in the program representation, for simplicity we treat every token in the program as a degree of freedom with the same weight (1.). Another term ensures that the produced geometry does not deviate too far from the target structure. We calculate the geometric error (more on this in the next paragraph), and add that into our objective function with a weight of 10.

The geometric error function we use takes in two sets of unordered primitives. For every pair of primitives from the predicted to target set, we calculate the maximum minimum distance between any two corners from one primitive to the other. We then use a matching algorithm to assign a stable pairing between the two sets. If any of the distances is above a threshold (0.25, where shapes are normalized to lie within the unit sphere), then we say that there is infinite geometric error. Otherwise, the geometric error is an average of the maximum minimum corner distance (MMCD), calculated according to the best match.

A.2 Network Design

We implement all of our networks in PyTorch [Paszke et al. 2017]. All of our experiments are run on NVIDIA GeForce RTX 3090 graphic cards with 24GB of VRAM. We use the Adam optimizer [Kingma and Ba 2014] with a learning rate of 1e-4. We implement our recognition network as a Transformer decoder. Our network has 4 layers, 4 heads, model dim of 256, and a full feature dim of 1024.

This network has full attention over the conditioning information: each primitive in the input shape is quantized and treated as a discrete token. We order the primitives according to their x-y-z positions, as we do not know how they should be ordered otherwise. Programs are similarly tokenized, and our network is trained through teacher forcing. We use learned positional encodings, these cap the maximum sequence lengths and primitive amounts our network can reason over: 20 primitives and programs of up to length 64. We train with a batch size of 128. For point cloud inputs, we replace the primitive token encodings with an embedding produced by a PointNet++ [Qi et al. 2017] network. For voxel inputs, we replace the primitive token encodings with an embedding produced by a 3D-CNN. We train our networks for between 4-12 hours, depending on the category and task.

A.3 Synthetic Data Sampler

We perform two rounds of automated feedback for each 'sample_shape' function generated by the *o1* LLM model. This iterative approach aims to refine the sampler's outputs by addressing discrepancies and improving alignment with respect to seed set patterns. In each round of feedback, we evaluate the function by sampling a diverse set of shapes and assessing various aspects of its behavior. We examine whether all functions in the library were used, whether all parameter types were employed, and whether all output structures described in the function's documentation were produced. These checks are performed automatically. Additionally, we analyze the structures generated by the sampled functions and determine their similarity to those observed during the validation stage. If significant deviations are detected, measured in the parameter space of each function, the sampler is instructed to update its logic to produce outputs closer to the expected structures.

B ADDITIONAL EXPERIMENTAL DETAILS

B.1 Cost and Timing

We provide detailed estimates for how expensive it is (from a time and API monetary expense perspective) to use our system to discover libraries of shape abstraction functions. To produce 20 shape descriptions from images using gpt-40: 10 cents and 1-2 minutes. To create library interfaces from textual descriptions with o1mini: 25 cents, 2-4 minutes. To propose function applications over (20) shapes with (1) o1mini call and (4) gpt-40 calls: \$2-3 and 15-25 minutes. To propose (4) implementations for each function with o1mini: \$2-4 and 15-30 minutes. To propose a single program sampler with o1: 50 cents and 1 minute. In total, this amounts to \$5-8 and 30 minutes to 1 hour.

Notice that by default we use o1mini, but sometimes deviate based on our developmental experience. Making function applications without knowing function implementations is a 'guess-based' exercise, so we are fine with the increased error rate that 40 produces in this step. For the most complex tasks, like implementing a synthetic data sampler, we turn to o1 as we are able to provide enough task guidance and directives to make use of its 'reasoning' capabilities.

B.2 Data

Collections of example shapes in the seed set are chosen by an expert user who has a design intent in mind (they also express this intent in natural language in the function descriptions). Specifically, we have the user select 20 partNet shapes and put them in a list, and then we can automatically produce the rest of the structured data from the partNet annotations. Currently, we manually render associated ShapeNet meshes in MeshLab [Cignoni et al. 2008], but this could be easily relaxed for ease of use.

After we have selected these two shapes, we create separate 'training' and 'validation' sets of shapes by randomly splitting up Partnet object instances. We run all experiments over validation shapes, unless otherwise stated, and use the training shapes to get paired data for the visual program induction step that maps from unstructured geometry to a shape abstraction program. The size of these train/val sets is 4000/1000 for chairs, 1216/400 for storage, 4000/1000 for tables, 434/400 for faucet, and 2625/656 for lamps.

B.3 LLM-Direct Baseline

The LLM-direct is an ablated version of our method that relies on only the prior of the LLM and the design intent of the expert user in the form of function descriptions. We compare against it to validate the need for using the seed set of shapes alongside the natural language specification.

This baseline, is equivalent to our method modulo a few critical changes. The interface creation step is exactly the same. After this step though, it immediately implements each function, without using any input/output guidance about how this function should constructed. As it has no seed set, it assumes that the LLM has perfectly implemented each function, and next advances to the synthetic sampler design stage where it prompts the LLM to produce a 'sample_shape' function from its constructed library. Then, like the full ShapeLib system, we can train a recognition network on data produced by this random sampling procedure.

B.4 ShapeCoder

In our comparisons against ShapeCoder we use the officially released implementation. The only change we make is removing the rotation operation from the base ShapeCoder language, as we focus on structures of axis-aligned primitives in our experiments. We develop ShapeCoder's library of abstraction over the same seed set of 20 shapes, which is much smaller than the large datasets used in the original ShapeCoder system (400 shapes). Nevertheless, we find that ShapeCoder can generalize (in terms of compression, at least) fairly well even from these 20 shapes.

We experiment with discovering ShapeCoder libraries over a larger seed set of 400 shapes, and find that compression improves slightly on validation shapes, but not by a huge margin (Obj goes from 52.1 to 46.1, while the average library size grows from 19 to 24). Despite learning this library over a large collection of shapes, we still observe that this 'ShapeCoder-400' variant does not find more semantically aligned function applications over validation structures. In fact, its semantic entropy performance worsens (chair: 1.67 to 1.84, table: 1.578 to 2.16, storage: 2.07 to 2.08, lamp: 1.7 to 1.9, faucet: 2.1 to 2.3) We view this result as lending our framing

additional support: compression alone (even over a large dataset) is not enough to develop good shape abstraction libraries, top-down semantic guidance is also required. ShapeLib: designing a library of procedural 3D shape abstractions with Large Language Models • 11



Fig. 3. Examples of functions from the shape libraries discovered by ShapeLib. For each category, we show a function implementation, and a few example applications of the function. For each application, we show the full output shape, with parts corresponding to the function marked in the same color as the function name, and the function parameters. We can see that function applications are well-aligned with part semantics and that each function typically requires only a small set of parameters to represent a rich variety of part shapes.



Fig. 4. ShapeLib's abstraction functions provide a semantically aligned and interpretable interface that support downstream applications: text-based LLM editing and visual program induction from unstructured geometry.