Uncertainty-Aware Search and Value Models: Mitigating Search Scaling Flaws in LLMs

Fei Yu, Yingru Li[†], Benyou Wang[†]

The Chinese University of Hong Kong, Shenzhen, China yufei21@outlook.com, szrlee@gmail.com, wangbenyou@cuhk.edu.cn

Abstract

Value model-guided search is effective in steering the generation but suffers from scaling flaws: Its superiority diminishes with larger sample sizes, underperforming non-search baselines. This limitation arises from reliability degradation in value models in unseen reasoning paths. To address this, we propose an uncertainty-aware search framework that includes two key components: (1) uncertaintyaware value models that incorporate uncertainty into predictions, and (2) an uncertaintyaware selection process using the proposed efficient Group Thompson Sampling algorithm. Experiments on GSM8K show that our method mitigates search scaling flaws, achieving 90.5% coverage at 16 samples compared to 85.8% for conventional value-guided search. This work establishes the first systematic integration of uncertainty quantification in LLM search paradigms.

1 Introduction

arXiv:2502.11155v1 [cs.AI] 16 Feb 2025

Test-time scaling (Brown et al., 2024; Snell et al., 2024; Wu et al., 2024) boosts performance significantly on multi-step mathematical reasoning tasks (Cobbe et al., 2021; Hendrycks et al., 2021). Value Model (VM)-guided search (Yu et al., 2024; Wan et al., 2024) efficiently solves more problems by steering the generation toward more effective reasoning paths.

However, a recent study (Yu et al., 2025) identifies scaling flaws in conventional VM-guided search: it outperforms repeated sampling (i.e. nonsearch baseline) at small sample sizes but improves more slowly, leading to inferior performance at larger sample sizes. As shown in Table 1, VMguided search surpasses repeated sampling at a sample size of 1 (75.4% v.s. 52.9%), but loses the superiority as the sample sizes increase to 8 and 16 (85.8% v.s. 90.8%). Table 1: Comparison of coverage on GSM8K: Conventional VM-guided search faces search scaling flaws, underperforming the non-search baseline (repeated sampling). Our proposed uncertainty-aware search effectively enhances the effectiveness of the search scaling.

Sample Size	1	8	16
Repeated Sampling VM-Guided Search Uncertainty-Aware Search (Ours)	$52.9\% \pm 0.6\% \\ 75.4\% \pm 0.6\% \\ 67.8\% \pm 0.4\%$	84.7% ± 0.8% 84.0% ± 0.4% 87.5% ± 0.6%	90.8% ± 0.1% 85.8% ± 0.3% 90.5% ± 0.1%

According to Yu et al. (2025), this issue arises from VM failures during the evaluation and selection of candidates in the search process. When VMs underestimate the values of promising candidates and misidentify them, the selection fails, ultimately leading to search failures.

Uncertainty-Aware Modeling To mitigate scaling flaws, it is crucial to address unreliable VM predictions at the selection stage. Since VMs rely heavily on training data, they are more likely to provide unreliable predictions when encountering unseen data during inference. This can be addressed by incorporating **uncertainty** to reflect the reliability of VM evaluations, particularly for candidates underrepresented in the training data. Intuitively, candidates less frequently seen during training have higher uncertainty, indicating lower VM reliability and greater risk of selection failures.

To capture uncertainty and develop **Uncertainty-Aware Value Models (UVMs)**, we employ Ensemble++ architecture (Li et al., 2024a,b) to model value distributions, which encapsulate the inherent uncertainty, with a more dispersed distribution indicating higher uncertainty. The trained UVM allows us to evaluate candidates while accounting for uncertainty by sampling from the value distribution.

Uncertainty-Aware Selection During Search Leveraging the accessibility to uncertainty-aware value distributions, we develop an efficient algo-

[†]Corresponding to Yingru Li and Benyou Wang.



Figure 1: Comparison of scaling laws between OVM-guided search and UVM-guided search. Our proposed uncertainty-aware search framework alleviates search scaling flaws and coverages to higher coverage than the conventional VM-guided search.

rithm for uncertainty-aware candidate selection. We propose the **Group Thompson Sampling** algorithm, an innovative extension of Thompson Sampling (Thompson, 1933; Russo et al., 2018). This algorithm selects candidates based on their probability of being the optimal choice within the candidate set, i.e. top-1 probability. This method is effective and remains efficient, without the need for explicit top-1 probability estimation. As shown in Table 1 and Figure 1, our approach outperforms the conventional VM in search scaling effectiveness.

In summary, our **contributions** are as follows: (1) We introduce an uncertainty-aware search framework that incorporates uncertainty quantification into the selection stages during the search process, enhancing the search scaling effectiveness (2) We develop uncertainty-aware value models, equipping VMs with uncertainty quantification (3) We propose the Group Thompson Sampling algorithm, enabling efficient uncertainty-aware candidate selection.

2 Background

This section first defines the problem and introduces the primary solution framework – search. Then, we introduce outcome value models employed in search, and highlight the issues associated with search and value models.

Problem definition A mathematical reasoning question q requires both the intermediate steps and the final answer as output: The solution path is represented as $S = [s^1, \ldots, s^T, a]$, where s^i is the i-th step, a is the answer, and T is the step count.

Search Search explores correct solutions more efficiently by guiding the process towards more

effective paths during the generation. This is achieved through alternating generation and selection stages. In each generation stage, K partial path candidates $\mathbb{S}^{(1:t)} = \{S_k^{(1:t)}\}_{k=1}^K$ are produced, where $S_k^{(1:t)} = [s_k^1, \dots, s_k^t]$ is the k-th partial path, and these candidates are then sent to the selection stage. The selection stage then evaluates and selects promising candidates while pruning unpromising ones. The selected candidates are passed to the next generation stage. This process continues until completion. Following Yu et al. (2025), we adopt the step-level beam search framework in this paper, which parallel explores and finally produces b solution paths. See details in Appendix A.3.

Scaling flaws Scaling sample size b or candidate size K are expected to handle more problems. However, Yu et al. (2025) observed that search suffers from scaling flaws: (1) the performance increases at a slower rate than the non-search baseline as b grows, ultimately converging to a much lower point (2) the performance remains unimproved and even degrades as K scale.

These issues stem from the failures in the selection stage, where promising paths among candidates are not identified and are improperly pruned. These arise due to the use of imperfect value models for candidate evaluation (Yu et al., 2025).

OVM and VM failures The Outcomesupervised Value Model (Yu et al., 2024) trains a value model to evaluate each candidate by predicting the probability of it reaching a correct answer. Then, it selects candidates with the highest predicted values from the set $\mathbb{S}^{(1:t)}$.

However, imperfect value models may misiden-

tify and incorrectly rank promising paths, which leads to selection failures and search scaling flaws (Yu et al., 2025).

3 Uncertainty-Aware Value Modelling

In this section, we first explain the motivation for uncertainty-aware value modelling. Then, we describe the technique used to implement the uncertainty-aware value model in Section 3.1 and how to utilize it in Section 3.2. Finally, we introduce the training process in Section 3.3.

Motivation The performance of VMs heavily depends on the training data. Quantifying uncertainty can reveal the sufficiency of similar training data. Specifically, when sufficient similar data is available in training, the VM offers low-uncertainty, reliable predictions during testing. Conversely, scarce similar data leads to high uncertainty and reduced prediction reliability. By quantifying this uncertainty and evaluating candidates in an uncertainty-aware manner, we can make more informed decisions during the search process.

3.1 Uncertainty-Aware Value Model

Ensemble++ Ensemble++ (Li et al., 2024a,b) is an ensemble-based approach that captures data uncertainty by modelling the posterior distribution. When test data resembles sufficiently seen data, the posterior distribution is concentrated; otherwise, it is more dispersed. This approach is simple to implement, requiring only a learnable linear transformation of the existing representation x. It learns to map a predefined distribution p_{ζ} , like a Gaussian, to the target posterior distribution.

UVM We borrow Ensemble++ (Li et al., 2024a,b) to model uncertainty-aware values as illustrated in Figure 2 (i). There are three processes involved in UVM: (1) representation encoding (2) index sampling (3) index mapping

Representation encoding: The last hidden states from a LLM backbone (parameterized by θ) serve as the representation x. Specifically, for a given question q and a partial path $S^{(1:t)}$, the representation x is obtained as:

$$\mathbf{x} = \text{LLM}(q, S^{(1:t)}; \boldsymbol{\theta}) \tag{1}$$

Index sampling: This process samples an index from the predefined distribution, i.e. $\zeta \sim p_{\zeta}$

Index mapping: The index is mapped to the posterior value by summing a mean value term and

an uncertainty term: ¹

$$v = \underbrace{\mathbf{xb}}_{\text{mean estimator}} + \underbrace{\mathbf{x}(\mathbf{W} + \mathbf{W}_0)\boldsymbol{\zeta}^T}_{\text{uncertainty estimator}}$$
(2)

Through these processes, a trained UVM maps the predefined distribution p_{ζ} to the posterior value distribution $p(v|q, S^{(1:t)})$.

Additional parameters Here, $\mathbf{W}^{d \times m}$ and $\mathbf{b}^{d \times 1}$ are learnable parameters, while $\mathbf{W}_0^{d \times m}$ are frozen parameters that are randomly initialized. *d* represents the dimension of the backbone's hidden states $\mathbf{x}^{1 \times d}$. *m* is a hyperparameter for the dimension of the index $\zeta^{1 \times m}$. Notably, UVM is simple and straightforward to implement on top of OVM, requiring only an additional linear transformation.

UVM architectural insight It extends conventional approaches through a dual-branch architecture, as shown in Figure 2:

- Deterministic Branch (blue): Maintain standard value estimation, equivalent to OVM
- Uncertainty Branch (orange): Learn distribution through ensemble perturbations

Intuitive explanation UVM can be regarded as a last-layer ensemble of *m* components, controlled by the index vector $\zeta^{1 \times m}$: (1) When $\zeta^{1 \times m}$ is a zero vector [0, ..., 0], UVM retains only the deterministic branch, degenerating to OVM (2) When $\zeta^{1 \times m}$ is a one-shot index vector, with a 1 in the *i*-th position and 0s elsewhere, it queries the *i*-th component for the prediction (3) When $\zeta^{1 \times m}$ is a non-one-shot vector, it is equivalent to use a linear combination of the *m* components.

3.2 Accessing Values

Although the explicit formalization of $p(v|q, S^{(1:t)})$ is unavailable, we can sample values and compute the distribution's mean and standard deviation.

Sampling from posterior value distribution To derive a posterior value, we (1) sample an index $\zeta \sim p_{\zeta}$ and (2) map it to the value sample v using Equation 1-2. Notably, deriving multiple posterior values only requires one-time representation encoding, i.e. forward pass through the LLM backbone (Equation 1), followed by multiple posterior value mappings (Equation 2) with repeated index sampling and mapping.

¹For simplicity, we present the main expression and omit the hyperparameters involved in the practical implementation. Details on the practical implementation can be found in A.2.



Figure 2: Illustration of the UVM structure, value learning process, and its relationship to OVM: (i) This figure shows how UVM extends OVM by adding uncertainty with minimal additional parameters. The blue branch represents OVM, which computes a mean value for a sequence. The orange branch introduces the uncertainty term in UVM, calculated using parameters W and W₀. This uncertainty term varies with the input index ζ , leading to diverse posterior value samples. The process of using UVM is simple: UVM derives a mean value like OVM, but also samples from a fixed distribution and adds the uncertainty term. (ii)-(iii) For training, UVM uses the same training set as OVM, but samples 2m posterior values $[v_1, \ldots, v_{2m}]$ using a discrete coordinate distribution $[e_1, \ldots, e_{2m}]$, rather than estimating a single value. The model is trained by averaging the MSE over these posterior samples.

Capturing the distribution's mean and standard deviation The mean is obtained by using a zero vector as the index ζ and mapping it. The standard deviation is estimated by sampling multiple posterior values, which involves repeated index sampling and mapping.

3.3 Uncertainty-Aware Value Learning

UVM does not require any additional training data and can use the same training dataset as OVM. The training dataset construction is described in Appendix A.1, which consists of $(q, S^{(1:T)}, y)$ tuples, where y denotes the correctness of the final answer.

Given the same training dataset, the key difference in value learning between OVM and UVM lies in their training objectives:

Training loss of OVM OVM learns single-point estimates (Figure 2 (iii)). Its loss is the Mean Squared Error (MSE) with respect to the binary label y, for each $(q, S^{(1:T)}, y)$ tuple:

$$L^{\text{OVM}}(q, S^{(1:T)}, y) = \sum_{t=1}^{T} (\text{OVM}(q, S^{(1:t)}) - y)^2$$
(3)

where $\text{OVM}(\cdot)$ evaluates and maps a given partial path $S^{(1:T)}$ and the question q to a value scalar.

Training loss of UVM UVM is learning a posterior value distribution, which complicates its learning (Figure 2 (iii)). Following Ensemble++ (Li et al., 2024a,b), a discrete coordi-

nate distribution is used in training. This distribution consists of 2m one-hot index vectors $[e_1, \ldots, e_m, e_{m+1}, \ldots, e_{2m}]$. For each $i = 1, \ldots, m$, the *i*-position of e_i is 1, while of e_{m+i} is -1, with 0s elsewhere. The training loss for each $(q, S^{(1:T)}, y)$ tuple is

$$L^{\text{UVM}}(q, S^{(1:T)}, y) = \sum_{t=1}^{T} \frac{1}{2m} \sum_{i=1}^{2m} (\text{UVM}(q, S^{(1:t)}, \boldsymbol{e}_i) - y)^2 \quad (4)$$

Notably, the gradients of the term \mathbf{W} are stopped to prevent them from propagating to the backbone parameters $\boldsymbol{\theta}$.

Explanation on the learning process Under this objective, the posterior uncertainty term W learns to offset the random prior W_0 , while the parameters b focus on modeling the mean of the posterior distribution. When posterior learning is sufficient, the posterior uncertainty term W reduces the noise introduced by the prior W_0 , leading to a low-variance posterior distribution. If learning is insufficient, the prior W_0 dominates, causing a high-variance posterior distribution.

4 Uncertainty-Aware Selection

This section describes (1) the implementation of posterior value sampling during inference and (2) uncertainty-aware selection with the accessibility to the posterior value distribution. We propose a novel algorithm, Group Thompson Sampling, to effectively and efficiently select multiple candidates. **Posterior value sampling of UVM during inference** Following Ensemble++ (Li et al., 2024a,b), a *m*-dimensional continuous Gaussian distribution is used as the index distribution p_{ζ} to access the expressive posterior value distribution during inference, as described in Section 3.2. Intuitively, we are training *m* individual components during value learning, and then combine them linearly to make predictions during inference.

Top-1 probability for candidate selection For each step t, we evaluate and rank K candidates in the set $\mathbb{S}^{(1:t)}$ based on their posterior value distribution. Specifically, we assess the probability of each candidate being the best, i.e. the likelihood of it having the highest value, within the set, referred to as the top-1 probability

$$p(S_i^{(1:t)} \text{ is the best among } \mathbb{S}^{(1:t)})$$

$$= \mathbb{E}_{v_i \sim p(v|q, S_i^{(1:t)}), v_j \sim p(v|q, S_j^{(1:t)}) \ \forall j \neq i} \left[\prod_{j \neq i} \mathbb{I}(v_i \ge v_j) \right]$$
(5)

We perform candidate selection by sampling from the top-1 probability distribution

$$S^{(1:t)} \sim p(S^{(1:t)} \text{ is the best among } \mathbb{S}^{(1:t)})$$
 (6)

We use top-1 probability for candidate selection instead of the well-known Upper Confidence Bound (UCB) 2 for two main reasons:

- Top-1 probability better captures the distribution's characteristics, balancing mean and variance. In candidate selection, it is important to balance the predicted mean value with the uncertainty (i.e., the distribution's variance). Candidates with extreme uncertainty will be prioritized by UCB, potentially overlooking the mean value prediction in such cases. In contrast, top-1 probability provides a more balanced approach that not overemphasizes uncertainty.
- *Top-1 probability inherently ranks candidates against each other*. UCB evaluates each candidate independently, without considering its relation to others. In contrast, top-1 probability intrinsically compares each candidate to all others in the set, ranking them based on the likelihood of being the best in the set.

However, explicitly estimating the top-1 probability for each candidate requires multiple posterior value samples, which involves repeated index sampling and mapping. This process can be computationally expensive.

Group Thompson Sampling: An efficient algorithm for group selection based on top-1 probability Group Thompson Sampling is an extension of the Thompson sampling algorithm, designed to efficiently select a group of candidates based on their top-1 probability. Thompson sampling (Thompson, 1933; Russo et al., 2018) is a straightforward method for selecting a single candidate, by performing one posterior sampling and choosing the one with the highest sampled value

$$v_i \sim p(v|q, S_i^{(1:t)}), \forall i$$

$$S_i^{(1:t)} = \operatorname*{argmax}_i v_i$$
(7)

To extend this for selecting multiple candidates, we introduce Group Thompson Sampling algorithm in Algorithm 1. This method repeats Thompson sampling b times to select b candidates, incorporating a mechanism to avoid duplication.

Algorithm 1 Group Thompson Sampling		
	Input: Question q , candidates $\{S_1, \ldots, S_K\}$, sample size b	
	Output: <i>b</i> selected candidates	
	Model: UVM	
	Hyperparameter: Maximum tries T^{max}	
1:	Sample index $\xi \sim p_{\xi}$ and select $i =$	
	$\underset{i=1,\dots,K}{\operatorname{argmax}} \operatorname{UVM}(S_i; q, \xi)$	
2:	Initialize selected set $\mathcal{I} \leftarrow \{i\}$	
3:	repeat	
4:	Sample $\xi \sim p_{\xi}$ and select $i =$	
	$\operatorname{argmax} UVM(S_i; q, \xi)$	
	i=1,,K	
5:	Add <i>i</i> to \mathcal{I} if $i \notin \mathcal{I}$; otherwise try 4 again	
6:	After T^{max} tries, instead sample non-repeated <i>i</i> uni-	
	formly	
7:	until there are b selected candidates	
	return $\{S_i i \in \mathcal{I}\}$	

Algorithmic innovation Group Thompson Sampling addresses two key challenges in uncertaintyaware search:

- Computational efficiency: Avoid explicit top-1 probability estimation through smart sampling
- *Comprehensive selection range*: Ensure that candidates with varying levels of uncertainty are appropriately considered for selection through an uncertainty-aware stochastic selection mechanism

²UCB scores each candidate using the sum of an exploitation term and an exploration term, i.e. the sum of mean values and standard variation in our case.

5 Experiment Results

This section outlines our experiment settings and presents the results of overall performance and ablation studies.

5.1 Experimental Settings

Benchmarks and models We conduct experiments on GSM8K (Cobbe et al., 2021) using Mistral 7B (Jiang et al., 2023). We use the official training split and test split for all the experiments.

Baselines We compare our method, UVMguided search, with two baselines: (1) repeated sampling, which directly samples multiple solution paths without any search mechanism, and (2) conventional OVM-guided search, which does not incorporate uncertainty.

Evaluation Following the study of search scaling flaws (Yu et al., 2025), we evaluate our method using coverage – the fraction of problems whose correct solutions for which the correct solution is covered by the generated paths, i.e., at least one sampled path is correct. This metric is also referred to as pass@k, where k denotes the number of generated paths. ³

Scaling beam search Yu et al. (2025) observes scaling flaws related to both sample sizes and candidate sizes. We also investigate the effectiveness of our methods on with respect to these two factors:

Sample size: This refers to the number of complete solution paths generated by the algorithm. For beam search, it corresponds to the beam size b, while for repeated sampling, it is the number of attempts. We consider sample sizes of 1, 2, 4, 8, 16, and 32. For beam search experiments, we fix the number of generated paths per beam K/b at 8.

Candidate size: This represents the number of candidates considered during the search process. In these experiments, we fix the sample size at 16, where OVM-guided search underperforms repeated sampling. We conduct experiments with candidate sizes of 32, 64, 128, and 256.

Each experiment is repeated three times, and we report the average coverage along with its standard deviation.

5.2 Implementation

Training generators We train the base models (i.e. Mistral 7B) on the official training set. We use the newline character as the marker for the end of each step. Supervised fine-tuning is performed for 2 epochs with a batch size of 128. We use a linear learning rate scheduler with a maximum learning rate of 2e-6. The AdamW optimizer (Loshchilov and Hutter, 2019) is used for training.

Building training dataset for UVMs The dataset construction process is introduced in Appendix A.1. We sample 50 solution paths per problem in the training set. We use a decoding temperature of 0.7 and top-k set to 50 for dataset collection. The maximum new token length is 400. We apply vllm (Kwon et al., 2023) to accelerate the generation process.

Training UVMs/OVMs To construct UVMs, we set the number of components to 10. UVMs are initialized from the corresponding generator checkpoints and trained for one epoch, using the same backbone learning rate scheduler. The maximum learning rate for the uncertainty-aware value head is set to 2e-3, with a batch size of 128. The optimizer used for training is AdamW. After training, we derive OVMs by setting $\zeta = 0$.

Step-level beam search The hyperparameters for decoding are consistent with those used in the UVMs' training dataset collection. The maximum number of steps is 10.

5.3 Overall Performance

We present the overall performance in Figure 1, showing that UVM-guided search consistently outperforms conventional OVM-guided search both when scaling sample sizes and scaling candidate sizes.

Scaling flaws UVM-guided search mitigates the scaling flaws of conventional VM-guided search. As shown in Figure 1(a), VM-guided search leads to over 20% higher coverage than repeated sampling when the sample size is 1. However, its advantage diminishes as the sample size scales to 8. In contrast, our UVM-guided search continues to outperform repeated sampling at this sample size and remains comparable even at a sample size of 16.

Moreover, as shown in Figure 1(b), the performance of conventional VM-guided search deterio-

 $^{^{3}}$ In our paper, K represents the candidate size during the intermediate search process, rather than the number of final produced paths. To avoid confusion, we use the term "coverage".

rates significantly as the candidate size scales. In contrast, UVM-guided search efficiently mitigates this issue, resulting in a 5.5% performance improvement over VM-guided search at the largest tested candidate size, 256.

Convergent points of coverage UVM-guided search ultimately converges to higher coverage than conventional VM-guided search. As illustrated in Figure 1(a), UVM-guided search outperforms conventional VM-guided search once the sample size increases to 4. It reaches the performance comparable to the best result of conventional VM-guided search (among all tested sample sizes) using only 25% of its budget. Furthermore, it ultimately achieves 4.2% higher coverage at the largest tested sample size, 32.

These results highlight the effectiveness of our method in enhancing search scaling.

5.4 Ablation Study

In this section, we conduct ablation studies on the design choices of uncertainty-aware selection and demonstrate the superiority of the Group Thompson Sampling algorithm in Figure 3.

Baselines We consider two deterministic baselines for uncertainty-aware selection: UCB ranking and the naive top-1 probability ranking.

UCB ranking: UCB scores each candidate by summing the mean and standard deviation of the posterior value distribution, which are computed using 100,000 sampled posterior values. Then, candidates with the highest UCB scores are selected.

Naive top-1 probability ranking: This method explicitly calculates the probability of each candidate being the best, as described in Equation 5, using 100,000 sampled posterior values. It ranks and selects candidates based on the highest probabilities, rather than sampling from the probability distribution.

Top-1 probability ranking v.s. UCB ranking *Top-1 probability is better for candidate evaluation.* As shown in Figure 3, UCB ranking performs poorly, even underperforming the conventional OVM baseline. In contrast, the top-1 probability ranking surpasses the UCB, highlighting the effectiveness of using top-1 probability for candidate evaluation.

Group Thompson Sampling v.s. top-1 probability ranking Group Thompson Sampling is an effective algorithm for uncertainty-aware selection. As illustrated in Figure 3, our proposed Group Thompson Sampling algorithm achieves higher coverage than the naive top-1 probability ranking. Furthermore, by sampling candidates according to the underlying top-1 probability distribution, Group Thompson Sampling eliminates the need for explicit top-1 probability estimation, making it more efficient.

These results show the superiority of our Group Thompson Sampling algorithm: It achieves significantly higher coverage than the other baselines while requiring fewer computations.



Figure 3: Ablation on design choices of uncertaintyaware selection

6 Analysis

In this section, we conduct in-depth analyses of VM selection failures, which are the underlying causes of search scaling flaws (Yu et al., 2025). Specifically, we investigate the effectiveness of UVM in mitigating selection failures across various sparsity of correct paths among candidates.

Selection stages We define a selection stage as comprising three key components: (1) the candidate set (2) the evaluation scores assigned to each candidate (3) the selected candidates from the set.

The presence of correct paths within the candidate set depends on the quality of candidates generated during the generation stage. In this section, we focus on the effectiveness of the selection stages and exclude issues related to the generation stages. Therefore, we only consider those selection stages where correct paths are present within the candidate set. **Selection failures** When correct paths are present in the candidate set, a selection failure is identified if none of the correct paths are selected.

In this section, we analyze the distribution of selection failures and compare the effectiveness of UVM and OVM across various scenarios.

Experimental Setup We extract all selection stages during the OVM-guided search with b = 8, K = 64, as this setup begins to experience scaling issues while retaining a reasonable computational cost for correct path labeling and target selection stage identification.

Correct path labeling To identify the correct candidate paths, we complete each partial path by rolling out 4 samples and checking whether any of them reach the correct answer. A candidate is deemed a correct path if at least one of its rollouts leads to the correct final answer.

Target selection stage identification Given the correctness of all candidate paths across all selection stages, we can filter all the selection stages where correct paths are available among the candidate set for the subsequent studies.

Analysis on Correct Path Sparsity *Correct path sparsity* refers to the fraction of correct paths within the candidate set. As sparsity increases—i.e., fewer correct paths are present among the candidates—identifying the correct paths becomes more challenging for VMs (Yu et al., 2025).

Similar to the analysis in Yu et al. (2025), we categorize the correct path sparsity of all targeted selection stages (where correct paths are available) into three uniform groups. We then apply both OVM and UVM selection to the candidate sets within these stages. Then we plot the distribution of selection failures, where no correct path is identified, across the three sparsity groups in Figure 4.

UVM is effective across all correct path sparsity groups. As shown in Figure 4, UVM consistently reduces the frequency of selection failures across all sparsity groups. Specifically, it reduces selection failures by 6% in the low-sparsity group, 6% in the medium-sparsity group, and 14% in the highsparsity group.

UVM is most effective in high-sparsity regimes. Notably, although higher correct path sparsity increases the difficulty of the selection task, UVM continues to perform well, and even offers greater benefits in reducing selection failures in highsparsity regimes (14% failure reduction). This demonstrates its ability to retain high-uncertainty yet potentially correct paths that conventional models would typically discard prematurely.



Figure 4: Comparison of failures frequency between OVM selection and UVM selection, across various correct path sparsity

7 Discussion

Quantifying uncertainty in current search-based methods has several practical implications for LLM reasoning tasks as follows: (1) Discovering correct solutions: Correct solutions may lie along paths that are underrepresented in the training data. By incorporating uncertainty, our approach increases the likelihood of discovering these solutions. (2) Improved performance with limited resources: Uncertainty-aware search methods enhance performance without a significant increase in computational resources. This is because the process of quantifying uncertainty is computationally inexpensive. (3) Adaptability to real-world applications: Real-world applications often encounter outof-distribution data. Methods that account for uncertainty are better equipped to handle such cases, enabling more reliable performance in deployment scenarios where the data may differ from training distributions.

8 Conclusion

VM-guided search suffers from search scaling flaws due to the use of imperfect VMs, which could produce unreliable predictions when the evaluated data is underrepresented in the training data. To address these issues, we propose an uncertainty-aware search framework, including training uncertaintyaware VMs and applying uncertainty-aware selection during the search. Experiment results in GSM8K show the effectiveness of our methods.

Limitation

While uncertainty can indicate the reliability of VM predictions, it alone cannot guarantee correct predictions. This highlights that, although uncertainty can be useful, effective selection still heavily depends on the performance of the VMs. In scenarios where VMs perform poorly, such as in the more challenging MATH dataset (Hendrycks et al., 2021), uncertainty alone offers limited assistance and proves ineffective. In such scenarios, improving the quality of the VMs should be prioritized over merely equipping them with uncertainty qualifications. Besides, uncertainty does not fully capture the accuracy of value predictions. It is possible for a low-uncertainty prediction to still be incorrect, a scenario that is not addressed in this paper.

References

- Bradley C. A. Brown, Jordan Juravsky, Ryan Saul Ehrlich, Ronald Clark, Quoc V. Le, Christopher Ré, and Azalia Mirhoseini. 2024. Large language monkeys: Scaling inference compute with repeated sampling. *CoRR*, abs/2407.21787.
- Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021. Training verifiers to solve math word problems. *CoRR*, abs/2110.14168.
- Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021. Measuring mathematical problem solving with the MATH dataset. In Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmarks 1, NeurIPS Datasets and Benchmarks 2021, December 2021, virtual.
- Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de Las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Lélio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. 2023. Mistral 7b. CoRR, abs/2310.06825.
- Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph Gonzalez, Hao Zhang, and Ion Stoica. 2023. Efficient memory management for large language model serving with pagedattention. In *Proceedings of the 29th Symposium on Operating Systems Principles, SOSP 2023, Koblenz, Germany, October 23-26, 2023*, pages 611– 626. ACM.
- Yingru Li, Jiawei Xu, Lei Han, and Zhi-Quan Luo. 2024a. Q-star meets scalable posterior sampling:

Bridging theory and practice via hyperagent. In *Forty-first International Conference on Machine Learning, ICML 2024, Vienna, Austria, July 21-27, 2024.* OpenReview.net.

- Yingru Li, Jiawei Xu, Baoxiang Wang, and Zhi-Quan Luo. 2024b. Scalable thompson sampling via ensemble++ agent. *Preprint*, arXiv:2407.13195.
- Ilya Loshchilov and Frank Hutter. 2019. Decoupled weight decay regularization. In 7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019. OpenReview.net.
- Daniel Russo, Benjamin Van Roy, Abbas Kazerouni, Ian Osband, and Zheng Wen. 2018. A tutorial on thompson sampling. *Found. Trends Mach. Learn.*, 11(1):1–96.
- Charlie Snell, Jaehoon Lee, Kelvin Xu, and Aviral Kumar. 2024. Scaling LLM test-time compute optimally can be more effective than scaling model parameters. *CoRR*, abs/2408.03314.
- William R Thompson. 1933. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25(3-4):285–294.
- Ziyu Wan, Xidong Feng, Muning Wen, Stephen Marcus McAleer, Ying Wen, Weinan Zhang, and Jun Wang. 2024. Alphazero-like tree-search can guide large language model decoding and training. In Fortyfirst International Conference on Machine Learning, ICML 2024, Vienna, Austria, July 21-27, 2024. Open-Review.net.
- Yangzhen Wu, Zhiqing Sun, Shanda Li, Sean Welleck, and Yiming Yang. 2024. Inference scaling laws: An empirical analysis of compute-optimal inference for problem-solving with language models. *arXiv preprint arXiv:2408.00724*.
- Fei Yu, Anningzhe Gao, and Benyou Wang. 2024. Ovm, outcome-supervised value models for planning in mathematical reasoning. In *Findings of the Association for Computational Linguistics: NAACL 2024, Mexico City, Mexico, June 16-21, 2024*, pages 858– 875. Association for Computational Linguistics.
- Fei Yu, Yingru Li, and Benyou Wang. 2025. Scaling flaws of verifier-guided search in mathematical reasoning. *arXiv preprint arXiv:2502.00271*.

A Appendix

Table 2: Summary of Notations Used in the Paper

Notation	Description
q	Mathematical reasoning question requiring a sequence of steps
S	Solution path for a question, $S = [s^1, \dots, s^T, a]$
s^i	<i>i</i> -th step in a solution path
a	Final answer in a solution path
T	Number of steps in a solution path
y	Binary label (0 or 1) indicating the correctness of a
$S^{(1:t)}$	Partial solution path up to step $t, S^{(1:t)} = [s^1, \dots, s^t]$
$S^{(1:t)}$	Set of candidate partial paths $\mathbb{S}^{(1:t)} = \{S_k^{(1:t)}\}_{k=1}^K$
K	Candidate size
b	Beam size
v	Value (scalar) of a partial path
$p(v q, S^{(1:t)})$	Posterior distribution of values for a partial path
m	Number of components in UVM head
\mathbf{W}, \mathbf{b}	Learnable parameters of UVM head
\mathbf{W}_0	Fixed parameters of UVM head
θ	Parameters of the value model backbone
d	Dimension of value model backbone's hidden states
x	Last hidden states output by VM's backbone
ζ	Index vector of dimension m
p_{ζ}	Index distribution

A.1 Construction of VMs' Training Dataset

The training dataset is created using the generator and the question-answer pairs. For each pair $(q, a) \in Q$, the generator produces n solution paths, resulting in a total of $|Q| \times n$ question-solution pairs. The label y for each solution S is assigned based on the correctness of the final answer, which is determined by comparing it to the ground truth answer a. A label of 1 indicates the answer is correct, while 0 indicates it is incorrect. This process forms a training dataset consisting of (q, S, y) tuples for value model training.

A.2 Detailed UVM Structure

Given the representation \mathbf{x} , the sampled index $\boldsymbol{\zeta}$ is mapped to the posterior value sample as:

$$v = \underbrace{\mathbf{xb}}_{\text{mean estimator}} + \underbrace{\mathbf{x}(u\mathbf{W} + p_0\mathbf{W}_0)\boldsymbol{\zeta}^T}_{\text{uncertainty estimator}}$$
(8)

Here, u and p_0 are hyperparameters. Specifically, u controls the tradeoff between the uncertainty terms W, W_0 and the mean value term b, and p_0 controls the tradeoff between the posterior term W and the prior term W_0 .

A.3 Step-Level Beam Search

The algorithm is shown in Algorithm 2.

Algorithm 2 Step-Level Beam Search

	mum step count T^{max}
	Output: \hat{b} solution sequences for q
	Model: Generator and VM
1:	Initialize sequences $\mathbb{S} \leftarrow \{\}$
2:	Sample the first steps $\{s_1^1, \ldots, s_K^1\}$
3:	Select b steps via SELECTION $(q, \{s_1^1, \ldots, s_K^1\}, b, VM)$
	and add to \mathbb{S}
4:	$t \leftarrow 1$
5:	while any sequence of S is not complete and $t < T^{max}$
	do
6:	$\mathbb{S}_{\text{next}} \leftarrow \{\}$
7:	for $S^{(1:t)}$ in \mathbb{S} do
8:	for $i = 1$ to K/b do
9:	$S_i^{(1:t+1)} = \text{Generator}(S_i^{(1:t)}; q)$
10:	$\mathbb{S}_{\text{next}} \leftarrow \mathbb{S}_{\text{next}} + S_i^{(1:t+1)}$
11:	$\mathbb{S} \leftarrow \text{SELECTION}(q, \mathbb{S}_{\text{next}}, b, \text{VM})$
12:	$t \leftarrow t + 1$

Input: Question q, Beam size b, Candidate size K, Maxi-

return S