BOLIMES: Boruta–LIME optiMized fEature Selection for Gene Expression Classification

Bich-Chung Phan¹, Thanh Ma¹, Huu-Hoa Nguyen¹, and Thanh-Nghi Do¹

Can Tho University, Vietnam {pbchung,mtthanh,nhhoa,dtnghi}@ctu.edu.vn

Abstract. Gene expression classification is a pivotal yet challenging task in bioinformatics, primarily due to the high dimensionality of genomic data and the risk of overfitting. To bridge this gap, we propose BOLIMES, a novel feature selection algorithm designed to enhance gene expression classification by systematically refining the feature subset. Unlike conventional methods that rely solely on statistical ranking or classifier-specific selection, we integrate the robustness of Boruta with the interpretability of LIME, ensuring that only the most relevant and influential genes are retained. BOLIMES first employs Boruta to filter out non-informative genes by comparing each feature against its randomized counterpart, thus preserving valuable information. It then uses LIME to rank the remaining genes based on their local importance to the classifier. Finally, an iterative classification evaluation determines the optimal feature subset by selecting the number of genes that maximizes predictive accuracy. By combining exhaustive feature selection with interpretability-driven refinement, our solution effectively balances dimensionality reduction with high classification performance, offering a powerful solution for high-dimensional gene expression analysis.

Keywords: Image Classification \cdot Gene Expression \cdot Boruta \cdot LIME \cdot Feature Selection

1 Introduction

Gene expression classification [1,17,9,10,18] has emerged as a fundamental tool in bioinformatics, enabling the identification of disease subtypes, prediction of patient outcomes, and discovery of potential therapeutic targets. With the advent of high-throughput sequencing technologies, researchers can now analyze vast gene expression profiles across thousands of genes simultaneously. However, this progress comes with a significant computational and analytical challenge: the **curse of dimensionality** [22,2]. In typical gene expression datasets, the number of genes (p) far exceeds the number of samples (n), often by several orders of magnitude. This imbalance leads to severe overfitting in machine learning models, where classifiers struggle to generalize due to the overwhelming presence of irrelevant or redundant features. Additionally, the high dimensionality increases computational complexity, making conventional classification models inefficient and impractical for real-world applications.

To address these challenges, **feature selection** plays a critical role in gene expression classification. By identifying and retaining only the most informative genes, feature selection not only improves model generalization but also enhances interpretability, allowing researchers to derive biologically meaningful insights from machine learning predictions [9,20]. Furthermore, reducing the feature space significantly lowers computational costs, enabling faster model training and inference. More importantly, gene selection aligns with the biological reality that only a subset of genes actively contributes to disease mechanisms, making feature selection a crucial step in biomedical analysis. Without an effective selection strategy, classifiers are prone to noise, reduced accuracy, and difficulty in extracting meaningful biomarkers for clinical applications.

Given the importance of feature selection, extensive research has been conducted to develop robust selection techniques tailored for gene expression data. Traditional methods include filter-based approaches [11,5,8,26], which rely on statistical measures such as mutual information, correlation, and entropy to rank features independently of the classifier. Although computationally efficient, filter methods often fail to capture complex gene interactions. Wrapper-based methods [3,33,21,28], such as recursive feature elimination (RFE) [7,34] and genetic algorithms [25], iteratively refine feature subsets based on classifier performance but tend to be computationally expensive for high-dimensional data. Meanwhile, embedded techniques [19,31,16], such as LASSO [13,29] and tree-based models [14,27], integrate feature selection within the classification process but may not always provide optimal feature subsets for different classifiers. Despite these advancements, no single approach consistently outperforms others across all gene expression datasets, necessitating hybrid strategies that leverage the strengths of multiple selection paradigms.

To bridge this gap, we propose BOLIMES (Boruta–LIME Enhanced eXtraction), a novel feature selection algorithm designed to enhance gene expression classification by systematically refining the feature subset. Unlike conventional methods that rely solely on statistical ranking or classifier-specific selection, BOLIMES integrates the robustness of Boruta [24,36] with the interpretability of LIME [30], ensuring that only the most relevant and influential genes are retained. BOLIMES first applies Boruta, a powerful wrapper method that iteratively refines feature sets by comparing real genes against randomly permuted shadow features, ensuring that no informative gene is prematurely discarded. Then, LIME [30,23] (Local Interpretable Model-agnostic Explanations) is employed to assess the local importance of each selected gene, providing an interpretable ranking of features that capture model-specific contributions. Finally, an iterative classification evaluation determines the optimal feature subset by selecting the number of genes that maximize predictive accuracy. By integrating Boruta's exhaustive feature selection with LIME's interpretability-driven refinement, BOLIMES effectively balances dimensionality reduction with model performance, making it a powerful solution for high-dimensional gene expression analysis.

The remainder of this paper is structured as follows: we briefly presents a fundamental background in Section 2. Next, Section 3 describes our proposal algorithm. Then, Section 4 represents the experiment, the results of the models and an discussion. Finally, Section 5 shows the conclusions and future work.

2 Background

In this section, we present the foundation of our approach with integrating Boruta and Lime. We also provide the ML algorithm that will be used for the gene expression classification task.

2.1 Gene Expression Classification with ML models

Gene expression classification [9,10,18] lies at the forefront of biomedical research, offering profound insights into the molecular mechanisms underlying various diseases. ML models have become indispensable in this domain, as they can uncover complex patterns within vast and high-dimensional gene expression datasets. However, these datasets often contain a plethora of features, many of which are redundant or irrelevant, potentially obscuring the most critical biological signals and leading to overfitting. Consequently, feature selection becomes imperative—it refines the dataset by isolating the most informative genes, thereby enhancing model accuracy, interpretability, and computational efficiency. By focusing solely on the pivotal biomarkers, this research is able to achieve more reliable predictive outcomes. In this paper, we investigate and evaluate the classification with various ML techniques. Namely, we experiment our selected features with ML algorithms, i.e., SVM [32], Random Forest [4], XGB [6], Gradient Boosting [15].

Definition 1 (Classification). Let D = (X, y) be a dataset where $X \subseteq \mathbb{R}^n$ is the feature space and $y \in \mathcal{Y} = \{1, 2, ..., k\}$ represents the class labels. A classifier is a function

 $f: X \to \mathcal{Y},$

that assigns a predicted label $\hat{y} = f(x)$ to each input $x \in X$. The function f is learned from the labeled examples

$$D = \{ (x_i, y_i) \mid x_i \in X, y_i \in \mathcal{Y}, i = 1, ..., N \},\$$

by minimizing a loss function $\ell : \mathcal{Y} \times \mathcal{Y} \to \mathbb{R}_{\geq 0}$ that quantifies the error between the predicted and true labels. Once trained, f is used to classify new, unseen inputs.

While numerous feature selection techniques exist, our study concentrates on two: Boruta and LIME. We choose Boruta for its robust ability to identify all truly relevant features within high-dimensional datasets, ensuring that no significant predictor is overlooked. Complementing this, LIME is employed for its

exceptional capacity to provide local, interpretable explanations of model predictions, which is crucial when assessing feature importance through numerous distance calculations. Together, these methods offer a powerful and efficient approach to refining our gene expression classification models. Now, we introduce Boruta and Lime in the next session.

2.2 Leveraging Boruta for Robust Feature Extraction

Boruta [24,36] is a powerful wrapper-based feature selection algorithm designed to identify all truly relevant variables in a dataset. By comparing the importance of actual features with that of randomly generated "shadow" features, Boruta systematically filters out irrelevant variables while preserving essential predictors. This rigorous selection process is particularly valuable in high-dimensional applications, such as gene expression classification, where capturing meaningful signals is crucial. Rather than directly improving predictive accuracy, Boruta refines the feature set, which can indirectly enhance model interpretability and performance. For clarity, we formally define Boruta as follows:

Definition 2 (Boruta Feature Selection). Let D = (X, y) be a dataset with features $X = \{x_1, x_2, ..., x_p\}$ and target y. The Boruta algorithm identifies all relevant features in X as follows:

- 1. Shadow Feature Generation: For each $x_i \in X$, create a shadow feature x_i^{shadow} by randomly permuting its values, forming the set X^{shadow} .
- 2. Importance Estimation: Train a classifier (e.g., Random Forest) on the combined set $X \cup X^{shadow}$ and compute the importance score I(z) for each z.
- 3. Feature Comparison: For each x_i , define

$$I_{\max}^{shadow} = \max_{z \in X^{shadow}} I(z).$$

Then classify x_i as relevant if $I(x_i)$ is significantly greater than I_{\max}^{shadow} , irrelevant if significantly lower, or tentative otherwise.

4. Iteration: Remove irrelevant features and repeat until all features are decisively classified.

The final selected subset $X^* \subseteq X$ comprises all features deemed relevant.

2.3 XAI for Feature Selection

Explainable AI (XAI) [12,35] represents a forefront of AI research, aiming to elucidate the decision-making processes of complex models. In the context of gene expression classification, where feature selection is pivotal to model performance and interpretability, our study leverages LIME—Local Interpretable Model-Agnostic Explanations—to demystify and extract critical features. LIME approximates the behavior of a sophisticated, black-box model with a simpler, locally interpretable surrogate, thereby pinpointing the most influential predictors in the vicinity of a given instance. This approach enhances the transparency of the model's predictions and facilitates a more informed and rigorous feature selection process, ultimately contributing to both improved accuracy and trustworthiness of the classification system. Now, we provide a formal definition of LIME as follows:

Definition 3 (LIME-based Feature Selection). Let $D^* = (X^*, y)$ be the dataset resulting from Boruta, where $X^* \subseteq \mathbb{R}^{p^*}$ is the set of relevant features. Given a trained black-box classifier $f : X^* \to \mathcal{Y}$ and an instance $x \in X^*$, LIME constructs an interpretable surrogate model $g \in G$ (typically linear), expressed as

$$g(z) = w_0 + \sum_{j=1}^{p^*} w_j z_j,$$

by solving the optimization problem

$$\min_{g\in G}\sum_{z\in Z_x}\pi_x(z)\left(f(z)-g(z)\right)^2+\Omega(g),$$

where Z_x is a set of perturbed samples in the neighborhood of x, $\pi_x(z)$ is a proximity measure, and $\Omega(g)$ enforces simplicity. The absolute coefficients $|w_j|$ indicate the local importance of each feature, enabling a further refined selection $X_{selected} \subseteq X^*$ for classification.

3 BOLIMEX algorithm

Our methodology begins with applying the Boruta algorithm to sift through the high-dimensional gene expression dataset, effectively filtering out irrelevant features and isolating those that are truly significant. This initial reduction is critical because LIME, our subsequent interpretability tool, involves generating numerous perturbed samples and calculating distances—a computationally intensive process, especially in large feature spaces. By narrowing the focus to a refined subset via Boruta, we significantly reduce the computational burden and enhance the precision of LIME's local explanations. This sequential approach streamlines the overall feature selection process and fortifies the reliability and clarity of our model's interpretability, ultimately leading to improved classification performance.

However, the key question remains: how many features should be selected for optimal classification? In our proposed BOLIMES algorithm, which integrates Boruta and LIME, we first reduce the high-dimensional feature set by eliminating irrelevant variables with Boruta. Then, we further refine this subset using LIME to assess the local importance of each feature. Finally, we determine the optimal number of features by evaluating classification performance—selecting the subset that yields the highest accuracy for model training. In general, our model is both efficient and robust, relying only on the most informative features for gene expression classification.

Algorithm 1: Optimal Feature Selection for Classification using Boruta and LIME

Input : Dataset $D = (X, y)$ with $X \subseteq \mathbb{R}^p$ and class labels y.
Output: Optimal feature subset X_{opt} and trained classifier f_{opt} .
1 begin
2 $X^* \leftarrow \text{Boruta}(D)$ // Identify relevant features from X
3 $I \leftarrow \text{LIME}(f, X^*)$ // Compute local importance scores on X^*
$4 \qquad X_R^* \leftarrow \{x_{(i)}^*\}_{i=1}^{ X^* } \qquad \mathcal{I}(x_{(1)}^*) \geq \cdots \geq \mathcal{I}(x_{(X^*)}^*) // \text{ Rank features in } X^* \text{ in descending order of } I$
5 best_acc $\leftarrow 0, k^* \leftarrow 0$
6 for $k = 1$ to $ X^* $ do
7 $S_k \leftarrow \{x_{(i)}^*\}_{i=1}^k$ // Select top-k features from X_R^*
8 $f_k \leftarrow \text{TrainClassifier}(D_{S_k})$ // Train classifier on D_{S_k}
9 $\operatorname{acc} \leftarrow \operatorname{Evaluate}(f_k, D_{S_k})$ // Compute classification accuracy
10 if acc > best_acc then
11 best_acc \leftarrow acc
12 $k^* \leftarrow k$
13 $f_{opt} \leftarrow f_k$
14 $X_{ ext{opt}} \leftarrow \{x^*_{(i)}\}_{i=1}^{k^*}$ // Select top- k^* features from X^*_R
15 return X_{opt}, f_{opt}

The algorithm presents an optimal feature selection framework by integrating Boruta and LIME to refine feature subsets for classification. Given a dataset D = (X, y), it first applies Boruta to extract a subset X^* of relevant features. LIME then computes local importance scores I for X^* , producing a ranked set X_R^* where

$$X_R^* \leftarrow \{x_{(i)}^*\}_{i=1}^{|X^*|}, \quad I(x_{(1)}^*) \ge \dots \ge I(x_{(|X^*|)}^*).$$

An iterative search determines the optimal number of features k^* by selecting the top-k ranked features, training a classifier f_k , and evaluating its accuracy:

$$S_k \leftarrow \{x_{(i)}^*\}_{i=1}^k, \quad f_k \leftarrow \text{TrainClassifier}(D_{S_k}).$$

The best-performing classifier defines k^* , yielding the final subset X_{opt} and trained model f_{opt} .

The algorithm's complexity is driven by three key stages: Boruta for feature selection, LIME for ranking, and iterative classification. Boruta, relying on multiple iterations of Random Forest, has a worst-case complexity of $O(T \cdot p^2 \log p)$. LIME, which perturbs m samples per feature, contributes $O(m \cdot p)$. The final stage trains classifiers iteratively over p^* ranked features, leading to an overhead of $O(np^{*2})$ assuming a model with O(nk) complexity. Thus, the total complexity is: $O(T \cdot p^2 \log p) + O(m \cdot p) + O(np^{*2})$, where $p^* \ll p$ in practice, making the approach feasible for moderate-dimensional data but computationally intensive for extremely large p.

4 Experiment and results

This section offers a brief description of the gene expression datasets while delivering a detailed comparative analysis of the classification models. Furthermore, we also provide the results of Boruta. Our source code has been made publicly accessible on GitHub¹.

4.1 Dataset and Configurations

The gene expression datasets summarized in Table 1 exemplify the inherent challenges of high-dimensional biomedical data. With sample sizes ranging from 53 to 575 and feature counts spanning from approximately 11,950 to over 54,600, these datasets present a significant imbalance between the number of available samples and the vast dimensionality of gene expression profiles. Additionally, the variability in the number of classes—from as few as 3 to as many as 14—further complicates the classification task by introducing diverse and complex biological signals. This high dimensionality coupled with limited sample sizes accentuates the risk of overfitting and underscores the critical need for effective feature selection. Robust feature selection methods are essential to isolate the most informative genes, thereby enhancing model interpretability and predictive accuracy in gene expression classification. In this study, our feature selection strategy is specifically designed to address these challenges, ensuring that only the most relevant features are retained for subsequent classification tasks.

ID	Dataset	#Datapoints	#Dimensions	#Classes
1	E-GEOD-20685	327	54627	6
2	$\operatorname{E-GEOD-20711}$	90	54675	5
3	$\operatorname{E-GEOD-21050}$	310	54613	4
4	E-GEOD-21122	158	22283	7
5	E-GEOD-29354	53	22215	3
6	E-GEOD-30784	229	54675	3
$\overline{7}$	E-GEOD-31312	498	54630	3
8	E-GEOD-31552	111	33297	3
9	E-GEOD-32537	217	11950	7
10	E-GEOD-33315	575	22283	10
11	$\operatorname{E-GEOD-36895}$	76	54675	14
12	E-GEOD-37364	94	54675	4
13	$\operatorname{E-GEOD-39582}$	566	54675	6
14	E-GEOD-39716	53	33297	3
15	E-GEOD-44077	226	33252	4

Table 1: Dataset Characteristics

To evaluate our approach and the training model, we implement the AI libraries *(i.e., tensorflow (version 3.10.0), Keras (version 3.0))* and run the experiments on the computer with the following configuration: AMD Ryzen 7 6800HS, Ceator Edition 3.20 GHZ, 16 GB RAM, Windows 10 OS.

¹ https://github.com/Vannguyen0312/Manholes-App/

4.2 Boruta's Feature Selection

In this study, we adopt Boruta as our primary feature selection method to substantially reduce the dimensionality of our gene expression datasets before applying LIME for model interpretation. The rationale behind this choice is to prevent an explosion in computational complexity and potential loss of interpretability when LIME is applied to an excessively high-dimensional feature space. By using Boruta, we are able to effectively eliminate irrelevant features while retaining those that are truly informative for classification. As evidenced in Table 2, datasets such as E-GEOD-20685 were reduced from 54,627 dimensions to only 545 confirmed features, thereby rendering the subsequent LIME analysis both feasible and efficient. To achieve this, Boruta was executed with the following parameters via the BorutaPy library: a random forest classifier ('rf') with 300 estimators, a maximum of 200 iterations, an alpha value of '0.01', a percentile threshold of 95, two-step feature selection enabled, and a fixed random state of 42, with verbose output enabled. These parameter settings were meticulously chosen to ensure a rigorous and robust selection process, ultimately facilitating a more interpretable and high-performing classification model.

ID	Dataset		Features		Feature Selection
]	E-GEOD-*	Confirmed	Tentative	Rejected	Time (s)
1	20685	545	262	53820	633,0205021
2	20711	111	33	54531	$140,\!0120337$
3	21050	72	17	54524	350, 3323104
4	21122	271	124	21888	$219,\!2371044$
5	29354	28	3	22184	$91,\!59759808$
6	30784	171	64	54440	279,9282582
7	31312	213	42	54375	777,7057292
8	31552	79	48	33170	$136,\!9728532$
9	32537	96	17	11837	$232,\!6542134$
10	33315	483	108	21692	$1176,\!811348$
11	36895	39	14	54622	$122,\!578902$
12	37364	59	43	54573	129,0980539
13	39582	640	253	53782	1306,720685
14	39716	124	29	33144	99,24336505
15	44077	227	231	32794	$221,\!3678348$

Table 2: Feature Selection Results

4.3 Classification results

In our study, we conducted extensive experiments with four advanced algorithms to determine the method yielding the highest accuracy across various gene expression datasets. We configured an SVM using SVC with a radial basis function kernel, setting C to 100,000, gamma to "scale", and class weights to "balanced", ensuring reproducibility with a random state of 42. In parallel, we employed a Random Forest classifier with 200 estimators, a maximum depth of 10, and balanced class weights. Additionally, we implemented both an XGBClassifier and a GradientBoostingClassifier, each configured with 50 estimators, a maximum depth of 10, and a learning rate of 0.01, with the random state fixed at 42. Our comparative evaluation revealed that while the SVM excelled on datasets with fewer samples, the ensemble methods—particularly Random Forest and XG-Boost—demonstrated more robust performance on high-dimensional data. This comprehensive analysis highlights the critical role of algorithm selection and fine-tuning in achieving optimal classification performance in gene expression studies.

ID Dataset Class Method Samples Top K Classification Results Time (s) Prec Rec F1 Score Training Preprocess Features Acc Total 112.137 327 107 0.955 0.956 0.955 0.9551.151 12.951ours 206856 327 1 112, 137 $0.955 \ 0.956 \ 0.955$ 0.9551,15112,951327 107 0.955 0.956 0.955 0,944 0,952 0,944 17,7542 20711 590 67 0.944 0.2983.7451,4943 210504 31070 $0.677 \ 0.710 \ 0.677$ 0.67810,400295.98221122 7 158170 0.938 0.915 0.938 0.9220.5482.01082.092 4 3 5293545310 1,000 1,000 1,000 1.0000.1650.8230.1656 30784 3 22914 1,000 1,000 1,000 1,000 0.7308.197 3.47631312 3 498430,900 0,900 0,900 0.900 0.063 19,236 2.1448 315523 111 15 0.957 0.917 0.957 0.9360.2992.6421.816 9 32537 7 21740 0.796 0.730 0.796 0.7470,7350.91821.20110 33315 105752730,878 0,860 0,878 0.8670,1384,844 33,250 36895 1476150,929 0,893 0,929 0.9050,2283,1991,30411 12 37364 4 94 17 0.947 0.965 0.947 0.9470.2593.3932.08313 39582 6 5662510,877 0,889 0,877 0.880 0,13020,51225,05814 39716 3 5312 1,000 1,000 1,000 1.000 0.1571.6420,4541544077 4 226 18 1,000 1.000 1.000 1.000 0,5785,5135,220

Table 3: SVM Classification Results with Top K Features

The classification results obtained using SVM, Random Forest, XGBoost, and Gradient Boosting reveal distinct performance and computational tradeoffs. SVM generally delivers high accuracy and balanced precision, recall, and F1 scores across most datasets, with relatively low training times in some cases; however, its preprocessing time can be substantial when handling a large number of features. In contrast, Random Forest exhibits competitive accuracy, often outperforming SVM on certain datasets, yet it tends to incur significantly higher training times, particularly when the number of top features increases—as observed in dataset 1 where training time was notably high. XGBoost demonstrates robust performance with competitive accuracy and precision; its moderate training and preprocessing times suggest that it strikes a balance between model complexity and computational efficiency, though its performance can be datasetdependent (e.g., lower accuracy on dataset 13). Meanwhile, Gradient Boosting achieves near-perfect accuracy on several datasets, indicating high robustness in

classification, yet its training and total processing times vary considerably across datasets.

Table 4: Random Forest Classification Results with Top K Features

ID	Dataset	Class	Samples	Top N	Cla	assifica	ation I	Results			
				Features	Acc	Prec	Rec	F1 Score	Training	Preprocess	Total
1	20685	6	327	487	0,970	0,971	0,970	0,970	40,762	13,055	16306,229
2	20711	5	90	10	0,833	0,841	0,833	0,830	5,396	3,703	5,396
3	21050	4	310	72	0,726	0,727	0,726	0,711	25,093	10,252	1507,624
4	21122	7	158	104	0,938	0,922	0,938	0,925	11,577	1,971	1039,209
5	29354	3	53	10	1,000	1,000	1,000	1,000	3,325	1,059	3,325
6	30784	3	229	12	1,000	1,000	1,000	1,000	14,531	8,278	43,917
7	31312	3	498	161	0,900	0,821	0,900	0,858	1,594	19,739	221,322
8	31552	3	111	12	1,000	1,000	1,000	1,000	6,667	2,608	20,318
9	32537	7	217	87	0,773	0,680	0,773	0,707	17,146	0,935	1238,228
10	33315	10	575	444	0,887	0,854	0,887	0,868	3,215	4,947	985,866
11	36895	14	76	20	0,929	0,929	0,929	0,929	4,347	3,242	46,355
12	37364	4	94	10	0,947	0,953	0,947	0,947	5,579	3,380	5,579
13	39582	6	566	189	0,877	0,890	0,877	0,876	1,908	20,970	304, 137
14	39716	3	53	15	1,000	1,000	1,000	1,000	3,172	1,528	19,338
15	44077	4	226	52	1,000	1,000	1,000	1,000	15,408	6,125	$642,\!643$

Table 5: XGB Classification Results with Top K Features

IID	Dataset	Class	Samples	Top N	Cla	Classification Results Time (s)					
				Features	Acc	Prec	Rec	F1 Score	Training	Preprocess	Total
1	20685	6	327	114	0,955	0,962	0,955	0,955	0,395	14,439	40,015
2	20711	5	90	10	0,833	0,841	0,833	0,830	0,328	3,800	0,328
3	21050	4	310	60	0,790	0,791	0,790	0,784	0,286	11,975	16,186
4	21122	7	158	159	0,938	0,921	0,938	0,925	0,293	4,028	44,087
5	29354	3	53	10	1,000	1,000	1,000	1,000	0,271	2,541	0,271
6	30784	3	229	50	0,978	0,979	0,978	0,976	0,127	10,126	6,344
7	31312	3	498	10	0,860	0,848	0,860	0,843	0,388	21,554	0,388
8	31552	3	111	10	1,000	1,000	1,000	1,000	0,557	4,239	0,557
9	32537	7	217	95	0,796	0,693	0,796	0,736	0,299	2,478	26,388
10	33315	10	575	425	0,870	0,842	0,870	0,855	1,341	6,495	389,225
11	36895	14	76	29	0,929	0,929	0,929	0,929	0,250	3,364	6,509
12	37364	4	94	21	1,000	1,000	1,000	1,000	0,142	4,804	1,862
13	39582	6	566	556	0,825	0,833	0,825	0,824	1,564	22,414	554,762
14	39716	3	53	44	1,000	1,000	1,000	1,000	0,101	3,074	3,746
15	44077	4	226	57	0,978	0,980	0,978	0,979	0,139	6,925	8,332

The four classification algorithms reveal distinct trade-offs between predictive performance and computational efficiency when applied to high-dimensional gene expression data. For instance, on dataset E-GEOD-20685 (ID 1), SVM attained an accuracy of 95.5% with 107 selected features and a total processing time of 112.137 seconds, while Random Forest achieved a marginally higher accuracy of 97.0% but at a prohibitive total time of 16,306.229 seconds. In contrast, XGBoost matched SVM's accuracy (95.5%) with a considerably lower training

IID	Dataset	Class	Samples	Top N	Cla	Classification Results			Time (s)			
				Features	Acc	Prec	Rec	F1 Score	Training	Preprocess	Total	
1	20685	6	327	468	0,939	0,947	0,939	0,936	17,957	12,795	17,957	
2	20711	5	90	38	0,889	0,921	0,889	0,892	0,664	3,832	0,664	
3	21050	4	310	65	0,807	0,802	0,807	0,804	1,844	9,923	1,844	
4	21122	7	158	257	0,875	0,872	0,875	0,871	5,544	1,890	5,544	
5	29354	3	53	12	1,000	1,000	1,000	1,000	0,387	0,822	0,387	
6	30784	3	229	39	0,957	0,957	0,957	0,957	0,747	8,048	0,747	
$\overline{7}$	31312	3	498	169	0,880	0,853	0,880	0,854	4,961	18,680	4,961	
8	31552	3	111	13	0,957	0,917	0,957	0,936	0,310	2,594	0,310	
9	32537	7	217	54	0,773	0,705	0,773	0,734	2,249	0,906	2,249	
10	33315	10	575	351	0,896	0,865	0,896	0,877	40,149	4,819	40,149	
11	36895	14	76	11	0,857	0,857	0,857	0,857	0,826	3,260	1,645	
12	37364	4	94	24	0,947	0,953	0,947	0,947	0,480	3,327	0,480	
13	39582	6	566	352	0,816	0,828	0,816	0,816	24,821	20,419	24,821	
14	39716	3	53	24	1,000	1,000	1,000	1,000	0,299	1,468	0,299	
15	44077	4	226	18	1,000	1,000	1,000	1,000	0,711	5,468	0,711	

Table 6: Gradient Boosting Classification Results with Top N Features

time of 0.395 seconds and an overall time of 40.015 seconds, suggesting a more balanced performance. Gradient Boosting, on the other hand, reached an accuracy of 93.9% using 468 features, with a total time of 17.957 seconds—indicating competitive speed but slightly reduced accuracy compared to the other methods.

Similar trends are observed in other datasets; for example, in E-GEOD-29354 (ID 5), all algorithms achieved perfect accuracy, yet their feature counts and processing times varied substantially. These differences underscore the critical need for an approach that not only maintains high classification performance but also minimizes computational overhead. Although Random Forest often produces high accuracy, its excessive time cost can limit its practicality in real-world applications. Conversely, XGBoost offers a compelling balance between accuracy and efficiency, making it particularly well-suited for gene expression classification tasks. Overall, these results emphasize that algorithm selection should be guided by both predictive metrics and computational feasibility, especially in scenarios involving high-dimensional data.

4.4 Discussion

5 Conclusion and future work

In conclusion, our study introduces BOLIMES, a novel feature selection algorithm that integrates the robustness of Boruta with the interpretability of LIME to tackle the challenges inherent in gene expression classification. By systematically filtering out non-informative genes and ranking the remaining ones based on their local importance, BOLIMES effectively reduces the dimensionality of genomic data while mitigating the risk of overfitting. The iterative evaluation process further refines the feature subset by identifying the optimal number of genes that maximize predictive accuracy, thereby ensuring both high classification performance and enhanced interpretability. Looking ahead, several promising avenues exist for further advancement of this work. Future research could explore the incorporation of additional interpretability methods alongside LIME to offer a more comprehensive assessment of feature relevance. Moreover, extending BOLIMES to accommodate multi-omics data, such as proteomic and metabolomic profiles, may broaden its applicability in complex biological analyses. Integrating deep learning-based classifiers could also be investigated to further boost performance in intricate gene expression scenarios. Finally, validating the approach on larger, more diverse datasets and real-world clinical samples will be crucial to establish its robustness and generalizability in practical settings.

Acknowledgements: This study is received support from the European Union's Horizon research and innovation program under the MSCA-SE (Marie Skłodowska-Curie Actions Staff Exchange) grant agreement 101086252; Call: HORIZON-MSCA-2021-SE-01; Project title: STARWARS.

References

- Ahmed, O., Brifcani, A.: Gene expression classification based on deep learning. In: 2019 4th Scientific International Conference Najaf (SICN). pp. 145–149. IEEE (2019)
- Bach, F.: Breaking the curse of dimensionality with convex neural networks. Journal of Machine Learning Research 18(19), 1–53 (2017)
- Bajer, D., Dudjak, M., Zorić, B.: Wrapper-based feature selection: how important is the wrapped classifier? In: 2020 International conference on smart systems and technologies (SST). pp. 97–105. IEEE (2020)
- 4. Breiman, L.: Random forests. Machine learning 45, 5–32 (2001)
- Cervante, L., Xue, B., Zhang, M., Shang, L.: Binary particle swarm optimisation for feature selection: A filter based approach. In: 2012 IEEE Congress on Evolutionary Computation. pp. 1–8. IEEE (2012)
- 6. Chen, T.: Xgboost: extreme gradient boosting. R package version 0.4-2 1(4) (2015)
- Chen, X.w., Jeong, J.C.: Enhanced recursive feature elimination. In: Sixth international conference on machine learning and applications (ICMLA 2007). pp. 429–435. IEEE (2007)
- Cherrington, M., Thabtah, F., Lu, J., Xu, Q.: Feature selection: filter methods performance challenges. In: 2019 International Conference on Computer and Information Sciences (ICCIS). pp. 1–4. IEEE (2019)
- Do, T.N.: Enhancing gene expression classification through explainable machine learning models. SN Computer Science 5(5), 1–16 (2024)
- Do, T.N., Tran-Nguyen, M.T.: Ensemble learning with svm for high-dimensional gene expression data. In: International Conference on Intelligent Systems and Data Science. pp. 29–40. Springer (2023)
- 11. Duch, W.: Filter methods. In: Feature extraction: foundations and applications, pp. 89–117. Springer (2006)
- Dwivedi, R., Dave, D., Naik, H., Singhal, S., Omer, R., Patel, P., Qian, B., Wen, Z., Shah, T., Morgan, G., et al.: Explainable ai (xai): Core ideas, techniques, and solutions. ACM Computing Surveys 55(9), 1–33 (2023)
- Fonti, V., Belitser, E.: Feature selection using lasso. VU Amsterdam research paper in business analytics 30, 1–25 (2017)

¹² Bich-Chung Phan et al.

- Freeman, C., Kulić, D., Basir, O.: Feature-selected tree-based classification. IEEE transactions on cybernetics 43(6), 1990–2004 (2013)
- Friedman, J.H.: Stochastic gradient boosting. Computational statistics & data analysis 38(4), 367–378 (2002)
- Hamed, T., Dara, R., Kremer, S.C.: An accurate, fast embedded feature selection for svms. In: 2014 13th International conference on machine learning and applications. pp. 135–140. IEEE (2014)
- 17. Huynh, P.H., Nguyen, V.H., Do, T.N.: Random ensemble oblique decision stumps for classifying gene expression data. In: proceedings of the 9th international symposium on information and communication technology. pp. 137–144 (2018)
- Huynh, P.H., Nguyen, V.H., Do, T.N.: Novel hybrid dcnn–svm model for classifying rna-sequencing gene expression data. Journal of Information and Telecommunication 3(4), 533–547 (2019)
- Imani, M.B., Keyvanpour, M.R., Azmi, R.: A novel embedded feature selection method: a comparative study in the application of text categorization. Applied Artificial Intelligence 27(5), 408–427 (2013)
- 20. Karim, M.R., Cochez, M., Beyan, O., Decker, S., Lange, C.: Onconetexplainer: explainable predictions of cancer types based on gene expression data. In: 2019 IEEE 19th International conference on bioinformatics and bioengineering (BIBE). pp. 415–422. IEEE (2019)
- Kasongo, S.M., Sun, Y.: A deep learning method with wrapper based feature extraction for wireless intrusion detection system. Computers & Security 92, 101752 (2020)
- Köppen, M.: The curse of dimensionality. In: 5th online world conference on soft computing in industrial applications (WSC5). vol. 1, pp. 4–8 (2000)
- Kumarakulasinghe, N.B., Blomberg, T., Liu, J., Leao, A.S., Papapetrou, P.: Evaluating local interpretable model-agnostic explanations on clinical machine learning classification models. In: 2020 IEEE 33rd international symposium on computerbased medical systems (CBMS). pp. 7–12. IEEE (2020)
- Kursa, M.B., Jankowski, A., Rudnicki, W.R.: Boruta–a system for feature selection. Fundamenta Informaticae 101(4), 271–285 (2010)
- Leardi, R., Boggia, R., Terrile, M.: Genetic algorithms as a strategy for feature selection. Journal of chemometrics 6(5), 267–281 (1992)
- Lee, I.H., Lushington, G.H., Visvanathan, M.: A filter-based feature selection approach for identifying potential biomarkers for lung cancer. Journal of clinical Bioinformatics 1, 1–8 (2011)
- Liu, H., Zhou, M., Liu, Q.: An embedded feature selection method for imbalanced data classification. IEEE/CAA Journal of Automatica Sinica 6(3), 703–715 (2019)
- Mufassirin, M.M., Ragel, R.G.: A novel filter-wrapper based feature selection approach for cancer data classification. In: 2018 IEEE International Conference on Information and Automation for Sustainability (ICIAfS). pp. 1–6. IEEE (2018)
- Muthukrishnan, R., Rohini, R.: Lasso: A feature selection technique in predictive modeling for machine learning. In: 2016 IEEE international conference on advances in computer applications (ICACA). pp. 18–20. Ieee (2016)
- 30. Ribeiro, M.T., Singh, S., Guestrin, C.: "why should i trust you?" explaining the predictions of any classifier. In: Proceedings of the 22nd ACM SIGKDD international conference on knowledge discovery and data mining. pp. 1135–1144 (2016)
- Stańczyk, U.: Feature evaluation by filter, wrapper, and embedded approaches. Feature selection for data and pattern recognition pp. 29–44 (2015)
- 32. Vapnik, V.: Support-vector networks. Machine learning 20, 273–297 (1995)

- 14 Bich-Chung Phan et al.
- 33. Wang, H., Khoshgoftaar, T.M., Napolitano, A.: Stability of filter-and wrapperbased software metric selection techniques. In: Proceedings of the 2014 IEEE 15th International Conference on Information Reuse and Integration (IEEE IRI 2014). pp. 309–314. IEEE (2014)
- Yan, K., Zhang, D.: Feature selection and analysis on correlated gas sensor data with recursive feature elimination. Sensors and Actuators B: Chemical 212, 353– 363 (2015)
- Zacharias, J., von Zahn, M., Chen, J., Hinz, O.: Designing a feature selection method based on explainable artificial intelligence. Electronic Markets 32(4), 2159– 2184 (2022)
- Zhou, H., Xin, Y., Li, S.: A diabetes prediction model based on boruta feature selection and ensemble learning. BMC bioinformatics 24(1), 224 (2023)