Uplink Coordinated Pilot Design for 1-bit Massive MIMO in Correlated Channel

Hyeongtak Yun, Juntaek Han, Kaiming Shen, and Jeonghun Park

Abstract-In this paper, we propose a coordinated pilot design method to minimize the channel estimation mean squared error (MSE) in 1-bit analog-to-digital converters (ADCs) massive multiple-input multiple-output (MIMO). Under the assumption that the well-known Bussgang linear minimum mean square error (BLMMSE) estimator is used for channel estimation, we first observe that the resulting MSE leads to an intractable optimization problem, as it involves the arcsin function and a complex multiple matrix ratio form. To resolve this, we derive the approximate MSE by assuming the low signal-to-noise ratio (SNR) regime, by which we develop an efficient coordinated pilot design based on a fractional programming technique. The proposed pilot design is distinguishable from the existing work in that it is applicable in general system environments, including correlated channel and multi-cell environments. We demonstrate that the proposed method outperforms the channel estimation accuracy performance compared to the conventional approaches.

I. INTRODUCTION

In multi-user multiple-input multiple-output (MU-MIMO) systems, channel state information (CSI) acquisition is a critical part to achieve high spectral efficiency performance, as imperfect CSI incurs additional interference, which severely limits the achievable spectral efficiency [1], [2]. In cellular networks, CSI estimation performance is mainly determined by two key factors: i) the channel estimation algorithm and ii) the pilot sequence. If the channel vector is modeled as a Gaussian distribution, it has been well studied that the optimal mean squared error (MSE) performance is achievable by using the linear minimum mean squared error (LMMSE) estimator [3]. This paper focuses on the pilot sequence aspect.

Typically, if sufficient time and frequency resources are available compared to the number of users, assigning mutually orthogonal pilots to all the users is optimal in terms of the MSE. However, when the pilots are reused in multicell environments [4], i.e., pilot contamination occurs, it is infeasible to ensure orthogonality between the pilot sequences. This non-orthogonality leads to significant interference during channel estimation, resulting in a notable increase in MSE. In such cases, it becomes crucial to design pilot sequences in a coordinated manner taking into account both channel estimation accuracy and mitigation of pilot interference. This motivates several advanced pilot design methods. In particular, it has been shown that coordinated pilot design across multiple cells to minimize overall MSE is effective in mitigating pilot contamination by minimizing the overall MSE [5]–[9]. Notably, in [7], a fractional programming (FP) based pilot design technique via a matrix quadratic transform technique [10] was devised for coordinated pilot sequence optimization. A common consideration of the above mentioned prior work is ideal hardware MIMO systems, such as an analog-to-digital converter (ADC) with no quantization error.

Recently, massive MIMO with low resolution ADCs (particularly 1-bit ADCs) has gained significant attention thanks to its energy and hardware efficiency [11]–[13]. When the channel estimation is performed on the basis of 1-bit quantized measurements, the nonlinear nature of quantization makes the observations no longer follow a Gaussian distribution, so as to render conventional LMMSE channel estimation far from optimal. Addressing this, one promising approach is the Bussgang LMMSE (BLMMSE) [14], [15]. The key idea of the BLMMSE is to use the Bussgang decomposition, wherein the output of the nonlinear function can be expressed as the sum of linear terms and an uncorrelated distortion term, enabling the derivation of LMMSE estimators for systems with nonlinearities.

One essential aspect in BLMMSE for 1-bit ADC channel estimation is that the MSE characterization is significantly changed. To be specific, the analytical form of the MSE achieved by BLMMSE is determined by the normalized autocorrelation matrix of the output signal, which is characterized by an element-wise arcsin function [14]. As a result, the existing pilot design approaches, which are based on ideal hardware assumptions such as high-resolution ADCs, are not directly applicable. To resolve this issue, [16] developed a pilot design method that accounts for the non-linearity of 1-bit ADCs and minimizes the MSE under a hypersphere constraint via a steepest-descent approach. Despite this, it is only applicable to limited environments, such as uncorrelated Rayleigh channel and a single cell environment. By considering that the pilot contamination problem becomes more pronounced in a multicell environment and that realistic channel conditions are often correlated due to sparse scattering [17], there exists a need for a new pilot design approach that incorporates more generalized system environments.

In this paper, we propose a novel pilot design method for 1-bit massive MIMO. To address the previous limitations, we consider a multi-cell setup with correlated Rayleigh channels.

This work was supported in part by Institute of Information & communications Technology Planning & Evaluation (IITP) grant funded by the Korea government (MSIT) (No. RS-2024-00397216, Development of the Upper-mid Band Extreme massive MIMO (E-MIMO) and No. RS-2024-00435652, 6GARROW: 6G Ai-native integrated RAN-Core networks). H. Yun, J. Han, and J. Park are with School of Electrical and Electronic Engineering, Yonsei University, Seoul, South Korea (e-mail: yht3114, jthan1218, jhpark@yonsei.ac.kr). K. Shen is with School of Science and Engineering, The Chinese University of Hong Kong, Shenzhen, China (e-mail: shenkaiming@cuhk.edu.cn).

In such a case, assuming that the BLMMSE algorithm [14], [15] is used for the channel estimation, we observe that the MSE form of the BLMMSE algorithm is hard to handle in the pilot design optimization problem. To resolve this challenge, we obtain the approximate MSE expression by assuming the low signal-to-noise ratio (SNR) regime, derived as the form of a multiple matrix ratio. Upon this, we characterize the matrix ratio as a quadratic form, by which we develop a pilot design method based on a FP technique that minimizes the sum of MSEs for all the uplink users. Numerical results demonstrate that the proposed method provides substantial channel estimation performance gains compared to baseline cases in general multi-cell cellular scenarios with correlated channels.

II. SYSTEM MODELS

A. Signal Model

We consider an uplink 1-bit massive MIMO system consisting of *L* cells. Each cell $\ell \in \{1, ..., L\}$ includes a base station (BS) equipped with *M* antennas. Each antenna is paired with two 1-bit ADCs to separately process the real and imaginary parts of the received signal [14]. Each cell includes *K* users, each equipped with a single antenna. The full coherence bandwidth is reused across all users. The channel for user $k \in \{1, ..., K\}$ in cell *i* to cell ℓ , denoted as $\mathbf{h}_{\ell ik} \in \mathbb{C}^M$, is expressed as

$$\mathbf{h}_{\ell i k} = \sqrt{\beta_{\ell i k}} \mathbf{g}_{\ell i k},\tag{1}$$

where $\mathbf{g}_{\ell ik} \sim \mathcal{CN}(0, \mathbf{R}_{\ell ik})$ describes the small-scale fading, $\beta_{\ell ik}$ is the large-scale fading coefficient, and $\mathbf{R}_{\ell ik} \in \mathbb{C}^{M \times M}$ represents the covariance matrix. $\mathbf{R}_{\ell ik} \neq \mathbf{I}$ implies that each channel is inherently correlated with respect to the receiving antennas.

During the training phase, all *K* users simultaneously transmit their corresponding pilot sequences, each consisting of τ symbols, to the BS. Focusing on cell ℓ without loss of generality, the received pilot signal at the BS is

$$\mathbf{Y}_{\ell} = \sum_{k=1}^{K} \sqrt{\beta_{\ell\ell k}} \mathbf{g}_{\ell\ell k} \phi_{\ell k}^{\top} + \underbrace{\sum_{i \neq \ell} \sum_{k=1}^{K} \sqrt{\beta_{\ell i k}} \mathbf{g}_{\ell i k} \phi_{i k}^{\top}}_{\text{pilot interference}} + \mathbf{Z}_{\ell} \qquad (2)$$

$$= \mathbf{H}_{\ell\ell} \boldsymbol{\Phi}_{\ell}^{\top} + \sum_{i \neq \ell} \mathbf{H}_{\ell i} \boldsymbol{\Phi}_{i}^{\top} + \mathbf{Z}_{\ell}, \qquad (3)$$

where $\phi_{\ell k} \in \mathbb{C}^{\tau}$ represents the pilot sequence vector of user k, $\mathbf{H}_{\ell \ell}^{\top} = [\sqrt{\beta_{\ell \ell 1}} \mathbf{g}_{\ell \ell 1}^{\top}, \dots, \sqrt{\beta_{\ell \ell K}} \mathbf{g}_{\ell \ell K}^{\top}]$ denotes the channel matrix, and $\mathbf{\Phi}_{\ell}^{\top} = [\phi_{\ell 1}^{\top}, \dots, \phi_{\ell K}^{\top}]$ is the corresponding pilot matrix. $\mathbf{Z}_{\ell} \sim \mathcal{CN}(0, \sigma^2 \mathbf{I}_{\tau M})$ represents the additive white Gaussian noise (AWGN) matrix. The pilot sequence $\phi_{\ell k}$ is designed under the following constraints:

$$\phi_{\ell k} \in \mathbb{C}^{\tau}, \quad \|\phi_{\ell k}\|_2^2 \le \tau P, \quad \forall \ell, \forall k.$$
(4)

where P is the power constraint.

Next, vectorizing (3), the received signal (3) is re-expressed as

$$\mathbf{y}_{\ell} = \bar{\mathbf{\Phi}}_{\ell} \bar{\mathbf{h}}_{\ell\ell} + \sum_{i \neq \ell} \bar{\mathbf{\Phi}}_{i} \bar{\mathbf{h}}_{\ell i} + \mathbf{z}_{\ell}, \tag{5}$$

where $\mathbf{y}_{\ell} = \text{vec}(\mathbf{Y}_{\ell})$, $\bar{\mathbf{\Phi}}_{\ell} = \mathbf{\Phi}_{\ell} \otimes \mathbf{I}_{M}$, $\bar{\mathbf{h}}_{\ell i} = \text{vec}(\mathbf{H}_{\ell i})$, and $\mathbf{z}_{\ell} = \text{vec}(\mathbf{Z}_{\ell})$. After passing through the 1-bit ADCs, the quantized received signal \mathbf{b}_{ℓ} is given by

$$\mathbf{b}_{\ell} = \Omega(\mathbf{y}_{\ell}) = \Omega\left(\bar{\mathbf{\Phi}}_{\ell}\bar{\mathbf{h}}_{\ell\ell} + \sum_{i\neq\ell}\bar{\mathbf{\Phi}}_{i}\bar{\mathbf{h}}_{\ell i} + \mathbf{z}_{\ell}\right). \tag{6}$$

The 1-bit quantization operation in $\Omega(\cdot)$ is defined as $\Omega(\cdot) = \frac{1}{\sqrt{2}} (\operatorname{sign} (\mathfrak{R}(\cdot)) + j \operatorname{sign} (\mathfrak{I}(\cdot)))$. As a result, output \mathbf{b}_{ℓ} is drawn from the set $\mathbf{b}_{\ell} \in \frac{1}{\sqrt{2}} \{1 + j, 1 - j, -1 + j, -1 - j\}$.

B. Bussgang-Aided Channel Estimation

The signal received through 1-bit ADCs is subject to a nonlinear operation (specifically sign(\cdot) operation (6)). This nonlinearity complicates the subsequent analysis of estimation performance. To address these challenges, we exploit the fact that the received signal \mathbf{y}_{ℓ} follows a Gaussian distribution [14]. By applying the Bussgang decomposition [14], [15], the nonlinear operation is transformed into a statistically equivalent linear model. To be specific, \mathbf{b}_{ℓ} in (6) can be characterized as

$$\mathbf{b}_{\ell} = \mathbf{A}_{\ell} \mathbf{y}_{\ell} + \mathbf{e}_{\ell},\tag{7}$$

where $\mathbf{A}_{\ell} \in \mathbb{C}^{\tau M \times \tau M}$ represents the linear operation matrix based on the LMMSE estimation, and $\mathbf{e}_{\ell} \in \mathbb{C}^{\tau M}$ denotes the quantization noise, which is uncorrelated with both \mathbf{y}_{ℓ} and \mathbf{g}_{ℓ} according to the Bussgang theorem. The autocorrelation matrix of \mathbf{y}_{ℓ} is obtained as

$$\mathbf{R}_{\mathbf{y}_{\ell}} = \mathbb{E}[\mathbf{y}_{\ell}\mathbf{y}_{\ell}^{\mathsf{H}}] = \bar{\mathbf{\Phi}}_{\ell}\mathbf{R}_{\mathbf{h}_{\ell\ell}}\bar{\mathbf{\Phi}}_{\ell}^{\mathsf{H}} + \sum_{i\neq\ell}\bar{\mathbf{\Phi}}_{i}\mathbf{R}_{\mathbf{h}_{\ell i}}\bar{\mathbf{\Phi}}_{i}^{\mathsf{H}} + \sigma^{2}\mathbf{I}_{\tau M}, \quad (8)$$

where $\mathbf{R}_{\mathbf{h}_{\ell i}} = \text{diag}\{\mathbf{R}_{\ell i 1}, \mathbf{R}_{\ell i 2}, \cdots, \mathbf{R}_{\ell i K}\}$ is the autocorrelation matrix of the channel coefficients for all the users to cell ℓ . The cross-correlation matrix between \mathbf{y}_{ℓ} and \mathbf{b}_{ℓ} is given by

$$\mathbf{R}_{\mathbf{y}_{\ell}\mathbf{b}_{\ell}} = \mathbb{E}[\mathbf{y}_{\ell}\mathbf{b}_{\ell}^{\mathsf{H}}] = \sqrt{\frac{2}{\pi}}\mathbf{R}_{\mathbf{y}_{\ell}}\boldsymbol{\Sigma}_{\mathbf{y}_{\ell}}^{-\frac{1}{2}}, \qquad (9)$$

where $\Sigma_{y_{\ell}}$ is the diagonal matrix of $R_{y_{\ell}}$. The linear operation matrix A_{ℓ} can be written as

$$\mathbf{A}_{\ell} = \mathbf{R}_{\mathbf{y}_{\ell}\mathbf{b}_{\ell}}\mathbf{R}_{\mathbf{y}_{\ell}}^{-1} = \sqrt{\frac{2}{\pi}}\mathbf{R}_{\mathbf{y}_{\ell}}\boldsymbol{\Sigma}_{\mathbf{y}_{\ell}}^{-1/2}\mathbf{R}_{\mathbf{y}_{\ell}}^{-1}.$$
 (10)

By substituting (10) into (7),

$$\mathbf{b}_{\ell} = \sqrt{\frac{2}{\pi}} \Sigma_{\mathbf{y}_{\ell}}^{-1/2} \left(\bar{\mathbf{\Phi}}_{\ell} \bar{\mathbf{h}}_{\ell \ell} + \sum_{i \neq \ell} \bar{\mathbf{\Phi}}_{i} \bar{\mathbf{h}}_{\ell i} + \mathbf{z}_{\ell} \right) + \bar{\mathbf{z}}_{\ell}, \qquad (11)$$

where $\bar{\mathbf{z}}_{\ell} = \sqrt{\frac{2}{\pi}} \Sigma_{\mathbf{y}_{\ell}}^{-1/2} \mathbf{z}_{\ell} + \mathbf{e}_{\ell}$ is the effective noise and is also uncorrelated with both $\bar{\mathbf{h}}_{\ell i}$ and $\bar{\mathbf{h}}_{\ell \ell}$.

We adopt the BLMMSE estimator [14] to estimate the channel from \mathbf{b}_{ℓ} . BLMMSE is known as a computationally efficient solution for channel estimation under the Bussgang linearized system model, while also ensuring robust performance [14], [15]. BLMMSE computes

$$\hat{\mathbf{h}}_{\ell\ell k} = \mathbf{R}_{\mathbf{b}_{\ell}\mathbf{h}_{\ell\ell k}} \mathbf{R}_{\mathbf{b}_{\ell}}^{-1} \mathbf{b}_{\ell}, \qquad (12)$$

where

$$\mathbf{R}_{\mathbf{b}_{\ell}\mathbf{h}_{\ell\ell k}} = \sqrt{\frac{2}{\pi}} \beta_{\ell\ell k} \mathbf{R}_{\ell\ell k} \left(\phi_{\ell k}^{\mathsf{H}} \otimes \mathbf{I}_{M} \right) \boldsymbol{\Sigma}_{\mathbf{y}_{\ell}}^{-\frac{1}{2}}.$$
 (13)

The correlation matrix of the quantized signal b_ℓ , denoted as R_{b_ℓ} , is obtained by applying the arcsine law as follows:

$$\mathbf{R}_{\mathbf{b}_{\ell}} = \frac{2}{\pi} \left[\operatorname{arcsin} \left(\boldsymbol{\Sigma}_{\mathbf{y}_{\ell}}^{-\frac{1}{2}} \mathfrak{R}(\mathbf{R}_{\mathbf{y}_{\ell}}) \boldsymbol{\Sigma}_{\mathbf{y}_{\ell}}^{-\frac{1}{2}} \right) + j \operatorname{arcsin} \left(\boldsymbol{\Sigma}_{\mathbf{y}_{\ell}}^{-\frac{1}{2}} \mathfrak{I}(\mathbf{R}_{\mathbf{y}_{\ell}}) \boldsymbol{\Sigma}_{\mathbf{y}_{\ell}}^{-\frac{1}{2}} \right) \right].$$
(14)

Accordingly, the sum of MSEs for all the uplink users is characterized as

$$MSE_{\Sigma} = \sum_{(\ell,k)} \beta_{\ell\ell k} tr\left(\mathbf{R}_{\ell\ell k}\right) - \sum_{(\ell,k)} tr\left(\mathbf{R}_{\mathbf{b}_{\ell}\mathbf{h}_{\ell\ell k}}\mathbf{R}_{\mathbf{b}_{\ell}}^{-1}\mathbf{R}_{\mathbf{b}_{\ell}\mathbf{h}_{\ell\ell k}}^{\mathsf{H}}\right).$$
(15)

C. Pilot Design Problem Formulation

We aim to minimize MSE_{Σ} in (15) by coordinately designing the pilot sequence $\phi_{\ell k}$, $\forall \ell, k$. We observe from (15) that $\mathbf{R}_{\mathbf{b}_{\ell}\mathbf{h}_{\ell\ell k}}$ and $\mathbf{R}_{\mathbf{b}_{\ell}}$ are functions related to $\{\phi\} = \{\phi_{11}, \cdots, \phi_{\ell k}\}$. Therefore, the pilot design problem is formulated to

$$\underset{\{\phi\}}{\text{maximize}} \quad \sum_{(\ell,k)} \operatorname{tr} \left(\mathbf{R}_{\mathbf{b}_{\ell} \mathbf{h}_{\ell \ell k}} \mathbf{R}_{\mathbf{b}_{\ell}}^{-1} \mathbf{R}_{\mathbf{b}_{\ell} \mathbf{h}_{\ell k}}^{\mathsf{H}} \right)$$
(16a)

subject to
$$\|\phi_{\ell k}\|_2^2 \le \tau P$$
, $\forall (\ell, k)$. (16b)

However, this optimization problem is non-convex and in an intractable form, due to i) the presence of the element-wise arcsine function in $\mathbf{R}_{\mathbf{b}_{\ell}}$ and ii) the multiple matrix ratio form. To address these, we reformulate (16a) into a more tractable form in the next section.

III. PROBLEM REFORMULATION

A. Low SNR Approximation

By considering that the performance degradation caused by 1-bit ADCs is alleviated in the low SNR regime (with only a 1.96 dB loss as SNR approaches 0 [13]), it is suitable to operate the 1-bit massive MIMO system in the low SNR regime. Motivated by this, we derive an approximate MSE expression under the assumption of the low SNR regime. Later, we demonstrate that, despite the low SNR approximation, our pilot design method performs effectively even in the high SNR regime. By applying the first-order Taylor approximation of the arcsine function near 0, we have $\arcsin(x) \approx x$. Upon this, we approximate $\mathbf{R}_{\mathbf{b}_{\ell}}$ as

$$\mathbf{R}_{\mathbf{b}_{\ell}} \approx \frac{2}{\pi} \arcsin\left(\boldsymbol{\Sigma}_{\mathbf{y}_{\ell}}^{-\frac{1}{2}} \mathbf{R}_{\mathbf{y}_{\ell}} \boldsymbol{\Sigma}_{\mathbf{y}_{\ell}}^{-\frac{1}{2}}\right)$$
(17)

$$=\begin{cases} \frac{2}{\pi} \Sigma_{\mathbf{y}_{\ell}}^{-\frac{1}{2}} \mathbf{R}_{\mathbf{y}_{\ell}} \Sigma_{\mathbf{y}_{\ell}}^{-\frac{1}{2}}, & \text{if } i \neq j, \\ 1, & \text{otherwise.} \end{cases}$$
(18)

$$= \frac{2}{\pi} \boldsymbol{\Sigma}_{\mathbf{y}_{\ell}}^{-\frac{1}{2}} \mathbf{R}_{\mathbf{y}_{\ell}} \boldsymbol{\Sigma}_{\mathbf{y}_{\ell}}^{-\frac{1}{2}} + \left(1 - \frac{2}{\pi}\right) \mathbf{I}_{\tau M}$$
(19)

By using the approximation result of $\mathbf{R}_{\mathbf{b}_{\ell}}$, we substitute it into (16a), allowing us to reformulate the optimization problem as

$$\underset{\{\phi\}}{\text{maximize}} \quad \sum_{(\ell,k)} \operatorname{tr} \left(\mathbf{A}_{\ell k} \mathbf{B}_{\ell}^{-1} \mathbf{A}_{\ell k}^{\mathsf{H}} \right)$$
(20a)

subject to $\|\phi_{\ell k}\|_2^2 \le \tau P$, $\forall (\ell, k)$, (20b)

where $\mathbf{A}_{\ell k} \in \mathbb{C}^{M \times \tau M}$ and $\mathbf{B}_{\ell} \in \mathbb{C}^{\tau M \times \tau M}$ are given by

$$\mathbf{A}_{\ell k} = \beta_{\ell \ell k} \mathbf{R}_{\ell \ell k} \left(\phi_{\ell k}^{\mathsf{H}} \otimes \mathbf{I}_{M} \right), \ \mathbf{B}_{\ell} = \mathbf{R}_{\mathbf{y}_{\ell}} + \left(\frac{\pi}{2} - 1 \right) \boldsymbol{\Sigma}_{\mathbf{y}_{\ell}}.$$
(21)

Subsequently, we transform (20a), so as to make the multipleratio optimization problem tractable.

B. Matrix Quadratic Transform

The objective function in (20) is expressed in a multipleratio fractional form, making it intractable. To address this, we exploit the quadratic transform technique, which has been recently introduced in the matrix FP framework [7], [18]. This enables us to equivalently reformulate the problem by simultaneously decoupling the numerators and denominators of the multiple ratios. Applying this, (20) is equivalently transformed to

$$\underset{\{\phi\},\{\Lambda\}}{\text{maximize}} \qquad \sum_{(\ell,k)} \operatorname{tr} \left(2\Re \left\{ \mathbf{A}_{\ell k} \mathbf{\Lambda}_{\ell k} \right\} - \mathbf{\Lambda}_{\ell k}^{\mathsf{H}} \mathbf{B}_{\ell} \mathbf{\Lambda}_{\ell k} \right) \quad (22a)$$

subject to
$$\|\phi_{\ell k}\|_2^2 \le \tau P$$
, (22b)

$$\Lambda_{\ell k} \in \mathbb{C}^{\tau M \times M}, \quad \forall (\ell, k), \tag{22c}$$

where $\Lambda_{\ell k}$ is defined as an auxiliary variable for $\mathbf{A}_{\ell k} \mathbf{B}^{-1} \mathbf{A}_{\ell k}^{\mathsf{H}}$. The equivalence between (20a) and (22a) is discussed in detail in [18]. Also, it can be established by substituting the optimal $\{\Lambda\} = \{\Lambda_{11}, \dots, \Lambda_{\ell k}\}$ while fixing $\{\phi\}$.

IV. PILOT DESIGN

As shown in [18], optimizing $\{\phi\}$ and $\{\Lambda\}$ in an alternating fashion ensures that the objective function remains non-decreasing. Further, provided that the original objective function is differentiable, it was also demonstrated that the alternating optimization approach converges to a stationary solution point. Motivated by this, we solve (22a) by employing the alternating optimization approach.

When $\{\phi\}$ is fixed, the optimal $\{\Lambda\}$ is obtained by differentiating the objective function with respect to $\Lambda_{\ell k}$, resulting in $\Lambda_{\ell k}^* = \mathbf{B}_{\ell}^{-1}\mathbf{A}_{\ell k}$. Thereafter, we update $\{\phi\}$ while keeping $\{\Lambda\}$ fixed. Before this, we rewrite the objective function to allow the optimal value of $\{\phi\}$ to be derived in closed form. Specifically, the first terms of the objective function in (22) is expressed as

$$\sum_{(\ell,k)} \operatorname{tr} \left(2\Re \left\{ \mathbf{A}_{\ell k} \mathbf{\Lambda}_{\ell k} \right\} \right) = \sum_{(\ell,k)} 2\Re \left\{ \phi_{\ell k}^{\mathsf{H}} \mathbf{v}_{\ell k} \right\}, \qquad (23)$$

where the (p,q)th entry of $\mathbf{v}_{\ell k} \in \mathbb{C}^{\tau}$ is expressed as

$$\mathbf{v}_{\ell k}[p,q] = \beta_{\ell \ell k} \sum_{m=1}^{M} \mathbf{R}_{\ell \ell k}[m,:] \mathbf{\Lambda}_{\ell k}[(p-1)M+1:iM,m+(q-1)M].$$
(24)

Next, the second terms of the objective function in (22) is also expressed as

$$\sum_{(\ell,k)} \operatorname{tr} \left(\boldsymbol{\Lambda}_{\ell k}^{\mathsf{H}} \mathbf{B}_{\ell} \boldsymbol{\Lambda}_{\ell k} \right)$$
(25)

$$= \sum_{(\ell,k)} \operatorname{tr} \left(\sum_{(i,j)} \beta_{\ell i j} \left(\phi_{i j} \phi_{i j}^{\mathsf{H}} \otimes \mathbf{R}_{\ell i j} \right) \widetilde{\mathbf{\Lambda}}_{\ell k} \right) \\ + \left(\frac{\pi}{2} - 1 \right) \sum_{(\ell,k)} \operatorname{tr} \left(\mathbf{\Sigma}_{\mathbf{y}_{\ell}} \widetilde{\mathbf{\Lambda}}_{\ell k} \right) + \operatorname{const}$$
(26)

$$= \sum_{(\ell,k)} \phi_{\ell k}^{\mathsf{H}} \left(\sum_{(i,j)} \mathbf{S}_{i\ell k j} \right) \phi_{\ell k} + \left(\frac{\pi}{2} - 1 \right) \sum_{(\ell,k)} \phi_{\ell k}^{\mathsf{H}} \left(\sum_{(i,j)} \mathbf{T}_{i\ell k j} \right) \phi_{\ell k}$$

+ const (27)

$$= \sum_{(\ell,k)} \phi_{\ell k}^{\mathsf{H}} \mathbf{M}_{\ell k} \phi_{\ell k} + \text{const.}$$
(28)

Here, we have

T

$$\widetilde{\boldsymbol{\Lambda}}_{\ell k} = \boldsymbol{\Lambda}_{\ell k} \boldsymbol{\Lambda}_{\ell k}^{\mathsf{H}},$$

$$\mathbf{S}_{\ell i j k}[p, q]$$

$$= \beta_{\ell i j} \sum_{m=1}^{M} \mathbf{R}_{\ell i j}[m, :] \widetilde{\boldsymbol{\Lambda}}_{\ell k}[(p-1)M+1: pM, m+(q-1)M],$$
(30)

$$\mathbf{T}_{\ell i j k}[p,q] = \begin{cases} \beta_{\ell i j} \sum_{m=1}^{M} \mathbf{R}_{\ell i j}[m,m] \\ \times \widetilde{\mathbf{A}}_{\ell k}[m+(p-1)M,m+(q-1)M], & \text{if } p = q, \\ 0, & \text{otherwise,} \end{cases}$$
(31)

$$\mathbf{M}_{\ell k} = \sum_{(i,j)} \left(\mathbf{S}_{\ell i j k} + \left(\frac{\pi}{2} - 1\right) \mathbf{T}_{\ell i j k} \right).$$
(32)

Finally, we note that const = $\sigma^2 \sum_{(\ell,k)} \operatorname{tr}(\widetilde{\Lambda}_{\ell k})$ does not depend on $\{\phi\}$. Leveraging the derived form, we obtain the optimal pilot $\phi_{\ell k}^*$ as $\phi_{\ell k}^* = (\mathbf{M}_{\ell k} + \eta_{\ell k} \mathbf{I}_{\tau M})^{-1} \mathbf{v}_{\ell k}$. Here, the Lagrangian multiplier $\eta_{\ell k}$ is adjusted by using the bisection search method to ensure that $\phi_{\ell k}^*$ does not exceed the power constraint (22b). By iterating the optimization process until the MSE converges, we find the local optimum $\phi_{\ell k}^*$.

V. NUMERICAL RESULTS

In this section, we numerically demonstrate the proposed pilot design method. For the simulation, we consider 7 hexagonal cells, where each BS is located at the center of the cell and separated by 0.5 km from adjacent BSs. We assume that 4 users are uniformly distributed in each cell. The transmission power of each user P is set to 23 dBm, while the noise power spectral density and bandwidth are set to -169 dBm/Hz and 20 MHz, respectively. For large-scale fading, the 3GPP model [19] was adopted, and the large-scale attenuation coefficient $\beta_{\ell ik}$ (dB) is modeled as

$$\beta_{\ell ik} = 128.1 + 37.6 \log_{10} \left(d_{\ell ik} \right) + \psi_{\ell ik}. \tag{33}$$

Here, $d_{\ell ik}$ (km) represents the distance between the BS and the corresponding user, and $\psi_{\ell ik}$ represents shadow fading and follows a log-normal distribution parameters $\mathcal{N}(0, 64)$. In addition, the correlated channel is modeled using an exponential model [20], where the channel covariance matrix $\mathbf{R}_{\ell ik}$ is expressed as

$$\mathbf{R}_{\ell i k}[m, n] = \begin{cases} \omega_{\ell i k}^{m-n}, & \text{if } m \ge n; \\ \mathbf{R}_{\ell i j}^{\mathsf{H}}[m, n], & \text{otherwise,} \end{cases}$$
(34)

where $\omega = v e^{j\theta}$, v = 0.5, and θ follows an i.i.d uniform distribution $U[0, 2\pi)$. The channel estimation performance was evaluated based on the normalized MSE, defined as

$$\text{NMSE} = \frac{\sum_{\ell} \sum_{k} \|\mathbf{h}_{\ell\ell k} - \mathbf{h}_{\ell\ell k}\|_{2}^{2}}{\sum_{\ell} \sum_{k} \|\mathbf{h}_{\ell\ell k}\|_{2}^{2}}.$$
 (35)

For the baseline methods, we consider the followings. i) the discrete Fourier transform (DFT) pilots, ii) the random pilots, iii) the FP based pilots [7], and iv) the NMSE lower bound [16]. To be specific, in the DFT pilots, we assign the pilot sequence to each user by normalizing τ column vectors of a DFT matrix, which are reused in each cell. In the FP based pilots [7], we directly apply the conventional FP algorithm to 1-bit ADC systems without any modifications. In the NMSE lower bound [16], we note that this bound was derived under the particular assumptions that i) a single-cell environment, ii) uncorrelated Rayleigh channel, and iii) max-min power control, while our proposed method is applicable in general multi-cell environments. For the channel estimation, we adopt the BLMMSE estimator [14]. For clarity, we refer to our proposed method as the Bussgang-aided FP (BFP) method.

In Fig. 1, we illustrate the NMSE vs. the transmit power. Since the NMSE lower bound [16] was derived under a single-cell scenario with max-min power control, to evaluate this in our environment, we adapt our setup to be fitted to [16]. Specifically, focusing on a certain cell, we forcefully fix $\beta_{\ell ik}$ values to the same constant and assume the uncorrelated Rayleigh fading, i.e., $\mathbf{R}_{\ell i k} = \mathbf{I}$. Additionally, we treat interference coming from the other cells as additive Gaussian noise, which not only simplifies the analysis but also effectively extends the existing NMSE lower bound to the multi-cell scenario. As observed in Fig. 1, the proposed BFP method outperforms other methods as well as the NMSE lower bound across all transmit power levels in terms of NMSE. Since this lower bound was obtained under the single-cell and uncorrelated case, the pilot contamination in a multi-cell and the impact on channel correlation was not incorporated. On the contrary to that, our BFP method is able to alleviate the inter-cell interference and adaptively capture the correlation across channels. Although the FP method also considers these aspects, it lacks the capability to account for the autocorrelation in the modified MSE caused by 1-bit ADCs. Therefore, our method achieves superior performance as it is designed to be well-suited for this environment.

It is worth noting that the MSE of the FP pilot degrades in the high transmit power region. In the high SNR regime, the impact of quantization noise becomes more significant than that of AWGN. However, since the FP pilot was designed without accounting for its effect on the MSE, it results in performance degradation in this regime.



Fig. 1. NMSE vs. transmit power

For more comprehensive performance evaluation, we also plot the cumulative distribution function (CDF) of the NMSE in Fig. 2. In this case, we conduct a system-level simulation, wherein we use general $\beta_{\ell ik}$ following [19]. In this case, the NMSE lower bound is not plotted as it is incompatible with the considered setup. Fig. 2 also shows that the proposed BFP method achieves the best NMSE over the other baseline methods. In the low NMSE region, where quantization distortion dominates, the performance gap between BFP and FP increases. On the other hand, in the high NMSE region, where inter-cell interference becomes dominant, the gap between BFP and DFT increases. These results align with Fig. 1.

VI. CONCLUSION

In this paper, we proposed a novel pilot design for 1-bit massive MIMO systems by assuming correlated Rayleigh channels and multi-cell environments. This addresses the limitations of existing approach confined to ideal (uncorrelated Rayleigh and single-cell) setups. Our key idea is to approximate the MSE obtained from BLMMSE to formulate a tractable optimization problem and solve it using the FP algorithm. Numerical results demonstrated superior NMSE performance over the existing baseline methods. Future research could focus on extending our framework to various system environments, such as a fewbit ADCs, frequency division duplex, and integrated sensing and communication.

REFERENCES

- J. Park, N. Lee, J. G. Andrews, and R. W. Heath, "On the optimal feedback rate in interference-limited multi-antenna cellular systems," *IEEE Trans. Wireless Commun.*, vol. 15, no. 8, pp. 5748–5762, 2016.
- [2] G. Caire, N. Jindal, M. Kobayashi, and N. Ravindran, "Multiuser MIMO achievable rates with downlink training and channel state feedback," *IEEE Trans. Inf. Theory*, vol. 56, no. 6, pp. 2845–2866, 2010.
- [3] H. Yin, D. Gesbert, M. Filippou, and Y. Liu, "A coordinated approach to channel estimation in large-scale multiple-antenna systems," *IEEE J. Sel. Areas Commun.*, vol. 31, no. 2, pp. 264–273, 2013.
- [4] T. L. Marzetta, "Noncooperative cellular wireless with unlimited numbers of base station antennas," *IEEE Trans. Wireless Commun.*, vol. 9, no. 11, pp. 3590–3600, 2010.
- [5] H. Al-Salihi, T. Van Chien, T. A. Le, and M. R. Nakhai, "A successive optimization approach to pilot design for multi-cell massive MIMO systems," *IEEE Commun. Lett.*, vol. 22, no. 5, pp. 1086–1089, 2018.



Fig. 2. CDF of NMSE

- [6] S. Stein Ioushua and Y. C. Eldar, "Pilot sequence design for mitigating pilot contamination with reduced RF chains," *IEEE Trans. Commun.*, vol. 68, no. 6, pp. 3536–3549, 2020.
- [7] K. Shen, H. V. Cheng, X. Chen, Y. C. Eldar, and W. Yu, "Enhanced channel estimation in massive MIMO via coordinated pilot design," *IEEE Trans. Commun.*, vol. 68, no. 11, pp. 6872–6885, 2020.
- [8] Y. Wu, S. Ma, and Y. Gu, "Distributed non-orthogonal pilot design for multi-cell massive MIMO systems," in *Proc. IEEE Int. Conf. Acoust., Speech and Sig. Proc.*, 2020, pp. 5195–5199.
- [9] B. Lim, W. J. Yun, J. Kim, and Y.-C. Ko, "Joint pilot design and channel estimation using deep residual learning for multi-cell massive MIMO under hardware impairments," *IEEE Trans. Veh. Technol.*, vol. 71, no. 7, pp. 7599–7612, 2022.
- [10] K. Shen and W. Yu, "Fractional programming for communication systems—Part I: Power control and beamforming," *IEEE Trans. Signal Process.*, vol. 66, no. 10, pp. 2616–2630, 2018.
- [11] R. Walden, "Analog-to-digital converter survey and analysis," *IEEE J. Sel. Areas Commun.*, vol. 17, no. 4, pp. 539–550, 1999.
- [12] J. Choi, J. Park, and N. Lee, "Energy efficiency maximization precoding for quantized massive MIMO systems," *IEEE Trans. Wireless Commun.*, vol. 21, no. 9, pp. 6803–6817, 2022.
- [13] A. Mezghani and J. A. Nossek, "Analysis of 1-bit output noncoherent fading channels in the low SNR regime," in *Proc. IEEE Int. Symp. Info. Theory*, 2009, pp. 1080–1084.
- [14] Y. Li, C. Tao, G. Seco-Granados, A. Mezghani, A. L. Swindlehurst, and L. Liu, "Channel estimation and performance analysis of one-bit massive MIMO systems," *IEEE Trans. Signal Process.*, vol. 65, no. 15, pp. 4075–4089, 2017.
- [15] Q. Wan, J. Fang, H. Duan, Z. Chen, and H. Li, "Generalized Bussgang LMMSE channel estimation for one-bit massive MIMO systems," *IEEE Trans. Wireless Commun.*, vol. 19, no. 6, pp. 4234–4246, 2020.
- [16] Z. Yi, P. Wei, L. Zhang, and H. Zhang, "Pilot design of the 1-bit massive MIMO in Rayleigh-fading channel," *IEEE Trans. Wireless Commun.*, vol. 21, no. 8, pp. 5903–5915, 2022.
- [17] N. Kim, I. P. Roberts, and J. Park, "Splitting messages in the dark–Ratesplitting multiple access for FDD massive MIMO without CSI feedback," *IEEE Trans. Wireless Commun.*, pp. 1–1, 2025.
- [18] K. Shen, W. Yu, L. Zhao, and D. P. Palomar, "Optimization of MIMO device-to-device networks via matrix fractional programming: A minorization-maximization approach," *IEEE/ACM Trans. Networking*, vol. 27, no. 5, pp. 2164–2177, 2019.
- [19] W. Yu, T. Kwon, and C. Shin, "Multicell coordination via joint scheduling, beamforming, and power spectrum adaptation," *IEEE Trans. Wireless Commun.*, vol. 12, no. 7, pp. 1–14, 2013.
- [20] S. Loyka, "Channel capacity of MIMO architecture using the exponential correlation matrix," *IEEE Commun. Lett.*, vol. 5, no. 9, pp. 369–371, 2001.