

# Mitigating Popularity Bias in Collaborative Filtering through Fair Sampling

Jiahao Liu  
Fudan University  
Shanghai, China  
jiahaoliu23@m.fudan.edu.cn

Dongsheng Li  
Microsoft Research Asia  
Shanghai, China  
dongсли@microsoft.com

Hansu Gu  
Independent  
Seattle, United States  
hansug@acm.org

Peng Zhang  
Fudan University  
Shanghai, China  
zhangpeng\_@fudan.edu.cn

Tun Lu  
Fudan University  
Shanghai, China  
lutun@fudan.edu.cn

Li Shang  
Fudan University  
Shanghai, China  
lishang@fudan.edu.cn

Ning Gu  
Fudan University  
Shanghai, China  
ninggu@fudan.edu.cn

## Abstract

Recommender systems often suffer from popularity bias, where frequently interacted items are overrepresented in recommendations. This bias stems from propensity factors influencing training data, leading to imbalanced exposure. In this paper, we introduce a Fair Sampling (FS) approach to address this issue by ensuring that both users and items are selected with equal probability as positive and negative instances. Unlike traditional inverse propensity score (IPS) methods, FS does not require propensity estimation, eliminating errors associated with inaccurate calculations. Our theoretical analysis demonstrates that FS effectively neutralizes the influence of propensity factors, achieving unbiased learning. Experimental results validate that FS outperforms state-of-the-art methods in both point-wise and pair-wise recommendation tasks, enhancing recommendation fairness without sacrificing accuracy. The implementation is available at <https://anonymous.4open.science/r/Fair-Sampling>.

## CCS Concepts

• Information systems → Recommender systems.

## Keywords

unbiased ranking, collaborative filtering, implicit feedback

## ACM Reference Format:

Jiahao Liu, Dongsheng Li, Hansu Gu, Peng Zhang, Tun Lu, Li Shang, and Ning Gu. 2025. Mitigating Popularity Bias in Collaborative Filtering through Fair Sampling. In *Proceedings of Make sure to enter the correct conference title*

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from [permissions@acm.org](mailto:permissions@acm.org).  
*Conference acronym 'XX, Woodstock, NY*

© 2025 Copyright held by the owner/author(s). Publication rights licensed to ACM.  
ACM ISBN 978-1-4503-XXXX-X/2025/06  
<https://doi.org/XXXXXXX.XXXXXXX>

from your rights confirmation email (Conference acronym 'XX). ACM, New York, NY, USA, 6 pages. <https://doi.org/XXXXXXX.XXXXXXX>

## 1 Introduction

Recommender systems gather vast amounts of data on user behavior, especially implicit feedback from user-item interactions, to model user preferences [15–20, 29]. However, user interactions are shaped not only by intrinsic user preferences but also by external factors, such as item popularity [30]. Directly modeling observed user interactions may lead to predictions that are overly skewed toward popular items [26]. The Matthew effect exacerbates this by making long-tail items less likely to be recommended, thus diminishing the novelty, diversity, and fairness of recommendations [8].

Several methods based on inverse propensity scores (IPS) [24, 25] have been proposed to mitigate popularity bias by weighting samples during model training. However, estimating propensity scores in practical applications can be highly challenging. These methods often rely on overly simplified assumptions—for instance, assuming that the propensity score depends solely on item popularity—which can lead to high variance [22]. Although variance reduction techniques, such as clipping the scores, can be applied, these adjustments compromise unbiasedness. Furthermore, the difficulty in accurately estimating propensity scores prevents IPS-based methods from effectively eliminating popularity bias.

In this paper, we first analyze the optimization objectives of ideal and classical loss functions, identifying that the bias in classical loss functions stems from the inclusion of propensity factors in the model output. Meanwhile, popular items are more likely to be treated as positive samples during training, which leads to higher propensity factor scores and subsequently higher interaction scores, with popularity being mistakenly interpreted as user preference. Building on this insight, we propose a fair sampling (FS) method that ensures each user and each item has an equal likelihood of being selected as both positive and negative instances during training, thus preventing popular items from being overly selected as positive samples. Theoretical analysis demonstrates that

the proposed FS can effectively eliminate the influence of propensity factors without the need to estimate the propensity score, thereby mitigating popularity bias and overcoming the limitations of IPS-based methods.

FS is a sampling-level optimization method that can be applied to both point-wise and pair-wise loss functions. Depending on the type of loss function, we implement FS-Point for point-wise loss and FS-Pair for pair-wise loss. We compare FS-Point and FS-Pair against their respective point-wise and pair-wise baselines. Experimental results show that FS achieves state-of-the-art performance.

## 2 Related Work

IPS-based methods mitigate popularity bias in recommender systems through sample weighting. We categorize related work by the type of loss function: point-wise or pair-wise.

**Point-wise.** Rel-MF [25] formulates interaction occurrence as a two-step process—exposure and interaction—and introduces an unbiased point-wise loss function. DU [10] refines this method by enhancing propensity score estimation. CJMF [34] introduces a joint learning framework to simultaneously model unbiased user-item relevance and propensity. BISER [11] addresses item bias via self-inverse propensity weighting and employs bilateral unbiased learning to unify two complementary models. More recently, ReCRec [14] improves bias correction by distinguishing unexposed from disliked items, enabling better reasoning over unclicked data.

**Pair-wise.** UBPR [24] builds on the two-step interaction assumption to introduce an unbiased pair-wise loss function. UPL [22] extends this approach with a variance-reduced learning method. CPR [26] redefines unbiasedness in ranking and leverages cross pairs to improve unbiased learning. UpliftRec [4] applies uplift modeling to dynamically optimize top-N recommendations, revealing latent user preferences while maximizing click-through rates. Additionally, PU [3] models feedback labels as a noisy proxy for exposure outcomes and integrates a theoretically noise-resistant loss function into propensity estimation.

## 3 Methods

We first introduce the notations in Section 3.1 and formalize the ideal and classic loss functions in Sections 3.2 and 3.3, respectively. Then, in Section 3.4, we analyze the bias in the classic loss function by comparing its optimization objective with that of the ideal loss function. Finally, in Section 3.5, we present the proposed fair sampling (FS) method and analyze how it mitigates popularity bias.

### 3.1 Notations

For a user  $u \in \mathcal{U}$  and an item  $i \in \mathcal{I}$ , we refer to a user-item pair as a *positive pair* if an interaction occurs between them; otherwise, we call it a *negative pair*. A interaction occurs through a *two-step process* [24, 25]: first, a user **observes** an item; then, based on how **relevant** the item is to the user's preferences, the user decide whether to **interact** with it. Next, we define three binary indicator matrices: (1) **Observation matrix**  $O \in \{0, 1\}^{|\mathcal{U}| \times |\mathcal{I}|}$ , where  $O_{u,i}$  indicates whether  $u$  has observed  $i$  (or, equivalently, whether  $i$  has been exposed to  $u$ ); (2) **Relevance matrix**  $R \in \{0, 1\}^{|\mathcal{U}| \times |\mathcal{I}|}$ , where  $R_{u,i}$  indicates whether  $u$  would interact with  $i$  given  $O_{u,i} = 1$  (or, equivalently, whether  $u$  likes  $i$ ); (3) **Interaction matrix**  $Y \in$

$\{0, 1\}^{|\mathcal{U}| \times |\mathcal{I}|}$ , where  $Y_{u,i}$  indicates whether  $u$ - $i$  is a positive pair. Note that only  $Y$  is observable, while both  $O$  and  $R$  are latent variables.

Clearly,  $u$ - $i$  is a positive pair ( $Y_{u,i} = 1$ ) if and only if  $u$  has observed  $i$  ( $O_{u,i} = 1$ ) and the two have high relevance ( $R_{u,i} = 1$ ). This can be expressed as  $Y_{u,i} = O_{u,i} \cdot R_{u,i}$ , or in matrix form,  $Y = O \odot R$ . Consequently,

$$\begin{aligned} P(Y_{u,i} = 1) &= P(O_{u,i} = 1, R_{u,i} = 1) \\ &= P(O_{u,i} = 1 | R_{u,i} = 1) \cdot P(R_{u,i} = 1), \end{aligned} \quad (1)$$

where  $P(R_{u,i} = 1)$  denotes the relevance probability between  $u$  and  $i$ , and  $P(O_{u,i} = 1 | R_{u,i} = 1)$  represents the exposure probability—the probability that  $i$  is observed by  $u$  given their relevance. Assuming the exposure probability can be decomposed into user propensity, item propensity, and user-item relevance, it can be expressed as:

$$P(O_{u,i} = 1 | R_{u,i} = 1) = \theta_u \cdot \theta_i \cdot P(R_{u,i} = 1)^\alpha. \quad (2)$$

Here,  $\theta_u$  and  $\theta_i$  are user-specific and item-specific propensity factors, respectively, which tend to have higher values for active users and popular items. The term  $P(R_{u,i} = 1)^\alpha$  indicates that a higher relevance score increases the exposure probability, where  $\alpha$  is a positive constant used to moderate its influence.

### 3.2 Ideal Point-wise Loss and Pair-wise Loss

Ideally, a recommendation model should reflect users' intrinsic preferences  $R$  rather than simply imitating observed user behaviors  $Y$ . For this to hold, users must observe **all** items and decide whether to interact with them based on relevance. In this scenario, all elements of  $O$  are assigned a value of 1, making  $Y$  identical to  $R$ .

**3.2.1 Ideal Point-wise Loss.** One commonly used point-wise loss is the cross-entropy loss. Let  $s_{u,i}$  denote the predicted score of  $u$ - $i$  produced by the model, then  $\delta^+(u, i) = -\log(s_{u,i})$  and  $\delta^-(u, i) = -\log(1 - s_{u,i})$ , where  $\delta^+(u, i)$  and  $\delta^-(u, i)$  denote the loss contributions for  $u$ - $i$  being a positive and a negative pair, respectively. The **ideal point-wise loss** is defined as follows:

$$\mathcal{L}_{\text{ideal}}^{\text{point}} = \sum_{(u,i;R_{u,i}) \in \mathcal{U} \times \mathcal{I}} [R_{u,i} \cdot \delta^+(u, i) + (1 - R_{u,i}) \cdot \delta^-(u, i)]. \quad (3)$$

**3.2.2 Ideal Pair-wise Loss.** One commonly used pair-wise loss is the BPR loss, which is defined as  $\zeta(u, i, j) = -\ln \sigma(s_{u,i} - s_{u,j})$ , where  $\sigma(\cdot)$  is the sigmoid function. The **ideal pair-wise loss** is defined as follows:

$$\mathcal{L}_{\text{ideal}}^{\text{pair}} = \sum_{(u,i,j;R_{u,i},R_{u,j}) \in \mathcal{U} \times \mathcal{I} \times \mathcal{I}} [R_{u,i} \cdot (1 - R_{u,j}) \cdot \zeta(u, i, j)]. \quad (4)$$

**3.2.3 Discussion.** The ideal loss functions can guide the model to learn users' inherent preferences. However, since  $R$  is unobservable, the ideal loss functions **cannot** be computed directly.

### 3.3 Classic Point-wise Loss and Pair-wise Loss

**3.3.1 Classic Point-wise Loss.** WMF [6] introduced a **point-wise loss** for modeling implicit feedback data:

$$\mathcal{L}_{\text{bias}}^{\text{point}} = \sum_{(u,i;Y_{u,i}) \in \mathcal{U} \times \mathcal{I}} [Y_{u,i} \cdot \delta^+(u, i) + (1 - Y_{u,i}) \cdot \delta^-(u, i)]. \quad (5)$$

3.3.2 *Classic Pair-wise Loss.* BPR [23] introduced a **pair-wise loss** for modeling implicit feedback data:

$$\mathcal{L}_{\text{bias}}^{\text{pair}} = \sum_{(u,i,j;Y_{u,i},Y_{u,j}) \in \mathcal{U} \times \mathcal{I} \times \mathcal{I}} [Y_{u,i} \cdot (1 - Y_{u,j}) \cdot \zeta(u, i, j)]. \quad (6)$$

3.3.3 *Discussion.* Classic loss functions are designed to directly model the interaction matrix  $Y$ . Since  $Y$  depends not only on  $R$  but also on  $O$ , classic loss functions provide biased approximations of the ideal loss functions.

### 3.4 Analysis

Let  $s_{u,i}^{\text{ideal}}$  and  $s_{u,i}^{\text{bias}}$  denote the predicted results obtained by optimizing the model with the ideal loss ( $\mathcal{L}_{\text{ideal}}^{\text{point}}$  or  $\mathcal{L}_{\text{ideal}}^{\text{pair}}$ ) and the classic loss ( $\mathcal{L}_{\text{bias}}^{\text{point}}$  or  $\mathcal{L}_{\text{bias}}^{\text{pair}}$ ), respectively.  $s_{u,i}^{\text{ideal}}$  captures users' intrinsic preferences  $R$ , while  $s_{u,i}^{\text{bias}}$  reflects users' interaction behaviors  $Y$ . Therefore,

$$\begin{aligned} s_{u,i}^{\text{ideal}} &= P(R_{u,i} = 1) > 0, \\ s_{u,i}^{\text{bias}} &= P(Y_{u,i} = 1) = \theta_u \theta_i P(R_{u,i} = 1)^{\alpha+1} > 0. \end{aligned} \quad (7)$$

Intuitively, classic loss functions introduce biases as they inherently incorporate propensity factors into the model's output. As a result, even if user  $u$  exhibits the same level of preference for both items  $i$  and  $j$  ( $P(R_{u,i} = 1) = P(R_{u,j} = 1)$ ), the optimization outcome of classic loss functions tends to favor the item with a higher propensity factor ( $\theta_u \theta_i P(R_{u,i} = 1)^\alpha$  or  $\theta_u \theta_j P(R_{u,j} = 1)^\alpha$ ).

3.4.1 *Point-wise Loss.* The optimization objective of  $\mathcal{L}_{\text{ideal}}^{\text{point}}$  is to increase  $s_{u,i}^{\text{ideal}}$  when  $R_{u,i} = 1$  and decrease  $s_{u,i}^{\text{ideal}}$  when  $R_{u,i} = 0$ . We use  $\Delta x$  to denote the change in  $x$  after one optimization step (e.g., gradient descent). Therefore,

$$\begin{cases} \Delta s_{u,i}^{\text{ideal}} = \Delta P(R_{u,i} = 1) > 0 & \text{if } R_{u,i} = 1, \\ -\Delta s_{u,i}^{\text{ideal}} = -\Delta P(R_{u,i} = 1) > 0 & \text{if } R_{u,i} = 0, \end{cases} \quad (8)$$

which can also be written as:

$$\begin{cases} \Delta \ln P(R_{u,i} = 1) > 0 & \text{if } R_{u,i} = 1, \\ -\Delta \ln P(R_{u,i} = 1) > 0 & \text{if } R_{u,i} = 0. \end{cases} \quad (9)$$

While for  $\mathcal{L}_{\text{bias}}^{\text{point}}$ , its optimization objective is to increase  $s_{u,i}^{\text{bias}}$  when  $Y_{u,i} = 1$  and decrease  $s_{u,i}^{\text{bias}}$  when  $Y_{u,i} = 0$ . Therefore,

$$\begin{cases} \Delta s_{u,i}^{\text{bias}} = \Delta P(Y_{u,i} = 1) > 0 & \text{if } Y_{u,i} = 1, \\ -\Delta s_{u,i}^{\text{bias}} = -\Delta P(Y_{u,i} = 1) > 0 & \text{if } Y_{u,i} = 0, \end{cases} \quad (10)$$

which can also be written as<sup>1</sup>:

$$\begin{cases} \Delta \ln P(Y_{u,i} = 1) \\ = \Delta \ln \theta_u + \Delta \ln \theta_i + (\alpha + 1) \Delta \ln P(R_{u,i} = 1) > 0 & \text{if } Y_{u,i} = 1, \\ -\Delta \ln P(Y_{u,i} = 1) \\ = -\Delta \ln \theta_u - \Delta \ln \theta_i - (\alpha + 1) \Delta \ln P(R_{u,i} = 1) > 0 & \text{if } Y_{u,i} = 0. \end{cases} \quad (11)$$

<sup>1</sup>Note that  $\Delta(x + y) = \Delta x + \Delta y$ , and  $\Delta ax = a \Delta x$ , where  $a$  is a constant.

**Table 1: Dataset statistics.**

Dataset	# User	# Item	# Interaction	Density
Kindle	6,214	7,410	305,782	0.0083
Gowalla	5,992	5,639	281,412	0.0042
Yelp	12,471	10,363	543,487	0.0066

3.4.2 *Pair-wise Loss.* Assume that  $u-i$  is a positive pair, and  $u-j$  is a negative pair. The optimization objective of  $\mathcal{L}_{\text{ideal}}^{\text{pair}}$  is to increase the margin between  $s_{u,i}^{\text{ideal}}$  and  $s_{u,j}^{\text{ideal}}$ . Therefore,

$$\Delta(\ln P(R_{u,i} = 1) - \ln P(R_{u,j} = 1)) = \Delta \ln \frac{P(R_{u,i} = 1)}{P(R_{u,j} = 1)} > 0. \quad (12)$$

While for  $\mathcal{L}_{\text{bias}}^{\text{pair}}$ , its optimization objective is to increase the margin between  $s_{u,i}^{\text{bias}}$  and  $s_{u,j}^{\text{bias}}$ . Therefore,

$$\begin{aligned} &\Delta(\ln P(Y_{u,i} = 1) - \ln P(Y_{u,j} = 1)) \\ &= \Delta \ln \frac{\theta_j}{\theta_i} + (\alpha + 1) \Delta \ln \frac{P(R_{u,i} = 1)}{P(R_{u,j} = 1)} > 0. \end{aligned} \quad (13)$$

3.4.3 *Discussion.* By comparing Equation (9) with (11), and Equation (12) with (13), it can be observed that  $\mathcal{L}_{\text{bias}}^{\text{point}}$  and  $\mathcal{L}_{\text{bias}}^{\text{pair}}$  improperly optimize the propensity factors ( $\theta_u$  and  $\theta_i$  for  $\mathcal{L}_{\text{bias}}^{\text{point}}$ , and  $\theta_i$  and  $\theta_j$  for  $\mathcal{L}_{\text{bias}}^{\text{pair}}$ ). Since popular items and active users are more frequently selected to form positive pairs during training, their propensity factors tend to be higher. Ultimately, propensity factors related to exposure probability  $P(O_{u,i} = 1 | R_{u,i} = 1)$ , rather than relevance probability  $P(R_{u,i} = 1)$ , lead to higher interaction scores  $P(Y_{u,i} = 1)$ , which is not the intended outcome.

### 3.5 Fair Sampling

Fair sampling (FS) constructs supplementary sample(s) for each original sample in the classic loss during model training, helping to prevent the improper optimization of propensity factors and thereby mitigating popularity bias. Depending on the type of loss function, FS has two variants: **FS-Point**, designed for point-wise loss, and **FS-Pair**, designed for pair-wise loss.

3.5.1 *FS-Point.* The sample set utilized by the classic point-wise loss function  $\mathcal{L}_{\text{bias}}^{\text{point}}$  is:

$$\mathcal{D}_{\text{bias}}^{\text{point}} = \{(u, i; Y_{u,i}) | u \in \mathcal{U}, i \in \mathcal{I}\}. \quad (14)$$

For each  $(u, i; Y_{u,i}) \in \mathcal{D}_{\text{bias}}^{\text{point}}$ , we can find a corresponding  $(\tilde{u}, \tilde{i})$  that satisfies the conditions  $Y_{\tilde{u}, \tilde{i}} = Y_{u,i}$ ,  $Y_{\tilde{u}, i} = 1 - Y_{u,i}$ , and  $Y_{u, \tilde{i}} = 1 - Y_{u,i}$ . Then, we can obtain the sample set for FS-Point loss by combining them together:

$$\mathcal{D}_{\text{FS}}^{\text{point}} = \mathcal{D}_{\text{bias}}^{\text{point}} \cup \{(\tilde{u}, \tilde{i}; Y_{\tilde{u}, \tilde{i}}), (\tilde{u}, i; Y_{\tilde{u}, i}), (u, \tilde{i}; Y_{u, \tilde{i}}) | (u, i; Y_{u,i}) \in \mathcal{D}_{\text{bias}}^{\text{point}}\}. \quad (15)$$

Finally, **FS-Point loss** is defined as:

$$\mathcal{L}_{\text{FS}}^{\text{point}} = \sum_{(u,i;Y_{u,i}) \in \mathcal{D}_{\text{FS}}^{\text{point}}} [Y_{u,i} \cdot \delta^+(u, i) + (1 - Y_{u,i}) \cdot \delta^-(u, i)]. \quad (16)$$

We assume  $Y_{u,i} = 1$  (a similar conclusion can be drawn when  $Y_{u,i} = 0$ ). Based on Equation (11), when  $(u, i; Y_{u,i} = 1)$  is input

**Table 2: Overall performance comparison.**

Model			Kindle			Gowalla			Yelp		
			Recall $\uparrow$	NDCG $\uparrow$	ARP $\downarrow$	Recall $\uparrow$	NDCG $\uparrow$	ARP $\downarrow$	Recall $\uparrow$	NDCG $\uparrow$	ARP $\downarrow$
Point-wise	IPS	WMF	0.1095	0.0979	1896	0.1052	0.0924	3995	0.0398	0.0297	4231
		Rel-MF	0.1192	0.1088	1660	0.1116	0.0975	3800	0.0471	0.0359	3651
		DU	0.1264	0.1141	1497	0.1168	0.1018	3356	0.0504	0.0382	3286
		CJMF	0.1254	0.1133	1534	0.1134	0.0993	3645	0.0487	0.0375	3327
		BISER	0.1298	0.1183	1403	0.1184	0.1036	3126	0.0512	0.0398	3025
		ReCRec	0.1392	0.1247	1280	0.1202	0.1032	2839	0.0523	0.0409	2865
	Causal	ExpoMF	0.1353	0.1226	1354	0.1186	0.1013	3173	0.0514	0.0401	3105
		CauseE	0.1336	0.1233	1447	0.1179	0.1005	3159	0.0528	0.0408	3025
		MACR	0.1364	0.1237	1303	0.1192	0.1014	2854	0.0523	0.0412	2730
	<b>Our</b>	<b>FS-Point</b>	<b>0.1413</b>	<b>0.1263</b>	<b>1175</b>	<b>0.1217</b>	<b>0.1067</b>	<b>2261</b>	<b>0.0554</b>	<b>0.0437</b>	<b>2420</b>
Pair-wise	IPS	BPR	0.1431	0.1169	1572	0.1179	0.0943	3703	0.0527	0.0388	3939
		UBPR	0.1414	0.1196	1156	0.1125	0.0936	2447	0.0600	0.0452	2489
		CPR	0.1516	0.1275	1406	0.1240	0.1023	2509	0.0634	0.0478	2901
		UPL	0.1483	0.1241	1263	0.1194	0.0981	2485	0.0616	0.0457	2641
		UpliftRec	0.1532	0.1289	1120	0.1239	0.1026	2018	0.0645	0.0485	2348
		PU	0.1545	0.1293	1087	0.1258	0.1033	1932	0.0673	0.0498	2083
	Causal	DICE	0.1454	0.1195	1303	0.1160	0.0966	2302	0.0599	0.0455	2459
		PD	0.1418	0.1214	1254	0.1162	0.0953	2388	0.0613	0.0469	2404
		CGCL	0.1591	0.1317	1034	0.1272	0.1031	1703	0.0685	0.0506	1839
	<b>Our</b>	<b>FS-Pair</b>	<b>0.1652</b>	<b>0.1384</b>	<b>865</b>	<b>0.1294</b>	<b>0.1052</b>	<b>1140</b>	<b>0.0741</b>	<b>0.0552</b>	<b>1534</b>

into  $\mathcal{L}_{\text{FS}}^{\text{point}}$  for optimization,  $\ln \theta_u$  and  $\ln \theta_i$  are amplified. However, when the corresponding supplementary samples— $(\tilde{u}, \tilde{i}; Y_{\tilde{u}, \tilde{i}} = 1)$ ,  $(\tilde{u}, i; Y_{\tilde{u}, i} = 0)$ , and  $(u, \tilde{i}; Y_{u, \tilde{i}} = 0)$ —are input into  $\mathcal{L}_{\text{FS}}^{\text{point}}$  for optimization, the optimization effect on the propensity factors is offset:

$$\begin{aligned} & (\Delta \ln \theta_u + \Delta \ln \theta_i) + (\Delta \ln \theta_{\tilde{u}} + \Delta \ln \theta_{\tilde{i}}) + \\ & (-\Delta \ln \theta_{\tilde{u}} - \Delta \ln \theta_i) + (-\Delta \ln \theta_u - \Delta \ln \theta_{\tilde{i}}) = 0. \end{aligned} \quad (17)$$

**3.5.2 FS-Pair.** The sample set utilized by the classic pair-wise loss function  $\mathcal{L}_{\text{bias}}^{\text{pair}}$  is:

$$\mathcal{D}_{\text{bias}}^{\text{pair}} = \{(u, i, j; Y_{u,i}, Y_{u,j}) | u \in \mathcal{U}, i, j \in \mathcal{I}\}. \quad (18)$$

For each  $(u, i, j; Y_{u,i}, Y_{u,j}) \in \mathcal{D}_{\text{bias}}^{\text{pair}}$ , we can find a corresponding  $(\tilde{u}, j, i)$  that satisfies the conditions  $Y_{\tilde{u}, j} = Y_{u,i}$  and  $Y_{\tilde{u}, i} = Y_{u,j}$ . Then, we can obtain the sample set for FS-Pair loss by combining them together:

$$\mathcal{D}_{\text{FS}}^{\text{pair}} = \mathcal{D}_{\text{bias}}^{\text{pair}} \cup \{(\tilde{u}, j, i; Y_{\tilde{u}, j}, Y_{\tilde{u}, i}) | (u, i, j) \in \mathcal{D}_{\text{bias}}^{\text{pair}}\} \quad (19)$$

Finally, **FS-Pair loss** is defined as:

$$\mathcal{L}_{\text{FS}}^{\text{pair}} = \sum_{(u, i, j; Y_{u,i}, Y_{u,j}) \in \mathcal{D}_{\text{FS}}^{\text{pair}}} [Y_{u,i} \cdot (1 - Y_{u,j}) \cdot \zeta(u, i, j)]. \quad (20)$$

Since a sample contributes to the loss only when  $Y_{u,i} = 1$  and  $Y_{u,j} = 0$ , we focus on this case. Based on Equation (13), when  $(u, i, j; Y_{u,i} = 1, Y_{u,j} = 0)$  is input into  $\mathcal{L}_{\text{FS}}^{\text{pair}}$  for optimization,  $\ln \frac{\theta_i}{\theta_j}$  is amplified. However, when the corresponding supplementary sample  $(\tilde{u}, j, i; Y_{\tilde{u}, j} = 1, Y_{\tilde{u}, i} = 0)$  is input into  $\mathcal{L}_{\text{FS}}^{\text{pair}}$  for optimization,  $\ln \frac{\theta_j}{\theta_i}$  is amplified, which offsets the optimization effect on the propensity factors:

$$\Delta \ln \frac{\theta_i}{\theta_j} + \Delta \ln \frac{\theta_j}{\theta_i} = \Delta (\ln \frac{\theta_i}{\theta_j} + \ln \frac{\theta_j}{\theta_i}) = 0. \quad (21)$$

**3.5.3 Discussion.** The idea of FS is simple—whenever a user or item is chosen to form a positive/negative pair, the user or item is simultaneously selected to form a corresponding negative/positive pair. Equations (17) and (21) indicate that FS-Point loss and FS-Pair loss no longer optimize propensity factors. Consequently, only the preference-related factor  $P(R_{u,i} = 1)$  is optimized, effectively mitigating the popularity bias. Note that FS does not require estimating the propensity score, which avoids the incomplete removal of popularity bias in IPS-based methods, which stems from their inability to estimate the propensity score accurately.

## 4 Experiments

### 4.1 Settings

**4.1.1 Datasets.** We experiment with three widely used datasets: Amazon Review (Kindle) [21], Gowalla [5], and Yelp. These datasets contain log data capturing observed user behavior. Under the two-step interaction assumption, these datasets exhibit popularity bias. We retain only interactions with ratings  $\geq 4$  and ensure that both users and items have at least 10 interactions. Table 1 presents the statistics of the processed datasets.

Following prior offline evaluation protocols [2, 12, 28], we construct unbiased validation and test sets by sampling from the full dataset with equal selection probability for each item. The remaining data serves as the training set. The dataset is split into training, validation, and test sets in a 7:1:2 ratio.

**4.1.2 Evaluation.** We evaluate performance using three metrics: Recall@K, NDCG@K, and ARP@K, with K set to 20 by default. Recall@K and NDCG@K are widely used to assess recommendation accuracy. Average Recommendation Popularity at K (ARP@K) serves as a complementary metric for measuring recommendation bias [1, 31]. It calculates the average popularity of the top-K recommended items per user, where lower ARP@K values indicate

reduced bias. To ensure result reliability, we report the average outcomes over five independent runs.

**4.1.3 Baselines.** All methods introduced in Section 2 serve as baselines. Additionally, we incorporate several causal inference methods that quantify popularity bias during training and mitigate it during inference. Specifically, these methods consist of three point-wise approaches—ExpoMF [13], CauseE [2], and MACR [27]—and three pair-wise approaches—PD [32], DICE [33], and CGCL [7]. To ensure fairness, all methods use MF [9] as the backbone model and share the same hyperparameter search space. All point-wise methods use cross-entropy loss, while all pair-wise methods use BPR loss.

## 4.2 Results

As shown in Table 2, FS-Point achieves the highest Recall and NDCG, and the lowest APR among point-wise learning methods. Similarly, FS-Pair achieves the best performance in these metrics among pair-wise methods. This suggests that, compared to other baselines, FS more effectively mitigates the influence of popularity bias, increasing the likelihood of recommending unpopular items without sacrificing recommendation accuracy. Notably, despite its simplicity, theoretical analysis confirms that FS completely eliminates popularity bias, enabling optimal performance under the current evaluation strategy, where the test set is designed to be unaffected by item popularity.

## 5 Conclusions

We propose a fair sampling (FS) method, which mitigates popularity bias in collaborative filtering by ensuring that each item appears equally as both a positive and negative sample during training. Both theoretical analysis and experimental results demonstrate the effectiveness of the proposed FS method. A potential limitation of FS is that it completely overlooks the influence of popularity, even though popularity is often correlated with higher quality. Strategically adjusting the sampling ratio between popular and non-popular items may help balance recommendation diversity and quality. Applying the concept of fair sampling at the attribute level is a promising avenue for future research.

## Acknowledgments

## References

- [1] Himan Abdollahpouri, Robin Burke, and Bamshad Mobasher. 2019. Managing popularity bias in recommender systems with personalized re-ranking. *arXiv preprint arXiv:1901.07555* (2019).
- [2] Stephen Bonner and Flavian Vasile. 2018. Causal embeddings for recommendation. In *Proceedings of the 12th ACM conference on recommender systems*. 104–112.
- [3] Tianwei Cao, Qianqian Xu, Zhiyong Yang, Zhanyu Ma, and Qingming Huang. 2024. Practically Unbiased Pairwise Loss for Recommendation with Implicit Feedback. *IEEE Transactions on Pattern Analysis and Machine Intelligence* (2024).
- [4] Jiaju Chen, Wang Wenjie, Chongming Gao, Peng Wu, Jianxiong Wei, and Qingsong Hua. 2024. Treatment Effect Estimation for User Interest Exploration on Recommender Systems. In *Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval*. 1861–1871.
- [5] Eunjoon Cho, Seth A Myers, and Jure Leskovec. 2011. Friendship and mobility: user movement in location-based social networks. In *Proceedings of the 17th ACM SIGKDD international conference on Knowledge discovery and data mining*. 1082–1090.
- [6] Yifan Hu, Yehuda Koren, and Chris Volinsky. 2008. Collaborative filtering for implicit feedback datasets. In *2008 Eighth IEEE international conference on data mining*. Ieee, 263–272.
- [7] Meng Jian, Yulong Bai, Xusong Fu, Jingjing Guo, Ge Shi, and Lifang Wu. 2024. Counterfactual Graph Convolutional Learning for Personalized Recommendation. *ACM Transactions on Intelligent Systems and Technology* (2024).
- [8] Anastasiia Klimashevskaya, Dietmar Jannach, Mehdi Elahi, and Christoph Trattner. 2024. A survey on popularity bias in recommender systems. *User Modeling and User-Adapted Interaction* 34, 5 (2024), 1777–1834.
- [9] Yehuda Koren, Robert Bell, and Chris Volinsky. 2009. Matrix factorization techniques for recommender systems. *Computer* 42, 8 (2009), 30–37.
- [10] Jae-woong Lee, Seongmin Park, and Jongwuk Lee. 2021. Dual unbiased recommender learning for implicit feedback. In *Proceedings of the 44th International ACM SIGIR Conference on Research and Development in Information Retrieval*. 1647–1651.
- [11] Jae-woong Lee, Seongmin Park, Joonseok Lee, and Jongwuk Lee. 2022. Bilateral Self-unbiased Learning from Biased Implicit Feedback. In *Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval*. 29–39.
- [12] Dawen Liang, Laurent Charlin, and David M Blei. 2016. Causal inference for recommendation. In *Causation: Foundation to Application, Workshop at UAI. AUAI*.
- [13] Dawen Liang, Laurent Charlin, James McInerney, and David M Blei. 2016. Modeling user exposure in recommendation. In *Proceedings of the 25th international conference on World Wide Web*. 951–961.
- [14] Siyi Lin, Sheng Zhou, Jiawei Chen, Yan Feng, Qihao Shi, Chun Chen, Ying Li, and Can Wang. 2024. ReCRec: Reasoning the causes of implicit feedback for debiased recommendation. *ACM Transactions on Information Systems* 42, 6 (2024), 1–26.
- [15] Jiahao Liu, Dongsheng Li, Hansu Gu, Tun Lu, Jiongran Wu, Peng Zhang, Li Shang, and Ning Gu. 2023. Recommendation unlearning via matrix correction. *arXiv preprint arXiv:2307.15960* (2023).
- [16] Jiahao Liu, Dongsheng Li, Hansu Gu, Tun Lu, Peng Zhang, and Ning Gu. 2022. Parameter-free dynamic graph embedding for link prediction. *Advances in Neural Information Processing Systems* 35 (2022), 27623–27635.
- [17] Jiahao Liu, Dongsheng Li, Hansu Gu, Tun Lu, Peng Zhang, Li Shang, and Ning Gu. 2023. Personalized graph signal processing for collaborative filtering. In *Proceedings of the ACM Web Conference 2023*. 1264–1272.
- [18] Jiahao Liu, Dongsheng Li, Hansu Gu, Tun Lu, Peng Zhang, Li Shang, and Ning Gu. 2023. Triple structural information modelling for accurate, explainable and interactive recommendation. In *Proceedings of the 46th International ACM SIGIR Conference on Research and Development in Information Retrieval*. 1086–1095.
- [19] Jiahao Liu, Yiyang Shao, Peng Zhang, Dongsheng Li, Hansu Gu, Chao Chen, Longzhi Du, Tun Lu, and Ning Gu. 2024. Filtering Discomforting Recommendations with Large Language Models. *arXiv preprint arXiv:2410.05411* (2024).
- [20] Sijia Liu, Jiahao Liu, Hansu Gu, Dongsheng Li, Tun Lu, Peng Zhang, and Ning Gu. 2023. Autoseqrec: Autoencoder for efficient sequential recommendation. In *Proceedings of the 32nd ACM International Conference on Information and Knowledge Management*. 1493–1502.
- [21] Jianmo Ni, Jiacheng Li, and Julian McAuley. 2019. Justifying recommendations using distantly-labeled reviews and fine-grained aspects. In *Proceedings of the 2019 conference on empirical methods in natural language processing and the 9th international joint conference on natural language processing (EMNLP-IJCNLP)*. 188–197.
- [22] Yi Ren, Hongyan Tang, Jiangpeng Rong, and Siwen Zhu. 2023. Unbiased Pairwise Learning from Implicit Feedback for Recommender Systems without Biased Variance Control. *arXiv preprint arXiv:2304.05066* (2023).
- [23] Steffen Rendle, Christoph Freudenthaler, Zeno Gantner, and Lars Schmidt-Thieme. 2012. BPR: Bayesian personalized ranking from implicit feedback. *arXiv preprint arXiv:1205.2618* (2012).
- [24] Yuta Saito. 2020. Unbiased pairwise learning from biased implicit feedback. In *Proceedings of the 2020 ACM SIGIR on International Conference on Theory of Information Retrieval*. 5–12.
- [25] Yuta Saito, Suguru Yaginuma, Yuta Nishino, Hayato Sakata, and Kazuhide Nakata. 2020. Unbiased recommender learning from missing-not-at-random implicit feedback. In *Proceedings of the 13th International Conference on Web Search and Data Mining*. 501–509.
- [26] Qi Wan, Xiangnan He, Xiang Wang, Jiancan Wu, Wei Guo, and Ruiming Tang. 2022. Cross pairwise ranking for unbiased item recommendation. In *Proceedings of the ACM Web Conference 2022*. 2370–2378.
- [27] Tianxin Wei, Fuli Feng, Jiawei Chen, Ziwei Wu, Jinfeng Yi, and Xiangnan He. 2021. Model-agnostic counterfactual reasoning for eliminating popularity bias in recommender system. In *Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery & Data Mining*. 1791–1800.
- [28] Ying-Xin Wu, Xiang Wang, An Zhang, Xiangnan He, and Tat-Seng Chua. 2022. Discovering invariant rationales for graph neural networks. *arXiv preprint arXiv:2201.12872* (2022).
- [29] Jiafeng Xia, Dongsheng Li, Hansu Gu, Jiahao Liu, Tun Lu, and Ning Gu. 2022. FIRE: Fast incremental recommendation with graph signal processing. In *Proceedings of the ACM Web Conference 2022*. 2360–2369.

- [30] Longqi Yang, Yin Cui, Yuan Xuan, Chenyang Wang, Serge Belongie, and Deborah Estrin. 2018. Unbiased offline recommender evaluation for missing-not-at-random implicit feedback. In *Proceedings of the 12th ACM conference on recommender systems*. 279–287.
- [31] Hongzhi Yin, Bin Cui, Jing Li, Junjie Yao, and Chen Chen. 2012. Challenging the long tail recommendation. *arXiv preprint arXiv:1205.6700* (2012).
- [32] Yang Zhang, Fuli Feng, Xiangnan He, Tianxin Wei, Chonggang Song, Guohui Ling, and Yongdong Zhang. 2021. Causal intervention for leveraging popularity bias in recommendation. In *Proceedings of the 44th International ACM SIGIR Conference on Research and Development in Information Retrieval*. 11–20.
- [33] Yu Zheng, Chen Gao, Xiang Li, Xiangnan He, Yong Li, and Depeng Jin. 2021. Disentangling user interest and conformity for recommendation with causal embedding. In *Proceedings of the Web Conference 2021*. 2980–2991.
- [34] Ziwei Zhu, Yun He, Yin Zhang, and James Caverlee. 2020. Unbiased implicit recommendation and propensity estimation via combinational joint learning. In *Proceedings of the 14th ACM Conference on Recommender Systems*. 551–556.