Logit Disagreement: OoD Detection with Bayesian Neural Networks

Kevin Raina¹

Department of Mathematics and Statistics, University of Ottawa, ON, K1N 6N5, Canada krain033@uottawa.ca

Abstract. Bayesian neural networks (BNNs), which estimate the full posterior distribution over model parameters, are well-known for their role in uncertainty quantification and its promising application in outof-distribution detection (OoD). Amongst other uncertainty measures, BNNs provide a state-of-the art estimation of predictive entropy (total uncertainty) which can be decomposed as the sum of mutual information and expected entropy. In the context of OoD detection the estimation of predictive uncertainty in the form of the predictive entropy score confounds aleatoric and epistemic uncertainty, the latter being hypothesized to be high for OoD points. Despite these justifications, the mutual information score has been shown to perform worse than predictive entropy. Taking inspiration from Bayesian variational autoencoder (BVAE) literature, this work proposes to measure the disagreement between a corrected version of the pre-softmax quantities, otherwise known as logits, as an estimate of epistemic uncertainty for Bayesian NNs under mean field variational inference. The three proposed epistemic uncertainty scores demonstrate marked improvements over mutual information on a range of OoD experiments, with equal performance otherwise. Moreover, the epistemic uncertainty scores perform on par with the Bayesian benchmark predictive entropy on a range of MNIST and CIFAR10 experiments.

Keywords: Out-of-distribution detection \cdot Bayesian neural networks \cdot Uncertainty quantification

1 Introduction

Deep neural networks (DNNs) have shown strong predictive performance on a variety of machine learning tasks such as computer vision [25, 46], natural language processing [35, 36], speech recognition [16, 44] and bio-informatics [1]. Despite their success, DNNs can erroneously produce confident predictions on inputs drawn from a different distribution than the training data, otherwise known as out-of-distribution (OoD) inputs [18,41]. The detection of OoD inputs is crucial in safety-critical applications with harmful, offensive, or fatal consequences [2]. An added challenge is dealing with noisy or ambiguous datasets, which also appear in safety-critical applications [19, 20]. It is clear that there is

a need to equip DNNs with uncertainty awareness to prevent erroneous usage and signal human intervention when needed.

Bayesian neural networks (BNNs) offer a principled approach for robust uncertainty quantification in deep learning [13, 31, 38] with inherent probabilistic interpretations. While exact Bayesian inference is often computationally intractable, several implementations of posterior inference have been proposed [3, 5, 32] enabling practical application. In result, the Bayesian NN literature has grown with the proposal and adaptation of many uncertainty measures [12, 21, 26, 50]. Amongst many other uncertainty measures, predictive entropy (PE) and mutual information (MI) are recurring scores studied in the context of OoD detection [23, 24, 28, 43, 47].



Fig. 1: (a): The DirtyMNIST dataset, comprising of classic MNIST [10] and 60K samples of generated ambiguous digits (AmbiguousMNIST) with FashionMNIST [52] as OoD. (b): Entropy of DNNs, which capture aleatoric uncertainty, can not efficiently separate DirtyMNIST from FashionMNIST. Figure derived with permission of the authors [37].

In review of the dichotomy of uncertainty present in Bayesian modelling, there are two major sources of uncertainty: epistemic and aleatoric [11,21]. Epistemic uncertainty accounts for uncertainty in the model parameters which occurs due to lack of similar training data and is reducible with the incorporation of more data. Logically, OoD data are hypothesized to have high epistemic uncertainty as such inputs should not resemble the training data. Aleatoric uncertainty is uncertainty due to inherent noise and stochasticity in the observations and is high when presented with ambiguous or noisy inputs. Aleatoric uncertainty is irreducible, as we can not change the structure of an input with additional data. For instance, in Figure 1 (a) the AmbiguousMNIST part of the DirtyMNIST dataset [37] consists of hand-written digits that we may identify with one or more digits. From the framework of uncertainty modelling, predictive entropy captures both aleatoric and epistemic uncertainty, while mutual information is thought to capture epistemic uncertainty. The incorporation of both uncertainties in predictive entropy offers an explanation to why this uncertainty measure can yield poor OoD detection performance when the in-distribution (iD) dataset consists of noisy inputs [23]. For instance, Figure 1 (b) provides histograms of softmax entropy from DNNs trained on DirtyMNIST, which contains an equal representation of the dataset MNIST and AmbiguousMNIST. Mutual information, however, does not incorporate aleatoric uncertainty and may be more robust on such datasets. Crucially, we also do not have control over the ambiguity of an input, but its familiarity in the dataset. This rationale suggests another advantage of epistemic uncertainty scores such as mutual information in OoD detection.

Despite theoretical justifications, the mutual information is shown to yield promising but not optimal performance on curated datasets [33]. One possible explanation can be attributed to the miscalibration of softmax scores [15]. Several uncertainty quantification methods for deep neural networks have bypassed this issue by basing their scores on earlier DNN layer features, and have demonstrated improved OoD detection capabilities [30,37,42,48]. In this work, easy-toimplement and model-agnostic epistemic uncertainty scores based off measuring the disagreement in the maximum logit value across posterior samples are proposed and evaluated for BNNs. In particular the disagreement scores are taken from Bayesian variational autoencoder (BVAE) literature, wherein they are applied to marginal likelihoods instead [8,14].

2 Background

Bayesian Deep Learning. The Bayesian approach is to treat the weights of a deep neural network as random variables [31, 38]. By assuming a prior distribution $p(\omega)$ on the model weights, we can infer a posterior distribution $p(\omega|\mathcal{D})$ from a given dataset $\mathcal{D} = \{(x_i, y_i)\}_{i=1}^N$ via variational inference [3], wherein there is a need to specify the variational approximating distribution $q_{\theta}(\omega)$ indexed by variational parameter θ . Variational inference aims to find the closest distribution to the true posterior from the parametric family $Q = \{q_{\theta}(\omega); \theta \in \Theta\}$ where closeness is often measured by Kullback-Leibler (KL) divergence. Consequently, we aim to minimize the objective function:

$$\mathcal{F}(\mathcal{D},\omega) = \int q_{\theta}(\omega) \log \frac{q_{\theta}(\omega)}{p(\omega)p(\mathcal{D}|\omega)} d\omega$$

= **KL**[q_{\theta}(\omega)||p(\omega)] - \mathbb{E}_{q_{\theta}(\omega)}[\log p(\mathcal{D}|\omega)] (1)

which can be approximated in practice by employing the reparametrization trick and Monte Carlo sampling from the variational distribution. In the classification setting, each posterior sample $\omega_i \sim p(w|\mathcal{D})$ and input x is associated with a categorical distribution $p(y|x,\omega)$ over the labels $y \in \mathcal{Y}$, *i.e.*, an individual model from an infinite ensemble. The predictive distribution is obtained by marginalizing out the model weights over the posterior distribution: $p(y|x,\mathcal{D}) = \mathbb{E}_{p(\omega|\mathcal{D})}[p(y|x,\omega)]$.

In variational inference, expectations of a similar form are effectively approximated by sampling from the variational distribution and then using the Monte Carlo estimator

$$\mathbb{E}_{p(\omega|\mathcal{D})}[f(\omega, x)] = \int p(\omega|\mathcal{D})f(\omega, x)d\omega$$

$$\approx \int q_{\hat{\theta}}(\omega)f(\omega, x)d\omega$$

$$\approx \sum_{i=1}^{T} f(\omega_i, x), \omega_{1,...,T} \sim q_{\hat{\theta}}(\omega).$$
(2)

Uncertainty Quantification. Within the Bayesian framework, a well-known decomposition is that of the predictive uncertainty, which itself quantifies total uncertainty. Following Smith and Gal's [47] terminology, the predictive entropy can be represented as the sum of mutual information (epistemic component) and expected entropy (aleatoric component), *i.e.*, $\mathbb{H}[p(y|x, \mathcal{D})] = \mathbb{I}[y, \omega|x, \mathcal{D}] + \mathbb{E}_{p(\omega|\mathcal{D})}[\mathbb{H}[p(y|x, \omega)]]$, and these quantities can be approximated by (2). The mutual information score can be expressed to intuitively quantify the expected information gain in the posterior distribution over labels, with the addition of an observable point (x, y) augmented into the training set, *i.e.*, if $\mathcal{D}^* = \mathcal{D} \cup \{(x, y)\}$, then

$$\mathbb{I}[y,\omega|x,\mathcal{D}] = \mathbb{E}_{p(y|x,\mathcal{D})}[\mathbf{KL}[p(\omega|\mathcal{D}^*)||p(\omega|\mathcal{D})]].$$
(3)

3 Methodology

Intuition: Following Bayesian VAE methods [8,14] that measure the disagreement in marginal likelihoods $\{p(x|\omega_i)\}_{i=1}^M$ from a set $\Omega = \{\omega_i\}_{i=1}^M$ of model parameter samples $\omega_i \sim q_{\hat{\theta}}(\omega)$, the aim is to measure epistemic uncertainty in Bayesian NNs and apply it to OoD detection by measuring variation or disagreement in the conditional likelihoods $\{p(\hat{y}|x,\omega_i)\}_{i=1}^M$, where \hat{y} is the predicted label selected from the predictive distribution. Intuitively, if the models $\{\omega_i\}_{i=1}^M$ agree on how likely/probable the predicted label y is associated with an input x, then x is in favor of being in-distribution. However, if the models $\{\omega_i\}_{i=1}^M$ disagree on the likelihood/probability of associating the predicted label y with an input x, then x is in favor of being OoD.

Disagreement and Model Informativeness: To see a stronger connection between model disagreement and epistemic uncertainty, reconsider the initial Bayesian NN setting of inferring a posterior distribution $p(\omega|\mathcal{D})$ from a likelihood $p(\mathcal{D}|\omega)$ and prior $p(\omega)$:

$$p(\omega|\mathcal{D}) = \frac{p(\mathcal{D}|\omega)}{p(\mathcal{D})}p(\omega).$$
(4)

Another distribution of interest is the augmented posterior, which is the posterior distribution updated with the additional observation (x, y). In this context, $\mathcal{D}^* = \mathcal{D} \cup \{(x, y)\}$ and the augmented posterior can be inferred as

$$p(\omega|\mathcal{D}^*) = \frac{p(y|x,\omega)}{p(y|x,\mathcal{D})} p(\omega|\mathcal{D}),$$
(5)

where it is readily observable that the change in the posterior distribution at model ω from augmenting the training data with observation (x, y) depends on the ratio $\frac{p(y|x,\omega)}{p(y|x,\mathcal{D})}$, also referred to as the normalized likelihood. Applying (2) to estimate the predictive distribution results in

$$\frac{p(y|x,\omega)}{p(y|x,\mathcal{D})} \approx \frac{p(y|x,\omega)}{\frac{1}{M} \sum_{\omega \in \Omega} p(y|x,\omega)} = M\eta_{\omega}; \quad \text{where} \quad \eta_{\omega} = \frac{p(y|x,\omega)}{\sum_{\omega \in \Omega} p(y|x,\omega)}.$$
(6)

From the approximation (6), $\frac{p(y|x,\omega)}{p(y|x,\mathcal{D})} \approx 1$ when $\eta_w = \frac{1}{M}$, or there is no change in the posterior from augmenting observation (x, y) if all models agree on its likelihood. Conversely, more disagreement amongst model likelihoods, will lead to more change in the posterior distribution. Likewise, we can derive a similar structure when specifically considering the KL Divergence between $p(\omega|\mathcal{D})$ and $p(\omega|\mathcal{D}^*)$. In particular:

$$\mathbf{KL}[p(\omega|\mathcal{D})||p(\omega|\mathcal{D}^*)] = \mathbb{E}_{p(\omega|\mathcal{D})} \left[\log \frac{p(\omega|\mathcal{D})}{p(\omega|\mathcal{D}^*)} \right]$$
$$= -\mathbb{E}_{p(\omega|\mathcal{D})} \left[\log \frac{p(\omega|\mathcal{D}^*)}{p(\omega|\mathcal{D})} \right]$$
$$= -\mathbb{E}_{p(\omega|\mathcal{D})} \left[\log \frac{p(y|x,\omega)}{p(y|x,\mathcal{D})} \right] \quad (5)$$
$$\approx -\mathbb{E}_{p(\omega|\mathcal{D})} \left[\log M\eta_{\omega} \right] \quad (6)$$
$$\approx -\frac{1}{M} \sum_{\omega \in \Omega} \log M\eta_{\omega} \quad (2)$$

where again, setting $\eta_{\omega} = \frac{1}{M}$ (all models agree on the likelihood) results in zero KL divergence. Moreover, when one model dominates the likelihood scores, *i.e.*, $\eta_{\omega} \approx 1$ for some ω , then the disagreement is high and the KL Divergence will be maximized. We observe model disagreement being related to informativeness and epistemic uncertainty. Notice that throughout the derivations, y was assumed to be known, which is seldom the case in practice. To work around this, we can either use the predicted label, or take an expectation over the predictive distribution. The former is considered in this work, whereas the latter is undertaken by the baseline score mutual information.

Logit Proxy: Despite the justifications of disagreement scores, it is well-known that the softmax probabilities are often miscalibrated, and produce consistently

overconfident predictions on certain OoD samples [15,41]. Recent works in DNNs have shown promising structure in the pre-softmax outputs, otherwise known as logits, for OoD detection [17,51]. Specifically the maximum logit method (MLS) [17], equivalently to apply the logit value associated with the class of the predicted label, has outperformed the traditional maximum softmax probability (MSP) [18] in OoD detection on multi-class datasets, despite bearing similarities. From a Bayesian perspective, measuring disagreement between maximum logit values across posterior samples $\{z(\hat{y}, x, \omega_i)\}_{i=1}^{M}$ in place of softmax likelihoods $\{p(\hat{y}|x, \omega_i)\}_{i=1}^{M}$ may prove to be a relatively simple yet improved measure of epistemic uncertainty with improved OoD detection abilities. Moreover, this substitution requires no further training, and is applicable to pre-trained Bayesian neural networks, with inherent advantages of being easy-to-use and model-agnostic. Many existing epistemic uncertainty scores from Bayesian VAEs operate exclusively on non-negative likelihood values. In order to allow such scores to operate on the maximum logit, a logit truncation is required:

$$z^*(\hat{y}, x, \omega) = \begin{cases} z(\hat{y}, x, \omega) & \text{if } z(\hat{y}, x, \omega) > 0, \\ \epsilon & \text{otherwise.} \end{cases}$$
(8)

where ϵ is a small positive constant (e.g. 1×10^{-15}). In the experiments it is important to note that virtually all of the structure in the max logit can be captured at non-negative values, as negative max logits can be considered to be outliers for both in-distribution and OoD samples. Our goal is now to measure disagreement amongst max logit values $\{z^*(\hat{y}, x, \omega)\}_{i=1}^M$, corresponding to posterior samples $\{\omega_i\}_{i=1}^M$ as a proxy to the softmax likelihoods.

Daxberger and Hernández-Lobato [8] suggests to calculate the disagreement score (DS) $D[\cdot]$ on marginal likelihoods, which captures uncertainty of the models about the specific input. The DS is justified as the effective sample size (ESS) [34] in an importance sampling estimation framework, where $p(\omega|\mathcal{D})$ is the proposal distribution and $p(\omega|\mathcal{D}^*)$ is the target distribution. Equivalently, DS quantifies the change in distribution between the proposal and target. By simply substituting the proposed logit proxy in place of the softmax likelihood, we obtain:

$$\tilde{D}_{\Omega}[x] = \frac{1}{\sum_{\omega \in \Omega} \tilde{\eta}_{\omega}^2}; \quad \text{with} \quad \tilde{\eta}_{\omega} = \frac{z^*(\hat{y}, x, \omega)}{\sum_{\omega \in \Omega} z^*(\hat{y}, x, \omega)}, \tag{9}$$

while the orginal softmax-based DS operates on the η_{ω} defined in (6) instead. The max logits are first normalized and represented as weights $\tilde{\eta}_{\omega}$ defined in (9), which can be interpreted as the probability that the sample was generated from model ω . In the extreme case that all max logit values are identical, the weight values will follow a discrete uniform distribution. At the other extremity, one max logit value may dominate resulting in a degenerate distribution with all probability mass at a single model. The disagreement score is the composition of first summing up the squares of the weights and then taking the reciprocal. If the score is large, it means that all models return close values of the logits. On the contrary, if the score is 1, then there is one model that dominates. Figure



Fig. 2: Epistemic uncertainty for OoD using logit disagreement. Top: Strip plot of the disagreement score (DS) using the truncated logit score computed from a Bayesian LeNet-5 [29] trained on MNIST categorized by dataset. Bottom: A comparison between the disagreement score applied to the proposed logit proxy and the softmax likelihood for MNIST vs FashionMNIST.

2 demonstrates the difference between applying the DS to the truncated logits and softmax scores in OoD detection on MNIST.

Additionally considered are two variants of measuring diagreement between marginal likelihoods proposed by Glazunov et al. [14] which are adapted to the max logits. Firstly, the weight entropy (WE) measures the Shannon information entropy of the normalized max logits $\tilde{\eta}_{\omega}$:

$$\tilde{\mathbb{H}}_{\Omega}[x] = -\sum_{\omega \in \Omega} \tilde{\eta}_{\omega} \log \tilde{\eta}_{\omega}.$$
(10)

Higher entropy will associate with more uniform plausibility across model parameters. Conversely, low entropy suggest lower uniformity in the choice of potential models, and higher disagreement in model possibilities. Secondly, sample standard deviation of the log-logits (Std of LLs) is considered:

$$\tilde{\Sigma}_{\Omega}[x] = \sqrt{\frac{1}{M-1} \sum_{\omega \in \Omega} (\log z^*(\hat{y}, x, \omega) - \overline{\log z^*(\hat{y}, x, \omega)})^2}$$
(11)

which is a classical estimator of variation. Naturally higher values lead to larger uncertainty arising from the posterior distribution.

4 Experiments and Observations

BCNN details. The PyTorch Bayesian CNN implementation by Shridhar et al. [45], which efficiently applies the Bayes by Backprop method of Blundell et al. [3] to CNNs is adapted for the experiments. For MNIST experiments, we follow Shridhar et al. and use the Softplus activation with $\beta = 1$ on the LeNet-5 [29] CNN architecture. We place an isotropic Gaussian prior with 0 mean and variance 0.01 over the model weights, *i.e.*, $p(\omega) = \mathcal{N}(0, 0.01I)$. The variational posterior is taken as a diagonal Gaussian distribution with individual weights $\omega_i \sim \mathcal{N}(\omega_i | \mu_i, \sigma_i^2)$, where $\sigma_i = \log(1 + exp(\rho_i))$, and μ_i, ρ_i are initialized from $\mathcal{N}(0, 0.01), N(-5, 0.01)$ respectively. Gradient descent is performed on the variational parameters $\theta = (\mu, \rho)$ via the Adam Optimizer with an initial learning rate 0.001 on batches of size 256 for a total of 200 epochs. From mini-batches, the expected log-likelihood term from the variational objective is estimated with the stochastic gradient variational Bayes SGVB estimator [22] and the analytical divergence term is multiplied by $\pi = 0.1$ for relative weighting. At each epoch, variational parameters are saved when the validation accuracy improves on a hold-out validation set.

In the CIFAR10 [25] experiments a Bayesian ResNet34 CNN is trained with informative priors. The MOPED method [24] is applied with $\delta = 0.01$ to establish the prior distribution of each weight by employing weights pre-trained on the ImageNet1K [53] dataset. At inference time, the diagonal standard deviations of the linear layer is scaled by a factor of 100 to introduce higher variation from the posterior. Gradient descent is performed on the variational parameters $\theta = (\mu, \rho)$ via the Adam Optimizer with an initial learning rate 0.0005 on batches of size 32 for a total of 200 epochs. Likewise, the expected log-likelihood term from the variational objective is estimated with the stochastic gradient variational Bayes SGVB estimator [22] and the analytical divergence term is multiplied by $\pi = 0.1$ for relative weighting. Similar to MNIST training, variational parameters are saved when the validation accuracy improves on a hold-out validation set.

Experimental setting. Models are trained on the in-distribution dataset by randomly dividing the training set into an effective training set comprising 80 percent of data and the remaining 20 percent constituting the hold-out validation



Fig. 3: Histograms of select epistemic uncertainty scores for MNIST vs FashionMNIST, blue depicts in-distribution (iD) and orange - out-of-distribution (OoD). The red dotted line marks the 5th or 95th quantile of the iD scores. From left to right: MI and DS (logit proxy).

set. The model training and validation accuracies are reported in Table 1. In the first set of experiments, MNIST is the in-distribution with FashionMNIST [52] (fashion-product images), Omniglot [27] (handwritten characters from 50 alphabets), KuzushijiMNIST [7] (kanji characters) and notMNIST [4] (various fonts of letters A through I) as OoD. For the second set of experiments CIFAR10 is the in-distribution with SVHN [39] (cropped house number plates), CIFAR100 (superset of CIFAR10), Places365 [54] (scene recognition) and Textures [6] (texture and pattern images) as OoD. Following Daxberger et al. [8] 5000 in-distribution inputs are randomly sampled from the in-distribution set and 5000 OoD inputs are randomly sampled from each of the OoD datasets. For evaluation the positive class is treated as OoD. It is important to note that there is some disagreement in recent literature on which class to designate as positive; for example [48, 49] define in-distribution samples to be positive, *i.e.*, the opposite convention to the one presented. For this reason, the false-negative rate in Tables 1 and 2 is comparable to the false-positive rates in [49]. The following metrics are computed: (1) The area under the ROC curve (AUROC \uparrow), and (2) false-negative rate at 95 percent true-negative rate (FNR95 \downarrow). Sampling was generally carried out to preserve an equal representation of in-distribution and OoD labels. Notable instances are the Omniglot dataset, wherein a random selection of 250 from the 1623 labels were considered, and Places365 wherein images were randomly sampled. Nguyen et al. [40] remarks that taking fewer samples choice provides a more realistic assumption as it is generally be unfeasible to observe OoD data of the same size, providing a motivation for the designated sampling. For the computation of all scores, M = 500 models from the posterior distribution were sampled. Figures 3 and 4 depict histograms of the max logit disagreement score along with the baseline mutual information on the MNIST vs FashionMNIST and CIFAR10 vs SVHN experiments respectively.



Fig. 4: Histograms of select epistemic uncertainty scores for CIFAR10 vs SVHN, blue depicts in-distribution (iD) and orange - out-of-distribution (OoD). The red dotted line marks the 5th or 95th quantile of the iD score. From left to right: MI and DS (logit proxy).

Dataset		AUROC \uparrow				FNR95↓			
\mathcal{D}_{in}	\mathcal{D}_{out}	MI	\mathbf{DS}	Std of LLs	WE	MI	\mathbf{DS}	Std of LLs	WE
	FashionMNIST	95.81	98.14	98.01	98.16	28.58	8.74	10.74	9.40
MNIST	Omniglot	96.00	99.39	99.26	99.37	18.54	1.30	2.06	1.60
(99.0/98.5)	KMNIST	97.32	97.80	97.77	97.81	14.98	11.72	12.82	11.94
	$\operatorname{notMNIST}$	95.41	95.89	95.98	95.95	24.76	22.44	22.38	22.68
	SVHN	94.77	96.84	96.83	96.83	33.58	16.08	16.14	16.10
CIFAR10	CIFAR100	89.79	89.76	89.76	89.76	53.50	44.38	44.60	44.46
(99.0/96.1)	Places365	93.69	95.28	95.28	95.28	41.90	25.70	25.70	25.70
	Textures	93.86	95.02	95.02	95.02	43.80	34.00	34.00	34.10

Table 1: Comparison of epistemic uncertainty scores.

Results. Table 1 shows the proposed methods compared to the standard Bayesian epistemic uncertainty score. On benchmark tasks involving MNIST, the methods demonstrates improved OoD detection. In particular, there are significant improvements in the false-negative rate at 95 percent true-negative rate. Moreover, improvements in both AUROC and FNR95 are substantial for the far-OoD datasets Omniglot and FashionMNIST. The proposed methods always yielded the optimal performance in comparison to mutual information. Likewise on benchmark CIFAR10 tasks, the proposed methods show significant improvement in FNR95 across all experiments, and marked improvements in AUROC for SVHN, Places365 and Textures. In observation, the CIFAR100 experiment proved particularly difficult for all scores, but the proposed methods performed similar to mutual information in terms of AUROC. In observation, mutual information contribut-

Dataset		AUROC \uparrow				FNR95↓			
\mathcal{D}_{in}	\mathcal{D}_{out}	\mathbf{PE}	\mathbf{DS}	Std of LLs	WE	PE	\mathbf{DS}	Std of LLs	WE
	FashionMNIST	98.77	98.14	98.01	98.16	5.96	8.74	10.74	9.40
MNIST	Omniglot	99.82	99.39	99.26	99.37	0.50	1.30	2.06	1.60
(99.0/98.5)	KMNIST	97.29	97.80	97.77	97.81	15.58	11.72	12.82	11.94
	$\operatorname{notMNIST}$	96.00	95.89	95.98	95.95	22.08	22.44	22.38	22.68
	SVHN	96.65	96.84	96.83	96.83	21.56	16.08	16.14	16.10
CIFAR10	CIFAR100	90.30	89.76	89.76	89.76	50.72	44.38	44.60	44.46
(99.0/96.1)	Places365	94.51	95.28	95.28	95.28	36.94	25.70	25.70	25.70
	Textures	94.90	95.02	95.02	95.02	37.06	34.00	34.00	34.10

Table 2: Comparison of the proposed scores with the Bayesian benchmark (predictive entropy).

ing to worse OoD detection performance at extreme thresholds. Comparing the three proposed epistemic uncertainty scores to each other, note the disagreement score often performs the best in FNR95, but generally performs similarly to the standard deviation of log-logits and weight entropy. Predictive entropy demonstrates decent performance, and outperforms mutual information on these datasets as seen in Table 2. The proposed epistemic uncertainty scores appear to be on par with the leading Bayesian benchmark, evenly with out-performance. In MNIST experiments, predictive entropy performs optimally for FashionMNIST, Omniglot and notMNIST, with the epistemic uncertainty scores demonstrating optimal detection abilities for KMNIST. In CIFAR10 experiments, the proposed epistemic uncertainty scores demonstrate significant reduction in FNR95 accross all experiments compared to predictive entropy, and notable improvements in AUROC for SVHN, Places365 and Textures.

5 Conclusion

Bayesian neural networks offer principled uncertainty quantification as a possible answer for safeguarding DNNs against erroneous usage. Specifically, epistemic uncertainty scores such a mutual information have been proposed for OoD detection. In this work post-hoc, model-agnostic epistemic uncertainty scores based off measuring disagreement in the maximum logit across posterior samples are proposed and demonstrated improvements over the mutual information baseline for BNNs under mean field variational inference. Generally, this work aims to encourage future investigations on the feature space of BNNs - including but not limited to the logits - to measure epistemic uncertainty for OoD detection. Additionally, this work encourages the evaluation of other forms of posterior inference such as the Laplace approximation [9] in conjunction with these proposed scores for OoD detection.

References

- Alipanahi, B., Delong, A., Weirauch, M.T., Frey, B.J.: Predicting the sequence specificities of dna-and rna-binding proteins by deep learning. Nature biotechnology 33(8), 831–838 (2015)
- Amodei, D., Olah, C., Steinhardt, J., Christiano, P., Schulman, J., Mané, D.: Concrete problems in ai safety. arXiv preprint arXiv:1606.06565 (2016)
- Blundell, C., Cornebise, J., Kavukcuoglu, K., Wierstra, D.: Weight uncertainty in neural network. In: International conference on machine learning. pp. 1613–1622. PMLR (2015)
- 4. Bulatov, Y.: Notmnist dataset. google (books/ocr). Google (Books/OCR) (2011)
- 5. Chen, T., Fox, E., Guestrin, C.: Stochastic gradient hamiltonian monte carlo. In: International conference on machine learning. pp. 1683–1691. PMLR (2014)
- Cimpoi, M., Maji, S., Kokkinos, I., Mohamed, S., Vedaldi, A.: Describing textures in the wild. In: Proceedings of the IEEE conference on computer vision and pattern recognition. pp. 3606–3613 (2014)
- Clanuwat, T., Bober-Irizar, M., Kitamoto, A., Lamb, A., Yamamoto, K., Ha, D.: Deep learning for classical japanese literature. arXiv preprint arXiv:1812.01718 (2018)
- Daxberger, E., Hernández-Lobato, J.M.: Bayesian variational autoencoders for unsupervised out-of-distribution detection [v3]. arXiv (2019). https://doi.org/10. 48550/ARXIV.1912.05651, https://arxiv.org/abs/1912.05651
- Daxberger, E., Kristiadi, A., Immer, A., Eschenhagen, R., Bauer, M., Hennig, P.: Laplace redux-effortless bayesian deep learning. Advances in Neural Information Processing Systems 34, 20089–20103 (2021)
- 10. Deng, L.: The mnist database of handwritten digit images for machine learning research [best of the web]. IEEE signal processing magazine **29**(6), 141–142 (2012)
- Der Kiureghian, A., Ditlevsen, O.: Aleatory or epistemic? does it matter? Structural safety **31**(2), 105–112 (2009)
- Feinman, R., Curtin, R.R., Shintre, S., Gardner, A.B.: Detecting adversarial samples from artifacts. arXiv preprint arXiv:1703.00410 (2017)
- 13. Gal, Y., et al.: Uncertainty in deep learning (2016)
- 14. Glazunov, M., Zarras, A.: Do bayesian variational autoencoders know what they don't know? In: Uncertainty in Artificial Intelligence. pp. 718–727. PMLR (2022)
- Guo, C., Pleiss, G., Sun, Y., Weinberger, K.Q.: On calibration of modern neural networks. In: International conference on machine learning. pp. 1321–1330. PMLR (2017)
- Hannun, A., Case, C., Casper, J., Catanzaro, B., Diamos, G., Elsen, E., Prenger, R., Satheesh, S., Sengupta, S., Coates, A., et al.: Deep speech: Scaling up end-toend speech recognition. arXiv preprint arXiv:1412.5567 (2014)
- Hendrycks, D., Basart, S., Mazeika, M., Zou, A., Kwon, J., Mostajabi, M., Steinhardt, J., Song, D.: Scaling out-of-distribution detection for real-world settings. arXiv preprint arXiv:1911.11132 (2019)
- Hendrycks, D., Gimpel, K.: A baseline for detecting misclassified and out-ofdistribution examples in neural networks. arXiv preprint arXiv:1610.02136 (2016)
- Huang, Y., Chen, Y.: Autonomous driving with deep learning: A survey of stateof-art technologies. arXiv preprint arXiv:2006.06091 (2020)
- 20. Kamnitsas, K., Ferrante, E., Parisot, S., Ledig, C., Nori, A.V., Criminisi, A., Rueckert, D., Glocker, B.: Deepmedic for brain tumor segmentation. In: Brainlesion:

Glioma, Multiple Sclerosis, Stroke and Traumatic Brain Injuries: Second International Workshop, BrainLes 2016, with the Challenges on BRATS, ISLES and mTOP 2016, Held in Conjunction with MICCAI 2016, Athens, Greece, October 17, 2016, Revised Selected Papers 2. pp. 138–149. Springer (2016)

- 21. Kendall, A., Gal, Y.: What uncertainties do we need in bayesian deep learning for computer vision? Advances in neural information processing systems **30** (2017)
- 22. Kingma, D.P., Salimans, T., Welling, M.: Variational dropout and the local reparameterization trick. Advances in neural information processing systems **28** (2015)
- Kirsch, A., Mukhoti, J., van Amersfoort, J., Torr, P.H., Gal, Y.: On pitfalls in OoD detection: Predictive entropy considered harmful (2021), uncertainty in Deep Learning Workshop
- Krishnan, R., Subedar, M., Tickoo, O.: Specifying weight priors in bayesian deep neural networks with empirical bayes. In: Proceedings of the AAAI Conference on Artificial Intelligence. vol. 34, pp. 4477–4484 (2020)
- Krizhevsky, A., Hinton, G., et al.: Learning multiple layers of features from tiny images (2009)
- Kwon, Y., Won, J.H., Kim, B.J., Paik, M.C.: Uncertainty quantification using bayesian neural networks in classification: Application to ischemic stroke lesion segmentation. In: Medical Imaging with Deep Learning (2022)
- Lake, B.M., Salakhutdinov, R., Tenenbaum, J.B.: Human-level concept learning through probabilistic program induction. Science 350(6266), 1332–1338 (2015)
- Lakshminarayanan, B., Pritzel, A., Blundell, C.: Simple and scalable predictive uncertainty estimation using deep ensembles. Advances in neural information processing systems **30** (2017)
- LeCun, Y., Bottou, L., Bengio, Y., Haffner, P.: Gradient-based learning applied to document recognition. Proceedings of the IEEE 86(11), 2278–2324 (1998)
- Lee, K., Lee, K., Lee, H., Shin, J.: A simple unified framework for detecting outof-distribution samples and adversarial attacks. Advances in neural information processing systems **31** (2018)
- Mackay, D.J.C.: Bayesian methods for adaptive models. California Institute of Technology (1992)
- Maddox, W.J., Izmailov, P., Garipov, T., Vetrov, D.P., Wilson, A.G.: A simple baseline for bayesian uncertainty in deep learning. Advances in neural information processing systems **32** (2019)
- Malinin, A., Gales, M.: Predictive uncertainty estimation via prior networks. Advances in neural information processing systems 31 (2018)
- Martino, L., Elvira, V., Louzada, F.: Effective sample size for importance sampling based on discrepancy measures. Signal Processing 131, 386–401 (2017)
- Mikolov, T., Chen, K., Corrado, G., Dean, J.: Efficient estimation of word representations in vector space. arXiv preprint arXiv:1301.3781 (2013)
- Mikolov, T., Karafiát, M., Burget, L., Cernocký, J., Khudanpur, S.: Recurrent neural network based language model. In: Interspeech. vol. 2, pp. 1045–1048. Makuhari (2010)
- Mukhoti, J., Kirsch, A., van Amersfoort, J., Torr, P.H., Gal, Y.: Deep deterministic uncertainty: A new simple baseline. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 24384–24394 (2023)
- Neal, R.M.: Bayesian learning for neural networks, vol. 118. Springer Science & Business Media (2012)
- 39. Netzer, Y., Wang, T., Coates, A., Bissacco, A., Wu, B., Ng, A.Y.: Reading digits in natural images with unsupervised feature learning (2011)

- 14 K.Raina
- Nguyen, A.T., Lu, F., Munoz, G.L., Raff, E., Nicholas, C., Holt, J.: Out of distribution data detection using dropout bayesian neural networks. In: Proceedings of the AAAI Conference on Artificial Intelligence. vol. 36, pp. 7877–7885 (2022)
- Nguyen, A., Yosinski, J., Clune, J.: Deep neural networks are easily fooled: High confidence predictions for unrecognizable images. In: Proceedings of the IEEE conference on computer vision and pattern recognition. pp. 427–436 (2015)
- 42. Postels, J., Blum, H., Strümpler, Y., Cadena, C., Siegwart, R., Van Gool, L., Tombari, F.: The hidden uncertainty in a neural networks activations. arXiv preprint arXiv:2012.03082 (2020)
- Rawat, A., Wistuba, M., Nicolae, M.I.: Adversarial phenomenon in the eyes of bayesian deep learning. arXiv preprint arXiv:1711.08244 (2017)
- 44. Senior, A., Vanhoucke, V., Nguyen, P., Sainath, T., et al.: Deep neural networks for acoustic modeling in speech recognition. IEEE Signal processing magazine (2012)
- Shridhar, K., Laumann, F., Liwicki, M.: A comprehensive guide to bayesian convolutional neural network with variational inference. arXiv preprint arXiv:1901.02731 (2019)
- Simonyan, K., Zisserman, A.: Very deep convolutional networks for large-scale image recognition. arXiv preprint arXiv:1409.1556 (2014)
- 47. Smith, L., Gal, Y.: Understanding measures of uncertainty for adversarial example detection. arXiv preprint arXiv:1803.08533 (2018)
- Sun, Y., Ming, Y., Zhu, X., Li, Y.: Out-of-distribution detection with deep nearest neighbors. In: International Conference on Machine Learning. pp. 20827–20840. PMLR (2022)
- Vernekar, S., Gaurav, A., Abdelzad, V., Denouden, T., Salay, R., Czarnecki, K.: Out-of-distribution detection in classifiers via generation. arXiv preprint arXiv:1910.04241 (2019)
- 50. Wang, X., Aitchison, L.: Bayesian ood detection with aleatoric uncertainty and outlier exposure. arXiv preprint arXiv:2102.12959 (2021)
- Wei, H., Xie, R., Cheng, H., Feng, L., An, B., Li, Y.: Mitigating neural network overconfidence with logit normalization. In: International conference on machine learning. pp. 23631–23644. PMLR (2022)
- 52. Xiao, H., Rasul, K., Vollgraf, R.: Fashion-MNIST: a novel image dataset for benchmarking machine learning algorithms. arXiv preprint arXiv:1708.07747 (2017)
- Zhang, L., Goldstein, M., Ranganath, R.: Understanding failures in out-ofdistribution detection with deep generative models. In: International Conference on Machine Learning. pp. 12427–12436. PMLR (2021)
- Zhou, B., Lapedriza, A., Khosla, A., Oliva, A., Torralba, A.: Places: A 10 million image database for scene recognition. IEEE transactions on pattern analysis and machine intelligence 40(6), 1452–1464 (2017)