# Synthetic vs. Gold: The Role of LLM-Generated Labels and Data in Cyberbullying Detection

Arefeh Kazemi and Sri Balaaji Natarajan Kalaivendan and Joachim Wagner and Hamza Qadeer and Brian Davis

School of Computing, ADAPT Centre, Dublin City University, Dublin, Ireland Correspondence: firstname.lastname@adaptcentre.ie

#### Abstract

This study investigates the role of LLMgenerated synthetic data in cyberbullying detection. We conduct a series of experiments where we replace some or all of the authentic data with synthetic data, or augment the authentic data with synthetic data. We find that synthetic cyberbullying data can be the basis for training a classifier for harm detection that reaches performance close to that of a classifier trained with authentic data. Combining authentic with synthetic data shows improvements over the baseline of training on authentic data alone for the test data for all three LLMs tried. These results highlight the viability of synthetic data as a scalable, ethically viable alternative in cyberbullying detection while emphasizing the critical impact of LLM selection on performance outcomes.

#### 1 Introduction

The rapid proliferation of social media platforms has raised concerns over the prevalence of cyberbullying (CB), particularly among vulnerable populations like pre-adolescents. Detecting and mitigating CB is crucial for maintaining a safe digital environment and minimizing its psychological impact. However, creating high-quality labeled datasets for training CB detection models remains a significant challenge. Traditional data collection methods, relying on human annotators, are costly, time-consuming, and pose ethical concerns. Annotators may experience emotional distress or harm when exposed to harmful content, which raises questions about their well-being (AlEmadi and Zaghouani, 2024). This highlights the need for alternative approaches to generate labeled datasets without requiring human annotators to engage directly with harmful content. One promising solution is using large language models (LLMs) for synthetic data generation.

LLMs have shown remarkable capabilities in

generating human-like text and performing various NLP tasks, including text classification and sentiment analysis (Brown et al., 2020). These models can be fine-tuned for specific applications and can generate synthetic data that mimics authentic content while reducing the reliance on human annotators. The use of LLMs for synthetic dataset creation holds the potential to alleviate both the financial and ethical burdens associated with manual annotation. Recent studies have demonstrated the utility of LLM-generated data in NLP tasks where authentic datasets are scarce or difficult to acquire (Li et al., 2023).

In this paper, we explore the potential of LLMgenerated datasets for cyberbullying detection. We investigate several scenarios for integrating LLMs into the cyberbullying detection pipeline, including using LLMs directly as classifiers, generating synthetic data for training classifiers, and augmenting authentic data with synthetic samples. Through these experiments, we aim to determine the extent to which synthetic data can improve detection performance, considering different levels of availability of manually labeled authentic data.

#### 2 Background

In recent years, the use of LLMs for synthetic data generation has gained significant traction due to its efficiency, scalability, and cost-effectiveness compared to human-annotated datasets. Given that LLMs demonstrate human-like behavior in natural language understanding, many studies have explored their potential in generating synthetic datasets for various NLP tasks. Some works focus on creating entire datasets from scratch, while others utilize LLMs as annotators to label existing authentic data for knowledge distillation, self-training, and few-shot learning tasks, which was then annotated using state-of-the-art classifiers. (Bonifacio et al., 2022) employ LLMs to generate labeled data in a few-shot manner for information retrieval. The synthetic data is then used to fine-tune smaller retrieval models, which are later used to rerank search results from an initial retrieval system. (Yoo et al., 2021) generate augmented text samples by selecting a few sentences from task-specific training data and embedding them into prompts. (Anaby-Tavor et al., 2020) fine-tune a pre-trained LM on a small labeled dataset and then uses it to generate new labeled text samples based on class labels to improve text classification performance. (Meng et al., 2022) employ an LLM to generate class-conditioned texts based on label-descriptive prompts for classification task.

While the aforementioned studies focus on general NLP tasks, some research has specifically explored synthetic data generation for domains such as medical and harmful-content detection. (Wang et al., 2024) introduced NoteChat, a multi-agent framework designed to generate synthetic patientphysician conversations based on clinical documents. (Ghanadian et al., 2024) generated socially aware synthetic datasets for suicidal ideation detection. They first identified key social factors related to suicidal ideation. Then they generated synthetic datasets using zero-shot and few-shot learning techniques. These datasets were then used to fine-tune classifiers, which were tested on one authentic and synthetic-labeled datasets. Previous studies utilizing synthetic data have reported mixed findings on whether LLM-generated synthetic data can effectively train models to perform at a level comparable to those trained on real-world data(Li et al., 2023). There has also been research specifically focusing on generating semi-synthetic data for CB detection. (Ejaz et al., 2024) generated a semi-synthetic CB dataset by creating synthetic users. Aggressive and non-aggressive messages were then sourced from existing authentic datasets and randomly assigned to user interactions. The dataset labels CB instances using a threshold-based approach, flagging interactions as CB if they meet predefined criteria for peerness, intent to harm, and message repetition. This study creates a dataset which try to simulate real CB behaviors, where the users are semi-synthetic, and the messages are generated using a combination of existing authentic CB datasets and synthetic data. Perez and Karmakar (2023) generated a synthetic CB dataset using a Bayesian Network model trained on real-world survey data collected from minors. To generate synthetic data,

Notation	Description
$X_{\rm tr}$	Training set inputs (messages)
$y_{ m tr}^{ m gold}$	Gold labels for $X_{tr}$
$X_{ m val}$	Validation set inputs
$y_{ m val}^{ m gold}$	Gold labels for $X_{val}$
$X_{\text{test}}$	Test set inputs
$y_{\text{test}}^{\text{gold}}$	Gold labels for $X_{\text{test}}$
$(X, y)_{\rm tr}^{\rm llm}$	Synthetic training data
$(X, y)_{\rm val}^{\rm llm}$	Synthetic validation data

Table 1: Summary of notations used in the paper

the Bayesian Model Sampling algorithm was applied to the trained BN, producing risk profiles for synthetic agents. The final dataset consists of some synthetic players, each with demographic attributes and responses to 15 binary questions related to cyber risk. This dataset represents synthetic users' responses to 15 CB-related binary questions. In contrast to these works, our study aims to explore the use of LLMs to generate a fully syn-

plore the use of LLMs to generate a fully synthetic CB dataset or to augment existing authentic CB datasets. Our work uniquely applies LLMgenerated data to cyberbullying detection, an area where data collection is both ethically and logistically challenging. By assessing the effectiveness of LLM-generated datasets in comparison to authentic data, we provide new insights into the viability of LLMs in training models for sensitive tasks like CB detection, where the availability of diverse and annotated data is critical.

#### 3 Methodology

#### 3.1 Notations

The notations used throughout this paper are summarized in Table 1.

#### 3.2 Overview of Scenarios

In this study, we investigate the role of LLMs in CB detection, focusing on their utility under varying data availability conditions. To establish a baseline for comparison, we first evaluate a scenario in which a classifier is trained exclusively on gold-standard, manually labeled authentic data without any LLM involvement. We then define three additional scenarios, each illustrating how LLMs can aid cyberbullying detection depending on the availability and quantity of authentic data.

The scenarios are as follows.

#### 3.2.1 Scenario 1: Baseline

This scenario represents the ideal situation where sufficient manually labeled (gold-standard) data is

available for training, validation, and testing a CB classifier (such as BERT). It serves as the benchmark for evaluating the effectiveness of other approaches. In this setup, no synthetic data or LLMs are involved; the system relies entirely on human annotations. This scenario is feasible if resources such as time, budget, and expert annotators are abundant. However, it often proves impractical due to the high costs and scalability challenges of manual labeling.

#### 3.2.2 Scenario 2: LLM as Classifier

This scenario applies when labeled authentic data is unavailable, and there is no intention to train a separate classifier for CB detection. Instead, an instruction-tuned LLM is used directly as a classifier, leveraging its pre-trained knowledge and its ability to folow instructions to identify cyberbullying instances. This approach is particularly useful in contexts requiring rapid deployment or when computational or time resources for training a new model are limited. The primary advantage of this method is its elimination of the need for labeled data and training time. However, there are tradeoffs. While an LLM can handle nuanced language patterns, it may be less efficient and incur higher computational costs compared to simpler BERTbased classifiers with a classification head and finetuned on a labeled dataset. This scenario offers a quick solution but presents potential limitations in accuracy and efficiency.

#### 3.2.3 Scenario 3: Fully Synthetic Data

In this scenario, only a small set of manually labeled gold data is available for testing, with no access to authentic data for training or validation. To address this, we use an LLM to generate a fully synthetic dataset, consisting of both synthetic messages and corresponding labels, for training and validation.

This approach is particularly valuable in lowresource domains or emerging tasks where authentic data is scarce or difficult to collect. It is especially useful in situations where creating authentic datasets is costly, time-consuming, or ethically challenging, such as annotating harmful or sensitive content. This scenario underscores the potential of LLMs as a powerful tool for bootstrapping datasets under extreme resource constraints.

Scenario	Train	Validation	Test
1	$X_{ m tr}, y_{ m tr}^{ m gold}$	$X_{ m val}, y_{ m val}^{ m gold}$	$X_{\mathrm{test}}, y_{\mathrm{test}}^{\mathrm{gold}}$
2	-	-	$X_{\mathrm{test}}, y_{\mathrm{test}}^{\mathrm{gold}}$
3	$(X,y)_{\rm tr}^{ m llm}$	$(X, y)_{\rm val}^{\rm llm}$	$X_{\mathrm{test}}, y_{\mathrm{test}}^{\mathrm{gold}}$
4	$(X,y)_{tr}^{llm}$ +	$(X, y)_{\rm val}^{\rm llm}$ +	$X_{\mathrm{test}}, y_{\mathrm{test}}^{\mathrm{gold}}$
	$X_{ m tr}, y_{ m tr}^{ m gold}$	$X_{ m val}, y_{ m val}^{ m gold}$	

Table 2: Overview of data used in each scenario

# 3.2.4 Scenario 4: Data Augmentation with Synthetic Data

This scenario assumes the availability of a moderate amount of gold-labeled data for training and validation, which may be insufficient to achieve optimal performance. To augment the dataset, we use an LLM to generate additional synthetic data, which is then combined with the gold-labeled data during training and validation. The experiment systematically varies the ratio of synthetic-to-gold data to evaluate its impact on model performance. This scenario explores how LLMs can supplement authentic data, striking a balance between scalability and accuracy.

# 3.2.5 Summary of Scenarios

Table 2 presents an overview of the data used in the baseline system and each scenario, specifying the datasets utilized for training, validation, and testing. For Scenario 2, where no classifier is trained and the LLM is used directly as a classifier, only the test set is included.

#### 3.3 Intrinsic Evaluation Metrics

Intrinsic evaluation examines the inherent qualities of datasets, enabling the assessment of linguistic diversity, emotional tone, and conversational structure independently from task-specific performance. For our CB detection task, we utilize four categories of intrinsic metrics to compare the authentic WhatsApp dataset with LLM-generated synthetic data. These categories are: 1) lexical and linguistic characteristics, including metrics such as Mean Words per Message, Mean Word Length, and Type-Token Ratio; 2) content and CB indicators, such as rate of Harmful Messages, Bully Messages, Victim Messages, and Toxicity; 3) sentiment and emotional tone, which classifies messages into negative, positive, or neutral; and 4) dialogue act distribution, categorizing messages into types such as Question, Statement, Greeting, Accept/Reject, and Other. These categories are critical for understanding the fundamental differences between authentic and synthetic data in the context of CB detection, as they provide insight into how well the synthetic data replicates the linguistic, emotional, and conversational behaviors that are typically present in real-world online interactions.

To ensure a fair comparison between the authentic and synthetic datasets, we first normalize both dataset by employing pre-processing techniques such as tokenization using NLTK and punctuation handling. Additionally, data is segmented into equal-sized token slices to account for metrics that are influenced by corpus size.

Sentiment scores are measured using VADER (Hutto and Gilbert, 2014), a sentiment analysis tool optimized for short social media texts. Dialogue acts are classified using a Naive Bayes model trained on the NLTK nps-chat corpus, following Bird et al. (2019, Chp. 6, Sec. 2.2).<sup>1</sup> Type-Token Ratio (TTR), which is calculated by dividing the number of unique words by the total tokens in fixed-size slices, serves as a normalized measure of vocabulary diversity. Toxicity scores, which represent the ratio of messages containing profanity, are derived using a publicly available profanity list (SurgeAI, 2021).

# 3.4 Extrinsic Evaluation Metrics

We evaluate the synthetic data in two scenarios for their usefulness in training a binary classifier for harm detection. We choose accuracy of label prediction for development decisions and reporting since the labels are reasonably balanced in the test data with 30.3% items labelled with the minority label. In the appendix, we further report macro average F1 scores that are also widely used in the area of harmful content detection.

# 4 Experimental Setup

#### 4.1 Dataset Description

Social science research highlights the importance of detecting, intervening, and preventing cyberbullying by closely examining social interactions among pre-adolescents at a detailed level. The WhatsApp dataset (Verma et al., 2023; Sprugnoli et al., 2018) is the only publicly available dataset specifically focused on pre-adolescents and we use this for our experiments. The WhatsApp dataset was constructed through role-play activities in WhatsApp groups, each containing approximately 10 students. The roles are: cyberbully (2 students), cyberbully assistants (3–4 students), victim assistants (3–4 students), and a victim. Conversations were initiated using on of the four predefined cases<sup>2</sup> that addressed common teenage issues, such as gender stereotypes in sports or the spread of embarrassing videos. Table 9 in Appendix A presents an example of one case and the type of problem used to initiate the conversations. Details of the remaining three cases can be found in (Sprugnoli et al., 2018).

After creating conversations via role-playing, messages in the conversation are annotated manually by linguists following a fine-grained framework adapted from the "Guidelines for the Fine-Grained Analysis of Cyberbullying" by (Van Hee et al., 2015). The annotations categorized harmful expressions into detailed types, such as General Insults, Body Shame, Sexism, Racism and Body Shame. In this study, we aim to classify messages as either harmful or harmless. Therefore, instead of using fine-grained labeling, all categories of cyberbullying are grouped under the "harmful" label. Table 3 shows the statistics of the WhatsApp dataset.

Split	Size	Harmful
Training	1,314	30.1%
Validation	439	30.8%
Test	439	30.3%
Total	2,192	30.3%

Table 3: Whatsapp dataset: number of messages andfraction of harmful messages

#### 4.2 Large Language Models

In this study, we employ three LLMs for our experiments: GPT, LlamA, and Grok. Specifically, we use GPT-4.0, LlaMA 3, and Grok-2-latest models.

#### 4.3 Generating Synthetic Data and Labels

Prompt Engineering is essential for harnessing the full potential of LLMs. It involves crafting and refining the instructions provided to the LLM to elicit the desired outputs. The prompt design process for all scenarios began with a simple initial prompt, which was iteratively refined over multiple rounds of trial and error. This iterative approach allowed us for gradual improvements, with adjustments made

<sup>&</sup>lt;sup>1</sup>While no citation is provided by Bird et al. (2019), the source of this corpus seems to be Forsyth and Martell (2007); Forsyth et al. (2010).

<sup>&</sup>lt;sup>2</sup>Note that in the main paper, these cases are referred to as "scenarios." However, in this paper, we use the term "cases" to avoid confusion with the scenarios discussed in our main study.

based on the quality and relevance of the responses generated by the LLM on the development set.

In this paper, LLMs are utilized for two primary tasks in the context of CB detection: (1) generating synthetic data and (2) generating synthetic labels. More precisely, in Scenarios 2, 3 and 4 LLMs are employed as a classifier to generate synthetic labels for unlabeled authentic (scenario 2) or synthetic data (scenarios 3 and 4). Meanwhile, in Scenarios 3 and 4, LLMs are used to generate synthetic data to crate a new dataset or supplement existing ones. The subsections below detail the prompt design strategies employed for these two tasks.

# 4.3.1 Designing Prompts for Synthetic Label Generation

In this section, we describe the prompts designed to instruct an LLM to label unlabeled input data for the task of CB detection. In this context, the input data consists of messages, and the possible labels are "harmful" and "harmless". Harmful messages show instances of CB, while harmless messages are normal, safe communications. We explore two approaches to prompt design: (1) guideline-free (GF) and (2) guideline-enriched (GE). In the guidelinefree approach, the LLM is simply instructed to label messages as "harmful" or "harmless" for the task of CB detection, without providing additional guideline. In the guideline-enriched approach, the LLM is supplied with detailed instructions for labeling messages. These instructions are adapted from the annotation guidelines originally used by human annotators for labeling authentic data.

For this study, since the test set is derived from the WhatsApp dataset, we utilize the same guideline employed by human annotators to label this dataset. This guidelines is presented in Table 11 in AppendixA. Table 12 shows the prompts used to generate synthetic labels for both the GE and GF approaches.

# 4.3.2 Designing Prompts for Synthetic Data Generation

In this section, we present the prompts designed to guide a LLM in generating synthetic data for CB detection. Specifically, the synthetic data we aim to produce consists of conversations between participants, where the dialogue demonstrates instances of CB, including harmful messages. To train the CB classifier, we require labeled messages. Therefore, we first use the LLM to generate synthetic coversation and subsequently use the LLM to label the messages in the conversation.

We used the cases defined in the WhatsApp dataset to generate synthetic conversations.By providing the system with the predefined "cases" and "problem types" from the Whatsapp dataset, we prompted it to create conversations based on these inputs. Table 12 presents the prompts employed for generating synthetic data.

# 4.4 Amount of Synthetic Data

For a more meaningful comparison to results with the authentic data, we sample subsets of the generated data to match the size of the authentic data for each CB case. We also sample subsets of certain percentages of these sizes from 10% to 200%.<sup>3</sup> Since the test set is never synthetic, we measure sizes relative to the concatenation of training and validation data, i.e. 1314 + 439 = 1753 messages correspond to 100%.

# 5 Results and Discussion

Table 4 shows the results of the intrinsic evaluation across four categories for each dataset. In terms of lexical and linguistic characteristics, the synthetic datasets show significant differences from WhatsApp. Both Grok and Llama generate longer messages compared to WhatsApp. Meanwhile, GPT is closer but still produces longer messages. The Type-Token Ratio (TTR) is lower for all synthetic datasets compared to WhatsApp, indicating less lexical diversity in the synthetic data. This suggests that the synthetic data may lack the richness in vocabulary typically found in real-world WhatsApp conversations.

In the content and cyberbullying indicators category, the synthetic datasets show varying levels of harmful content, with Grok standing out by producing the highest percentage of harmful messages (65.27%) and toxicity (2.37%). This high level of harmful content in Grok can be valuable for detecting extreme cases of CB. While Llama (17.19%) and GPT (6.57%) have much lower harmful content, these datasets may still present valuable data for detecting subtler instances of CB, with Llama's content being more balanced and closely resembling real-world interactions.

In terms of sentiment scores, Llama and GPT are more similar to WhatsApp overall. Both Llama and GPT have a slightly higher percentage of positive

<sup>&</sup>lt;sup>3</sup>The appendix includes results for up to 600%.

Metric	WhatsApp	Llama	GPT	Grok
Lexical and Linguistic Character	istics			
Mean Words/Message	7.02	12.77	8.17	13.67
Mean Word Length	3.78	3.93	3.87	4.05
Type-Token Ratio (per 1000 Tkn)	32.17%	23.73%	29.66%	21.79%
Content and Cyberbullying Indic	cators			
Harmful	29.51%	17.19%	6.57%	65.27%
Bully Messages	28.74%	25.84%	20.77%	27.46%
Victim Messages	16.01%	20.53%	14.93%	13.27%
Toxicity (per 1000 Tkn)	1.08%	0.46%	0.02%	2.37%
Sentiment and Emotional Tone				
Negative	11.65%	12.05%	8.95%	17.77%
Neutral	72.67%	69.29%	72.37%	66.63%
Positive	15.66%	18.65%	18.66%	15.60%
Dialogue Act Distribution				
Question	12.45%	18.12%	11.28%	29.68%
Statement	69.80%	76.57%	81.65%	67.32%
Greet	2.87%	0.82%	2.97%	0.44%
Accept/Reject (%)	4.84%	3.78%	1.71%	2.00%
Other	10.04%	0.70%	2.39%	0.57%

 Table 4: Intrinsic Evaluation Metrics

messages compared to WhatsApp, but their neutral and negative sentiment distributions are fairly close to WhatsApp's. On the other hand, Grok's sentiment distribution deviates more significantly from WhatsApp. Grok has a much higher proportion of negative messages, which suggests that it over-represents hostile or aggressive tones. Its positive sentiment is similar to WhatsApp, but the higher negative sentiment creates a more polarized emotional tone in the data. This makes Grok less similar to WhatsApp in overall sentiment, but it could still be useful for detecting more extreme negative interactions, such as severe CB cases.

In terms of dialogue act distribution, the statement and accept/reject ratios are the most critical for CB detection. Llama is the most similar to WhatsApp, making it the best choice for generating synthetic data that closely mirrors real-world conversations. GPT and Grok have higher statement percentages but lower accept/reject rates, making them useful for augmenting data but less similar to WhatsApp compared to Llama.

Now we move to the results of our extrinsic evaluation training BERT-based classifiers in the task of detecting harmful messages.

Size	Dev.	Test
20%	$73.1\%\pm2.2$	$75.3\%\pm3.5$
50%	$77.4\%\pm2.0$	$80.4\%\pm1.3$
90%	$79.1\%\pm0.9$	$\textbf{81.0\%}\pm0.9$
100%	<b>79.4%</b> $\pm 1.3$	$80.9\%\pm1.6$

Table 5: Development and test set accuracy in scenario 1: training BERT-based classifiers on the training split of the authentic data; 10 repetitions with different random seeds; also shown for comparison results for training on samples of 20%, 90% and 50% (sampling without replacement; both the training set and the development set are sampled to the given relative size of the authentic data split)

#### 5.1 Scenario 1: Baseline

Table 5 presents the development and test set accuracies for BERT-based classifier trained on different portions of the training split of authentic data in scenario 1. The results indicate that increasing the training data generally improves both development and test accuracy. When training on only 20% of the data, test accuracy is the lowest at 75.3%. With 50% of the data, test accuracy increases to 80.4%, indicating a significant performance boost from using more data. At 90%, test accuracy reaches its highest value of 81.0%, suggesting that this amount of data provides the best generalization. Training on the full dataset (100%) results in a slight drop in test accuracy, despite the highest development accuracy. This suggests that using 90% of the data strikes the best balance between training effectiveness and generalization.

Overall, the results highlight that while increasing the dataset size generally improves performance, there exists a point of diminishing returns. The best test accuracy is observed when using 90% of the data, suggesting that the last 10% of the dataset does not contribute significantly to generalization and might even slightly increase overfitting. These findings suggest that careful tuning of dataset size could help optimize performance while minimizing computational cost.

# 5.2 Scenario 2: LLMs as a Classifier

Table 6 presents the accuracy of GPT-40, Grok, and Llama models using GE and GF prompts on both development and test sets in Scenario 2. We evaluate both GE and GF prompts on the development set and use the winning method (in all cases, GE) on the test set. GPT-40 achieves the highest accuracy with GE prompts, demonstrating its superior generalization, while Grok performs the lowest. The consistent underperformance of GF prompts, particularly for Grok, highlights the importance of prompt design for model accuracy. Overall, GPT-40 demonstrates the best performance across both sets, while the selection of GE prompts as the winning method proves effective for all models in test evaluation.

LLM	Prompt	Dev. Set	Test Set
GPT	GE	85.65%	83.14%
GPT	GF	85.65%	-
Grok	GE	81.32%	78.59%
Grok	GF	75.85%	-
Llama	GE	82.9%	80.4%
Llama	GF	82.0%	-

Table 6: Accuracy of different LLMs with GE and GF prompts on Development and Test sets in scenario 2: Using LLM as a CB Classifier. Dev. = development.

#### 5.3 Scenario 3: Fully Synthetic Data

Table 7 presents the development and test set accuracy for scenario 3: BERT-based classifiers trained on synthetic datasets generated by Llama, GPT, and Grok.

The results indicate that Llama consistently outperforms the other two models across different dataset sizes. GPT follows closely, while Grok exhibits the weakest performance, particularly on the test set, where its accuracy is significantly lower than that of the other models. This suggests that Llama-generated synthetic data is of higher quality and more beneficial for training the classifier, while Grok struggles to produce effective training samples.

Examining the impact of increasing the size of synthetic data, the results show a general trend of performance improvement for Llama and Grok, but little impact for GPT. For Llama, the test accuracy improves from 73.7% at 100% data size to a peak of 75.5% at 180%, before slightly decreasing to 75.2% at 200%. A similar trend is observed for Grok, where the test accuracy increases from 48.2% at 100% to 52.7% at 200%. In contrast, for GPT, the test accuracy remains relatively stable, with minimal improvement across the different data sizes. These results suggest that increasing synthetic data size enhances performance for some models, like Llama and Grok, but has little effect on GPT. This indicates that the effectiveness of synthetic data scaling may depend on the LLM and the quality of the data.

Comparing the training of BERT on authentic data (Table 5) with its training on synthetic data (Table 7) shows that, while authentic data yields the highest accuracy (81.0%), achieving 75.5% with Llama-generated synthetic data-without relying on any human-created data, is still notable. The 5.5% accuracy gap highlights the trade-off between performance and the reduced time, effort, and ethical complexities associated with humanannotated CB datasets. For sensitive and ethically challenging tasks, such as CB detection, synthetic data presents a valuable alternative, minimizing human involvement while maintaining competitive model performance. The results emphasize that high-quality synthetic data from advanced LLMs, such as Llama, can serve as a practical supplement or even a partial substitute, particularly in scenarios where authentic data collection is difficult or impractical.

# 5.4 Scenario 4

Table 8 shows the Development and test set accuracies in scenario 4. We investigate two key aspects: (1) The comparison of different LLMs (GPT, Llama, and Grok) for augmentation, (2) The minimum amount of authentic data required to achieve comparable results to using the full au-

Rel.	Llama		GPT		Grok	
Size	Dev.	Test	Dev.	Test	Dev.	Test
100%	$73.4\%\pm2.4$	$73.7\%\pm5.0$	$69.2\%\pm0.3$	$69.7\%\pm0.5$	$53.3\%\pm4.8$	$48.2\% \pm 5.7$
120%	$73.7\%\pm1.3$	$74.3\%\pm2.7$	$69.0\% \pm 1.4$	$69.6\%\pm0.9$	$54.2\%\pm5.1$	$48.5\%\pm6.2$
140%	$74.4\%\pm1.0$	$74.8\%\pm2.7$	$69.3\%\pm0.2$	$69.7\%\pm0.2$	$54.0\%\pm4.9$	$49.3\%\pm6.5$
160%	$74.1\%\pm1.6$	$74.4\%\pm3.9$	$69.4\%\pm0.5$	$69.6\%\pm0.4$	$56.4\%\pm7.7$	$51.1\%\pm8.0$
180%	$74.7\%\pm0.9$	$75.5\% \pm 2.3$	$69.5\% \pm 0.5$	$69.8\% \pm 0.4$	$57.3\%\pm5.2$	$51.7\%\pm4.9$
200%	$\textbf{74.8\%} \pm 0.9$	$75.2\%\pm2.1$	$69.2\%\pm0.1$	$69.8\%\pm0.2$	$\textbf{59.2\%} \pm 4.1$	$\textbf{52.7\%} \pm 4.5$

Table 7: Development and test set results in scenario 3: training a BERT-based classifier on synthetic data matching 100% to 200% of the size available in scenario 1; average and standard deviation for 10 repetitions with different random seeds

Si	Size Llama		Llama		PT	Gr	ok
WA	Syn.	Dev.	Test	Dev.	Test	Dev.	Test
10%	90%	$74.4\% \pm 1.1$	$75.6\%\pm2.9$	$70.9\%\pm1.5$	$72.4\% \pm 3.1$	$75.4\% \pm 2.0$	$75.1\% \pm 2.5$
20%	80%	$75.6\%\pm1.7$	$77.4\%\pm2.2$	$73.3\%\pm1.2$	$76.2\% \pm 1.4$	$77.2\% \pm 1.3$	$77.6\%\pm1.7$
30%	70%	$76.7\%\pm2.0$	$78.7\%\pm2.0$	$75.3\%\pm1.2$	$78.4\%\pm0.9$	$78.5\%\pm1.8$	$78.3\%\pm1.0$
40%	60%	$77.1\% \pm 1.4$	$79.1\% \pm 1.7$	$75.5\%\pm1.9$	$78.8\% \pm 1.3$	$79.1\%\pm0.8$	$79.1\%\pm0.9$
50%	50%	$77.8\%\pm1.6$	$79.8\%\pm1.0$	$76.4\%\pm1.8$	$79.8\%\pm1.3$	$79.4\% \pm 1.1$	$79.8\%\pm0.9$
60%	40%	$78.2\%\pm1.6$	$79.9\% \pm 1.1$	$77.8\%\pm1.3$	$80.1\%\pm1.5$	$79.5\%\pm1.0$	$80.6\%\pm1.4$
70%	30%	$78.1\%\pm1.3$	$80.1\%\pm0.9$	$77.9\%\pm2.2$	$79.7\%\pm1.2$	$79.5\%\pm0.5$	$80.6\%\pm1.1$
80%	20%	$78.6\%\pm1.6$	$81.4\%\pm1.1$	$79.4\%\pm1.0$	$81.2\%\pm1.3$	$79.6\%\pm0.7$	$81.1\%\pm1.4$
90%	10%	$79.3\%\pm1.0$	$81.5\%\pm0.7$	$79.2\%\pm1.3$	$81.8\%\pm0.9$	$79.6\%\pm1.0$	$81.2\%\pm0.9$
100%	0%	$79.4\% \pm 1.3$	$80.9\%\pm1.6$	$79.4\% \pm 1.3$	$80.9\%\pm1.6$	$79.4\% \pm 1.3$	$80.9\%\pm1.6$
100%	20%	<b>79.5%</b> ± 1.2	$81.5\% \pm 0.6$	$80.0\% \pm 0.7$	$82.0\% \pm 1.4$	$79.6\%\pm0.7$	<b>81.8%</b> ± 0.8
100%	40%	$79.0\% \pm 1.1$	$81.4\%\pm0.5$	$79.5\%\pm1.1$	$\textbf{82.2\%} \pm 1.4$	$79.7\% \pm 1.1$	$81.7\%\pm1.2$
100%	60%	$78.4\% \pm 1.0$	$81.1\%\pm1.1$	$79.4\% \pm 1.8$	$80.6\%\pm1.4$	$79.8\%\pm0.7$	$81.8\%\pm1.2$
100%	80%	$78.5\%\pm0.8$	$80.9\%\pm0.7$	$78.8\%\pm1.6$	$81.5\%\pm1.6$	$\textbf{80.3\%} \pm 0.8$	$81.6\%\pm1.3$
100%	100%	$78.0\% \pm 1.3$	$81.2\%\pm0.9$	$79.0\% \pm 1.4$	$81.1\%\pm1.1$	$80.3\%\pm0.8$	$81.8\%\pm1.1$

Table 8: Development and test set accuracies in scenario 4: training a BERT-based classifiers on a combination of authentic and synthetic data matching 0% to 100% of the size available in scenario 1; average and standard deviation for 10 repetitions with different random seeds

#### thentic dataset.

When comparing the potential of different LLMs for data augmentation, considering the rows with 100% authentic data, all three models initially show similar test accuracies. However, regardless of the LLM used, adding synthetic data consistently leads to improvements in performance, with one exception: GPT at the 100%-60% authentic-synthetic combination, where its accuracy slightly decreases. GPT demonstrates the most significant gains, reaching up to 82.2% accuracy with 40% synthetic data. An interesting observation is that, despite Grok being significantly weaker than both GPT and Llama in scenario 3 in Table 7, with a maximum accuracy of only 52.7%, it still performs well in data augmentation, providing valuable improvements to the overall model performance.

Analyzing Table 8, it is evident that introducing synthetic data allows the models to achieve comparable performance to using the full (100%) authentic dataset with a reduced amount of authentic data. For instance, at a 50% authentic-to-synthetic data ratio, all three models show test accuracies (79.8%), closely matching the 80.9% accuracy ob-

tained with the full authentic dataset. This suggests that using synthetic data, especially in balanced ratios (50% authentic and 50% synthetic), can significantly reduce the amount of authentic data required to maintain high model performance. Therefore, a 50% authentic data ratio appears to be the minimum threshold at which comparable results to using 100% authentic data can be achieved.

### 6 Conclusions

In this paper, we explored the potential of LLMgenerated synthetic data for cyberbullying detection, evaluating its effectiveness in various scenarios, including direct classification and data augmentation for training. Our results highlight that synthetic data can significantly reduce reliance on human annotators while maintaining competitive model performance, especially in low-resource settings. However, we also observed that the quality and utility of synthetic data depend heavily on prompt design and data selection strategies.

For future work, we want to expand the set of data availability scenarios to the following two scenarios we think may provide insights into the contribution of automatic labelling and synthetic data generation:

- Scenario 3b: Synthetic Labels for Unlabeled Data This scenario addresses the common situation where manual labeling resources are limited. Here, gold-standard labeled data is available only for the test set, while a significant amount of unlabeled authentic data is available for training and validation. To utilize this unlabeled data, we employ an LLM to generate synthetic labels. Two strategies are explored: (1) guiding the LLM with detailed labeling instructions, and (2) allowing the LLM to generate labels without such guidelines. This scenario demonstrates the utility of LLMs in resource-constrained settings, enabling cost-effective dataset creation from unannotated corpora.
- Scenario 4b: Data Augmentation with Synthetic Labels for Unlabeled Data In this scenario, we assume access to a mix of goldstandard labeled data and unlabeled authentic data for training the CB classifier. To maximize the utility of the unlabeled data, we use an LLM to generate synthetic labels for it. The resulting labeled authentic data and syntheticlabeled authentic data are combined to form the training and validation sets.

This setup is particularly relevant when large amounts of unlabeled authentic data are available, but manual annotation is prohibitively expensive. By converting unlabeled data into labeled training examples, this approach enhances dataset size and diversity, potentially improving the model's generalization capability.

We also plan to investigate how temperature settings during label and conversation generation affect data diversity and model performance, including whether mixing outputs from different temperature settings in an ensemble yields improvements. Additionally, we will apply confidence thresholds to synthetic labels generated with prompts requesting both labels and confidence scores, aiming to determine the most effective threshold for filtering reliable synthetic data. Finally, we intend to explore methods for selecting subsets of synthetic data based on their similarity to authentic data, with the goal of improving model generalization and alignment with real-world patterns

## Acknowledgments

This research is supported by the Disruptive Technologies Innovation Fund (DTIF) under the project "Cilter: Protecting Children Online" Grant No. DT 2021 0362 from the Department of Enterprise, Trade and Employment in Ireland and administered by Enterprise Ireland (EI). This research was conducted with the financial support of Science Foundation Ireland under Grant Agreement No. 13/RC/2106 P2 at the ADAPT SFI Research Centre at Dublin City University. ADAPT, the SFI Research Centre for AI-Driven Digital Content Technology, is funded by Science Foundation Ireland through the SFI Research Centres Programme. For the purpose of Open Access, the author has applied a CC BY public copyright licence to any Author Accepted Manuscript version arising from this submission.

# References

- Maryam M. AlEmadi and Wajdi Zaghouani. 2024. Emotional toll and coping strategies: Navigating the effects of annotating hate speech data. In *Proceedings of the Workshop on Legal and Ethical Issues in Human Language Technologies @ LREC-COLING* 2024, pages 66–72, Torino, Italia. ELRA and ICCL.
- Ateret Anaby-Tavor, Boaz Carmeli, Esther Goldbraich, Amir Kantor, George Kour, Segev Shlomov, Naama Tepper, and Naama Zwerdling. 2020. Do not have enough data? deep learning to the rescue! *Proceedings of the AAAI Conference on Artificial Intelligence*, 34(05):7383–7390.
- Steven Bird, Ewan Klein, and Edward Loper. 2019. Natural language processing with Python. Updated edition for NLTK version 3.0 accessed 15th of February 2025. A 2009 edition is distributed by O'Reilly Media Inc.
- Luiz Bonifacio, Hugo Abonizio, Marzieh Fadaee, and Rodrigo Nogueira. 2022. InPars: Unsupervised dataset generation for information retrieval. In *Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval*, SIGIR '22, pages 2387–2392, New York, NY, USA. Association for Computing Machinery.
- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020.

Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.

- Naveed Ejaz, Fakhra Kashif, and Salimur Choudhury. 2024. A multi-faceted semi-synthetic dataset for automated cyberbullying detection. *Preprint*, arXiv:2402.10231.
- Eric Forsyth, Jane Lin, and Craig Martell. 2010. NPS internet chatroom conversations, release 1.0 LDC2010T05. Web Download. Philadelphia: Linguistic Data Consortium.
- Eric N. Forsyth and Craig H. Martell. 2007. Lexical and discourse analysis of online chat dialog. In *International Conference on Semantic Computing (ICSC* 2007), pages 19–26.
- Hamideh Ghanadian, Isar Nejadgholi, and Hussein Al Osman. 2024. Socially aware synthetic data generation for suicidal ideation detection using large language models. *IEEE Access*, 12:14350–14363.
- Xuanli He, Islam Nassar, Jamie Kiros, Gholamreza Haffari, and Mohammad Norouzi. 2022. Generate, annotate, and learn: NLP with synthetic text. *Transactions of the Association for Computational Linguistics*, 10:826–842.
- Xuanli He, Islam Nassar, Jamie Ryan Kiros, Gholamreza Haffari, and Mohammad Norouzi. 2021. Generate, annotate, and learn: Generative models advance self-training and knowledge distillation. Manuscript submitted to ICLR 2022.
- C.J. Hutto and Eric Gilbert. 2014. VADER: A parsimonious rule-based model for sentiment analysis of social media text. *Proceedings of the Eighth International Conference on Weblogs and Social Media* (*ICWSM-14*), 8(1):216–225.
- Zhuoyan Li, Hangxiao Zhu, Zhuoran Lu, and Ming Yin. 2023. Synthetic data generation with large language models for text classification: Potential and limitations. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 10443–10461, Singapore. Association for Computational Linguistics.
- Yu Meng, Jiaxin Huang, Yu Zhang, and Jiawei Han. 2022. Generating training data with language models: Towards zero-shot language understanding. In *Advances in Neural Information Processing Systems*, volume 35, pages 462–477. Curran Associates, Inc.
- Christopher Perez and Sayar Karmakar. 2023. An NLPassisted Bayesian time-series analysis for prevalence of Twitter cyberbullying during the COVID-19 pandemic. *Social Network Analysis and Mining*, 13(51).
- Rachele Sprugnoli, Stefano Menini, Sara Tonelli, Filippo Oncini, and Enrico Piras. 2018. Creating a WhatsApp dataset to study pre-teen cyberbullying. In *Proceedings of the 2nd Workshop on Abusive Language Online (ALW2)*, pages 51–59, Brussels, Belgium. Association for Computational Linguistics.

Case	Type of addressed prob- lem
"Your shy male classmate	"Gendered division of
has a great passion for clas-	sport" practices
sical dance.Usually he does	
not talk much, but today	
he has decided to invite the	
class to watch him for his	
ballet show."	

Table 9: Example scenario and problem type for conversation initiation(Sprugnoli et al., 2018)

- SurgeAI. 2021. The obscenity list. https://github. com/surge-ai/profanity. Accessed: [15-02-2025].
- Cynthia Van Hee, Ben Verhoeven, Els Lefever, Guy De Pauw, Véronique Hoste, and Walter Daelemans. 2015. Guidelines for the fine-grained analysis of cyberbullying, version 1.0. T3 Technical Report – LT3 15-01.
- Kanishk Verma, Maja Popović, Alexandros Poulis, Yelena Cherkasova, Cathal Ó hÓbáin, Angela Mazzone, Tijana Milosevic, and Brian Davis. 2023. Leveraging machine translation for cross-lingual fine-grained cyberbullying classification amongst pre-adolescents. *Natural Language Engineering*, 29(6):1458–1480.
- Junda Wang, Zonghai Yao, Zhichao Yang, Huixue Zhou, Rumeng Li, Xun Wang, Yucheng Xu, and Hong Yu. 2024. NoteChat: A dataset of synthetic patientphysician conversations conditioned on clinical notes. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 15183–15201, Bangkok, Thailand. Association for Computational Linguistics.
- Kang Min Yoo, Dongju Park, Jaewook Kang, Sang-Woo Lee, and Woomyoung Park. 2021. GPT3Mix: Leveraging large-scale language models for text augmentation. In *Findings of the Association for Computational Linguistics: EMNLP 2021*, pages 2225–2239, Punta Cana, Dominican Republic. Association for Computational Linguistics.

# A Appendix

Table	10.	Advantages	and Disady	antages o	f Each 9	Scenario	in Cy	herbully	ving I	Detection
raute	10.	Auvantages	and Disauv	antages 0.	I Lacii v	Scenario	шCу	ocrouity	ing i	Julution

Scenario	Advantages	Disadvantages		
Baseline (Gold-Standard	High-quality, reliable data	High costs and scalability chal-		
Only)		lenges; Requires significant time		
		and expert annotation effort.		
LLM as Classifier	No need for labeled data or train-	Computationally expensive;		
	ing; Quick deployment; Handles	May be less accurate than		
	nuanced language patterns.	fine-tuned classifiers on domain		
		specific data.		
Fully Synthetic Data	Enables training when no au-	Synthetic data may lack diver-		
	thentic data is available; Suitable	sity and realism; Risk of overfit-		
	for low-resource domains.	ting to generated patterns.		
Data Augmentation with Syn-	Boosts training dataset size;	Synthetic data quality is critical;		
thetic Data	Scalable and cost-effective.	May not fully represent authen-		
		tic language nuances.		

cyberbullying-related text categories are described below:
Threat/Blackmail Physical or psychological threats or indications of blackmail.
Insult Abusive, degrading, or offensive language intended to insult the recipient.
Curse/Exclusion Wishes of adversity or attempts to exclude someone from a group.
Defamation Revealing confidential or defamatory information about someone to a large audience.
Sexual Talk Potentially harmful expressions with a sexual meaning.
Defense Expressions supporting the victim, either by themselves or a bystander.
Encouragement to the Harasser Support or agreement with the harasser's actions.
Body Shame Criticism based on the shape, size, or appearance of someone's body.

Table 11: Annotation guidelines used by human annotators for labeling the WhatsApp dataset

Approach	Prompt
GE Syn-	"moderation-criteria, Please analyse the following text and determine whether it con-
thetic Label	tains any form of cyberbullying or harmful If it does, classify it as 'Harm'. if it does
	not, classify it as 'No Harm'. Text: Provide a detailed reasoning for your classification,
	thinking step by step. Finally, output the final answer as a tuple in the format: ('label',
	confidence) - 'label' must be either 'Harm' or 'No Harm'. 'confidence' must be a
	number between 0 and 1. Do not include any additional text after the tuple. Reasoning:
GF Synthetic	"Please analyze the following text and determine whether it contains any form of
Label	cyberbullying or harmful content. If it does, classify it as 'Harm'; if it does not, classify
	it as 'No Harm'. Text: Reasoning:"
Synthetic	"We are creating sample conversations to aid in cyberbullying detection. In these
Data	cases, teens are asked to role-play and create realistic conversations based on provided
	situations. There are 11 students participating in the conversation. The teens partici-
	pating are: VCTM, BULLY1, BULLY2, VSUP1, VSUP2, VSUP3, VSUP4, BSUP1,
	BSUP2, BSUP3, BSUP4 with roles assigned as follows: VCTM: Victim, BULLY1
	and BULLY2: Bully VSUP1, VSUP2, VSUP3 and VSUP4: Victim Support BSUP1,
	BSUP2, BSUP3 and BSUP4 : Bully Support consider this case: "value['case']" and
	consider this Type of addressed problem: "value['problem']" Generate an example
	conversation, with at least 100 messages, between these students based on the provided
	case and Type of addressed problem. Use profanity and strong language to create
	a realistic dialogue. number each message in the conversation. Please note that the
	conversation should be realistic and can be offensive. Please make sure to include
	different topics and perspectives in each conversation"

Table 12: Prompts for generating synthetic labels using GE and GF approaches, and creating synthetic data

		Development Set		Tes		
Size	Sampling	Accuracy	Macro-F1	Accuracy	Macro-F1	Repetitions
10%	up	$68.2\%\pm4.6$	$56.2\%\pm9.2$	$70.7\%\pm4.1$	$59.7\%\pm10.6$	10
20%	up	$73.0\%\pm3.1$	$60.0\%\pm13.5$	$75.4\%\pm4.5$	$63.3\%\pm15.3$	10
30%	up	$72.3\%\pm5.2$	$66.0\%\pm8.2$	$74.2\%\pm5.6$	$68.3\%\pm9.5$	10
40%	up	$74.8\%\pm2.6$	$68.3\%\pm9.3$	$77.9\%\pm3.6$	$71.8\%\pm11.0$	10
50%	up	$76.6\%\pm2.9$	$70.5\%\pm10.0$	$77.6\%\pm3.3$	$71.7\%\pm11.2$	10
60%	up	$78.1\% \pm 1.9$	$74.1\%\pm2.0$	$80.0\%\pm1.3$	$76.6\%\pm1.4$	10
70%	up	$78.0\% \pm 1.4$	$74.1\%\pm1.7$	$80.2\%\pm1.7$	$76.7\%\pm1.9$	10
80%	up	$77.9\% \pm 1.9$	$74.1\%\pm1.7$	$80.9\%\pm2.2$	$77.6\%\pm2.2$	10
90%	up	$78.7\%\pm1.2$	$75.1\%\pm1.0$	$80.2\%\pm1.5$	$77.0\% \pm 1.5$	10
100%	up	$78.4\%\pm1.6$	$74.9\%\pm1.6$	$80.8\%\pm1.3$	$77.7\%\pm1.2$	10
10%	down	$55.9\%\pm10.7$	$49.4\%\pm8.1$	$59.3\%\pm9.7$	$52.8\%\pm9.2$	10
20%	down	$64.4\%\pm7.1$	$51.7\%\pm10.3$	$67.7\%\pm5.3$	$55.3\%\pm13.0$	10
30%	down	$68.9\%\pm4.0$	$61.2\%\pm10.9$	$70.3\%\pm2.9$	$63.1\%\pm11.5$	10
40%	down	$70.5\%\pm3.1$	$55.2\%\pm15.1$	$71.1\%\pm2.4$	$56.0\%\pm15.6$	10
50%	down	$70.6\%\pm2.3$	$61.0\%\pm13.4$	$72.0\%\pm2.6$	$62.4\%\pm14.4$	10
60%	down	$72.0\%\pm3.2$	$59.2\%\pm15.9$	$73.1\%\pm3.9$	$60.6\%\pm16.8$	10
70%	down	$71.5\%\pm3.2$	$59.1\%\pm15.3$	$73.1\%\pm3.6$	$60.6\%\pm16.7$	10
80%	down	$73.0\%\pm3.6$	$63.3\%\pm15.0$	$74.6\%\pm4.2$	$65.0\%\pm16.0$	10
90%	down	$72.2\%\pm3.5$	$60.5\%\pm15.3$	$73.5\%\pm3.7$	$61.8\%\pm16.3$	10
100%	down	$71.7\%\pm4.7$	$59.4\%\pm15.3$	$73.3\%\pm5.3$	$60.8\%\pm16.7$	10
10%	none	$69.2\%\pm0.7$	$45.8\%\pm7.5$	$69.6\%\pm0.8$	$46.5\%\pm7.7$	10
20%	none	$73.1\%\pm2.2$	$58.4\%\pm8.4$	$75.3\%\pm3.5$	$62.1\%\pm10.8$	10
30%	none	$72.1\%\pm3.3$	$53.9\%\pm14.4$	$72.8\%\pm4.1$	$54.3\%\pm15.8$	10
40%	none	$76.3\%\pm2.1$	$69.6\%\pm3.3$	$79.6\%\pm1.1$	$74.1\%\pm2.1$	10
50%	none	$77.4\%\pm2.0$	$71.4\%\pm2.7$	$80.4\%\pm1.3$	$75.3\%\pm1.2$	10
60%	none	$78.2\% \pm 1.7$	$73.1\%\pm2.1$	$80.6\%\pm1.6$	$76.3\%\pm1.9$	10
70%	none	$78.4\% \pm 1.3$	$73.3\%\pm1.7$	$81.2\%\pm1.8$	$76.9\%\pm1.9$	10
80%	none	$79.2\%\pm1.0$	$74.3\%\pm1.4$	$81.3\%\pm1.2$	$76.8\%\pm1.2$	10
90%	none	$79.1\%\pm0.9$	$74.5\%\pm1.2$	$81.0\%\pm0.9$	$76.8\%\pm0.9$	10
100%	none	$79.4\% \pm 1.3$	$75.0\%\pm1.5$	$80.9\%\pm1.6$	$76.9\%\pm1.4$	10
150%	none	$79.5\%\pm1.3$	$75.1\%\pm1.6$	$81.3\%\pm1.4$	$77.4\%\pm1.5$	10
200%	none	$79.9\%\pm1.1$	$75.5\%\pm1.2$	$81.6\%\pm1.6$	$77.6\% \pm 1.8$	10

Table 13: Development and test set results in scenario 1: training BERT-based classifiers on the training split of the authentic data; 10 repetitions with different random seeds; also shown for comparison results for training on samples from 10% to 90%, 150% and 200% (sampling without replacement, resetting the sampling urn when empty; both the training set and the development set are sampled to the given relative size of the authentic data split) "Sampling" refers to the strategy for addressing class imbalance in the training data;

Rel.		Developr	nent Set	Test		
Size	Sampling	Accuracy	Macro-F1	Accuracy	Macro-F1	Rep.
100%	up	$69.0\%\pm1.8$	$48.6\%\pm2.7$	$70.3\%\pm1.5$	$52.5\%\pm5.1$	10
120%	up	$69.7\%\pm0.7$	$48.4\%\pm2.4$	$70.4\%\pm1.2$	$50.7\%\pm3.0$	10
140%	up	$69.8\%\pm0.7$	$50.6\% \pm 1.7$	$71.1\%\pm1.5$	$53.8\%\pm3.1$	10
160%	up	$69.8\%\pm0.9$	$51.1\%\pm2.8$	$71.7\%\pm1.4$	$55.9\%\pm4.1$	10
180%	up	$70.2\%\pm1.0$	$50.4\%\pm2.6$	$71.5\%\pm1.8$	$53.9\% \pm 5.4$	10
200%	up	$70.5\%\pm0.8$	$51.8\%\pm2.3$	$71.9\%\pm1.2$	$55.4\%\pm4.9$	10
100%	down	$58.6\%\pm10.2$	$45.9\%\pm5.1$	$58.5\%\pm11.6$	$46.5\%\pm7.0$	10
120%	down	$59.0\%\pm9.2$	$49.0\%\pm7.0$	$57.0\%\pm11.2$	$47.8\%\pm7.3$	10
140%	down	$59.0\%\pm9.7$	$46.7\%\pm5.5$	$57.6\%\pm11.6$	$46.1\%\pm5.5$	10
160%	down	$63.9\%\pm5.7$	$49.7\%\pm7.8$	$63.8\%\pm6.5$	$50.6\%\pm8.6$	10
180%	down	$61.3\%\pm8.2$	$47.9\%\pm6.6$	$61.5\%\pm9.7$	$49.3\%\pm8.8$	10
200%	down	$63.1\%\pm6.9$	$49.4\%\pm7.4$	$62.0\%\pm8.9$	$49.4\%\pm8.1$	10
100%	none	$69.2\%\pm0.3$	$42.0\%\pm1.3$	$69.7\%\pm0.5$	$42.4\%\pm1.5$	10
120%	none	$69.0\% \pm 1.4$	$42.6\%\pm2.3$	$69.6\%\pm0.9$	$43.4\%\pm2.7$	10
140%	none	$69.3\%\pm0.2$	$41.4\%\pm1.4$	$69.7\%\pm0.2$	$41.7\%\pm1.0$	10
160%	none	$69.4\%\pm0.5$	$43.2\%\pm2.3$	$69.6\%\pm0.4$	$43.3\%\pm3.2$	10
180%	none	$69.5\%\pm0.5$	$43.4\%\pm2.3$	$69.8\%\pm0.4$	$43.3\%\pm2.4$	10
200%	none	$69.2\%\pm0.1$	$41.7\%\pm0.9$	$69.8\%\pm0.2$	$42.1\%\pm1.1$	10

Table 14: Development and test set results for ChatGPT in scenario 3: training a BERT-based classifier on synthetic data matching 100% to 200% of the size available in scenario 1. "Sampling" refers to the strategy for addressing class imbalance in the training data; average and standard deviation for 10 repetitions with different random seeds

Rel.		Develop	oment Set	Tes		
Size	Sampling	Accuracy	Macro-F1	Accuracy	Macro-F1	Rep.
100%	up	$74.0\%\pm1.8$	$64.6\%\pm2.0$	$72.9\%\pm4.0$	$64.2\%\pm2.6$	10
120%	up	$72.9\%\pm3.2$	$63.8\%\pm3.2$	$70.8\%\pm5.0$	$62.9\%\pm3.7$	10
140%	up	$73.6\%\pm1.9$	$65.7\% \pm 1.4$	$71.5\%\pm4.6$	$64.7\%\pm3.0$	10
160%	up	$73.5\%\pm1.5$	$66.1\%\pm2.7$	$74.3\%\pm2.7$	$68.4\%\pm2.6$	10
180%	up	$73.7\%\pm1.8$	$65.1\%\pm2.4$	$72.6\%\pm3.8$	$65.4\%\pm3.4$	10
200%	up	$73.6\%\pm1.4$	$66.3\%\pm2.1$	$73.4\%\pm3.8$	$67.8\%\pm3.2$	10
100%	down	$68.0\%\pm5.6$	$54.2\%\pm11.6$	$66.7\%\pm6.0$	$53.4\%\pm10.7$	10
120%	down	$68.9\% \pm 5.1$	$52.8\%\pm12.5$	$68.0\%\pm6.3$	$52.4\%\pm11.9$	10
140%	down	$67.3\%\pm6.1$	$57.1\%\pm11.2$	$65.7\%\pm7.2$	$56.1\%\pm10.5$	10
160%	down	$67.3\%\pm3.8$	$59.3\%\pm9.3$	$63.7\%\pm5.6$	$56.8\%\pm8.4$	10
180%	down	$70.3\%\pm4.4$	$60.9\%\pm11.1$	$66.9\% \pm 5.4$	$58.4\%\pm10.1$	10
200%	down	$71.3\%\pm3.8$	$63.0\%\pm7.8$	$69.2\%\pm5.7$	$61.9\%\pm8.3$	10
100%	none	$73.4\%\pm2.4$	$61.3\%\pm4.0$	$73.7\%\pm5.0$	$62.7\%\pm4.5$	10
120%	none	$73.7\%\pm1.3$	$58.8\%\pm3.8$	$74.3\%\pm2.7$	$60.4\%\pm4.6$	10
140%	none	$74.4\%\pm1.0$	$61.9\%\pm3.0$	$74.8\%\pm2.7$	$63.2\%\pm4.7$	10
160%	none	$74.1\%\pm1.6$	$63.2\%\pm2.1$	$74.4\%\pm3.9$	$64.5\%\pm4.1$	10
180%	none	$74.7\%\pm0.9$	$64.6\%\pm2.6$	$75.5\%\pm2.3$	$66.0\%\pm4.1$	10
200%	none	$74.8\%\pm0.9$	$63.3\%\pm2.7$	$75.2\%\pm2.1$	$64.4\%\pm3.0$	10

Table 15: Development and test set results for Llama3 in scenario 3: training a BERT-based classifier on synthetic data matching 100% to 200% of the size available in scenario 1. "Sampling" refers to the strategy for addressing class imbalance in the training data; average and standard deviation for 10 repetitions with different random seeds

Rel.		Develop	ment Set	Test		
Size	Sampling	Accuracy	Macro-F1	Accuracy	Macro-F1	Rep.
100%	up	$51.0\%\pm4.3$	$50.7\%\pm4.4$	$47.6\%\pm4.0$	$47.2\%\pm4.4$	10
120%	up	$54.9\%\pm5.8$	$54.5\%\pm5.5$	$49.2\%\pm5.3$	$48.9\%\pm5.4$	10
140%	up	$57.0\%\pm4.0$	$56.7\%\pm3.7$	$52.3\%\pm5.5$	$52.1\%\pm5.4$	10
160%	up	$52.0\%\pm3.5$	$51.8\%\pm3.6$	$47.0\%\pm3.8$	$46.6\%\pm4.0$	10
180%	up	$55.4\%\pm5.9$	$55.0\% \pm 5.4$	$51.1\%\pm7.3$	$50.8\%\pm7.3$	10
200%	up	$56.0\%\pm6.4$	$55.5\%\pm6.0$	$51.4\%\pm7.0$	$51.0\%\pm6.9$	10
100%	down	$56.8\%\pm6.7$	$56.2\%\pm5.8$	$52.4\%\pm6.6$	$52.0\%\pm6.2$	10
120%	down	$55.3\%\pm6.1$	$54.7\%\pm5.4$	$52.3\%\pm6.9$	$51.8\%\pm6.5$	10
140%	down	$55.6\%\pm6.0$	$55.3\%\pm5.5$	$50.5\%\pm5.8$	$50.2\%\pm5.6$	10
160%	down	$57.2\%\pm6.1$	$56.7\%\pm5.5$	$51.6\%\pm6.4$	$51.3\%\pm6.0$	10
180%	down	$58.2\%\pm6.5$	$57.6\%\pm6.1$	$52.7\%\pm7.4$	$52.3\%\pm7.2$	10
200%	down	$57.2\%\pm6.0$	$56.7\%\pm5.6$	$52.6\%\pm7.3$	$52.2\%\pm7.1$	10
100%	none	$53.3\%\pm4.8$	$53.1\%\pm4.6$	$48.2\%\pm5.7$	$47.9\%\pm5.6$	10
120%	none	$54.2\%\pm5.1$	$53.9\%\pm4.7$	$48.5\%\pm6.2$	$48.1\%\pm6.3$	10
140%	none	$54.0\%\pm4.9$	$53.7\%\pm4.8$	$49.3\%\pm6.5$	$48.9\%\pm6.5$	10
160%	none	$56.4\%\pm7.7$	$55.8\%\pm7.4$	$51.1\%\pm8.0$	$50.6\%\pm8.1$	10
180%	none	$57.3\%\pm5.2$	$57.0\%\pm4.8$	$51.7\%\pm4.9$	$51.6\%\pm4.9$	10
200%	none	$59.2\%\pm4.1$	$58.7\%\pm3.7$	$52.7\%\pm4.5$	$52.5\%\pm4.5$	10

Table 16: Development and test set results in scenario 3: training a BERT-based classifier on synthetic data matching 100% to 200% of the size available in scenario 1. "Sampling" refers to the strategy for addressing class imbalance in the training data; average and standard deviation for 10 repetitions with different random seeds

WA	Syn.		Development Set		Test		
Size	Size	Sampling	Accuracy	Macro-F1	Accuracy	Macro-F1	Rep.
0%	100%	up	$69.0\%\pm1.8$	$48.6\%\pm2.7$	$70.3\%\pm1.5$	$52.5\%\pm5.1$	10
10%	90%	up	$72.3\%\pm2.9$	$60.6\%\pm5.1$	$73.8\%\pm2.6$	$64.5\%\pm3.6$	10
20%	80%	up	$73.3\%\pm1.4$	$63.9\%\pm2.0$	$76.4\%\pm2.4$	$69.6\%\pm2.9$	10
30%	70%	up	$75.5\%\pm1.6$	$68.3\%\pm2.1$	$77.6\%\pm2.0$	$71.8\%\pm2.5$	10
40%	60%	up	$76.0\%\pm2.5$	$70.0\%\pm3.1$	$78.8\%\pm1.9$	$74.1\%\pm2.2$	10
50%	50%	up	$76.5\%\pm1.5$	$71.0\%\pm2.0$	$78.7\%\pm2.2$	$74.6\%\pm2.1$	10
60%	40%	up	$77.6\%\pm1.0$	$72.2\%\pm1.2$	$79.7\%\pm2.1$	$75.5\%\pm2.4$	10
70%	30%	up	$78.0\% \pm 1.1$	$73.2\%\pm1.9$	$80.2\%\pm2.0$	$76.4\%\pm2.2$	10
80%	20%	up	$78.9\% \pm 1.3$	$74.5\%\pm1.2$	$81.0\%\pm1.8$	$77.4\%\pm1.7$	10
90%	10%	up	$78.8\%\pm1.3$	$74.8\%\pm1.1$	$81.4\%\pm0.9$	$78.1\%\pm0.9$	10
100%	0%	up	$78.4\% \pm 1.6$	$74.9\%\pm1.6$	$80.8\%\pm1.3$	$77.7\%\pm1.2$	10
100%	20%	up	$79.4\%\pm0.8$	$75.2\% \pm 1.3$	$81.2\%\pm1.0$	$77.6\%\pm0.9$	10
100%	40%	up	$79.4\% \pm 1.7$	$75.3\%\pm1.7$	$80.8\%\pm1.8$	$77.3\%\pm2.0$	10
100%	60%	up	$78.8\% \pm 1.3$	$74.3\%\pm1.3$	$81.2\%\pm1.1$	$77.5\%\pm1.4$	10
100%	80%	up	$78.4\% \pm 1.5$	$74.0\%\pm1.6$	$80.5\%\pm1.5$	$76.7\%\pm1.4$	10
100%	100%	up	$78.2\%\pm0.9$	$73.6\%\pm1.0$	$80.2\% \pm 1.4$	$76.6\%\pm1.4$	10
100%	150%	up	$78.5\%\pm1.4$	$73.8\%\pm1.8$	$79.7\%\pm1.4$	$75.5\%\pm1.5$	10
100%	200%	up	$78.0\% \pm 1.3$	$73.3\%\pm1.2$	$80.0\%\pm1.1$	$76.3\%\pm0.9$	10
200%	100%	up	$79.2\%\pm0.9$	$75.0\%\pm1.1$	$80.5\%\pm1.0$	$77.0\% \pm 1.1$	10
200%	150%	up	$78.4\% \pm 1.5$	$74.0\%\pm2.0$	$80.8\%\pm1.1$	$77.3\%\pm1.3$	10
200%	200%	up	$78.1\%\pm1.6$	$73.5\%\pm1.9$	$80.4\%\pm1.2$	$76.8\%\pm1.2$	10
0%	100%	none	$69.2\%\pm0.3$	$42.0\%\pm1.3$	$69.7\%\pm0.5$	$42.4\%\pm1.5$	10
10%	90%	none	$70.9\%\pm1.5$	$52.8\%\pm6.4$	$72.4\%\pm3.1$	$56.1\%\pm9.4$	10
20%	80%	none	$73.3\%\pm1.2$	$60.2\%\pm3.9$	$76.2\% \pm 1.4$	$65.5\%\pm3.9$	10
30%	70%	none	$75.3\%\pm1.2$	$66.1\%\pm2.2$	$78.4\%\pm0.9$	$70.9\%\pm1.9$	10
40%	60%	none	$75.5\%\pm1.9$	$68.6\%\pm3.2$	$78.8\%\pm1.3$	$73.2\%\pm2.5$	10
50%	50%	none	$76.4\%\pm1.8$	$69.1\%\pm2.6$	$79.8\%\pm1.3$	$73.9\% \pm 1.5$	10
60%	40%	none	$77.8\% \pm 1.3$	$71.5\%\pm2.3$	$80.1\%\pm1.5$	$74.9\% \pm 1.5$	10
70%	30%	none	$77.9\%\pm2.2$	$72.3\%\pm3.4$	$79.7\% \pm 1.2$	$75.2\%\pm1.8$	10
80%	20%	none	$79.4\% \pm 1.0$	$74.4\%\pm1.5$	$81.2\%\pm1.3$	$76.8\%\pm1.3$	10
90%	10%	none	$79.2\% \pm 1.3$	$74.1\%\pm1.5$	$81.8\%\pm0.9$	$77.4\% \pm 1.2$	10
100%	0%	none	$79.4\% \pm 1.3$	$75.0\% \pm 1.5$	$80.9\%\pm1.6$	$76.9\% \pm 1.4$	10
100%	20%	none	$80.0\%\pm0.7$	$75.3\%\pm1.4$	$82.0\% \pm 1.4$	$77.8\% \pm 1.8$	10
100%	40%	none	$79.5\%\pm1.1$	$74.8\% \pm 1.1$	$82.2\% \pm 1.4$	$78.1\% \pm 1.5$	10
100%	60%	none	$79.4\% \pm 1.8$	$74.6\%\pm2.1$	$80.6\%\pm1.4$	$76.2\% \pm 1.5$	10
100%	80%	none	$78.8\%\pm1.6$	$73.8\%\pm2.0$	$81.5\%\pm1.6$	$77.4\% \pm 1.8$	10
100%	100%	none	$79.0\% \pm 1.4$	$74.0\%\pm1.7$	$81.1\%\pm1.1$	$76.7\%\pm1.5$	10
100%	150%	none	$78.5\%\pm1.2$	$73.2\%\pm1.1$	$81.3\%\pm1.3$	$76.9\%\pm1.5$	10
100%	200%	none	$78.9\% \pm 1.4$	$74.0\%\pm2.0$	$80.8\%\pm1.1$	$76.3\%\pm1.3$	10
200%	100%	none	$79.7\%\pm1.4$	$75.0\%\pm2.0$	$81.5\%\pm0.9$	$77.2\%\pm1.3$	10
200%	150%	none	$79.3\%\pm1.3$	$74.7\%\pm1.5$	$82.1\%\pm1.6$	$78.1\%\pm1.9$	10
200%	200%	none	$79.6\%\pm1.1$	$75.2\% \pm 1.1$	$81.2\%\pm1.4$	$77.1\% \pm 1.2$	10

Table 17: Development and test set results for augmenting authentic training (and development) data with ChatGPTgenerated synthetic data (scenario 4) "Sampling" refers to the strategy for addressing class imbalance in the training data; average and standard deviation for 10 repetitions with different random seeds

WA	Syn.		Development Set		Test		
Size	Size	Sampling	Accuracy	Macro-F1	Accuracy	Macro-F1	Rep.
0%	100%	up	$74.0\%\pm1.8$	$64.6\%\pm2.0$	$72.9\%\pm4.0$	$64.2\%\pm2.6$	10
10%	90%	up	$75.2\%\pm1.6$	$68.2\%\pm2.3$	$76.3\%\pm2.0$	$70.1\%\pm2.8$	10
20%	80%	up	$75.0\%\pm1.3$	$68.0\% \pm 1.7$	$76.8\%\pm2.2$	$71.2\%\pm2.4$	10
30%	70%	up	$75.8\%\pm1.7$	$69.9\%\pm2.0$	$77.9\%\pm2.1$	$73.0\%\pm2.3$	10
40%	60%	up	$76.9\%\pm0.7$	$71.6\%\pm0.6$	$78.0\% \pm 1.4$	$73.4\% \pm 1.5$	10
50%	50%	up	$76.8\%\pm1.4$	$71.8\%\pm1.3$	$79.0\% \pm 1.6$	$74.7\%\pm1.9$	10
60%	40%	up	$77.9\% \pm 1.6$	$73.1\%\pm1.8$	$79.5\%\pm1.3$	$75.6\%\pm1.4$	10
70%	30%	up	$78.2\%\pm0.7$	$73.6\%\pm0.7$	$79.7\% \pm 1.4$	$75.8\% \pm 1.7$	10
80%	20%	up	$79.1\%\pm1.3$	$74.9\% \pm 1.2$	$81.1\%\pm1.1$	$77.5\%\pm1.0$	10
90%	10%	up	$78.9\% \pm 1.3$	$75.0\%\pm1.3$	$81.2\%\pm1.1$	$77.9\% \pm 1.1$	10
100%	0%	up	$78.4\% \pm 1.6$	$74.9\%\pm1.6$	$80.8\%\pm1.3$	$77.7\% \pm 1.2$	10
100%	20%	up	$79.1\% \pm 1.2$	$74.9\%\pm1.0$	$80.9\%\pm0.9$	$77.5\%\pm0.9$	10
100%	40%	up	$78.4\% \pm 1.2$	$74.3\%\pm1.2$	$80.1\% \pm 1.1$	$76.5\%\pm1.3$	10
100%	60%	up	$78.3\%\pm1.0$	$74.0\%\pm1.1$	$80.7\%\pm1.1$	$77.1\% \pm 1.3$	10
100%	80%	up	$78.1\%\pm1.0$	$74.2\%\pm1.1$	$80.5\%\pm1.4$	$77.2\% \pm 1.6$	10
100%	100%	up	$78.1\% \pm 1.2$	$74.0\% \pm 1.4$	$80.8\%\pm0.8$	$77.3\% \pm 1.0$	10
100%	150%	up	$77.7\% \pm 1.3$	$73.4\% \pm 1.5$	$80.6\% \pm 1.4$	$77.1\% \pm 1.7$	10
100%	200%	up	$77.1\%\pm0.8$	$72.9\% \pm 1.2$	$80.0\% \pm 1.7$	$76.5\%\pm1.8$	10
200%	100%	up	$78.1\% \pm 1.1$	$74.2\% \pm 1.3$	$81.4\%\pm1.1$	$78.2\% \pm 1.4$	10
200%	150%	up	$78.2\%\pm0.9$	$74.1\%\pm0.8$	$80.9\% \pm 1.1$	$77.4\% \pm 1.4$	10
200%	200%	up	$77.7\%\pm0.7$	$73.6\%\pm0.8$	$80.7\% \pm 1.0$	$77.4\% \pm 1.2$	10
0%	100%	none	$73.4\%\pm2.4$	$61.3\%\pm4.0$	$73.7\%\pm5.0$	$62.7\%\pm4.5$	10
10%	90%	none	$74.4\%\pm1.1$	$63.5\%\pm2.9$	$75.6\%\pm2.9$	$65.9\%\pm3.9$	10
20%	80%	none	$75.6\%\pm1.7$	$65.7\%\pm3.3$	$77.4\%\pm2.2$	$69.0\%\pm3.7$	10
30%	70%	none	$76.7\%\pm2.0$	$68.3\%\pm3.0$	$78.7\%\pm2.0$	$71.7\%\pm2.5$	10
40%	60%	none	$77.1\% \pm 1.4$	$69.9\%\pm2.2$	$79.1\% \pm 1.7$	$72.8\%\pm3.0$	10
50%	50%	none	$77.8\% \pm 1.6$	$71.2\%\pm2.4$	$79.8\% \pm 1.0$	$74.1\% \pm 1.6$	10
60%	40%	none	$78.2\% \pm 1.6$	$71.6\%\pm2.9$	$79.9\% \pm 1.1$	$74.1\% \pm 1.7$	10
70%	30%	none	$78.1\% \pm 1.3$	$72.2\%\pm1.8$	$80.1\%\pm0.9$	$74.7\% \pm 1.3$	10
80%	20%	none	$78.6\%\pm1.6$	$72.8\%\pm2.2$	$81.4\%\pm1.1$	$76.6\%\pm1.6$	10
90%	10%	none	$79.3\%\pm1.0$	$74.2\%\pm1.7$	$81.5\%\pm0.7$	$77.0\% \pm 1.0$	10
100%	0%	none	$79.4\% \pm 1.3$	$75.0\%\pm1.5$	$80.9\% \pm 1.6$	$76.9\% \pm 1.4$	10
100%	20%	none	$79.5\% \pm 1.2$	$74.2\% \pm 1.7$	$81.5\%\pm0.6$	$77.0\% \pm 1.0$	10
100%	40%	none	$79.0\% \pm 1.1$	$73.6\%\pm1.6$	$81.4\%\pm0.5$	$76.8\%\pm0.7$	10
100%	60%	none	$78.4\% \pm 1.0$	$73.1\%\pm0.9$	$81.1\% \pm 1.1$	$76.8\%\pm1.6$	10
100%	80%	none	$78.5\%\pm0.8$	$72.6\%\pm1.5$	$80.9\%\pm0.7$	$75.8\%\pm0.9$	10
100%	100%	none	$78.0\% \pm 1.3$	$72.5\%\pm1.5$	$81.2\%\pm0.9$	$76.8\%\pm1.3$	10
100%	150%	none	$78.1\%\pm1.6$	$72.7\%\pm2.0$	$81.1\%\pm1.2$	$76.5\%\pm1.8$	10
100%	200%	none	$77.7\% \pm 1.4$	$72.0\%\pm1.7$	$81.1\%\pm1.7$	$76.5\%\pm2.2$	10
200%	100%	none	$79.4\% \pm 1.0$	$74.2\%\pm1.3$	$81.8\% \pm 1.0$	$77.2\% \pm 1.4$	10
200%	150%	none	$78.8\%\pm1.0$	$73.8\%\pm1.4$	$81.2\%\pm1.3$	$76.8\%\pm1.5$	10
200%	200%	none	$78.3\% \pm 1.3$	$73.1\% \pm 1.8$	$81.5\% \pm 1.6$	$77.2\% \pm 1.8$	10

Table 18: Development and test set results for augmenting authentic training (and development) data with Llama3generated synthetic data (scenario 4) "Sampling" refers to the strategy for addressing class imbalance in the training data; average and standard deviation for 10 repetitions with different random seeds

WA	Syn.		Development Set		Test		
Size	Size	Sampling	Accuracy	Macro-F1	Accuracy	Macro-F1	Rep.
0%	100%	up	$51.0\%\pm4.3$	$50.7\%\pm4.4$	$47.6\%\pm4.0$	$47.2\%\pm4.4$	10
10%	90%	up	$74.0\%\pm2.2$	$70.4\%\pm2.2$	$72.2\%\pm2.6$	$69.3\%\pm2.2$	10
20%	80%	up	$77.0\% \pm 1.2$	$72.7\%\pm1.6$	$76.0\%\pm1.5$	$72.3\%\pm1.5$	10
30%	70%	up	$77.4\% \pm 1.7$	$73.3\%\pm2.1$	$76.5\%\pm1.8$	$73.1\%\pm1.6$	10
40%	60%	up	$77.7\%\pm1.3$	$73.8\% \pm 1.4$	$78.0\% \pm 1.3$	$74.7\%\pm1.4$	10
50%	50%	up	$78.2\% \pm 1.4$	$74.8\%\pm1.0$	$78.4\% \pm 1.5$	$75.2\% \pm 1.4$	10
60%	40%	up	$78.9\% \pm 1.0$	$75.2\% \pm 1.3$	$80.2\%\pm1.6$	$77.1\% \pm 1.5$	10
70%	30%	up	$78.4\% \pm 1.1$	$74.9\%\pm1.1$	$79.3\%\pm1.6$	$76.2\%\pm1.6$	10
80%	20%	up	$79.5\% \pm 1.4$	$75.8\% \pm 1.5$	$80.6\%\pm1.3$	$77.4\% \pm 1.5$	10
90%	10%	up	$78.9\% \pm 1.3$	$75.3\% \pm 1.2$	$80.8\% \pm 1.1$	$77.7\% \pm 1.2$	10
100%	0%	up	$78.4\% \pm 1.6$	$74.9\% \pm 1.6$	$80.8\% \pm 1.3$	$77.7\% \pm 1.2$	10
100%	20%	up	$79.4\% \pm 1.1$	$75.9\%\pm0.9$	$80.6\%\pm0.8$	$77.5\% \pm 0.9$	10
100%	40%	up	$79.4\% \pm 1.1$	$75.9\% \pm 1.1$	$80.9\% \pm 1.3$	$77.7\% \pm 1.4$	10
100%	60%	up	$79.0\%\pm0.9$	$75.6\% \pm 0.8$	$80.3\% \pm 1.2$	$77.2\% \pm 1.5$	10
100%	80%	up	$79.4\% \pm 0.6$	$75.9\% \pm 0.6$	$80.0\% \pm 1.0$	$76.9\% \pm 1.3$	10
100%	100%	up	$79.2\% \pm 1.0$	$75.9\% \pm 1.1$	$80.2\%\pm0.8$	$77.3\% \pm 1.0$	10
100%	150%	up	$79.6\% \pm 1.0$	$76.2\% \pm 1.1$	$80.4\% \pm 1.2$	$77.5\% \pm 1.4$	10
100%	200%	up	$79.2\% \pm 1.3$	$75.8\% \pm 1.4$	$79.9\% \pm 1.6$	$77.0\% \pm 1.7$	10
200%	100%	up	$79.7\% \pm 1.0$	$76.4\% \pm 1.2$	$80.8\% \pm 1.4$	$77.9\% \pm 1.4$	10
200%	150%	up	$79.7\% \pm 0.9$	$76.2\% \pm 1.1$	$80.7\% \pm 1.2$	$77.7\% \pm 1.3$	10
200%	200%	up	$79.5\% \pm 1.0$	$76.2\% \pm 1.0$	$80.1\% \pm 1.0$	$77.0\% \pm 1.1$	10
0%	100%	none	$53.3\% \pm 4.8$	$53.1\% \pm 4.6$	$48.2\% \pm 5.7$	$47.9\% \pm 5.6$	10
10%	90%	none	$75.4\% \pm 2.0$	$70.0\% \pm 2.2$	$75.1\% \pm 2.5$	$70.9\% \pm 2.5$	10
20%	80%	none	$77.2\% \pm 1.3$	$71.4\% \pm 1.9$	$77.6\% \pm 1.7$	$72.8\% \pm 1.5$	10
30%	70%	none	$78.5\% \pm 1.8$	$73.2\% \pm 2.2$	$78.3\% \pm 1.0$	$73.6\% \pm 1.0$	10
40%	60%	none	$79.1\% \pm 0.8$	$73.7\% \pm 1.2$	$79.1\% \pm 0.9$	$74.2\% \pm 1.4$	10
50%	50%	none	$79.4\% \pm 1.1$	$74.5\% \pm 1.5$	$79.8\% \pm 0.9$	$75.2\% \pm 1.3$	10
60%	40%	none	$79.5\% \pm 1.0$	$74.3\% \pm 1.2$	$80.6\% \pm 1.4$	$75.9\% \pm 1.9$	10
70%	30%	none	$79.5\% \pm 0.5$	$74.3\% \pm 0.7$	$80.6\% \pm 1.1$	$76.3\% \pm 1.3$	10
80%	20%	none	$79.6\% \pm 0.7$	$75.0\% \pm 0.8$	$81.1\% \pm 1.4$	$77.0\% \pm 1.6$	10
90%	10%	none	$79.6\% \pm 1.0$	$75.1\% \pm 1.5$	$81.2\% \pm 0.9$	$77.1\% \pm 1.3$	10
100%	0%	none	$79.4\% \pm 1.3$	$75.0\% \pm 1.3$	$80.9\% \pm 1.0$	$76.9\% \pm 1.4$	10
100%	20%	none	$79.0\% \pm 0.7$	$75.2\% \pm 1.0$ 75.0% + 1.5	$81.8\% \pm 0.8$	$78.0\% \pm 0.7$	10
100%	40%	none	$79.7\% \pm 1.1$	$75.0\% \pm 1.3$	$81.7\% \pm 1.2$	$77.0\% \pm 1.3$	10
100%	00% 800	none	$79.8\% \pm 0.7$	$75.2\% \pm 0.9$	$81.8\% \pm 1.2$	$77.9\% \pm 1.3$	10
100%	80% 1007	none	$80.3\% \pm 0.8$	$75.5\% \pm 1.1$	$81.0\% \pm 1.3$	$77.4\% \pm 1.3$	10
100%	100%	none	$00.3\% \pm 0.8$	$73.4\% \pm 1.4$ 75.1% $\pm 0.0$	$01.0\% \pm 1.1$ $81.0\% \pm 1.2$	$11.3\% \pm 1.3$ 76.8% $\pm 1.6$	10
100%	130%	none	$00.0\% \pm 0.3$	$75.1\% \pm 0.9$ 75.4% $\pm 1.1$	$01.0\% \pm 1.3$ $91.5\% \pm 1.4$	$70.8\% \pm 1.0$ 77 5% $\pm 1.7$	10
100% 200%	200% 100%	none	$00.1\% \pm 0.8$ $00.2\% \pm 1.1$	$13.4\% \pm 1.1$ 75.0% $\pm 1.2$	$01.3\% \pm 1.4$ $91.5\% \pm 1.4$	$11.3\% \pm 1.7$	10
200% 200%	100%	none	$50.3\% \pm 1.1$	$13.9\% \pm 1.3$ 75 10% $\pm 1.2$	$01.3\% \pm 1.4$ $81.0\% \pm 0.7$	$11.4\% \pm 1.7$	10
200%	130%	none	$00.0\% \pm 0.8$	$13.4\% \pm 1.3$	$01.9\% \pm 0.7$	$11.0\% \pm 0.8$	10
200%	200%	none	$80.5\% \pm 0.6$	/5.8% ± 0.8	$\delta 1.8\% \pm 0.8$	//.0% ± 0.8	10

Table 19: Development and test set results for augmenting authentic training (and development) data with Grokgenerated synthetic data (scenario 4) "Sampling" refers to the strategy for addressing class imbalance in the training data; average and standard deviation for 10 repetitions with different random seeds