WildLong: Synthesizing Realistic Long-Context Instruction Data at Scale

Jiaxi Li^{†*} Xingxing Zhang[‡] Xun Wang[‡] Xiaolong Huang[‡] Li Dong[‡] Liang Wang[‡] Si-Qing Chen[‡] Wei Lu[†] Furu Wei[‡] [†]Singapore University of Technology and Design [‡]Microsoft Research

Abstract

Large language models (LLMs) with extended context windows enable tasks requiring extensive information integration but are limited by the scarcity of highquality, diverse datasets for long-context instruction tuning. Existing data synthesis methods focus narrowly on objectives like fact retrieval and summarization, restricting their generalizability to complex, real-world tasks. WildLong extracts meta-information from real user queries, models co-occurrence relationships via graph-based methods, and employs adaptive generation to produce scalable data. It extends beyond single-document tasks to support multi-document reasoning, such as cross-document comparison and aggregation. Our models, finetuned on 150K instruction-response pairs synthesized using WildLong, surpasses existing opensource long-context-optimized models across benchmarks while maintaining strong performance on short-context tasks without incorporating supplementary shortcontext data. By generating a more diverse and realistic long-context instruction dataset. WildLong enhances LLMs' ability to generalize to complex, real-world reasoning over long contexts, establishing a new paradigm for long-context data synthesis.

1 Introduction

The growing demand for AI systems capable of processing and reasoning over extensive information has driven the development of large language models (LLMs) with significantly expanded context windows (Dubey et al., 2024; Achiam et al., 2023; Team et al., 2024). Among long-context tasks, needle-in-a-haystack (NIAH) (Kamradt, 2023) retrieval-where models locate specific information within large contexts—has emerged as a relatively simple benchmark, with previous work showing that continued pretraining on long-context data significantly boosts NIAH performance (Fu et al., 2024; Hsieh et al., 2024; Li et al., 2024c). However, while many LLMs excel at NIAH, they often struggle with more complex challenges, such as passage ranking and dialogue analysis, which require reasoning and synthesis across extended contexts (Hsieh et al., 2024; Yen et al., 2025; Zhang et al., 2024b; Levy et al., 2024; Vodrahalli et al., 2024; Li et al., 2024b). The ability to reason over long contexts is essential for real-world applications, such as legal document analysis and book review (Liu et al., 2024b; Karpinska et al., 2024; Xu et al., 2024b,c; Jimenez et al., 2024; Wang et al., 2024a). These more difficult tasks require models not only to retrieve information but also to integrate and reason over it in realistic, multi-faceted scenarios. Addressing this gap calls for high-quality, diverse, and generalized instruction-tuning datasets designed specifically for long-context reasoning. Such datasets are essential for equipping LLMs to effectively leverage their extended context capabilities in complex, real-world applications.

A major bottleneck in enhancing long-context reasoning is the lack of high-quality instruction tuning data. Unlike short-context tuning, which benefits from abundant human-annotated data, manually

Preprint.

^{*}Work done during internship at Microsoft Research.



Figure 1: Overview of the two-stage WildLong Framework. Stage 1 extracts meta-information from real-world user-chatbot conversations, classifies documents by type, constructs graphs to represent meta-information relationships, and samples paths to generate tailored instructions. Stage 2 pairs long documents from the pre-training corpus with these instructions, generating instruction-response pairs by rewriting the instructions and answering based on the document context.

constructing long-context instruction data is impractical due to the complexity of reasoning over extended contexts. Existing methods rely on data synthesis using LLMs (Dubey et al., 2024; An et al., 2024b; Bai et al., 2024; Xiong et al., 2024, 2025b). For instance, prior approaches (Xiong et al., 2024; Bai et al., 2024) generate long-context instruction-tuning data by extracting short text spans from long documents, synthesizing question-answer pairs based on these snippets, and incorporating the full document during training. Other approaches, such as Llama-3.1 (Dubey et al., 2024), further utilize hierarchical summarization to construct long-context datasets. While effective at leveraging models' short-context capabilities for data generation, these methods primarily focus on fact extraction and summarization. This narrow scope limits the diversity and generalizability of the resulting data, leaving critical gaps in supporting more complex and realistic tasks.

To address this limitation, we propose WildLong, a scalable framework for generating diverse and realistic instruction-response pairs for long-context reasoning. Our approach integrates metainformation extraction, graph-based modeling, and adaptive instruction-response generation. The pipeline of our framework is illustrated in Figure 1. We extract meta-information, such as user intents, tasks, and constraints, from real-world user-chatbot conversations. This process ensures that the generated instruction-response pairs are grounded in realistic interactions and reflect the complexity of real-world scenarios. To enhance diversity and scalability, we model the extracted metainformation as a graph, where nodes represent individual meta-information value and edges capture their co-occurrence frequencies. By performing random walks on this graph, we generate novel combinations of meta-information, introducing diverse and varied instruction templates. Adaptive instruction-response generation further supports scalability and diversity. Each combination of metainformation is paired with long-context examples sampled from the pretraining corpus, introducing variability in the contexts associated with the instructions. The availability of abundant pretraining data ensures that large-scale datasets can be generated efficiently. As shown in Figure 3, our dataset spans a wide range of document types and task types, reflecting the diversity and complexity required for real-world long-context reasoning.

We fine-tuned Mistral-7B-Instruct- $v0.2^2$ and Llama-3.1-8B-Instruct³ on 150K synthesized instructionresponse pairs and evaluated them on various long-context benchmarks with input lengths up to 128K tokens. Notably, our fine-tuned Mistral-7B model achieves a substantial +14.7 improvement on the RULER benchmark (Hsieh et al., 2024), while our Llama-3.1-8B model performed competitively with much larger models, scoring 84.1 on RULER (vs. 85.1 for Llama-3.1 70B) and 6.8 on LongBench-Chat (Bai et al., 2024) (vs. 6.7 for Llama-3.1 70B). Importantly, our fine-tuned models retain short-context performance without fine-tuning on additional short-context data, which existing

²https://huggingface.co/mistralai/Mistral-7B-Instruct-v0.2

³https://huggingface.co/meta-llama/Llama-3.1-8B-Instruct



Figure 2: This figure demonstrates examples of instructions generated from sampled paths in a narrative text graph. Solid lines represent connections within paths, while dotted lines show node interconnections during graph construction. Using a random walk algorithm, diverse instructions are generated by combining nodes. For instance, the knowledge node "understanding of narrative structure" and the context node "participation in a creative storytelling exercise" appear in multiple paths but result in distinct instructions due to varying other meta information.

methods typically use to prevent degradation. This demonstrates the robustness and generalizability of our synthetic data.

2 Proposed Method

In this section, we describe our methodology for generating diverse and realistic instruction-response pairs for long-context tasks. As shown in Figure 1, our approach comprises two main stages. In Stage 1, we extract meta-information from real-world user-chatbot conversations and construct document-type-specific graphs to model co-occurrences among meta-information. Instructions are generated by sampling paths from these graphs. In Stage 2, these instructions are paired with long documents from the pretraining corpus to create instruction-response pairs. Below, we provide an overview of each component in the framework.

2.1 Meta Information Extraction

We leverage the WildChat dataset (Zhao et al., 2024b), a large corpus of user-chatbot conversations, and focus specifically on single-turn conversations that involve long contexts. WildChat is particularly suitable for our task because it contains realistic user queries and high-quality responses, which facilitate the accurate annotation of meta information fields. From each conversation, we extract 13 fields of meta information that represent key attributes relevant to understanding and modeling long-context instructions:

document type, tasks or requests, user intention, user profile, language style, context, knowledge/commonsense involved for user, knowledge/commonsense involved for chatbot, long context capability involved, output format, sentiment, constraint of the request, simplified instruction.

These fields encompass essential aspects of the interaction, ensuring a comprehensive representation of user intent, contextual nuances, and task-specific requirements. We prompt GPT-4 to extract meta information from each conversation⁴. For example, tasks such as "extract details" for informational articles or "continue the story" for fictional narratives are explicitly labeled. Contexts like "preparing for a presentation" or "research related to ancient Greece" are extracted for professional or historical texts, respectively. The extracted meta information reflects realistic user scenarios involving long-context conversations and serves as a structured foundation for subsequent stages of our methodology.

⁴The prompt used for meta information extraction is detailed in Table 6.

2.2 Graph Construction

Instructions are generally document-type-specific, necessitating the construction of separate graphs for each document type. To build document-type-specific graphs, we first identify document types for each conversation as free-form values during the meta information extraction process. To group these values into coherent and meaningful categories, we apply K-Means clustering. The total number of clusters, set to 10, is predefined to balance between generalization and specificity based on the observed diversity of the dataset. Each cluster represents a distinct document type, and the cluster centers are rewritten to serve as the final document type labels. The distribution of the document types is illustrated in Figure 3.

For each document type d, we construct an undirected graph $G_d = (\mathbb{V}_d, E_d)$ to model the co-occurrence relationships among meta information values extracted from user-chatbot conversations⁵. This graph represents the interactions between meta information fields and facilitates the systematic exploration of realistic and diverse combinations for instruction generation. The construction process is detailed as follows.

Nodes Each node corresponds to a unique value of a meta information field. Let $\mathbb{M} = \{m_1, m_2, \dots, m_{11}\}$ denote the set of 11 meta information fields used to construct the graph (e.g., task type, sentiment, output format). The set of nodes \mathbb{V}_d is defined as:

 $\mathbb{V}_d = \{v \mid v \text{ is a value of some field } m_i \in \mathbb{M} \text{ in any conversation for document type } d\}.$

Nodes are independent of individual conversations and collectively capture all unique meta information values observed for the document type.

Edges Edges represent the co-occurrence of meta information values in the same conversation, provided they belong to different fields. Formally, an edge $(v, u) \in E_d$ exists if:

- 1. v is a value of field $m_i \in \mathbb{M}$,
- 2. *u* is a value of field $m_i \in \mathbb{M}$, where $i \neq j$, and
- 3. v and u co-occur in at least one conversation for document type d.

For each conversation, the extracted meta information values from the 11 fields are interconnected, forming a fully connected bipartite subgraph, where edges connect values from different fields.

Edge Weights The weight of an edge $(v, u) \in E_d$ reflects the frequency of co-occurrence of v and u across all conversations for document type d. The edge weight is computed as:

$$w(v, u) = \log(f_{co}(v, u) + \varepsilon),$$

where $f_{co}(v, u)$ is the raw count of co-occurrences, and ε is a small constant for numerical stability. The logarithmic scaling mitigates the influence of highly frequent pairs while preserving distinctions among lower-frequency edges.

We build document-type-specific graphs by fully connecting meta information values co-occurring in the same conversation, with edges weighted by log-scaled co-occurrence. By preserving the variety of meta information and accurately capturing their co-occurrence patterns, the graph facilitates the generation of realistic, meaningful and diverse instruction paths.

2.3 Meta Information Path Sampling

To ensure that instruction generation is guided by realistic and diverse criteria, we first sample structured combinations of meta information values. Since meta information fields interact in complex ways, manually enumerating all meaningful combinations is infeasible. Instead, we apply a weighted random walk on the document-type-specific graphs to systematically explore plausible meta information combinations. To generate sampled paths $\hat{P} = \{v_1, v_2, \ldots, v_k\}$ that represent meta information combinations, we employ a weighted random walk algorithm on G_d .

The walk begins by randomly selecting an initial node $v_1 \in \mathbb{V}_d$ from a uniformly sampled meta information category $m_c \in \mathbb{M}$. At each step t, the walk transitions from the current node v_t to a neighboring node v_{t+1} , which belongs to a different meta information category that has not yet been visited. The transition probability from v_t to v_{t+1} is determined by edge weights:

$$p(v_{t+1} \mid v_t) = \frac{\exp(w(v_t, v_{t+1}))}{\sum_{v_k \in \mathcal{N}(v_t)} \exp(w(v_t, v_k))},$$
(1)

⁵Eleven meta information fields are used to construct the graph. The "document type" field is used to classify documents such that we can construct a separate graph for each document type. The "simplified instruction" field is used as a demonstration when generating instructions based on paths, see Section 2.4.

where $w(v_t, v_{t+1})$ is the weight of the edge between v_t and v_{t+1} , and $\mathcal{N}(v_t)$ is the set of neighbors of v_t . The walk continues for up to N steps, producing a path that spans N distinct meta information fields. Based on our preliminary experiments on instruction synthesis, we determined that N = 6 strikes the right balance: larger values of N introduce overly restrictive criteria, making instruction generation challenging and prone to producing convoluted instructions joined by "and" to satisfy all requirements. Conversely, smaller values of N result in overly simple instructions with limited complexity. The limit of six meta information fields provides sufficient criteria to guide instruction generation while allowing the model to flexibly incorporate other relevant meta information creatively. By leveraging edge weights to guide transitions, the algorithm captures realistic co-occurrence patterns, enabling the scalable synthesis of diverse instruction templates, while maintaining flexibility to explore less frequent connections. These paths serve as structured templates to generate diverse and representative instructions for long-context tasks.

2.4 Instruction Generation with Sampled Paths

To synthesize instructions aligned with the sampled meta-information paths, we prompt GPT-4 with a one-shot demonstration. GPT-4 generates natural language instructions that follow the criteria defined by the meta information fields in the sampled path⁶. Figure 2 illustrates instructions generated from sampled paths in a narrative text graph. Using the random walk algorithm, diverse instructions emerge by combining different meta information values. For example, two paths may share "understanding of narrative structure" as the "knowledge involved for chatbot" field but differ in others. One path, with values like "detailed language style" and "literature research purpose," guides an instruction for analyzing plot development. Another, with "entertainment purpose" and "emotional sentiment," leads to an instruction for crafting a heartfelt monologue.

2.5 Instruction-Response Pair Generation





Figure 3: Distribution of document types (inner circle) and task types (outer circle) in our dataset.

of long documents makes it well-suited for tasks requiring extensive context. As instructions are document-type-specific, we first classify sampled documents into one of ten predefined document types using a custom classifier⁸.

To ensure the paired documents reflect realistic user needs for long-context capabilities, we resample SlimPajama's long documents to align their document type distribution with that of WildChat long conversations. This adjustment ensures the data distribution is representative of how users typically query about long contexts. Once the document types are predicted, we pair each document with an instruction generated from the graph corresponding to its type. To make the instructions more contextually grounded, the sampled instruction and paired document are provided as input to GPT-4, which generates an adapted instruction aligned with the document, and a corresponding response⁹. This ensures the final instruction-response pairs are coherent, relevant, and reflective of the document's context.

2.6 Extending Instructions to Multi-Document Settings

We observe that the filtered WildChat dataset predominantly contains instructions designed only for singledocument contexts, with limited coverage of multi-document tasks. To address this gap, we extend our method to generate instructions suitable for multi-document settings by adapting the extracted meta information and graph-based framework.

The extension begins with adapting the "tasks or requests" field in the meta information to reflect multi-document requirements while keeping other fields unchanged. Each single-document task node is rewritten to explicitly

⁶Details about how to select the demonstration can be found in Appendix A.2 and the prompt can be found in Table 7 in Appendix C.

⁷SlimPajama is an open-source reproduction of the LLaMA pretraining data mixture (Touvron et al., 2023).

⁸Details about the classifier are provided in Appendix A.1.

⁹Details about the prompt can be found in Table 8 in Appendix C.

involve handling information across multiple documents using GPT-4. For instance, a task like "Summarize the key points of the document" is transformed into "Summarize and compare the key points across multiple documents."¹⁰

Following this adaptation, we construct document-type-specific graphs for multi-document tasks, sample paths using the same random walk algorithm, and generate instructions based on the sampled paths. The steps for graph construction, path sampling, and instruction synthesis remain largely consistent with the single-document setting. During the document-instruction pairing stage, we sample pairs of documents of the same type from the SlimPajama dataset, concatenate them, and pair the concatenated documents with a multi-document instruction of the same type. The concatenated documents and their paired instruction are then input to GPT-4 to generate a refined, contextually aligned instruction and a corresponding response. By integrating these modifications, our method systematically generates instructions and responses that support multi-document reasoning tasks.

3 Experiments

We evaluate our framework comprehensively on both long-context and short-context benchmarks. This section outlines implementation details, compares our method with baseline pretrained and specialized long-context optimized models, benchmarks against existing long-context supervised fine-tuning (SFT) datasets, and presents ablation studies to analyze the contributions of essential components in our framework.

3.1 Implementation Details

Data Curation We filter single-turn WildChat conversations exceeding 2K tokens, yielding 32K instances. We then filter long-context documents from the SlimPajama corpus into two subsets: single-document (2K–30K tokens) and multi-document (2K–20K tokens). For multi-document, we pair two same-type documents and concatenate them. We sample 100K single-document and 50K multi-document examples, totaling 150K samples.

Training Details. We fine-tune Mistral-7B-Instruct-v0.2 and Llama-3.1-8B-Instruct using our curated dataset. For Mistral-7B-Instruct-v0.2, we adjust the RoPE base from 1e6 to 1e7 to support longer positional embeddings¹¹. Both models are optimized using the Adam optimizer, with learning rates of 1e-6 and 5e-7 respectively. Training is conducted for 2 epochs with a batch size of 512^{12} .

3.2 Baselines

Proprietary Long-Context Models. We include two proprietary long-context models Gemini-1.5-Pro and GPT-4 as upper bounds due to their strong performance on long-context tasks.

Open-Sourced Pretrained Long-Context Models. Additionally, we evaluate open-source pretrained language models with long-context capabilities, including GLM4-9B (GLM et al., 2024), Yi-34B (AI et al., 2024), Llama3.1-70B (Dubey et al., 2024), Phi-3-medium (Abdin et al., 2024), and Qwen2.5 (Yang et al., 2024).

Specialized Long-Context Optimized Models. We compare our approach to specialized long-context LLMs that extend or optimize model capabilities for long inputs. FILM (An et al., 2024b) and ChatQA-2 (Xu et al., 2025) fine-tunes Mistral-7B-Instruct-v0.2 and Llama-3-8B with synthetic long-context QA pairs. SEALONG (Li et al., 2024d) applies preference optimization on Llama-3.1-8B-Instruct with extended-context QA pairs, while ProLong (Gao et al., 2024b) continue-pretrain Llama-3-8B-Instruct to 512K context window and finetune with short-context data.

Prior Long-Context SFT Data. We fine-tune Llama-3.1 on open-source long-context instruction-tuning datasets. LongAlpaca (Chen et al., 2024b) comprises 9K curated long QA pairs and 3K short QA pairs, covering tasks such as book questions and summarization. LongAlign (Bai et al., 2024) includes QA pairs generated by Claude 2.1 from extended documents, while LongReward (Zhang et al., 2024a) similarly uses GLM4 to produce long-context QA pairs via a self-instruct framework.

3.3 Evaluation Benchmarks

To comprehensively evaluate the performance of our model, we assess both long-context and short-context capabilities. For long-context tasks, we benchmark our model against established baselines, whereas for short-context tasks, we compare its performance with the base model used for fine-tuning.

¹⁰The rewriting prompt is shown in Table 9. The modifications emphasize the need for synthesis, comparison, or aggregation across documents while preserving coherence and relevance.

¹¹Increasing RoPE base supports longer context. More details can be seen in Appendix B.

¹²More details about computational budget and and infrastructure can be found in Appendix A.

Table 1: Main evaluation results of our models on RULER, HELMET and Longbench-Chat compared with baselines. Results on RULER and HELMET are averaged over sequence lengths ranging from 4K to 128K and 8K to 128K respectively.

Madala	Size	RULER			HELMET					Long				
widdels		NIAH	VT	Agg	QA	Avg	RAG	ICL	Cite	Rank	QA	Summ	Avg	Chat
Proprietary Long-Context Models														
Gemini-1.5-Pro	-	99.7	99.9	96.6	77.2	93.4	72.1	78.8	44.5	69.0	47.6	38.5	58.4	7.6
GPT-4	-	95.4	99.9	93.4	70.3	89.8	70.6	65.1	24.9	53.4	47.7	32.6	49.1	8.4
Open-Sourced Pretrained Long-Context Models														
GLM-4-1M	9B	98.2	99.4	72.2	69.4	84.8	67.9	77.3	31.4	41.7	44.2	28.8	48.6	5.9
Yi-200k	34B	95.1	93.6	74.3	67.1	82.5	64.1	78.6	4.8	33.4	25.1	12.2	36.4	4.0
Llama-3.1	70B	96.1	93.2	83.3	67.8	85.1	68.6	77.2	32.9	52.2	46.0	33.3	51.7	6.7
Phi-3-medium	14B	88.7	76.5	77.4	59.3	75.5	58.9	67.0	17.1	23.9	22.4	26.6	36.0	5.2
Qwen2.5	7B	83.3	81.7	73.2	57.0	73.8	53.1	75.8	17.7	31.2	28.4	28.1	39.1	5.8
Specialized Long-Context Optimized Models														
FILM	7B	81.7	92.8	64.9	63.0	75.6	52.6	78.0	6.4	28.0	26.9	22.1	35.7	4.9
ProLong-512k	8B	98.5	97.8	69.4	65.5	82.8	67.2	76.4	14.4	39.1	36.7	25.9	43.3	5.9
ChatQA-2	8B	97.1	98.1	66.8	53.6	78.9	63.2	81.3	2.9	23.7	36.2	13.9	36.9	3.7
SEALONG	8B	98.4	91.0	66.6	66.1	80.5	64.9	78.5	19.6	45.0	36.2	30.1	45.7	6.6
Mistral	7B	72.6	74.4	64.4	52.2	65.9	47.1	63.6	8.2	25.0	19.2	20.3	30.6	4.5
+ WildLong	7B	95.2	95.9	67.0	64.2	80.6	62.1	74.6	12.4	34.3	34.4	29.2	41.2	6.3
LLaMA 3.1	8B	98.1	91.6	66.2	66.1	80.5	66.1	77.4	18.5	39.0	37.1	28.0	44.5	6.2
+ WildLong	8B	98.7	95.7	74.3	67.9	84.1	67.6	78.8	22.6	40.8	38.5	30.8	46.5	6.8

For long-context tasks, we use three benchmarks designed to test a wide range of capabilities across varying input lengths:

RULER (Hsieh et al., 2024). This benchmark evaluates four synthetic task types across input lengths ranging from 4K to 128K tokens, including Needle-in-a-haystack (NIAH) retrieval, Multi-hop Tracing with Variable Tracking (VT), Aggregation (Agg), and Question Answering (QA).

HELMET (Yen et al., 2025). We evaluate our model on six tasks from HELMET: Retrieval-augmented generation (RAG), Generation with citations (Cite), Passage re-ranking (Re-rank), Long-document question answering (LongQA), Summarization (Summ), and Many-short in-context learning (ICL). The Recall task is excluded due to its overlap with the synthetic NIAH task in RULER.

Longbench-Chat (Bai et al., 2024). This benchmark tests instruction-following abilities over long contexts (10K to 100K tokens) using real-world queries. It includes 40 queries in English and 10 in Chinese. GPT-4-128K serves as an impartial judge to evaluate model-generated responses.

For short-context tasks, we assess general language understanding and reasoning using MMLU (Hendrycks et al., 2021), Winogrande (Sakaguchi et al., 2020), ARC-C (Clark et al., 2018), and GSM8K (Cobbe et al., 2021), and evaluate instruction-following capabilities with IFEval¹³ (Zhou et al., 2023).

3.4 Results

Our finetuned models demonstrates strong performance over established models. We significantly improve upon our baseline models, with Mistral-7B gaining +14.7 and +10.6 points on RULER and HELMET, and Llama-3.1-8B gaining +3.6 and +2.0. Against open-source long-context models, our Llama-3.1-8B matches or exceeds larger alternatives. Notably on LongBench-Chat, our Llama-3.1-8B model outperforms most established models except for proprietary ones. We also outperform specialized long-context methods. Despite using ten times more data, FILM scores lower than our Mistral-7B (e.g., 75.6 vs. 80.6 on RULER). SEALONG, based on Llama-3.1-8B-Instruct achieves lower scores, with an 8-point deficit on RULER compared with our Llama-based model. ProLong and ChatQA-2 perform well on synthetic tasks but struggle with real-world queries and complex tasks. These results highlight the effectiveness of our framework.

Our method enhances performance compared to other long-context instruction-tuning data. We compare our method with previous long-context instruction-tuning datasets, including LongAlpaca, LongAlign and LongReward. We finetune Llama-3.1-8b-instruct with all these datasets with the same hyperparameters. As demonstrated in Table 2, these datasets yield only slight improvements, with scores of 81.4, 81.9, and 81.2 on RULER, respectively. In contrast, our method significantly improves performance across all tasks, achieving an average

¹³Details on evaluation settings are in Appendix A.3.



Figure 4: Comparison of short-context performances between finetuned and the baseline models. Models fine-tuned with our method preserve short-context capabilities.

score of 84.1 on RULER. The substantial improvements in aggregation tasks, which involve integrating multiple relevant details, can likely be attributed to our dataset's focus on detail-oriented summarization and information synthesis, as illustrated in Figure 3. This broad coverage appears to better equip models for complex long-context reasoning. This suggests our dataset's diversity better equips models for complex reasoning and aggregation tasks.

Short context performance is preserved without mixing short-context data. Previous works (An et al., 2024b; Bai et al., 2024; Zhang et al., 2024a) mix short-context instruction-tuning data into the fine-tuning data to mitigate degradation in short-context capabilities after long-context alignment. In contrast, our approach exclusively employs long-context data while effectively preserving short-context performance. Referring to Figure 4, we maintain an average score of 75.9 for Llama-3.1-8B, comparable to the baseline 75.8. For Mistral-7B, we observe a slight drop of less than one point, potentially due to changes in RoPE base. We analyze this further in Section 3.5.

Table 2: Performance comparison of Llama-3.1-8B-instruct fine-tuned with various long-context instruction-tuning datasets.

Madala	RULER						
wiodels	NIAH	VT	Agg	QA	Avg		
LongAlpaca	97.9	95.2	67.0	65.4	81.4		
LongAlign	98.5	94.8	65.7	68.5	81.9		
LongReward	98.4	94.2	65.6	66.7	81.2		
WildLong	98.7	95.7	74.3	67.9	84.1		

These results underscore the effectiveness of our dataset: finetuning on general, realistic long-context data significantly enhances long-context capabilities while largely preserving short-context performance without additional data mixing.

3.5 Ablation Studies

We conduct comprehensive ablation studies to investigate the efficacy of our data synthesis framework.

Effectiveness of graph-based modeling. To evaluate the effectiveness of our graph-based instruction generation approach, we compare it against two baseline methods for synthesizing long-context instructiontuning datasets, using 20k samples for each setting. The first baseline, denoted as simple-instruct, directly extracts instructions from user-chat conversations in WildChat and pairs them with long documents sampled from SlimPajama. The second baseline, denoted as WildChat-long, finetunes directly on samples from the filtered long WildChat subset. We finetune both Mistral-7B-Instruct-v0.2 and Llama-3.1-8binstruct using these three datasets and evaluated them on the RULER benchmark. As shown in Table 3, our graph-based method consistently outperforms the baselines. In particular, Mistral-7B achieves a score of 78 with WildLong, outperforming WildChat-Long



Figure 5: Short-context and long-context performance of variations of Mistral models.

and Simple-Instruct by +5 and +3.8 points. We suspect the improved performance, particularly on complex tasks like aggregation and variable tracking, arises from the graph-based method's ability to generate more diverse and challenging instructions while preserving generalizability.

Effectiveness of multi-document data. We assess the impact of multi-document data by fine-tuning both Mistral and Llama models on 20k datasets across three settings: single-document, multi-document, and a mix of both. As shown in Table 4, the results reveal varying effects depending on the model and task. For the Mistral models, the multi-document setting significantly enhances performance on tasks requiring complex reasoning, such as variable tracking (VT) and aggregation (Agg). In contrast, single-document data proves more effective for QA tasks, which focus on extracting specific information from a single source. For the Llama models, the effect of multi-document data is less pronounced. The multi-document setting. However, the mixed setting achieves the highest performance on variable tracking (93.7 vs. 93.0 for both single and multi) and matches the single-document setting in overall average performance (82.6). These findings suggest that while single-document and multi-document data have distinct strengths, combining them provides greater diversity and balance, enabling models to perform robustly across a wide range of tasks.

Effectiveness of WildLong under RoPE Scaling. We investigate the impact of modifying the RoPE base parameter to extend the context length of the Mistral-7B model. Specifically, we compare three variants: (1) Mistral-7B (Baseline): The original model with context length 32k and RoPE base 1e6, (2) Mistral-7B (RoPE 1e7): Extended RoPE base of 1e7, and (3) Mistral-7B (Ours): RoPE base 1e7, finetuned with our WildLong data. Performance is evaluated on short-context tasks (<1k) and long-context tasks (4k-128k).

The length-wise performance is shown in Figure 5. Our results reveal that increasing the RoPE base parameter enables support for longer contexts, improving performance on tasks requiring extreme context lengths (e.g., 64k-128k, +18.6 and +32.7 points over the baseline Mistral-7B respectively). However, this adjustment comes with a significant trade-off, as short-context performance drops markedly from 58.2 to 55.0, and performance on mid-range context lengths (4k-8k) also slightly declines. Finetuning with WildLong mitigates these trade-offs, recovering short-context performance to 57.4 while further boosting mid- and long-context performance. This analysis highlights that while extending RoPE theta directly allows models to process longer contexts, it introduces a clear trade-off in short-context capability. Finetuning with generalized long-context datasets, such as Wildlong, not only recovers some short-context degradation but also enhances performance across mid-range and extended contexts. These findings address a gap in prior research and emphasize the importance of finetuning strategies to balance short- and long-context performance effectively.

Table 3: Effect of graph-based modeling adopted by WildLong compared with two baseline methods.

Table 4:	Performance	comparison	among
single-doo	cument, multi-c	locument, and	d a mix-
ture of sir	gle- and multi	-document da	ata.

	Deteret	RULER					
Wiodei	Dataset	NIAH	VT	Agg	QA	Avg	
	WildChat-long	87.7	84.2	59.9	60.3	73.0	
Mistral	Simple Instruct	89.5	90.2	52.6	64.3	74.2	
	WildLong	91.4	92.0	64.7	63.9	78.0	
	WildChat-long	98.2	93.5	69.3	67.7	82.2	
LLaMA	Simple Instruct	98.5	94.1	67.6	68.7	82.2	
	WildLong	98.9	93.7	70.0	67.7	82.6	

Madal	Deterrt	RULER						
Model	Dataset	NIAH	VT	Agg	QA	Avg		
	Single	91.6	90.9	63.9	64.2	77.7		
Mistral	Multi	92.1	94.4	66.9	64.1	79.4		
	WildLong	91.4	92.0	64.7	63.9	78.0		
	Single	98.6	93.0	70.5	68.2	82.6		
LLaMA	Multi	98.8	93.0	69.3	67.0	82.0		
	WildLong	98.9	93.7	70.0	67.7	82.6		

4 Related Work

Long-context Extending of LLMs. Several methods attempt to extend context windows with minimal training overhead. Position extrapolation approaches (Chen et al. (2023); Peng et al. (2024); Su et al. (2021); Ding et al. (2024); Chen et al. (2024a); Liu et al. (2024a); Zhu et al. (2024); Wu et al. (2024); Hu et al. (2024)) adjust positional embeddings or apply rope-based techniques to accommodate longer inputs. Others manipulate attention mechanisms to scale context length (Jin et al. (2024); Xiao et al. (2024b,a); Ding et al. (2023); An et al. (2024a, 2025)), ensuring model capacity for extended sequences without complete retraining. A separate line of work focuses on novel architectures designed for efficient long-context modeling. These include methods like Jamba (Lieber et al. (2024)). Unlimiformer (Bertsch et al. (2024)), and other enhancements (Wang et al. (2024b); Yen et al. (2024)) to handle large inputs without quadratic complexity scaling. Some methods rely on significant resources to equip LLMs with long-context capabilities. Llama3.1 (Dubey et al. (2024)) conducts extensive continued pretraining on 800B tokens plus targeted fine-tuning on long-context data, and GLM (GLM et al. (2024)) uses human-annotated datasets for supervised fine-tuning and DPO. While effective, these strategies can be labor-intensive or costly. To mitigate data constraints, synthetic long-context datasets have been explored. For instance, An et al. (2024b) synthesizes QA for short context and concatenates short contexts to form long contexts, while Zhao et al. (2024a) synthesizes long tables to improve long-context reasoning. Xu et al. (2025) uses NarrativeQA to construct long contexts by combining semantically related paragraphs, offering task-specific solutions. Structured approaches have targeted specific long-context tasks. Chen et al. (2024c) model document correlations to curate multi-hop datasets and generate QA pairs from intra-document data. Bai et al. (2024) leverage Self-Instruct to create long-context instruction datasets but restrict prompts to four task types, limiting

task generalization. Xiong et al. (2025a) trains the model on synthetic key-value retrieval data to improve multi-document reasoning. These methods show promise but often remain narrow in focus or require substantial manual or computational effort. Recent approaches like LongPO (Chen et al., 2025) and SEALONG (Li et al., 2024d) have shown that LLMs can self-improve on long-context tasks, particularly in contextual QA. LongPO extends short-context capabilities to long contexts through self-generated preference data, while SEALONG uses multiple output sampling and preference optimization to refine model responses. However, these methods focus primarily on QA tasks and do not address the broader range of challenges requiring full-context reasoning. Our approach, WildLong, is orthogonal to these methods, offering a scalable way to generate generalized data for diverse long-context tasks.

Scaling synthetic data creation Previous work on synthetic data creation for alignment has focused on leveraging human interactions with LLMs (Conover et al., 2023; Zhao et al., 2024b; Zheng et al., 2024; Köpf et al., 2023). However, manually crafting instructions is time-consuming and labor-intensive. Recent approaches have scaled instruction datasets by prompting LLMs to generate synthetic instructions, starting with a small set of human-annotated seed instructions (Yu et al., 2024; Wang et al., 2023; Taori et al., 2023; Xu et al., 2024a; Sun et al., 2024). Keypoints-driven strategies (Li et al. (2024a); Tang et al. (2024); Huang et al. (2024)) enrich prompts with diverse topics or knowledge bases. PersonaHub Ge et al. (2024) introduces billions of personas to maximize coverage. We follow this keypoints-driven philosophy but focus on long-context data synthesis, extracting meta-information from real-world conversations to generate diverse, realistic instructions closely tied to document context. By integrating document type–specific details, our framework provides a scalable route for creating high-quality long-context training data without excessive manual overhead.

5 Conclusion

We propose WildLong, a framework for synthesizing diverse, scalable, and realistic instruction-response datasets for long-context tasks. It integrates meta-information extraction to ensure realistic complexity, graph-based modeling for systematic instruction expansion, and adaptive instruction generation for enhanced contextual relevance. Our fine-tuned models consistently outperform baselines and maintain short-context performance without mixing short-context data. Notably, our finetuned Llama-3.1-8B model surpasses most open-source long-context models on Longbench-Chat and demonstrates competitive performances with even larger models caross benchmarks. WildLong enables the synthesis of instruction-tuning data that produces robust models capable of handling diverse long-context tasks. Extending beyond synthetic QA and summarization, it bridges the gap to more complex, realistic challenges, advancing the effectiveness of long-context LLMs. We hope WildLong provides insights into generalizing synthetic data and inspires further progress in long-context reasoning for LLMs.

6 Limitations

While WildLong advances synthetic data generation for long-context tasks, several limitations warrant consideration. First, although the framework mimics "realistic" instruction-response pairs, synthetic data may lack the nuanced complexity, ambiguity, or cultural specificity inherent in human-generated interactions. This could limit the model's ability to handle edge cases or interpret context-dependent subtleties in real-world scenarios. Second, biases embedded in the source meta-information extracted from real user queries—such as language preferences, cultural assumptions, or domain-specific imbalances—risk propagating into the generated dataset, potentially reinforcing societal or structural inequities. Finally, while graph-based modeling captures co-occurrence relationships between entities, it may oversimplify semantic or causal dependencies, leading to superficial multi-document reasoning. These limitations highlight the need for hybrid data pipelines combining synthetic and human-curated examples, alongside rigorous bias audits, to enhance robustness.

References

Marah Abdin, Jyoti Aneja, Hany Awadalla, Ahmed Awadallah, Ammar Ahmad Awan, Nguyen Bach, Amit Bahree, Arash Bakhtiari, Jianmin Bao, Harkirat Behl, Alon Benhaim, Misha Bilenko, Johan Bjorck, Sébastien Bubeck, Martin Cai, Qin Cai, Vishrav Chaudhary, Dong Chen, Dongdong Chen, Weizhu Chen, Yen-Chun Chen, Yi-Ling Chen, Hao Cheng, Parul Chopra, Xiyang Dai, Matthew Dixon, Ronen Eldan, Victor Fragoso, Jianfeng Gao, Mei Gao, Min Gao, Amit Garg, Allie Del Giorno, Abhishek Goswami, Suriya Gunasekar, Emman Haider, Junheng Hao, Russell J. Hewett, Wenxiang Hu, Jamie Huynh, Dan Iter, Sam Ade Jacobs, Mojan Javaheripi, Xin Jin, Nikos Karampatziakis, Piero Kauffmann, Mahoud Khademi, Dongwoo Kim, Young Jin Kim, Lev Kurilenko, James R. Lee, Yin Tat Lee, Yuanzhi Li, Yunsheng Li, Chen Liang, Lars Liden, Xihui Lin, Zeqi Lin, Ce Liu, Liyuan Liu, Mengchen Liu, Weishung Liu, Xiaodong Liu, Chong Luo, Piyush Madan, Ali Mahmoudzadeh, David Majercak, Matt Mazzola, Caio César Teodoro Mendes, Arindam Mitra, Hardik Modi, Anh Nguyen, Brandon Norick, Barun Patra, Daniel Perez-Becker, Thomas Portet, Reid Pryzant, Heyang Qin, Marko Radmilac, Liliang Ren, Gustavo de Rosa, Corby Rosset, Sambudha Roy, Olatunji Ruwase, Olli Saarikivi, Amin Saied, Adil Salim, Michael Santacroce, Shital Shah, Ning Shang, Hiteshi Sharma, Yelong Shen, Swadheen Shukla, Xia Song, Masahiro Tanaka, Andrea Tupini, Praneetha Vaddamanu, Chunyu Wang, Guanhua Wang, Lijuan Wang, Shuohang Wang, Xin Wang, Yu Wang, Rachel Ward, Wen Wen, Philipp Witte, Haiping Wu, Xiaoxia Wu, Michael Wyatt, Bin Xiao, Can Xu, Jiahang Xu, Weijian Xu, Jilong Xue, Sonali Yadav, Fan Yang, Jianwei Yang, Yifan Yang, Ziyi Yang, Donghan Yu, Lu Yuan, Chenruidong Zhang, Cyril Zhang, Jianwen Zhang, Li Lyna Zhang, Yi Zhang, Yue Zhang, Yunan Zhang, and Xiren Zhou. Phi-3 technical report: A highly capable language model locally on your phone, 2024. URL https://arxiv.org/abs/2404.14219.

- Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023. URL https://arxiv.org/abs/2303.08774.
- 01. AI, :, Alex Young, Bei Chen, Chao Li, Chengen Huang, Ge Zhang, Guanwei Zhang, Heng Li, Jiangcheng Zhu, Jianqun Chen, Jing Chang, Kaidong Yu, Peng Liu, Qiang Liu, Shawn Yue, Senbin Yang, Shiming Yang, Tao Yu, Wen Xie, Wenhao Huang, Xiaohui Hu, Xiaoyi Ren, Xinyao Niu, Pengcheng Nie, Yuchi Xu, Yudong Liu, Yue Wang, Yuxuan Cai, Zhenyu Gu, Zhiyuan Liu, and Zonghong Dai. Yi: Open foundation models by 01.ai, 2024. URL https://arxiv.org/abs/2403.04652.
- Chenxin An, Fei Huang, Jun Zhang, Shansan Gong, Xipeng Qiu, Chang Zhou, and Lingpeng Kong. Training-free long-context scaling of large language models. In *Proceedings of ICML*, 2024a. URL https://arxiv.org/abs/2402.17463.
- Chenxin An, Jun Zhang, Ming Zhong, Lei Li, Shansan Gong, Yao Luo, Jingjing Xu, and Lingpeng Kong. Why does the effective context length of LLMs fall short? In *Proceedings of ICLR*, 2025. URL https: //openreview.net/forum?id=eoln5WgrPx.
- Shengnan An, Zexiong Ma, Zeqi Lin, Nanning Zheng, Jian-Guang Lou, and Weizhu Chen. Make your LLM fully utilize the context. In *Proceedings of NeurIPS*, 2024b. URL https://openreview.net/forum?id=YGTVEmBXtV.
- Yushi Bai, Xin Lv, Jiajie Zhang, Yuze He, Ji Qi, Lei Hou, Jie Tang, Yuxiao Dong, and Juanzi Li. LongAlign: A recipe for long context alignment of large language models. In *Findings of EMNLP*, 2024. doi: 10.18653/v1/ 2024.findings-emnlp.74. URL https://aclanthology.org/2024.findings-emnlp.74/.
- Edward Beeching, Clémentine Fourrier, Nathan Habib, Sheon Han, Nathan Lambert, Nazneen Rajani, Omar Sanseviero, Lewis Tunstall, and Thomas Wolf. Open Ilm leaderboard. https://huggingface.co/spaces/open-llm-leaderboard-old/open_llm_leaderboard, 2023.
- Marco Bellagente, Jonathan Tow, Dakota Mahan, Duy Phung, Maksym Zhuravinskyi, Reshinth Adithyan, James Baicoianu, Ben Brooks, Nathan Cooper, Ashish Datta, et al. Stable Im 2 1.6 b technical report. *arXiv preprint arXiv:2402.17834*, 2024. URL https://arxiv.org/abs/2402.17834.
- Amanda Bertsch, Uri Alon, Graham Neubig, and Matthew Gormley. Unlimiformer: Long-range transformers with unlimited length input. In *Proceedings of NeurIPS*, 2024. URL https://openreview.net/forum? id=lJWUJWLCJo¬eId=CJ00EonS46.
- bloc97. Ntk-aware scaled rope allows llama models to have extended (8k+) context size without any fine-tuning and minimal perplexity degradation, 2023. URL https://www.reddit.com/r/LocalLLaMA/comments/ 14lz7j5/ntkaware_scaled_rope_allows_llama_models_to_have/.
- Guanzheng Chen, Xin Li, Zaiqiao Meng, Shangsong Liang, and Lidong Bing. CLEX: Continuous length extrapolation for large language models. In *Proceedings of ICLR*, 2024a. URL https://openreview.net/forum?id=wXpSidPpc5.
- Guanzheng Chen, Xin Li, Michael Shieh, and Lidong Bing. LongPO: Long context self-evolution of large language models through short-to-long preference optimization. In *Proceedings of ICLR*, 2025. URL https://openreview.net/forum?id=qTrEq31Shm.
- Shouyuan Chen, Sherman Wong, Liangjian Chen, and Yuandong Tian. Extending context window of large language models via positional interpolation. *arXiv preprint arXiv:2306.15595*, 2023. URL https://arxiv.org/pdf/2306.15595.
- Yukang Chen, Shengju Qian, Haotian Tang, Xin Lai, Zhijian Liu, Song Han, and Jiaya Jia. Longlora: Efficient fine-tuning of long-context large language models. In *Proceedings of ICLR*, 2024b. URL https://openreview.net/forum?id=6PmJoRfdaK.

- Zhi Chen, Qiguang Chen, Libo Qin, Qipeng Guo, Haijun Lv, Yicheng Zou, Wanxiang Che, Hang Yan, Kai Chen, and Dahua Lin. What are the essential factors in crafting effective long context multi-hop instruction datasets? insights and best practices. arXiv preprint arXiv:2409.01893, 2024c. URL https://arxiv.org/abs/2409.01893.
- Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. Think you have solved question answering? try arc, the ai2 reasoning challenge. *arXiv preprint arXiv:1803.05457*, 2018. URL https://arxiv.org/abs/1803.05457.
- Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. Training verifiers to solve math word problems. arXiv preprint arXiv:2110.14168, 2021. URL https://arxiv.org/abs/2110. 14168.
- Mike Conover, Matt Hayes, Ankit Mathur, Jianwei Xie, Jun Wan, Sam Shah, Ali Ghodsi, Patrick Wendell, Matei Zaharia, and Reynold Xin. Free dolly: Introducing the world's first truly open instruction-tuned llm, 2023. URL https://www.databricks.com/blog/2023/04/12/ dolly-first-open-commercially-viable-instruction-tuned-llm.
- Tri Dao. FlashAttention-2: Faster attention with better parallelism and work partitioning. In *Proceedings of ICLR*, 2024.
- Jiayu Ding, Shuming Ma, Li Dong, Xingxing Zhang, Shaohan Huang, Wenhui Wang, and Furu Wei. Longnet: Scaling transformers to 1,000,000,000 tokens. In *Proceedings of ICLR*, 2023. URL https://arxiv.org/ abs/2307.02486.
- Yiran Ding, Li Lyna Zhang, Chengruidong Zhang, Yuanyuan Xu, Ning Shang, Jiahang Xu, Fan Yang, and Mao Yang. Longrope: Extending llm context window beyond 2 million tokens. In *Proceedings of ICLR*, 2024. URL https://arxiv.org/abs/2402.13753.
- Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024. URL https://arxiv.org/abs/2407.21783.
- Yao Fu, Rameswar Panda, Xinyao Niu, Xiang Yue, Hannaneh Hajishirzi, Yoon Kim, and Hao Peng. Data engineering for scaling language models to 128k context. In *Proceedings of ICML*, 2024. URL https://arxiv.org/abs/2402.10171.
- Leo Gao, Jonathan Tow, Baber Abbasi, Stella Biderman, Sid Black, Anthony DiPofi, Charles Foster, Laurence Golding, Jeffrey Hsu, Alain Le Noac'h, Haonan Li, Kyle McDonell, Niklas Muennighoff, Chris Ociepa, Jason Phang, Laria Reynolds, Hailey Schoelkopf, Aviya Skowron, Lintang Sutawika, Eric Tang, Anish Thite, Ben Wang, Kevin Wang, and Andy Zou. A framework for few-shot language model evaluation, 2024a. URL https://zenodo.org/records/12608602.
- Tianyu Gao, Alexander Wettig, Howard Yen, and Danqi Chen. How to train long-context language models (effectively), 2024b. URL https://arxiv.org/abs/2410.02660.
- Tao Ge, Xin Chan, Xiaoyang Wang, Dian Yu, Haitao Mi, and Dong Yu. Scaling synthetic data creation with 1,000,000,000 personas. *arXiv preprint arXiv:2406.20094*, 2024. URL https://arxiv.org/abs/2406. 20094.
- Team GLM, Aohan Zeng, Bin Xu, Bowen Wang, Chenhui Zhang, Da Yin, Dan Zhang, Diego Rojas, Guanyu Feng, Hanlin Zhao, et al. Chatglm: A family of large language models from glm-130b to glm-4 all tools. arXiv preprint arXiv:2406.12793, 2024. URL https://arxiv.org/abs/2406.12793.
- Wenhan Xiong Grattafiori, Alexandre Défossez, Jade Copet, Faisal Azhar, Hugo Touvron, Louis Martin, Nicolas Usunier, Thomas Scialom, and Gabriel Synnaeve. Code llama: Open foundation models for code. arXiv preprint arXiv:2308.12950, 2023.
- Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. In *Proceedings of ICLR*, 2021. URL https://openreview.net/forum?id=d7KBjmI3GmQ.
- Cheng-Ping Hsieh, Simeng Sun, Samuel Kriman, Shantanu Acharya, Dima Rekesh, Fei Jia, and Boris Ginsburg. RULER: What's the real context size of your long-context language models? In *Proceedings of COLM*, 2024. URL https://arxiv.org/abs/2404.06654.

- Zhiyuan Hu, Yuliang Liu, Jinman Zhao, Suyuchen Wang, Yan Wang, Wei Shen, Qing Gu, Anh Tuan Luu, See-Kiong Ng, Zhiwei Jiang, and Bryan Hooi. Longrecipe: Recipe for efficient long context generalization in large language models. *CoRR*, 2024. URL https://doi.org/10.48550/arXiv.2409.00509.
- Yiming Huang, Xiao Liu, Yeyun Gong, Zhibin Gou, Yelong Shen, Nan Duan, and Weizhu Chen. Key-pointdriven data synthesis with its enhancement on mathematical reasoning. arXiv preprint arXiv:2403.02333, 2024. URL https://arxiv.org/abs/2403.02333.
- Carlos E Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik R Narasimhan. SWE-bench: Can language models resolve real-world github issues? In *Proceedings of ICLR*, 2024. URL https://openreview.net/forum?id=VTF8yNQM66.
- Hongye Jin, Xiaotian Han, Jingfeng Yang, Zhimeng Jiang, Zirui Liu, Chia-Yuan Chang, Huiyuan Chen, and Xia Hu. Llm maybe longlm: Selfextend llm context window without tuning. In *Proceedings of ICML*, 2024. URL https://arxiv.org/abs/2401.01325.
- Gregory Kamradt. Needle in a haystack pressure testing llms., 2023. URL https://github.com/gkamradt/ LLMTestNeedleInAHaystack/tree/main.
- Marzena Karpinska, Katherine Thai, Kyle Lo, Tanya Goyal, and Mohit Iyyer. One thousand and one pairs: A "novel" challenge for long-context language models. In *Proceedings of EMNLP*, 2024. URL https: //aclanthology.org/2024.emnlp-main.948.
- Andreas Köpf, Yannic Kilcher, Dimitri von Rütte, Sotiris Anagnostidis, Zhi Rui Tam, Keith Stevens, Abdullah Barhoum, Duc Minh Nguyen, Oliver Stanley, Richárd Nagyfi, Shahul ES, Sameer Suri, David Alexandrovich Glushkov, Arnav Varma Dantuluri, Andrew Maguire, Christoph Schuhmann, Huu Nguyen, and Alexander Julian Mattick. Openassistant conversations - democratizing large language model alignment. In Proceedings of NeurIPS Datasets and Benchmarks Track, 2023. URL https://openreview.net/forum? id=VSJotgbPHF.
- Mosh Levy, Alon Jacoby, and Yoav Goldberg. Same task, more tokens: the impact of input length on the reasoning performance of large language models. In *Proceedings of ACL*, 2024. doi: 10.18653/v1/2024.acl-long.818. URL https://aclanthology.org/2024.acl-long.818/.
- Haoran Li, Qingxiu Dong, Zhengyang Tang, Chaojun Wang, Xingxing Zhang, Haoyang Huang, Shaohan Huang, Xiaolong Huang, Zeqiang Huang, Dongdong Zhang, Yuxian Gu, Xin Cheng, Xun Wang, Si-Qing Chen, Li Dong, Wei Lu, Zhifang Sui, Benyou Wang, Wai Lam, and Furu Wei. Synthetic data (almost) from scratch: Generalized instruction tuning for language models, 2024a. URL https://arxiv.org/abs/2402.13064.
- Huayang Li, Pat Verga, Priyanka Sen, Bowen Yang, Vijay Viswanathan, Patrick Lewis, Taro Watanabe, and Yixuan Su. Alr²: A retrieve-then-reason framework for long-context question answering, 2024b. URL https://arxiv.org/abs/2410.03227.
- Mo Li, Songyang Zhang, Yunxin Liu, and Kai Chen. Needlebench: Can llms do retrieval and reasoning in 1 million context window?, 2024c. URL https://arxiv.org/abs/2407.11963.
- Siheng Li, Cheng Yang, Zesen Cheng, Lemao Liu, Mo Yu, Yujiu Yang, and Wai Lam. Large language models can self-improve in long-context reasoning, 2024d. URL https://arxiv.org/abs/2411.08147.
- Opher Lieber, Barak Lenz, Hofit Bata, Gal Cohen, Jhonathan Osin, Itay Dalmedigos, Erez Safahi, Shaked Meirom, Yonatan Belinkov, Shai Shalev-Shwartz, et al. Jamba: A hybrid transformer-mamba language model. In *Proceedings of ICLR*, 2024. URL https://openreview.net/forum?id=JFPaD71pBD.
- Jiaheng Liu, ZhiqiBai ZhiqiBai, Yuanxing Zhang, Chenchen Zhang, YuangZh YuangZh, Ge Zhang, JiakaiWang JiakaiWang, Haoran Que, Yukang Chen, Wenbo Su, Tiezheng Ge, Jie Fu, Wenhu Chen, and Bo Zheng. E2-LLM: Efficient and extreme length extension of large language models. In *Findings of ACL*, 2024a. doi: 10.18653/v1/2024.findings-acl.252. URL https://aclanthology.org/2024.findings-acl.252.
- Nelson F Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics*, 2024b. URL https://aclanthology.org/2024.tacl-1.9/.
- Xiaoran Liu, Hang Yan, Chenxin An, Xipeng Qiu, and Dahua Lin. Scaling laws of rope-based extrapolation. In *Proceedings of ICLR*, 2024c.
- Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Proceedings of NeurIPS*, 2019.

- Bowen Peng, Jeffrey Quesnelle, Honglu Fan, and Enrico Shippole. Yarn: Efficient context window extension of large language models. In *Proceedings of ICLR*, 2024. URL https://arxiv.org/pdf/2309.00071.
- Keisuke Sakaguchi, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. Winogrande: An adversarial winograd schema challenge at scale. In *Proceedings of AAAI*, 2020. URL https://arxiv.org/abs/1907.10641.
- Daria Soboleva, Faisal Al-Khateeb, Robert Myers, Jacob R Steeves, Joel Hestness, and Nolan Dey. Slimpajama: A 627b token cleaned and deduplicated version of redpajama, 2023. URL https://huggingface.co/ datasets/cerebras/SlimPajama-627B.
- Jianlin Su, Yu Lu, Shengfeng Pan, Ahmed Murtadha, Bo Wen, and Yunfeng Liu. Roformer: Enhanced transformer with rotary position embedding. *arXiv preprint arXiv:2104.09864*, 2021. URL https://arxiv.org/pdf/2104.09864.
- Zhiqing Sun, Yikang Shen, Qinhong Zhou, Hongxin Zhang, Zhenfang Chen, David Cox, Yiming Yang, and Chuang Gan. Principle-driven self-alignment of language models from scratch with minimal human supervision. *Proceedings of NeurIPS*, 2024. URL https://openreview.net/forum?id=p40XRfBX96.
- Zhengyang Tang, Xingxing Zhang, Benyou Wang, and Furu Wei. Mathscale: Scaling instruction tuning for mathematical reasoning. In *Proceedings of ICML*, 2024. URL https://arxiv.org/abs/2403.02884.
- Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B. Hashimoto. Stanford alpaca: An instruction-following llama model. https://github.com/tatsu-lab/stanford_alpaca, 2023.
- Gemini Team, Petko Georgiev, Ving Ian Lei, Ryan Burnell, Libin Bai, Anmol Gulati, Garrett Tanzer, Damien Vincent, Zhufeng Pan, Shibo Wang, et al. Gemini 1.5: Unlocking multimodal understanding across millions of tokens of context. arXiv preprint arXiv:2403.05530, 2024. URL https://arXiv.org/abs/2403.05530.
- Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurelien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. Llama: Open and efficient foundation language models, 2023. URL https://arxiv.org/abs/2302.13971.
- Kiran Vodrahalli, Santiago Ontanon, Nilesh Tripuraneni, Kelvin Xu, Sanil Jain, Rakesh Shivanna, Jeffrey Hui, Nishanth Dikkala, Mehran Kazemi, Bahare Fatemi, Rohan Anil, Ethan Dyer, Siamak Shakeri, Roopali Vij, Harsh Mehta, Vinay Ramasesh, Quoc Le, Ed Chi, Yifeng Lu, Orhan Firat, Angeliki Lazaridou, Jean-Baptiste Lespiau, Nithya Attaluri, and Kate Olszewska. Michelangelo: Long context evaluations beyond haystacks via latent structure queries, 2024. URL https://arxiv.org/abs/2409.12640.
- Minzheng Wang, Longze Chen, Fu Cheng, Shengyi Liao, Xinghua Zhang, Bingli Wu, Haiyang Yu, Nan Xu, Lei Zhang, Run Luo, Yunshui Li, Min Yang, Fei Huang, and Yongbin Li. Leave no document behind: Benchmarking long-context LLMs with extended multi-doc QA. In *Proceedings of EMNLP*, 2024a. doi: 10.18653/v1/2024.emnlp-main.322. URL https://aclanthology.org/2024.emnlp-main.322/.
- Weizhi Wang, Li Dong, Hao Cheng, Xiaodong Liu, Xifeng Yan, Jianfeng Gao, and Furu Wei. Augmenting language models with long-term memory. In *Proceedings of NeurIPS*, 2024b. URL https://openreview.net/forum?id=lJWUJWLCJo¬eId=CJ00EonS46.
- Yizhong Wang, Yeganeh Kordi, Swaroop Mishra, Alisa Liu, Noah A Smith, Daniel Khashabi, and Hannaneh Hajishirzi. Self-instruct: Aligning language models with self-generated instructions. In *Proceedings of ACL*, 2023. URL https://aclanthology.org/2023.acl-long.754/.
- T Wolf. Huggingface's transformers: State-of-the-art natural language processing. *arXiv preprint arXiv:1910.03771*, 2019.
- Wenhao Wu, Yizhong Wang, Yao Fu, Xiang Yue, Dawei Zhu, and Sujian Li. Long context alignment with short instructions and synthesized positions. *arXiv preprint arXiv:2405.03939*, 2024. URL https://arxiv.org/abs/2405.03939.
- Chaojun Xiao, Pengle Zhang, Xu Han, Guangxuan Xiao, Yankai Lin, Zhengyan Zhang, Zhiyuan Liu, and Maosong Sun. InfLLM: Training-free long-context extrapolation for LLMs with an efficient context memory. In *Proceedings of NeurIPS*, 2024a. URL https://openreview.net/forum?id=bTHFrqhASY.
- Guangxuan Xiao, Yuandong Tian, Beidi Chen, Song Han, and Mike Lewis. Efficient streaming language models with attention sinks. In *Proceedings of ICLR*, 2024b. URL https://arxiv.org/abs/2309.17453.

- Wenhan Xiong, Jingyu Liu, Igor Molybog, Hejia Zhang, Prajjwal Bhargava, Rui Hou, Louis Martin, Rashi Rungta, Karthik Abinav Sankararaman, Barlas Oguz, et al. Effective long-context scaling of foundation models. In *Proceedings of NAACL*, 2024. URL https://aclanthology.org/2024.naacl-long.260/.
- Zheyang Xiong, Vasilis Papageorgiou, Kangwook Lee, and Dimitris Papailiopoulos. From artificial needles to real haystacks: Improving retrieval capabilities in LLMs by finetuning on synthetic data. In *Proceedings of ICLR*, 2025a. URL https://openreview.net/forum?id=8m7p4k6Zeb.
- Zheyang Xiong, Vasilis Papageorgiou, Kangwook Lee, and Dimitris Papailiopoulos. From artificial needles to real haystacks: Improving retrieval capabilities in LLMs by finetuning on synthetic data, 2025b. URL https://openreview.net/forum?id=8m7p4k6Zeb.
- Can Xu, Qingfeng Sun, Kai Zheng, Xiubo Geng, Pu Zhao, Jiazhan Feng, Chongyang Tao, Qingwei Lin, and Daxin Jiang. WizardLM: Empowering large pre-trained language models to follow complex instructions. In *Proceedings of ICLR*, 2024a. URL https://openreview.net/forum?id=CfXh93NDgH.
- Peng Xu, Wei Ping, Xianchao Wu, Lawrence McAfee, Chen Zhu, Zihan Liu, Sandeep Subramanian, Evelina Bakhturina, Mohammad Shoeybi, and Bryan Catanzaro. Retrieval meets long context large language models. In *Proceedings of ICLR*, 2024b. URL https://openreview.net/forum?id=xw5nxFWMlo.
- Peng Xu, Wei Ping, Xianchao Wu, Chejian Xu, Zihan Liu, Mohammad Shoeybi, and Bryan Catanzaro. ChatQA 2: Bridging the gap to proprietary LLMs in long context and RAG capabilities. In *Proceedings of ICLR*, 2025. URL https://openreview.net/forum?id=cPD2hU35x3.
- Zhe Xu, Jiasheng Ye, Xiangyang Liu, Tianxiang Sun, Xiaoran Liu, Qipeng Guo, Linlin Li, Qun Liu, Xuanjing Huang, and Xipeng Qiu. Detectiveqa: Evaluating long-context reasoning on detective novels. *arXiv preprint arXiv:2409.02465*, 2024c. URL https://arxiv.org/abs/2409.02465.
- An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, Junyang Lin, Kai Dang, Keming Lu, Keqin Bao, Kexin Yang, Le Yu, Mei Li, Mingfeng Xue, Pei Zhang, Qin Zhu, Rui Men, Runji Lin, Tianhao Li, Tingyu Xia, Xingzhang Ren, Xuancheng Ren, Yang Fan, Yang Su, Yichang Zhang, Yu Wan, Yuqiong Liu, Zeyu Cui, Zhenru Zhang, and Zihan Qiu. Qwen2.5 technical report. arXiv preprint arXiv:2412.15115, 2024.
- Howard Yen, Tianyu Gao, and Danqi Chen. Long-context language modeling with parallel context encoding. In *Proceedings of ACL*, 2024. doi: 10.18653/v1/2024.acl-long.142. URL https://aclanthology.org/ 2024.acl-long.142/.
- Howard Yen, Tianyu Gao, Minmin Hou, Ke Ding, Daniel Fleischer, Peter Izsak, Moshe Wasserblat, and Danqi Chen. HELMET: How to evaluate long-context models effectively and thoroughly. In *Proceedings of ICLR*, 2025. URL https://openreview.net/forum?id=293V3bJbmE.
- Longhui Yu, Weisen Jiang, Han Shi, Jincheng YU, Zhengying Liu, Yu Zhang, James Kwok, Zhenguo Li, Adrian Weller, and Weiyang Liu. Metamath: Bootstrap your own mathematical questions for large language models. In *Proceedings of ICLR*, 2024. URL https://openreview.net/forum?id=N8N0hgNDRt.
- Jiajie Zhang, Zhongni Hou, Xin Lv, Shulin Cao, Zhenyu Hou, Yilin Niu, Lei Hou, Yuxiao Dong, Ling Feng, and Juanzi Li. Longreward: Improving long-context large language models with ai feedback. *arXiv preprint arXiv:2410.21252*, 2024a. URL https://arxiv.org/abs/2410.21252.
- Xinrong Zhang, Yingfa Chen, Shengding Hu, Zihang Xu, Junhao Chen, Moo Hao, Xu Han, Zhen Thai, Shuo Wang, Zhiyuan Liu, et al. ∞ bench: Extending long context evaluation beyond 100k tokens. In *Proceedings* of ACL, 2024b. URL https://aclanthology.org/2024.acl-long.814/.
- Liang Zhao, Tianwen Wei, Liang Zeng, Cheng Cheng, Liu Yang, Peng Cheng, Lijie Wang, Chenxia Li, Xuejie Wu, Bo Zhu, et al. Longskywork: A training recipe for efficiently extending context length in large language models. *arXiv preprint arXiv:2406.00605*, 2024a. URL https://arxiv.org/abs/2406.00605.
- Wenting Zhao, Xiang Ren, Jack Hessel, Claire Cardie, Yejin Choi, and Yuntian Deng. Wildchat: 1m chatGPT interaction logs in the wild. In *Proceedings of ICLR*, 2024b. URL https://openreview.net/forum?id=B18u7ZR1bM.
- Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Tianle Li, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zhuohan Li, Zi Lin, Eric Xing, Joseph E. Gonzalez, Ion Stoica, and Hao Zhang. LMSYS-chat-1m: A large-scale real-world LLM conversation dataset. In *Proceedings of ICLR*, 2024. URL https://openreview.net/forum?id=B0fDKxfwt0.

- Jeffrey Zhou, Tianjian Lu, Swaroop Mishra, Siddhartha Brahma, Sujoy Basu, Yi Luan, Denny Zhou, and Le Hou. Instruction-following evaluation for large language models. *arXiv preprint arXiv:2311.07911*, 2023. URL https://arxiv.org/abs/2311.07911.
- Dawei Zhu, Nan Yang, Liang Wang, Yifan Song, Wenhao Wu, Furu Wei, and Sujian Li. PoSE: Efficient context window extension of LLMs via positional skip-wise training. In *Proceedings of ICLR*, 2024. URL https://openreview.net/forum?id=3Z1gxuAQrA.

A Experimental Details

A.1 Document Classifier

We trained a random forest classifier on semantic features extracted from a small language model. The classifier was trained on annotations of 20,000 long documents from SlimPajama, achieving 90% accuracy on a held-out test set. Specifically, we annotated 20,000 long documents sampled from SlimPajama using GPT-4. The annotation prompt explicitly required the output to match one of the predefined document types, ensuring consistency with the categories defined during meta information clustering. Using these annotations, we trained a random forest classifier on semantic features extracted with StableLM-2-1.6B (Bellagente et al., 2024), where the mean of the last layer's hidden states was used as the feature representation. The classifier achieved 90% accuracy on a held-out test set, enabling efficient and accurate predictions of document types for unseen SlimPajama data.

A.2 Instruction Generation with Paths

To synthesize instructions aligned with sampled meta information paths, we prompt GPT-4 with a one-shot demonstration derived from seed paths extracted from the WildChat long conversations. Each seed path includes all meta information fields and a corresponding simplified instruction. Given a sampled path \hat{P} , we identify the most similar seed path P^* based on the of their nodes. The similarity between paths is computed as intersection_ $sim(\hat{P}, P^*) = |\hat{P} \cap P^*|$. The selected example path and its instruction are included in the prompt to guide GPT-4 in generating a new instruction given a new path. This ensures the generated instruction aligns with the sampled meta information criteria, while benefiting from the contextual relevance provided by the seed example. GPT-4 synthesizes a natural language instructions adhering to the sampled path's constraints with the prompt shwon in Table 7.

A.3 Evaluation Settings

For short-context evaluation, we utilize the lm-evaluaton-harness framework Gao et al. (2024a) and following the evaluation settings in (Beeching et al., 2023): 25-shots for ARC-C, and 5-shots for MMLU, Winogrande and GSM8K. We use 0-shot for IFEval. We report the acc_norm metric for ARC-C, the acc metric for MMLU, Winogrande and GSM8K. We average the metrics prompt_level_strict_acc, inst_level_strict_acc, prompt_level_loose_acc, and inst_level_loose_acc for IFEval.

For long-context evaluations, we evaluate our models and all baselines following the settings in the original benchmarks. Table 5 presents the sources of evaluation results for the models across three benchmarks.

Table 5: Evaluation source for each model on three benchmarks. \checkmark indicates that the evaluation was conducted by ourselves, while \star indicates that results were sourced from the original benchmark.

Models	RULER	HELMET	Longbench-Chat					
Proprietary Long-Context Models								
Gemini-1.5-Pro	★	*	 ✓ 					
GPT-4	*	*	*					
Open-Sourced Pretrained Long-Context Models								
GLM-4-1M	*	~	~					
Yi-200k	*	*	✓					
Llama-3.1-70B	*	*	v					
Phi-3-medium	*	*	v					
Qwen2.5	~	~	✓					
Mistral-7B	~	~	✓					
Llama-3.1-8B	~	~	~					
Specialized Long-Context Optimized Models								
FILM	 ✓ 	~	v					
ProLong-512k	~	~	v					
ChatQA-2	~	~	✓					
SEALONG	 ✓ 	~	 ✓ 					

A.4 Technical Details

We employ several open-source libraries and tools for model training. Specifically, we use PyTorch (Paszke et al., 2019) and the Hugging Face Transformers library (Wolf, 2019) for implementing and fine-tuning the model. To enhance computational efficiency, we integrate FlashAttention 2 (Dao, 2024) for optimized attention

computation. The fine-tuning process is conducted on eight AMD Radeon Instinct MI300 GPUs, each equipped with 192GB of memory. Training on 150K synthetic data samples requires approximately 480 GPU hours.

B Discussion on RoPE Base

Recent studies demonstrate that adjusting the base value in Rotary Position Embedding (RoPE) significantly enhances language models' ability to handle long-context sequences (bloc97, 2023). The scalability of RoPE for long-context has been systematically demonstrated through base parameter adjustments (Liu et al., 2024c). By increasing the base parameter (e.g., from 10^4 to 10^6), the wavelength of positional encoding grows exponentially as $\lambda_i \propto base^{2i/d}$, where d is the embedding dimension and i indexes frequency bands. This prolongs the non-repeating positional patterns across distant tokens, effectively mitigating encoding collisions that impair long-range dependency modeling. Practical implementations like Code Llama (Grattafiori et al., 2023) and ChatGLM (GLM et al., 2024) have adopted base scaling to extend context windows to 16k+ tokens while preserving local positional sensitivity. Our experiments align with these findings, showing that larger base values improve coherence in tasks requiring cross-sentence reasoning.

C Prompts

The prompts used by the WildLong framework can be seen from Table 6, Table 7, Table 8, and Table 9.

Below is a conversation between a user and an AI Language Model, likely involving a long document.

Conversation

{conversation}

Your Tasks

Based on the conversation above, try to finish the following tasks.

- Determine whether the query of the user involves a long document (or any form of long text).

- If the conversation involves a long document, analyse the conversation and provide the following information using concise phrases.

- Document Type: Specify the format or category of the document, such as a research paper, technical report, fictional story, instruction manual, etc. Ideally, extract one document type. However, if you believe there are multiple types, limit the number to two.

- Tasks or Requests: Identify 1 to 3 the specific tasks the user wants the chatbot to perform given the long context. This may include summarizing key points, integrating multiple pieces of information, continuing the dialogue or story, providing an analysis, or any other specific task relevant to the long text. - Purpose of Query: Define the objective behind the user's query, such as educational purposes, decision-making, research, entertainment, etc. List 1 to 3 items.

- User Intention: Determine the underlying goal or reason behind the user's request, such as completing an assignment, preparing for a debate, gaining a general understanding, etc. List 1 to 3 items.

- User Profile: Describe the possible characteristics and background of the user in 1 to 5 phrases.

- User's Language Style: Identify the language style of the user. List 1 to 3 items.

- Context: Describe the situational background influencing the query, such as working on a group project, preparing for an exam, etc. List 1 to 3 context items.

- Knowledge/Commonsense Involved for User: Identify the prior knowledge or commonsense the user is expected to have. List 1 to 5 items.

- Knowledge/Commonsense Involved for Chatbot: Identify the prior knowledge or commonsense the chatbot is expected to have to address the query. List 1 to 5 items.

- Long Context Capability Involved: Determine the comprehension and information processing skills required to address the user's request, such as long document comprehension, key information retrieval, handling multiple perspectives, etc. List 1 to 3 items.

- Output Format: Identify the desired format of the response. List 1 to 3 items.

- Sentiment: Determine the expected emotional tone or attitude in the response. List 1 to 3 items.

- Constraint of the Request: Identify the limitations or additional requirements that the user has for the chatbot's response. List 0 to 3 constraints, if any.

- Simplified Instruction by User: Provide a simplified version of the user's request, removing any context or background information.

Output Format

Document Type: 1. doc type 1 ... 2. doc type 2 ...

Task or Request:

request type 1 ...
 request type 2 ...

2. request type 2 ..

•••

Additional Requirements for Output

- Analyze the entire conversation to produce your answers, taking into account both the user's and the chatbot's contributions. Do not limit your analysis to just one side.

- If the user query does not involve a long document (or any form of long text), output only "No long document involved".

- For each output field, output commonly used phrases or short sentences in academic or industry if applicable.

- If you cannot extract anything for a particular field, output "NA" for that field.

Table 6: The prompt to extract meta information with GPT-4.

You are tasked with generating 3 realistic user queries or instructions for a chatbot about a long document. The user is interacting with a long $\{doc_type\}$, but you do not have access to the exact content of the document. Your task is to create reasonable user queries or instructions that meet specific meta information criteria. There are 12 meta information categories that define the characteristics of a user query or instruction. You will be provided with 6 key meta information fields that must be incorporated into each of your generated queries or instructions. For the remaining 6 categories, you have the flexibility to explore different possibilities to create varied and diverse queries or instructions. You will be given an example meta information criteria and a corresponding sample query or instruction to help you understand the context and how to apply the meta information.

Additional requirements

- Incorporate All Key Fields: Aim to integrate all 6 key meta information fields into each query or instruction you create. If a field is particularly challenging to include, substitute it with a reasonable alternative.

- Ensure Coherence and Creativity: Your generated queries or instructions should be coherent, natural, and flow smoothly. They should not appear as a direct combination of the meta information fields, instead aiming for a realistic scenario that a user in the given context might actually encounter.

- Creative Interpretation: The meta information criteria represent high-level characteristics of a user's query or instruction. You can interpret and apply them creatively to generate a range of realistic and diverse outputs.

- Output Format: Present your generated queries or instructions in bullet points, formatted as follows:

1. query 1

2. query 2

3. query 3

Definitions of the 12 meta information categories

- Tasks or Requests: tasks the user wants the chatbot to perform given the long context.

- Purpose of Query: the objective behind the user's query, such as educational purposes, decisionmaking, research, entertainment, etc.

- User Intention: the underlying goal or reason behind the user's request, such as completing an assignment, preparing for a debate, gaining a general understanding, etc.

- User Profile: the possible characteristics and background of the user.

- User's Language Style: the language style of the user.

- Context: the situational background influencing the query, such as working on a group project, preparing for an exam, etc.

- Knowledge/Commonsense Involved for User: the prior knowledge or commonsense the user is expected to have.

- Knowledge/Commonsense Involved for Chatbot: the prior knowledge or commonsense the chatbot is expected to have to address the query.

- Long Context Capability Involved: the comprehension and information processing skills required to address the user's request, such as long document comprehension, key information retrieval, handling multiple perspectives, etc.

- Output Format: the desired format of the response.

- Sentiment: the expected emotional tone or attitude in the response.

- Constraint of the Request: the limitations or additional requirements that the user has for the chatbot's response.

Example meta information criteria

{example_meta_info}

Example query/instruction

{example_instruction}

Your task

Generate a new query or instruction that aligns with the given meta information criteria: {path_meta_info}

Table 7: The prompt to generate instruction given a sampled meta-information path.

Long Document: {long_doc}

Example Query/Instruction: {example_instruct}

Your Task:

You have been provided with a long document above, along with an example query or instruction that was formulated for another similar long document.

Your task is to create a new query or instruction that can be addressed using the information contained within the long document provided.

The new query or instruction should be inspired by the structure and intent of the given example but is not a direct copy. You should adapt the query or instruction to fit the context of the long document while still addressing a similar type of task.

Once you have formulated the query or instruction, provide a response based on the content of the long document.

Please format your output as follows: Query/Instruction: {{query_or_instruction}} Response: {{response}}

Table 8: The prompt to generate instruction-response pairs.

The following are tasks or requests made by users when querying a chatbot about a single document. Modify the tasks or requests as if the user is querying multiple documents. Ensure that the modifications reflect a realistic need to handle information across multiple sources, incorporating cognitive operations usually applied to multiple documents. The document type is {doc_type}. Avoid simply adding phrases like "across multiple documents." Instead, adapt each task to reflect a more complex interaction with multiple sources, focusing on the cognitive operation that makes sense in the multi-document context. Cognitive operations - Comparison: identifying similarities, differences, or evaluating multiple documents - Synthesis: integrating information from multiple sources to create a new, cohesive understanding - Aggregation: collecting and presenting information from multiple sources without integrating or interpreting - Verification and Validation: cross-referencing and fact-checking across documents - Consensus Analysis: identifying agreement across documents - Divergence Analysis: recognizing conflicting or differing points of view - Problem Solving: formulating solutions based on multiple documents - Decision Making: formulating decisions based on multiple documents - Exploration: discovery across multiple sources without a predefined goal - Trend and Pattern Identification: detecting larger patterns or trends from multiple documents - Hypothesis Generation: forming new hypotheses through integrated data - Creative Synthesis: fostering novel ideas or concepts from the documents Original tasks or requests {original_tasks_or_requests} **Output** format 1. {original_tasks_or_requests}: {modified_tasks_or_requests} 2. {original_tasks_or_requests}: {modified_tasks_or_requests} ...

Table 9: The prompt to convert single-document tasks to multi-document tasks.