Batch normalization does not improve initialization

Joris Dannemann^{*}, Gero Junike[†]

February 26, 2025

Abstract

Batch normalization is one of the most important regularization techniques for neural networks, significantly improving training by centering the layers of the neural network. There have been several attempts to provide a theoretical justification for batch normalization. Santurkar and Tsipras (2018) [How does batch normalization help optimization? Advances in neural information processing systems, 31] claim that batch normalization improves initialization. We provide a counterexample showing that this claim is not true, i.e., batch normalization does not improve initialization.

Keywords: neural network, batch normalization, initialization

1 Introduction

Neural networks are functions with many parameters. To train a neural network, the parameters are randomly initialized at the beginning of the training and are then calibrated to a learning set by minimizing a loss function via gradient decent, see [4].

Batch normalization (BN), see [6], is a technique to improve the training of neural networks. It has been used in many applications [6, 4, 10, 11, 2, 7] to make training faster and more stable. According to [4, p. 317], "Batch normalization (Ioffe and Szegedy, 2015) is one of the most exciting recent innovations in optimizing deep neural networks". Similarly, [1, p. 1] concludes: "Nowa-days, there is little disagreement in the machine learning community that BN accelerates training, enables higher learning rates, and improves generalization accuracy [...] and BN has successfully proliferated throughout all areas of deep learning".

However, the working mechanism of BN is not yet fully understood. The authors in [8] are among the first to analyze BN from a more theoretical point

^{*}Carl von Ossietzky Universität, Institut für Mathematik, 26129 Oldenburg, Germany, E-mail: joris.dannemann@uni-oldenburg.de

[†]Corresponding author. Carl von Ossietzky Universität, Institut für Mathematik, 26129 Oldenburg, Germany, ORCID: 0000-0001-8686-2661, E-mail: gero.junike@uol.de

of view. They provide several theoretical arguments why BN improves training, in particular they claim in Lemma 4.5 "that BN also offers an advantage in initialization", see [8, p. 8]. This statement, i.e., [8, Lemma 4.5], is also cited in [11, Lemma 7.2]. However, we provide a straightforward counterexample showing that this lemma is incorrect, i.e., BN does not improve initialization.

This article is structured as follows: in Section 2 we give a brief introduction to neural networks and BN. In Section 3, we provide a counterexample showing that BN does not improve initialization.

2 Neural networks and batch normalization

For an introduction to neural networks with BN, see [4, Section 8.7.1] and [11, Section 7.15]. In this section, we summarize the most important definitions: A *neural network* is a function from some *input space* (e.g., a subspace of \mathbb{R}^p) to some *output space* (e.g., a subspace of \mathbb{R}). A neural network consists of *layers*, that consist of *neurons*, which use *activation functions*. The regularization technique *batch normalization* acts on one or more layers. We write $\|\cdot\|$ and $\langle \cdot, \cdot \rangle$ for the Euclidean norm and the inner product on \mathbb{R}^d , respectively.

Definition 2.1. An activation function is a function $g : \mathbb{R} \to \mathbb{R}$.

For example, the identity, Sigmoid, tanh and ReLu (Rectified linear unit) activation functions are defined by $x \mapsto x$, $x \mapsto \frac{1}{1+e^{-x}}$, $x \mapsto \tanh(x)$ and $x \mapsto \max(x, 0)$, respectively. Next, we define a neuron, that has k inputs and one output.

Definition 2.2. A *neuron* is a function h with weights $w \in \mathbb{R}^k$ and bias $b \in \mathbb{R}$ and activation function g, such that

$$h: \mathbb{R}^k \to \mathbb{R}, \quad \boldsymbol{x} \mapsto g(\langle \boldsymbol{w}, \boldsymbol{x} \rangle + b).$$

Definition 2.3. Let $h_1, ..., h_n : \mathbb{R}^k \to \mathbb{R}$ be *n* neurons. A layer is a function

 $f: \mathbb{R}^k \to \mathbb{R}^n, \quad \boldsymbol{x} \mapsto (h_1(\boldsymbol{x}), ..., h_n(\boldsymbol{x}))^{\mathsf{T}}$

consisting of $n \in \mathbb{N}$ neurons. Each neuron has k inputs.

Example 2.4. In the special case that each neuron of the layer has the identity as its activation function and zero bias, it holds that $f(\boldsymbol{x}) = W\boldsymbol{x}$ for a matrix $W \in \mathbb{R}^{n \times k}$ of weights.

Definition 2.5. Suppose the input space has dimension p. A neural network (NN) consists of $L \in \mathbb{N}$ layers $f_1 : \mathbb{R}^{k_1} \to \mathbb{R}^{n_1}, ..., f_L : \mathbb{R}^{k_L} \to \mathbb{R}^{n_L}$ with $k_1 = p$, $k_2 = n_1, ..., k_L = n_{L-1}$. The layers have $n_1, n_2, ..., n_L$ neurons. The neural network is the function

$$\varphi_{\Theta}: \mathbb{R}^p \to \mathbb{R}^{n_L}, \quad \boldsymbol{x} \mapsto f_L(f_{L-1}(\dots f_2(f_1(\boldsymbol{x})))).$$

The input \boldsymbol{x} is also called the *input layer*. The last layer f_L is also called the *output layer*. The layers f_1, \ldots, f_{L-1} are called *hidden layers*. All parameters of the NN, e.g., the weights and the biases of the neurons, are stored in a vector Θ .

The optimal parameters Θ^* of the NN are usually found via minimizing some loss function, e.g.,

$$\Theta^* = \operatorname{argmin}_{\Theta} \frac{1}{N} \sum_{i=1}^{N} \left(\varphi_{\Theta} \left(\bar{\boldsymbol{x}}^{(i)} \right) - \bar{\boldsymbol{y}}^{(i)} \right)^2,$$

where $\bar{\boldsymbol{x}}^{(i)} \in \mathbb{R}^p$ and $\bar{y}^{(i)} \in \mathbb{R}$ and $\{(\bar{\boldsymbol{x}}^{(1)}, \bar{y}^{(1)}), ..., (\bar{\boldsymbol{x}}^{(N)}, \bar{y}^{(N)})\}$ is a learning set of size N. The loss function is minimized by (stochastic) gradient descent. It is recommended to initialize Θ randomly, see [3, 5]. During the optimization, the learning set is divided into several disjoint sets, so called *batches*.

Next, we define layers with BN, introduced by [6]. Note that the input layer of a batch of size M has dimension $p \times M$ and the output of the *l*-th layer has dimension $n_l \times M$.

Definition 2.6. Consider a NN with of L layers. The *l*-th layer $f_l : \mathbb{R}^{k_l} \to \mathbb{R}^{n_l}$ consists of n_l neurons. Apply the NN to a batch of size $M \in \mathbb{N}$. The output of the *l*-th layer has the form

$$\mathbb{Z}_l = \begin{pmatrix} z_{11} & \dots & z_{1M} \\ \vdots & & \vdots \\ z_{n_l 1} & \dots & z_{n_l M} \end{pmatrix} \in \mathbb{R}^{n_l \times M}.$$

Let

$$\mu_j = \frac{1}{M} \sum_{m=1}^M z_{jm}$$
, and $\sigma_j = \sqrt{\frac{1}{M} \sum_{m=1}^M (z_{jm} - \mu_j)^2}$, $j = 1, ..., n_l$.

Let $\gamma_1, ..., \gamma_{n_l} \in \mathbb{R}$ and $\beta_1, ..., \beta_{n_l} \in \mathbb{R}$ be parameters and define

$$\hat{\mathbb{Z}}_{l} = \begin{pmatrix} \gamma_{1} \frac{z_{11} - \mu_{1}}{\sigma_{1}} + \beta_{1} & \dots & \gamma_{1} \frac{z_{1M} - \mu_{1}}{\sigma_{1}} + \beta_{1} \\ \vdots & & \vdots \\ \gamma_{n_{l}} \frac{z_{n_{l}1} - \mu_{n_{l}}}{\sigma_{n_{l}}} + \beta_{n_{l}} & \dots & \gamma_{n_{l}} \frac{z_{n_{l}M} - \mu_{n_{l}}}{\sigma_{n_{l}}} + \beta_{n_{l}} \end{pmatrix} \in \mathbb{R}^{n_{l} \times M}.$$

 $\hat{\mathbb{Z}}_l$ is called *batch normalization transform* of layer \mathbb{Z}_l .

Remark 2.7. During the training, the NN is trained on the transformed data $\hat{\mathbb{Z}}_l$ and the parameters γ_j and β_j , $j = 1, ..., n_l$ are trainable as well. If $\gamma_j = \sigma_j$ and $\beta_j = \frac{\mu_j}{\sigma_j}$ then $\hat{\mathbb{Z}}_l = \mathbb{Z}_l$, i.e., one "could recover the original activations, if that were the optimal thing to do", see [6, Section 3, p. 3]. For prediction, the average values (over all batches) of the parameters μ_j and σ_j are used.

3 Counterexample: BN does not improve initialization

[8] analyze individual layers of a NN assuming that all neurons in that layer have the identity as activation function and that β and γ for the BN are constants. In [8, Lemma 4.5] it is claimed that BN offers an advantage in initialization:

"(BatchNorm leads to a favorable initialization). Let \mathbf{W}^* and $\widehat{\mathbf{W}}^*$ be the set of local optima for the weights in the normal and BN networks, respectively. For any initialization W_0

$$\left\| W_0 - \widehat{W}^* \right\|^2 \le \|W_0 - W^*\|^2 - \frac{1}{\|W^*\|^2} \left(\|W^*\|^2 - \langle W^*, W_0 \rangle \right)^2, \qquad (1)$$

if $\langle W_0, W^* \rangle > 0$, where \widehat{W}^* and W^* are closest optima for BN and standard network, respectively.", see [8, p. 9].

Remark 3.1. The matrix $W_0 \in \mathbb{R}^{n \times k}$ is understood as the initial weights of a particular layer with k inputs consisting of n neurons with biases equal to zero. W^* and \widehat{W}^* are the locally optimal weights of the layer with respect to the loss function with and without BN, respectively. The norm and the inner product applied to matrices in Inequality (1) are understood column wise.

In the next example, we will show that [8, Lemma 4.5] is wrong. We will construct a NN consisting of a single neuron with the identity as activation function with initial weights W_0 identical to the optimal weights W^* and show that any weights \widehat{W}^* satisfying Inequality (1) cannot be optimal for the BN network.

Example 3.2. We consider a learning set $\{(\bar{x}^{(1)}, \bar{y}^{(1)}), ..., (\bar{x}^{(3)}, \bar{y}^{(3)})\}$ consisting of three samples, where

$$\bar{\boldsymbol{x}}^{(1)} = \begin{pmatrix} 1\\1 \end{pmatrix}, \quad \bar{\boldsymbol{x}}^{(2)} = \begin{pmatrix} 1\\2 \end{pmatrix}, \quad \bar{\boldsymbol{x}}^{(3)} = \begin{pmatrix} 2\\3 \end{pmatrix}, \quad \bar{y}^{(1)} = 2, \quad \bar{y}^{(1)} = 5, \quad \bar{y}^{(1)} = 13.$$

There is the following relation: $\bar{y}^{(i)} = (\bar{x}_1^{(i)})^2 + (\bar{x}_2^{(i)})^2$. To learn this relation, we consider a NN consisting of a single neuron and the identity as activation function: $\varphi_{\boldsymbol{w}}(\boldsymbol{x}) = \langle \boldsymbol{w}, \boldsymbol{x} \rangle$, where $\boldsymbol{w} = (w_1, w_2) \in \mathbb{R}^2$ are the weights of the neuron. The bias is set to zero. We initialize the NN with the weights $W_0 := (1,3)$. We consider a batch identical to the learning set. The output matrix of the hidden layer of the NN for the batch is therefore (we omit the index *l* since there is only one layer):

$$\mathbb{Z} = \begin{pmatrix} w_1 + w_2 & w_1 + 2w_2 & 2w_1 + 3w_2 \end{pmatrix} \in \mathbb{R}^{1 \times 3}.$$

The mean μ and standard-deviation σ over the batch are then given by (the index j omitted)

$$\mu = \frac{4}{3}w_1 + 2w_2$$

$$\sigma = \frac{1}{3}\sqrt{2w_1^2 + 6w_1w_2 + 6w_2^2}$$

We choose $\gamma = 1$ and $\beta = 0$ as parameters for the BN transform. This means the NN with BN is given by

$$\widehat{\varphi}_{\boldsymbol{w}}(\boldsymbol{x}) = \frac{\langle \boldsymbol{w}, \boldsymbol{x} \rangle - \mu}{\sigma}.$$

For the cost function we use the squared Euclidean norm. More specifically, for the standard network, let

$$\mathcal{C}(\boldsymbol{w}) = \sum_{i=1}^{3} \left(\varphi_{\boldsymbol{w}}(\bar{\boldsymbol{x}}^{(i)}) - \bar{y}^{(i)} \right)^2$$

= $(w_1 + w_2 - 2)^2 + (w_1 + 2w_2 - 5)^2 + (2w_1 + 3w_2 - 13)^2.$

This function achieves its global minimum at $W^* = (1,3)$. The cost function for the BN network $\widehat{\varphi}_{w}$ is given by

$$\begin{aligned} \widehat{\mathcal{C}}(\boldsymbol{w}) &= \sum_{i=1}^{3} \left(\widehat{\varphi}_{\boldsymbol{w}}(\bar{\boldsymbol{x}}^{(i)}) - \bar{y}^{(i)} \right)^2 = \left(\frac{-w_1 - 3w_2}{\sqrt{2w_1^2 + 6w_1w_2 + 6w_2^2}} - 2 \right)^2 \\ &+ \left(\frac{-w_1}{\sqrt{2w_1^2 + 6w_1w_2 + 6w_2^2}} - 5 \right)^2 \\ &+ \left(\frac{2w_1 + 3w_2}{\sqrt{2w_1^2 + 6w_1w_2 + 6w_2^2}} - 13 \right)^2. \end{aligned}$$

The gradient of $\widehat{\mathcal{C}}$ at W^* does not vanish, it is given by (-0.34, 0.11). In particular, $\widehat{\mathcal{C}}$ cannot attain a local minium at W^* . Since $W_0 = W^*$, it holds that

$$\langle W_0, W^* \rangle = \langle W_0, W_0 \rangle = ||W_0||^2 > 0.$$

It can be shown that $\widehat{\mathcal{C}}$ achieves a local minimum at any (w_1, w_2) satisfying $w_1 > 0$ and $3w_1 = 5w_2$, which is a consequence of BN being scale invariant. Thus, $\widehat{\boldsymbol{W}}^* \neq \emptyset$. Let $\widehat{W}^* \in \widehat{\boldsymbol{W}}^*$. Assume the statement in [8, Lemma 4.5] were true. Then by Inequality (1) it holds that

$$\|W_0 - \widehat{W}^*\|^2 \le \underbrace{\|W_0 - W^*\|^2}_{=0} - \frac{1}{\|W^*\|^2} \Big(\underbrace{\|W^*\|^2 - \langle W^*, W_0 \rangle}_{=\|W^*\|^2 - \|W^*\|^2 = 0}\Big)^2 = 0,$$

which implies $\widehat{W}^* = W_0$. Hence, W_0 would also be a local optimum for the cost function of the BN network. However, this does not hold since the gradient of $\widehat{\mathcal{C}}$ does not vanish at W_0 . Hence, the statement in [8, Lemma 4.5] is wrong. In conclusion, BN does not improve initialization.

and

Remark 3.3. The (incorrect) proof of this statement can be found in [9]. Let W be some weights of a layer. In the proof it is claimed that if W leads to a local optimum of the loss function before BN then W also leads to a local optimum after BN, which is not correct: The cost function of the standard network in Example 3.2 has a local minimum at $W^* = (1,3)$ but the cost function $\widehat{\mathcal{C}}$ of the BN network cannot have a local minimum at W^* since the gradient of $\widehat{\mathcal{C}}$ does not vanish at W^* .

Disclosure statement.

The authors report there are no competing interests to declare.

References

- Nils Bjorck, Carla P Gomes, Bart Selman, and Kilian Q Weinberger. Understanding batch normalization. Advances in neural information processing systems, 31, 2018.
- [2] Solveig Flaig and Gero Junike. Scenario generation for market risk models using generative neural networks. *Risks*, 10(11):199, 2022.
- [3] Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pages 249–256. JMLR Workshop and Conference Proceedings, 2010.
- J. Courville. [4] Ian Goodfellow, Yoshua Bengio, and Aaron Deep Learning. MIT Press, Cambridge, MA. USA, 2016.http://www.deeplearningbook.org.
- [5] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE international conference on computer* vision, pages 1026–1034, 2015.
- [6] Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. arXiv preprint arXiv:1502.03167, 2015. https://arxiv.org/abs/1502.03167.
- [7] Jian Liang, Ran He, and Tieniu Tan. A comprehensive survey on test-time adaptation under distribution shifts. *International Journal of Computer Vision*, 133(1):31–64, 2025.
- [8] Shibani Santurkar, Dimitris Tsipras, Andrew Ilyas, and Aleksander Madry. How does batch normalization help optimization? Advances in neural information processing systems, 31, 2018.

- [9] Shibani Santurkar, Dimitris Tsipras, Andrew Ilyas, and Aleksander Madry. How Does Batch Normalization Help Optimization? arXiv preprint arXiv:1805.11604v5, 2019. https://arxiv.org/abs/1805.11604.
- [10] David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, et al. Mastering the game of go without human knowledge. *Nature*, 550(7676):354–359, 2017.
- [11] Xian-Da Zhang. A matrix algebra approach to artificial intelligence. Springer, Singapore, 2020. https://link.springer.com/book/10.1007/978-981-15-2770-8.