

Reward Shaping to Mitigate Reward Hacking in RLHF

Jiayi Fu^{1,2*}, Xuandong Zhao^{3*}, Chengyuan Yao², Heng Wang², Qi Han², Yanghua Xiao^{1†}

¹Fudan University ²StepFun ³UC Berkeley

fujy22@m.fudan.edu.cn

xuandongzhao@berkeley.edu

shawyh@fudan.edu.cn

Abstract

Reinforcement Learning from Human Feedback (RLHF) is essential for aligning large language models (LLMs) with human values. However, RLHF is susceptible to *reward hacking*, where the agent exploits flaws in the reward function rather than learning the intended behavior, thus degrading alignment. While reward shaping helps stabilize RLHF and partially mitigate reward hacking, a systematic investigation into shaping techniques and their underlying principles remains lacking. To bridge this gap, we present a comprehensive study of the prevalent reward shaping methods. Our analysis suggests three key design principles: (1) RL reward is ideally bounded, (2) RL benefits from rapid initial growth followed by gradual convergence, and (3) RL reward is best formulated as a function of centered reward. Guided by these insights, we propose Preference As Reward (PAR), a novel approach that leverages the latent preferences embedded within the reward model itself as the signal for reinforcement learning. We evaluated PAR on two base models, Gemma2-2B and Llama3-8B, using two datasets, Ultrafeedback-Binarized and HH-RLHF. Experimental results demonstrate PAR’s superior performance over other reward shaping methods. On the AlpacaEval 2.0 benchmark, PAR achieves a win rate at least 5 percentage points higher than competing approaches. Furthermore, PAR exhibits remarkable data efficiency, requiring only a single reference reward for optimal performance, and maintains robustness against reward hacking even after two full epochs of training. Code is available at <https://github.com/PorUna-byte/PAR>.¹

1 Introduction

Reinforcement learning from human feedback is essential for the capabilities of powerful large lan-

*Equal contribution.

†Corresponding author.

¹Work done during internship at StepFun by Jiayi Fu.




Figure 1: RLHF training pipeline with reward shaping. Responses from the policy model are evaluated by the reward model, producing proxy rewards. These rewards are then reshaped (optionally using reference rewards, as shown in the dashed box) before being used to update the policy via RL. The blue box details the PAR reward shaping function, which uses a sigmoid applied to the centered reward.

guage models (Ouyang et al., 2022; OpenAI, 2024). It not only aligns LLMs with human intentions (Bai et al., 2022) but also enhances their general capabilities (Guo et al., 2024). However, an inherent issue in RLHF, known as reward hacking (Amodei et al., 2016; Gao et al., 2023), has raised concerns about the reliability of this paradigm. Reward hacking occurs when a policy model optimizes for higher reward model scores while failing to improve its actual performance. For example, the policy model might produce repetitive or formulaic content to maximize rewards, rather than genuinely accomplishing the intended tasks (Singhal et al., 2023).

Proximal Policy Optimization (PPO) (Schulman et al., 2017) is the de facto RL algorithm for RLHF and is widely used for training LLMs (Ouyang et al., 2022). However, PPO also suffers from reward hacking, limiting its overall performance. To address this problem, we focus on reward shaping. Reward shaping techniques, such as clipping and rescaling, are relatively straightforward to implement and have demonstrated effectiveness in mitigating reward hacking by modifying the proxy reward (Dai et al., 2023; Wang et al., 2024). However, a comprehensive comparison of these techniques and a set of well-defined design principles

for their application remain largely unexplored.

To address the research gap and establish a foundation for future advancements in reward shaping techniques, we conduct a systematic investigation of widely used methods. Our findings demonstrate that during PPO training with a specific reward model, a distinct reward threshold emerges (Moskovitz et al., 2023). Exceeding this threshold frequently indicates the onset of reward hacking, marked by a decrease in the model’s win rate. We hypothesize that excessively high rewards from the reward model often become misaligned with true performance and lose meaningful correlation with the task’s goals. These inflated rewards can also hinder the critic model’s ability to learn an accurate value function. This insight leads to our first design principle: *(1) RL reward is ideally bounded.* Moreover, we observe that the low-reward region is considerably safer for optimization compared to the high-reward region, prompting our second design principle: *(2) RL benefits from rapid initial growth followed by gradual convergence.* Finally, we highlight that the absolute values of proxy rewards are uninformative, as different reward models and prompts yield varying scores independent of response quality. Instead, optimizing the relative difference between rewards is more reliable (Wang et al., 2024). This motivates our third principle: *(3) RL reward is best formulated as a function of centered reward.*

Motivated by these principles, we introduce Preference As Reward (PAR), a novel reward shaping technique (see Figure 1). PAR applies a sigmoid function to the centered reward (the difference between the proxy reward r and a reference reward r_{ref}). This design is intuitive: since the policy model is typically initialized from a reference model, the centered reward is initially near zero. The sigmoid function’s steep slope at zero promotes rapid initial learning. Crucially, the sigmoid’s gradual convergence towards its upper bound ensures training stability. We further observe that PAR’s functional form closely resembles the Bradley-Terry model (Bradley and Terry, 1952), interpreting the exponential of the proxy reward as an Elo score (Elo, 1978). In this context, the RL reward $r_{\text{RL}} = \text{sigmoid}(r - r_{\text{ref}})$ can be interpreted as the relative preference of the policy response over the reference response, as determined by the reward model.

We conduct experiments on two base models, Gemma2-2B (Google, 2024) and Llama3-

8B (Meta, 2024), using two widely used RLHF datasets, Ultrafeedback-Binarized (Cui et al., 2023) and HH-RLHF (Bai et al., 2022). The result shows that PAR achieves high winrates on the test set after training of one epoch. We also evaluate its performance on two benchmarks AlpacaEval2.0 (Li et al., 2023) and MT-Bench (Zheng et al., 2023a), the PAR consistently tops the benchmark and achieves a winrate that is at least 5 percentage points higher than that of its competitors. Additionally, PAR is data-efficient, requiring only a single reference reward to perform well. It also remains robust against reward hacking, even after two epochs of training.

In conclusion, our contributions are threefold.

- We propose three key principles for designing effective reward shaping strategies.
- We introduce PAR, a novel reward shaping technique, and analyze its connection to the underlying preferences of the reward model.
- We conduct extensive experiments demonstrating PAR’s superiority in mitigating reward hacking compared to other baselines.

2 Related Work

2.1 Reward Hacking in Traditional RL

Reward hacking arises when an RL agent exploits flaws or ambiguities in the reward function to achieve high rewards without performing the intended task (Weng, 2024). This aligns with Goodhart’s Law: *When a measure becomes a target, it ceases to be a good measure.* For example: A bicycle agent rewarded for not falling and moving toward a goal (but not penalized for moving away) learns to circle the goal indefinitely (Randløv and Alstrøm, 1998). A walking agent in the DMControl suite, rewarded for matching a target speed, learns to walk unnaturally using only one leg (Lee et al., 2021). An RL agent allowed to modify its body grows excessively long legs to fall forward and reach the goal (Ha, 2018). In the Elevator Action ALE game, the agent repeatedly kills the first enemy on the first floor to accumulate small rewards (Toromanoff et al., 2019).

Amodei et al. (2016) propose several potential mitigation strategies to address reward hacking, including *(1) Adversarial Reward Functions:* Treating the reward function as an adaptive agent capable of responding to new strategies where the model achieves high rewards but receives low human ratings. *(2) Model Lookahead:* Assigning

rewards based on anticipated future states; for example, penalizing the agent with negative rewards if it attempts to modify the reward function (Everitt et al., 2016). (3) *Adversarial Blinding*: Restricting the model’s access to specific variables to prevent it from learning information that could facilitate reward hacking (Ajakan et al., 2015). (4) *Careful Engineering*: Designing systems to avoid certain types of reward hacking by isolating the agent’s actions from its reward signals, such as through sandboxing techniques (Babcock et al., 2016). (5) *Trip Wires*: Deliberately introducing vulnerabilities into the system and setting up monitoring mechanisms to detect and alert when reward hacking occurs.

2.2 Reward Hacking in RLHF of LLMs

Reward hacking in RLHF for large language models has been extensively studied. Gao et al. (2023) systematically investigate the scaling laws of reward hacking in small models, while Wen et al. (2024) demonstrate that language models can learn to mislead humans through RLHF. Beyond exploiting the training process, reward hacking can also target evaluators. Although using LLMs as judges is a natural choice given their increasing capabilities, this approach is imperfect and can introduce biases. For instance, LLMs may favor their own responses when evaluating outputs from different model families (Liu et al., 2024b) or exhibit positional bias when assessing responses in sequence (Wang et al., 2023).

To mitigate reward hacking, several methods have been proposed. Reward ensemble techniques have shown promise in addressing this issue (Eisenstein et al., 2023; Ram’e et al., 2024; Ahmed et al., 2024; Coste et al., 2023; Zhang et al., 2024), and shaping methods have also proven straightforward and effective (Yang et al., 2024; Jinnai et al., 2024). Miao et al. (2024) introduce an information bottleneck to filter irrelevant noise, while Moskovitz et al. (2023) employ constrained RLHF to prevent reward over-optimization. Chen et al. (2024) propose the ODIN method, which uses a linear layer to separately output quality and length rewards, reducing their correlation through an orthogonal loss function. Similarly, Sun et al. (2023) train instructable reward models to give a more comprehensive reward signal from multiple objectives. Dai et al. (2023) constrain reward magnitudes using regularization terms. Liu et al. (2024a) curate diverse pairwise training data. Additionally, post-




Figure 2: Loss curves from PPO training show that PAR exhibits greater stability, particularly in critic loss, compared to Vanilla training. This stability is attributed to PAR’s bounded RL reward.

processing techniques have been explored, such as the log-sigmoid centering transformation introduced by Wang et al. (2024).

3 Method

3.1 Design Principles

As detailed in Section 1, we restate our three design principles here: (1) RL reward is ideally bounded, (2) RL benefits from rapid initial growth followed by gradual convergence, and (3) RL reward is best formulated as a function of centered reward. To elucidate the rationale behind these principles, we examine the Proximal Policy Optimization (PPO) policy and critic loss functions (notation detailed in Table 3):

$$\mathcal{L}_{\text{policy}}(\theta) = \hat{\mathbb{E}}_t \left[\min \left(\frac{\pi_{\theta}(y_t|x, y_{<t})}{\pi_{\theta_{\text{old}}}(y_t|x, y_{<t})} \cdot \hat{A}_t, \text{clip} \left(\frac{\pi_{\theta}(y_t|x, y_{<t})}{\pi_{\theta_{\text{old}}}(y_t|x, y_{<t})}, 1 - \epsilon, 1 + \epsilon \right) \cdot \hat{A}_t \right) \right],$$

$$\mathcal{L}_{\text{critic}}(\alpha) = \hat{\mathbb{E}}_t [\|V_{\alpha}(x, y_{<t}) - G_t\|_2^2].$$

For the policy loss, $\hat{A}_t = \sum_{l=t}^T (\gamma\lambda)^{l-t} \delta_l$ represents the generalized advantage estimation (GAE) at token t , where $\delta_t = r_t + \gamma V_{\alpha_{\text{old}}}(s_{t+1}) - V_{\alpha_{\text{old}}}(s_t)$ is the temporal difference (TD) error. π_{θ} denotes the current policy model, and $\pi_{\theta_{\text{old}}}$ refers to the policy model from the previous iteration. $V_{\alpha_{\text{old}}}$ is the critic’s value function from the previous iteration. For the critic loss, $G_t = \sum_{l=t}^T \gamma^{l-t} r_l$ represents the return, defined as the discounted sum of per-token rewards.

The per-token reward at position t , denoted as r_t , is defined as:

$$r_t = \begin{cases} r_{\text{RL}} - \eta \log \frac{\pi_{\theta}(y_t|x, y_{<t})}{\pi_{\text{ref}}(y_t|x, y_{<t})} & \text{if } t = T \\ -\eta \log \frac{\pi_{\theta}(y_t|x, y_{<t})}{\pi_{\text{ref}}(y_t|x, y_{<t})} & \text{if } t < T \end{cases}$$

This formulation ensures that the final token receives the RL reward r_{RL} while earlier tokens are shaped by the KL divergence regularization term.

The first principle, advocating for bounded RL rewards, is crucial for stabilizing critic training. Excessively large rewards can hinder the critic model’s ability to accurately learn the value function, as illustrated in Figure 2. We hypothesize that this issue arises from the nature of the regression loss used in the critic model. Specifically, large reinforcement learning rewards r_{RL} lead to large returns G_t , making the critic loss $\mathcal{L}_{\text{critic}}(\alpha)$ more challenging to optimize. Furthermore, this effect propagates to the excessive advantage estimate \hat{A}_t , rendering it unstable and leading to overly aggressive policy updates.

The second principle focuses on regulating the rate of change in the advantage function. A rapid change early in training encourages the policy model to learn quickly, while a slower change toward the end of training helps prevent the policy model from collapsing. We posit that this behavior is due to the advantage function’s role in controlling both the direction and magnitude of the policy model’s optimization steps.

Finally, the third principle addresses the per-prompt problem, where certain prompts are inherently assigned higher rewards by the reward model, regardless of the actual quality of the generated responses. By centering the reward around a reference response, we focus on relative improvement, mitigating the impact of these per-prompt biases.

To operationalize these principles, we explore several candidate functions that satisfy these criteria, including: the sigmoid function $\sigma(x) = \frac{1}{1+e^{-x}}$ and its variants with $\sigma_k(x) = \frac{1}{1+e^{-kx}}$, $k = 2, 3$, the hyperbolic tangent (tanh) function, and a fitted fifth-order polynomial designed to approximate the sigmoid function. The corresponding curves for these functions are illustrated in Figure 6.

3.2 Preference as Reward

After careful consideration and empirical evaluation, we recommend using the sigmoid function applied to centered rewards as the preferred reward shaping method. The sigmoid function is bounded, has the steepest slope at the initial point (zero), and converges gradually to its upper bound of one. This property makes it particularly suitable for stabilizing the RL training process. Furthermore, our analysis reveals that this shaping approach is intrinsically linked to the hidden preferences encoded

within the reward model. The reward model is designed to simulate human preferences, and the RL training process aims to maximize the reward using an RL algorithm. Given a reward model r_ϕ , the hidden preference between two responses y and y' to a prompt x can be expressed as:

$$\mathcal{P}_\phi(y \succ y'|x) = \sigma(r_\phi(x, y) - r_\phi(x, y'))$$

This formulation shows that applying the sigmoid function to centered rewards corresponds precisely to the preference score of the policy response over the reference response. Consequently, we term this method **Preference As Reward (PAR)**, which is defined as follows. To enhance stability, we use multiple M reference rewards:

$$r_{\text{RL}} = \frac{1}{M} \sum_{m=1}^M \sigma(r - r_{\text{ref}}^m) = \frac{1}{M} \sum_{m=1}^M \mathcal{P}_\phi(y \succ y_{\text{ref}}^m)$$

Our proposed PAR method serves exclusively as a reward shaping technique, which is fundamentally orthogonal to other strategies for mitigating reward hacking, such as robust reward model training (Dai et al., 2023) or the construction of diverse datasets (Liu et al., 2024a).

The pseudo-code for the reward shaping procedure under PAR is detailed in Algorithm 4, while the complete implementation of the Proximal Policy Optimization (PPO) algorithm is provided in Algorithm 1. Additionally, the pipeline for reward shaping is illustrated in Figure 1.

4 Experiment

Our analysis is structured to first validate the three key design principles, followed by a comparison of PAR with other reward mitigation methods, and finally, an evaluation of the data efficiency and robustness of PAR.

4.1 Experimental Setting

Datasets and Models We utilize two dialogue datasets: HH-RLHF (Bai et al., 2022) and Ultrafeedback-Binarized (Cui et al., 2023), alongside two base models, Gemma-2B (Google, 2024) and Llama3-8B (Meta, 2024), for our experiments. We present the results of Gemma2-2B on the Ultrafeedback-Binarized in this section. For additional results and comprehensive training details, please refer to Appendix B.

Mitigation Baselines We evaluate seven baseline methods to mitigate reward hacking, which are described as follows:

- **WARM** (Ram’e et al., 2024): This approach combines the weights of multiple reward models and employs the aggregated model to provide rewards for reinforcement learning training.
- **ODIN** (Chen et al., 2024): This method introduces an additional head (length head) during reward training to capture the response length. Only the quality head is utilized for reinforcement learning training.
- **Reg** (Dai et al., 2023): A regularization term is integrated into the reward training loss, defined as: $l_{\text{reward}} = \mathbb{E}_{(x, y_w, y_l) \sim D} [-\log \sigma(r_\phi(x, y_w) - r_\phi(x, y_l)) + \beta \|r_\phi(x, y_w)\|_2^2 + \beta \|r_\phi(x, y_l)\|_2^2]$.
- **Meanstd**: The reward is normalized using the running mean and running standard deviation: $r_{\text{RL}} = \frac{r - \mu}{s}$, where μ and s represent the running mean and standard deviation, respectively.
- **Clip**: The reward is clipped based on the running mean and standard deviation: $r_{\text{RL}} = \text{clip}(r, \mu - s, \mu + s)$.
- **Minmax**: The reward is normalized using the running minimum and maximum rewards: $r_{\text{RL}} = \frac{r - r_{\min}}{r_{\max} - r_{\min}}$, where r_{\max} and r_{\min} denote the running maximum and minimum rewards, respectively.
- **LSC** (Wang et al., 2024): The reward is normalized using the log-sigmoid-centered shaping method, defined as: $r_{\text{RL}} = \log \sigma(r - r_{\text{ref}}^{.85})$ where $r_{\text{ref}}^{.85}$ represents the 85th percentile of the normal distribution, calculated from the mean and variance of the reference rewards.

Evaluation Metrics Two primary metrics are employed to monitor training progress, both computed on the test set: Proxy Reward (shown as a solid line) and Winrate (shown as a dashed line). The winrate measures the policy model’s winning rate against the SFT model, as evaluated by DeepSeek-V3 (DeepSeek-AI, 2024). For the benchmarks AlpacaEval2.0 (Li et al., 2023) and MT-Bench (Zheng et al., 2023a), six metrics are utilized, with all metrics except the length metric being assessed by DeepSeek-V3.

Training Details We briefly outline the training details here; for a comprehensive discussion, please refer to Appendix B. The dataset is preprocessed




Figure 3: PPO training curves over two epochs. ‘ceil5.0’ indicates that $r_{\text{RL}} = \min(r, 5.0)$, and ‘kl0.1’ refers to the KL penalty with $\beta = 0.1$. This figure indicates two important results: (1) Excessive rewards can cause reward hacking, hence the RL reward is ideally bounded. (2) PAR is more robust than Minmax and WARM.

to remove noise, and hyperparameters are carefully tuned to ensure continuous growth in the proxy reward. The SFT model is trained for two epochs on chosen responses with a learning rate of $5e-6$, while the reward model, consisting of a linear head appended to the base model, is trained for one epoch with a learning rate of $5e-6$. The policy model, initialized as the SFT model, is trained for one epoch with a learning rate of $3e-7$, and the critic model, initialized as the reward model, is trained for one epoch with a learning rate of $5e-6$. A linear learning rate scheduler is employed for all training procedures, gradually increasing the learning rate from 0 to the maximum value during the first 0.1 epoch. To generate the reward and winrate curves, the policy model is evaluated on the test set at intervals of 0.1 epochs, yielding 10 checkpoints for each mitigation method.

4.2 Principle One

To validate the first principle that *RL reward is ideally bounded*, we conducted experiments by employing a larger KL penalty coefficient and constraining the maximum reward during reinforcement learning training (see Figure 3). The results demonstrate that limiting excessive rewards significantly mitigates reward hacking. For instance, increasing the KL penalty coefficient from 0.01 to 0.1 leads to a rise in the winrate curve and a corresponding decline in the reward curve. A similar effect is observed when reducing the reward ceiling (i.e., the maximum reward threshold). Furthermore, Figure 3 reveals that while PAR and kl0.1 exhibit comparable proxy rewards, PAR consistently out-




Figure 4: The calibration between hidden preference score given by reward model and winrate given by DeepSeek-V3 for different mitigation methods. For all reward shaping methods, the preference score aligns well with winrate initially followed by sudden winrate decrease as preference score exceeds 0.8, while PAR can effectively resist such decrease by constrain the preference score. As for the methods that modify the reward model itself, there is no calibration at all.

performs kl0.1 in terms of winrate, highlighting the superiority of our proposed PAR method.

We also investigate the calibration between the hidden preference score of the reward model and the winrate provided by DeepSeek-V3 (see Figure 4). For all reward shaping methods, the preference score initially calibrates well with the winrate but deteriorates when the preference score exceeds 0.8. Notably, PAR effectively resists this deterioration by limiting the preference score. In contrast, methods that modify the reward model itself exhibit poor calibration, rendering their results less meaningful.

4.3 Principle Two and Three

To validate the second and third principles—which state that *RL reward is best formulated as a function of centered reward and exhibit rapid initial growth followed by gradual convergence*—we conducted experiments using several sigmoid-like functions, including their centered and uncentered variants, such as tanh, fitted polynomial, sigmoidk2, and sigmoidk3. The results are presented in Figure 5.

We observe that functions applied to centered rewards achieve higher winrates compared to their uncentered counterparts, providing strong support for the third principle. Furthermore, all sigmoid-like functions operating on centered rewards exhibit similar performance, and their shapes (see Figure 6) demonstrate rapid growth near the initial point (zero) and slow convergence toward their up-




Figure 5: Average winrate for different sigmoid-like functions. Here, ‘tanh(centered)’ denotes $r_{\text{RL}} = \frac{1}{M} \sum_{m=1}^M \tanh(r - r_{\text{ref}}^m)$ and ‘tanh(uncentered)’ denotes $r_{\text{RL}} = \tanh(r)$. Note that ‘sigmoid(centered)’ corresponds to our PAR method. The number of reference rewards for the centered method is $M = 10$. RL reward that formulated as a function of centered reward achieves higher winrate than its uncentered counterpart.




Figure 6: The mathematical formulation for the sigmoid-like function is given by $\sigma_k(x) = \frac{1}{1+e^{-kx}}$, where $k = 2, 3$ corresponds to sigmoidk2 and sigmoidk3, respectively. The poly_fitted is a fifth-order polynomial function fitted to approximate the sigmoid function.

per bound (one). Notably, the centered reward is initially zero because the policy model is initialized as the reference model. By combining the properties of sigmoid-like functions with centered rewards, we ensure that the RL reward exhibits the intended behavior of rapid initial growth and gradual convergence. We also evaluate a function that increases slowly at the beginning but accelerates towards the end, referred to as SgFc. This function is a bounded function of centered reward, and its curve is depicted in Figure 6. As shown in Figure 7, SgFc exhibits a lower winrate compared to PAR in the initial stages and also demonstrates reward hacking issues in later stages. This behavior aligns with the second principle, further validating its implications.




Figure 7: PPO training curve for different mitigation methods on Gemma2-2B and Ultrafeedback-Binarized. Solid lines denote the Proxy Reward, and dashed lines denote the Winrate. Vanilla PPO demonstrates significant reward hacking. ODIN, Reg, Meanstd, Clip, and LSC fail to mitigate this issue, indicated by increasing proxy rewards but decreasing winrates. PAR achieves highest winrate at the end of training.

4.4 PAR Effectively Mitigates Reward Hacking

Reward and Winrate Curve As illustrated in Figure 7, the Vanilla PPO suffers from the reward hacking problem severely. To address this issue, we conduct a comprehensive study of several mitigation methods. While some approaches, such as ODIN, Reg, Meanstd, Clip, and LSC, fail to mitigate the problem, others, including WARM, Minmax, and PAR, demonstrate varying degrees of effectiveness over a single training epoch. Notably, the PAR method achieves the highest winrate by the end of the training process.

Another intriguing observation is that Vanilla, Meanstd, Clip, and LSC exhibit hacking behavior when the proxy reward reaches a specific threshold, such as 6.0, as shown in Figure 7. In contrast, Minmax and PAR show no signs of hacking, and their proxy rewards do not exceed this threshold.

Benchmark Performance We further investigate the generalization ability of the policy model on out-of-distribution (OOD) data. For each mitigation method, we select the checkpoint after one epoch of training and evaluate these checkpoints on two benchmarks: AlpacaEval2.0 and MT-bench. The results, presented in Table 1, align with the training curve depicted in Figure 7. The Vanilla PPO method exhibits complete deterioration, while the top-performing methods are PAR, Minmax, and

WARM.

To assess whether PAR enhances peak performance—defined as the performance of the best checkpoint on the benchmark—we select the checkpoint with the highest winrate on the test set during a single PPO training epoch for each mitigation method and compare their performance on the benchmarks. The results, shown in Table 2, indicate that all mitigation methods achieve comparable peak performance.

4.5 PAR is Data Efficient

The default number of reference rewards for each prompt in our PAR method is set to 10. However, we hypothesize that this number may be higher than necessary for PAR to function effectively. To explore this, we conduct an experiment to determine the minimum number of reference rewards required for PAR to perform efficiently. As shown in Figure 8, the results reveal that PARref1 to PARref10 exhibit similar trends in both proxy reward and winrate during training. This suggests that a single reference reward is sufficient for PAR to operate effectively. In contrast, the sigmoid method, which can be viewed as a variant of PAR without any reference rewards, performs significantly worse than PARref1. This indicates that completely eliminating reference rewards is not feasible for maintaining performance.

Method	AlpacaEval2.0			MT-Bench		
	LC Winrate(%) ↑	Winrate(%) ↑	Length ↓	T1 ↑	T2 ↑	Overall ↑
SFT	50.000	50.000	899	5.150	3.975	4.563
Vanilla	0.100	0.370	2008	2.150	1.700	1.925
WARM	60.670	63.170	1073	5.525	3.938	4.731
ODIN	0.000	0.000	3672	1.375	1.338	1.356
Reg	0.000	0.000	1868	1.513	1.388	1.450
Meanstd	0.030	0.120	3183	1.713	1.300	1.506
Clip	0.000	0.000	3096	1.288	1.225	1.256
Minmax	66.980	70.930	1159	5.750	4.013	4.881
LSC	47.560	53.790	1556	5.538	4.100	4.819
PAR	70.810	75.370	1207	5.813	4.313	5.063

Table 1: In our evaluation, the checkpoint after one epoch of PPO training is selected for comparison, while the SFT model checkpoint is chosen after two epochs of training. The results indicate that PAR consistently achieves superior performance across all benchmark metrics.

Method	AlpacaEval2.0	MT-Bench
	LC Winrate(%) ↑	Overall ↑
SFT	50.00	4.56
Vanilla	70.48	4.94
WARM	70.03	4.83
ODIN	68.96	5.06
Reg	69.44	4.74
Meanstd	69.88	4.90
Clip	70.55	4.92
Minmax	68.95	4.81
LSC	72.24	4.89
PAR	69.43	4.93

Table 2: For comparison, we select the checkpoint with the highest win rate on the test set within one epoch of PPO training. For the SFT model, we utilize the checkpoint obtained after two epochs of training. All methods exhibit comparable peak performance during the training process.

4.6 PAR is Robust

To assess the robustness of the mitigation methods discussed earlier, we select the top three performing methods on benchmarks: PAR, Minmax, and WARM. For a more comprehensive evaluation, we extend the training process to two epochs instead of one. The rationale is that if a mitigation method can effectively address the reward hacking problem even under prolonged training, it can be considered robust. The training curves for proxy reward and winrate are presented in Figure 3.

Among the three methods, it is evident that Minmax and WARM lack robustness when the training process is extended to two epochs. In contrast, PAR demonstrates consistent robustness throughout the extended training period. Notably, PAR




Figure 8: PPO training curves, evaluated across varying numbers of reference rewards for the PAR method. E.g., the PAR5 means $r_{RL} = \frac{1}{5} \sum_{m=1}^5 \sigma(r - r_{ref}^m)$. Single reference reward is suffice for PAR to achieve comparable winrate.

consistently achieves the highest winrate among all methods, further highlighting its effectiveness and reliability in mitigating reward hacking over extended training durations.

5 Discussion

Reward shaping is not applicable to DPO (Rafailov et al., 2023), as it does not require a reward model during training. We also explore online DPO, which employs the policy model to generate two responses, and the reward model selects the response with the higher reward as the chosen response and the lower reward as the rejected response. However, since most reward shaping techniques are monotonic, they do not alter the binary preference and therefore, they do not influence the training procedure of online DPO.

For GRPO (Shao et al., 2024), we argue that its advantage calculation inherently normalizes the

proxy reward, making linear transformations (e.g., Minmax and mean_std) ineffective. However, our non-linear PAR demonstrates slightly better performance than Vanilla GRPO in later stages (see Appendix G). An important observation is that GRPO does not exhibit the reward hacking problem during training, primarily because its advantage calculation effectively normalizes the rewards. Although the win rate decreases in the later stages, the proxy rewards also decrease proportionally, maintaining alignment between the optimization objective and the desired outcomes.

6 Conclusion

We identify that for a given reward model, there exists a specific threshold beyond which the proxy reward becomes both meaningless and inaccurate. Based on this observation, we establish three fundamental principles for designing reward shaping methods.

In alignment with these principles, we propose an effective shaping method, Preference As Reward (PAR). Through extensive experimentation with various mitigation approaches, our results demonstrate that PAR not only outperforms other baseline methods by the end of one training epoch but also maintains a high winrate after two epochs of training. Notably, PAR is also data-efficient, requiring only a single reference reward to achieve strong performance.

Limitations

Although our PAR method effectively mitigates reward hacking, it does not improve peak performance, as measured by the winrate of the best checkpoint. Furthermore, its design principles lack precision. While PAR sets the upper bound of the RL reward to 1.0, alternative bounds and their selection criteria remain unexplored. Additionally, the dynamics of reward adjustment—such as the initial rate of increase and the pace of convergence—are not fully elucidated.

Ethical Considerations

Our research addresses the ethical challenges of reward hacking in RLHF by proposing a method to mitigate this problem. By ensuring robust alignment with human values, enhancing transparency in reward design, and proactively addressing biases and safety risks, our approach aims to develop

RLHF systems that are fair, reliable, and aligned with societal well-being.

References

- Ahmed M. Ahmed, Rafael Rafailov, Stepan Sharkov, Xuechen Li, and Sanmi Koyejo. 2024. [Scalable ensembling for mitigating reward overoptimisation](#). *Preprint*, arXiv:2406.01013.
- Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, and Mario Marchand. 2015. [Domain-adversarial neural networks](#). *Preprint*, arXiv:1412.4446.
- Dario Amodei, Chris Olah, Jacob Steinhardt, Paul Christiano, John Schulman, and Dan Mané. 2016. Concrete problems in ai safety. *arXiv preprint arXiv:1606.06565*.
- James Babcock, János Kramár, and Roman Yampolskiy. 2016. The agi containment problem. In *Artificial General Intelligence: 9th International Conference, AGI 2016, New York, NY, USA, July 16-19, 2016, Proceedings 9*, pages 53–63. Springer.
- Yuntao Bai, Andy Jones, Kamal Ndousse, Amanda Askell, Anna Chen, Nova DasSarma, Dawn Drain, Stanislav Fort, Deep Ganguli, Tom Henighan, Nicholas Joseph, Saurav Kadavath, Jackson Kernion, Tom Conerly, Sheer El-Showk, Nelson Elhage, Zac Hatfield-Dodds, Danny Hernandez, Tristan Hume, Scott Johnston, Shauna Kravec, Liane Lovitt, Neel Nanda, Catherine Olsson, Dario Amodei, Tom Brown, Jack Clark, Sam McCandlish, Chris Olah, Ben Mann, and Jared Kaplan. 2022. [Training a helpful and harmless assistant with reinforcement learning from human feedback](#). *Preprint*, arXiv:2204.05862.
- Ralph Allan Bradley and Milton E. Terry. 1952. [Rank analysis of incomplete block designs: I. the method of paired comparisons](#). *Biometrika*, page 324.
- Lichang Chen, Chen Zhu, Davit Soselia, Jiu-hai Chen, Tianyi Zhou, Tom Goldstein, Heng Huang, Mohammad Shoeybi, and Bryan Catanzaro. 2024. [Odin: Disentangled reward mitigates hacking in rlhf](#). *ArXiv*, abs/2402.07319.
- Thomas Coste, Usman Anwar, Robert Kirk, and David Krueger. 2023. Reward model ensembles help mitigate overoptimization. *arXiv e-prints*, pages arXiv–2310.
- Ganqu Cui, Lifan Yuan, Ning Ding, Guanming Yao, Wei Zhu, Yuan Ni, Guotong Xie, Zhiyuan Liu, and Maosong Sun. 2023. [Ultrafeedback: Boosting language models with high-quality feedback](#). *Preprint*, arXiv:2310.01377.
- Josef Dai, Xuehai Pan, Ruiyang Sun, Jiaming Ji, Xinbo Xu, Mickel Liu, Yizhou Wang, and Yaodong Yang. 2023. [Safe rlhf: Safe reinforcement learning from human feedback](#). *ArXiv*, abs/2310.12773.

- DeepSeek-AI. 2024. [Deepseek-v3 technical report](#). *Preprint*, arXiv:2412.19437.
- Jacob Eisenstein, Chirag Nagpal, Alekh Agarwal, Ahmad Beirami, Alex D’Amour, Dj Dvijotham, Adam Fisch, Katherine Heller, Stephen R. Pfohl, Deepak Ramachandran, Peter Shaw, and Jonathan Berant. 2023. [Helping or herding? reward model ensembles mitigate but do not eliminate reward hacking](#). *ArXiv*, abs/2312.09244.
- ArpadE. Elo. 1978. The rating of chessplayers, past and present.
- Tom Everitt, Daniel Filan, Mayank Daswani, and Marcus Hutter. 2016. [Self-modification of policy and utility function in rational agents](#). *Preprint*, arXiv:1605.03142.
- Benjamin Eysenbach, Ruslan Salakhutdinov, and Sergey Levine. 2019. [Search on the replay buffer: Bridging planning and reinforcement learning](#). *Preprint*, arXiv:1906.05253.
- Leo Gao, John Schulman, and Jacob Hilton. 2023. Scaling laws for reward model overoptimization. In *International Conference on Machine Learning*, pages 10835–10866. PMLR.
- Google. 2024. [Gemma](#). Accessed: 2025-02-24.
- Daya Guo, Qihao Zhu, Dejian Yang, Zhenda Xie, Kai Dong, Wentao Zhang, Guanting Chen, Xiao Bi, Y. Wu, Y. K. Li, Fuli Luo, Yingfei Xiong, and Wenfeng Liang. 2024. [Deepseek-coder: When the large language model meets programming – the rise of code intelligence](#). *Preprint*, arXiv:2401.14196.
- David Ha. 2018. [Reinforcement learning for improving agent design](#). *arXiv preprint arXiv:1810.03779*. <https://designrl.github.io>.
- Yuu Jinnai, Tetsuro Morimura, Kaito Ariu, and Kenshi Abe. 2024. [Regularized best-of-n sampling to mitigate reward hacking for language model alignment](#). *Preprint*, arXiv:2404.01054.
- Kimin Lee, Laura Smith, and Pieter Abbeel. 2021. [Pebble: Feedback-efficient interactive reinforcement learning via relabeling experience and unsupervised pre-training](#). *Preprint*, arXiv:2106.05091.
- Xuechen Li, Tianyi Zhang, Yann Dubois, Rohan Taori, Ishaan Gulrajani, Carlos Guestrin, Percy Liang, and Tatsunori B. Hashimoto. 2023. [AlpacaEval: An automatic evaluator of instruction-following models](#). https://github.com/tatsu-lab/alpaca_eval.
- Tianqi Liu, Wei Xiong, Jie Ren, Lichang Chen, Junru Wu, Rishabh Joshi, Yang Gao, Jiaming Shen, Zhen Qin, Tianhe Yu, Daniel Sohn, Anastasiia Makarova, Jeremiah Liu, Yuan Liu, Bilal Piot, Abe Ittycheriah, Aviral Kumar, and Mohammad Saleh. 2024a. [Rrm: Robust reward model training mitigates reward hacking](#). *Preprint*, arXiv:2409.13156.
- Yiqi Liu, Nafise Sadat Moosavi, and Chenghua Lin. 2024b. [Llms as narcissistic evaluators: When ego inflates evaluation scores](#). *Preprint*, arXiv:2311.09766.
- Meta. 2024. [Llama 3 model card](#). Accessed: 2025-02-24.
- Yuchun Miao, Sen Zhang, Liang Ding, Rong Bao, Lefei Zhang, and Dacheng Tao. 2024. [Inform: Mitigating reward hacking in rlhf via information-theoretic reward modeling](#). *Preprint*, arXiv:2402.09345.
- Ted Moskovitz, Aaditya K. Singh, DJ Strouse, Tuomas Sandholm, Ruslan Salakhutdinov, Anca D. Dragan, and Stephen McAleer. 2023. [Confronting reward model overoptimization with constrained rlhf](#). *Preprint*, arXiv:2310.04373.
- OpenAI. 2024. [Gpt-4 technical report](#). *Preprint*, arXiv:2303.08774.
- Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul F Christiano, Jan Leike, and Ryan Lowe. 2022. [Training language models to follow instructions with human feedback](#). In *Advances in Neural Information Processing Systems*, volume 35, pages 27730–27744. Curran Associates, Inc.
- Andrew Patterson, Victor Liao, and Martha White. 2023. [Robust losses for learning value functions](#). *Preprint*, arXiv:2205.08464.
- Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. 2023. [Direct preference optimization: Your language model is secretly a reward model](#). In *Advances in Neural Information Processing Systems*, volume 36, pages 53728–53741. Curran Associates, Inc.
- Alexandre Ram’e, Nino Vieillard, L’eonard Hussenot, Robert Dadashi, Geoffrey Cideron, Olivier Bachem, and Johan Ferret. 2024. [Warm: On the benefits of weight averaged reward models](#). *ArXiv*, abs/2401.12187.
- Jette Randløv and Preben Alstrøm. 1998. [Learning to drive a bicycle using reinforcement learning and shaping](#). In *International Conference on Machine Learning*.
- John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. 2017. [Proximal policy optimization algorithms](#). *ArXiv*, abs/1707.06347.
- Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. 2024. [Deepseekmath: Pushing the limits of mathematical reasoning in open language models](#). *Preprint*, arXiv:2402.03300.

- Prasann Singhal, Tanya Goyal, Jiacheng Xu, and Greg Durrett. 2023. A long way to go: Investigating length correlations in rlhf. *arXiv preprint arXiv:2310.03716*.
- Zhiqing Sun, Yikang Shen, Hongxin Zhang, Qinrong Zhou, Zhenfang Chen, David D Cox, Yiming Yang, and Chuang Gan. 2023. Salmon: Self-alignment with principle-following reward models. *CoRR*.
- Marin Toromanoff, Emilie Wirbel, and Fabien Moutarde. 2019. Is deep reinforcement learning really superhuman on atari? leveling the playing field. *Preprint*, arXiv:1908.04683.
- Peiyi Wang, Lei Li, Liang Chen, Zefan Cai, Dawei Zhu, Binghuai Lin, Yunbo Cao, Qi Liu, Tianyu Liu, and Zhifang Sui. 2023. Large language models are not fair evaluators. *Preprint*, arXiv:2305.17926.
- Zihao Wang, Chirag Nagpal, Jonathan Berant, Jacob Eisenstein, Alex D’Amour, Oluwasanmi Koyejo, and Victor Veitch. 2024. Transforming and combining rewards for aligning large language models. *ArXiv*, abs/2402.00742.
- Jiaxin Wen, Ruiqi Zhong, Akbir Khan, Ethan Perez, Jacob Steinhardt, Minlie Huang, Samuel R. Bowman, He He, and Shi Feng. 2024. Language models learn to mislead humans via rlhf. *Preprint*, arXiv:2409.12822.
- Lilian Weng. 2024. Reward hacking in reinforcement learning. *lilianweng.github.io*.
- Rui Yang, Ruomeng Ding, Yong Lin, Huan Zhang, and Tong Zhang. 2024. Regularizing hidden states enables learning generalizable reward model for llms. *Preprint*, arXiv:2406.10216.
- Shun Zhang, Zhenfang Chen, Sunli Chen, Yikang Shen, Zhiqing Sun, and Chuang Gan. 2024. Improving reinforcement learning from human feedback with efficient reward model ensemble. *Preprint*, arXiv:2401.16635.
- Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. 2023a. Judging llm-as-a-judge with mt-bench and chatbot arena. *Preprint*, arXiv:2306.05685.
- Rui Zheng, Shihan Dou, Songyang Gao, Yuan Hua, Wei Shen, Binghai Wang, Yan Liu, Senjie Jin, Qin Liu, Yuhao Zhou, Limao Xiong, Lu Chen, Zhiheng Xi, Nuo Xu, Wenbin Lai, Minghao Zhu, Cheng Chang, Zhangyue Yin, Rongxiang Weng, Wensen Cheng, Haoran Huang, Tianxiang Sun, Hang Yan, Tao Gui, Qi Zhang, Xipeng Qiu, and Xuanjing Huang. 2023b. Secrets of rlhf in large language models part i: Ppo. *Preprint*, arXiv:2307.04964.

Symbol	Meaning
\mathcal{D}	Dataset
$x, y_w, y_l \sim \mathcal{D}$	Prompt, chosen response, rejected response in Dataset
π_θ	Policy model
π_{ref}	Reference model, also the SFT model
r_ϕ	Reward model
V_α	Critic model
$y \sim \pi_\theta(\cdot x)$	The response generated by policy model for prompt x
$y_{\text{ref}} \sim \pi_{\text{ref}}(\cdot x)$	Reference response, the response generated by reference model
$r = r_\phi(x, y)$	Proxy reward, the reward given directly by reward model
$r_{\text{ref}} = r_\phi(x, y_{\text{ref}})$	Reference reward, the proxy reward for reference response
$\mathcal{P}_\phi(y > y_{\text{ref}} x) = \text{sigmoid}(r - r_{\text{ref}})$	The hidden preference of reward model r_ϕ
$r_{\text{centered}} = r - r_{\text{ref}}$	Centered reward, the proxy reward subtracted by reference reward.
$r_{\text{RL}} = f(r_{\text{centered}})$	RL reward, the reward for RL training
$s_t = [x, y_1, \dots, t]$	The state at position t
$a_t = y_{t+1}$	The Action taken at position t
$\hat{A}_t = \sum_{l=t}^T (\gamma\lambda)^{l-t} \delta_l$	The generalized advantage estimation (GAE)
$\delta_t = r_t + \gamma V_{\alpha_{\text{old}}}(s_{t+1}) - V_{\alpha_{\text{old}}}(s_t)$	The temporal difference (TD) error
$G_t = \sum_{l=t}^T \gamma^{l-t} r_l$	The return
$r_t = \begin{cases} r_{\text{RL}} - \eta \log \frac{\pi_\theta(y_t x, y < t)}{\pi_{\text{ref}}(y_t x, y < t)} & \text{if } t = T \\ -\eta \log \frac{\pi_\theta(y_t x, y < t)}{\pi_{\text{ref}}(y_t x, y < t)} & \text{if } t < T \end{cases}$	The per token reward

Table 3: Summary of notations.

A Notations

The definitions of the notations used in this paper are summarized in Table 3.

B Training Details

Dataset Our experiments are conducted on two datasets: Ultrafeedback-Binarized (Cui et al., 2023) and the helpful-base subset of HH-rlhf (Bai et al., 2022). Both datasets undergo preprocessing to eliminate noise and constrain their overall length. For the Ultrafeedback-Binarized dataset, we select examples where the prompt length, chosen response length, and rejected response length are each less than 512 tokens. Additionally, we ensure that the chosen response score exceeds the rejected response score and that the substring 'confidence' does not appear in either the chosen or rejected responses. For the HH-rlhf dataset, we apply the same length constraints (prompt, chosen, and rejected responses each under 512 tokens). Furthermore, we ensure that each prompt appears only once across both datasets and limit the test set to 256 examples. The training set of Ultrafeedback-Binarized contains around 33,000 examples and HH-RLHF helpful base contains 43,000 examples. All training are carried on 8*A800(80G) GPUs.

Base Models For the base models, we utilize Gemma-2B (Google, 2024) and Llama3-8B (Meta, 2024). In all training procedures, we implement a linear learning rate scheduler, which gradually

increases the learning rate from 0 to the maximum value over the first 0.1 epoch.

SFT Model The Supervised Fine-Tuned (SFT) model is initialized from the base model and trained on the chosen responses for two epochs with a learning rate of 5e-6. Gradient norm clipping is applied when the norm exceeds 10.

Reward Model The reward model is initialized from the base model, with the logit head replaced by a linear head above the last embedding layer to output a scalar value. It is trained for one epoch with a learning rate of 5e-6, achieving an accuracy of approximately 70% on the test set. Gradient norm clipping is applied when the norm exceeds 5.

For ODIN training, we use two linear heads to output length reward and quality reward separately, following the training loss described in Chen et al. (2024). Only the quality head is used during RL training.

For WARM training, we train five reward models on the same dataset with varying learning rates (3e-6, 4e-6, 5e-6, 6e-6, 7e-6) and different random seeds.

For Reg training, we adopt the loss function from (Dai et al., 2023), with a regularization term coefficient of 0.005.

Policy Model The policy model is initialized from the SFT model and trained on the same prompts for one epoch using the PPO algorithm with a learning rate of 3e-7. Gradient norm clipping

is applied when the norm exceeds 5.

Critic Model The critic model is initialized from the reward model and trained alongside the policy model for one epoch with a learning rate of $5e-6$. Gradient norm clipping is applied when the norm exceeds 5.

Hyper-Parameters Responses are sampled from the policy model using a temperature of 0.9, with top-k set to 50, top-p set to 0.9, and a length penalty of 2. The coefficient for the KL penalty is 0.005, and the default number of reference rewards is 10. For PPO training, the buffer size is set to 4, with $\epsilon = 0.2$, $\lambda = 0.95$, $\gamma = 1.0$. For GRPO training, the $\epsilon = 0.2$, the buffer size is 4, and the group size is 5.

C Evaluation

C.1 Winrate on Test Set

To leverage the strong grading capability of DeepSeek-V3 for comparing the SFT model and the policy model on the test set, we design a detailed evaluation prompt. The system prompt and user input format are provided in Listing 1 and 2.

To address position bias (Wang et al., 2023), we evaluate each pair of responses twice, alternating their order, and aggregate the scores. Specifically, for two responses A and B, we first evaluate them in the order A-B and then in the order B-A. In each evaluation, the winner receives a score of 1, the loser receives 0, and in the case of a tie, both responses receive 0.5. The final scores of A and B are compared, and the response with the higher score is declared the winner. If the scores are tied, both responses receive 0.5 win counts. The win counts are used to calculate the winrate.

C.2 Benchmark

We also evaluate the model on two benchmarks, using DeepSeek-V3 to simulate human evaluation. The metrics and their meanings are as follows:

AlpacaEval 2.0

- **LC Winrate:** The length-controlled win rate measures the model’s performance while controlling for the length of generated responses. It compares the model’s outputs to a baseline (e.g., the SFT model) and adjusts for the influence of response length on human preferences.
- **Winrate:** The standard win rate measures the proportion of times the model’s outputs are pre-

ferred over the baseline’s outputs in human evaluations.

- **Length:** The average length of the model’s generated responses, measured in tokens or characters, providing insight into the model’s verbosity.

MT-bench

- **T1:** Turn 1 Score evaluates the model’s performance on the first turn of a multi-turn dialogue, assessing relevance, coherence, and informativeness. Scores are normalized as 0-10.
- **T2:** Turn 2 Score evaluates the model’s performance on the second turn, measuring its ability to maintain context and provide consistent, high-quality responses. Scores are also normalized as 0-10.
- **Overall:** The overall score is the average of the T1 and T2 scores, providing a comprehensive evaluation of the model’s performance across both turns.

D More Results

D.1 Llama3-8B and Ultrafeedback Binarized

Figure 10a presents the PPO training curves for different mitigation methods on Llama3-8B with the Ultrafeedback Binarized dataset. PAR demonstrates robustness against reward hacking and maintains a high win rate throughout one epoch of training.

D.2 Gemma2-2B and HH-RLHF

The PPO training curves for various mitigation methods on Gemma2-2B with the HH-RLHF dataset are shown in Figure 10b. PAR exhibits resilience to reward hacking and sustains a high win rate during one epoch of training.

D.3 Llama3-8B and HH-RLHF

Figure 10c illustrates the PPO training curves for different mitigation methods applied to Llama3-8B on the HH-RLHF dataset. While PAR shows signs of reward hacking toward the end of training, it maintains a consistently high win rate (above 60%) for an extended period, from 10,000 to 30,000 steps. We hypothesize that the observed reward hacking in the later stages is due to the convergence rate of the sigmoid function approaching its upper bound.

E Case Study

We identify several patterns of reward hacking observed in Vanilla PPO training, using the checkpoint trained after one epoch for detailed examination. We show the examples in Figure 11.

F PPO Training

PPO (Proximal Policy Optimization) is an online reinforcement learning algorithm that generates a response given a prompt, computes a reward for the response using a reward model, and updates the policy and critic models to maximize the reward.

We employ several PPO techniques to ensure stable training, including advantage normalization (Zheng et al., 2023b), value loss clipping (Paterson et al., 2023), a replay buffer (Eysenbach et al., 2019), per-token KL penalty, and length penalty. The pseudo-code for the PPO algorithm is provided in Algorithm 1.

G Reward Shaping Is Not Applicable to DPO and GRPO

In this section, we explain why monotonous reward shaping techniques, such as PAR, are not applicable to the Direct Preference Optimization (DPO). And why linear shaping techniques are not applicable to the Group Relative Policy Optimization (GRPO) algorithms.

G.1 DPO and Reward Shaping

Vanilla DPO is an offline alignment algorithm that trains the policy model directly on paired responses using a contrastive loss. Since the vanilla DPO algorithm does not rely on an explicit reward model, reward shaping techniques are inherently inapplicable. We also explore an online variant of DPO, which generates two responses for a given prompt and employs a reward model to determine the chosen and rejected responses. The policy model is then trained on these responses (see Algorithm 6). However, any monotonous transformation of the proxy reward will not alter the chosen and rejected responses. For instance, if $r_1 > r_2$, then $f(r_1) > f(r_2)$ for any monotonous function $f(\cdot)$, including PAR. Consequently, PAR is also not applicable to online DPO.

G.2 GRPO and Reward Shaping

For GRPO, the advantage value is computed as a normalization of proxy rewards. Consider a prompt x and N responses y_1, \dots, y_N sampled from the

policy model. A reward model r_ϕ assigns scores r_1, \dots, r_N to each response. The advantage $A_{i,t}$ for response y_i at token position t is given by:

$$A_{i,t} = \frac{r_i - \mu}{s},$$

where $\mu = \frac{1}{N} \sum_{i=1}^N r_i$ and $s = \sqrt{\frac{1}{N} \sum_{i=1}^N (r_i - \mu)^2}$ are the mean and standard deviation of the rewards, respectively.

Assume a linear transformation is applied to the proxy reward, such that $\hat{r} = a \cdot r + b$ ($a > 0$). We prove that the new advantage $\hat{A}_{i,t}$ is identical to the original $A_{i,t}$. First, the new mean $\hat{\mu} = a \cdot \mu + b$, and the new standard deviation $\hat{s} = a \cdot s$. The new advantage is computed as:

$$\begin{aligned} \hat{A}_{i,t} &= \frac{\hat{r}_i - \hat{\mu}}{\hat{s}} = \frac{ar_i + b - (a\mu + b)}{as} \\ &= \frac{ar_i - a\mu}{as} = \frac{r_i - \mu}{s} \\ &= A_{i,t}. \end{aligned}$$

Thus, linear transformations do not influence the advantage calculation in GRPO. Furthermore, since the sigmoid function is a non-linear function, PAR is applicable to GRPO training. We validate this through experiments, as shown in Figure 9. No reward hacking problem is observed in the GRPO training process, as the advantage calculation inherently performs reward normalization.




Figure 9: The training curves for GRPO, evaluated on Gemma2-2B with the Ultrafeedback-Binarized dataset, demonstrate that Vanilla, Meanstd, Minimax exhibit similar proxy rewards throughout the training process. This is because linear transformations of the proxy rewards do not affect the advantage value in GRPO. The PAR is a non-linear function and slightly better before collapse. No reward hacking issue is observed in the GRPO training process, as the advantage calculation inherently normalizes the rewards.

Please act as an impartial evaluator to assess the quality of two responses from different AI assistants to an incomplete dialogue between a user (<|user|>) and an AI assistant (<|assistant|>). The dialogue will be missing the last turn, and both Assistant-A (<Assistant-A response>) and Assistant-B (<Assistant-B response>) are expected to complete it. Focus your evaluation on the following five aspects:

1. Clarity and Relevance: Responses should be concise, directly addressing the question. They should use clear, natural language and remain on-topic.
2. Accuracy and Honesty: Responses must provide factual, truthful information. Disclose limitations or uncertainties when necessary.
3. Ethics and Appropriateness: Ensure the responses are free from harmful, offensive, or discriminatory content.
4. Engagement and Depth: Responses should be engaging, educational, and sufficiently detailed to comprehensively address the user question.
5. Structure and Creativity: Responses should be logically organized and show originality or adaptability when necessary.

Note: The quality of the responses should not be judged solely by their length. Both brevity and detail are important depending on the context of the question. You will be given an incomplete dialogue (<question>) with the last turn left blank. Assistant-A (<Assistant-A response>) and Assistant-B (<Assistant-B response>) have each provided a response to complete the dialogue. Your task is to evaluate each response based on the five criteria above and provide a comparison.

Evaluation Format:

Assistant-A Response:
(Evaluate the quality of Assistant-A response based on the five aspects mentioned above.)

Assistant-B Response:
(Evaluate the quality of Assistant-B response based on the five aspects mentioned above.)


Comparison and Analysis:
Compare and contrast the responses from Assistant-A and Assistant-B to determine which one is more effective overall. Justify your reasoning clearly and concisely.

At the end, output the comparison result for both responses in the following format:
Better: X (X is A, B, or N, representing A is better, B is better, or both are of equal quality)


Listing 1: System Prompt For Winrate Evaluation on Test Set

```
<question>:
{user_question}
<Assistant-A response>:
{policy_response}
<Assistant-B response>:
{sft_response}
```


Listing 2: User Input Template For Winrate Evaluation on Test Set



(a) PPO training curve for different mitigation methods on Llama3-8B and Ultrafeedback-Binarized.



(b) PPO training curve for different mitigation methods on Gemma2-2B and HH-RLHF.



(c) PPO training curve for different mitigation methods on Llama3-8B and HH-RLHF.

Figure 10: PPO training curves for different mitigation methods across various models and datasets.

```
Prompt:
<|user|>i am going to give a ppt presentation on VLSI in aerospace and defence. what
I need is like introduction slide and Overview slide and related contents you
wish to be included give me<|assistant|>

Policy model response:
In enchanting architectural mosaics, fuse captivating cosmic threads VELCRO-ing
silicon's sacred architectural realm with adaptive aeronautical nebulae,
sculpting celestial gardens for efficient holographic compass landmarks.
Seamless Integrated Silicon Graphics (ISG) - .....
```

Listing 3: Gemma2-2B with Ultrafeedback-Binarized

```
Prompt:
<|user|>Can you help compare the price travel for a trip to the Caribbean to a trip
to Las Vegas?<|assistant|>

Policy model response:
Sure! Caribbean travel is a wonderful choice for a vacation. Caribbean destinations
offer some of the most beautiful beaches in the world, and the crystal clear
waters of the Caribbean Sea make for some of the most amazing snorkeling and
diving experiences. Caribbean resorts and hotels offer amenities like fine
dining, swimming pools, spa services, and a number of outdoor activities, such
as sailing, hiking, golfing, and horseback riding...
```

Listing 4: Gemma2-2B with HH-RLHF

```
Prompt:
<|user|>How can creative leaders ensure that their decisions align with their
organization's values and ethics?<|assistant|>

Policy model response:
Embed GDPR-grade encrypted traceability logs to GDPR-compliant audit records via
trusted pipelines, preventing unauthorized backups by blockchain timestamp
sealed secure encrypted logs copies through API certified audits against bespoke
compliance templates signatures, logs' timestamps assigned securely within
SharePoint backups or verified validation privacy signatures plus?,, ...
```

Listing 5: Llama3-8B with Ultrafeedback-Binarized

```
Prompt:
<|user|>What are some salty things I can put in oatmeal?<|assistant|>

Policy model response:
You might add salt, pepper, tomatoes, onions, celery, eggs, beans, yogurt, mushrooms
, tofu, berries, maple syrup, cinnamon, nutmeg, paprika, and dried herbs. Maybe
add some dark chocolate, almonds, walnuts, and pumpkin seeds. And you can also
drink plenty of water, avoid soda and caffeinated drinks, eat healthy carbs and
avoid saturated fats, stay hydrated and watch for high blood pressure, have
sufficient vitamin intake. Sleep at least 8 hours per day, limit your red meat
intake, be active by cooking, swimming, running, weightlifting, and eating
outdoors, eat good fats like olive oil, eat nuts and seeds and go light on salt,
avoid greasy foods and snacks like cheese chips. Get plenty of fresh air, have
fun indoors an outside. Avoid smoking and overeating, and take some time daily
to enjoy your favorite activities, be grateful, and be thankful. Keep active and
move in ways that encourage fitness. Take a deep breath and take a journey!
Make your oatmeal a treat!
```

Listing 6: Llama3-8B with HH-RLHF

Figure 11: Analysis of reward hacking patterns observed in Vanilla PPO training, based on a detailed examination of the model checkpoint after one epoch.

Algorithm 1 PPO

Input: sft model π_{sft} , reward model r_ϕ , prompt set \mathcal{D} .

Output: Aligned model π_{θ^*}

- 1: Initialize policy model $\pi_\theta \leftarrow \pi_{\text{sft}}$
- 2: Initialize reference model $\pi_{\text{ref}} \leftarrow \pi_{\text{sft}}$
- 3: Initialize critic model $V_\alpha \leftarrow r_\phi$
- 4: **for** $x \in \mathcal{D}$ **do**
- 5: ppo_batch = build_ppo_batch($x, \pi_\theta, \pi_{\text{ref}}, V_\alpha, r_\phi$)
- 6: ppo_batch = buffer.substitute(ppo_batch) ▷ sample a ppo_batch from replay buffer and save current ppo_batch into the buffer
- 7: $\mathcal{L}_{\text{ppo}}(\theta), \mathcal{L}_{\text{critic}}(\alpha) = \text{calculate_loss}(\text{ppo_batch}, \pi_\theta, V_\alpha)$
- 8: $\theta \leftarrow \theta - \text{plr} * \nabla_\theta \mathcal{L}_{\text{ppo}}(\theta)$ ▷ update policy model via gradient descent, plr is policy learning rate
- 9: $\alpha \leftarrow \alpha - \text{clr} * \nabla_\alpha \mathcal{L}_{\text{critic}}(\alpha)$ ▷ clr is critic learning rate
- 10: **end for**
- 11: **return** π_{θ^*}

Algorithm 2 build_ppo_batch

Input: prompt x , four models $\pi_\theta, \pi_{\text{ref}}, V_\alpha, r_\phi$.

Output: ppo_batch: A dictionary

- 1: Initialize ppo_batch =
- 2: sample $y \sim \pi_\theta(\cdot|x)$
- 3: sample $y_{\text{ref}}^{1,\dots,M} \sim \pi_{\text{ref}}(\cdot|x)$ ▷ optional
- 4: $r = r_\phi(x, y)$
- 5: $r_{\text{ref}}^{1,\dots,M} = r_\phi(x, y_{\text{ref}}^{1,\dots,M})$ ▷ optional
- 6: $r_{\text{RL}} = \text{reward_reshape}(r, r_{\text{ref}}^{1,\dots,M}, \text{len}(y), \text{mode} = \text{PAR})$
- 7: Now we split (x,y) into $(s_t, a_t)_{t=0}^T$
- 8: $\text{KL_penalty} = \log \pi_\theta(a_t|s_t) - \log \pi_{\text{ref}}(a_t|s_t)$
- 9: construct per-token rewards $r_{1,\dots,T}$ from r_{RL} and KL_penalty
- 10: $V_t = V_\alpha(s_t)$
- 11: Compute GAE \hat{A}_t and Return G_t from V_t and r_t .
- 12: ppo_batch = $(\log \pi_\theta(a_t|s_t), G_t, \hat{A}_t, V_t, s_t, a_t)$
- 13: **return** ppo_batch

Algorithm 3 Buffer.substitute

Input: ppo_batch.

Output: ppo_batch: A dictionary

- 1: Global List pool = []
- 2: Global buffer_size = 4
- 3: IF $\text{len}(\text{pool}) < \text{buffer_size}$:
- 4: pool.append(ppo_batch)
- 5: **return** None
- 6: ELSE:
- 7: selected_batch = random.choice(pool)
- 8: pool.pop(selected_batch)
- 9: pool.append(ppo_batch)
- 10: **return** selected_batch

Algorithm 4 reward_reshape

Input: policy reward r , reference reward $r_{\text{ref}}^{1,\dots,M}$, response length l , reshape mode mode.

Output: RL reward

- 1: IF $l > 300$:
 - 2: $r = r - 0.01 * (l - 300)$ ▷ penalize long response
 - 3: IF mode==meanstd:
 - 4: $r_{\text{RL}} = \frac{r - \mu}{s}$ ▷ μ, s are running mean and running standard variance respectively.
 - 5: IF mode==reward_clip:
 - 6: ...
 - 7: IF mode==PAR:
 - 8: $r_{\text{RL}} = \frac{1}{M} \sum_{m=1}^M \sigma(r - r_{\text{ref}}^m)$
-

Algorithm 5 calculate_loss

Input: ppo_batch, policy model π_θ , critic model V_α .

Output: policy loss $\mathcal{L}_{\text{ppo}}(\theta)$, critic loss $\mathcal{L}_{\text{critic}}(\alpha)$

- 1: $(\log \pi_{\theta_{\text{old}}}(a_t|s_t), G_t, \hat{A}_t, V_t, s_t, a_t) = \text{ppo_batch}$ ▷ Extract elements from ppo_batch
 - 2: $\mathcal{L}_{\text{ppo}}(\theta) = \hat{\mathbb{E}}_t \left[\min \left(\frac{\pi_\theta(a_t|s_t)}{\pi_{\theta_{\text{old}}}(a_t|s_t)} \hat{A}_t, \text{clip} \left(\frac{\pi_\theta(a_t|s_t)}{\pi_{\theta_{\text{old}}}(a_t|s_t)}, 1 - \epsilon, 1 + \epsilon \right) \hat{A}_t \right) \right]$
 - 3: $\mathcal{L}_{\text{critic}}(\alpha) = \hat{\mathbb{E}}_t \left[\max \left(\|V_\alpha(s_t) - G_t\|_2^2, \|\text{clip}(V_\alpha(s_t), V_t - \delta, V_t + \delta) - G_t\|_2^2 \right) \right]$ ▷ Critic clip trick
 - 4: **return** $\mathcal{L}_{\text{ppo}}(\theta), \mathcal{L}_{\text{critic}}(\phi)$
-

Algorithm 6 Online DPO

Input: sft model π_{sft} , reward model r_ϕ , prompt set \mathcal{D} .

Output: Aligned model π_{θ^*}

- 1: Initialize policy model $\pi_\theta \leftarrow \pi_{\text{sft}}$
 - 2: Initialize reference model $\pi_{\text{ref}} \leftarrow \pi_{\text{sft}}$
 - 3: **for** $x \in \mathcal{D}$ **do**
 - 4: Sample $y_1, y_2 \sim \pi_\theta(\cdot|x)$
 - 5: Calculate rewards $r_1 = r_\phi(x, y_1), r_2 = r_\phi(x, y_2)$
 - 6: IF $r_1 > r_2$:
 - 7: $y_w = y_1, y_l = y_2$
 - 8: ELSE:
 - 9: $y_w = y_2, y_l = y_1$
 - 10: $\mathcal{L}_{\text{DPO}}(\theta) = - \left[\log \sigma \left(\beta \left(\log \frac{\pi_\theta(y_w|x)}{\pi_{\text{ref}}(y_w|x)} - \log \frac{\pi_\theta(y_l|x)}{\pi_{\text{ref}}(y_l|x)} \right) \right) \right]$
 - 11: $\theta \leftarrow \theta - lr * \nabla_\theta \mathcal{L}_{\text{DPO}}(\theta)$
 - 12: **end for**
 - 13: **return** π_{θ^*}
-