

The Structural Complexity of Matrix-Vector Multiplication

Emile Anand

Georgia Institute of Technology

EMILE@GATECH.EDU

Jan van den Brand

Georgia Institute of Technology

VDBRAND@GATECH.EDU

Rose McCarty

Georgia Institute of Technology, Princeton University

RMCCARTY3@GATECH.EDU

Abstract

We consider the problem of preprocessing an $n \times n$ matrix \mathbf{M} , and supporting queries that, for any vector v , returns the matrix-vector product $\mathbf{M}v$. This problem has been extensively studied in both theory and practice: on one side, practitioners have developed algorithms that are highly efficient in practice, whereas on the other side, theoreticians have proven that the problem cannot be solved faster than naive multiplication in the worst-case. This lower bound holds even in the average-case, implying that existing average-case analyses cannot explain this gap between theory and practice. Therefore, we study the problem for *structured* matrices. We show that for $n \times n$ matrices of VC-dimension d , the matrix-vector multiplication problem can be solved with $\tilde{O}(n^2)$ preprocessing and $\tilde{O}(n^{2-1/d})$ query time. Given the low constant VC-dimensions observed in most real-world data, our results posit an explanation for why the problem can be solved so much faster in practice. Moreover, our bounds hold even if the matrix does not have a low VC-dimension, but is obtained by (possibly adversarially) corrupting at most a subquadratic number of entries of any unknown low VC-dimension matrix.

In turn, our results also yield the first non-trivial upper bounds for many applications. In previous works, the online matrix-vector (OMv) hypothesis (conjecturing that quadratic time is needed per query, even over the boolean semi-ring) was used to prove many conditional lower bounds, showing that it is impossible to compute and maintain high-accuracy estimates for shortest paths, Laplacian solvers, effective resistance, and triangle detection in graphs subject to node insertions and deletions in subquadratic time. Yet, via a reduction to our matrix-vector-multiplication result, we show we can maintain the aforementioned problems efficiently if the input is structured, providing the first subquadratic upper bounds in the high-accuracy regime.

Keywords: Online Matrix-Vector Multiplication, Boolean Matrix Multiplication, VC dimension, Parameterized Complexity,

Contents

1	Introduction	3
1.1	Our Results	4
1.2	Applications	6
1.3	Further Related Work	8
2	Preliminaries	9
3	The Structural Complexity of Matrix-Vector Multiplication	9
3.1	Matrix Vector Products via Minimum Spanning Trees	10
3.2	Existence of Low Weight Δ -labeled Minimum Spanning Trees	11
3.3	Dynamic Matrices	14
4	Conclusion	14
5	Acknowledgements	14
A	Online Matrix Vector Data Structure	23
A.1	Static Online Matrix Vector Multiplication Data Structure	23
A.2	Dynamic OMv Data Structure	26
A.3	Extension to Structured Non-Boolean Matrices	28
B	Applications	31
B.1	High-accuracy Dynamic Laplacian Solver	31
B.2	Effective Resistance	32
B.3	Triangle Detection	32
B.4	Single-Source Shortest Paths and k-Center	33
C	Characterization of matrices with constant VC-dimension	34
C.1	Examples of low VC-dimension matrices	35

1. Introduction

Computing sequential matrix-vector products is a workhorse of many iterative algorithms in machine learning. In optimization (Renegar, 1996; Vempala et al., 2020; Lin et al., 2023a; Chaudhari et al., 2024), computational geometry (Har-Peled, 2009; Welzl, 1992; Fisikopoulos and Penaranda, 2016), online algorithms (Lin et al., 2024; Anand and Qu, 2024; Murray et al., 2021), and dynamic algorithms (Liu, 2024; Jiang et al., 2023; Anand et al., 2024b; Jin and Xu, 2022; Lin et al., 2023b), sequential matrix-vector products are essential subroutines underlying performant algorithms. The current learning revolution is powered by hardware specifically designed to perform such products, as both neural network evaluation and back-propagation require repeated matrix-vector products (Sørensen, 2012; Rumelhart et al., 1986). Hence, matrix-vector products are arguably one of the most important and fundamental subroutines, with any complexity improvement having wide-ranging implications, and is thus a prevalent research topic in both theory and practice.

The problem can be modeled via the following data structure task: construct a data structure that preprocesses a given $n \times n$ matrix \mathbf{M} . After preprocessing, we want to multiply vectors with \mathbf{M} faster than naive matrix-vector multiplication. Depending on the application, this matrix \mathbf{M} is fixed or the data structure may need to handle changes to \mathbf{M} . For instance, when calculating probabilities of a random walk (e.g., in the PageRank algorithm (Page et al., 1999)), performing the power-method, and evaluating a neural network, the matrix is fixed. On the other hand, in convex optimization problems, such as in solving a linear or semi-definite program, applying Newton-Raphson’s method, and training a neural network, the matrix is either the inverse of a Hessian, or is given by the network’s weights, which changes from one iteration to the next.

Beyond speedups due to improving hardware accelerators, practitioners have made tremendous progress in accelerating the computation of matrix-vector products through heuristics that run in $\text{nnz}(\mathbf{M})$ (the number of non-zero entries of \mathbf{M}) worst-case time, but which are much faster in practice. This has led to speedups in training graph neural networks (Alves et al., 2024) and other learning algorithms (Floros et al., 2024).

While practitioners have had success in accelerating the computation of matrix vector products, from a theory perspective there are substantial lower bounds. Gronlund and Larsen (2015) showed that any $\text{poly}(n)$ -space data structure for arbitrary matrix-vector multiplication over sufficiently large fields (such as \mathbb{R}) require $\Omega(n^2/\log n)$ time. In particular, any “generic” algorithm that does not make assumptions about the specific field needs $\Omega(n^2/\log n)$ time. This quadratic lower bound was also proven for arithmetic circuits (Frandsen et al., 2001). While these are worst-case lower bounds, they also hold for the average case (Henzinger et al., 2022). The only non-trivial upper bounds beating quadratic time are over the Boolean semi-ring (i.e., $\{0, 1\}$ with $x \oplus y = \min(1, x + y)$). Here, the famous mailman algorithm (Liberty and Zucker, 2006) achieves $O(n^2/\log n)$ runtime. In a line of work that reduced the problem to finding neighborhoods in a graph and smaller algebraic products, this query complexity was improved to $O(n^2/\log^2 n)$ (Williams, 2007) and $O(n^{2-o(1)})$ (Larsen and Williams, 2017; Chakraborty et al., 2018; Abboud et al., 2024). However, none of these algorithms are truly subquadratic, i.e., $O(n^{2-\epsilon})$ for some constant $\epsilon > 0$.

Moreover, while the $\Omega(n^2)$ lower bounds only hold for fields, even over the Boolean semi-ring it is conjectured that no truly subquadratic time algorithm exists (Henzinger et al., 2015), referred to as the OMv (online matrix-vector multiplication) conjecture. This has led to a line of works that use the conditional hardness of OMv to prove tight time lower bounds for a host of dynamic algorithms, such as dynamic matrix inversion (Brand et al., 2019a,b), dynamic subgraph connectivity (Henzinger and Neumann, 2016), dynamic regression (Jiang et al., 2023), dynamic range mode (Jin and Xu, 2022), Erickson’s problem and Langerman’s problem (Jin and Xu, 2022), as well as high-dimensional generalizations of Klee’s measure problem (Yildiz and Suri, 2012).

In summary, there is a substantial difference between the perspectives of this problem in theory and practice: there are heuristics that are fast in practice, but from a theoretical perspective the problem is hard, and an entire subarea of fine-grained-complexity has been built on this hardness. Moreover, average-case

analysis cannot explain this difference between theory and practice, as even the average-case is provably hard. In this work, we resolve this conflict. Since the average-case (i.e., random non-structured input) is hard, the observed efficiency of practical algorithms must stem from some inherent structure in the real-world input data. Thus, we must study the complexity for structured inputs.

A popular measure for structural complexity is the Vapnik-Chervonenkis (VC) dimension, which finds many applications in machine learning (Shalev-Shwartz and Ben-David, 2014; Bartlett et al., 2019), structural graph theory (Nguyen et al., 2024; Alon et al., 2016; Karczmarz and Zheng, 2024), computational geometry (Har-Peled, 2009; B. Chazelle, 1989; Fisikopoulos and Penaranda, 2016) (see the preliminaries in Section 2 for a definition of the VC-dimension). Many structured objects studied by theoreticians have inherently low VC dimension. For instance, the hypothesis class of intervals on \mathbb{R} , star and interval graphs, and rank-one projection matrices, have VC-dimension 2, planar graphs have VC dimension 4, and any H -minor free graph has VC dimension at most $|V(H)| - 1$. Beyond being an established complexity measure in theory, it has also been empirically verified that real-world data has low VC dimension (Coudert et al., 2024). This observation can be explained via the following structural characterization of matrices with low VC dimension:

Fact 1 (Proof in Appendix C) *Consider a hereditary class of 0/1-matrices \mathcal{M} , meaning that \mathcal{M} is closed under row/column deletion (i.e., each matrix $\mathbf{M} \in \mathcal{M}$ is still in \mathcal{M} after deleting a row or column). If \mathcal{M} is non-trivial, (i.e., does not contain every possible matrix), then there exists an absolute constant $c \in \mathbb{N}$ such that the VC-dimension of any matrix in \mathcal{M} is at most c .*

Presumably, whatever unknown structure is common in real-world matrices should not be lost when deleting rows/columns. We note that Fact 1 does not preclude other matrices, that do not satisfy this hereditary property, from having constant VC dimension, e.g., adjacency matrices of minor-free graphs.

1.1. Our Results

While theoretical objects such as grid-graphs, intersection graphs, and kernel-matrices have a low VC-dimension, they are not perfect representations of real-world data. For instance, while city street networks in the US are predominantly grid-graphs, there are always exceptions in form of bridges or a few diagonal streets. Exceptions can also occur due to errors in measurements or other corruptions. To capture such *almost low VC-dimension objects*, we define the “corrupted VC-dimension.”

Definition 2 (Corrupted VC-dimension d) *We say that a set system \mathcal{F} on a ground set of size n has “corrupted VC-dimension d ” if there is another set system \mathcal{F}' of VC-dimension $\leq d$ such that \mathcal{F} can be obtained from \mathcal{F}' by adding and/or removing (i.e., corrupting) at most $O(n^{1-1/d})$ elements to/from each set.*

For matrices $\mathbf{M} \in \{0, 1\}^{m \times n}$, the corrupted VC-dimension d is equivalent to the existence of matrices $\mathbf{L} \in \{0, 1\}^{m \times n}$ and $\mathbf{S} \in \{-1, 0, 1\}^{m \times n}$ with $\mathbf{M} = \mathbf{L} + \mathbf{S}$ where \mathbf{L} has VC-dimension d and the corruption matrix \mathbf{S} has at most $O(n^{1-1/d})$ non-zero entries per row, i.e., flipping at most $O(n^{1-1/d})$ bits per row of \mathbf{L} .

Note that merely the existence of such an \mathcal{F}' (i.e., \mathbf{L}) of VC-dimension d suffices for \mathcal{F} (i.e., \mathbf{M}) to have corrupted VC-dimension d . We do not need to know \mathcal{F}' (i.e., \mathbf{L}) or which sets have been corrupted (i.e., \mathbf{S}). Furthermore, set families of corrupted VC-dimension d are strict generalizations of set families of VC-dimension exactly d . Therefore, while we state our main results for matrices with corrupted VC-dimension d , they also hold for general matrices with VC-dimension d .

We now state the theoretical guarantees of our accelerated matrix-vector multiplication algorithm in Theorem 3, where the runtimes are parameterized by the corrupted VC dimension measure.

Theorem 3 (*Static Online Matrix-Vector Multiplication*). *If a matrix $\mathbf{M} \in \{0, 1\}^{m \times n}$ has corrupted VC-dimension d , then after an $\tilde{O}(mn)$ -time preprocessing, there is a data structure \mathcal{D} that can compute $\mathbf{M}v$ for any $v \in \mathbb{R}^n$ in $\tilde{O}(mn^{1-1/d} + n)$ time, with high probability.*

The problem of approximating the VC-dimension of any set system within a $(2 - \epsilon)$ accuracy for any $\epsilon > 0$ is known to be Σ_3^P -hard (Mossel and Umans, 2002); however, for our theorem, the algorithm does not need to know or compute the VC-dimension to achieve this runtime.

This data structure is based on Gasieniec and Lingas (2003) which proposed an algorithm for Boolean matrix multiplication. Their algorithm computes the matrix-matrix product via n matrix-vector products, thus implicitly providing a matrix-vector multiplication data structure as well. Their complexity depends on the weight of the minimum spanning tree defined with respect to the Hamming-distance between the rows of \mathbf{M} . While $O(n^2)$ in worst-case, they conjecture this should be unlikely in real-world data. This data structure was recently independently rediscovered in the graph neural networks community (Alves et al., 2024) where they experimentally verified that the algorithm is indeed efficient on real-world inputs. Our Theorem 3 now gives a theoretical explanation as to why these practical algorithm behave so much more efficient in practice than the worst-case and average-case lower bounds of $\Omega(mn)$.

We obtain Theorem 3 via techniques from computational geometry. A line of works (Welzl, 1988; B. Chazelle, 1989; Matoušek, 1991; Har-Peled, 2009) consider the following *geometric intersection* data structure problem: given a set of points in \mathbb{R}^d , preprocess them. Then, given a convex polytope for each query, return whether any of the points intersect the polytope.

Matrix vector products can be interpreted as $O(m)$ intersection problems if we only care about Boolean outputs, because in the Boolean case $(\mathbf{M}v)_i \neq 0$ if and only if there is an intersection between the position of the non-zero elements in v and the non-zero elements in the i -th row of \mathbf{M} . We show that the computational geometry techniques work even for non-boolean outputs, and we also extend them from bounded VC-dimension to our notion of corrupted VC-dimension. We provide details of this proof in Section 3.2.

At last, we remark that prior work for the geometric intersection problem had exponential preprocessing time (Welzl, 1992) or unspecified polynomial time (Matoušek, 1991).

In addition to our novel complexity bound, we also provide alternative algorithms to that of Gasieniec and Lingas (2003); Alves et al. (2024). We provide more details below.

Dynamic Setting We extend Theorem 3 by allowing \mathbf{M} to undergo row and column updates. The proof is given in Appendix A.2.

Theorem 4 (*Dynamic Online Matrix-Vector Multiplication*). *Given a matrix $\mathbf{M} \in \{0, 1\}^{m \times n}$, there is a data structure \mathcal{D} with $\tilde{O}(mn)$ preprocessing time that supports row and column updates (insertions/deletions) to \mathbf{M} in $\tilde{O}(n)$ and $\tilde{O}(m)$ time respectively. Upon querying the data structure \mathcal{D} with a vector $v \in \mathbb{R}^n$, it outputs $\mathbf{M}v$ in $\tilde{O}(mn^{1-1/d^*} + n)$ time, with high probability, where d^* is the largest corrupted VC-dimension of \mathbf{M} throughout the history of its updates.*

In the special case where the updates to \mathbf{M} keep its corrupted VC-dimension d invariant, each matrix-vector product is computed with high probability in $\tilde{O}(mn^{1-1/d} + n)$ time.

Extensions to Transposed Matrices. Assume we have a small VC-dimension bound on \mathbf{M}^\top , then the VC-dimension of \mathbf{M} could be much larger than that of \mathbf{M}^\top . If d bounds the VC-dimension of \mathbf{M}^\top , then the best bound on the VC-dimension of \mathbf{M} is 2^{d+1} (Assouad, 1983), so Theorem 3 would have only $\tilde{O}(mn^{1-1/2^d})$ query time. To alleviate this substantial slow-down in Theorems 3 and 4, we extend the algorithms so their complexity is also bounded by the VC-dimension of \mathbf{M}^\top .

When $\mathbf{M}^\top \in \{0, 1\}^{n \times m}$ has corrupted VC-dimension d' , we prove analogous versions of Theorems 3 and 4 that allow computing $\mathbf{M}v$ with high probability in $O(nm^{1-1/d'} + m)$ time after a $\tilde{O}(mn)$ -time preprocessing. Thus, if $\mathbf{M} \in \{0, 1\}^{m \times n}$ has corrupted VC-dimension d and $\mathbf{M}^\top \in \{0, 1\}^{n \times m}$ has corrupted

VC-dimension d' , then after an $\tilde{O}(mn)$ -time preprocessing, we can compute $\mathbf{M}v$ in time $\min\{O(mn^{1-1/d} + n, nm^{1-1/d'} + m)\}$. For this, we do not need to know d or d' , as the algorithm automatically achieves the minimum runtime.

Extension to Non-Boolean Matrices. The Pollard pseudodimension is a popular extension of the VC-dimension to non-binary thresholds, which also finds many applications in machine learning (Shalev-Shwartz and Ben-David, 2014; Bartlett et al., 2019) and structural graph theory (Karczmarz and Zheng, 2024) (see the preliminaries in Section 2 for a definition of the Pollard pseudodimension). For a real-valued matrix $\mathbf{M} \in \{0, 1\}^{m \times n}$, if d bounds the Pollard pseudodimension of \mathbf{M} and if A bounds the number of thresholds of \mathbf{M} , then by lemma 29, $\mathbf{M}v$ can be computed in time $\tilde{O}(Amn^{1-1/d} + n)$. For $A \leq \tilde{O}(1)$, this provides a subquadratic runtime.

1.2. Applications

A Scaling technique with Applications to Random Walks and PageRank. Let $\mathbf{A} \in \mathbb{R}^{n \times n}$ be the adjacency matrix of an n -node graph and let $\mathbf{D} \in \mathbb{R}^{n \times n}$ be the diagonal matrix with vertex-degrees on the diagonal. Then the normalized Laplacian is $\tilde{\mathbf{L}} = \mathbf{I} - \mathbf{D}^{-1/2}\mathbf{A}\mathbf{D}^{-1/2}$. Even though $\tilde{\mathbf{L}}$ is not Boolean, we can still use Theorem 3 since $\tilde{\mathbf{L}}v = \mathbf{D}^{-1/2}(w - \mathbf{A}w)$ for $w = \mathbf{D}^{-1/2}v$ and the product $\mathbf{A}w$ can be computed via Theorem 3. The same technique extends to random-walk probability matrices. In turn, this allows fast simulations of Markov chains to compute stationary distributions and iterative computation of the PageRank (Page et al., 1999) via Theorem 3.

Complexity-Theoretic Implications. The Boolean matrix multiplication (BMM) conjecture states that no algorithm can multiply two boolean $n \times n$ matrices in $O(n^{3-\epsilon})$ time for constant $\epsilon > 0$ (Basch et al., 1995; Williams and Williams, 2010). This conjecture is used to prove lower bounds on combinatorial algorithms (i.e., algorithms that do not make use of Strassen-style fast matrix multiplication methods), motivated by the property that fast matrix multiplication, while being theoretically fast (currently $O(n^{2.372})$ Williams et al. (2024)), is very slow in practice due to large constants hidden in O -notation. Hence BMM gives a lower bound on more practical algorithms and can be used to prove that any further complexity improvement would require fast matrix multiplication.

Theorem 3 implies that for matrices with corrupted VC-dimension d , BMM can be solved in $\tilde{O}(n^{3-1/d})$ time, allowing for improved combinatorial upper bounds. BMM was the original motivation for Gasieniec and Lingas (2003). Moreover, as demonstrated in Alves et al. (2024), this algorithm is also highly efficient in practice and does not encounter the large constant of fast matrix multiplication. For matrices of VC-dimension 1, Theorem 3 achieves the optimal matrix-multiplication time of $\tilde{O}(n^2)$ (upto polylogarithmic factors). Through this view, Theorem 3 implies that problems with lower bounds based on BMM, may be solved more efficiently on structured inputs.

Corollary 5 *Suppose we are given Boolean matrices $\mathbf{M}_1, \mathbf{M}_2 \in \{0, 1\}^{n \times n}$, such that \mathbf{M}_i has corrupted VC-dimension d_i and \mathbf{M}_i^\top has corrupted VC dimension d'_i for $i \in \{1, 2\}$. Let $s = \min\{d_1, d_2, d'_1, d'_2\}$. Then, there is an algorithm for boolean matrix multiplication with in $O(n^{3-\frac{1}{s}})$ time complexity.*

Another relevant conjecture is the OMv conjecture, which states that no algorithm can preprocess a Boolean matrix $M \in \{0, 1\}^{n \times n}$ in polynomial time, and then answer n queries that compute $\mathbf{M}v^{(i)}$ for an online sequence of Boolean vectors $v^{(1)}, \dots, v^{(n)} \in \{0, 1\}^n$ in total time $O(n^{3-\epsilon})$. Observe that here the vector $v^{(i+1)}$ is only given after the data structure returned $\mathbf{M}v^{(i)}$, hence the use of fast matrix multiplication to compute the matrix product $\mathbf{M} [v^{(1)} | \dots | v^{(n)}]$ is ruled out.

This conjecture is used to prove conditional lower bounds for many dynamic problems, such as maintaining shortest paths, effective resistances, reachability, maximum flow, bipartite matching, triangle detection, and many others in graphs undergoing vertex insertions and deletions (Henzinger et al., 2015). Even with

use of fast matrix multiplication, no algorithm can beat $O(n^2)$ time on dense graphs, which for many of these problems is equivalent to re-solving them from scratch whenever the graph changes. Since Theorem 3 shows the OMv conjecture does not hold for structured matrices, it opens up improved dynamic algorithms.

We next list some examples of new dynamic algorithms obtained via this technique, whose upper bounds are only achievable due to their structured nature, otherwise violating either the BMM or OMv conjecture.

Implications for Dynamic Algorithms. In the following, we state results for dynamic graph algorithms. These are data structures that maintain some graph property while the underlying graph changes over time. We defer the formal proofs for these results to Appendix B.

An important class of instances of linear equations that arise in practice has the form $\mathbf{L}x = b$, where \mathbf{L} is the Laplacian of an undirected graph $G = (V, E)$ given by $\mathbf{L} := \mathbf{D} - \mathbf{A}$ where \mathbf{D} is a diagonal matrix such that $\mathbf{D}_{i,i} = \deg(i)$ for $i \in [n]$ where $|V| = n$, and \mathbf{A} is the adjacency matrix of the graph. There are Laplacian solvers that run in time nearly linear in the number of edges of the underlying graph (Spielman and Teng, 2004). We study the problem of constructing a dynamic Laplacian solver for $\mathbf{L}_t x = b_t$ where the Laplacian changes over time through vertex updates to the graph, and each b_t is an arbitrary new vector.

Previous upper bounds could only handle a $\text{poly}(1/\epsilon)$ accuracy by maintaining spectral sparsifiers (Abraham et al., 2016; Bernstein et al., 2022) or vertex sparsifiers (Durfee et al., 2019; Chen et al., 2020). Moreover, exact or $O(\log 1/\epsilon)$ -time dependencies are ruled out by the OMv conjecture (since no algorithm beats naive recomputation from scratch in $\tilde{O}(|E|) = \tilde{O}(n^2)$ time via nearly-linear time Laplacian system solvers (Spielman and Teng, 2004)). We provide the first result faster than naive recomputation from scratch in the high-accuracy $\log(1/\epsilon)$ regime.

Theorem 6 (Dynamic Laplacian Solver). *There is a dynamic algorithm that, given a dynamic graph $G = (V, E)$ with corrupted VC-dimension bounded by d , maintains a Laplacian system solver. The data structure supports queries that receive a vector $b \in \mathbb{R}^{|V|}$ and error parameter $\epsilon > 0$. Then, in $\tilde{O}(n^{2-1/d} \log 1/\epsilon)$ time, the algorithm returns the (approximate) solution x to $\mathbf{L}x^* = b$ where $\|x - x^*\|_{\mathbf{L}} \leq \epsilon \|x^*\|_{\mathbf{L}}$. Each vertex update to G takes $\tilde{O}(n)$ time.*

Using the fast dynamic Laplacian solver, we maintain dynamic effective resistances of a graph, which is a critical computation for graph clustering (Alev et al., 2017), fault-tolerant computing (Ghosh et al., 2008), network analysis (Tizghadam and Leon-Garcia, 2008; Anand and Umans, 2023; Anand et al., 2024a), and biological systems (Klein et al., 2022), as it signifies the degree of connectivity between two vertices. The effective resistance $r_G(a, b)$ between vertex a and vertex b in a graph G is a graph-theoretic analog of leverage scores that represents the energy needed to route one unit of electric flow from a to b , and has a natural linear algebraic formulation: let \mathbf{e}_i denote the i -th standard basis vector. Then, for all $a, b \in V$, $r_G(a, b) = (\mathbf{e}_a - \mathbf{e}_b)^\top \mathbf{L}^\dagger (\mathbf{e}_a - \mathbf{e}_b)$, where \mathbf{L} is the Laplacian of G . Finally, \mathbf{L}^\dagger denotes the Moore-Penrose pseudoinverse of \mathbf{L} .

Theorem 7 (Dynamic Effective Resistance). *There is a dynamic algorithm that, given a dynamic graph $G = (V, E)$ with corrupted VC-dimension bounded by d , maintains effective resistances in G . The data structure supports queries that receive a pair of vertices $u, v \in V$ and error parameter $\epsilon > 0$. Then, in $\tilde{O}(n^{2-1/d} \log 1/\epsilon)$ time, the algorithm returns a $(1 \pm \epsilon)$ -approximation of the effective resistance. Moreover, each node update to G in the dynamic data structure takes $\tilde{O}(n)$ time.*

Our dynamic matrix-vector multiplication data structure also leads to faster dynamic triangle detection algorithms for graphs with corrupted VC-dimension d , which are critical components of fraud detection systems and community-detection algorithms. No subquadratic time algorithm exists for vertex updates, conditional on BMM (Abboud and Vassilevska Williams, 2014), and also conditional on OMv (Henzinger et al., 2015). We show that these lower bounds can be broken on structured graphs.

Theorem 8 (Dynamic Triangle Detection). *There is a dynamic algorithm that, given a dynamic graph $G = (V, E)$ with corrupted VC-dimension d , maintains whether G contains a triangle or not. Each vertex update to G takes $O(n^{2-1/d})$ time and returns a Boolean indicator for whether G contains a triangle or not.*

Furthermore, our techniques lead to faster dynamic approximate algorithms for single-source distances. In this problem, we are tasked with finding the distances from a designated source vertex to every other vertex.

Theorem 9 (Dynamic Approximate Single-Source Shortest Paths). *There is a dynamic algorithm that maintains $(1 + \epsilon)$ -approximate single source distances on a dynamic unweighted undirected graph $G = (V, E)$. If the corrupted VC-dimension of G is bounded by d , each vertex update to G takes $\tilde{O}(kn^{2-1/(2d)}/\epsilon)$ time, and querying the distances for any source node takes $O(n^{2-1/(2d)}/\epsilon)$ time.*

Given a metric space \mathcal{M} with n points and a positive integer $k \leq n$, the k -center problem asks one to select k points, referred to as centers, such that the maximum distance of any point in the metric space to its closest center is minimized. It is known that the k -center is NP-hard to approximate within a factor of $(2 - \epsilon)$ for any $\epsilon > 0$ (Hsu and Nemhauser, 1979). The best existing dynamic algorithms (Cruciani et al., 2024) only work with edge updates and use fast matrix multiplication as a black-box. We present an algorithm without fast matrix multiplication that supports more powerful vertex updates.

Theorem 10 (Dynamic Approximate k -center). *Given an unweighted undirected graph $G = (V, E)$, there is a dynamic algorithm for $(2 + \epsilon)$ -approximate k -center with node update time $O(kn^{2-1/2d}/\epsilon)$, where d is a bound on the corrupted VC-dimension of G .*

1.3. Further Related Work

Results for general Boolean matrix multiplication. A line of work shows that the complexity of matrix-vector multiplication for general Boolean matrices (where the multiplication is over the Boolean semiring) can attain a subpolynomial speed-up. For instance, Williams (2007) showed that BMM can be computed in $O(n^3/\log n)$ time. Larsen and Williams (2017) extended this to $O(n^3/2^{\Omega(\sqrt{\log n})})$. This was further extended in Abboud et al. (2024) to $O(n^3/2^{\Omega(\sqrt[3]{\log n})})$.

Results for structured matrices. When the underlying matrix is Vandermonde, Toeplitz, Hankel, or Cauchy, a body of work shows that they admit fast matrix-vector multiplications (Motzkin, 1951; Gohberg and Olshevsky, 1994; Olshevsky and Shokrollahi, 2000; Pan and Tsagaridas, 2014). Orthogonal-vector (OV) matrices are structured matrices where each row and column receives a label $v \in \{0, 1\}^d$ and $M_{i,j} = 1$ if and only if the corresponding two labels are orthogonal. Similar to our corrupted VC-dimension results, Alman and Vassilevska Williams (2020) show that such OV matrices allow for fast matrix-vector products if there are few corruptions to the matrix.

Another approach to handle structured inputs is through the algorithms with predictions regime, where some learning algorithm extracts the structure and can predict information about future vectors, leading to faster matrix-vector multiplication algorithms Henzinger et al. (2024); Brand et al. (2024).

Result for dynamic structured graphs. Our dynamic algorithms hold for any structured graph, even if we do not know their structure. When the structure is known, there exist specialized dynamic algorithms tailored to the specific graph class. These include, for instance, interval graphs Crespelle (2019); Chen et al. (2024), geometric graphs defined from Kernels (Alman et al., 2020), planar graphs (Korhonen et al., 2024), dynamic planar graphs (Abboud and Dahlgaard, 2016), and H-minor free graphs (Dorn et al., 2012).

Matrix vector multiplication in optimization. For convex optimization algorithms, there is a long history on developing data structures that facilitate fast matrix-vector products. Here the matrices are generally projection matrices that require computation of some matrix inverse. While historically, most research was on accelerating the maintenance of the matrix inverse (Karmarkar, 1984; Vaidya, 1989; Lee and Sidford, 2015; Cohen et al., 2021; Lee et al., 2019; Brand, 2020; Jiang et al., 2021, 2020a; Huang et al., 2022; Jiang et al., 2022; Lee et al., 2015; Jiang et al., 2020b), this research has progressed so far that the current bottleneck for the fastest linear program solvers are simple matrix-vector products (Brand et al., 2020, 2021).

2. Preliminaries

Notation. Let $[n] = \{1, \dots, n\}$. We use $O(\cdot)$ to hide constant factors, and \tilde{O} to hide polylogarithmic factors. Let $\|\cdot\|_1$ denote the ℓ_1 (Manhattan distance). For any matrix \mathbf{M} , let \mathbf{M}_i and $\mathbf{M}_{:,i}$ denote the i 'th column and i 'th row (respectively) of \mathbf{M} . For a set V we write $\mathbf{M} \in \mathbb{R}^{m \times V}$ for the $m \times |V|$ matrix where we can index columns by $x \in V$, i.e., $\mathbf{M}_x \in \mathbb{R}^m$. For any vector $x \in \mathbb{R}^n$, the Hamming weight of x is the number of non-zero entries of x also denoted by $\text{nnz}(x)$. For Boolean vectors $x, y \in \{0, 1\}^n$, the Hamming distance between x and y is given by $\|x - y\|_1$. Finally, for any vector $x \in \mathbb{R}^n$ and positive definite matrix $\mathbf{L} \in \mathbb{R}^{n \times n}$, define the \mathbf{L} -induced norm of x by $\|x\|_{\mathbf{L}} = \sqrt{x^\top \mathbf{L} x}$.

VC-Dimension of Range Spaces. A range space (also called a set system) is a pair $\mathfrak{R} = (X, R)$ where X is a set and R is a set of subsets of X . Let $\Pi_R(A) = \{A \cap r : r \in R\}$. The VC-dimension of \mathfrak{R} is given by $\text{VC}(\mathfrak{R}) = \max\{|S| : S \subseteq X \text{ and } |\Pi_R(S)| = 2^{|S|}\}$. The primal shatter function π of \mathfrak{R} is given by $\pi(m) = \max\{|\Pi_R(A)| : A \subseteq X, |A| = m\}$ for $m \geq 0$. Let B be a set of ranges in R . Then, let $\Pi_X^*(B) = \{C : C \subseteq X \text{ and } C \text{ is not crossed by any range in } B\}$ and let $\Pi_X^*(B)$ be maximal. Then, for $m \geq 0$, the dual shatter function π^* of the range space is given by $\pi^*(m) = \max\{|\Pi_X^*(B)| : B \subseteq R, |B| = m\}$.

VC-Dimension of Matrices. Any matrix $\mathbf{M} \in \{0, 1\}^{m \times n}$ corresponds to a set family given by $\mathcal{F}_{\mathbf{M}} = \{j : \mathbf{M}_{i,j} = 1\} : i \in [m]\}$, i.e., consider each row of \mathbf{M} as the indicator vector of some set. Through it, we can encode \mathbf{M} by the range space $\mathfrak{R}_{\mathbf{M}} = ([n], \mathcal{F}_{\mathbf{M}})$. Then, the VC-dimension of \mathbf{M} is defined as the VC-dimension of $\mathfrak{R}_{\mathbf{M}}$. Here, a subset S of the columns of \mathbf{M} is said to be *shattered* if each of the $2^{|S|}$ many 0/1 strings appears in some row in the restriction of \mathbf{M} to the columns in S . Then, the VC-dimension of \mathbf{M} is the maximum size of a shattered subset of the columns of \mathbf{M} . Moreover, the VC-dimension $d_{m,n}$ of a matrix $\mathbf{M} \in \{0, 1\}^{m \times n}$ satisfies $1 \leq d_{m,n} \leq \log n$.

Pollard Pseudodimension of Matrices. For a family of functions \mathcal{F} mapping V to $\{0, \dots, \ell - 1\}$, the Pollard pseudodimension of \mathcal{F} , denoted by $\text{Pdim}(\mathcal{F})$, is the largest integer d such that there exists $x_1, \dots, x_d \in V$ and thresholds $y_1, \dots, y_d \in [\ell]$ such that for any d -length bit vector $\mathbf{b} = (b_1, \dots, b_d) \in \{0, 1\}^d$, there exists an $f \in \mathcal{F}$ such that for all $i \in [d]$, $f(x_i) \leq y_i$ if and only if $b_i = 1$. For a real matrix \mathbf{M} , define the pseudo-dimension of \mathbf{M} , denoted by $\text{Pdim}(\mathbf{M})$ by thinking of the rows of \mathbf{M} as functions and taking the pseudo-dimension of the resulting class of functions. Specifically, if \mathbf{M} is an $m \times n$ matrix, for each $i \in \{1, \dots, m\}$, define $f_{\mathbf{M},i} : \{1, \dots, n\} \rightarrow \mathbb{R}$ by $f_{\mathbf{M},i}(j) = \mathbf{M}_{i,j}$, and let $\text{Pdim}(\mathbf{M}) = \text{Pdim}(\{f_{\mathbf{M},i} : i \in \{1, \dots, m\}\})$.

3. The Structural Complexity of Matrix-Vector Multiplication

We present a technical overview of the algorithms and the main theorems. We begin this section with a quick recap of previous work Björklund and Lingas (2001); Alves et al. (2024) who established a connection between matrix vector products and minimum spanning trees on n points $\{0, 1\}^m$, where the edge weights are given by the Hamming distance between two points (i.e., matrix \mathbf{M} defines a collection of points).

Having established this connection, we prove one of our main results in Section 3.2. We prove via techniques from computational geometry that the weight of the minimum spanning tree must be bounded, if the matrix \mathbf{M} has corrupted VC-dimension at most d . This then yields our main result Theorem 3.

3.1. Matrix Vector Products via Minimum Spanning Trees

We here recap the algorithm idea by Björklund and Lingas (2001), which was later independently rediscovered by Alves et al. (2024). We also explain how to extend the results from \mathbf{M} to \mathbf{M}^\top .

Differential Compression. Let $\mathbf{M} \in \{0, 1\}^{m \times n}$ be a binary matrix, and let \mathbf{M}_i denote the i 'th column of \mathbf{M} for $i \in [n]$. We differentially compress \mathbf{M} by writing each column \mathbf{M}_x as the sum of another column \mathbf{M}_y and a *change vector* $\Delta_{x,y}$ such that $\mathbf{M}_y = \mathbf{M}_x + \Delta_{x,y}$ and $\Delta_{x,y} = \mathbf{M}_x - \mathbf{M}_y$.

If \mathbf{M}_x and \mathbf{M}_y are similar, then $\|\Delta_{x,y}\|_1$ likely to be smaller than the number of nonzero elements of \mathbf{M}_x . Therefore, it is more efficient to indirectly represent \mathbf{M}_x with respect to \mathbf{M}_y , rather than through the matrix \mathbf{M} . This necessitates an algorithm that finds a suitable chain of Δ 's to represent all columns of \mathbf{M} : for each column \mathbf{M}_x , identify a similar column \mathbf{M}_y that characterizes the former, such that the Hamming weight of $\Delta_{x,y}$ required to represent \mathbf{M}_x is minimized subject to \mathbf{M}_y .

Since the algorithm measures the Hamming distance for each pair of columns in \mathbf{M} , we can model this compression by an undirected weighted graph on G on n vertices, where vertex i represents column i of \mathbf{M} , and the weight of each edge (x, y) corresponds to the Hamming distance between columns x and y . We can then find a Minimum Spanning Tree (MST) of G , which by definition spans G with the minimum sum of edge weights possible. Therefore, any MST of G rooted at vertex r defines a chain of Δ 's that, starting at r , can represent all the columns of \mathbf{M} .

We formalize this intuition by defining the Δ -labeled spanning tree of a matrix and its weight.

Definition 11 (Δ -labeled spanning tree of matrix \mathbf{M}) A Δ -labeled tree is a tree $T = (V, E)$ with some explicit root x , where each edge $e \in E$ is directed away from x and labeled by a vector $\Delta_e \in \mathbb{R}^m$. We say T is a Δ -labeled spanning tree for matrix $\mathbf{M} \in \mathbb{R}^{m \times n}$ if $\mathbf{M}_x = \mathbf{0}$ for root x , and for all edges $(i, j) \in E$ we have $\Delta_{i,j} := \mathbf{M}_j - \mathbf{M}_i$.

Definition 12 (Weight of a Δ -labeled spanning tree) For any Δ -labeled spanning tree of \mathbf{M} denoted by T with directed edge-set E , define $\text{weight}(T)$ as the total number of non-zero entries given by $\sum_{e \in T} \text{nnz}(\Delta_e)$.

The minimum spanning tree of \mathbf{M} is then the Δ -labeled spanning tree with the smallest possible weight. Given any spanning tree of \mathbf{M} , we use the weight of the Δ -labeled spanning tree to parameterize the runtime of the matrix-vector multiplication algorithm. Here, the lower the weight of the Δ -labeled spanning tree, the faster the runtime.

Lemma 13 (Gasieniec and Lingas (2003); Alves et al. (2024)) Given a Δ -labeled spanning tree T of $\mathbf{M}^\top \in \{0, 1\}^{n \times m}$ and a vector $v \in \mathbb{R}^n$, there is an algorithm that computes $\mathbf{M}v$ in $O(\text{weight}(T) + n + m)$ time.

We describe this procedure in Algorithm 1.

As a quick recap, the algorithm computes $\mathbf{M}v$ by starting at a root node $r \in T$ of the spanning tree and performing depth-first search (DFS). The algorithm initializes an output vector and computes $(\mathbf{M}v)_r$ in $O(n + m)$ time. For each edge (x, y) traversed in the recursion tree, the algorithm computes $(\mathbf{M}v)_y = (\mathbf{M}v)_x + \Delta_{y,x}^\top v$. The complexity of this iterative procedure is proportional to $\text{weight}(T) = \sum_{e \in E(T)} \delta_e$ where for each edge $e = (x, y)$ in the Δ -labeled spanning tree, δ_e is the number of non-zeros in Δ_e , i.e., the Hamming distance between row x and row y of \mathbf{M} . For completeness sake, we provide a proof for Lemma 13 in Appendix A.1.

Since the weight of the Δ -labeled spanning tree of \mathbf{M}^\top can be different from the weight of the Δ -labeled spanning tree of \mathbf{M} , we provide a new algorithm with an analogous theoretical guarantee in lemma 14.

Lemma 14 *Given a Δ -labeled spanning tree T of $\mathbf{M} \in \{0, 1\}^{m \times n}$ and a vector $v \in \mathbb{R}^n$, there is an algorithm that can compute $\mathbf{M}v$ in $O(\text{weight}(T) + n + m)$ time.*

To utilize the Δ -labeled spanning tree of \mathbf{M} , note that $\mathbf{M}v = \sum_{i=1}^n \mathbf{M}_i v_i$. For simplicity, consider the special case where \mathbf{M} has only two columns, then $\mathbf{M}v = \mathbf{M}_1 v_1 + \mathbf{M}_2 v_2 = \mathbf{M}_1(v_1 + v_2) + \Delta_{1,2} v_2$. For more columns, this can be extended to require only a product with \mathbf{M}_1 and products with each Δ_e of the Δ -labeled spanning tree. Thus the complexity is bounded by $O(m + n + \text{weight}(T))$.

We provide proofs for Lemma 14 in Appendix A.1.

Since we wish to minimize the time complexity, we compute a minimum spanning tree. In [Alves et al. \(2024\)](#) this was done naïvely, whereas in [Björklund and Lingas \(2001\)](#) this is done via Theorem 4.2 of [Indyk and Motwani \(1998\)](#).

Lemma 15 (Theorem 4.2 of [Indyk and Motwani \(1998\)](#)) *For any $\epsilon > 0$, we can compute an $(1 + \epsilon)$ -approximate MST with respect to the Hamming distance of n points in $\{0, 1\}^m$ in $\tilde{O}(mn^{1+1/(1+\epsilon)})$ time.*

Theorem 16 *Given Boolean $m \times n$ matrix \mathbf{M} , we can construct in $\tilde{O}(nm)$ time a Δ -labeled spanning tree whose weight is at most a $O(\log n)$ -factor larger than the minimum spanning tree (MST) of \mathbf{M} .*

Proof of Theorem 16 Run Lemma 15 on the columns of \mathbf{M} for $\epsilon = \log n$ to construct an $O(\log n)$ -approximate MST in $\tilde{O}(mn)$ time. Next, iterate over the edges of the MST and compute the Δ -labels, i.e., label each tree edge (x, y) by $\Delta_{x,y} = \mathbf{M}_x - \mathbf{M}_y$. This takes $\tilde{O}(mn)$ time as there are only $n - 1$ tree edges and $\Delta_{x,y} \in \mathbb{R}^m$. \blacksquare

3.2. Existence of Low Weight Δ -labeled Minimum Spanning Trees

The Hamming distance between any two columns in \mathbf{M} is at most m . Since there are $O(n)$ edges in the Δ -labeled MST, this gives a coarse bound of $O(mn)$ which is achieved for Hadamard matrices. One of our main technical contributions is to prove that Δ -labeled MST's with low weight exist for structure matrices. We give a bound on the MST weight parameterized by the corrupted VC-dimension of the matrix.

Theorem 17 *If a matrix has corrupted VC-dimension d , then the weight of the corresponding MST is at most $O(mn^{1-1/d} \log n)$.*

We show that for matrices of bounded VC-dimension, the minimum spanning tree T has small weight. For this, we work directly with the definition of VC-dimension and use set terminology, which allows us to use relevant work from [Welzl \(1988\)](#); [B. Chazelle \(1989\)](#); [Matoušek \(1991\)](#); [Har-Peled \(2009\)](#). This previous work studied bounded VC-dimensions in the context of computational geometry. We here use their results to bound the complexity of matrix vector products.

Definition 18 (Set crossings) *Let A and r be sets. We say that A crosses r if the symmetric difference is non-empty, i.e. $A \Delta r \neq \emptyset$. In other words, A crosses r if neither $A \subseteq r$ nor $A \cap r = \emptyset$ holds.*

Definition 19 (Spanning Tree) *Let $A \subset X$ be a finite set of elements of a range space (X, R) . A spanning tree on A is an undirected (unrooted) tree with node set A .*

Definition 20 (Crossing number $\kappa(T)$ of spanning tree T) *A crossing of a range $r \in R$ in T is an edge in T that is crossed by r (i.e., an edge that has one endpoint in r and the other endpoint in $[n] \setminus r$). The crossing number $\kappa_r(T)$ of a range $r \in R$ is the number of crossings of r in T . The crossing number $\kappa(T)$ of T is the maximum crossing number of a range $r \in R$ in T . In other words, $\kappa(T) := \max_{r \in R} \kappa_r(T)$.*

This notion of a spanning tree corresponds to the notion of the Δ -labeled spanning tree for matrix \mathbf{M} . The set system (X, R) induced by $\mathbf{M} \in \{0, 1\}^{m \times n}$ uses set $X = [n]$ (i.e., column indices) with the rows of \mathbf{M} being the indicator vectors of m subsets of X . Thus, a spanning tree T_X for (X, R) and a spanning tree T_M for \mathbf{M} both consist of edges that connect elements from $[n]$. Furthermore, the number of crossings for an edge $(x, y) \in T_X$ is exactly the number of indices i where $(\mathbf{M}_x)_i$ and $(\mathbf{M}_y)_i$ differ. Thus the crossing number of a tree T_X for (X, R) is exactly the weight of the corresponding Δ -labeled spanning tree for \mathbf{M} .

For the rest of this section, we will argue that range spaces (X, R) of corrupted VC-dimension d have spanning trees with small crossing number.

The literature on finding a spanning tree on X with a low crossing number stems from a line of earlier works on computational geometry from the 1900s (Welzl, 1988; B. Chazelle, 1989; Matoušek, 1991; Har-Peled, 2009). They used the trees so preprocess a set of points in \mathbb{R}^d to quickly answer queries where for any arbitrary convex polytope, the query returns a point within the polytope. Here, we transfer these techniques to the online matrix-vector multiplication problem and extend them to the notion of corrupted VC-dimension.

Lemma 21 (Lemma 4.1 of Welzl (1988)) *Let (X, R) be a range space VC-dimension at most d . For every $A \subseteq X$, $|A| = n \geq 1$ and every multiset Q of ranges in R with $|Q| = m$, there are two elements $x, y \in A$ where $x \neq y$ such that the number of ranges in Q crossing (x, y) is at most $O(m \cdot n^{-1/d} \log n)$.*

This lemma allows us to prove the existence of a Δ -labeled spanning tree for matrices with bounded VC-dimension. We later extend this to corrupted VC-dimension.

Lemma 22 *Let (X, R) be a range-space with $|X| = n, |R| = m$ of VC-dimension at most d . Then there exists a spanning tree T of crossing number $\kappa(T) = O(mn^{1-1/d})$.*

Proof Let $A_0 = X$. Consider the following process where initially $i = 0$. By lemma 21, there exists distinct $x_i, y_i \in A_i$ such that the number of ranges in R crossing (x_i, y_i) is at most $O(m \cdot |A_i|^{-1/d} \log n)$. Letting $A_{i+1} \leftarrow A_i \setminus x_i$ and repeating, constructs a spanning tree T .

By lemma 21, the total number of ranges that cross the edges in T is at most

$$\begin{aligned} \sum_{i=1}^n O(m(n-i)^{-1/d} \log(n-i)) &\leq O\left(m \log n \int_1^n x^{-1/d} dx\right) \\ &= O(mn^{1-1/d} \log n). \end{aligned}$$

which proves the claim. ■

We now extend Lemma 22 to corrupted VC-dimension. For this, we want to linearize the tree constructed in Lemma 22, i.e., we make sure the tree is a single line of vertices. This is to reduce the impact of corruptions, so that any single corruption does not affect the number of crossings too much.

Consider for example where $X = [n]$, R is a multi-set of m empty ranges (corresponding to an $m \times n$ zero matrix \mathbf{M}), and the spanning tree is a star with $1 \in X$ at the center. The corruption matrix \mathbf{S} now adds 1 to each of the empty sets in R (equivalently, turning the first column of \mathbf{M} to an all-1-column). This would still fit into the definition of corrupted VC-dimension since each set is corrupted by only one element. Now the number of crossings of each edge is $O(m)$ because 1 is in each of the m sets, but none of the other elements in X are in any set, and there are $n - 1$ edges each connecting 1 to another element of X . Thus there are $O(m)$ crossings and the tree has $O(mn)$ crossings in total.

If, however, the tree had been a single line, then the corruption would affect at most 2 edges, and the number of crossings in the tree would go up by only $O(m)$.

Lemma 23 For range space (X, R) , $|X| = n$ with spanning tree T , there exists a permutation $\pi \in S_n$ such that the crossing number of the corresponding spanning tree T' (which is just the line $\pi(1), \pi(2), \dots, \pi(n)$) is at most twice that of T .

Proof

Enumerate all the ranges in R by R_1, \dots, R_m , where $R_i := \{c : \mathbf{M}_{i,c} = 1\}$ for $i \in [m]$.

The crossing number of R_i in T counts the number of edges in T such that one endpoint of the edge is in R_i and the other endpoint is in $[n] \setminus R_i$. Suppose the spanning tree T on X has a crossing number of κ_i for just R_i and let $\kappa = \sum_{i=1}^m \kappa_i$ be the crossing number of T for (X, R) .

Perform a DFS traversal on T , and write the in-order traversal \mathcal{I} . We use the permutation $\pi(i) = \mathcal{I}_i$ for $i \in [n]$. Let T' be the corresponding linear tree.

We see then that this vertex path can (in the worst case) cross R_i $2\kappa_i$ times, that is because DFS uses each edge (x, y) of T twice: once when visiting y (going down one level in the tree) and once when it is done processing y (DFS pops the current level from the stack).

Thus the total number of crossings $\kappa(T')$ for the linear tree T' is $\kappa(T') \leq \sum_{i=1}^m 2\kappa_i \leq 2\kappa(T)$. ■

Proof of Theorem 17 Suppose that $\mathbf{M} \in \{0, 1\}^{m \times n}$ has corrupted VC-dimension d . Let $\mathbf{L} \in \{0, 1\}^{m \times n}$, $\mathbf{S} \in \{-1, 0, 1\}^{m \times n}$ with $\mathbf{M} = \mathbf{L} + \mathbf{S}$ where \mathbf{L} has VC-dimension d and \mathbf{S} has at most $O(n^{1-1/d})$ non-zero entries per row. These matrices exist by definition of corrupted VC-dimension, i.e., \mathbf{S} describes the corruption.

Let (X, R) be the set system induced by \mathbf{L} , i.e., $X = [n]$ and each row of \mathbf{L} is the indicator vector of a set in R with $|R| = m$. Then (X, R) also has VC-dimension d and by Lemma 22 there exists a spanning tree T of (X, R) with crossing number bounded by $O(mn^{1-1/d} \log n)$.

This also implies the existence of a spanning tree T' which is a single line that has crossing number $O(mn^{1-1/d} \log n)$ by Lemma 23.

Now consider the range space (X, R_c) for the corrupted matrix \mathbf{M} . The spanning tree T' has the same crossing number on (X, R_c) as on (X, R) , except for extra crossings induced by the corruption. We consider a range $r \in R_c$ and count the number of new crossings it has incurred due to the corruption: an edge (x, y) only has a new crossing for some range $r \in R_c$ if x or y was corrupted in r . Since each $x \in X$ has at most 2 incident edges in T' (since it is a line) each corruption to r leads to at most 2 new crossings. Since each range has at most $O(n^{1-1/d})$ corruptions by definition of VC-corruption, the total number of new crossing over all ranges is at most $O(mn^{1-1/d} \log n)$.

Thus, T' is a spanning tree for (X, R_c) with crossing number bounded by $O(mn^{1-1/d} \log n)$. This spanning tree corresponds to a Δ -labeled spanning tree for \mathbf{M} , as $X = [n]$ are the column indices and the number of crossings for an edge (x, y) is exactly the number of entries where \mathbf{M}_x and \mathbf{M}_y differ.

Since the minimum spanning tree can only have lower weight, we get an upper bound of $O(mn^{1-1/d} \log n)$ on the weight of the MST. ■

We can now put everything together to prove Theorem 3.

Theorem 3 (Static Online Matrix-Vector Multiplication). If a matrix $\mathbf{M} \in \{0, 1\}^{m \times n}$ has corrupted VC-dimension d , then after an $\tilde{O}(mn)$ -time preprocessing, there is a data structure \mathcal{D} that can compute $\mathbf{M}v$ for any $v \in \mathbb{R}^n$ in $\tilde{O}(mn^{1-1/d} + n)$ time, with high probability.

Proof Given matrix \mathbf{M} , preprocess it by constructing a Δ -labeled spanning tree T via Theorem 16. This takes $\tilde{O}(mn)$ time.

When receiving a vector $v \in \mathbb{R}^n$, pass v together with T to the algorithm of Lemma 14. It returns the product $\mathbf{M}v$ in time $\tilde{O}(m + n + \text{weight}(T))$.

By Theorem 17, if \mathbf{M} has corrupted VC-dimension bounded by d , then the MST of \mathbf{M} has weight bounded by $O(mn^{1-1/d})$. Since T is a $O(\log n)$ -approximation of the MST, answering a query takes $\tilde{O}(mn^{1-1/d} + n)$ time. ■

3.3. Dynamic Matrices

At last, we outline how to handle matrices \mathbf{M} that are allowed to update over time, i.e., Theorem 4.

Theorem 4 (*Dynamic Online Matrix-Vector Multiplication*). *Given a matrix $\mathbf{M} \in \{0, 1\}^{m \times n}$, there is a data structure \mathcal{D} with $\tilde{O}(mn)$ preprocessing time that supports row and column updates (insertions/deletions) to \mathbf{M} in $\tilde{O}(n)$ and $\tilde{O}(m)$ time respectively. Upon querying the data structure \mathcal{D} with a vector $v \in \mathbb{R}^n$, it outputs $\mathbf{M}v$ in $\tilde{O}(mn^{1-1/d^*} + n)$ time, with high probability, where d^* is the largest corrupted VC-dimension of \mathbf{M} throughout the history of its updates.*

We sketch how to handle column insertions: Let \mathbf{M} be the current matrix. We split it into smaller matrices $\mathbf{M}^{(0)}, \mathbf{M}^{(1)}, \dots, \mathbf{M}^{(\log n)}$, where each $\mathbf{M}^{(i)}$ contains at most 2^i columns of \mathbf{M} . When a new column is inserted to \mathbf{M} , we insert that column to $\mathbf{M}^{(0)}$. When any $\mathbf{M}^{(i)}$ contains more than 2^i columns, then all its columns are inserted to $\mathbf{M}^{(i+1)}$ and $\mathbf{M}^{(i)}$ is reset to an empty matrix. Thus, any $\mathbf{M}^{(i)}$ receives new columns at most once every 2^i iterations to \mathbf{M} .

When an $\mathbf{M}^{(i)}$ receives new columns, we initialize a new matrix-vector multiplication data structure (Theorem 3) on it. This takes $\tilde{O}(m2^i)$ time, but amortizes to $\tilde{O}(m)$ time per insertion to \mathbf{M} since it only happens at most once every 2^i insertions. This yields an amortized time of $\sum_{i=0}^{\log n} \tilde{O}(m) = \tilde{O}(m)$ time to maintain all $\mathbf{M}^{(i)}$ for $i = 0, \dots, \log n$.

To answer a matrix-vector multiplication query $\mathbf{M}v$, we split v into vectors $v^{(0)}, \dots, v^{(\log n)}$ such that $\mathbf{M}v = \sum_{i=0}^{\log n} \mathbf{M}^{(i)}v^{(i)}$. For the time complexity, note that each $\mathbf{M}^{(i)}$ is a submatrix of \mathbf{M} . Thus, the time complexity needed to multiply a vector by $\mathbf{M}^{(i)}$ is bounded by $\tilde{O}(mn^{1-1/d})$.

For column deletions, we can ignore them until $\mathbf{M}^{(i)}$ is reinitialized: simply set $v_j = 0$ for the columns that should have been deleted. We can handle row deletions updates to \mathbf{M} in a similar way, by splitting the matrix again into $\log m$ matrices, each containing at most 2^j rows. The full proof is given in Appendix A.2.

4. Conclusion

In this work, we study the structural complexity of sequential matrix-vector multiplication. We propose a theoretical framework to study heuristic algorithms that have achieved tremendous practical success. Building on the VC-dimension literature, we propose the notion of a corrupted VC-dimension d and provide structural characterizations in Fact 1. In theorem 3, we show that if a matrix $\mathbf{M} \in \{0, 1\}^{m \times n}$ has corrupted VC-dimension d , then its matrix-vector product $\mathbf{M}v$ can be computed in $O(mn^{1-1/d})$ time, providing polynomial speed-ups over existing methods. Moreover, our algorithm maintains updates to \mathbf{M} in $\tilde{O}(m)$ and $\tilde{O}(n)$ time. This leads to the first $O(n^{2-\epsilon})$ -time algorithms for maintaining high-accuracy estimates for Laplacian solvers, effective resistance, and triangle detection in graphs with node insertions and deletions.

Our results motivate interesting future work: for instance, it would be interesting if alternate generalizations of the VC-dimension, such as the Natarajan dimension, can also parameterize the structural complexity of matrix-vector multiplication. Moreover, we conjecture that our algorithm can be used to provide combinatorial accelerations to the context-free grammar parsing and the k -clique detection problem in structured instances. Finally, for the non-Boolean setting where we provide subquadratic runtimes in matrices with bounded Pollard pseudodimension, we conjecture that the dependence of the number of thresholds A in the runtime can be reduced to be polylogarithmic instead of linear.

5. Acknowledgements

This work was supported by NSF Grant CCF 2338816. We also express our thanks to Ce Jin, Shunhua Jiang, Elia Gorokhovskiy, and Jingtong Sun for insightful discussions.

References

- Amir Abboud and Søren Dahlgaard. Popular conjectures as a barrier for dynamic planar graph algorithms. *IEEE 57th Annual Symposium on Foundations of Computer Science*, 2016. URL <https://arxiv.org/abs/1605.03797>.
- Amir Abboud and Virginia Vassilevska Williams. Popular conjectures imply strong lower bounds for dynamic problems. In *55th IEEE Annual Symposium on Foundations of Computer Science, FOCS 2014, Philadelphia, PA, USA, October 18-21, 2014*, pages 434–443. IEEE Computer Society, 2014. doi: 10.1109/FOCS.2014.53. URL <https://doi.org/10.1109/FOCS.2014.53>.
- Amir Abboud, Nick Fischer, Zander Kelley, Shachar Lovett, and Raghu Meka. New graph decompositions and combinatorial boolean matrix multiplication algorithms. *STOC 2024: Proceedings of the 56th Annual ACM Symposium on Theory of Computing*, 2024.
- Ittai Abraham, David Durfee, Ioannis Koutis, Sebastian Krinninger, and Richard Peng. On fully dynamic graph sparsifiers. In *2016 IEEE 57th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 335–344, 2016. doi: 10.1109/FOCS.2016.44.
- Vedat Levi Alev, Nima Anari, Lap Chi Lau, and Shayan Oveis Gharan. Graph clustering using effective resistance. *9th Innovations in Theoretical Computer Science Conference (ITCS 2018)*, 2017. URL <https://arxiv.org/abs/1711.06530>.
- Josh Alman and Virginia Vassilevska Williams. OV graphs are (probably) hard instances. In Thomas Vidick, editor, *11th Innovations in Theoretical Computer Science Conference, ITCS 2020, January 12-14, 2020, Seattle, Washington, USA*, volume 151 of *LIPICs*, pages 83:1–83:18. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2020. doi: 10.4230/LIPICs.ITCS.2020.83. URL <https://doi.org/10.4230/LIPICs.ITCS.2020.83>.
- Josh Alman, Timothy Chu, Aaron Schild, and Zhao Song. Algorithms and hardness for linear algebra on geometric graphs. In Sandy Irani, editor, *61st IEEE Annual Symposium on Foundations of Computer Science, FOCS 2020, Durham, NC, USA, November 16-19, 2020*, pages 541–552. IEEE, 2020. doi: 10.1109/FOCS46700.2020.00057. URL <https://doi.org/10.1109/FOCS46700.2020.00057>.
- Noga Alon, Shay Moran, and Amir Yehudayoff. Sign rank versus VC dimension. In Vitaly Feldman, Alexander Rakhlin, and Ohad Shamir, editors, *29th Annual Conference on Learning Theory*, volume 49 of *Proceedings of Machine Learning Research*, pages 47–80, Columbia University, New York, New York, USA, 23–26 Jun 2016. PMLR. URL <https://proceedings.mlr.press/v49/alon16.html>.
- João N. F. Alves, Samir Moustafa, Siegfried Benkner, Alexandre P. Francisco, Wilfried N. Gansterer, and Luís M. S. Russo. Accelerating graph neural networks with a novel matrix compression format, 2024. URL <https://arxiv.org/abs/2409.02208>.
- Emile Anand and Guannan Qu. Efficient reinforcement learning for global decision making in the presence of local agents at scale. *arXiv preprint arXiv:2403.00222*, 2024. URL <https://arxiv.org/abs/2403.00222>.
- Emile Anand and Chris Umans. Pseudorandomness of the sticky random walk. *California Institute of Technology, Thesis Archive*, 2023. URL <https://arxiv.org/abs/2307.11104>.
- Emile Anand, Ishani Karmarkar, and Guannan Qu. Mean-field sampling for cooperative multi-agent reinforcement learning. *ArXiv*, abs/2412.00661, 2024a. URL <https://arxiv.org/abs/2412.00661>.

- Emile Anand, Jan van den Brand, Mehrdad Ghadiri, and Daniel J. Zhang. The Bit Complexity of Dynamic Algebraic Formulas and Their Determinants. In Karl Bringmann, Martin Grohe, Gabriele Puppis, and Ola Svensson, editors, *51st International Colloquium on Automata, Languages, and Programming (ICALP 2024)*, volume 297 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 10:1–10:20, Dagstuhl, Germany, 2024b. Schloss Dagstuhl – Leibniz-Zentrum für Informatik. ISBN 978-3-95977-322-5. doi: 10.4230/LIPIcs.ICALP.2024.10.
- P. Assouad. Densité et dimension. *Annales de l’Institut Fourier*, 33:233–282, 1983. URL <https://api.semanticscholar.org/CorpusID:123874242>.
- Emo Welzl B. Chazelle. Quasi-optimal range searching in spaces of finite vc-dimension. *Discrete & computational geometry*, 4(5):467–490, 1989. URL <http://eudml.org/doc/131092>.
- Peter L. Bartlett, Nick Harvey, Christopher Liaw, and Abbas Mehrabian. Nearly-tight vc-dimension and pseudodimension bounds for piecewise linear neural networks. *Journal of Machine Learning Research*, 20(63):1–17, 2019. URL <http://jmlr.org/papers/v20/17-612.html>.
- Julien Basch, Sanjeev Khanna, and Rajeev Motwani. On diameter verification and boolean matrix multiplication. Technical report, Stanford University, Stanford, CA, USA, 1995.
- Aaron Bernstein, Jan van den Brand, Maximilian Probst Gutenberg, Danupon Nanongkai, Thatchaphol Saranurak, Aaron Sidford, and He Sun. Fully-dynamic graph sparsifiers against an adaptive adversary. In Mikolaj Bojanczyk, Emanuela Merelli, and David P. Woodruff, editors, *49th International Colloquium on Automata, Languages, and Programming, ICALP 2022, July 4-8, 2022, Paris, France*, volume 229 of *LIPIcs*, pages 20:1–20:20. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2022. doi: 10.4230/LIPIcs.ICALP.2022.20. URL <https://doi.org/10.4230/LIPIcs.ICALP.2022.20>.
- Andreas Björklund and Andrzej Lingas. Fast boolean matrix multiplication for highly clustered data. In Frank Dehne, Jörg-Rüdiger Sack, and Roberto Tamassia, editors, *Algorithms and Data Structures*, pages 258–263, Berlin, Heidelberg, 2001. Springer Berlin Heidelberg. ISBN 978-3-540-44634-7.
- Nicolas Bousquet, Aurélie Lagoutte, Zhentao Li, Aline Parreau, and Stéphan Thomassé. Identifying codes in hereditary classes of graphs and vc-dimension. *SIAM Journal on Discrete Mathematics*, 29(4):2047–2064, January 2015. ISSN 1095-7146. doi: 10.1137/14097879x.
- Jan van den Brand. A deterministic linear program solver in current matrix multiplication time. In *SODA*, pages 259–278. SIAM, 2020. URL <https://dl.acm.org/doi/abs/10.5555/3381089.3381105>.
- Jan van den Brand, Danupon Nanongkai, and Thatchaphol Saranurak. Dynamic matrix inverse: Improved algorithms and matching conditional lower bounds. In *FOCS*, pages 456–480. IEEE Computer Society, 2019a. URL <https://arxiv.org/pdf/1905.05067.pdf>.
- Jan van den Brand, Danupon Nanongkai, and Thatchaphol Saranurak. Dynamic matrix inverse: Improved algorithms and matching conditional lower bounds. In *2019 IEEE 60th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 456–480. IEEE, 2019b.
- Jan van den Brand, Yin Tat Lee, Aaron Sidford, and Zhao Song. Solving tall dense linear programs in nearly linear time. In *Proceedings of the 52nd Annual ACM SIGACT Symposium on Theory of Computing, STOC 2020, Chicago, IL, USA, June 22-26, 2020*, pages 775–788. ACM, 2020. doi: 10.1145/3357713.3384309. URL <https://dl.acm.org/doi/abs/10.1145/3357713.3384309>.

- Jan van den Brand, Yin Tat Lee, Yang P. Liu, Thatchaphol Saranurak, Aaron Sidford, Zhao Song, and Di Wang. Minimum cost flows, mdps, and ℓ_1 -regression in nearly linear time for dense instances. In *STOC*, pages 859–869. ACM, 2021.
- Jan van den Brand, Sebastian Forster, Yasamin Nazari, and Adam Polak. On dynamic graph algorithms with predictions. In David P. Woodruff, editor, *Proceedings of the 2024 ACM-SIAM Symposium on Discrete Algorithms, SODA 2024, Alexandria, VA, USA, January 7-10, 2024*, pages 3534–3557. SIAM, 2024. doi: 10.1137/1.9781611977912.126. URL <https://doi.org/10.1137/1.9781611977912.126>.
- Diptarka Chakraborty, Lior Kamma, and Kasper Green Larsen. Tight cell probe bounds for succinct boolean matrix-vector multiplication. In Ilias Diakonikolas, David Kempe, and Monika Henzinger, editors, *Proceedings of the 50th Annual ACM SIGACT Symposium on Theory of Computing, STOC 2018, Los Angeles, CA, USA, June 25-29, 2018*, pages 1297–1306. ACM, 2018. doi: 10.1145/3188745.3188830. URL <https://doi.org/10.1145/3188745.3188830>.
- Shreyas Chaudhari, Srinivasa Pranav, Emile Anand, and José M. F. Moura. Peer-to-peer learning dynamics of wide neural networks. *IEEE International Conference on Acoustics, Speech, and Signal Processing 2025*, 2024. URL <https://arxiv.org/abs/2409.15267>.
- Jingbang Chen, Meng He, J. Ian Munro, Richard Peng, Kaiyu Wu, and Daniel J. Zhang. Distance queries over dynamic interval graphs. *Comput. Geom.*, 122:102103, 2024. doi: 10.1016/J.COMGEO.2024.102103. URL <https://doi.org/10.1016/j.comgeo.2024.102103>.
- Li Chen, Gramoz Goranci, Monika Henzinger, Richard Peng, and Thatchaphol Saranurak. Fast dynamic cuts, distances and effective resistances via vertex sparsifiers. In Sandy Irani, editor, *61st IEEE Annual Symposium on Foundations of Computer Science, FOCS 2020, Durham, NC, USA, November 16-19, 2020*, pages 1135–1146. IEEE, 2020. doi: 10.1109/FOCS46700.2020.00109.
- Michael B. Cohen, Yin Tat Lee, and Zhao Song. Solving linear programs in the current matrix multiplication time. *J. ACM*, 68(1):3:1–3:39, 2021. Announced at STOC’19.
- David Coudert, Mónika Csikós, Guillaume Ducoffe, and Laurent Viennot. Practical Computation of Graph VC-Dimension. In Leo Liberti, editor, *22nd International Symposium on Experimental Algorithms (SEA 2024)*, volume 301 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 8:1–8:20, Dagstuhl, Germany, 2024. Schloss Dagstuhl – Leibniz-Zentrum für Informatik. ISBN 978-3-95977-325-6. doi: 10.4230/LIPIcs.SEA.2024.8. URL <https://drops.dagstuhl.de/entities/document/10.4230/LIPIcs.SEA.2024.8>.
- Christophe Crespelle. Fully dynamic representations of interval graphs. *Theor. Comput. Sci.*, 759:14–49, 2019. doi: 10.1016/J.TCS.2019.01.007.
- Emilio Cruciani, Sebastian Forster, Gramoz Goranci, Yasamin Nazari, and Antonis Skarlatos. Dynamic algorithms for-center on graphs. In *SODA*, pages 3441–3462, 2024. URL <https://doi.org/10.1137/1.9781611977912.123>.
- Frederic Dorn, Fedor V. Fomin, and Dimitrios M. Thilikos. Catalan structures and dynamic programming in h-minor-free graphs. *Journal of Computer and System Sciences*, 78(5):1606–1622, 2012. ISSN 0022-0000. doi: <https://doi.org/10.1016/j.jcss.2012.02.004>. JCSS Special Issue: Cloud Computing 2011.
- David Durfee, Yu Gao, Gramoz Goranci, and Richard Peng. Fully dynamic spectral vertex sparsifiers and applications. In Moses Charikar and Edith Cohen, editors, *Proceedings of the 51st Annual ACM SIGACT Symposium on Theory of Computing, STOC 2019, Phoenix, AZ*,

- USA, June 23-26, 2019, pages 914–925. ACM, 2019. doi: 10.1145/3313276.3316379. URL <https://doi.org/10.1145/3313276.3316379>.
- David Eppstein. Graphs with bounded radial order are small. In *Proceedings of the 3rd Annual European Symposium on Algorithms (ESA)*, volume 979 of *Lecture Notes in Computer Science*, pages 392–404. Springer, 1995. doi: 10.1007/3-540-60313-1_165.
- Vissarion Fisikopoulos and Luis Penaranda. Faster geometric algorithms via dynamic determinant computation. *Computational Geometry*, 54:1–16, 2016.
- Dimitris Floros, Nikos Pitsianis, and Xiaobai Sun. Algebraic vertex ordering of a sparse graph for adjacency access locality and graph compression, 2024. URL <https://arxiv.org/abs/2408.08439>.
- Gudmund Skovbjerg Frandsen, Johan P. Hansen, and Peter Bro Miltersen. Lower bounds for dynamic algebraic problems. *Inf. Comput.*, 171(2):333–349, 2001. doi: 10.1006/INCO.2001.3046. URL <https://doi.org/10.1006/inco.2001.3046>.
- Leszek Gasieniec and Andrzej Lingas. An improved bound on boolean matrix multiplication for highly clustered data. In Frank K. H. A. Dehne, Jörg-Rüdiger Sack, and Michiel H. M. Smid, editors, *Algorithms and Data Structures, 8th International Workshop, WADS 2003, Ottawa, Ontario, Canada, July 30 - August 1, 2003, Proceedings*, volume 2748 of *Lecture Notes in Computer Science*, pages 329–339. Springer, 2003. doi: 10.1007/978-3-540-45078-8_29. URL https://doi.org/10.1007/978-3-540-45078-8_29.
- Arpita Ghosh, Stephen Boyd, and Amin Saberi. Minimizing effective resistance of a graph. *SIAM Review*, 50(1):37–66, 2008. doi: 10.1137/050645452. URL https://web.stanford.edu/~boyd/papers/pdf/eff_res.pdf.
- I. Gohberg and V. Olshevsky. Fast algorithms with preprocessing for matrix-vector multiplication problems. *Journal of Complexity*, 10(4):411–427, 1994. ISSN 0885-064X. doi: <https://doi.org/10.1006/jcom.1994.1021>. URL <https://www.sciencedirect.com/science/article/pii/S0885064X84710211>.
- Raphael Clifford. Allan Gronlund and Kasper Green Larsen. New unconditional hardness results for dynamic and online problems. In *Proceedings of the 2015 IEEE 56th Annual Symposium on Foundations of Computer Science (FOCS)*, FOCS '15, page 1089–1107, USA, 2015. IEEE Computer Society. ISBN 9781467381918. doi: 10.1109/FOCS.2015.71. URL <https://doi.org/10.1109/FOCS.2015.71>.
- Sariel Har-Peled. Approximating spanning trees with low crossing number. *ArXiv*, abs/0907.1131, 2009. URL <https://api.semanticscholar.org/CorpusID:15811439>.
- Monika Henzinger and Stefan Neumann. Incremental and Fully Dynamic Subgraph Connectivity For Emergency Planning. In Piotr Sankowski and Christos Zaroliagis, editors, *24th Annual European Symposium on Algorithms (ESA 2016)*, volume 57 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 48:1–48:11, Dagstuhl, Germany, 2016. Schloss Dagstuhl – Leibniz-Zentrum für Informatik. ISBN 978-3-95977-015-6. doi: 10.4230/LIPIcs.ESA.2016.48. URL <https://drops.dagstuhl.de/entities/document/10.4230/LIPIcs.ESA.2016.48>.
- Monika Henzinger, Sebastian Krininger, Danupon Nanongkai, and Thatchaphol Saranurak. Unifying and strengthening hardness for dynamic problems via the online matrix-vector multiplication conjecture. In *Proceedings of the Forty-Seventh Annual ACM Symposium on Theory of Computing*, STOC '15, page

- 21–30, New York, NY, USA, 2015. Association for Computing Machinery. ISBN 9781450335362. doi: 10.1145/2746539.2746609. URL <https://doi.org/10.1145/2746539.2746609>.
- Monika Henzinger, Andrea Lincoln, and Barna Saha. The complexity of average-case dynamic subgraph counting. In Joseph (Seffi) Naor and Niv Buchbinder, editors, *Proceedings of the 2022 ACM-SIAM Symposium on Discrete Algorithms, SODA 2022, Virtual Conference / Alexandria, VA, USA, January 9 - 12, 2022*, pages 459–498. SIAM, 2022. doi: 10.1137/1.9781611977073.23. URL <https://doi.org/10.1137/1.9781611977073.23>.
- Monika Henzinger, Barna Saha, Martin P. Seybold, and Christopher Ye. On the complexity of algorithms with predictions for dynamic graph problems. *15th Innovations in Theoretical Computer Science Conference, ITCS 2024*, 287:62:1–62:25, 2024. doi: 10.4230/LIPICS.ITCS.2024.62. URL <https://doi.org/10.4230/LIPICS.ITCS.2024.62>.
- Wen-Lian Hsu and George L. Nemhauser. Easy and hard bottleneck location problems. *Discrete Applied Mathematics*, 1(3):209–215, 1979. ISSN 0166-218X. doi: [https://doi.org/10.1016/0166-218X\(79\)90044-1](https://doi.org/10.1016/0166-218X(79)90044-1). URL <https://www.sciencedirect.com/science/article/pii/0166218X79900441>.
- Baihe Huang, Shunhua Jiang, Zhao Song, Runzhou Tao, and Ruizhe Zhang. Solving SDP faster: A robust IPM framework and efficient implementation. In *63rd IEEE Annual Symposium on Foundations of Computer Science, FOCS 2022, Denver, CO, USA, October 31 - November 3, 2022*, pages 233–244. IEEE, 2022. doi: 10.1109/FOCS54457.2022.00029.
- Piotr Indyk and Rajeev Motwani. Approximate nearest neighbors: towards removing the curse of dimensionality. In *Proceedings of the Thirtieth Annual ACM Symposium on Theory of Computing, STOC '98*, page 604–613, New York, NY, USA, 1998. Association for Computing Machinery. ISBN 0897919629. doi: 10.1145/276698.276876. URL <https://doi.org/10.1145/276698.276876>.
- Haotian Jiang, Tarun Kathuria, Yin Tat Lee, Swati Padmanabhan, and Zhao Song. A faster interior point method for semidefinite programming. In *FOCS*, pages 910–918. IEEE, 2020a.
- Haotian Jiang, Yin Tat Lee, Zhao Song, and Sam Chiu-wai Wong. An improved cutting plane method for convex optimization, convex-concave games, and its applications. In *STOC*, pages 944–953. ACM, 2020b.
- Shunhua Jiang, Zhao Song, Omri Weinstein, and Hengjie Zhang. A faster algorithm for solving general lps. In *STOC*, pages 823–832. ACM, 2021.
- Shunhua Jiang, Bento Natura, and Omri Weinstein. A faster interior-point method for sum-of-squares optimization. In *ICALP*, volume 229 of *LIPICs*, pages 79:1–79:20. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2022.
- Shunhua Jiang, Binghui Peng, and Omri Weinstein. The complexity of dynamic least-squares regression. In *64th IEEE Annual Symposium on Foundations of Computer Science, FOCS 2023, Santa Cruz, CA, USA, November 6-9, 2023*, pages 1605–1627. IEEE, 2023. doi: 10.1109/FOCS57990.2023.00097.
- Ce Jin and Yinzhan Xu. Tight dynamic problem lower bounds from generalized bmm and omv. In *Proceedings of the 54th Annual ACM SIGACT Symposium on Theory of Computing, STOC 2022*, page 1515–1528, New York, NY, USA, 2022. Association for Computing Machinery. ISBN 9781450392648. doi: 10.1145/3519935.3520036. URL <https://doi.org/10.1145/3519935.3520036>.

Adam Karczmarz and Da Wei Zheng. Subquadratic algorithms in minor-free digraphs: (weighted) distance oracles, decremental reachability, and more. *arXiv*, 2024. URL <https://arxiv.org/abs/2410.12003>.

N. Karmarkar. A new polynomial-time algorithm for linear programming. *Combinatorica*, 4(4):373–396, 1984.

Toni Maria Klein, Christine Blome, C. Elise Kleyn, Curdin Conrad, Paul G. Sator, Mona Stähle, Kilian Eyerich, Marc Alexander Radtke, Christine Bundy, Myriam Cordey, Christopher E. M. Griffiths, and Matthias Augustin. Real-world experience of patient-relevant benefits and treatment satisfaction with apremilast in patients with psoriasis: An analysis of the appreciate study. *Dermatology and Therapy*, 12(1):81–95, 2022. doi: 10.1007/s13555-021-00628-3. URL <https://doi.org/10.1007/s13555-021-00628-3>.

Tuukka Korhonen, Wojciech Nadara, Michal Pilipczuk, and Marek Sokolowski. Fully dynamic approximation schemes on planar and apex-minor-free graphs. In David P. Woodruff, editor, *Proceedings of the 2024 ACM-SIAM Symposium on Discrete Algorithms, SODA 2024, Alexandria, VA, USA, January 7-10, 2024*, pages 296–313. SIAM, 2024. doi: 10.1137/1.9781611977912.12.

Rasmus Kyng and Sushant Sachdeva. Approximate gaussian elimination for laplacians - fast, sparse, and simple. In *FOCS*, pages 573–582. IEEE Computer Society, 2016.

Kasper Green Larsen and Ryan Williams. Faster online matrix-vector multiplication. In *Proceedings of the Twenty-Eighth Annual ACM-SIAM Symposium on Discrete Algorithms, SODA '17*, page 2182–2189, USA, 2017. Society for Industrial and Applied Mathematics.

Yin Tat Lee and Aaron Sidford. Efficient inverse maintenance and faster algorithms for linear programming. In *FOCS*, pages 230–249. IEEE Computer Society, 2015.

Yin Tat Lee, Aaron Sidford, and Sam Chiu-wai Wong. A faster cutting plane method and its implications for combinatorial and convex optimization. In *FOCS*, pages 1049–1065. IEEE Computer Society, 2015.

Yin Tat Lee, Zhao Song, and Qiuyi Zhang. Solving empirical risk minimization in the current matrix multiplication time. In *COLT*, volume 99 of *Proceedings of Machine Learning Research*, pages 2140–2157. PMLR, 2019.

Edo Liberty and Steven W. Zucker. The mailman algorithm: A note on matrix-vector multiplication. *Information Processing Letters*, 109(3):179–182, 2006. ISSN 0020-0190. doi: <https://doi.org/10.1016/j.ipl.2008.09.028>. URL <https://www.sciencedirect.com/science/article/pii/S0020019008002949>.

Yiheng Lin, James A Preiss, Emile Timothy Anand, Yingying Li, Yisong Yue, and Adam Wierman. Online adaptive policy selection in time-varying systems: No-regret via contractive perturbations. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023a. URL <https://openreview.net/forum?id=hDajsofjRM>.

Yiheng Lin, James A Preiss, Emile Timothy Anand, Yingying Li, Yisong Yue, and Adam Wierman. Learning-augmented control via online adaptive policy selection: No regret via contractive perturbations. In *ACM SIGMETRICS, Workshop on Learning-augmented Algorithms: Theory and Applications 2023*, 2023b. URL <https://learning-augmented-algorithms.github.io/papers/sigmetrics23-lata-posters->

- Yiheng Lin, James A. Preiss, Fengze Xie, Emile Anand, Soon-Jo Chung, Yisong Yue, and Adam Wierman. Online policy optimization in unknown nonlinear systems. In Shipra Agrawal and Aaron Roth, editors, *Proceedings of Thirty Seventh Conference on Learning Theory*, volume 247 of *Proceedings of Machine Learning Research*, pages 3475–3522. PMLR, 30 Jun–03 Jul 2024. URL <https://proceedings.mlr.press/v247/lin24a.html>.
- Yang P. Liu. On approximate fully-dynamic matching and online matrix-vector multiplication, 2024. URL <https://arxiv.org/abs/2403.02582>.
- Alane Marie de Lima, Murilo da Silva, and André Vignatti. A range space with constant vc dimension for all-pairs shortest paths in graphs. *Journal of Graph Algorithms and Applications*, 27:603–619, 08 2023. doi: 10.7155/jgaa.00636.
- Jiří Matoušek. Spanning trees with low crossing number. *RAIRO - Theoretical Informatics and Applications - Informatique Théorique et Applications*, 25(2):103–123, 1991.
- Jiří Matoušek. *Lectures on Discrete Geometry*, volume 212 of *Graduate Texts in Mathematics*. Springer, 2002. ISBN 978-0-387-95373-0. doi: 10.1007/978-1-4613-0039-7.
- Elchanan Mossel and Christopher Umans. On the complexity of approximating the vc dimension. *Journal of Computer and System Sciences*, 65(4):660–671, 2002. ISSN 0022-0000. doi: [https://doi.org/10.1016/S0022-0000\(02\)00022-3](https://doi.org/10.1016/S0022-0000(02)00022-3). Special Issue on Complexity 2001.
- Theodore S. Motzkin. Evaluation of polynomials and evaluation of rational functions. *Bulletin of the American Mathematical Society*, 57(2):163–169, 1951.
- Riley Murray, Venkat Chandrasekaran, and Adam Wierman. Newton polytopes and relative entropy optimization. *Foundations of Computational Mathematics*, 21(6):1703–1737, 2021. doi: 10.1007/s10208-021-09497-w.
- Tung Nguyen, Alex Scott, and Paul Seymour. Induced subgraph density. vi. bounded vc-dimension. *arXiv*, 2024. URL <https://arxiv.org/abs/2312.15572>.
- Vadim Olshevsky and Amin Shokrollahi. Matrix-vector product for confluent cauchy-like matrices with application to confluent rational interpolation. In *Proceedings of the Thirty-Second Annual ACM Symposium on Theory of Computing*, STOC '00, page 573–581, New York, NY, USA, 2000. Association for Computing Machinery. ISBN 1581131844. doi: 10.1145/335305.335380. URL <https://doi.org/10.1145/335305.335380>.
- Lawrence Page, Sergey Brin, Rajeev Motwani, and Terry Winograd. The pagerank citation ranking: Bringing order to the web. Technical Report 1999-66, Stanford InfoLab, 1999. URL <https://ilpubs.stanford.edu:8090/422/>.
- Victor Y. Pan and Elias P. Tsigaridas. Nearly optimal computations with structured matrices. In *Proceedings of the 2014 Symposium on Symbolic-Numeric Computation*, SNC '14, page 21–30, New York, NY, USA, 2014. Association for Computing Machinery. ISBN 9781450329637. doi: 10.1145/2631948.2631954. URL <https://doi.org/10.1145/2631948.2631954>.
- James Renegar. Condition numbers, the barrier method, and the conjugate-gradient method. *SIAM Journal on Optimization*, 6(4):879–912, 1996.
- David E. Rumelhart, Geoffrey E. Hinton, and Ronald J. Williams. Learning representations by back-propagating errors. *Nature*, 323(6088):533–536, 1986. doi: 10.1038/323533a0.

- Shai Shalev-Shwartz and Shai Ben-David. *Understanding Machine Learning: From Theory to Algorithms*. Cambridge University Press, Cambridge, UK, 2014. ISBN 978-1-107-05713-5.
- Hans Henrik Brandenborg Sørensen. High-performance matrix-vector multiplication on the gpu. In Michael Alexander, Pasqua D’Ambra, Adam Belloum, George Bosilca, Mario Cannataro, Marco Danelutto, Beniamino Di Martino, Michael Gerndt, Emmanuel Jeannot, Raymond Namyst, Jean Roman, Stephen L. Scott, Jesper Larsson Traff, Geoffroy Vallée, and Josef Weidendorfer, editors, *Euro-Par 2011: Parallel Processing Workshops*, pages 377–386, Berlin, Heidelberg, 2012. Springer Berlin Heidelberg. ISBN 978-3-642-29737-3.
- Daniel A. Spielman and Shang-Hua Teng. Nearly-linear time algorithms for graph partitioning, graph sparsification, and solving linear systems. In *STOC’04: Proceedings of the 36th Annual ACM Symposium on the Theory of Computing*, pages 81–90. ACM, 2004.
- Ali Tizghadam and Alberto Leon-Garcia. On robust traffic engineering in transport networks. In *IEEE GLOBECOM 2008 - 2008 IEEE Global Telecommunications Conference*, pages 1–6, 2008. doi: 10.1109/GLOCOM.2008.ECP.456.
- Pravin M. Vaidya. Speeding-up linear programming using fast matrix multiplication (extended abstract). In *FOCS*, pages 332–337. IEEE Computer Society, 1989.
- Jan van den Brand, Sebastian Forster, and Yasamin Nazari. Fast deterministic fully dynamic distance approximation. In *63rd IEEE Annual Symposium on Foundations of Computer Science, FOCS 2022, Denver, CO, USA, October 31 - November 3, 2022*, pages 1011–1022. IEEE, 2022. doi: 10.1109/FOCS54457.2022.00099. URL <https://doi.org/10.1109/FOCS54457.2022.00099>.
- Santosh S Vempala, Ruosong Wang, and David P Woodruff. The communication complexity of optimization. In *Proceedings of the Fourteenth Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 1733–1752. SIAM, 2020.
- E. Welzl. Partition trees for triangle counting and other range searching problems. In *Proceedings of the Fourth Annual Symposium on Computational Geometry, SCG ’88*, page 23–33, New York, NY, USA, 1988. Association for Computing Machinery. ISBN 0897912705. doi: 10.1145/73393.73397.
- Emo Welzl. On spanning trees with low crossing numbers. *Lecture Notes in Computer Science*, 1992.
- Ryan Williams. Matrix-vector multiplication in sub-quadratic time: (some preprocessing required). In *Proceedings of the Eighteenth Annual ACM-SIAM Symposium on Discrete Algorithms, SODA ’07*, page 995–1001, USA, 2007. Society for Industrial and Applied Mathematics. ISBN 9780898716245.
- Virginia Vassilevska Williams and Ryan Williams. Subcubic equivalences between path, matrix and triangle problems. In *51th Annual IEEE Symposium on Foundations of Computer Science, FOCS 2010, October 23-26, 2010, Las Vegas, Nevada, USA*, pages 645–654. IEEE Computer Society, 2010. doi: 10.1109/FOCS.2010.67. URL <https://doi.org/10.1109/FOCS.2010.67>.
- Virginia Vassilevska Williams, Yinzhan Xu, Zixuan Xu, and Renfei Zhou. New bounds for matrix multiplication: from alpha to omega. In *SODA*, pages 3792–3835. SIAM, 2024.
- Hakan Yildiz and Subhash Suri. On klee’s measure problem for grounded boxes. In *Proceedings of the Twenty-Eighth Annual Symposium on Computational Geometry, SoCG ’12*, page 111–120, New York, NY, USA, 2012. Association for Computing Machinery. ISBN 9781450312998. doi: 10.1145/2261250.2261267. URL <https://doi.org/10.1145/2261250.2261267>.

Appendix A. Online Matrix Vector Data Structure

In this section we prove all the intermediate lemmas required for our first two main results on subquadratic online matrix-vector multiplication. The proof that combined the technical lemmas was already given in Section 3.

Theorem 3 (*Static Online Matrix-Vector Multiplication*). *If a matrix $\mathbf{M} \in \{0, 1\}^{m \times n}$ has corrupted VC-dimension d , then after an $\tilde{O}(mn)$ -time preprocessing, there is a data structure \mathcal{D} that can compute $\mathbf{M}v$ for any $v \in \mathbb{R}^n$ in $\tilde{O}(mn^{1-1/d} + n)$ time, with high probability.*

Theorem 4 (*Dynamic Online Matrix-Vector Multiplication*). *Given a matrix $\mathbf{M} \in \{0, 1\}^{m \times n}$, there is a data structure \mathcal{D} with $\tilde{O}(mn)$ preprocessing time that supports row and column updates (insertions/deletions) to \mathbf{M} in $\tilde{O}(n)$ and $\tilde{O}(m)$ time respectively. Upon querying the data structure \mathcal{D} with a vector $v \in \mathbb{R}^n$, it outputs $\mathbf{M}v$ in $\tilde{O}(mn^{1-1/d^*} + n)$ time, with high probability, where d^* is the largest corrupted VC-dimension of \mathbf{M} throughout the history of its updates.*

A.1. Static Online Matrix Vector Multiplication Data Structure

Definition 11 (Δ -labeled spanning tree of matrix \mathbf{M}) *A Δ -labeled tree is a tree $T = (V, E)$ with some explicit root x , where each edge $e \in E$ is directed away from x and labeled by a vector $\Delta_e \in \mathbb{R}^m$. We say T is a Δ -labeled spanning tree for matrix $\mathbf{M} \in \mathbb{R}^{m \times n}$ if $\mathbf{M}_x = \mathbf{0}$ for root x , and for all edges $(i, j) \in E$ we have $\Delta_{i,j} := \mathbf{M}_j - \mathbf{M}_i$.*

Definition 12 (**Weight of a Δ -labeled spanning tree**) *For any Δ -labeled spanning tree of \mathbf{M} denoted by T with directed edge-set E , define $\text{weight}(T)$ as the total number of non-zero entries given by $\sum_{e \in T} \text{nnz}(\Delta_e)$.*

Lemma 13 (**Gasieniec and Lingas (2003); Alves et al. (2024)**) *Given a Δ -labeled spanning tree T of $\mathbf{M}^\top \in \{0, 1\}^{n \times m}$ and a vector $v \in \mathbb{R}^n$, there is an algorithm that computes $\mathbf{M}v$ in $O(\text{weight}(T) + n + m)$ time.*

Proof Consider Algorithm 1 which takes as input $\mathbf{M} \in \{0, 1\}^{m \times n}$, a Δ -labeled spanning tree of \mathbf{M}^\top (denoted by T), and a vector $v \in \mathbb{R}^n$.

We inductively prove that $\Phi = \mathbf{M}v$ over the number of visited vertices. This is true when only one vertex is visited, as that is the root r and by definition $\Phi_r = (\mathbf{M}v)_r$.

For the inductive step, assume DFS visits the $(k + 1)$ st vertex x . Let y be the parent of the vertex, then the algorithm assigns

$$\begin{aligned} \Phi_x &= \Phi_y + \Delta_{y,x}^\top v \\ &= (\mathbf{M}v)_y + (\mathbf{M}_x - \mathbf{M}_y)v \\ &= (\mathbf{M}v)_x. \end{aligned}$$

Here Φ_y is already computed since it was among the first k visited vertices.

Runtime analysis. Let $\delta_{i,j}$ be the number of non-zero entries in $\Delta_{i,j}$ for all $(i, j) \in E(T)$. Initializing the vector Φ and populating its first element Φ_r takes $O(n + m)$ time. The cost of populating the remaining entries is proportional to the number of non-zero entries in each $\Delta_{x,y}$, since we can store each Δ via a sparser representation of only its non-zero entries and use this to compute $\Delta_{y,x}^\top v$ in time $O(\delta_{y,x})$. Thus, the total time complexity is $O(\sum_{(x,y) \in E(T)} \delta_{x,y}) = O(\text{weight}(T))$. Hence, the runtime of algorithm 1 is $O(\text{weight}(T) + n + m)$, proving the lemma. \blacksquare

Algorithm 1 Online Matrix-vector multiplication (given a Δ -labeled tree of \mathbf{M}^\top)

Require: Input matrix $\mathbf{M} \in \{0, 1\}^{m \times n}$, and a Δ -labeled tree of \mathbf{M}^\top denoted by T and rooted at r .

Require: Input vector $v \in \mathbb{R}^n$.

Initialize: $\Phi = 0^m$

$\Phi_r = \mathbf{M}_r^\top v$

Run DFS on T from root r . Whenever DFS visits a vertex $x \in V$ via some edge (y, x) , then

set $\Phi_x = \Phi_y + \Delta_{x,y}v$

Return Φ

Definition 24 (Path- Δ matrix $\mathbf{N}^{(T)}$) Given a Δ -labeled subtree $T = (V, E)$ with root r , define the path- Δ matrix $\mathbf{N}^{(T)} \in \mathbb{R}^{m \times V}$ such that for $u \in V$,

$$\mathbf{N}_u^{(T)} := \sum_{e \in P(r \rightarrow u)} \Delta_e.$$

Here, $P(r \rightarrow u)$ denotes the edges of the unique (since T is acyclic) directed path from r to u .

Lemma 25 For Δ -labeled tree $T = (V, E)$, and a vector $v \in \mathbb{R}^V$, let $\sigma \in \mathbb{R}^E$ with $\sigma_{(y,c)} = \sum_{z \in V(T_c)} v_z$, where T_c is the subtree rooted at $c \in V$. Let $\Delta \in \mathbb{R}^{m \times E}$ be the matrix with columns being the labels of tree T . Then $\Delta\sigma = \mathbf{N}^{(T)}v$.

Proof By the definition of $\mathbf{N}^{(T)}$, we have

$$\begin{aligned} \mathbf{N}^{(T)}v &= \sum_{y \in V} \mathbf{N}_y^{(T)} \cdot v_y \\ &= \sum_{y \in V} \sum_{e \in P(r \rightarrow y)} \Delta_e \cdot v_y \end{aligned}$$

Now consider how often any one edge e shows up in this sum: an edge $e = (x, z)$ is in $P(r \rightarrow y)$ if and only if z is an ancestor of y (or $y = z$) (or, in other words, if y is a descendant of z (or $y = z$)). This condition can be written as $y \in T_z$. Thus we write the sum as

$$\begin{aligned} \sum_{y \in V} \sum_{e \in P(r \rightarrow y)} \Delta_e \cdot v_y &= \sum_{(x,z) \in E} \sum_{y \in T_z} \Delta_{x,z} \cdot v_y \\ &= \sum_{(x,z) \in E} \Delta_{x,z} \sum_{y \in T_z} v_y \\ &= \sum_{(x,y) \in E} \Delta_{x,y} \sigma_y \\ &= \Delta\sigma, \end{aligned}$$

which proves the claim. ■

Lemma 26 Let T be a Δ -labeled spanning tree of \mathbf{M} where the root r of T has $\mathbf{M}_r = \mathbf{0}$, then $\mathbf{N}^{(T)} = \mathbf{M}$.

Proof We prove this by induction over the width of \mathbf{M} .

Base Case. For width 1, T is just the root r , so $\mathbf{N}^{(T)} = \mathbf{0} = \mathbf{M}$.

Inductive Step. Suppose the statement holds for matrices of width $< n$ and we now have a matrix \mathbf{M} of width n . Let $L \subset V$ be the leaves of T . Let T' be the tree T with these leafs removed, and let $\mathbf{M}' \in \{0, 1\}^{m \times (V \setminus L)}$ be matrix \mathbf{M} with all columns corresponding to L removed. Then for any $y \in V \setminus L$

$$\mathbf{M}_y = \mathbf{M}'_y \stackrel{(1)}{=} \mathbf{N}_y^{(T')} \stackrel{(2)}{=} \mathbf{N}_y^{(T)}$$

where equality (1) uses the induction hypothesis and equality (2) uses the fact that any path in the leaf-removed tree T' also exists in T .

For any $y \in L$ let z be its ancestor in T . Therefore, $z \notin L$. Then, we have

$$\mathbf{N}_y^{(T)} = \mathbf{N}_z^{(T)} + \Delta_{z,y} \tag{1}$$

$$= \mathbf{N}_z^{(T')} + \Delta_{z,y} \tag{2}$$

$$= \mathbf{M}'_z + \Delta_{z,y} \tag{3}$$

$$= \mathbf{M}_z + (\mathbf{M}_y - \mathbf{M}_z) = \mathbf{M}_y,$$

where equation 1 uses the fact that the path from root r to y is a path from root r to z with one extra edge (z, y) . Equation 2 uses the fact the path from r to z in T also exists in T' , and finally equation 3 follows by the induction hypothesis. Together, they prove the lemma. \blacksquare

Lemma 14 *Given a Δ -labeled spanning tree T of $\mathbf{M} \in \{0, 1\}^{m \times n}$ and a vector $v \in \mathbb{R}^n$, there is an algorithm that can compute $\mathbf{M}v$ in $O(\text{weight}(T) + n + m)$ time.*

Proof

Algorithm: We compute $\mathbf{N}^{(T)}v$ via Lemma 25 which requires us to compute the vector $\sigma \in \mathbb{R}^E$ with $\sigma_{(y,c)} = \sum_{z \in V(T_c)} v_z$ for all $(y, c) \in E$ where T_c is the subtree of T rooted at c . This can be done in $O(n)$ time via a simple “dynamic programming on trees” algorithm: For any $c \in V$, let C be its children. Then

$$\begin{aligned} \sigma_{(y,c)} &= \sum_{z \in V(T_c)} v_z \\ &= v_c + \sum_{x \in C} \sum_{z \in V(T_x)} v_z \\ &= v_c + \sum_{x \in C} \sigma_{(c,x)}. \end{aligned}$$

So we can compute σ in $O(n)$ by starting at the leaf-edges, then propagating the sums up towards the root. At last, we multiply $\Delta\sigma$ in $O(\text{weight}(T))$ time as that is the number of non-zeros in Δ (which is the matrix consisting of the tree labels as column-vectors).

Correctness. Without loss of generality, assume that for root r of tree T we have $\mathbf{M}_r = \mathbf{0}$. Otherwise, append a $\mathbf{0}$ -column to \mathbf{M} , and add edge $(n+1, r)$ to T with label $\Delta_{n+1,r} = \mathbf{M}_r - \mathbf{M}_{n+1} = \mathbf{M}_r$, and make $n+1$ the new root of T . This increases the tree weight by at most m , resulting in an additive $O(m)$ in the time complexity.

Append another entry to v so that the dimensions match and $\mathbf{M}v$ is well-defined. By lemma 26, we thus have $\mathbf{N}^{(T)}v = \mathbf{M}v$. \blacksquare

A.2. Dynamic OMv Data Structure

In this section we give a black-box reduction from dynamic OMv to static OMv. In the static version, we are given a matrix \mathbf{M} to preprocess. This matrix stays fixed, while we receive an online sequence of vectors and must repeatedly compute $\mathbf{M}v$. In the dynamic version, we can inform the data structure about changes to \mathbf{M} . In particular, we are allowed to add/remove/change rows and columns of the matrix.

Using the reduction from dynamic to static, we obtain Theorem 4.

Theorem 4 (*Dynamic Online Matrix-Vector Multiplication*). *Given a matrix $\mathbf{M} \in \{0, 1\}^{m \times n}$, there is a data structure \mathcal{D} with $\tilde{O}(mn)$ preprocessing time that supports row and column updates (insertions/deletions) to \mathbf{M} in $\tilde{O}(n)$ and $\tilde{O}(m)$ time respectively. Upon querying the data structure \mathcal{D} with a vector $v \in \mathbb{R}^n$, it outputs $\mathbf{M}v$ in $\tilde{O}(mn^{1-1/d^*} + n)$ time, with high probability, where d^* is the largest corrupted VC-dimension of \mathbf{M} throughout the history of its updates.*

The idea of this reduction is to split the columns of \mathbf{M} into $\log n$ matrices $\mathbf{M}_0, \dots, \mathbf{M}_{\log n}$ where \mathbf{M}_i contains at most 2^i columns. Each \mathbf{M}_i is used as input to a static OMv data structure which is reinitialized whenever \mathbf{M}_i changes which occurs at most once every 2^i updates to \mathbf{M} . This allows to amortize the reinitialization cost over multiple updates.

Lemma 27 *Assume there is a static OMv data structure for matrices of size $m \times n$ with preprocessing time $P(m, n)$ and query time $Q(m, n)$. Then there exists a dynamic OMv data structure supporting row and column insertions and deletions. The preprocessing time is $\tilde{O}(P(m, n))$, the amortized row update time is*

$$O\left(\sum_{j=0}^{\log m} \frac{P(2^j, n)}{2^j}\right)$$

and for column updates

$$O\left(\sum_{i=0}^{\log n} \frac{P(m, 2^i)}{2^i}\right)$$

and query time is $\tilde{O}(Q(m, n))$. This reduction runs several static OMv data structures, each receiving a submatrix of the dynamic input matrix.

We start by proving column updates only, then extend the reduction to support row updates as well.

Lemma 28 *Assume there is a static OMv data structure for matrices of size $m \times n$ with preprocessing time $P(m, n)$ and query time $Q(m, n)$. Then there exists a dynamic OMv data structure supporting column insertions and deletions. The preprocessing time is $\tilde{O}(P(m, n))$, the query time is $\tilde{O}(Q(m, n))$, and the amortized update time is*

$$O\left(\sum_{i=0}^{\log m} \frac{P(m, 2^i)}{2^i}\right)$$

This reduction runs several static OMv data structures, each receiving a submatrix of the dynamic input matrix.

Proof Let \mathbf{M} be the input matrix that changes over time.

Initialization. We run $\log n$ instances of the static OMv data structure, where the i th instance is guaranteed to run on a matrix with at most 2^i columns. Let $\mathbf{M}^{(0)}, \dots, \mathbf{M}^{(\log n)}$ be the respective input matrices to these instances. Initially, only the last ($i = \log n$) data structure receives the initial matrix \mathbf{M} as input, and all other instances of the data structure initialize on an empty matrix. Hence initialization takes $O(P(m, n))$ time.

Insertions. Whenever there is a column insertion to $\mathbf{M}^{(i)}$ we reinitialize the i th static OMv data structure on that new matrix. When $\mathbf{M}^{(i)}$ has more than 2^i columns, then all columns are removed (i.e., we set $\mathbf{M}^{(i)} = 0$) and inserted to matrix $\mathbf{M}^{(i+1)}$. All column insertions to \mathbf{M} are passed to $\mathbf{M}^{(0)}$. Observe that any $\mathbf{M}^{(i)}$ is updated every 2^i updates to \mathbf{M} , hence the amortized update time is

$$O\left(\sum_{i=0}^{\log n} P(m, 2^i)/2^i\right).$$

Queries. We can answer queries by observing that

$$\mathbf{M} = [\mathbf{M}^{(\log m)} | \dots | \mathbf{M}^{(1)} | \mathbf{M}^{(0)}].$$

So, for a query vector v we split it into corresponding pieces $v^{(0)}, \dots, v^{(\log m)}$ and query each $\mathbf{M}^{(i)} v^{(i)}$. The time for this is

$$O(Q(m, n) \log n)$$

because each $\mathbf{M}^{(i)}$ is a submatrix of \mathbf{M} and we have $\log n$ such matrices.

Deletions. When deleting a column of \mathbf{M} , we do not delete the column from the respective $\mathbf{M}^{(i)}$. Instead, all future query vectors v will have an extra 0 entry for the deleted column.

When all columns from $\mathbf{M}^{(i)}$ are appended to $\mathbf{M}^{(i+1)}$ because of some insertions, then the deleted columns are not appended to $\mathbf{M}^{(i+1)}$. Hence whenever a static OMv data structure is initialized, it is a submatrix of the input matrix \mathbf{M} .

When there have been $2^i/2$ postponed deletions to any $\mathbf{M}^{(i)}$, then the columns are actually deleted and the respective static OMv data structure is reinitialized on the new $\mathbf{M}^{(i)}$. The remaining columns in $\mathbf{M}^{(i)}$ all exist in the current dynamic input \mathbf{M} , so again, the static OMv data structure receives a submatrix of \mathbf{M} as input. For any one i , this takes amortized $O(P(n, 2^i)/2^i)$ time which is subsumed by the complexity of handling insertions.

Observe that internally, our matrices $\mathbf{M}^{(i)}$ are always at most twice their intended size because of the yet to be removed columns. Thus the query complexity increases by at most a constant factor. ■

Proof of Lemma 27 (Row & Column Updates) Here, we extend Lemma 28 to support row updates as well. The reduction follows the same idea as Lemma 28.

Let \mathbf{N} be the dynamic input matrix. We run $\log n$ copies of the column update data structure Lemma 28 on matrices $\mathbf{N}^{(0)}, \dots, \mathbf{N}^{(\log n)}$, with the i th matrix having at most 2^i rows. When inserting new rows to \mathbf{N} , they are passed to $\mathbf{N}^{(0)}$. When $\mathbf{N}^{(i)}$ has more than 2^i rows, all rows are appended to $\mathbf{N}^{(i+1)}$. When rows are appended to any $\mathbf{N}^{(i)}$, the respective data structure is reinitialized. To handle deletions, we remove the respective row from the output until $2^i/2$ rows have been deleted from $\mathbf{N}^{(i)}$, then the rows are removed from $\mathbf{N}^{(i)}$ and the respective data structure is reinitialized.

The amortized row update time thus becomes

$$O\left(\sum_{j=0}^{\log n} \text{Time to initialize Lemma 28 on } 2^j \times n \text{ matrix}/2^j\right) = O\left(\sum_{j=0}^{\log m} P(2^j, n)/2^j\right).$$

For column updates, each of the $\mathbf{N}^{(i)}$ receives a new column, so each of the $\log m$ column update data structures is updated which takes:

$$O\left(\sum_{j=0}^{\log m} \sum_{i=0}^{\log n} P(2^j, 2^i)/2^i\right) = O\left(\sum_{i=0}^{\log n} P(m, 2^i)/2^i\right)$$

because geometric sums are bounded by their largest term in O -notation.

Finally, the query time is

$$\tilde{O}\left(\sum_{j=0}^{\log m} Q(2^j, n)\right) = \tilde{O}(Q(m, n)),$$

which proves the lemma. ■

Proof of Theorem 4 (Dynamic OMv for corrupted VC-dimension d) The initialization cost of static OMv is $P(m, n) = \tilde{O}(mn)$, and the query complexity is $Q(m, n) = \tilde{O}(mn^{1-1/d})$ by Theorem 3. This complexity also holds for submatrices, i.e., $Q(a, b) = \tilde{O}(mn^{2-1/d} + n)$ for any $a \times b$ sized submatrix.

Thus we have update time for column updates:

$$O\left(\sum_{i=0}^{\log n} P(m, 2^i)/2^i\right) = \tilde{O}\left(\sum_{i=0}^{\log n} m2^i/2^i\right) = \tilde{O}(m)$$

and for row updates we have

$$O\left(\sum_{j=0}^{\log m} P(2^j, n)/2^j\right) = \tilde{O}\left(\sum_{j=0}^{\log m} 2^j n/2^j\right) = \tilde{O}(n)$$

and for query time we have

$$\tilde{O}(Q(m, n)) \leq \tilde{O}(mn^{1-1/d} + n),$$

which proves the theorem. ■

A.3. Extension to Structured Non-Boolean Matrices

In this section, we prove the following lemma.

Lemma 29 *Suppose that the Pollard pseudodimension of the matrix $\mathbf{M} \in \mathbb{R}^{m \times n}$ is d , and that the number of thresholds is A . Then, after an $\tilde{O}(Amn)$ time preprocessing, there is a data structure that, upon receiving a vector $v \in \mathbb{R}^n$, can return $\mathbf{M}v$ in time $O(Amn^{1-1/d} + An)$.*

Recall the definition of the Pollard pseudodimension:

Definition 30 (Pollard Pseudodimension) *For a family of functions F mapping V to $\{0, \dots, \ell - 1\}$, the Pollard pseudodimension of \mathcal{F} , denoted by $\text{Pdim}(\mathcal{F})$, is the largest integer d such that there exists $x_1, \dots, x_d \in V$ and thresholds $y_1, \dots, y_d \in [\ell]$ such that for any d -length bit vector $\mathbf{b} = (b_1, \dots, b_d) \in \{0, 1\}^d$, there exists an $f \in \mathcal{F}$ such that $\forall i, f(x_i) \leq y_i \iff b_i = 1$.*

As an example, consider an integer matrix and split each row into the different thresholds.

$$[1 \quad 2 \quad 4 \quad 2] \rightarrow \begin{bmatrix} 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 \\ 1 & 1 & 0 & 1 \\ 1 & 1 & 1 & 1 \end{bmatrix}$$

Then, the right matrix has VC dimension d , if and only if the left matrix has Pollard pseudodimension d .

Definition 31 (Multiball vectors) Let $v \in V$ be a vertex of the graph G . Let r be a real number and Δ be a set of distances $-\infty = \delta_0 < \delta_1 < \dots < \delta_{\ell-1} < \delta_\ell = \infty$. Define the multiball vectors as follows:

$$\mathbf{MB}(v, r, \Delta) = (y_u)_{u \in V} \text{ where } y_u \in [\ell] \text{ is the smallest integer such that } u \in \mathbf{B}(v, r + \delta_{y_u}).$$

Let $\mathbf{MB}_{G, \Delta} = \{\mathbf{MB}(v, r, \Delta) | v \in V, r \in \mathbb{R}\}$ be the set of all multiball vectors in G with shifts Δ .

Theorem 32 (Karczmarz and Zheng (2024)) For a K_h -minor-free graph G , for any set Δ of ℓ distances, the set of multiball vectors $\mathbf{MB}_{G, \Delta}$ has pseudodimension at most $h - 1$.

Lemma 33 (Generalized Sauer-Shelah lemma) Let \mathcal{F} be a family of functions mapping a ground set with n elements to $[\ell]$. If the pseudodimension of \mathcal{F} is at most d , then $|\mathcal{F}| \leq O(n^d \ell^d)$.

Lemma 34 Let \mathcal{F} be a family of functions mapping a ground set with n elements to $[\ell]$. Let $\mathcal{F}_S = \mathcal{F} \cap [\ell]^S$ be a restriction of \mathcal{F} to S . Then, $\text{Pdim}(\mathcal{F}_S) \leq \text{Pdim}(\mathcal{F})$.

Corollary 35 Let \mathcal{F} be a family of functions mapping a ground set with n elements to $[\ell]$, and let S be any subset of the ground set of \mathcal{F} . Suppose $\text{Pdim}(\mathcal{F}) = d$. Then, $|\mathcal{F}_S| = O(|S|^d \ell^d)$.

Definition 36 For a real matrix \mathbf{M} , define the pseudo-dimension of \mathbf{M} , denoted by $\text{Pdim}(\mathbf{M})$ by thinking of the rows of \mathbf{M} as functions and taking the pseudo-dimension of the resulting class of functions. Specifically, if \mathbf{M} is an $m \times n$ matrix, for each $i \in \{1, \dots, m\}$, define $f_{\mathbf{M}, i} : \{1, \dots, n\} \rightarrow \mathbb{R}$ by $f_{\mathbf{M}, i}(j) = \mathbf{M}_{i, j}$ and let $\text{Pdim}(\mathbf{M}) = \text{Pdim}(\{f_{\mathbf{M}, i} : i \in \{1, \dots, m\}\})$.

Lemma 37 Given any matrix $\mathbf{M} \in \mathbb{Z}^{n \times n}$, construct the Boolean matrix $\mathbf{N} \in \{0, 1\}^{n \times n}$ such that $\mathbf{N}_{i, j} = \mathbb{1}\{\mathbf{M}_{i, j} \geq 0\}$ for $i, j \in [n]$. Then, $\text{VC}(\mathbf{N}) \leq \text{Pdim}(\mathbf{M})$.

Proof Given a matrix \mathbf{M} , we have threshold functions $f_{\mathbf{M}, i}$ such that $f_{\mathbf{M}, i}(j) = \mathbf{M}_{i, j}$ and can use this this to define a set family

$$\mathcal{F} = \{f_{\mathbf{M}, i} : \{1, \dots, n\} \rightarrow \mathbb{R} | i = 1, \dots, m\},$$

and $\text{Pdim}(\mathbf{M}) = \text{Pdim}(\mathcal{F})$.

By definition, $\text{Pdim}(\mathbf{M})$ is the largest integer d such that $\exists x_1, \dots, x_d \in \{0, \dots, \ell - 1\}$ and thresholds $y_1, \dots, y_d \in [\ell]$ such that for any vector $b_1, \dots, b_d \in \{-1, 1\}^d$, there is an $f \in \mathcal{F}$ such that $\forall i, \text{sign}(f(x_i) - y_i) = b_i$.

Define the following 0/1 profile of matrix \mathbf{M} . For each row i of \mathbf{M} , define the binary function

$$g_{\mathbf{M}, i} : \{1, \dots, n\} \rightarrow \{0, 1\}$$

by

$$g_{\mathbf{M}, i}(j) = \mathbb{1}\{f_{\mathbf{M}, i}(j) \geq 0\} := \mathbb{1}\{\mathbf{M}_{i, j} \geq 0\},$$

and use this to define the set family

$$\mathcal{G} = \{g_{\mathbf{M}, i} : i = 1, \dots, m\}.$$

We want to show that if $\text{Pdim}(\mathbf{M})$ is low ($\text{Pdim}(\mathbf{M}) = d$), then the VC-dimension of \mathcal{G} is at most d . So, by way of contradiction, suppose $\text{Pdim}(\mathcal{F}) = d$ and $\text{VC}(\mathcal{G}) \geq d + 1$.

Then, there must exist $S \subset \{1, \dots, n\}$ with $|S| = d + 1$ that is shattered by \mathcal{G} . So, for every 0/1 labeling of $c : S \rightarrow \{0, 1\}$, there is some row i for which $g_{\mathbf{M}, i}(j) = c(j), \forall j \in S$.

Also, $\exists x_1, \dots, x_d \in \{0, \dots, \ell - 1\}$ and thresholds $y_1, \dots, y_d \in [\ell]$ such that for any vector $b_1, \dots, b_d \in \{-1, 1\}^d$, there is an $f \in \mathcal{F}$ such that $\forall i \in [d], \text{sign}(f(x_i) - y_i) = b_i$.

Also, note that the condition

$$g_{\mathbf{M},i}(j) = \mathbb{1}\{f_{\mathbf{M},i}(j) \geq 0\} = c(j)$$

is equivalent to

$$\text{sign}(f_{\mathbf{M},i}(j) - 0) = b_j^*, \text{ for } b_j^* = \begin{cases} +1, & c(j) = 1, \\ -1, & c(j) = 0 \end{cases}$$

but this just means that S is pseudo-shattered by the class \mathcal{F} , where the thresholds $y_1, \dots, y_d = 0$ for all $j \in S$. So, this implies $\text{Pdim}(\mathbf{M}) = d + 1$, which is a contradiction. So, $\text{VC}(\mathcal{G}) \leq \text{Pdim}(\mathcal{F})$. \blacksquare

Lemma 38 *Suppose that the Pollard pseudodimension of the matrix $\mathbf{M} \in \mathbb{R}^{m \times n}$ is d , and that the number of thresholds is A . Then, after an $\tilde{O}(Amn)$ time preprocessing, there is a data structure that, upon receiving a vector $v \in \mathbb{R}^n$, can return $\mathbf{M}v$ in time $O(Amn^{1-1/d} + An)$.*

Proof Given the matrix $\mathbf{M} \in \mathbb{R}^{n \times n}$ with A thresholds $\tau_1, \tau_2, \dots, \tau_A \in \mathbb{R}^A$, construct the Boolean matrix $\mathbf{N} \in \{0, 1\}^{Am \times n}$ as follows: for row $i \in [n]$ of \mathbf{M} , define the block $\mathcal{B}^{(i)} := \mathcal{B}(\mathbf{M}_i) \in \{0, 1\}^{A \times n}$ by

$$\mathcal{B}(\mathbf{M}_i) = \begin{bmatrix} \mathbb{1}\{\mathbf{M}_{i,1} \geq \tau_1\} & \mathbb{1}\{\mathbf{M}_{i,2} \geq \tau_1\} & \cdots & \mathbb{1}\{\mathbf{M}_{i,n-1} \geq \tau_1\} & \mathbb{1}\{\mathbf{M}_{i,n} \geq \tau_1\} \\ \mathbb{1}\{\mathbf{M}_{i,1} \geq \tau_2\} & \mathbb{1}\{\mathbf{M}_{i,2} \geq \tau_2\} & \cdots & \mathbb{1}\{\mathbf{M}_{i,n-1} \geq \tau_2\} & \mathbb{1}\{\mathbf{M}_{i,n} \geq \tau_2\} \\ & & \ddots & & \\ \mathbb{1}\{\mathbf{M}_{i,1} \geq \tau_A\} & \mathbb{1}\{\mathbf{M}_{i,2} \geq \tau_A\} & \cdots & \mathbb{1}\{\mathbf{M}_{i,n-1} \geq \tau_A\} & \mathbb{1}\{\mathbf{M}_{i,n} \geq \tau_A\} \end{bmatrix}$$

Then, matrix $\mathbf{N} \in \{0, 1\}^{Am \times n}$ is given by

$$\mathbf{N} = \begin{bmatrix} \mathcal{B}^{(1)} \\ \mathcal{B}^{(2)} \\ \vdots \\ \mathcal{B}^{(m)} \end{bmatrix}$$

By lemma 37, the VC-dimension of \mathbf{N} is at most the Pollard pseudodimension of \mathbf{M} , given by d . Constructing \mathbf{N} takes $O(mnA)$ time. Then, using theorem 3, we can preprocess \mathbf{N} in $\tilde{O}(Amn)$ time to support queries that return $\mathbf{N}v$ for any vector $v \in \mathbb{R}^n$ in time $\tilde{O}(Amn^{1-1/d} + n)$. To convert $\mathbf{N}v \in \mathbb{R}^{Am}$ to $\mathbf{M}v \in \mathbb{R}^m$, iterate over each of the m sets of A entries of $\mathbf{N}v$. For $i \in [m]$, denote the i 'th set of A entries by $x_i^{(1)}, x_i^{(2)}, \dots, x_i^{(A)}$, where $x_i^{(j)} := (\mathbf{M}v)_{A(i-1)+j}$. Then, defining y_i as the linear combination of the threshold maps with the outputs $x_i^{(j)}$, we have $y_i := \sum_{j=1}^A x_i^{(j)} \tau_j$. Therefore, $\mathbf{N}v$ is given by

$$\mathbf{N}v = \begin{bmatrix} y_1 \\ y_2 \\ \vdots \\ y_m \end{bmatrix},$$

which proves the claim. \blacksquare

Appendix B. Applications

In this section, we consider some applications of our OMv result in Theorem 4. These applications have quadratic $\Omega(n^2)$ -time lower bounds, conditional on the OMv conjecture. We show that on structured graph this lower bound can be beaten.

B.1. High-accuracy Dynamic Laplacian Solver

Theorem 6 (Dynamic Laplacian Solver). *There is a dynamic algorithm that, given a dynamic graph $G = (V, E)$ with corrupted VC-dimension bounded by d , maintains a Laplacian system solver. The data structure supports queries that receive a vector $b \in \mathbb{R}^{|V|}$ and error parameter $\epsilon > 0$. Then, in $\tilde{O}(n^{2-1/d} \log 1/\epsilon)$ time, the algorithm returns the (approximate) solution x to $\mathbf{L}x^* = b$ where $\|x - x^*\|_{\mathbf{L}} \leq \epsilon \|x^*\|_{\mathbf{L}}$. Each vertex update to G takes $\tilde{O}(n)$ time.*

We consider the setting where the Laplacian \mathbf{L} corresponds to a graph with bounded VC-dimension. First, recall the notion of spectral sparsifiers.

Definition 39 (($1 + \epsilon$)-spectral sparsifiers) *Let \mathbf{L}_X denote the Laplacian of any undirected graph X . Then, a $(1 \pm \epsilon)$ -spectral sparsifier H of a graph G is a subgraph of G such that for every vector $x \in \mathbb{R}^n$,*

$$(1 - \epsilon)x^\top \mathbf{L}_H x \leq x^\top \mathbf{L}_G x \leq (1 + \epsilon)x^\top \mathbf{L}_H x,$$

Then, a result from [Abraham et al. \(2016\)](#) provides a construction for a dynamic spectral sparsifier under edge deletions and insertions with polylogarithmic amortized update time:

Theorem 40 (Theorem 4.1 of [Abraham et al. \(2016\)](#)) *There exists a fully dynamic randomized algorithm with polylogarithmic update time for maintaining a $(1 \pm \epsilon)$ -spectral sparsifier H of a graph G , with probability at least $1 - 1/n^c$ for any $0 < \epsilon \leq 1$ and $c \geq 1$. Specifically, the amortized update time of the algorithm is $O(c\epsilon^{-2} \log^3 \rho \log^6 n)$ and the size of H is $O(cn\epsilon^{-2} \log^3 \rho \log^5 n \log W + m\rho^{-1})$, where $1 \leq \rho \leq m$ is a parameter of choice. Here, W is the ratio between the largest and the smallest edge weight in G .*

We use the following result for solving Laplacian systems in the static setting.

Lemma 41 ([K yng and Sachdeva \(2016\)](#)) *There is a randomized procedure that given any n -vertex m -edge graph G with Laplacian matrix \mathbf{L}_G , and vector $b \in \mathbb{R}^V$ such that there exists an $x \in \mathbb{R}^V$ with $\mathbf{L}_G x = b$ computes $\bar{x} \in \mathbb{R}^V$ with $\|\bar{x} - x\|_{\mathbf{L}_G} \leq \epsilon \|x\|_{\mathbf{L}_G}$ in $\tilde{O}(m \log \epsilon^{-1})$ with high probability.*

Lemma 42 *Let G be a dynamic graph and let \mathbf{A} be its dynamic adjacency matrix. Assume there is a dynamic OMv data structure for this \mathbf{A} with update time $U(n)$ and query time $Q(n)$.*

Then there exists a dynamic Laplacian System solver for the same dynamic graph G , supporting updates to G in $O(U(n) + n)$ time. The data structure supports queries which for any given $b \in \mathbb{R}^V$ and $\epsilon > 0$ in $\tilde{O}(Q(n) \log 1/\epsilon)$ time return $x \in \mathbb{R}^V$ with $\|x - x^\|_{\mathbf{L}_G} \leq \epsilon \|x^*\|_{\mathbf{L}_G}$ where x^* is the exact solution for $\mathbf{L}_G x = b$.*

Via Theorem 4 we have $U(n) = \tilde{O}(n)$ and $Q(n) = \tilde{O}(n^{2-1/d})$, thus obtaining Theorem 6.

Proof We run two separate data structures. The first is a dynamic spectral sparsifier Theorem 40 which maintains a spectral sparsifier $H \approx \mathbf{L}_G$ with error $\epsilon = 1/2$. We also run the dynamic OMv data structure for matrix \mathbf{A} (adjacency matrix).

The update time is thus $\tilde{O}(n + U(n))$ as the spectral sparsifier needs polylog time per edge updates, thus $\tilde{O}(n)$ time for node updates.

Queries When given a vector $b \in \mathbb{R}^V$ and error parameter $\epsilon > 0$, we use \mathbf{H}^{-1} as preconditioner for the linear system $\mathbf{L}_G x = b$. We can multiply with \mathbf{H}^{-1} by running a static Laplacian system solver Lemma 41 which takes $\tilde{O}(n)$ time per product as \mathbf{H} has $\tilde{O}(n)$ edges. In particular, we let

$$x^0 = \mathbf{H}^{-1}b$$

and then perform iterative refinement (Richardson iteration)

$$x^{t+1} \leftarrow x^t - \mathbf{H}^{-1}(\mathbf{L}_G x^t - b).$$

After $\tilde{O}(\log 1/\epsilon)$ iterations we have $\|x^t - x^*\|_{\mathbf{L}_G} \leq \epsilon \|x^*\|_{\mathbf{L}_G}$.

Each iteration takes $\tilde{O}(n + Q(n))$ time, where $\tilde{O}(n)$ is the time for multiplying by \mathbf{H}^{-1} , and $Q(n)$ the time for multiplying by \mathbf{L}_G . Observe that $\mathbf{L}_G v = \mathbf{D}v - \mathbf{A}v$ where \mathbf{D} is a diagonal matrix and \mathbf{A} is an adjacency matrix. So the first product takes $O(n)$ time and the second product is handled by the dynamic OMv data structure in $O(Q(n))$ time. Together, this proves the lemma. ■

B.2. Effective Resistance

The following Theorem 7 is a corollary of the dynamic Laplacian solver from Theorem 6.

Theorem 7 (Dynamic Effective Resistance). *There is a dynamic algorithm that, given a dynamic graph $G = (V, E)$ with corrupted VC-dimension bounded by d , maintains effective resistances in G . The data structure supports queries that receive a pair of vertices $u, v \in V$ and error parameter $\epsilon > 0$. Then, in $\tilde{O}(n^{2-1/d} \log 1/\epsilon)$ time, the algorithm returns a $(1 \pm \epsilon)$ -approximation of the effective resistance. Moreover, each node update to G in the dynamic data structure takes $\tilde{O}(n)$ time.*

Proof The effective resistance of a pair $u, v \in V$ is the energy of an electric flow, routing one unit of flow between u and v . The energy of an electric flow $f \in \mathbb{R}^E$ is $\sum_e f_e^2$ and the electric flow is given by $f = \mathbf{B}\mathbf{L}^\dagger(e_u - e_v)$ where $\mathbf{B} \in \{-1, 0, 1\}^{E \times V}$ is the incidence matrix of G with arbitrary directions. Thus the effective resistance is

$$\begin{aligned} \|\mathbf{B}\mathbf{L}^\dagger(e_u - e_v)\|_2^2 &= (e_u - e_v)^\top \mathbf{L}^\dagger \mathbf{B}^\top \mathbf{B} \mathbf{L}^\dagger (e_u - e_v) \\ &= (e_u - e_v)^\top \mathbf{L}^\dagger (e_u - e_v). \end{aligned}$$

This can be computed via the dynamic Laplacian system solver in Theorem 6. ■

B.3. Triangle Detection

Theorem 8 (Dynamic Triangle Detection). *There is a dynamic algorithm that, given a dynamic graph $G = (V, E)$ with corrupted VC-dimension d , maintains whether G contains a triangle or not. Each vertex update to G takes $O(n^{2-1/d})$ time and returns a Boolean indicator for whether G contains a triangle or not.*

The result follows from the following lemma for $U(n) = \tilde{O}(n)$ and $Q(n) = \tilde{O}(n^{2-1/d})$ from Theorem 4.

Lemma 43 *Let G be a dynamic graph and let \mathbf{A} be its dynamic adjacency matrix. Assume there is a dynamic OMv data structure for this \mathbf{A} with update time $U(n)$ and query time $Q(n)$.*

Then there exists a dynamic triangle detection algorithm for the same dynamic graph G , supporting updates in $O(U(n) + Q(n))$ time.

Proof Let \mathbf{A} be the adjacency matrix of the graph, then the diagonal entries $(\mathbf{A}^3)_{v,v}$ are non-zero if and only if v participates in a triangle. Thus by maintaining the sum $\sum_i (\mathbf{A}^3)_i$ we can detect if there is any triangle in the graph.

We maintain the sum as follows: Let \mathbf{A} be the incidence matrix before, and \mathbf{A}' after a node v is updated.

Then

$$\sum_i (\mathbf{A}'^3)_i = \left(\sum_i (\mathbf{A}^3)_i \right) + 3 \left(\underbrace{(\mathbf{A}'^3)_{v,v} - (\mathbf{A}^3)_{v,v}}_{\text{difference in \# of triangles } v \text{ participates in}} \right).$$

This is because each triangle v participates in is counted thrice in the sum (once for each vertex of the triangle). Thus we can maintain the sum by computing $(\mathbf{A}'^3)_{v,v}$ and $(\mathbf{A}^3)_{v,v}$. Observe that this is the vector-matrix-vector product of (i) the v th row of \mathbf{A} , (ii) matrix \mathbf{A} , (iii) and v -th column vector of \mathbf{A} . Thus it can be computed in $O(Q(n))$ time, with an extra $U(n)$ time to update \mathbf{A} to \mathbf{A}' . ■

B.4. Single-Source Shortest Paths and k-Center

Lemma 44 (van den Brand et al. (2022)) *Assume there is a dynamic distance oracle for unweighted undirected graphs with the following operations.*

An initialization procedure that is given $G = (V, E)$ and a threshold $1 \leq d \leq n$.

A node update operation with update time $U(n, d)$.

A query operation which for any source node, given during the query, returns the d -bounded single source distances in $O(Q(n, d))$. That is, return for each $v \in V$ the distance if it is at most d , or ∞ if the distance is $> d$.

Then for any $1 \leq k \leq n$ and $\epsilon > 0$ there exists a dynamic $(1 + \epsilon)$ -approximate single source distance data structure on unweighted undirected graphs. It supports node updates in

$$O \left(U \left(n, \frac{4}{\epsilon} \right) + \frac{k}{\epsilon} \cdot Q \left(n, \frac{4}{\epsilon} \right) + \frac{n^2}{k} \right)$$

time.

Theorem 9 (Dynamic Approximate Single-Source Shortest Paths). *There is a dynamic algorithm that maintains $(1 + \epsilon)$ -approximate single source distances on a dynamic unweighted undirected graph $G = (V, E)$. If the corrupted VC-dimension of G is bounded by d , each vertex update to G takes $\tilde{O}(kn^{2-1/(2d)}/\epsilon)$ time, and querying the distances for any source node takes $O(n^{2-1/(2d)}/\epsilon)$ time.*

Proof We first describe how to obtain a dynamic distance oracle that yields distances up to $1/\epsilon$. This is done by running the dynamic OMv data structure of Theorem 4 on the adjacency matrix of G . Then single source distances up to $1/\epsilon$ from source vertex u can be computed by repeatedly multiplying $w \leftarrow \mathbf{A}w$ for initial $w = e_u$, i.e., we compute $\mathbf{A}^i e_u$ for $i = 1, 2, \dots, 1/\epsilon$. The smallest i with $(\mathbf{A}^i e_u)_v \neq 0$ is the smallest number of steps to reach from u to v , i.e., the distance between the vertices.

This data structure internally constructs the a Δ -labeled spanning tree of the boolean matrix \mathbf{A} , where the weight of the tree gives us the time complexity per query.

Hence, while we do not know the corrupted VC-dimension d , we do know how much time each query is going to take.

So when running Lemma 44 on the above distance data structure, we can pick $k = n/\sqrt{T}$ where $T \geq n$ is the weight of the spanning tree. Thus, we get the update time

$$\begin{aligned} \tilde{O}\left(n + \frac{k}{\epsilon}T + nk + \frac{n^2}{k}\right) &= \tilde{O}\left(n + \frac{n\sqrt{T}}{\epsilon} + \frac{n}{\sqrt{T}}\right) \\ &= \tilde{O}(n^{2-\frac{1}{2d}}), \end{aligned}$$

which proves the claim. ■

Theorem 10 (*Dynamic Approximate k -center*). *Given an unweighted undirected graph $G = (V, E)$, there is a dynamic algorithm for $(2 + \epsilon)$ -approximate k -center with node update time $O(kn^{2-1/2d}/\epsilon)$, where d is a bound on the corrupted VC-dimension of G .*

This result is a corollary of Theorem 9, as k -center can be reduced to computing k -single source distances.

Lemma 45 (**Theorem 7.3 by Cruciani et al. (2024)**) *Given a graph $G = (V, E)$, a positive parameter $\epsilon \leq 1/2$, and a fully-dynamic data structure that maintains $(1 + \epsilon)$ -approximate single source distances with update time $T(n, m, \epsilon)$ and $Q(n, m, \epsilon)$ query time, there is a dynamic algorithm that maintains a $2(1 + 4\epsilon)$ -approximate solution to fully-dynamic k -center in time $O(T(n, m, \epsilon) + k \cdot (Q(n, m, \epsilon) + n))$.*

Appendix C. Characterization of matrices with constant VC-dimension

In this section, we provide a characterization of matrices with constant VC-dimension. Particularly, we prove Fact 1 and state a number of examples of other constant VC-dimension matrices.

Fact 1. *Consider a hereditary class of 0/1-matrices \mathcal{M} , meaning that \mathcal{M} is closed under row/column deletion (i.e., each matrix $\mathbf{M} \in \mathcal{M}$ is still in \mathcal{M} after deleting a row or column). If \mathcal{M} is non-trivial, (i.e., does not contain every possible matrix), then there exists an absolute constant $c \in \mathbb{N}$ such that the VC-dimension of any matrix in \mathcal{M} is at most c .*

Fact 1 provides a structural characterization of some matrices with constant VC-dimension, and it is an analogous result to the fact that non-trivial hereditary classes of graphs have low VC-dimension. To prove Fact 1, we introduce the notion of a bipartisation of a graph.

Definition 46 *A bipartite graph $H = (A \cup B, E)$ is a bipartisation of graph G if removing all edges in A and B in G yields H for some partition A, B of $V(G)$. A graph class \mathcal{G} is said to be hereditary if it is closed under induced subgraphs.*

Lemma 47 (**Lemma 3.4 of Bousquet et al. (2015)**) *For any hereditary class \mathcal{C} of graphs and for any bipartite graph H , if the graphs in \mathcal{C} have infinite VC-dimension, then \mathcal{C} contains a graph G whose bipartisation is H .*

By transposition, we get the following corollary:

Corollary 48 *The equivalent contrapositive statement is that for any hereditary class \mathcal{C} of graphs and for any bipartite graph H , if \mathcal{C} does not contain a graph G whose bipartisation is $H = (A \cup B, E)$ where $A \cup B = V(G)$, then the graphs in \mathcal{C} have finite VC-dimension.*

Lemma 49 *The VC-dimension of any matrix in \mathcal{M} is upper bounded by a finite constant.*

Proof Since $\mathbf{M} \in \mathcal{M}$ is Boolean, we can treat it as a bipartite graph G , with rows representing left vertices and columns representing right vertices. In particular, we can treat \mathcal{M} as a class of bipartite graphs closed under vertex deletion (row deletion = deleting a left vertex, column deletion = deleting a right vertex). Thus we can apply lemma 47 to \mathcal{M} .

Since \mathcal{M} is non-trivial, there must be some graph H not contained in it. For this excluded graph H , define H' as the same graph but add one extra left vertex and one extra right vertex. Connect this new left vertex to every vertex on the right, and connect the new right vertex to every vertex on the left. Note that since H was not contained in \mathcal{M} and it is closed under vertex deletion, H' also cannot be contained in \mathcal{M} .

Now assume there is $G \in \mathcal{M}$ that contains H' as bipartization. Then there is a partition A, B of V , such that keeping only the edges between A and B of G , results in H' . Because of the left vertex in H' that connects to all right vertices, and the right vertex connecting to all left vertices, we must have that A are all left and B are all the right vertices of G (or the other way around). But that means no edges were removed from G when restricting to edges between A and B , since a bipartite graph by definition only has edges connecting left and right vertices. So $G = H'$ and $H' \in \mathcal{M}$. This is a contradiction because by construction of H' , it does not exist in \mathcal{M} .

We conclude, that set of bipartite graphs corresponding to \mathcal{M} does not contain any graph whose bipartization is H' . Hence by Theorem 48 the VC-dimension must be a finite constant. Note that this is equivalent to the VC-dimension of the adjacency matrices being bounded, but \mathcal{M} are not adjacency matrices. The adjacency matrices are of form

$$\begin{bmatrix} 0 & \mathbf{M} \\ \mathbf{M}^\top & 0 \end{bmatrix}$$

for matrices $\mathbf{M} \in \mathcal{M}$. We already argued that each adjacency matrix has constant VC-dimension, and since removing rows does not increase the VC-dimension (it is equivalent to deleting sets), this implies \mathbf{M} also has constant VC-dimension. In conclusion, each matrix in \mathcal{M} has constant VC-dimension. ■

C.1. Examples of low VC-dimension matrices

We provide some broad families of matrices with constant VC dimension.

Adjacency matrices of H -minor free graphs. Eppstein (1995) showed that H -minor free directed graphs (where the minor can be obtained through vertex deletion, edge deletion, and edge contraction) has VC-dimension at most $|V(H)| - 1$. As an immediate consequence, since bipartite-graphs are triangle (K_3) free, the VC-dimension of any bipartite graph is 2. As a consequence, given any adjacency matrix \mathbf{A} of a H -minor free graph G , for any $k \geq 1$, \mathbf{A}^k is the adjacency matrix of a H -minor free graph G' (since \mathbf{A}^k corresponds to the reachability graph where an edge $(u, v) \in E(G')$ corresponds to the existence of a k -length walk between u and v in G). Therefore, the VC-dimension of \mathbf{A}^k is also at most $|V(H)| - 1$.

Adjacency matrices of interval graphs. Interval graphs are the intersection graphs of a family of intervals on the real line. Then, since the hypothesis class of intervals on the real line $\mathcal{H} = \{\mathbb{1}_{a,b} : a \leq x \leq b\}$ has VC-dimension 2 (any two points can be shattered by choosing an interval that includes one or both points, but no set of three points can always be shattered), every interval graph has VC-dimension at most 2.

Boolean kernel matrices. A matrix where each column i (and each row) receives some label $\ell_i \in L$ from some (possibly infinite) set of possible labels L . Then, suppose each entry of \mathbf{M} satisfies $\mathbf{M}_{i,j} = f(\ell_i, \ell_j)$ for some function $f : L \rightarrow \{0, 1\}$. For example, the labels could be points in $L = \mathbb{R}^d$ with f being indicator that the distance is at most some threshold. If f, L is fixed (i.e., independent of the number of rows/columns) then these graphs are closed under row/column deletion and thus have bounded VC-dimension by Fact 1.

Shortest-path structures Let G be an undirected graph with non-negative edge weights and let S be a subset of its shortest paths such that, for every pair (u, v) of distinct vertices, S contains exactly one shortest path between u and v . [Marie de Lima et al. \(2023\)](#) defines a range space associated with S and proves that its VC dimension is 2.

Adjacency matrices of planar graphs. Let G be a planar graph. Then, there is a planar drawing of G , and deleting vertices and edges retains this property. Therefore, these graphs are closed under row/column deletion and thus have bounded VC-dimension by Fact 1.

Adjacency matrices of semi-algebraic graphs of bounded description complexity. By the Milnor-Thom theorem in real algebraic geometry ([Matoušek, 2002](#)) and the Sauer-Shelah lemma ([Assouad, 1983](#)), semi-algebraic graphs of bounded description complexity have constant VC-dimensions. In turn, this extends to adjacency matrices of string graphs where every two curves intersect.

Practical matrices. [Coudert et al. \(2024\)](#) computes the VC-dimension of families of graphs that arise in practice, from protein interaction networks to autonomous Internet systems to web graphs. Even for such graphs with millions of nodes, the VC-dimension of the graphs are typically between 3 and 8.