

---

# TOWARDS FAIRNESS FOR THE RIGHT REASONS: USING SALIENCY MAPS TO EVALUATE BIAS REMOVAL IN NEURAL NETWORKS

---

A PREPRINT

Lukasz Sztukiewicz\* Ignacy Stępa\* Michał Wiliński\* Jerzy Stefanowski  
Institute of Computing Science, Poznan University of Technology

## ABSTRACT

The widespread adoption of machine learning systems has raised critical concerns about fairness and bias, making mitigating harmful biases essential for AI development. In this paper, we investigate the relationship between fairness improvement and the removal of harmful biases in neural networks applied to computer vision tasks. First, we introduce a set of novel XAI-based metrics that analyze saliency maps to assess shifts in a model’s decision-making process. Then, we demonstrate that successful debiasing methods systematically redirect model focus away from protected attributes. Additionally, we show that techniques originally developed for artifact removal can be effectively repurposed for fairness. These findings underscore the importance of ensuring that models are **fair for the right reasons**, contributing to the development of more ethical and trustworthy AI systems.

## 1 Introduction

The widespread adoption of machine learning (ML) systems across a range of domains has not only brought impressive predictive capabilities but also raised critical concerns about fairness and bias. Recent regulations, such as those discussed in [23], underscore the importance of this problem. While some degree of bias is inherent in machine learning models, harmful biases that affect sensitive areas of human life pose ethical issues [7].

Neural networks, especially in computer vision applications, present unique challenges for fairness assessment and bias mitigation [22]. Unlike tabular data, where features are explicitly defined, images lack semantic meaning at the raw pixel level. To gain predictive power, models learn to extract high-level semantic features. This becomes particularly problematic when dealing with protected attributes (such as gender or race), which are high-level features (concepts) that are inaccessible to models operating only on pixel data without explicit featurization. Neural networks are known to develop internal representations that encode not only useful high-level features but also harmful biases [5]. This phenomenon mirrors a well-known problem in tabular data, known as the ‘fairness through unawareness’ [9], where models can still exhibit biases by inferring protected attributes through proxy or composite features. For example, in the CelebA dataset [15], wearing a necktie is highly correlated with the male gender. It means that the ‘wearing necktie feature’ can be used as a proxy feature to infer gender, thus creating potential unintended pathways for discrimination.

To address discrimination and ensure fairness in ML models, various approaches have been proposed [16]. While existing debiasing methods generally improve fairness metrics, they often fail to explicitly address harmful biases encoded in models’ internal representations. We examine the relationship between successful fairness improvement and removal of harmful biases from these representations. To address the evaluation gap, we propose new metrics that quantify the properties of saliency maps given a region of interest, and capture the extent to which biases are removed from the model’s decision-making process. Our findings provide evidence that effective debiasing methods based on fine-tuning redirect the model’s focus away from protected attributes, thus altering the internal model representations. Building on these insights, we show that techniques originally developed for *artifact removal*, such as the family of CIArC methods [10], can be repurposed for fairness improvement, even though they do not explicitly optimize any

---

\* Authors contributed equally, and the order has been randomized.

fairness metric. Finally, we advocate that fairness should go hand in hand with concept removal to make models **fair for the right reasons**. Our key contributions include:

1. A set of new XAI-based metrics that quantify shifts in the model’s decision-making process based on saliency maps.
2. Empirical evidence that successful debiasing methods systematically redirect model attention away from protected attributes
3. Demonstration that artifact removal methods, when applied to localized protected attributes, score excellent on fairness metrics and naturally align with the principle of being *fair for the right reasons*

## 2 Related Work

**Debiasing methods** are active area of research, usually in the context of tabular data, with a vast landscape of methods applied at various stages of model development [8]. The methods employed in our study represent approaches to debiasing in a post-hoc manner, that is, after a model is trained, within a binary classification setup. In our work, we consider three groups of methods. The first group consists of simple threshold optimizers, represented in our experiments by ThrOpt[11]. These methods adjust classification thresholds to optimize fairness metrics predefined by the user. The second group focuses on approaches that optimize fairness with adversarial fine-tuning. Zhang’s adversarial learning (ZhangAL) [24] formulates debiasing as a minimax optimization game between a predictor and an adversary that attempts to predict protected attributes from model outputs. Savani’s adversarial fine-tuning (SavaniAFT) [19] leverages first-order optimization with a critic model that learns to predict bias in minibatches, serving as a differentiable proxy for typically non-differentiable fairness metrics. Finally, the third group focuses on concept-based interventions (artifact removal), exemplified by CIArC variants [2, 10], which operate directly on the model’s internal representations through interventions in activation space. These methods use Concept Activation Vectors (CAVs) to identify and manipulate directions in activation space associated with protected attributes. CIArC variants include augmentation during fine-tuning (A-CIArC), or gradient-space regularization (RR-CIArC).

**Saliency maps** are explainable AI methods that provide insights into model decision-making process by highlighting regions of input data that influence predictions. Although there are many visualization techniques, they can generally be categorized into gradient-based [21, 17] and relevance-based methods [4]. Integrated Gradients [21] attributes predictions to input features by integrating gradients along a path from a baseline to the input, satisfying important axioms, including sensitivity and implementation invariance. LRP [4] employs a fundamentally different approach based on a conservation principle, where relevance scores are propagated backward through the network layers while maintaining a constant sum.

**Quantitative evaluation of saliency maps** is crucial for assessing whether models make decisions based on appropriate features rather than biased artifacts or protected attributes. Early approaches, such as the inside-outside ratio [14, 3], established a foundation by quantifying the relevance contained within a bounding box relative to the relevance outside it. This concept has been further developed and implemented as part of the Quantus toolbox [13], which provides a framework for evaluating explanations through various localization metrics. Motzkus et al. [18] advanced this approach by adapting the inside-outside metric to compute the ratio of positively attributed relevance within a binary class mask to the overall positive relevance, specifically focusing on the context of individual concepts. Despite these advances, there remains a gap in methods specifically designed to quantify the importance of protected attributes in saliency maps. In this work, we address this limitation by introducing five complementary metrics that evaluate the saliency of protected attributes by measuring the concentration and distribution of relevance within defined regions of interest.

## 3 Metrics for Saliency Maps

In this section, we present metrics designed to quantify the importance of protected attributes in the model’s decision-making process. Our focus is specifically on localized features that can be bounded by rectangular regions of interest (ROIs). These metrics evaluate whether an ROI plays an important role in the model’s reasoning by analyzing saliency maps. The proposed metrics can be used with any standard saliency map generation method. We divide them into two groups investigating properties of saliency maps (Sec. 3.1) and the improvement of the debiasing method over Vanilla model (Sec. 3.2).

To establish our framework, we define several key components. The dimensions of an image are given by width  $N$  and height  $M$ , with  $p_{ij}$  representing the intensity (or relevance) of the pixel  $(i, j)$ . Within this image, we consider an

ROI defined by width  $W$  and height  $L$ , where  $W \leq N$  and  $L \leq M$ . We denote the set of pixels within this ROI as  $R$ , such that  $|R| = W \cdot L$ .

### 3.1 Saliency Map Evaluation Metrics

Here, we introduce two metrics that evaluate the relationship between ROI and the entire image by analyzing pixel intensity scores in saliency maps. These metrics provide different perspectives on the importance of the selected region in the model’s decision-making process.

#### 3.1.1 Rectangle Relevance Fraction (RRF)

For ROI is defined as:

$$\mathbf{RRF} = \frac{\sum_{(i,j) \in R} p_{ij}}{\sum_{i=1}^N \sum_{j=1}^M p_{ij}} \quad (1)$$

RRF provides a direct measure of the ROI’s importance in the context of the model’s prediction by calculating what percentage of the total relevance falls within the region. RRF helps us understand the relative contribution of the selected region to the overall decision-making process of the model.

#### 3.1.2 High-Relevance Fraction (HRF)

HRF quantifies the density of significant pixels within the ROI:

$$\mathbf{HRF} = \frac{1}{|R|} \sum_{(i,j) \in R} \mathbb{1}_{\{p_{ij} > \epsilon\}} \quad (2)$$

This metric calculates the fraction of pixels inside the ROI whose relevance exceeds a predefined threshold  $\epsilon$ . The threshold serves an important purpose in eliminating low-intensity pixels that may be artifacts of the saliency map generation process. HRF has a natural interpretation as a percentage and indicates the concentration of highly important pixels within the region, providing insight into how densely packed the significant features are within the ROI.

### 3.2 Improvement over Vanilla Model

To evaluate the effectiveness of debiasing methods, we introduce three metrics that compare the saliency maps of a debiased model with those of the original Vanilla model. These metrics specifically focus on changes within the ROI, helping us quantify how successful the debiasing process has been in reducing the model’s reliance on protected attributes.

#### 3.2.1 Average Difference in Region (ADR)

ADR provides a direct measure of how the saliency values within the ROI change after debiasing:

$$\mathbf{ADR} = \frac{1}{|R|} \sum_{(i,j) \in R} p_{ij}^v - p_{ij}^d \quad (3)$$

where  $p_{ij}^v$  and  $p_{ij}^d$  represent pixel intensities in the Vanilla and debiased saliency maps, respectively. A positive ADR value indicates that the Vanilla model generally assigned higher importance to pixels within the ROI compared to the debiased model, suggesting a successful reduction in the model’s reliance on these features.

#### 3.2.2 Decreased Intensity Fraction (DIF)

DIF quantifies the proportion of pixels within the ROI that show reduced importance after debiasing:

$$\mathbf{DIF} = \frac{1}{|R|} \sum_{(i,j) \in R} \mathbb{1}_{\{p_{ij}^d < p_{ij}^v\}} \quad (4)$$

This metric calculates the fraction of pixels where the debiased model shows lower saliency values compared to the Vanilla model. The DIF provides insight into how widespread the changes are within the ROI, complementing the ADR’s measurement of average change magnitude.

### 3.2.3 Rectangle Difference Distribution Testing (RDDT)

RDDT metric assesses whether the Vanilla model assigns a higher importance to pixels within the ROI compared to the debiased model. For each image, we compute the difference between the mean intensities of vanilla and debiased saliency maps within the ROI:

$$d = \mu_{\text{vanilla}} - \mu_{\text{debiased}} \quad (5)$$

where  $\mu_{\text{vanilla}}$  and  $\mu_{\text{debiased}}$  represent the mean pixel intensities within the ROI for the Vanilla and debiased models respectively. We then perform a one-sample t-test on these differences across with  $H_0 : \mu_d = 0$  and  $H_1 : \mu_d > 0$ . The test returns 1 if  $p < 0.01$ , indicating statistically significant evidence that the Vanilla model assigns a higher importance to the ROI than the debiased model, and 0 otherwise.

## 4 Experiments

In the experiments below, we aim to explore the following two research questions. **RQ1:** Is there a bidirectional relationship between shifting the importance of pixels in the saliency map out of the ROI and optimizing fairness metrics? **RQ2:** Are debiasing methods capable of decreasing the saliency within ROI w.r.t. a standard end-to-end trained Vanilla model?

The experiment procedure is as follows. First, we train ResNet-50 [12] on the training set, which results in a Vanilla model. Then, using the hold-out debias set we apply the considered debiasing methods. In the next step, we validate resulting models on test set on which we calculate the prediction performance, fairness, and our proposed metrics. Both training and debias datasets, while disjoint, are sampled from the same data distribution, thus have the same *protected attribute-target* (PA-T) correlation – aligning with the most straightforward practical use case, where one does not want to tune how to perform this split. However, the split used for testing is artificially balanced to systematically measure predictive performance (Accuracy) and fairness metric (EqualizedOdds) [6].

In the experiments we employ methods described in Sec. 2 implemented within DetoxAI library<sup>1</sup> [20]. Quantitative metrics and qualitative summaries are computed for saliency maps of LRP and Integrated Gradients, which also come from DetoxAI and are implemented there with Zennit [1] library.

### 4.1 Qualitative assessment

We perform a qualitative assessment of the debiasing by inspecting the relevancy maps before and after applying different debiasing methods. Fig. 2 presents LRP saliency maps for images aggregated by PA-T combinations, where the protected attribute is *WearingNecktie* and the target attribute is *Smiling*. The black rectangles highlight the ROI roughly corresponding to the necktie area (see Fig. 1).

Several key observations can be made from these visualizations. The Vanilla model (second column) shows considerable attention to the necktie region, particularly for the (PA=1, T=0) combination, indicating that the model has learned to associate the necktie area with its predictions. Interestingly, for the (PA=1, T=1) combination (bottom row), the necktie area shows strong negative relevance (blue), suggesting the model uses this feature to make negative predictions about smiling.

Simple threshold optimization (ThrOpt) does not substantially alter the saliency patterns compared to Vanilla, maintaining similar attention to the necktie area. This suggests that merely adjusting classification thresholds does not change the underlying reasoning of the model. Adversarial fine-tuning methods (SavaniAFT and ZhangAL) show modest reductions in the attention to the ROI but largely preserve the overall saliency patterns of the Vanilla model. The CIArC-based methods show the most noticeable shifts. A-CIArC reduces the saliency in the necktie region across all PA-T combinations, redirecting attention to facial features, relevant to the *Smiling* attribute. RR-CIArC shows the most visible improvements, excluding the second row, almost completely eliminating the relevance from ROI. These observations suggest that, while all debiasing methods may improve fairness metrics, they differ in how they alter the model’s underlying decision-making process. Methods from the CIArC family most effectively redirect the model’s attention away from the protected attribute region.

### 4.2 Quantitative experiments

While the CelebA dataset exhibits inherent attribute correlations, we artificially enforced specific PA-T correlations in our experimental framework to amplify the biases. This was done by rebalancing the dataset by undersampling

<sup>1</sup><https://github.com/FairUnlearn/detoxai>




Figure 1: On the left raw images, on the right LRP saliency maps. Red color, above 0.5 indicates positive relevance for the correct ground-truth class, while blue color below 0.5, negative contribution towards that class.




Figure 2: LRP saliency maps for images aggregated by PA-T combinations for a batch of size 128. The considered protected attribute is WearingNecktie and the target is Smiling.

attribute combinations to control their correlation with the target. Desired attribute correlations were achieved by manipulating the distributions of binary attributes. We measure correlation using Yule’s  $\phi$ :

$$\phi = \frac{n_{11}n_{00} - n_{10}n_{01}}{\sqrt{(n_{11} + n_{10})(n_{11} + n_{01})(n_{00} + n_{10})(n_{00} + n_{01})}} \quad (6)$$

where  $n_{ij}$  represents the percentage of samples with a particular PA-T combination.

In this experiment, we considered two PA-T combinations: *WearingHat–Smiling* and *WearingNecktie–Smiling*, using saliency maps generated with LRP [4] and IntegratedGradients [21]. However, in the following, we only report the

Metric	Type	Scope	Reported Value	Direction
RRF	Relationship	Per-image	Mean over dataset	min
HRF			Mean over dataset	
ADR	Improvement	Per-image	Mean over dataset	max
DIF		Per-image	Mean over dataset	
RDDT		Dataset	Statistical test	

Table 1: Summary of introduced saliency map metrics.




Figure 3: Quantitative metrics for WearingNecktie-Smiling PA-T combination, measured on saliency maps generated with LRP. Metrics in the upper row are supposed to be minimized, while in the lower row, maximized.

results for LRP and *WearingNecktie-Smiling* combination (in Fig. 3), while we move the rest to the Appendix, because the conclusions from all experiment variants are the same. In these plots, we report metrics from Sec. 3, summarized in Tab. 1, along with EqualizedOdds metric calculated with a following formula:

$$\text{EqualizedOdds} = \max(|\text{TPR}_{PA=1} - \text{TPR}_{PA=0}|, |\text{FPR}_{PA=1} - \text{FPR}_{PA=0}|) \quad (7)$$

where TPR and FPR stand for true and false positive rates respectively, and  $PA = 0$ ,  $PA = 1$  protected attribute value assignments.

First, it is clear that as  $\phi$  increases, all methods achieve a higher EqualizedOdds value, which indicates more bias in their predictions. The best performing method on this metric is ZhangAL, which directly optimizes it internally. However, most methods decrease the EqualizedOdds score w.r.t. Vanilla’s, which shows they are effective.

ThrOpt, a post-hoc classification threshold optimization method, does not shift the relevancy in or out of the ROI. Its bars are empty for ADR and RDDT and equal to Vanilla on DIF, RRF and HRF, indicating that no change in the saliency maps was recorded. This is expected since no changes are made to the reasoning process with this method.

SavaniAFT and ZhangAL both perform well across most metrics. ZhangAL scores remarkably well across saliency map-based metrics. It consistently lowers the metric values in the first row of the plot, showing that it moves the saliency out of ROI. Moreover, it also scores visibly well on the metrics in the lower row, which measure the improvement over the Vanilla model within the ROI. This provides evidence that optimizing with a fairness-oriented objective as a fine-tuning step can significantly shift the model’s reasoning process.

In particular, RR-CIaRC and A-CIaRC methods do not optimize any fairness objective. Yet, they effectively debias the model (as captured by EqualizedOdds) and significantly shift model relevancy within the ROI. Both score high at DIF and ADR, and often appear on RDDT (the more bars the better). Regarding attention outside the ROI, they tend to lower RRF and HRF with respect to Vanilla, which suggests that more attention is given to features outside the ROI, what is the desired outcome.

## 5 Discussion

Our experiments provide evidence for a bidirectional relationship between shifting pixel importance in saliency maps away from regions of interest and optimizing fairness metrics, validating the premise of our RQ1. We demonstrate that methods which effectively redirect model attention away from protected attributes score better on EqualizedOdds. This confirms our hypothesis that successful concept unlearning should shift attention from protected attributes and opens an avenue employ such methods for fairness, even though they do not explicitly optimize the fairness objective.

Furthermore, experiments show that effective debiasing methods decrease saliency within the ROI compared to the Vanilla model, which positively answers the RQ2. Both qualitative and quantitative analyses reveal that while threshold optimization (ThrOpt) produces no changes in saliency maps, fine-tuning-based approaches yield significant improvements. This is expected because threshold optimization does not alter internal representations of the model, thus cannot change the patterns inherited from Vanilla in its saliency maps. Notably, ZhangAL and SavaniAFT and CIaRC-based methods (A-CIaRC and RR-CIaRC) redirect the attention away from protected features toward task-relevant features like facial expressions for smile detection. In case of the latter, the saliency redirection is stronger while achieving competitive EqualizedOdds, despite not directly optimizing any fairness objective.


We believe that this research provides useful evidence for further work on fairness methods, which could adapt concept removal methods directly in the field of fair machine learning. In future studies, our aim is to extend CIaRC-based methods with fairness objectives to further expand this analysis.



## References

- [1] Anders, C.J., Neumann, D., Samek, W., Müller, K.R., Lapuschkin, S.: Software for dataset-wide xai: From local explanations to global insights with Zennit, CoRelAy, and ViRelAy (2021)
- [2] Anders, C.J., Weber, L., Neumann, D., Samek, W., Müller, K.R., Lapuschkin, S.: Finding and removing clever hans: Using explanation methods to debug and improve deep models. *Information Fusion* **77**, 261–295 (2022)
- [3] Bach, S., Binder, A., Montavon, G., Müller, K.R., Samek, W.: Analyzing classifiers: Fisher vectors and deep neural networks. 2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR) pp. 2912–2920 (2015)
- [4] Bach, S., Binder, A., Montavon, G., Klauschen, F., Müller, K.R., Samek, W.: On pixel-wise explanations for non-linear classifier decisions by layer-wise relevance propagation. *PLOS ONE* **10**(7), 1–46 (07 2015)
- [5] Bolukbasi, T., Chang, K.W., Zou, J.Y., Saligrama, V., Kalai, A.T.: Man is to computer programmer as woman is to homemaker? debiasing word embeddings. *Advances in Neural Information Processing Systems* **29** (2016)
- [6] Brzezinski, D., Stachowiak, J., Stefanowski, J., Szczech, I., Susmaga, R., Aksenyuk, S., Ivashka, U., Yasinskyi, O.: Properties of fairness measures in the context of varying class imbalance and protected group ratios. *ACM Transactions on Knowledge Discovery from Data* **18**(7), 1–18 (2024)
- [7] Buyl, M., De Bie, T.: Inherent limitations of ai fairness. *Commun. ACM* **67**(2), 48–55 (Jan 2024)
- [8] Caton, S., Haas, C.: Fairness in machine learning: A survey. *ACM Comput. Surv.* **56**(7) (Apr 2024)
- [9] Datta, A., Tschantz, M., Datta, A.: Automated experiments on ad privacy settings. *Proceedings on Privacy Enhancing Technologies* **1** (04 2015)
- [10] Dreyer, M., Pahde, F., Anders, C.J., Samek, W., Lapuschkin, S.: From hope to safety: Unlearning biases of deep models via gradient penalization in latent space. *Proceedings of the AAAI Conference on Artificial Intelligence* **38**(19), 21046–21054 (Mar 2024)
- [11] Hardt, M., Price, E., Price, E., Srebro, N.: Equality of opportunity in supervised learning. In: Lee, D., Sugiyama, M., Luxburg, U., Guyon, I., Garnett, R. (eds.) *Advances in Neural Information Processing Systems*. vol. 29 (2016)
- [12] He, K., Zhang, X., Ren, S., Sun, J.: Deep residual learning for image recognition. In: *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*. pp. 770–778 (2016)

- 
- [13] Hedström, A., Weber, L., Krakowczyk, D., Bareeva, D., Motzkus, F., Samek, W., Lapuschkin, S., Höhne, M.M.C.: Quantus: An explainable ai toolkit for responsible evaluation of neural network explanations and beyond. *Journal of Machine Learning Research* **24**(34), 1–11 (2023)
  - [14] Kohlbrenner, M., Bauer, A., Nakajima, S., Binder, A., Samek, W., Lapuschkin, S.: Towards best practice in explaining neural network decisions with lrp. In: 2020 International Joint Conference on Neural Networks (IJCNN). pp. 1–7. IEEE (2020)
  - [15] Liu, Z., Luo, P., Wang, X., Tang, X.: Deep learning face attributes in the wild. In: Proceedings of International Conference on Computer Vision (ICCV) (2015)
  - [16] Mehrabi, N., Morstatter, F., Saxena, N., Lerman, K., Galstyan, A.: A survey on bias and fairness in machine learning. *ACM Computing Surveys* **54**(6) (Jul 2021)
  - [17] Molnar, C.: *Interpretable Machine Learning*. 2 edn. (2022)
  - [18] Motzkus, F., Mikriukov, G., Hellert, C., Schmid, U.: Locally testing model detections for semantic global concepts. In: World Conference on Explainable Artificial Intelligence. pp. 137–159. Springer (2024)
  - [19] Savani, Y., White, C., Govindarajulu, N.S.: Intra-processing methods for debiasing neural networks. In: Larochelle, H., Ranzato, M., Hadsell, R., Balcan, M., Lin, H. (eds.) *Advances in Neural Information Processing Systems*. vol. 33, pp. 2798–2810. Curran Associates, Inc. (2020)
  - [20] Stepka, I., Sztukiewicz, L., Wilinski, M.: Detoxai: a python package for debiasing neural networks, <https://github.com/FairUnlearn/detoxai>
  - [21] Sundararajan, M., Taly, A., Yan, Q.: Axiomatic attribution for deep networks. In: International Conference on Machine Learning. pp. 3319–3328. PMLR (2017)
  - [22] Tian, H., Zhu, T., Liu, W., Zhou, W.: Image fairness in deep learning: Problems, models, and challenges. *Neural Computing and Applications* **34**(15), 12875–12893 (Aug 2022)
  - [23] Wachter, S., Mittelstadt, B., Russell, C.: Counterfactual explanations without opening the black box: automated decisions and the gdpr. *Harvard Journal of Law and Technology* **31**(2) (2018)
  - [24] Zhang, B.H., Lemoine, B., Mitchell, M.: Mitigating unwanted biases with adversarial learning. In: Proceedings of the 2018 AAAI/ACM Conference on AI, Ethics, and Society. p. 335–340. AIES '18, Association for Computing Machinery, New York, NY, USA (2018)

## Appendix

Figure 4: Metric values for the IG attributions and *WearingNecktie* protected attribute.

Figure 5: Metric values for the LRP attributions and *WearingHat* protected attributeFigure 6: Metric values for the IG attributions and *WearingHat* protected attribute