# On the time complexity of finding a well-spread perfect matching in bridgeless cubic graphs<sup>\*</sup>

Babak Ghanbari and Robert Šámal

Computer Science Institute, Charles University, Prague, Czech Republic {babak,samal}@iuuk.mff.cuni.cz

Abstract. We present an algorithm for finding a perfect matching in a 3-edge-connected cubic graph that intersects every 3-edge cut in exactly one edge. Specifically, we propose an algorithm with a time complexity of  $O(n \log^4 n)$ , which significantly improves upon the previously known  $O(n^3)$ -time algorithms for the same problem. The technique we use for the improvement is efficient use of cactus model of 3-edge cuts. As an application, we use our algorithm to compute embeddings of 3-edge-connected cubic graphs with limited number of singular edges (i.e., edges that are twice in the boundary of one face) in  $O(n \log^4 n)$  time; this application contributes to the study of the well-known Cycle Double Cover conjecture.

Keywords: Algorithm  $\cdot$  Perfect matching  $\cdot$  Cut representation  $\cdot$  Embedding

# 1 Introduction

It is well known that every bridgeless cubic graph admits a perfect matching [Pet91]. Using Edmonds' blossom algorithm, a maximum matching can be found in polynomial time. Gabow [Gab90] demonstrated that the weighted matching problem on general graphs can be solved in time  $O(n(m + n \log n))$ .

Consequently, the minimum weight perfect matching problem for bridgeless cubic graphs can be solved in  $O(n^2 \log n)$  time. Diks and Stańczyk [DS10] proposed an improved algorithm for finding perfect matchings in bridgeless cubic graphs with time complexity of  $O(n \log^2 n)$ .

In this paper we study the complexity of finding a perfect matching M in a bridgeless cubic graph such that in every 3-edge cut M contains exactly one edge. By parity, M can contain one or three edges in a 3-edge cut; so our condition says no 3-edge cut is contained in M. We shortly express this by saying M is well spread.

Kaiser et al. [KKN06] showed that a wells spread perfect matching exists in every bridgeless cubic graph (and went on to use this to find how much of the

<sup>\*</sup> Supported by the project GAUK182623 of the Charles University Grant Agency and by grant 25-16627SS of the Czech Science Foundation.

graph can be covered by two, three, etc. perfect matchings). Their proof uses Edmonds perfect matching polytope (vector (1/3, 1/3, ...) is a fractional perfect matching, thus it is a convex combination of perfect matchings – each of them is well spread). This, however, doesn't yield an efficient algorithm.

In [BIT13], Boyd et al. focus on developing algorithms for finding 2-factors in bridgeless cubic graphs that cover specific edge-cuts, which brings these 2-factors closer to Hamiltonian cycles. They provide an efficient algorithm that finds a minimum-weight 2-factor that covers all 3-edge cuts in weighted bridgeless cubic graphs (in contrast with finding a Hamiltonian cycle, which is computationally hard). They also provide both a polyhedral description of such 2-factors and of their complements – well spread perfect matchings. This is the first known polynomial-time algorithm for this problem, with a time complexity of  $O(n^3)$ , where n is the number of vertices. In this work, we improve this result for 3-edge connected cubic graphs using Algorithm 1 with time complexity  $O(n \log^4 n)$ .

Boyd et al. find a "peripheral 3-edge-cut" (a cut such that one side of it is internally 4-edge-connected) and then use recursion. We save computation by using the cactus model, also called a tree of cuts. In this tree it is easy to find the peripheral cut and also to update the tree when we contract a part of the cut. This leads to much improved time complexity, although only for 3-edgeconnected graphs.

We then proceed to apply this result to the study of the well-known Cycle Double Cover (or CDC) Conjecture [Sze73,Sey79]. In the language of graph embedding, CDC conjecture is equivalent to every bridgeless cubic graph having a surface embedding with no singular edges (i.e., with no edge that is on the boundary of one face twice). As an application of our work, for a 3-edge-connected cubic graph we can find embeddings with a bounded number of singular edges in time  $O(n \log^4 n)$ .

The structure of the paper is as follows. In the next section, we introduce the necessary definitions and concepts. In Section 3, we discuss the cactus model, a key component in deriving our results. Section 4 presents our main result, an efficient algorithm to find the well-spread perfect matching. Finally, in Section 5, we apply our algorithm to get results about the well-known CDC conjecture.

# 2 Preliminaries

Let G = (V, E) be a graph with vertex set V and edge set E. A graph in which all vertices have degree 3 is called *cubic*. A *cycle* is a connected 2-regular graph. A *bridge* in a graph G is an edge whose removal increases the number of components of G. Equivalently, a bridge is an edge that is not contained in any cycles of G. A graph is *bridgeless* if it contains no bridge. An *edge cut* in a graph is a set of edges whose removal increases the number of connected components of the graph. An edge cut C in G is called a *non-trivial cut* if every component of G - C has at least two vertices. Otherwise it is called *trivial*. A *k-edge-cut* in a graph is an edge cut that contains exactly k edges. A connected graph is k*edge-connected* if it remains connected whenever fewer than k edges are removed. A graph is cyclically k-edge-connected, if at least k edges must be removed to disconnect it into two components such that each component contains a cycle. We say that a subset  $F \subset E$  covers an edge-cut D if  $F \cap D \neq \emptyset$ . For a subset  $S \subseteq E$ , G/S is the graph obtained from G by contracting all the edges in S. Note that we keep multiple edges and only remove loops in such contraction.

Petersen's theorem [Pet91] states that every bridgeless cubic graph contains a perfect matching. Schönberger [Sch35] proved the following strengthened form of Petersen's theorem.

**Theorem 1** ([Sch35]). Let G = (V, E) be a bridgeless cubic graph with specified edge  $e^* \in E$ . Then there exists a perfect matching of G that contains  $e^*$ .

A perfect matching containing a specified edge  $e^*$  in a bridgeless cubic graph can be found in  $O(n \log^4 n)$  time [BBDL01].

A graph G is *embedded* in a surface S if the vertices of G are distinct elements of S and every edge of G is a simple arc connecting in S the two vertices which it joins in G, such that its interior is disjoint from other edges and vertices. An *embedding* of a graph G in S is an isomorphism of G with a graph G' embedded in S.

Let G be a graph that is cellularly embedded in a surface S, that is, every face is homeomorphic to an open disk. Let  $\pi = \{\pi_v | v \in V(G)\}$  where  $\pi_v$  is the cyclic permutation of the edges incident with the vertex v such that  $\pi_v(e)$  is the successor of e in the clockwise ordering around v. The cyclic permutation  $\pi_v$  is called the *local rotation* at v, and the set  $\pi$  is the *rotation system* of the given embedding of G in S.

Let G be a connected multigraph. A combinatorial embedding of G is a pair  $(\pi, \lambda)$  where  $\pi = \{\pi_v | v \in V(G)\}$  is a rotation system, and  $\lambda$  is a signature mapping which assigns to each edge  $e \in E(G)$  a sign  $\lambda(e) \in \{-1, 1\}$ . If e is an edge incident with  $v \in V(G)$ , then the cyclic sequence  $e, \pi_v(e), \pi_v^2(e), \ldots$  is called the  $\pi$ -clockwise ordering around v (or the local rotation at v). Given an embedding  $(\pi, \lambda)$  of G we say that G is  $(\pi, \lambda)$ -embedded. It is known that the combinatorial embedding uniquely determines a cellular embedding to some surface, up to homeomorphism [MT01, Theorems 3.2.4 and 3.3.1].

A closed walk is a sequence  $(v_0, e_0, v_1, e_1, \ldots, e_{n-1}, v_n)$  where  $v_0 = v_n$  and for every  $i, e_i = \{v_i, v_{i+1}\}$ . We say that a collection of closed walks  $C_1, \ldots, C_n$ forms a partial circuit double cover (or partial CDC) if each edge is covered at most once by one of  $C_i$ 's or exactly twice by two different  $C_i$  and  $C_j$ , and for every vertex v and edges e and f where  $e \cap f = \{v\}$ , there exists at most one closed walk  $C_i$  such that  $\{e, f\} \subseteq E(C_i)$ .

# 3 The cactus model

Here we follow the notations and definition of [NI08]. A general way to represent a subset of cuts within a graph G involves constructing a cactus representation  $(T, \varphi)$ . In this representation, T is a graph, and  $\varphi$  is a function mapping vertices from V(G) to V(T). The cactus representation (or the *cactus model*) was introduced in [DKL76]. It was further utilized in [Gab91,Din93]. This model plays a crucial role in understanding both edge connectivity and graph rigidity problems.

**Definition 1.** Let G be a graph. A pair  $(T, \varphi)$  with  $\varphi : V(G) \to V(T)$  is called a cactus representation (or cactus model) for graph G if it meets the following criteria:

- 1. For an arbitrary minimum cut  $\{S, V(T) S\} \in C(T)$ , the cut  $\{X, \overline{X}\}$  in G defined by  $X = \{u \in V(G) \mid \varphi(u) \in S\}$ , and  $\overline{X} = \{u \in V \mid \varphi(u) \in V(T) S\}$  is a minimum cut in G.
- 2. Conversely, for every minimum cut  $\{X, \overline{X}\}$  in G, there exists a minimum cut  $\{S, V(T) S\} \in C(T)$  such that  $X = \{u \in V \mid \varphi(u) \in S\}$ , and  $\overline{X} = \{u \in V \mid \varphi(u) \in V(T) S\}$ .

In this context, we use *vertex* when referring to elements of V(G) and *node* for elements of V(T). The set V(T) may include a node x that does not correspond to any vertex  $v \in V(G)$  with  $\varphi(v) = x$ ; such a node is referred to as an *empty* node. We use C(T) for the set of all minimum cuts in T.

It was shown in [DKL76] that every G has a cactus representation using a cactus graph – a multigraph where every edge is exactly one cycle. A special case of such graph is a tree with every edge doubled. It is known that when the connectivity is odd, the cactus representation is of this special type. In this case we will just call it a tree of cuts (or cactus tree). For a 3-edge-connected cubic graph G, the vertices of the graph G correspond to the leaf nodes of the cactus tree T and all the interior nodes of T are empty nodes (see Fig. 1). We will also use the following estimate for the size of T.



Fig. 1. A 3-edge-connected cubic graph G and its cactus tree T. Small white circles represents empty vertices. Dashed lines represent a non-trivial 3-edge cut in G and its equivalent edge in T.

 $\mathbf{5}$ 

**Lemma 1** ([Din93]). Let G be a 3-edge-connected cubic graph with n vertices and let T be its cactus tree. Then

$$|E(T)| \le 2n - 3.$$

# 4 Well spread perfect matchings in bridgeless cubic graphs

In this section, we present an algorithm that finds a perfect matching in a 3edge-connected cubic graph that intersects all 3-edge cuts in exactly one edge and is substantially faster than the algorithm introduced by Boyd et al. [BIT13]. We first explain the underlying technique. Let G be a graph with a 3-edge cut  $\{A, \bar{A}\}$ ; that is  $|\delta(A)| = 3$ . We let  $G_1 = G/A$  (all vertices in A are contracted to a single vertex a) and  $G_2 = G/\bar{A}$  (with a new vertex  $\bar{a}$ ). A well-spread matching M in G contains exactly one edge of  $\delta(A)$ , thus it gives us a perfect matching  $M_1$ in  $G_1$  and  $M_2$  in  $G_2$ . As edges out of a in  $G_1$  and out of  $\bar{a}$  in  $G_2$  are in natural correspondence with edges of  $\delta(A)$ , we will identify them and say that  $M_1$  and  $M_2$  agree on  $\delta(A)$ . For our algorithm the following is crucial.

**Theorem 2.** Let G, A,  $G_1$  and  $G_2$  be as above. Given a well-spread perfect matching  $M_1$  in  $G_1$  and  $M_2$  in  $G_2$  that agree on the cut  $\delta(A)$ , the union  $M_1 \cup M_2$  is a well-spread perfect matching in G.

*Proof.* The fact that  $M_1 \cup M_2$  is a perfect matching is clear as these matchings agree on  $\delta(A)$ . The fact that M is well-spread follows from the fact that 3-edge cuts in a 3-edge-connected graph do not cross, see [BIT13] for details.

Boyd et al. [BIT13] use the above theorem together with repeated finding of a "peripheral 3-edge-cut"  $\{A, \overline{A}\}$ : one where G/A is internally 4-edge-connected. We refine their approach by utilizing (and updating) the model for all 3-edge cuts that will allow us to find peripheral cuts quickly. Also, we will use the model of the cuts to quickly decompose the graph G in G/A and  $G/\overline{A}$  and then combine them back.

We will also use the following information about structure of cuts in  $G_1$  and  $G_2$ .

**Theorem 3.** Let G, A,  $G_1$  and  $G_2$  be as above. Let  $(\varphi, T)$  be the cactus tree for G. Let  $e = x_1x_2$  be the edge of T corresponding to A; that is the components of T - e are  $T'_1$ ,  $T'_2$ ,  $x_i \in V(T'_i)$  and  $A = \varphi^{-1}(V(T'_2))$ . Put  $T_i = T'_i + e$  for i = 1, 2. Define  $\varphi_1$  as a restriction of  $\varphi$  to  $\overline{A}$  and put  $\varphi_1(a) = x_1$ . We define  $\varphi_2$ symmetrically.

Then  $(\varphi_i, T_i)$  is the cactus tree representation of 3-edge cuts in  $G_i$  (for i = 1, 2).

The proof follows the same idea as that of Theorem 2: minimum odd edgecuts do not cross. We omit the details in this extended abstract.

# 6 B. Ghanbari and R. Šámal

In our application we have a 3-regular 3-edge-connected graph, so all vertices are mapped to leaf nodes of the cactus tree and nontrivial 3-cuts correspond to edges that are not incident with a leaf. In particular, when the cactus tree is a star there are no nontrivial 3-cuts and we may simply find any perfect matching. In a sense, the purpose of our algorithm is to efficiently combine matchings coming from these "special cases" of internally 4-edge-connected graphs.

To this end, we pick root in the cut model T. Let  $e_x$  be the edge connecting x to its parent. We let  $C_x$  be the three edges in the cut corresponding to  $e_x$ . We let  $A_x$  be the vertices of G that are mapped by  $\varphi$  to descendants of x (including x), so that  $C_x = \delta(A_x)$ .

We do not use this definition directly, instead we recursively update  $A_x$ ,  $C_x$  while traversing the tree. We can compute  $A_x$  as a union of  $A_y$  for all children y of x. We can compute  $C_x$  by going over  $C_y$  for all children y of x, excluding edges that lead withing  $A_x$  (between  $A_y$  and  $A_{y'}$  for two children of x). To do this efficiently we utilize the Union-Find algorithm.

In a typical step of decomposition part of the algorithm, we use Theorem 3, with the new graphs being  $G_x$  (which we store for later) and updated version of G. To illustrate the algorithm, in Figure 2 we show one step including the updated trees. We see that  $T_x$  is a star – which means  $G_x$  is internally 4-edge-connected. Updated T simply removes children of x. However, we actually do not need to update T and compute  $T_x$  in the algorithm.

In a typical step of assembling part of the algorithm, we use Theorem 2. For graph G we have our well-spread matching from the recursion. For the other graph,  $G_x$ , we compute it easily, as the graph is internally 4-edge-connected, so any perfect matching will do. Figure 3 illustrates this part of the algorithm.

**Theorem 4.** The output of Algorithm 1 is a well spread perfect matching.

*Proof.* Follows from Theorem 2 and 3 and the discussion above.

#### 4.1 Complexity Analysis

The construction of the tree of cuts (the cactus model) can be done in time  $O(n \log n)$  [Gab91]. By Lemma 1 we have |V(T)| = O(n). Next, the algorithm decomposes the graph G along 3-edge cuts. Here the main work is keeping track of the sets  $A_x$  and  $C_x$ , updating the graph G and  $G_x$ . For this we use the standard Union-Find algorithm plus a constant amount of work for changing three edges of the cut  $C_x$  at each step. Thus the total time required for this loop is  $O(n\alpha(n))$ .

In the assembly step, we repeatedly look for a perfect matching in an internally 4-edge-connected cubic graph  $G_x$  containing a given edge. By [BBDL01], this can be done in time  $O(|G_x| \log^4 |G_x|)$ . (The initial step where x is the root is faster, as we don't need to specify an edge, but this bound works as well.) The remaining work (combining the matchings) needs only a constant time per edge, so linear in total. Algorithm 1 **Require:** A 3-edge-connected cubic graph G. **Ensure:** A well spread perfect matching M. Find  $\varphi: G \to T$  using [Gab91]. Choose any node of T as root.  $\triangleright$  Decomposing G along 3-edge-cuts for all  $x \in V(T)$  in post-order do if x is the root **then**  $\triangleright$  no proper 3-edge-cut remains Do nothing, end of the for loop. else if x is a leaf then  $\triangleright$  Dealing with a trivial cut  $A_x \leftarrow \varphi^{-1}(x)$  $\triangleright$  Single vertex  $C_x \leftarrow \delta(A_x)$  $\triangleright$  three edges incident to it else  $A_x \leftarrow \bigcup \{A_y \mid y \text{ a child of } x\}$  $\triangleright$  Use Union-Find  $C_x \leftarrow \{u, v\} \in \bigcup \{C_y \mid y \text{ a child of } x\}$  s.t. only one of u, v is in  $A_x$  $G_x \leftarrow G/\bar{A}_x$  $\triangleright$  contract  $\bar{A}_x$  to a single vertex  $\bar{a}_x$ put a link to  $C_x$ ,  $G_x$  to x $G \leftarrow G/A_x$  $\triangleright$  contract  $A_x$  to a single vertex  $a_x$  $\varphi \leftarrow \varphi/\bar{A}_x \cup \{(a,x)\}$ ▷ Assembling the perfect matching  $\triangleleft$ for all  $x \in V(T)$  in reverse pre-order do if x is a root of T then Find any perfect matching M in G.  $\triangleright$  G is now internally 4-edge-connected else if x is not a leaf then  $\triangleright$  First we find which edge of  $C_x$  does M use.  $\triangleleft$  $b \leftarrow \text{neighbor of } a_x \text{ in } M$  $a \leftarrow \text{neighbor of } b \text{ in } C_x$ Find a perfect matching  $M_x$  in  $G_x$  using the edge  $a\bar{a}_x$ .  $\triangleright G_x$  is int.4-edgeconnected $M \leftarrow M \cup M_x$ return M



**Fig. 2.** A typical step in the decomposition part of the algorithm. We show a concrete 3edge-connected cubic graph G and its cactus tree T, together with the updated version of G and T and the internally 4-edge-connected graph  $G_x$  with the star cactus tree  $T_x$ .



**Fig. 3.** A typical step in the assembly part of the algorithm: we combine a perfect matching M in "new G" and  $M_x$  in  $G_x$  to get a matching in the original graph G.

#### 10 B. Ghanbari and R. Šámal

Note that  $|G_x|$  is the degree of x in T; let  $d_x$  denote this quantity. We know that  $\sum_x d_x = 2|E(T)| = O(n)$ . The time complexity is thus

$$O(n\log n) + O(n\alpha(n)) + O(n) + \sum_{x \in V(T)} d_x \log^4 d_x.$$

So the leading term in the time complexity is the final sum. As the function  $f(d) = d \log^4 d$  is convex, the sum will be maximal when one  $d_x$  is as large as possible (namely, O(n)) and the other as small as possible (namely, 1) – otherwise we can increase the sum of  $f(d_x)$ , while keeping sum of  $d_x$  constant. For this extreme case we get our bound for time complexity of the algorithm,  $O(n \log^4 n)$ .

**Theorem 5.** Algorithm 1 finds a well spread perfect matching M in a 3-edgeconnected cubic graph G in time  $O(n \log^4 n)$ .

# 5 Application

In [GS24], Ghanbari and Samal establish an upper bound of  $\frac{n}{10}$  on the number of singular edges in an embedding of a bridgeless cubic graph on a surface. They also raise the question of how efficiently one can find a perfect matching in a bridgeless cubic graph that contains no odd cut of size 3 — an essential step in determining the time complexity of finding such an embedding. Here, we answer their question for 3-edge connected cubic graphs and describe an algorithm that constructs an embedding with at most  $\frac{n}{10}$  bad edges. To provide context, we first state their results.

**Lemma 2** ([GŠ24]). Let G be a bridgeless cubic graph, and  $C_1, C_2, \ldots, C_t$  be a collection of closed walks in G. If  $C_1, C_2, \ldots, C_t$  form a partial CDC, then there is an embedding  $(\pi, \lambda)$  of G where  $C_1, \ldots, C_t$  are some of the facial walks of  $(\pi, \lambda)$ . Moreover, such an embedding can be found by a linear time algorithm.

**Theorem 6** ([GŠ24]). Let G be a bridgeless cubic graph. There exists an embedding of G with at most  $\frac{n}{10}$  singular edges.

To prove Theorem 6, in [GŠ24], we first construct a perfect matching  $M_1$ such that  $M_1$  contains no odd cut of size 3. This guarantees the existence of another perfect matching  $M_2$  satisfying  $|M_1 \cap M_2| \leq \frac{n}{10}$  (see [KKN06]). Next, we show that  $M_1 \cap M_2$  can be extended to an embedding using Lemma 2, where the potential singular edges of the embedding are precisely those in  $M_1 \cap M_2$ , and this completes their proof.

Suppose that the cubic graph G is 3-edge-connected. To find  $M_1$ , we employ Algorithm 1, which finds a perfect matching in time  $O(n \log^4 n)$ . Consequently, determining the overall time complexity reduces to finding the perfect matching  $M_2$ . We utilize Diks and Stańczyk's algorithm [DS10] to find  $M_2$  in time  $O(n \log^2 n)$ . Thus, the embedding guaranteed by Theorem 6 can be found in total time

$$O(n \log^2 n) + O(n \log^4 n) = O(n \log^4 n).$$

# 6 Conclusion

We studied a new approach to finding a perfect matching that includes all 3-edge cuts in a 3-edge-connected cubic graph, utilizing the cactus representation of the graph. We referred to such a perfect matching as *well spread*. In Section 4, we presented an algorithm that finds a well-spread perfect matching in a 3-edge-connected cubic graph in time  $O(n \log^4 n)$ .

In general, the best-known algorithm for finding a well-spread perfect matching in a bridgeless cubic graph has a time complexity of  $O(n^3)$  [BIT13]. In the future, it would be interesting to determine whether the cactus representation can be leveraged to develop a faster algorithm for finding such a well-spread perfect matching. However, the issue is that representing 3-edge-cuts in a graph that may contain 2-edge-cuts is more complicated.

# References

- BBDL01. Therese C. Biedl, Prosenjit Bose, Erik D. Demaine, and Anna Lubiw. Efficient algorithms for Petersen's matching theorem. J. Algorithms, 38(1):110– 134, 2001.
- BIT13. Sylvia Boyd, Satoru Iwata, and Kenjiro Takazawa. Finding 2-factors closer to TSP tours in cubic graphs. SIAM Journal on Discrete Mathematics, 27(2):918–939, 2013.
- Din93. Efim Dinitz. The 3-edge-components and a structural description of all 3edge-cuts in a graph. In Ernst W. Mayr, editor, *Graph-Theoretic Concepts in Computer Science*, pages 145–157, Berlin, Heidelberg, 1993. Springer Berlin Heidelberg.
- DKL76. E. Dinic, Alexander Karzanov, and M. Lomonosov. The system of minimum edge cuts in a graph. In book: Issledovaniya po Diskretnoi Optimizatsii (Engl. title: Studies in Discrete Optimizations), A.A. Fridman, ed., Nauka, Moscow, 290-306, in Russian,, 01 1976.
- DS10. Krzysztof Diks and Piotr Stanczyk. Perfect matching for biconnected cubic graphs in  $O(n \log^2 n)$  time. In Jan van Leeuwen, Anca Muscholl, David Peleg, Jaroslav Pokorný, and Bernhard Rumpe, editors, *SOFSEM 2010: Theory and Practice of Computer Science*, pages 321–333, Berlin, Heidelberg, 2010. Springer Berlin Heidelberg.
- Gab90. Harold N. Gabow. Data structures for weighted matching and nearest common ancestors with linking. In Proceedings of the First Annual ACM-SIAM Symposium on Discrete Algorithms, SODA '90, page 434–443, USA, 1990. Society for Industrial and Applied Mathematics.
- Gab91. Harold N. Gabow. Applications of a poset representation to edge connectivity and graph rigidity. [1991] Proceedings 32nd Annual Symposium of Foundations of Computer Science, pages 812–821, 1991.
- GŠ24. Babak Ghanbari and Robert Šámal. Approximate cycle double cover. In Adele Anna Rescigno and Ugo Vaccaro, editors, *Combinatorial Algorithms*, pages 421–432, Cham, 2024. Springer Nature Switzerland.
- KKN06. Tomáš Kaiser, Daniel Král', and Serguei Norine. Unions of perfect matchings in cubic graphs. In Martin Klazar, Jan Kratochvíl, Martin Loebl, Jiří Matoušek, Pavel Valtr, and Robin Thomas, editors, *Topics in Discrete Mathematics*, pages 225–230, Berlin, Heidelberg, 2006. Springer Berlin Heidelberg.

- 12 B. Ghanbari and R. Šámal
- MT01. Bojan Mohar and Carsten Thomassen. *Graphs on Surfaces.* Johns Hopkins series in the mathematical sciences. Johns Hopkins University Press, 2001.
- NI08. Hiroshi Nagamochi and Toshihide Ibaraki. Algorithmic aspects of graph connectivity. Encyclopedia of mathematics and its applications ; v. 123. Cambridge University Press, Cambridge, 2008.
- Pet91. Julius Petersen. Die Theorie der regulären graphs. Acta Math., 15(1):193–220, 1891.
- Sch35. Tibor Schönberger. Ein beweis des petersenschen graphensatzes. Acta litterarum ac scientiarum Regiae Universitatis Hungaricae Francisco-Josephinae: Sectio scientiarum mathematicarum, 7:51–57, 1935.
- Sey79. Paul D Seymour. Sums of circuits. *Graph theory and related topics*, 1:341–355, 1979.
- Sze73. G. Szekeres. Polyhedral decompositions of cubic graphs. Bulletin of the Australian Mathematical Society, 8(3):367–387, 1973.