DeLTa: A Decoding Strategy based on Logit Trajectory Prediction Improves Factuality and Reasoning Ability

Yunzhen He¹, Yusuke Takase¹, Yoichi Ishibashi^{2*}, Hidetoshi Shimodaira^{1,3}

¹Kyoto University, ²NEC, ³RIKEN AIP

he.yunzhen.25d@st.kyoto-u.ac.jp, y.takase@sys.i.kyoto-u.ac.jp, yoichi-ishibashi@nec.com, shimo@i.kyoto-u.ac.jp

Abstract

Large Language Models (LLMs) are increasingly being used in real-world applications. However, concerns about the reliability of the content they generate persist, as it frequently deviates from factual correctness or exhibits deficiencies in logical reasoning. This paper proposes a novel decoding strategy aimed at enhancing both factual accuracy and inferential reasoning without requiring any modifications to the architecture or pre-trained parameters of LLMs. Our approach adjusts next-token probabilities by analyzing the trajectory of logits from lower to higher layers in Transformers and applying linear regression. We find that this Decoding by Logit Trajectory-based approach (DeLTa) effectively reinforces factuality and reasoning while mitigating incorrect generation. Experiments on TruthfulQA demonstrate that DeLTa attains up to a 4.9% improvement over the baseline. Furthermore, it enhances performance by up to 8.1% on StrategyQA and 7.3% on GSM8K, both of which demand strong reasoning capabilities.¹

1 Introduction

Natural language processing has advanced significantly with the rise of large language models (LLMs) (OpenAI, 2024; Dubey et al., 2024). However, ensuring the factual accuracy of LLMgenerated text remains challenging. A notable issue is hallucination, where models produce factually incorrect content, posing risks in fields like information retrieval, medicine, and law (Huang et al., 2024). Calculation errors in the logical reasoning further contribute to inaccuracies, stemming from incorrect token predictions during decoding. Mitigation strategies for these issues include the selection of dataset, modifications to loss functions (Ouyang et al., 2022), and the incorporation




Figure 1: Overview of DeLTa. When input tokens are fed into the LLM, the logits from each layer (e.g., layers 30, 31, and 32) are computed and shown as bar graphs to illustrate changes between tokens (e.g., "Seattle" vs. "Olympia"). A linear regression (red line) approximates the logit trajectory (blue dots). Using this regression, we extrapolate the logits for a virtual 33rd layer (red dot) and improve prediction beyond the original outputs.

of external knowledge (Wan et al., 2024). However, implementing these methods requires refining models or acquiring additional data, which can incur substantial costs.

To overcome these limitations, we propose a decoding strategy, that boosts generation accuracy without extra training or data. Inspired by Chuang et al. (2024), who observed that correct token probabilities tend to rise in higher Transformer layers, we introduce **De**coding by Logit **Tra**jectory-based approach (DeLTa), which treats each layer's logits as a time-series and use linear regression to predict upper-layer logits (Figure 1).

Experiments demonstrate that DeLTa enhances factuality by up to 4.9% on TruthfulQA, 5.0% on TriviaQA, and 2.4% on Natural Questions, while also improving reasoning on StrategyQA and GSM8K by up to 8.1%. These findings confirm that DeLTa refines token prediction, leading to improved factuality and reasoning capabilities.

^{*} Work done while at Kyoto University.

¹Our code is available at https://github.com/githubhyz/DeLTa.

2 Related Work

Previous research on guiding LLMs to generate factually accurate text can be broadly categorized into training-based (Lin et al., 2024; Liang et al., 2024) and non-training-based approaches. DeLTa falls into the latter category. Among non-training-based methods, Chang et al. (2024) introduced Asymptotic Probability Decoding, which extrapolates output probabilities from LLMs of different sizes under Contrastive Decoding (CD) (Li et al., 2023). Another method, Sharma et al. (2024) showed that certain capabilities of Transformers are concentrated in the latter layers and achieved improvements in sentiment classification by applying linear extrapolation to a text classifier based on CD. These approaches estimate probabilities using linear regression or extrapolation, relying on only two data points (e.g., the outputs of two models or an intermediate layer and the final layer). In contrast, DeLTa predicts logits instead of probabilities and performs regression across the entire sequence of logits from intermediate layers to the final layer, then recalculates the probability values. Another non-training-based approach, DoLa (Chuang et al., 2024), uses the difference in log probabilities between a lower and higher layer of the model within CD to encourage factually based text generation. Given its strong performance in factuality-sensitive tasks, DoLa serves as a valuable reference for comparison.

3 Method

DeLTa aims to improve the probability of generating the correct token during decoding by focusing on changes in the logits across the Transformer's layers. Specifically, when decoding the next token in an N-layer Transformer, we regard the logits produced by each layer as a time series (§ 3.1). Based on the observation that higher layers generally assign higher probabilities to the correct token (Chuang et al., 2024), we employ a simple linear regression model (§ 3.2) to predict the logits of the higher layers. By leveraging the upward trend from lower to higher layers, this approach enhances the final prediction performance.

3.1 Token Probability at Arbitrary Layers

Let x_t denote the token at position t, and let the preceding token sequence be $x_{<t} = \{x_1, \ldots, x_{t-1}\}$. The application of the Logit Lens (nostalgebraist, 2020), enables the computation of the hypothetical probability distribution at any arbitrary layer denoted by the set of all possible values of the layer, i.e., $\ell \ (1 \le \ell \le N)$.

$$P_{\ell}(x_t \mid x_{\leq t}) = \operatorname{softmax}\left(\operatorname{logit}^{(\ell)}\right)_{x_t} \quad x_t \in \mathcal{X}.$$

Here, softmax represents the softmax function, and \mathcal{X} denotes the vocabulary set.

3.2 Decoding by Logit Trajectory

We employ a linear regression to model changes in logits across Transformer layers, thereby enabling the estimation of logits at virtual layers. Because the probability of the correct token generally increases in higher layers, we explicitly learn this upward trend to produce more reliable token probabilities. Concretely, we select an intermediate layer N_{mid} ($1 \le N_{mid} \le N - 1$) and use its logit vectors up to the final layer N to estimate logits. We then compute token probability $P_L(x_t \mid x_{< t})$ for a virtual layer L ($L \in \mathbb{R}$)

Linear Regression. We define the explanatory variable as the Transformer layer indices:

$$\boldsymbol{X}_{\text{reg}} = [N_{mid}, N_{mid} + 1, \cdots, N]$$

and the response variable as the logit vectors:

 $m{Y}_{\mathsf{reg}} = [\mathbf{logit}^{(N_{mid})}, \mathbf{logit}^{(N_{mid}+1)}, \cdots, \mathbf{logit}^{(N)}]$

Based on the least squares method, the estimated logit at a virtual layer L is computed as follows:

$$\widehat{\mathbf{logit}}^{(L)} = \hat{\boldsymbol{\beta}}_0 + \hat{\boldsymbol{\beta}}_1 L,$$

where $\hat{\beta}_0$ is the intercept and $\hat{\beta}_1$ is the regression coefficient. These parameters are determined by:

$$\hat{\boldsymbol{\beta}}_0 = E(\boldsymbol{Y}_{\text{reg}}) - \hat{\boldsymbol{\beta}}_1 E(\boldsymbol{X}_{\text{reg}}), \hat{\boldsymbol{\beta}}_1 = \frac{C(\boldsymbol{X}_{\text{reg}}, \boldsymbol{Y}_{\text{reg}})}{V(\boldsymbol{X}_{\text{reg}})}$$

Here, E, V, and C represent the mean, variance, and covariance, respectively.

Token Probability Computation. The final token probability is computed from logit $\widehat{\log it}^{(L)}$, filtered by the candidate token set \mathcal{V}_{head} :

$$\hat{P}_L(x_t \mid x_{< t}) = \operatorname{softmax}(\widehat{\operatorname{logit}}_{\mathcal{V}_{\text{head}}}^{(L)})_{x_t}$$

Here, the candidate set V_{head} is determined following Chuang et al. (2024) as:

$$\mathcal{V}_{\text{head}} = \left\{ x_t \in \mathcal{X} : \dot{P}(x_t \mid x_{< t}) \ge \alpha \max_{w} P_N(w \mid x_{< t}) \right\}.$$
(1)

Tokens that are not included in the candidate set are assigned a probability of 0.

	Factuality				СоТ		
Model	TruthfulQA (Open QA)		Closed QA		Reasoning		
	%True↑	%Info↑	%True*Info↑	TriviaQA	NQ	StrQA	GSM8K
Qwen2.5-7B	68.9	92.4	64.1	39.1	11.5	76.9	78.7
+ filter	67.4	93.3	60.7	44.1	13.0	78.1	81.6
+ DoLa (early-layer)	71.2	91.6	62.9	41.9	12.8	73.8	76.3
+ DoLa (late-layer)	79.6	75.0	55.0	33.6	10.2	67.7	67.9
+ DeLTa	66.8	98.0	65.4	44.1	13.0	81.2	81.6
Mistral-7B-v0.1	56.3	95.3	53.8	51.3	16.0	65.3	31.0
+ filter	59.4	81.1	40.9	54.5	18.2	69.7	35.8
+ DoLa (early-layer)	50.5	91.7	42.9	53.2	17.2	69.3	33.4
+ DoLa (late-layer)	51.2	91.2	42.9	53.3	17.0	71.3	33.7
+ DeLTa	54.3	92.1	47.0	54.1	17.9	72.5	38.2
Llama-3.1-8B	50.8	90.1	44.0	50.0	14.0	64.0	42.8
+ filter	50.7	95.2	46.9	53.8	16.4	66.0	47.8
+ DoLa (early-layer)	48.9	99.0	48.2	53.2	15.6	66.4	46.1
+ DoLa (late-layer)	49.2	99.3	48.5	53.1	15.3	64.9	45.9
+ DeLTa	51.5	97.1	48.9	53.8	16.4	72.1	50.1

Table 1: Experimental results on (1) factuality tasks, including TruthfulQA, TriviaQA, and Natural Questions (NQ) and (2) reasoning tasks involving Chain-of-Thought (CoT), including StrategyQA (StrQA) and GSM8K. Bold values represent the highest scores. DeLTa achieves a strong performance on the %True*Info metric for TruthfulQA and shows substantial improvements across multiple benchmarks, including TriviaQA and GSM8K. Importantly, in GSM8K, which requires not only factual knowledge but also arithmetic reasoning, DeLTa outperforms the baseline by more than 7 points. These results indicate that DeLTa enhances both knowledge-intensive tasks and complex reasoning capabilities.

4 **Experiments**

4.1 Setup

Models and Baselines. We use Qwen2.5-7B (Qwen Team, 2024), Mistral-7B-v0.1 (Jiang et al., 2023), and Llama-3.1-8B (Dubey et al., 2024), comparing them with four baselines. The first baseline is the raw model output. The second baseline (filter) applies \mathcal{V}_{head} (Equation (1)) to the raw model output. This baseline is specifically introduced to determine whether the performance improvement of our method primarily results from the filtering mechanism rather than from DeLTa. The third and fourth baselines, DoLa (early-layer) and DoLa (late-layer), are derived from DoLa (Chuang et al., 2024), a state-of-the-art decoding method that significantly enhances generation quality by leveraging the difference in log probabilities between an intermediate layer and the final layer. DoLa dynamically selects the intermediate layer from predefined layer buckets, which are primarily partitioned into two groups: early layers (lower half of the model) and late layers (upper half of the model). We denote these two configurations as DoLa (early-layer) and DoLa (late-layer), respectively. Originally, DoLa determines the optimal

bucket using a validation set. However, by comparing DeLTa with both DoLa (early-layer) and DoLa (late-layer), we assess whether DeLTa remains effective regardless of the specific intermediate layer bucket selection. This evaluation highlights the robustness and general applicability of DeLTa beyond DoLa's predefined selection strategy.

Tasks and Datasets. Following DoLa (Chuang et al., 2024), we evaluate open-ended generation tasks: TruthfulQA (Lin et al., 2022) (factual accuracy in open QA), StrategyQA (StrQA)(Geva et al., 2021), and GSM8K(Cobbe et al., 2021) (reasoning). To assess token-level accuracy across diverse tasks, we evaluate knowledge retrieval via closed QA tasks: TriviaQA (Joshi et al., 2017) and Natural Questions (NQ) (Kwiatkowski et al., 2019). Evaluation metrics are in Appendix A, and Appendix B details the prompt structure and generation hyperparameters. These settings follow DoLa for fair comparation. Additionally, Appendix E explains the selection of N_{mid} and virtual layer L for DeLTa.

4.2 Results

Factuality. Table 1 summarizes the model performance across factuality benchmarks, demonstrat-

ing the effectiveness of DeLTa compared to strong baselines, including filtering and DoLa variants. On TruthfulQA (%True*Info), which measures the proportion of responses that are both truthful and informative, DeLTa improves Llama-3.1-8B from 44.0% to 48.9%, surpassing the best baseline (46.9%) by 2 points. While existing methods such as filtering and DoLa (early-layer) offer some improvements, they fail to consistently enhance factual accuracy across datasets. For closed QA tasks, such as TriviaQA, Qwen2.5-7B achieves a 5-point increase (39.1% to 44.1%), but baselines plateau at 44.1%, indicating that DeLTa extracts additional factual knowledge beyond filtering alone. Similarly, on NQ, Qwen2.5-7B improves from 11.5% to 13.0%, matching the best baseline but exhibiting greater consistency across models. These findings suggest that DeLTa consistently produces responses with substantial factual accuracy across various datasets.

CoT Reasoning. DeLTa also demonstrates substantial improvements in CoT reasoning. On GSM8K, Qwen2.5-7B improves from 78.7% to 81.6%, Mistral-7B from 31.0% to 38.2%, and Llama-3.1-8B from 42.8% to 50.1%, achieving up to a 7.3-point gain. While baselines contribute to performance (e.g., Qwen2.5-7B reaches 81.6%), their impact is inconsistent across models. DoLa (early-layer) sometimes introduces minor improvements, while DoLa (late-layer) frequently fails to generalize, particularly on GSM8K. These results suggest that DeLTa enhances the accuracy of generated text, thereby leading to significant improvements in reasoning.

5 Analysis: Logit Linearity Over Layer Depths

In DeLTa, it is crucial to evaluate the extent to which the logits retain a linear structure across layers. Therefore, this section employs the coefficient of determination, which quantifies the goodness of fit in regression models, to assess the degree of linearity in the logits across different layers based on experimental results.

Experimental Procedure. First, a text is input into the LLM, and the top 50 tokens with the highest logits in the final layer are extracted. Next, following the procedure described in § 3.2, the predicted and original logits of these tokens from layer N_{mid} to N are used to compute the coefficient of




Figure 2: Mean coefficient of determination (mean R^2) obtained from the experimental procedure. Target LLMs are Qwen2.5-7B, Mistral-v0.1-7B, and Llama-3.1-8B. The vertical axis represents the mean R^2 , and the horizontal axis represents the ratio (N_{mid}/N) of layer indices.

determination R^2 for each token. Then, R^2 is averaged across these tokens and further averaged over multiple input sentences from the datasets described in §4.1 to obtain the mean R^2 value.

Results. As shown in Figure 2, the target LLMs—Qwen2.5-7B, Mistral-v0.1-7B, and Llama-3.1-8B—exhibit a substantial increase in mean R^2 at higher layers. For instance, Llama-3.1-8B reaches approximately 0.9 near the final layer. These results indicate that at higher layers, the coefficient of determination is high, suggesting that a simple linear model effectively captures logit relationships. However, at lower layers, it remains relatively low, implying that more complex functional forms may enhance accuracy. Optimizing the regression model by layer depth could further improve logit estimation. Detailed results for individual datasets are in Appendix D.

6 Conclusion

This study aimed to enhance the factual accuracy and reasoning of text generated by LLMs. The proposed method, DeLTa, operates without additional training or data. By leveraging token probability distributions across Transformer layers and employing linear regression, we developed a framework that is both computationally efficient and easily integrable. Empirical evaluations across multiple benchmarks demonstrate that DeLTa significantly improves factual accuracy and exhibits effectiveness in reasoning tasks.

7 Limitation

The proposed method (DeLTa) in this study has several limitations, as outlined below:

- This study primarily evaluates the method using English datasets (TruthfulQA, TriviaQA, Natural Questions, CoT). Its applicability to other languages remains unverified.
- Due to computational resource constraints, we could not conduct experiments on largescale language models. Whether our approach maintains its effectiveness in larger models needs to be investigated in future studies.

Future research should focus on overcoming these limitations to establish a more generalizable and highly accurate factuality correction method applicable to a broader range of language models.

Acknowledgement

This study was partially supported by JSPS KAK-ENHI 22H05106, 23H03355, JST CREST JP-MJCR21N3.

References

- Haw-Shiuan Chang, Nanyun Peng, Mohit Bansal, Anil Ramakrishna, and Tagyoung Chung. 2024. Explaining and improving contrastive decoding by extrapolating the probabilities of a huge and hypothetical LM. In Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing, pages 8503–8526, Miami, Florida, USA. Association for Computational Linguistics.
- Yung-Sung Chuang, Yujia Xie, Hongyin Luo, Yoon Kim, James R. Glass, and Pengcheng He. 2024. Dola: Decoding by contrasting layers improves factuality in large language models. In *The Twelfth International Conference on Learning Representations*.
- Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. 2021. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*.
- Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, et al. 2024. The Ilama 3 herd of models. *arXiv preprint arXiv:2407.21783*.
- Mor Geva, Daniel Khashabi, Elad Segal, Tushar Khot, Dan Roth, and Jonathan Berant. 2021. Did aristotle use a laptop? a question answering benchmark with implicit reasoning strategies. *Transactions of the Association for Computational Linguistics*, 9:346– 361.

- Lei Huang, Weijiang Yu, Weitao Ma, Weihong Zhong, Zhangyin Feng, Haotian Wang, Qianglong Chen, Weihua Peng, Xiaocheng Feng, Bing Qin, and Ting Liu. 2024. A survey on hallucination in large language models: Principles, taxonomy, challenges, and open questions. *ACM Trans. Inf. Syst.* Just Accepted.
- Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. 2023. Mistral 7b. *arXiv preprint arXiv:2310.06825*.
- Mandar Joshi, Eunsol Choi, Daniel Weld, and Luke Zettlemoyer. 2017. TriviaQA: A large scale distantly supervised challenge dataset for reading comprehension. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1601–1611, Vancouver, Canada. Association for Computational Linguistics.
- Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Jacob Devlin, Kenton Lee, Kristina Toutanova, Llion Jones, Matthew Kelcey, Ming-Wei Chang, Andrew M. Dai, Jakob Uszkoreit, Quoc Le, and Slav Petrov. 2019. Natural questions: A benchmark for question answering research. *Transactions of the Association for Computational Linguistics*, 7:452–466.
- Xiang Lisa Li, Ari Holtzman, Daniel Fried, Percy Liang, Jason Eisner, Tatsunori Hashimoto, Luke Zettlemoyer, and Mike Lewis. 2023. Contrastive decoding: Open-ended text generation as optimization. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 12286–12312, Toronto, Canada. Association for Computational Linguistics.
- Yuxin Liang, Zhuoyang Song, Hao Wang, and Jiaxing Zhang. 2024. Learning to trust your feelings: Leveraging self-awareness in llms for hallucination mitigation. arXiv preprint arXiv:2401.15449.
- Stephanie Lin, Jacob Hilton, and Owain Evans. 2022. Truthfulqa: Measuring how models mimic human falsehoods. In Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 3214–3252.
- Zhenghao Lin, Zhibin Gou, Yeyun Gong, Xiao Liu, yelong shen, Ruochen Xu, Chen Lin, Yujiu Yang, Jian Jiao, Nan Duan, and Weizhu Chen. 2024. Not all tokens are what you need for pretraining. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*.

nostalgebraist. 2020. Interpreting gpt: the logit lens.

OpenAI. 2024. Hello gpt-4o.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller,

	Latency (ms/token)		Throughput (token/s)		
Model	Baseline	DeLTa	Baseline	DeLTa	
Qwen2.5-7B	5.8	8.2	374.7	242	
Mistral-7B-v0.1	37.1	135.1	27.4	7.5	
Llama-3.1-8B	30.3	153.9	33.1	6.5	

Table 2: Comparison latency (ms/token) and throughput (token/s) for Different Models

Maddie Simens, Amanda Askell, Peter Welinder, Paul F Christiano, Jan Leike, and Ryan Lowe. 2022. Training language models to follow instructions with human feedback. In *Advances in Neural Information Processing Systems*, volume 35, pages 27730–27744. Curran Associates, Inc.

- Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. 2019. Pytorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems 32*, pages 8024–8035. Curran Associates, Inc.
- Qwen Team. 2024. Qwen2.5: A party of foundation models.
- Mayukh Sharma, Sean O'Brien, and Julian McAuley. 2024. Linear layer extrapolation for fine-grained emotion classification. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 20880–20888, Miami, Florida, USA. Association for Computational Linguistics.
- Fanqi Wan, Xinting Huang, Leyang Cui, Xiaojun Quan, Wei Bi, and Shuming Shi. 2024. Knowledge verification to nip hallucination in the bud. In Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing, EMNLP 2024, Miami, FL, USA, November 12-16, 2024, pages 2616–2633. Association for Computational Linguistics.
- Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, Mariama Drame, Quentin Lhoest, and Alexander M. Rush. 2020. Transformers: State-of-the-art natural language processing. In Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations, pages 38–45, Online. Association for Computational Linguistics.

A Evaluation Metrics

The evaluation metrics used for the datasets in our experiments are as follows:

- TruthfulQA: Following Lin et al. (2022), We use a fine-tuned GPT-4 model to compute the scores of truthfulness (%Truth) and informativeness (%Info) for responses generated by LLMs. %Truth measures the degree to which a response is factually accurate, while %Info quantifies the amount of useful information contained in the response. Additionally, %Truth*Info is the product of %Truth and %Info, representing the degree to which a response maintains truthfulness while being informative. Higher values indicate better performance.
- **TriviaQA and NQ**: The accuracy is calculated based on the exact match between the responses generated by the LLM and the gold answers.
- StrQA and GSM8K: The accuracy is computed based on the exact match between the extracted final answer from the LLMgenerated response and the gold answer.

B Generation Hyper-parameters

The hyperparameters employed for generation were standardized across all experiments, with the temperature parameter fixed at 0.9 and the top-k and top-p sampling parameters set to 50 and 0.95, respectively. The repetition penalty was set to 1.0 for the raw model output and to 1.2 for other methods. Furthermore, the maximum token length was set to 50 for the TruthfulQA, TriviaQA, and Natural Questions datasets, and 256 for the StrategyQA and GSM8K datasets. About α in Equation (1), we set $\alpha = 0.1$. The above parameters are all derived from DoLa (Chuang et al., 2024).

For each task, the LLM was provided with prompts and questions, and the generated responses were evaluated. The prompt structure and their




Figure 3: Logit linearity of different models (Qwen2.5-7B, Mistral-v0.1-7B, Llama-3.1-8B) on various datasets (TruthfulQA, TriviaQA, Natural Questions, StrategyQA, GSM8K), as calculated in § 5. The horizontal axis represents the layer ratio, while the vertical axis shows the mean R^2 , which denotes the average coefficient of determination.

selection followed Chuang et al. (2024). Specifically, we adopted the same few-shot examples as in Chuang et al. (2024) to ensure a fair comparison. However, due to computational resource constraints, we set the number of few-shot examples to 6.

C Computational Cost

The computational cost associated with the proposed method was measured using Latency and Throughput, and subsequently compared with the raw model output (Baseline).

As demonstrated in Table 2, DeLTa tends to increase latency and decrease throughput in comparison to the baseline. However, in Qwen2.5-7B, the increase in latency is limited to 1.4 times, and the throughput is maintained at a practical speed. Although there is an increase in cost in Mistral-7B-v0.1 and Llama-3.1-8B, it remains within an acceptable range. In summary, DeLTa can be employed without a substantial increase in computational cost compared to the Baseline, and it can be deemed sufficiently practical, contingent upon the model selection.

D Logit Linearity with Different Datasets

In this section, we examine the logit linearity across the intermediate layers of models for each dataset (TruthfulQA, TriviaQA, Natural Questions, StrategyQA, GSM8K), following the experimental procedure described in §5. The results are presented in Figure 3. The horizontal axis, N_{mid}/N , represents the starting point of the explanatory variables, while the vertical axis, mean R^2 , denotes the mean coefficient of determination.

When comparing the results across datasets, a general trend is observed: in the higher layers of the model (the last 4-5 layers), the mean R^2 values increase to around 0.8, indicating relatively high logit linearity. Notably, Mistral-v0.1-7B and Qwen2.5-7B consistently exhibit higher mean R^2 values than Llama-3.1-8B, suggesting that logit linearity is more pronounced in these models.

Conversely, in the lower layers, the mean R^2 values are relatively low, with significant variability across datasets and models. In particular, Llama-3.1-8B tends to have determination coefficients below 0.6 in the lower layers, suggesting lower linearity compared to other models.

Additionally, in the middle layers around $N_{mid} = 20$, a decline in mean R^2 is observed in

Dataset	Qwen2.5-7B	Mistral-7B-v0.1	Llama-3.1-8B
TruthfulQA	26, 28.5	31, 32.5	30, 32
TriviaQA	27, 28	28, 32	31, 32
Natural Questions	27, 28	27, 32	31, 32
Strategy QA	25, 28	29, 32	28, 32
GSM8K	27, 28	26, 32	28, 32

Table 3: Results of the selected M and L. The left and right numbers in each cell represent M and L, respectively.

some models. This phenomenon suggests that logits undergo nonlinear transformations in the intermediate layers. However, as the model approaches the final layers, mean R^2 increases again, indicating that logit representations become more linear.

Overall, consistent with the experimental results described in §5, these findings suggest that while logit linearity across layers is dataset-dependent, it generally stabilizes and improves as the model approaches the final layers.

E Configuration of DeLTa

DeLTa includes adjustable hyperparameters, N_{mid} and L. To select the optimal intermediate layer N_{mid} and the target virtual layer for estimation Lfor each model, we constructed validation and test datasets from each dataset. First, we determined the values of N_{mid} and L that maximize the accuracy of DeLTa for each model using the validation dataset. Then, using the selected N_{mid} and L, we conducted a comparison with the baseline on the test dataset.

For datasets without a validation set (TruthfulQA, StrQA), 10% of the test data was used as the validation data. On the other hand, for datasets with an existing validation set (TriviaQA, NQ, GSM8K), we extracted 10% of the existing validation dataset for use in our experiments.

In the experiments, we selected N_{mid} from $\{N-6, N-5, \ldots, N-1\}$ and L from $\{N, N+0.5\}$. The selected values of N_{mid} and L are presented in Table Table 3.

After experiments, as shown in Table Table 3, the values of N_{mid} and L selected based on validation exhibit different tendencies depending on the dataset. Notably, in TruthfulQA, selecting an outer layer contributed to performance improvement, whereas in other datasets, optimization through smoothing was found to be the most effective.

In conclusion, the range of selected N_{mid} and L values remains largely consistent across mod-

els, with no extreme differences observed between models. This suggests that DeLTa can be generally applied without dependence on specific datasets or models.

F Generated Examples

In this section, we present response examples from Qwen2.5-7B and DeLTa for questions in the GSM8K dataset. The example sentences included in the few-shot prompt are omitted, and only the pure model responses are compared. These examples illustrate cases where DeLTa functioned effectively. Among the responses to each question shown in Table 4, the output of DeLTa is listed in the right column.

G Implementation library

We used PyTorch (Paszke et al., 2019) and Hugging Face Transformers (Wolf et al., 2020) for all experiments.

H Computational Resources

In all experiments in this study, the GPUs used were NVIDIA RTX 6000 Ada Generation or NVIDIA RTX A6000. All experiments were performed using torch.float16, and the VRAM used was approximately 15GB to 40GB.

Method	Qwen2.5-7B	Qwen2.5-7B + DeLTa		
Question	Cecilia just bought a new puppy. According to her veterinarian, she has to feed the puppy 1 cup of dog food every day for the first 180 days. Then she has to feed the puppy 2 cups of dog food every day for the rest of its life. If one bag of dog food contains 110 cups, how many bags of dog food will Cecilia use in the first year?			
Answer	The puppy needs to be fed 1 cup of dog food per day for 180 days, so the total amount of food needed for the first 180 days is 1 cup/day x 180 days = 180 cups of dog food. If one bag of dog food contains 110 cups, then Cecilia will need 180 cups / 110 cups/bag = 1.64 bags of dog food. Since she can't buy a fraction of a bag, she will need to buy 2 bags of dog food for the first year. The answer is 2.	In the first 180 days, the puppy will consume 180 * $1 = 180$ cups of dog food. In the first year, there are 365 days. So after the first 180 days, there are 365 - 180 = 185 days remaining. In those remaining days, the puppy will consume 185 * $2 = 370$ cups of dog food. In total, the puppy will consume 180 + 370 = 550 cups of dog food in the first year. Since one bag contains 110 cups, Cecilia will need 550 / 110 = 5 bags of dog food in the first year. The answer is 5.		
Question		ays, she slept 2 hours less, each, because she had to she slept 1 hour more than those two days, how many		
Answer	Sadie slept 8 hours on Monday. On the next two days, she slept 2 hours less each day, so $8 - 2 = 6$ hours each day. For those two days, she slept $6 *$ 2 = 12 hours in total. For the rest of the week, she slept 1 hour more than those two days, so $6 + 1 =$ 7 hours each day. There are 5 days in the week, so for the rest of the week, she slept $7 * 5 = 35$ hours. In total, she slept 8 (Monday) + 12 (next two days) + 35 (rest of the week) = 55 hours throughout the week. The answer is 55.	Sadie slept 8 hours on Monday. On Tuesday and Wednesday, she slept 2 hours less than on Monday, so she slept $8 - 2 = 6$ hours on each of those days. In total for those three days, she slept $8 + 6 + 6 =$ 20 hours. For the rest of the week, she slept 1 hour more than on those two days, so she slept $6 + 1 =$ 7 hours on each of those days. She has four more days in the week, so she slept $7 * 4 = 28$ hours on those days. In total, she slept $20 + 28 = 48$ hours throughout the week. The answer is 48.		
Question	There are 700 bees in a hive. There are twice as many worker bees as baby bees, and there are twice as many babies as queens. How many worker bees are there?			
Answer	The total ratio is 2 (workers) + 1 (baby) + 1 (queen) = 4 parts. Each part has 700 / 4 = 175 bees. There- fore, there are 2 x 175 = 350 worker bees. The answer is 350.	Let's represent the number of worker bees as W, the number of baby bees as B, and the number of queens as Q. We know that there are 700 bees in total, so W + B + Q = 700. We also know that there are twice as many worker bees as baby bees, so W = 2B, and there are twice as many substitute these equations into the first equation to get 2B + B + Q = 700. Combining like terms, we get 3B + Q = 700. Now we can substitute B = 2Q into this equation to get 3(2Q) + Q = 700. Simplifying, we get 6Q + Q = 700. Combining like terms, we get 7Q = 700. Dividing both sides by 7, we get Q = 100. Now we can substitute Q = 100 back into B = 2Q to get B = 2(100) = 200. Finally, we can substitute B = 200 back into W = 2B to get W = 2(200) = 400. The answer is 400.		
Question	barbecue. It's a big event, so he has 60 potatoes to get	for making potato salad for his big family reunion through. The potatoes are roughly the same size, so it ach one. It takes Billy about a minute and a half to peel ong will it take Billy to finish prepping the potatoes?		
Answer	It takes Billy about 1.5 minutes to peel a potato, which is $1.5 \ge 60 = 90$ seconds. It takes him about 5 seconds to cut each potato. So it takes him about $90 + 5 \ge 60 = 90 + 300 = 390$ seconds. To convert this into minutes, we divide by 60, so it takes Billy about $390 / 60 = 6.5$ minutes to finish prepping the potatoes. The answer is 6.5.	It takes 1.5 minutes to peel each potato, so for 60 potatoes, it will take $1.5 * 60 = 90$ minutes to peel them all. It takes 5 seconds to cut each potato, so for 60 potatoes, it will take $5 * 60 = 300$ seconds to cut them all. To convert seconds to minutes, we divide by 60, so it will take $300 / 60 = 5$ minutes to cut the potatoes. In total, it will take 90 minutes $+ 5$ minutes $= 95$ minutes to prep the potatoes. The answer is 95 .		
Question		r each gallon they make it costs \$3 for lemons and \$2 asses per gallon. If they made \$25 in profit, how much		
Answer	They spent \$5 per gallon because $3 + 2 = 5$. They sold 8 gallons because $25 / 3.125 = 8$. They spent \$40 on lemons because $8 \times 5 = 40$. The answer is 40	They spent \$3 per gallon on lemons and \$2 per gallon on sugar, so a total of $$3 + $2 = $5 per gallon.$ They sell 20 glasses per gallon at \$0.50 each, so they make 20 * \$0.50 = \$10 per gallon. They made \$25 in profit, so they must have made \$25 + \$5 = \$30 in total. Since they make \$10 per gallon, they must have made \$30 / \$10 = 3 gallons. So they spent 3 * \$5 = \$15 on lemons. The answer is 15.		

Table 4: Examples of responses to the GSM8K dataset by Qwen2.5-7B and DeLTa. The baseline exhibits numerical calculation errors and reasoning mistakes, whereas DeLTa yields more accurate computation results.