Automatic Curriculum Design for Zero-Shot Human-AI Coordination

Won-Sang You¹, Tae-Gwan Ha², Seo-Young Lee¹ and Kyung-Joong Kim¹

¹Department of AI Convergence, Gwangju Institute of Science and Technology, ²School of Integrated Technology, Gwangju Institute of Science and Technology {u.wonsang0514, hataegwan, seoyoung.john}@gm.gist.ac.kr, kjkim@gist.ac.kr

Abstract

Zero-shot human-AI coordination is the training of an ego-agent to coordinate with humans without using human data. Most studies on zeroshot human-AI coordination have focused on enhancing the ego-agent's coordination ability in a given environment without considering the issue of generalization to unseen environments. Realworld applications of zero-shot human-AI coordination should consider unpredictable environmental changes and the varying coordination ability of co-players depending on the environment. Previously, the multi-agent UED (Unsupervised Environment Design) approach has investigated these challenges by jointly considering environmental changes and co-player policy in competitive twoplayer AI-AI scenarios. In this paper, our study extends the multi-agent UED approach to a zeroshot human-AI coordination. We propose a utility function and co-player sampling for a zeroshot human-AI coordination setting that helps train the ego-agent to coordinate with humans more effectively than the previous multi-agent UED approach. The zero-shot human-AI coordination performance was evaluated in the Overcooked-AI environment, using human proxy agents and real humans. Our method outperforms other baseline models and achieves a high human-AI coordination performance in unseen environments.

1 Introduction

Deep reinforcement learning has demonstrated success across diverse domains such as gaming [Silver *et al.*, 2017; Berner *et al.*, 2019; Vinyals *et al.*, 2019], autonomous vehicles [Kiran *et al.*, 2021], and robotic controls [Fang *et al.*, 2019]. Research on deep reinforcement learning has expanded to multiagent reinforcement learning in which multiple agents cooperate or compete to achieve specific objectives [Zhang *et al.*, 2021; Oroojlooy and Hajinezhad, 2023]. Most studies in this field have focused on developing powerful AI beyond human performance through AI-AI interactions. Recently, interest has shifted to problem-solving through human-AI interaction.

Some human-AI interaction studies focus on training the agents that coordinate with humans in common tasks and problem-solving. These studies typically require a large amount of human data for training but it is hard to get enough human data in the real world. To overcome this limitation, the zero-shot human-AI coordination study [Strouse et al., 2021] suggests an approach that trains the ego-agent to coordinate with humans without human data. This approach mainly uses population-based training (PBT) [Strouse et al., 2021; Lupu et al., 2021; Zhao et al., 2023; Lou et al., 2023]. During training, the ego-agent coordinates with various co-player agents within the population pool, instead of a specific coplayer agent. This prevents over-fitting to a specific coordinate strategy and helps generalize across diverse human coordinate strategies. However, these approaches only focus on unseen co-players and do not consider generalization to unseen environments. Real-world applications of human-AI coordination face various unpredictable variables and situations. Therefore, it is essential to train the ego-agent to be robust against both diverse co-players and environments.

The Unsupervised environment design (UED) [Dennis et al., 2020] is a method that selectively curates the environment to the agent by using a curriculum based on a given utility function. It curates increasingly difficult environments based on the current agent's policy. This approach allows the agent to develop the ability to generalize across all possible environments by facing diverse and challenging scenarios. These methods [Jiang et al., 2021a; Jiang et al., 2021b; Parker-Holder et al., 2022] mainly use a regret as a utility function. Recently, UED methods have been extended to competitive multi-agent settings [Samvelyan et al., 2023]. In a multi-agent setting, the co-player policy varies depending on the environment, so the multi-agent UED curates joint environment/co-player pair to the agent. This approach has successfully trained the robust agent across diverse environments and co-players. By extending this method to the zeroshot human-AI coordination setting, we could be able to train a robust agent that can coordinate with real humans across diverse environments.

However, there are main problems with extending multiagent UED methods to zero-shot human-AI coordination settings. The regret-based utility function and co-player sampling used in previous multi-agent UED approaches are unsuitable for these settings. These methods are designed for



Figure 1: **Overview of the proposed method.** The ego-agent is trained using a population of co-players whose individual environment buffers maintain a fixed size of K, containing the environments with the lowest coordination scores. Our approach samples the co-player based on their coordination scores within the population. Depending on the replay decision, the environment is either sampled from unseen environment buffer or from the co-player's buffer guided by a replay distribution that prioritizes the sampling of environments based on coordination scores. After sampling, our method calculates a return from the episode trajectory within the sampled environment which is utilized to compute the coordination score. This coordination score is then updated within the co-player's buffer.

zero-sum games and focus on minimizing the agent's regret to find a minimax strategy. In coordination settings, agents need to collaborate to achieve shared goals rather than minimize regret. Thus, the regret-based utility function and coplayer sampling conflict with the objectives of coordination settings.

To address these problem, we introduce the automatic curriculum design for zero-shot human-AI coordination. We adopt a return-based utility function and co-player sampling for zero-shot human-AI coordination. The return measures the coordination ability of the ego-agent with the co-players. It guides the agent to get better coordination strategies even in challenging scenarios and co-players.

The contributions of our study are the following: (1) We propose the multi-agent UED framework for zero-shot human-AI coordination by using a return-based utility function and co-player sampling. (2) We show that our method demonstrates higher coordination performance with human proxy agents and real human partners compared to other baselines. Figure 1 shows an overview of our proposed method.

2 Related Works

2.1 Unsupervised Environment Design Strategies

The Unsupervised Environment Design (UED) is a method in which the teacher curates a curriculum to enable the student agent to generalize across all possible levels of the environment based on a utility function. The simplest version of UED teacher uses the utility function as a constant C for uniformly random sampling the level of environment $U_t(\pi, \theta) =$ C. Here, t is the teacher, π is the student's policy, θ is the environment level parameter [Jakobi, 1997]. Most UED studies use regret as a teacher's utility function, defined as the difference between the expected return of the current policy and the optimal student policy. Teacher aims to maximize this regret [Dennis *et al.*, 2020; Gur *et al.*, 2021], which can be defined as : $U_t(\pi, \theta) = \max_{\pi^* \in \Pi} \{\text{RegRet}^{\theta}(\pi, \pi^*)\} = \max_{\pi^* \in \Pi} \{V_{\theta}(\pi^*) - V_{\theta}(\pi)\}$, where π^* is the optimal policy on θ , Π is the set of the student policies. This regretbased utility function encourages the teacher to curate challenging environments for the student agent. Through the training process, the student's policy will converge to the minimax regret policy by minimizing the regret in the teacher-curated environment [Dennis *et al.*, 2020]: $\pi \in \arg \min_{\pi \in \Pi} \{\max_{\theta, \pi^* \in \Theta, \Pi} \{\operatorname{RegRet}^{\theta}(\pi, \pi^*)\}\}$ where Θ is the set of environment level parameter. Since the optimal policy π^* cannot be accessed in practice, regret must be approximate.

There are several UED studies on the use of regret. Prioritized Level Replay (PLR) [Jiang *et al.*, 2021b] and Robust PLR [Jiang *et al.*, 2021a] leverage a regret-based utility function to train the agent by selectively sampling environments with high learning potential. ACCEL [Parker-Holder *et al.*, 2022] continuously edits the environment that pushes the boundaries of the student agent's capabilities by combining an evolutionary approach with Robust PLR. MAESTRO [Samvelyan *et al.*, 2023] extends single-agent UED to multi-agent UED in a competitive setting by curating the environment/co-player pairs while considering the environment-dependent co-player policy. In this paper, our method extends the competitive multi-agent UED to a zeroshot human-AI coordination setting using an appropriate utility function.

2.2 Zero-Shot Human-AI Coordination

In multi-agent cooperation tasks, achieving generalization to partner agents is an important problem. Zero-shot coordination [Hu *et al.*, 2020] and ad hoc team cooperation [Stone

et al., 2010] studies aim to address this problem. These approaches commonly rely on the self-play method which is an agent learns through collaboration with its clone. However, self-play methods suffer from limitations. Because they assume the partner agent to be optimal or similar to itself during the training process, its performance is poorly coordinated with unseen partners such as humans or other agents [Carroll *et al.*, 2019].

To address these issues, [Devlin et al., 2011] increase the partner diversity and encourage self-play agents to learn the different strategies. One of these approaches is Population-Based Training (PBT), leveraging the diversity within a population of partner agents. In each iteration, agents are paired with different partners from the population, enabling them to learn various strategies simultaneously. Fictitious Co-Play (FCP) [Strouse et al., 2021] is a well-known PBT-based approach. It uses the population of past checkpoint self-play agents as a partner to train the ego-agent. Trajectory Diversity (TrajeDi) [Lupu et al., 2021] enhanced performance in cooperative tasks by generating diverse policies within the population. It used the Jensen-Shannon divergence to measure the diversity between different policies. Additionally, MEP [Zhao et al., 2023] was proposed to mitigate potential issues arising from shifts in the distribution of self-play agents during interactions with unseen partners. In this study, we construct a population of co-player agents trained in various environments. Through this approach, we aim to address the poor coordination of human partners with unseen environments.

3 Automatic Curriculum Design For Zero-Shot Human-AI Coordination

3.1 Overview

In this section, we describe our proposed method, Automatic Curriculum Design for Zero-Shot Human-AI Coordination, which is an auto curriculum that trains the egoagent using return-based utility functions. Our method focuses on training the ego-agent to coordinate well with human partners in diverse environments, and it is based on the multi-agent UED approach [Samvelyan *et al.*, 2023]. It curates environment/co-player pairs with learning potential in Human-AI coordination to the ego-agent.

The training procedure of our proposed method is as shown in Algorithm 1. It begins by sampling the co-player π' agent that coordinates with the ego-agent from the co-player population during the training. This sampling is based on coordination performance (return), as described in Section 3.2. In the first epoch, the ego-agent coordinates with itself in the self-play method without sampling the co-player. After co-player sampling, our method employs a Replay-decision based on a Bernoulli distribution. This decision process determines whether to sample an environment θ from the coplayer's environment buffer or an unseen random environment θ from the finite set of training environments. When an environment is sampled from the co-player's environment buffer, our method follows the replay distribution given by Equation (1), which is based on the return. It then collects the trajectories from the ego-agent and the sampled

Algorithm 1 Automatic Curriculum Design for Zero-Shot			
Human-AI Coordination			
Input: Training environments Λ_{train}			
Initialise: Ego policy π , Co-player population \mathfrak{B}			
Initialise: Co-player Env buffers $\forall \pi' \in \mathfrak{B}, \mathbf{\Lambda}(\pi') := \emptyset$			
1: for $i = \{1, 2,\}$ do			
2: for N episodes do			
3: $\pi' \sim \mathfrak{B}$ \triangleright Sample co-player via Eq.2			
4: Sample <i>Replay-decision</i>			
5: if replaying then			
6: $\theta \sim \mathbf{\Lambda}(\pi') \triangleright$ Sample a replay env with dist.1			
7: Collect trajectory τ of π using (θ, π')			
8: Update π with rewards $\boldsymbol{R}(\tau)$			
9: else			
10: $\theta \sim \Lambda_{unseen/train} \triangleright$ Sample unseen random env			
11: Collect trajectory τ of π using (θ, π')			
12: end if			
13: Compute Coordination score $S = Return(\theta, \pi')$			
14: Update $\Lambda(\pi')$ with θ using score S			
15: end for			
16: $\mathfrak{B} \leftarrow \mathfrak{B} \cup \{\pi_i^{\perp}\}, \Lambda(\pi_i^{\perp}) := \emptyset$ \triangleright frozen weights			
17: end for			

environment/co-player pairs. The ego-agent's policy is updated whenever an environment is sampled from the coplayer's environment buffer. Coordination scores are calculated with collected trajectories and updated to the individual environment buffer of the sampled co-player accordingly. After N episodes training, the ego agent's frozen weight policy is added to the co-player population \mathfrak{B} with the environment buffer.

$$P_{\text{replay}} = (1 - \rho) \cdot P_S + \rho \cdot P_C \tag{1}$$

The replay distribution is a combination of two distributions: (P_S) , based on the learning potential score, which is measured using the return. (P_C) , based on how long each environment was sampled from the environment buffer, as detailed in the previous study [Jiang *et al.*, 2021b]. The staleness coefficient $\rho \in [0, 1]$ For more details on P_S , see Section 3.3.

3.2 Prioritized Co-player Sampling

The multiagent UED study for two-player zero-sum games [Samvelyan et al., 2023] prioritized sampling the co-player with the highest-regret environment in their buffer and focused on minimizing regret to obtain a minimax regret policy. However, it is hard to apply directly to the Human-AI coordination (common pay-off game) setting. The egoagent needs to learn a policy that not only minimizes regret but also considers the reward from coordination interaction, since the ego and the co-player agent receive the common reward together. We need to set the co-player sampling metric by considering the coordination for Human-AI coordination. Most Human-AI coordination studies [Zhao et al., 2023; Lou et al., 2023] typically use return as a co-player sampling metric. They sample the co-players who have a low return on a task, which means are hard to coordinate with. Because it optimizes the lower bound of coordination performance with



Figure 2: Evaluation Layouts. The evaluation layouts were selected based on a previous study [Yang *et al.*, 2022]. These layouts are selected to cover a range of difficulties, from easy $(test_0)$ to difficult $(test_4)$. The selection of layouts was based on rewards, to gain insight into the human-AI coordination performance across different difficulty levels. Easier layouts allow agents to work independently within separate areas, whereas harder layouts require coordination with other agents without collisions.

any co-player in the population, ensuring that the ego-agent can coordinate well with various co-players and human players [Zhao *et al.*, 2023]. We propose methods that prioritize the sampling of the co-player with the lowest-return environment in their buffer. It is different from previous Human-AI coordination co-player sampling by considering the environment jointly. Each co-player environment buffer has a fixed *k*size and it is stored based on the lowest return environments.

CO-PLAYER
$$\in \arg\min_{\pi'\in\mathfrak{B}}\left\{\min_{\theta\in\mathbf{A}(\pi')}Return(\theta,\pi')\right\}$$
 (2)

Here, \mathfrak{B} is the co-player population, $\Lambda(\pi')$ is the environment buffer of co-player agent π' , and $Return(\theta, \pi')$ is the return of the environment/co-player pairs (θ, π') .

3.3 Learning Potential Score Based on Return

Our method follows the replay distribution (1) when selecting an environment for the ego-agent from the individual coplayer buffer. P_S is the first prioritization distribution in the replay distribution (1) and it assigns higher priority to environments with learning potential to train the ego-agent. Return is the appropriate scoring metric to construct a prioritization distribution in human-AI coordination. It represents the coordination performance during the episode and indicates which environment requires more training. If the replayed environment has a low return, it indicates that the ego-agent is hard to coordinate in that environment. The details of S are as follows :

$$S_i = \frac{1}{T} \sum_{t=0}^{T} \operatorname{Return}_t(\theta_i, \pi')$$
(3)

$$P_{S}(\theta_{i}|S) = \frac{\operatorname{rank}\left(S_{i}\right)^{\frac{1}{\beta}}}{\sum_{i}\operatorname{rank}\left(S_{j}\right)^{\frac{1}{\beta}}}$$
(4)

Equation (3) is the expected return of the replayed environment with the sampled co-player during the episode. Here, Trepresents the total number of timesteps in the episode, and *i* denotes the index of the replayed environment from the coplayer's buffer. This environment score is normalized using Equation (4). We normalized the scores using a rank-based prioritization which sorts the scores in the co-player buffer in ascending order prioritizing the low-return environment. *j* denotes the index of environments in the co-player's buffer. $\beta \in [0, 1]$ is the range of values for the temperature parameter that adjusts the influence of a distribution.

4 Experiments Setup

Overcooked-AI [Carroll *et al.*, 2019] is a cooperative game played in a kitchen-inspired grid world environment. The main goal is to cook as much food as possible in a limited time. Agents can get rewards through completing the task sequentially such as ingredient preparation, cooking, and serving on plates. Cooperation is essential in this environment, where success or failure depends on the effectiveness of player coordination with their partner.

Baseline Model. We compare our method against three key baseline models related to UED: MAESTRO [Samvelyan *et al.*, 2023], Robust PLR [Jiang *et al.*, 2021b], and Domain Randomization [Jakobi, 1997]. Robust PLR and domain randomization are methods originally used in a single-agent setting, we modified them for the multi-agent setting using the self-play method. The ego-agent was trained using the PPO method [Schulman *et al.*, 2017], which is well-known for training reinforcement learning agents. The model architecture and hyperparameter choices are in Appendix A.

Layout Generation. In our experiments, we automatically generated a total of 6,000 different layouts for Overcooked-AI, each layout size was 7×5 . These layouts were generated using a heuristic-driven layout generator capable of adjusting three layout parameters: the number of interactive blocks (such as pots, plates, outlets, and onions), the number of spaces, and the size of layouts, which is fixed in this study. The generator was designed to ensure that each layout included at least 12 spaces and 5 interactive blocks. To prevent redundancy, the layout generator compared the layout array during generation. Additionally, check the layout solvability using the A* path-finding algorithm [Hart *et al.*, 1968], which can find the path for agent access to any interactive block. Further details on the algorithm are provided in Appendix B.

Human Proxy. To evaluate the coordination performance with the trained agent in our experiments, we utilized a human proxy agent from a previous study [Yang *et al.*, 2022] as a co-player agent. This human proxy agent performs as human-like as possible by adjusting its parameters based on human data using the cross-entropy methods.



Figure 3: (a) Overall results with a human proxy model. Our method achieves higher coordinate performance with the human proxy agent than other baselines on all five evaluation layouts (Mean and standard error were computed over 100 runs with three random seeds). (b) Utility function analysis (*Regret vs Return*). Using a return-based utility function has an advantage to train ego-agent than the regret-base utility function in multi-agent coordination settings (Mean and standard error were computed over 100 runs with three random seeds).



Figure 4: Learning curves for the training, training-evaluation and evaluation phases. The solid line shows the average episode reward for the different three random seeds, while the shaded areas show the maximum and minimum rewards. The results show that our model achieves higher performance in both the training and evaluation layouts.

Evaluation. We evaluated the human-AI zero-shot coordination performance on five unseen layouts (Figure 2), selected based on coordination difficulty. This helps to measure the adaptability of the ego-agent based on the difficulty of the layout. In addition, we conducted a utility function analysis.

5 Experiments Result

5.1 Experiments With Human Proxy

Overall Result. Figure 3(a) shows the comparison result of our method and the baseline models (MAESTRO, Robust PLR, and Domain Randomization) regarding the coordination performance with a human proxy agent on unseen layouts. The bar graph is the evaluation result, which is the average episode reward (three random seeds) with the human proxy agent on the evaluation layouts. As a result, our method showed a better performance on all five evaluation layouts compared to other baselines. We observe that our method achieves a higher generalization coordination performance with unseen partners in unseen evaluation layouts. Furthermore, we also conducted cross-play experiments, where our method outperformed other baselines in unseen evaluation layouts. The results of these experiments are provided in Appendix C.

5.2 Study of the Utility Function

Evaluation Result. We had an analysis to try to figure out which utility functions are appropriate for a Human-AI coordination setting. Figure 3(b) shows how the utility function affects the training of the ego-agent. Our method and Robust PLR improved coordination performance with the human proxy agent in all five evaluation layouts by setting the return as the utility function instead of regret.

In this experiment, return is a more appropriate utility function than regret in Human-AI coordination settings. The regret utility is not suitable for curating challenging environments that do not coordinate well with the environment buffer. Regret quantifies the opportunity cost of not making the optimal decision without considering coordination. Therefore, it is difficult to evaluate the effectiveness of coordination performance using regret. However, return is appropriate for evaluating the effectiveness of coordination performance because it is derived from the common rewards that agents receive through their collaborative efforts to achieve a common goal.

Learning Curve. Figure 4(a) shows the learning curves of our method and MAESTRO during training. By comparing these learning curves, we evaluate which utility function is more effective for training the ego-agent in Human-AI co-ordination. MAESTRO shows a high episode reward in the



(a) Human Study Result.

(b) Human Survey Result.

Figure 5: This plot shows the results of an experiment with 20 real humans: (a) The average reward obtained from the five unseen evaluation layouts (b) The average evaluation scores for the two items "Collaborativeness" and "Human Preference". Each subject was scored on a scale of 1 to 4 based on their voting ranking. A higher score indicates a more positive evaluation.

early training stage due to overfitting easy difficulty environments but high fluctuation when it encounters relatively less seen environments. On the other hand, our method steadily increases episode rewards by sampling more difficult environments according to the agent's coordination ability. Appendix D demonstrates how the buffer composition of each method player changes as training progresses. Figure 4(b) illustrates the coordination performance of the ego-agent with the human proxy agent on randomly selected layouts from the training set at each training step. Meanwhile, Figure 4(c)shows the evaluation graph of the ego-agent coordination performance with the human proxy agent in the evaluation layouts. The use of return as the utility function leads to an increase in episode reward, whereas regret does not. This suggests that ego-agents trained with a return-based approach achieve more effective coordination with the human proxy agent.

5.3 Human-AI coordination

Human Study Result. Additionally, we conducted a human study to evaluate coordination with real humans. We recruited 20 participants from the local student community and evaluated the proposed method and the baseline models with our participants. Figure 5 shows the average coordination performance of five evaluation layouts in the human study. Our method outperformed the baseline models on all layouts ($test_0$, $test_1$, $test_2$, $test_3$) except for the hardest layout($test_4$). These results suggest that our method was robust to the unseen environment and diverse human partners.

Human Survey Result. For each session of the experiment, the the participants ranked the models in terms of collaborativeness (the most collaborative partner) and human preference (their top preference). The scores of the human evaluations in Figure 5 (b) were converted to a scale of 1 to 4 based on each participant's subjective ranking of the models. A higher score indicates a better evaluation. The plot shows that our method has higher collaborativeness and human preference compared to the baseline model. Participants rated the agent trained with our method as more cooperative and preferred them for coordination over baseline models. The collaborativeness and human preference scores for each layout

are provided in Appendix E.

6 Conclusion

Summary. In this paper, we propose an Automatic Curriculum Design for zero-shot Human-AI coordination. Our method extends the multi-agent Unsupervised Environment Design (UED) approach to zero-shot Human-AI coordination, which trains the ego-agent to coordinate with human partners in unseen environments. We use return as a utility function, unlike previous multi-agent UED methods that use regret. Our method outperformed against other baselines when evaluated with a human proxy in an Overcooked AI. The ablation studies demonstrate the effectiveness of the proposed components. Finally, we had a real human experiment to evaluate the human-AI coordination outperforms our method. The result of human-AI coordination outperforms our method compared to other baselines.

Limitation and Future Work. When using the return as a measure of the learning potential of the environment/coplayer pair, the evaluation performance improved compared to the previous method regret. However, prioritizing environments with low returns leads to the issue of sampling environment/co-player pair that are too challenging for the agent to learn effectively. In the future, we plan to introduce an alternative metric to promote the sampling of learnable environment-co-player pairs for Human-AI coordination [Rutherford *et al.*, 2025]. We will also use mutation to adjust the environment that is sampled repeatedly to prevent overfitting the specific environments [Parker-Holder *et al.*, 2022; Wang *et al.*, 2020].

In the current Multi-agent UED, the co-player pool is constructed from the past frozen weights of trained ego agents. This approach mitigates the non-stationarity problem compared to the self-play approach, which the co-player policy is changed during the training. However, since it essentially plays with the past of itself, it fails to train diverse strategies. We plan to study about how to increase the diversity of the co-player pool in UED.

References

- [Berner et al., 2019] Christopher Berner, Greg Brockman, Brooke Chan, Vicki Cheung, Przemysław Dębiak, Christy Dennison, David Farhi, Quirin Fischer, Shariq Hashme, Chris Hesse, et al. Dota 2 with large scale deep reinforcement learning. arXiv preprint arXiv:1912.06680, 2019.
- [Carroll *et al.*, 2019] Micah Carroll, Rohin Shah, Mark K Ho, Tom Griffiths, Sanjit Seshia, Pieter Abbeel, and Anca Dragan. On the utility of learning about humans for human-ai coordination. *Advances in neural information processing systems*, 32, 2019.
- [Dennis *et al.*, 2020] Michael Dennis, Natasha Jaques, Eugene Vinitsky, Alexandre Bayen, Stuart Russell, Andrew Critch, and Sergey Levine. Emergent complexity and zero-shot transfer via unsupervised environment design. *Advances in neural information processing systems*, 33:13049–13061, 2020.
- [Devlin *et al.*, 2011] Sam Devlin, Daniel Kudenko, and Marek Grześ. An empirical study of potential-based reward shaping and advice in complex, multi-agent systems. *Advances in Complex Systems*, 14(02):251–278, 2011.
- [Fang *et al.*, 2019] Meng Fang, Tianyi Zhou, Yali Du, Lei Han, and Zhengyou Zhang. Curriculum-guided hindsight experience replay. *Advances in neural information processing systems*, 32, 2019.
- [Gur et al., 2021] Izzeddin Gur, Natasha Jaques, Yingjie Miao, Jongwook Choi, Manoj Tiwari, Honglak Lee, and Aleksandra Faust. Environment generation for zero-shot compositional reinforcement learning. *Advances in Neural Information Processing Systems*, 34:4157–4169, 2021.
- [Hart et al., 1968] Peter E Hart, Nils J Nilsson, and Bertram Raphael. A formal basis for the heuristic determination of minimum cost paths. *IEEE transactions on Systems Sci*ence and Cybernetics, 4(2):100–107, 1968.
- [Hu et al., 2020] Hengyuan Hu, Adam Lerer, Alex Peysakhovich, and Jakob Foerster. "other-play" for zero-shot coordination. In *International Conference on Machine Learning*, pages 4399–4410. PMLR, 2020.
- [Jakobi, 1997] Nick Jakobi. Evolutionary robotics and the radical envelope-of-noise hypothesis. *Adaptive behavior*, 6(2):325–368, 1997.
- [Jiang et al., 2021a] Minqi Jiang, Michael Dennis, Jack Parker-Holder, Jakob Foerster, Edward Grefenstette, and Tim Rocktäschel. Replay-guided adversarial environment design. Advances in Neural Information Processing Systems, 34:1884–1897, 2021.
- [Jiang et al., 2021b] Minqi Jiang, Edward Grefenstette, and Tim Rocktäschel. Prioritized level replay. In *International Conference on Machine Learning*, pages 4940– 4950. PMLR, 2021.
- [Kiran et al., 2021] B Ravi Kiran, Ibrahim Sobh, Victor Talpaert, Patrick Mannion, Ahmad A Al Sallab, Senthil Yogamani, and Patrick Pérez. Deep reinforcement learning for autonomous driving: A survey. *IEEE Transactions on Intelligent Transportation Systems*, 23(6):4909–4926, 2021.

- [Lou et al., 2023] Xingzhou Lou, Jiaxian Guo, Junge Zhang, Jun Wang, Kaiqi Huang, and Yali Du. Pecan: Leveraging policy ensemble for context-aware zero-shot human-ai coordination. In Proceedings of the 2023 International Conference on Autonomous Agents and Multiagent Systems, pages 679–688, 2023.
- [Lupu *et al.*, 2021] Andrei Lupu, Brandon Cui, Hengyuan Hu, and Jakob Foerster. Trajectory diversity for zero-shot coordination. In *International conference on machine learning*, pages 7204–7213. PMLR, 2021.
- [Oroojlooy and Hajinezhad, 2023] Afshin Oroojlooy and Davood Hajinezhad. A review of cooperative multi-agent deep reinforcement learning. *Applied Intelligence*, 53(11):13677–13722, 2023.
- [Parker-Holder *et al.*, 2022] Jack Parker-Holder, Minqi Jiang, Michael Dennis, Mikayel Samvelyan, Jakob Foerster, Edward Grefenstette, and Tim Rocktäschel. Evolving curricula with regret-based environment design. In *International Conference on Machine Learning*, pages 17473–17498. PMLR, 2022.
- [Rutherford *et al.*, 2025] Alexander Rutherford, Michael Beukman, Timon Willi, Bruno Lacerda, Nick Hawes, and Jakob Foerster. No regrets: Investigating and improving regret approximations for curriculum discovery. *Advances in Neural Information Processing Systems*, 37:16071–16101, 2025.
- [Samvelyan et al., 2023] Mikayel Samvelyan, Akbir Khan, Michael D Dennis, Minqi Jiang, Jack Parker-Holder, Jakob Nicolaus Foerster, Roberta Raileanu, and Tim Rocktäschel. MAESTRO: Open-ended environment design for multi-agent reinforcement learning. In *The Eleventh Inter*national Conference on Learning Representations, 2023.
- [Schulman *et al.*, 2017] John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.
- [Silver *et al.*, 2017] David Silver, Thomas Hubert, Julian Schrittwieser, Ioannis Antonoglou, Matthew Lai, Arthur Guez, Marc Lanctot, Laurent Sifre, Dharshan Kumaran, Thore Graepel, et al. Mastering chess and shogi by self-play with a general reinforcement learning algorithm. *arXiv preprint arXiv:1712.01815*, 2017.
- [Stone et al., 2010] Peter Stone, Gal Kaminka, Sarit Kraus, and Jeffrey Rosenschein. Ad hoc autonomous agent teams: Collaboration without pre-coordination. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 24, pages 1504–1509, 2010.
- [Strouse *et al.*, 2021] DJ Strouse, Kevin McKee, Matt Botvinick, Edward Hughes, and Richard Everett. Collaborating with humans without human data. *Advances in Neural Information Processing Systems*, 34:14502–14515, 2021.
- [Vinyals et al., 2019] Oriol Vinyals, Igor Babuschkin, Junyoung Chung, Michael Mathieu, Max Jaderberg, Wojciech M Czarnecki, Andrew Dudzik, Aja Huang, Petko

Georgiev, Richard Powell, et al. Alphastar: Mastering the real-time strategy game starcraft ii. *DeepMind blog*, 2:20, 2019.

- [Wang et al., 2020] Rui Wang, Joel Lehman, Aditya Rawal, Jiale Zhi, Yulun Li, Jeffrey Clune, and Kenneth Stanley. Enhanced poet: Open-ended reinforcement learning through unbounded invention of learning challenges and their solutions. In *International Conference on Machine Learning*, pages 9940–9951. PMLR, 2020.
- [Yang *et al.*, 2022] Mesut Yang, Micah Carroll, and Anca Dragan. Optimal behavior prior: Data-efficient human models for improved human-ai collaboration. *arXiv* preprint arXiv:2211.01602, 2022.
- [Zhang *et al.*, 2021] Kaiqing Zhang, Zhuoran Yang, and Tamer Başar. Multi-agent reinforcement learning: A selective overview of theories and algorithms. *Handbook of reinforcement learning and control*, pages 321–384, 2021.
- [Zhao et al., 2023] Rui Zhao, Jinming Song, Yufeng Yuan, Haifeng Hu, Yang Gao, Yi Wu, Zhongqian Sun, and Wei Yang. Maximum entropy population-based training for zero-shot human-ai coordination. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 37, pages 6145–6153, 2023.

Implementation Details and Hyperparameters. А

Our implementation is based on PLR [Jiang et al., 2021b] and the Overcooked environment [Carroll et al., 2019]. In all experiments, we train the ego agent using the PPO method [Schulman et al., 2017]. The details of the network architecture and hyperparameter choices are provided in Table 1 and Table 2, respectively. Additionally, we discuss our hyperparameter selections in Section 4. Table 3 presents the final hyperparameter choices for all methods.

Table 1: Network architecture details

Layers	Channels	Kernel Size
Conv2D + LeakyReLU	25	5×5
Conv2D + LeakyReLU	25	3×3
Conv2D + LeakyReLU	25	3×3
Flatten	/	/
$(FC + LeakyReLU) \times 3$	64	/
FC	6	/

Layers	Channels	Kernel Size
Conv2D + LeakyReLU	25	5×5
Conv2D + LeakyReLU	25	3×3
Conv2D + LeakyReLU	25	3×3
Flatten	/	/
$(FC + LeakyReLU) \times 3$	64	/
FC	6	/

Parameter	Value
РРО	
λ_{GAE}	0.98
γ	0.99
Number of epochs	8
Rollout Length	400
PPO clip range	0.05
RMSprop optimizer (ϵ)	0.00001
Learning rate	0.001
Value loss coefficient	0.1
Entropy Coefficient	0.1
Number of mini-batches	20
Minibatch size	5000

Table 2: PPO	agent hyperparameters
--------------	-----------------------

Parameter	Value	
Robust PLR		
Replay rate, p	0.5	
Buffer size, K	4,000	
Scoring function	Positive value loss	
Prioritization	rank	
Temperature, β	0.3	
Staleness coefficient, ρ	0.3	
MAESTRO		
$\lambda \operatorname{coef}$	0.2	
Buffer size of co-player, K	1,000	
Scoring function	Positive value loss	
Prioritization	rank	
Population size, <i>i</i>	8	
Episodes N	375	
Our		
$\lambda \operatorname{coef}$	0.2	
Buffer size of co-player, K	1,000	
Scoring function	return	
Prioritization	reverse-rank	
Population size, <i>i</i>	8	
Episodes N	375	

Table 3: Training hyperparameters for each method

Overcooked. To evaluate the improvement of zero-shot human-AI coordination performance in unseen environments, we experiment in the Overcooked environment, where players can cook and serve the food. The environment has interactive blocks such as onions, plates, pots, and outlets, wall blocks that agents cannot move through, and space blocks that agents can move through. To get a reward from the environment, each player picks up 3 onions (3 reward) and puts them in the pot (3 reward). After 20 seconds, the onion soup is ready, take a plate to serve the onion soup (5 reward). They then submit the dish to the outlets. Finally, all players get a common reward of 20. This reward shaping is based on a previous Overcooked benchmark paper [Carroll *et al.*, 2019].

B Layout Generator.

Algo	Algorithm 2 Layout generation process		
Inpu	input: Maximum size of layout buffer M , Number of interactive blocks N , Number of empty space E		
Initi	initialise: Layout buffer L		
1: •	while Size of layout buffer $< M$ do		
2:	Make random 7×5 array as a Layout		
3:	Randomly place N blocks		
4:	if Duplicate(Layout, L) then		
5:	Continue		
6:	end if		
7:	Place two players in a random position		
8:	Remove non-reachable blocks		
9:	if Sovability(Layout) then		
10:	Append Layout to L		
11:	end if		

12: end while

Algorithm 2 shows the overall layout generation process. A layout generator is a heuristic-driven tool whose input consists of three parameters: The maximum size of the layout buffer M, the number of interactive blocks N, and the number of empty spaces E. The generator ensures the presence of a minimum of E spaces and N interactive blocks within each map. The location of the block in the layout is selected randomly. In this experiment, we set the parameters as M=6,000, N= 6 ~ 9, and E=14. During the layout generation process, the generator checks the Hamming distance between embedded arrays to

eliminate any redundancy. In addition, the solvability of each layout is checked using the A* path-finding algorithm [Hart *et al.*, 1968], which checks whether or not the agent can reach each interactive block.



C Cross-Play Results.

Figure 6: AI-AI Cross-play result This result is the normalized value of the reward obtained by cross-playing the trained model on five evaluation layouts and their average.

Figure 6 represents the detailed results of experiments with AI-AI cross-play on the five evaluation layouts. This is a zero-shot coordination experiment in which different models are coordinated without direct encounters with others during the training phase. These scores are normalized relative to the highest reward obtained from that layout, with the maximum value set at 1 and the minimum value set to 0. our method performs better than the baselines in the other five evaluation layouts. The final mean graph shows the average value of the normalized scores for the five layouts. Our method also outperforms the baseline in self-play that each method plays itself and in cross-play that each method plays against different methods.

PLR and MAESTRO use a regret-based utility function, which is not suitable for cooperative environments, resulting in a worse performance than the Random method. In contrast, our method improves the lower bound of the performance by using a return-based utility function. This approach curates challenging environment/co-player pairs to the ego-agent. Our trained ego-agent generally performs well in easy-to-hard environments and is robust to unseen environments and co-players.

D Co-player's buffer analysis.

Difficulty	Reward Condition
Very Easy	$reward > \mu + 1.5\sigma$
Easy	$\mu + 0.5\sigma < reward \le \mu + 1.5\sigma$
Medium	$\mu - 0.5\sigma < reward \le \mu + 0.5\sigma$
Hard	$\mu - 1.5\sigma < reward \le \mu - 0.5\sigma$
Very Hard	$reward \le \mu - 1.5\sigma$

Table 4: Difficulty classification based on reward conditions

Define training layouts difficulty. To categorize the difficulty of the layouts, we obtained the average reward (50 runs) evaluated from the trained agent and the human proxy agent. Figure 7(a) shows the distribution of average rewards obtained from the 6,000 layouts used for training. We apply the criteria outlined in Table 4, categorizing the difficulty levels into five groups, from 'Very Hard' to 'Very Easy', based on the mean and standard deviation. According to this classification scheme, the





(b) Layout difficulty composition in the co-player's buffer



(c) Changing the layout difficulty composition of buffers

Figure 7: (a) Distribution of rewards obtained by the trained model on the training layout, playing with a human proxy. Difficulty is categorized based on these reward distributions. (b) Difficulty distribution of layouts sampled during the training process for the Our/MAESTRO method. (c) Difficulty configuration of the buffer changes as training progresses.

layouts classified as 'Medium' are the most numerous, while those classified as 'Very Hard' or 'Very Easy' are comparatively rare.

Co-player's buffer Composition. Figure 7(b) shows the cumulative composition of layout difficulties in the environment buffer of the co-player, which is first added to the co-player population during the training process. Both our method and MAESTRO prioritize layout(environment) sampling and store layouts in the co-player buffer of size 1,000 according to their own criteria. In our method, the percentage of 'Very Hard' layouts in the co-player buffer increases as training progresses from start to finish. This indicates that our method samples the more difficult layouts as the agent's performance improves, similar to curriculum learning. However, MAESTRO was likely to sample easier environments as training progress, so the percentage of 'easy' layouts in the co-player buffer increased. Figure7(c) represents details of the changing layouts from the co-player's buffer. These results support the idea that the return-based utility function is more appropriate than the regret-based utility function to assess learning potential in the coordination setting.

E Additional human study analysis.



Figure 8: Human survey results by test layouts Results from a survey of 20 human players on five evaluation layouts. In the layouts of $test_0, test_1, test_2$, and $test_3$, human players tended to prefer our model, but in the hardest layout of $test_4$, the human player had different preferences, and each model scored similarly.