Can Memory-Augmented Language Models Generalize on Reasoning-in-a-Haystack Tasks?

Payel Das^{*1} Ching-Yun Ko^{*1} Sihui Dai^{*12} Georgios Kollias¹ Subhajit Chaudhury¹ Aurelie Lozano¹

Abstract

Large language models often expose their brittleness in reasoning tasks, especially while executing long chains of reasoning over context. We propose MemReasoner, a new and simple memory-augmented LLM architecture, in which the memory learns the relative order of facts in context, and enables hopping over them, while the decoder selectively attends to the memory. Mem-Reasoner is trained end-to-end, with optional supporting fact supervision of varying degrees. We train MemReasoner, along with existing memoryaugmented transformer models and a state-space model, on two distinct synthetic multi-hop reasoning tasks. Experiments performed under a variety of challenging scenarios, including the presence of long distractor text or target answer changes in test set, show strong generalization of Mem-Reasoner on both single- and two-hop tasks. This generalization of MemReasoner is achieved using none-to-weak supporting fact supervision (using none and 1% of supporting facts for one- and twohop tasks, respectively). In contrast, baseline models overall struggle to generalize and benefit far less from using full supporting fact supervision. The results highlight the importance of explicit memory mechanisms, combined with additional weak supervision, for improving large language model's context processing ability toward reasoning tasks.

1. Introduction

Transformer-based large language models (LLMs) have recently shown impressive performance in many natural language processing (NLP) tasks, including machine translation, question answering, and reading comprehension, demonstrating the signature of general reasoning abilities. Despite these achievements, LLMs often fail to generate accurate information with respect to the context and are prone to hallucinations. Perhaps surprisingly, such hallucinations are found even on simple tasks that require some form of reasoning over the context. Oftentimes, irrespective of the specific type of reasoning involved, LLM hallucinations occur from failure to resolve a dependency chain over the input, rather than memorizing the exact training sequence. This issue of incorrectly modeling long-range dependency and reasoning has been reported for a variety of tasks including logical reasoning (Levy et al., 2024; Kuratov et al., 2024; Wan et al., 2024) and algorithmic reasoning (Liu et al., 2023b;a).

In this work, we provide a novel language model architecture that is designed to naturally handle iterative processing over the context to learn long-range dependencies. We refer to this model as MemReasoner, which is a memoryaugmented language model enhanced with two basic operations: (i) explicit learning of temporal orders of facts/events present within the context, and (ii) a mechanism for iteratively reading from the context and updating the query accordingly. We further explore benefits of utilizing noneto-weak supporting fact supervision (along with final answer supervision) during model training.

Multiple synthetic benchmarks (Hsieh et al., 2024; Kuratov et al., 2024; Liu et al., 2023a) have been recently proposed to stress test different language models, which are designed to isolate and probe simple reasoning errors, such as temporal awareness, coreference resolution, fact chaining. These synthetic benchmarks complement well the real-world benchmarks like Long Range Arena (Tay et al., 2020) and Big-Bench (Srivastava et al., 2022) and have been successfully demonstrating existing "reasoning" gap in current language models (Hosseini et al., 2024). We stress test MemReasoner, along with a number of existing baseline transformer-based and alternative language models, on two distinct synthetic tasks that require performing multiple hops over the input to track or bridge over entities. We evaluate how the task-finetuned models generalize to different test scenarios, which involve finding unseen response from the context, resolving the dependency chain over longer context that contains unseen hard or soft distractor text, or a combination of both. We also experiment with a generalization scenario, where a model trained on the two-hop task is tested on a single-hop version but includes longer instances.

^{*}Equal contribution ¹IBM AI Research ²Princeton University (Work done during internship at IBM Research). Correspondence to: Payel Das <daspa@us.ibm.com>.

Our main contributions are:

- A novel memory-augmented LLM architecture, namely MemReasoner, which is trained to execute *temporal processing and iterative read* over the context written to a latent memory module that is separate from the transformer decoder. For this purpose, a positional encoding scheme is proposed to learn the relative order of facts in memory, that helps with selective attention of the transformer decoder to the memory.
- We evaluate the proposed architecture, along with a number of language model baselines with and without a memory, on *two synthetic multi-hop reasoning-in-a-haystack tasks* (1) babi that include 1-hop and 2-hop logical reasoning tasks and (2) variable tracking (VT)- that require tracking entities with 1- and 2-hop connections.
- We subject the task-finetuned models to a variety of challenging generalization scenarios.
- Results show that MemReasoner, when compared to existing recurrent baselines, including a memory-augmented recurrent transformer (RMT) model (Bulatov et al., 2022) and Mamba (Gu & Dao, 2023), a state-space model, *generalize better* in the single hop task setting, where target answer, context length with hard/soft distractors, task complexity, or a combination of thereof, differs from training to test distribution.
- On tasks that require two hops, MemReasoner benefits from additional weak supervision on supporting facts.
 With usage of supporting facts only on 1% of training samples, the proposed model better generalizes to many different test scenarios, when compared to the baselines that utilize 100% of available supporting fact samples.

2. Related Work

Modeling long-range dependency Many tasks require multiple steps to be executed effectively and in the right order, which include, for example, logical and mathematical reasoning and multistep knowledge editing. Current transformer-based LLMs are known to produce erroneous output in those scenarios, possible reasons include learning shortcuts from training data bias (Ju et al., 2024; Ruder, 2021; Mitchell, 2023; Wu et al., 2024; Levy et al., 2024), fragile internal mechanisms like attention glitches (Liu et al., 2023a), and attention sink (Xiao et al., 2024; Liu et al., 2023c), which can be attributed to lack of recurrence in selfattention. At a high level, such failures can be attributed to a lack of "System-2" like thinking mode (Kahneman, 2011), which encourages deliberative and logical thinking steps, in vanilla transformer language models.

To address this limitation, recent works have attempted to include few-shot (Brown et al., 2020; Min et al., 2022) and chain of thought (CoT) prompting (Wei et al., 2022), providing access to external tools/reward models/verifiers (Schick et al., 2023; Khalifa et al., 2023), etc. Augmenting language models with memory modules has been proposed, e.g., in (Nye et al., 2021) the model is asked to output immediate reasoning steps to a "scratchpad" which is then recurrently processed by the model. Another promising research direction is to train the transformer model with an external latent memory module (Das et al., 2024) or with additional learnable memory tokens (Burtsev et al., 2021). Later, architectures that include segment-level recurrent processing over internal memory tokens have been proposed, e.g., Transformer-XL (Dai et al., 2019) and Recurrent Memory Transformer (RMT) (Bulatov et al., 2022). This line of work has shown the ability to process very long input and has emerged as a promising path for modeling long-term dependencies and exploiting memory processing ability for tasks like algorithmic and reasoning.

Structured state space models such as Mamba (Gu & Dao, 2023) have recently emerged as a promising alternative to self-attention layers and transformers for sequence modeling. A differential feature of Mamba is the selection mechanism, i.e., the context-aware ability to focus on or filter out inputs into a fixed-size sequential state. Mamba offers faster inference due to its fixed-memory recurrent architecture, which allows for efficient processing of long sequences. However, this constant-memory also can make the in-context recall ability brittle, compared to transformers (Jelassi et al., 2024; Waleffe et al., 2024; Park et al., 2024).

In MemReasoner, the segment-level processing takes place in the latent memory module, which is further augmented with a recency awareness and iterative read mechanism. This is inspired by the distinction between System 1 and System 2-like thinking (Kahneman, 2011), MemReasoner utilizes the decoder for fast output generation and the memory module for slow processing of the input, which are the two components tightly integrated via training. Generation of intermediate steps in MemReasoner is analogous to CoT method. And, using optional weak supervision on supporting facts in MemReasoner is similar to the line of works that uses rationales for supervised fine-tuning or for preference tuning of LLMs to enhance their reasoning abilities (Zelikman et al., 2022; Pang et al., 2024).

Different from recurrent passing of the global memory tokens from the previous segment to the next segment within the transformer layers themselves, as done in Transformer-XL and RMT, MemReasoner performs multiple hops over the "ordered" segment encodings stored in memory, updates the query accordingly, and provides only the final readout(s) to the decoder. In contrast to "scratchpad" and CoT line of works, MemReasoner does not maintain a memory of explicit (generated) tokens, rather operates over the latent encodings of context stored in memory.

Long-range dependency and reasoning benchmarks

Many datasets and benchmarks have been designed to isolate issues with long-range dependency modeling and generalization. Synthetic tasks have become increasingly popular for testing language models, as those, compared to real-world language datasets, provide a cleaner and more controlled setup for probing the abilities and limitations of transformer-based language models, which is why we evaluate MemReasoner and baselines on two synthetic tasks here (see section 4.1 for details). A number of recent benchmarks include synthetic tasks that require multi-hop processing, e.g., (Hsieh et al., 2024; Kuratov et al., 2024; Li et al., 2024; Liu et al., 2023a). One prevalent direction covered in those benchmarks is generalization to long input length, where long irrelevant (hard) distractor text has been added to the original input to artificially lengthen it. While retrieving a "needle" (a piece of text) from the long context input ("haystack") has been focus of many of the synthetic tasks, more recently, benchmarks have been proposed, which include tasks that require learning long-term dependencies over multi-hop connections, see Figure 4 for example. These benchmarks have become a natural testing ground for many long-context transformer-based LLMs as well as alternative architectures like state-space models (Gu & Dao, 2023). While some experimental settings consider training models, to be tested on those "reasoning"-in-a-haystack tasks, on sequences that include the irrelevant distractors of different lengths, here we focus on generalization from training samples that do not include the distractor text.

We also extend testing model's generalization beyond using long inputs with hard distractors in the following ways: (i) We create a new dataset that contains long input sequences that contain soft distractors. (ii) We include checking generalization to a distribution that contains test samples in which target answer is different from what is seen during training, which can be further combined with input length generalization. (iii) We also consider varying task complexity, i.e., a model trained on a two-hop task is tested on corresponding single-hop task, which again can include longer test sequences with distractors.

3. Multi-step Reasoning with MemReasoner

The key components of MemReasoner involve an LM encoder, an episodic memory module, and an LM decoder (see Figure 1a). The role of the episodic memory module is to enable *write* of the context encodings in the memory, to allow performing search over the context encodings and *read* from them, in order to feed the decoder to execute the task. Given a reasoning task, for which the final answer is available, the MemReasoner architecture is trained to recover the final answer, with or without using the groundtruth supporting fact supervision. An additional point worth mentioning is that, MemReasoner is also trained to learn the relative order of the facts in the context and use that for memory write/read, which can be crucial for explicitly maintaining temporal ordering of context. A search in the latent memory space is performed during training, to correctly output the final answer (and optionally the supporting facts). This imposes a "selection" mechanism over the memory of the context and helps "sharpening" decoder's attention over the fact that matters for correct output generation. Note that, the use of supporting fact supervision is optional: we consider training scenarios involving none-to-full supporting fact supervision with different loss objectives to study the benefits of various degrees of supervision. Details are provided below.

3.1. Using the Larimar Framework as Backbone for MemReasoner

The backbone memory-augmented LLM used in this study is Larimar (Das et al., 2024) (although our approach could in principle be used in conjunction with other LLMs augmented with an additional (episodic) memory module). Let \mathcal{X} be the LM input space, \mathcal{Z} be the latent space, and \mathcal{Y} be the LM output space. Larimar features an encoder e that maps an input to an embedding $z \in \mathcal{Z} \subseteq \mathbb{R}^D$, and a memory module \mathcal{M} . The memory \mathcal{M} is adaptable in the sense, that it allows "write" and "read" operations as episodes (aka, contexts C, where each context is comprised of E sentences) arrive, i.e., $\hat{M} = write(M, z), z_{read} = read(\hat{M}, z)$, wherein \hat{M} is the updated memory after an write. And, a decoder d that performs generations conditioned on the memory readout z_{read} .

Now, suppose one is given an input context C = $\{c_1, ..., c_E\}$ with E denoting the length of the context, and the target task is to answer a question q conditioned on the given context C. To approach the task within the Larimar framework, the input, both context C and query q, are encoded to their latents $(z_1, \ldots, z_E \text{ and } z_q)$ via the encoder e. Next, let M_0 be the initial memory, write the context to the memory via a *write* operation. To do so, Larimar follows the earlier works on Kanerva Machine (Wu et al., 2018), where the memory is viewed as a global latent variable in a generative model. In this framework, the goal is to learn a memory dependent data prior and learnable addresses, where the memory update and read/write are considered as Bayesian inference, i.e., the posterior parameters are updated as new data arrives. (Pham et al., 2022) reformulated the Bayesian updates for encoding new memories and for decoding data from memories into an equivalent minimization problem, which essentially amounts to solving a linear system of equations and can be efficiently done via computing matrix pseudo inverses indicated by † hereafter.

Specifically, memory is updated via the *write* operation such that, $\hat{M} = (Z_{\xi}M_0^{\dagger})^{\dagger}Z_{\xi}$, where $Z_{\xi} = [z_1 + \xi_1, z_2 + \xi_2, \ldots, z_E + \xi_E]$ and $\xi_i \sim \mathcal{N}(0, \sigma_{\xi}^2 I)$. Then, the *read* operation translates the query embedding from the lens of the encoded memory to a query readout z_r via $z_r =$



Figure 1. A diagram of the pipeline for reasoning with MemReasoner. (a) Conceptual overview of the framework. (b) Detailed architecture. q denotes the query, $c_1, ..., c_E$ denotes the context for answering the query. z_q denotes the encoding of the query while $\{z_1, ..., z_E\}$ denote encodings of each line of the context. We use \tilde{z} to denote temporally encoded latents.

 $(z_q \hat{M}^{\dagger} + \eta) \hat{M}$, where $\eta \sim \mathcal{N}(0, \sigma_{\eta}^2 I)$. Lastly, the decoder d decodes the query q conditioned on the readout by using a *learnable* broadcasting matrix of parameters W_M that casts z_r to each decoder layer and obtains h_k^m that serves as the past key values for $k = 1, \ldots, L$, where L is the number of layers in the decoder.

We use the memory-augmented LLM architecture of Larimar and the above operations as the backbone for Mem-Reasoner, due to its memory and space-efficient read/write abilities and demonstrated generalizability at test-time.

However, as such, Larimar's mechanisms are insufficient to handle complex tasks, such as making multi-hop connections over the context. We now introduce key additional features provided in MemReasoner to handle such tasks: (i) explicit learning of temporal orders of facts/events present within the context, and (ii) mechanism for iteratively reading from the context and updating the query accordingly.

3.2. Memory with Temporal Order

In Larimar, the latent encoding of facts $\{z_1, ..., z_E\}$ within a context episode C are written in the memory M in an orderinvariant manner. However, many multi-step reasoning tasks require some notion of temporal context. For example, when answering "where is John?" in the context of "[...] John is in the bathroom. [...] John goes to the garden." ('[...]' denotes irrelevant facts), there should be a mechanism in place to guarantee that the memory encodes the correct temporal order of the facts, and the readout should reflect "John goes to the garden." as the supporting fact instead of "John is in the bathroom.".

To introduce some temporal notion within the context (i.e. facts that appeared later in context are more recent), in Mem-Reasoner we introduce a temporal encoding module \mathcal{P} that transforms *un-ordered* fact latents $\{z_1, ..., z_E\}$ within a context episode to their *ordered* counterparts $\{\tilde{z}_1, ..., \tilde{z}_E\}$. In this paper, we will mainly leverage a learnable bidirectional GRU for temporal encoding, i.e.,

$$\{\tilde{z}_1, ..., \tilde{z}_E\} \leftarrow \text{GRU}(\{z_1, ..., z_E\})$$

This temporal encoding module \mathcal{P} , however, is generic and allows any structure featuring sequentiality within contexts. Additional discussion about this design choice is provided in the Appendix D.5.3. These ordered context embeddings $\{\tilde{z}_1, ..., \tilde{z}_E\}$ are then written to memory via Larimar's *write* operation.

It is worth mentioning that earlier works on memoryaugmented neural nets, which use a recurrent neural net together with an external memory, have investigated ideas like temporal feature learning and iterative hops over context, for example, see (Weston et al., 2014; Sukhbaatar et al., 2015). However, to our knowledge, this is the first study to enable those operations around a latent memory coupled to a transformer-based LLM during training and to test the resulting model's generalizability on long-range dependency learning.

3.3. Iterative Read And Query Update

A typical multi-step reasoning task often inherently requires "hops" between facts until the final solution is found. Additionally, the query embedding can be updated accordingly to reflect the most recent hop.

In order to perform hopping between facts, we first recall the three key components interacting with the memory module \mathcal{M} , the fact embeddings ($\{z_1, \ldots, z_E\}$) within a context episode, the query embedding z_q , and the memory readout z_r . Let us further assume that \mathcal{M} stores facts that have been ordered temporally $\{\tilde{z}_1, \ldots, \tilde{z}_E\}$.

To enable *iterative read*, we pass z_q through a linear layer to obtain $\hat{z}_q = W_q z_q$ before the *read* operation from the memory, where $W_q \in \mathbb{R}^{D \times D}$ is a learnable parameter that absorbs the scale changes introduced by the position encoding in the memory. Specifically, different from Section 3.1, here we have $z_r = (\hat{z}_q \hat{M}^{\dagger} + \eta) \hat{M}$.

To *update the query*, we first update the query latent and let $z_q \leftarrow z_q + \alpha \cdot z_r$, where $\alpha \in \mathbb{R}$ is a hyperparameter to balance the load from the previous readout. The updated query is then fed into the memory module for another *read* operation to obtain a new \tilde{z}_r . The query update procedure is repeated until the readout converges (i.e. $||\tilde{z}_r^t - \tilde{z}_r^{t+1}||_2 < \tau$ where \tilde{z}_r^t denotes the readout at time t and τ is a hyperparameter) or until it reaches a fixed number of maximum iterations.

3.4. Full Workflow

Now that we have discussed all components of MemReasoner, we elaborate the full pipeline in the following and provide a visualization in Figure 1.

Consider an input context $C = \{c_1, ..., c_E\}$, a question q, an encoder e, a temporal encoding module \mathcal{P} , an initial memory module \mathcal{M} , and a decoder d. We first encode the context C and query q to their latents, z_1, \ldots, z_E and z_q , via encoder e. Then, we follow Section 3.2 and transform z_1, \ldots, z_E to $\tilde{z}_1, \ldots, \tilde{z}_E$. Next, we write the ordered context $\tilde{z}_1, ..., \tilde{z}_E$ to the memory and obtain M. Subsequently, we read using the query latent from the memory M and perform query and read updates according to Section 3.3. After we have obtained a \tilde{z}_r as a final readout which does not undergo update anymore, we map \tilde{z}_r to the corresponding unordered encoding in M. This is because we only want the additional position information to be used when locating the most relevant contexts, but not during the decoding - if being fed to the decoder, the decoder may overfit to the ordering information in the latents. We do this by first finding the index of the most similar ordered latent encoding $i = \arg\min_{i \in \{1,...,E\}} ||\tilde{z}_r - \tilde{z}_j||_2$ and then obtaining the corresponding encoding z_i from the unordered encodings (prior to undergoing temporal encoding in Figure 1) $\{z_1...z_E\}$. Lastly, the decoder d decodes the prompt P_a given for answer generation conditioned on z_i . We provide the full pseudocode in Algorithm 1 in the Appendix A.

3.5. Inference-Time Update (IU)

To generalize on long-context tasks with a memoryaugmented LLM, a potential hurdle can come from the two fundamental operations of the memory, write and read, as described in Section 3.1. In both operations, numerical solves of the linear systems involve computing matrix pseudo inverses, which can be unstable when the matrix has many more columns than rows or the other way around. Secondly, encoding the temporal order in very long facts with a GRU can further incur vanishing or exploding gradient.

To cope with these, we further introduce an optional inference-time update (IU) step, where we dynamically filter irrelevant contexts before re-encoding the temporal order and the memory operations. Specifically, with the first pass of memory write and query read, we identify a subset of contexts that are most relevant to the query by their proximity in the ordered latent space $(||\tilde{z}_r - \tilde{z}_j||_2)$. Then, we re-encode the temporal order on this remaining contexts (much shorter) to get their ordered counterparts for the subsequent memory write and query read. This optional update step enables the model to focus on the most relevant information and avoids numerical instabilities. All Mem-Reasoner performance values in the main paper are obtained using IU, unless otherwise stated.

3.6. Training Objectives

Let $\mathcal{D}_{pretrain}$ denote the pretraining data distribution, while $\mathcal{D}_{\text{finetune}}$ denotes the data distribution corresponding to the reasoning task. Each sample from $\mathcal{D}_{\text{finetune}}$ is of the form (q, C, a) where q is the query, $C = \{c_1, ..., c_E\}$ are the facts in the context, and a is the answer. Depending on the availability of supporting fact information in each sample, we let $\mathcal{D}^*_{\text{finetune}}$ be the subset of samples with groundtruth supporting fact, i.e. each sample from $\mathcal{D}_{\text{finetune}}^*$ is of the form (q, C, a, S), where S is a set of indices corresponding to the supporting facts (we will use S_i to denote the *i*th supporting fact index in S). Meanwhile, the pretraining distribution corresponds to a generic corpus, e.g. Wikipedia. Remember, e denotes the encoder, d denotes the decoder, tdenotes temporal encoding, \tilde{z}_r^i denotes the *i*th temporally encoded readout from iterative reading with $\tilde{z}_r^0 = q, z_r^i$ represent the unordered encoding corresponding to the *i*th ordered readout, and P_a denotes the prompts for generating the answer. To train the model, we utilize the following loss function.

$$\begin{split} L &= \rho \underbrace{\mathbb{E}_{x \sim \mathcal{D}_{\text{pretrain}}} \ln p(d(e(x)))}_{\text{autoencoding of pretraining dataset}} \\ &+ \mathbb{E}_{(q,C,S,a) \sim \mathcal{D}_{\text{finetune}}} \underbrace{\mathbb{E}_{z_{r}^{|S|} \sim p(z_{r}^{|S|}|q,M,\tilde{z}_{r}^{0}\dots\tilde{z}_{r}^{|S|-1})} \ln p(a|z_{r}^{|S|},P_{a})}_{\text{reconstruction of answer}} \\ &+ \mathbb{E}_{(q,C,S,a) \sim \mathcal{D}_{\text{finetune}}} \left[\delta \underbrace{\sum_{i=1}^{|S|} \mathbb{E}_{\tilde{z}_{r}^{i} \sim p(\tilde{z}_{r}^{i}|q,M,\tilde{z}_{r}^{0}\dots\tilde{z}_{r}^{i-1})}_{\text{order}(\tilde{z}_{r}^{i},S_{i})} \right]$$

where δ and ρ are hyperparameters controlling regularization strength and ℓ_{order} is given by

$$v(z_r) = \text{softmax}([-||t(e(c_1)) - z_r||_2, ..., -||t(e(c_E)) - z_r||_2]^{\mathsf{T}})$$

$$\ell_{\text{order}}(z_r, s) = -\ln v(z_r)_s$$

In the overall loss L, the first term corresponds to the autoencoding loss on the pretraining dataset. The second term is the reconstruction loss of the answer with respect to the corresponding prompt for obtaining the answer P_a and final readout. Depending on the degree of supporting fact supervision, we further add an optional third loss encouraging

the index of the most similar entry (by 12 distance) to the ordered readout at each iteration to match the index of the supporting fact through computing the cross entropy. We note that $\mathcal{D}_{\text{finetune}}^*$ can be a smaller, as little as 1% of the training set size, subset of $\mathcal{D}_{\text{finetune}}$, covering the realistic scenario when supporting fact supervision is scarce.

4. Experimental Details and Results

4.1. Task Datasets and Data Pre-processing

We utilize two sets of tasks, both of which involve fact chaining by drawing multi-hop connections over the context. Namely, we resort to tasks 1 and 2 from the synthetic bAbi benchmark (Weston et al., 2015), and the Variable Tracking (VT) task from the RULER benchmark (Hsieh et al., 2024).

bAbi Tasks. The bAbi datasets were prepared by synthesizing relations among characters and objects across various locations, each represented as a fact, such as "Mary traveled to the garden". Task 1 requires performing a single hop to find the answer, whereas task 2 requires gathering two supporting facts in the right order (see Fig 4). For preprocessing bAbi data, we treat each training sample comprised of multiple facts as a single context episode, and individual sentence within that context as an instance within that episode. Each fact within an episode contains up to 64 tokens. In our experiments, we consider training models with bAbi task 1 and task 2 data. To evaluate the generalization of these models, we consider harder variants of bAbi:

BABILong. BABILong extends these single and multi-hop tasks to a long context setting (Kuratov et al., 2024) where the difficulty of the task is further varied by changing the length of the irrelevant (PG-19 distributed) text added to the initial bAbi samples. The BABILong leaderboard shows tasks 1 and 2, while simple, are challenging enough for off-the-shelf LLMs to solve in the presence of hard (irrelevant) distractor text. For BABILong (used during inference), if sentences are longer than 64 tokens, we split the sentences at multiples of 64 tokens.

BABILong-soft. We create a variant of BABILong that contains soft distractors (in-distribution padding) instead of hard ones in the original dataset, which we refer to as BABILong-soft. Using this padding, we increase context length up to 4k tokens. We provide details about how this data is generated in Appendix B.

Location change. We also evaluate the robustness of models to modified bAbi test samples that have locations that are unseen during training. Specifically, we map locations mentioned in bAbi samples to a different location (ie. office \rightarrow library). We provide details about all location mappings in Appendix B.

Variable Tracking (VT) tasks. Variable tracking, introduced by RULER benchmark (Hsieh et al., 2024), emulates a minimal coreference chain resolution task, which requires tracking relevant co-occurrence patterns and inferring skipped connections to bridge linked entities over long context. Specifically, the model is given context with lines with information about variable value assignment such as "VAR AAAAA = 16438" or "VAR BBBBB = AAAAA", and the model is prompted to obtain all variables with a specific value. Variable names have the format of 5 repeating letters randomly sampled from the alphabet. The task complexity is further increased by adding more chains. We provide an example and additional data details in Appendix B.4.

We train and evaluate with chains of length 2, 4, 6, 8, and 10 and return the average accuracy over all chain lengths for the 1-hop and 2-hop VT tasks. In order to pad the context for lengths 1k, 4k, and 16k during test, we follow the approach taken from RULER of padding with the following sentences as hard distractors "The grass is green. The sky is blue. The sun is yellow. Here we go. There and back again.\n" until the context reaches the desired length. This noise is not present during training and the 0k data follow the same distribution as the training data.

4.2. Baseline Models

We benchmark RMT and Mamba models that are finetuned on individual task and test them on corresponding bAbi/BABILong and VT test samples. Specifically, we finetune off-the-shelf RMT and Mamba models using the next token prediction loss on final answer reconstruction and optionally on supporting fact (SF) reconstruction (100% SF refers to all supporting facts used in training) on each task separately ¹. To our knowledge, this study is the first one to explore reasoning generalization of RMT and Mamba that use SF supervision. We also evaluate an RMT-.14B model finetuned on shorter BABILong samples from (Kuratov et al., 2024) on newly proposed BABILong-soft set. If not explicitly mentioned, size of the RMT model is .77B and the same for Mamba is 1.4B. We report task accuracy as the performance metric, so higher the better.

Due to space constraints, we defer the training details C, ablation studies D.5, more baselines D.7, and additional experiments on supporting fact supervision D.6 in Appendix.

4.3. Results

We now present results on evaluating the generalization capabilities of MemReasoner and baseline models. Across evaluation datasets, our results demonstrate that *the design* of MemReasoner allows it to take advantage of none-tolittle supporting fact information, which largely improves its

¹We note that this reconstruction loss differs from the ordering loss used in training MemReasoner (Equation 1) and instead matches a term we investigate in more depth in Appendix D.6. Training RMT or Mamba with the ordering loss is non-trivial and is beyond the scope of current work.

generalization capabilities. In comparison, other baselines generally struggle to generalize and do not benefit much from supporting fact information.

4.3.1. GENERALIZATION ON LONG-CONTEXT REASONING-IN-A-HAYSTACK BENCHMARKS

bAbi Tasks - BABILong Test. Figure 2 (left) reports the accuracy of MemReasoner, together with baseline models, on task 1 and task 2 test samples of varying length from BABILong, respectively. If supporting fact (SF) supervision is used during fine-tuning, it is mentioned explicitly as + x% SF, where x denotes amount of training samples that have corresponding supporting facts. If a model without SF supervision provides high accuracy, we do not show results with + SF. RMT and Mamba, when finetuned on bAbi, achieve near-perfect accuracy on both tasks on original bAbi test samples. In contrast, MemReasoner trained with supervision on final answer only, while performing comparably on task 1, it falls short on task 2. This low test accuracy of MemReasoner is due to making frequent errors at the second hop on the challenging 2-hop task. It is noteworthy that even a powerful baseline like GPT-3 (175 B parameters) with few-shot and chain-of-thought prompting (Yang et al., 2023) that performs well on task 1, does much worse on task 2 that requires learning temporal dependence and performing multiple hops across facts to generate the final answer of object location (see Appendix Table 5). Thus, we add supporting fact supervision (using ordering loss in eqn. 1) on 1% of the training samples. On 0k test samples, MemReasoner + 1% SF shows an accuracy improvement from 38% to 76%, while for MemReasoner + 100% SF the accuracy becomes near perfect. This result suggests that MemReasoner benefits from a small amount of supporting fact supervision on a two-hop task.

bAbi-finetuned RMT and Mamba models show a significant accuracy drop on BABILong samples beyond 0k input length, though both show near-perfect accuracy at 0k. Interestingly, additional supervision on 100% supporting facts during RMT or Mamba training (in the form of supporting fact reconstruction loss) did provide none-to-little performance boost. In contrast, MemReasoner trained on bAbi generalizes well on BABILong for task 1, providing an average accuracy of 91.6% and 89% on \leq 8k and \geq 16k BABI-Long samples, respectively. On task 2, MemReasoner also shows a performance drop from 0k to 1k. MemReasoner + 1% SF shows more robust performance on BABILong, as accuracy drops from 76% to only 43%, as input length increases from 0k to 1k. MemReasoner + 100% SF variant maintains 50-70% accuracy for longer inputs up to 128k.

bAbi Tasks - BABILong-soft Test. This long-context setting is more challenging. Therefore, in addition to the bAbifinetuned models, we also include the top-performing models from BABILong leaderboard, i.e., an RMT-.14B model finetuned on BABILong samples of up to 16k tokens, for comparison. Results are shown in Figure 2 (right) for tasks 1 and 2. On BABILong-soft task 1, all models lose accuracy compared to BABILong task 1. However, for Mem-Reasoner, the performance drop is lowest throughout these context lengths. For task 2, all models exhibit even more striking performance loss as input length increases, while MemReasoner with additional supporting fact supervision shows more robust performance in the 1-4k range.

Variable Tracking - Ruler Test. Figure 3 reports results on 1- and 2-hop variable tracking tasks. Remember that the longer test samples (1-16k length) from RULER benchmark do include additional noisy distractors in the input. In the single-hop VT experiments, MemReasoner maintains perfect accuracy over the entire context length range, whereas RMT shows a sharp drop from 100% at 0k to 5.7% at 1k. Even adding supervision on all supporting facts does not help RMT's performance. Mamba performs better than RMT at 1k, but also shows a stark accuracy lowering at 4k, which cannot be fixed with supporting fact supervision.

For the 2-hop VT task, we observe that it is difficult to train RMT with 2 segments. RMT can easily learn a shortcut and have high accuracy on the training set, but does not generalize well to the test set at 0k length (74.6% accuracy). At this length, we observe that RMT struggles with performance on longer chain lengths, achieving only 61.5% accuracy on 8 chains and 3% accuracy on 10 chains despite these chain lengths being present during training. Performance degrades further at longer context length. Again, access to supporting facts appears ineffective in fixing the underlying issue. Mamba without and with supporting fact supervision shows consistently better performance than RMT. MemReasoner in the absence of supervision on intermediate steps does poorly at 0k (28.1% accuracy), while maintaining it for longer inputs. With 1% SF supervision, MemReasoner shows above 90% accuracy for the entire 0-16k length range.

4.3.2. Generalization to unseen target answers and from 2-hop \rightarrow 1-hop

We create a new, more stringent testbed where the construct of the tasks remains the same, but the answer changes from training to test set (See section 4.1). As shown in Table 1, when no SF supervision is used, on task 1 the accuracy order is RMT < Mamba < MemReasoner, while on task 2 the order is RMT < MemReasoner < Mamba. Given that, in this setting the length of the test sequence is similar to that of the training one, Mamba handles it better for task 2, with an accuracy of 34.5%, though MemReasoner with 1% SF supervision shows 64.9% accuracy compared to 45.2% for Mamba with 100% SF.

Finally, we also check if the models trained on 2-hop bAbi/VT can solve the simpler 1-hop version, but on the



Figure 2. Performance of MemReasoner and baselines on varying lengths of BABILong (left) and BABILong-soft (right) data.



Figure 3. Performance on varying lengths of variable tracking.

Table 1. Robustness to location changes in bAbi test set. Bold: highest; underlined; second highest.

Model type	Task 1	Task 2
RMT	44.7	0.6
RMT + 100%SF	31.3	0
Mamba	<u>74.4</u>	34.5
Mamba + 100%SF	52.7	45.2
MemReasoner	98.6	20.7
MemReasoner + 1% SF	-	<u>49.6</u>
MemReasoner + 100% SF	-	63.9

corresponding long context samples. We show their results in Tables 2 and 3. From the table, it can be seen that Mem-Reasoner can generalize in this setting with no access to supporting facts for VT and with access to 1% of supporting facts for bAbi. Baseline models show minimal generalization at longer input length for the single-hop task and supporting fact supervision does not help much.

4.4. Conclusion and Limitations

Here we empirically investigate and compare generalization aspects of long-range dependency modeling across a variety of LLM architectures, including RMT, Mamba, and the proposed MemReasoner. The MemReasoner model comes with an external-to-transformer latent memory of context, which aims to learn temporal relations and meaningful hop-

Table 2. Performance on bAbi task $2 \rightarrow BABILong$ task 1 generalization.

ion.					
	Model type	0k	1k	2k	4k
	RMT	100	19	20	12
	RMT (bAbi) + 100%SF	95	21	22	16
	Mamba	86	33	24	7
	Mamba + 100%SF	<u>99</u>	55	27	9
	MemReasoner	45	12	22	14
	MemReasoner) + 1% SF	52	<u>45</u>	48	53
	MemReasoner + 100% SF	56	44	<u>43</u>	38

Table 3. Performance on VT 2-hop \rightarrow VT 1-hop generalization.

	•			
Model type	Ok	1k	2k	4k
RMT	0.8	0.6	0.2	0.1
RMT + 100%SF	58.3	1.8	2.0	0.8
Mamba	1.2	3.1	2.1	0.0
Mamba + 100%SF	1.2	3.8	1.4	0.0
MemReasoner	100	100	100	100

ping between facts, and enables a selective attention over the memory. These sets of operations, when fine-tuned with supervision on the final answer alone, are found effective in generalization in single-hop scenarios, when compared to the internal (to transformer) segment-recurrence mechanism within RMT and the selection mechanism in Mamba. On more challenging two-hop tasks, MemReasoner utilizes additional supervision on intermediate reasoning steps more effectively than other models, and shows stronger and more robust generalization in most experiments. MemReasoner's performance benefits from having supporting facts for as little as 1% training samples. The performance gain with supervision can depend on a number of factors (task, model, loss, testbed, and amount of supervision) which will be further explored in future work.

The current work is limited to testing the MemReasoner framework on simple synthetic reasoning tasks, that only encompass very basic skills such as fact chaining and order awareness. Further, the datasets used are of simple construct. Future work will extend the framework to investigating generalization on more real-world reasoning tasks and datasets. and train the models in a more task-general setting. Another possible direction to explore is defining a selective attention over a combination of token-level memory and segmentlevel memory. In general, designing alternative transformer architectures with new loss objectives that encourage the model to learn the underlying reasoning skills will a path to explore toward more robust reasoners.

References

- Brown, T., Mann, B., Ryder, N., Subbiah, M., Kaplan, J. D., Dhariwal, P., Neelakantan, A., Shyam, P., Sastry, G., Askell, A., et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33: 1877–1901, 2020.
- Bulatov, A., Kuratov, Y., and Burtsev, M. Recurrent memory transformer. *Advances in Neural Information Processing Systems*, 35:11079–11091, 2022.
- Burtsev, M. S., Kuratov, Y., Peganov, A., and Sapunov, G. V. Memory transformer, 2021. URL https://arxiv. org/abs/2006.11527.
- Dai, Z., Yang, Z., Yang, Y., Carbonell, J., Le, Q. V., and Salakhutdinov, R. Transformer-xl: Attentive language models beyond a fixed-length context, 2019. URL https://arxiv.org/abs/1901.02860.
- Das, P., Chaudhury, S., Nelson, E., Melnyk, I., Swaminathan, S., Dai, S., Lozano, A., Kollias, G., Chenthamarakshan, V., Jiří, Navrátil, Dan, S., and Chen, P.-Y. Larimar: Large language models with episodic memory control, 2024. URL https://arxiv.org/abs/2403. 11901.
- Gu, A. and Dao, T. Mamba: Linear-time sequence modeling with selective state spaces, 2023.
- Hosseini, A., Sordoni, A., Toyama, D., Courville, A., and Agarwal, R. Not all llm reasoners are created equal, 2024. URL https://arxiv.org/abs/2410.01748.
- Hsieh, C.-P., Sun, S., Kriman, S., Acharya, S., Rekesh, D., Jia, F., Zhang, Y., and Ginsburg, B. Ruler: What's the real context size of your long-context language models?, 2024. URL https://arxiv.org/abs/2404.06654.
- Jelassi, S., Brandfonbrener, D., Kakade, S. M., and Malach, E. Repeat after me: Transformers are better than state space models at copying, 2024.
- Ju, T., Chen, Y., Yuan, X., Zhang, Z., Du, W., Zheng, Y., and Liu, G. Investigating multi-hop factual shortcuts in

knowledge editing of large language models, 2024. URL https://arxiv.org/abs/2402.11900.

- Kahneman, D. Thinking, fast and slow. Farrar, Straus and Giroux, New York, 2011. ISBN 9780374275631 0374275637. URL https://www.amazon.de/ Thinking-Fast-Slow-Daniel-Kahneman/ dp/0374275637/ref=wl_it_dp_o_pdT1_ nS_nC?ie=UTF8&colid=151193SNGKJT9& coliid=I30CESLZCVDFL7.
- Khalifa, M., Logeswaran, L., Lee, M., Lee, H., and Wang, L. Grace: Discriminator-guided chain-of-thought reasoning, 2023. URL https://arxiv.org/abs/2305. 14934.
- Kollias, G., Das, P., and Chaudhury, S. Generation constraint scaling can mitigate hallucination, 2024. URL https://arxiv.org/abs/2407.16908.
- Kuratov, Y., Bulatov, A., Anokhin, P., Rodkin, I., Sorokin, D., Sorokin, A., and Burtsev, M. Babilong: Testing the limits of llms with long context reasoning-in-a-haystack. *arXiv preprint arXiv:2406.10149*, 2024.
- Levy, M., Jacoby, A., and Goldberg, Y. Same task, more tokens: the impact of input length on the reasoning performance of large language models, 2024. URL https://arxiv.org/abs/2402.14848.
- Li, M., Zhang, S., Liu, Y., and Chen, K. Needlebench: Can llms do retrieval and reasoning in 1 million context window?, 2024. URL https://arxiv.org/abs/ 2407.11963.
- Liu, B., Ash, J. T., Goel, S., Krishnamurthy, A., and Zhang, C. Exposing attention glitches with flip-flop language modeling, 2023a. URL https://arxiv.org/abs/ 2306.00946.
- Liu, B., Ash, J. T., Goel, S., Krishnamurthy, A., and Zhang, C. Transformers learn shortcuts to automata, 2023b. URL https://arxiv.org/abs/2210.10749.
- Liu, N. F., Lin, K., Hewitt, J., Paranjape, A., Bevilacqua, M., Petroni, F., and Liang, P. Lost in the middle: How language models use long contexts, 2023c.
- Min, S., Lyu, X., Holtzman, A., Artetxe, M., Lewis, M., Hajishirzi, H., and Zettlemoyer, L. Rethinking the role of demonstrations: What makes in-context learning work?, 2022. URL https://arxiv.org/abs/ 2202.12837.
- Mitchell, M. How do we know how smart ai systems are?, 2023.

- Nye, M., Andreassen, A. J., Gur-Ari, G., Michalewski, H., Austin, J., Bieber, D., Dohan, D., Lewkowycz, A., Bosma, M., Luan, D., Sutton, C., and Odena, A. Show your work: Scratchpads for intermediate computation with language models, 2021. URL https://arxiv.org/ abs/2112.00114.
- Pang, R. Y., Yuan, W., Cho, K., He, H., Sukhbaatar, S., and Weston, J. Iterative reasoning preference optimization, 2024. URL https://arxiv.org/abs/2404. 19733.
- Park, J., Park, J., Xiong, Z., Lee, N., Cho, J., Oymak, S., Lee, K., and Papailiopoulos, D. Can mamba learn how to learn? a comparative study on in-context learning tasks, 2024. URL https://arxiv.org/abs/ 2402.04248.
- Pham, K., Le, H., Ngo, M., Tran, T., Ho, B., and Venkatesh, S. Generative pseudo-inverse memory. In *International Conference on Learning Representations*, 2022.
- Ruder, S. Challenges and opportunities in nlp benchmarking, 2021.
- Schick, T., Dwivedi-Yu, J., Dessì, R., Raileanu, R., Lomeli, M., Zettlemoyer, L., Cancedda, N., and Scialom, T. Toolformer: Language models can teach themselves to use tools, 2023. URL https://arxiv.org/abs/ 2302.04761.
- Srivastava, A., Rastogi, A., Rao, A., Shoeb, A. A. M., Abid, A., Fisch, A., Brown, A. R., Santoro, A., Gupta, A., Garriga-Alonso, A., et al. Beyond the imitation game: Quantifying and extrapolating the capabilities of language models. arXiv preprint arXiv:2206.04615, 2022.
- Sukhbaatar, S., Szlam, A., Weston, J., and Fergus, R. End-toend memory networks, 2015. URL https://arxiv. org/abs/1503.08895.
- Tay, Y., Dehghani, M., Abnar, S., Shen, Y., Bahri, D., Pham, P., Rao, J., Yang, L., Ruder, S., and Metzler, D. Long range arena: A benchmark for efficient transformers. *arXiv preprint arXiv:2011.04006*, 2020.
- Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., and Polosukhin, I. Attention is all you need. *Advances in neural information* processing systems, 30, 2017.
- Waleffe, R., Byeon, W., Riach, D., Norick, B., Korthikanti, V., Dao, T., Gu, A., Hatamizadeh, A., Singh, S., Narayanan, D., Kulshreshtha, G., Singh, V., Casper, J., Kautz, J., Shoeybi, M., and Catanzaro, B. An empirical study of mamba-based language models, 2024. URL https://arxiv.org/abs/2406.07887.

- Wan, Y., Wang, W., Yang, Y., Yuan, Y., tse Huang, J., He, P., Jiao, W., and Lyu, M. R. Logicasker: Evaluating and improving the logical reasoning ability of large language models, 2024. URL https://arxiv.org/ abs/2401.00757.
- Wei, J., Wang, X., Schuurmans, D., Bosma, M., Xia, F., Chi, E., Le, Q. V., Zhou, D., et al. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837, 2022.
- Weston, J., Chopra, S., and Bordes, A. Memory networks. arXiv preprint arXiv:1410.3916, 2014.
- Weston, J., Bordes, A., Chopra, S., Rush, A. M., Van Merriënboer, B., Joulin, A., and Mikolov, T. Towards ai-complete question answering: A set of prerequisite toy tasks. *arXiv preprint arXiv:1502.05698*, 2015.
- Wu, J., Yang, L., Wang, Z., Okumura, M., and Zhang, Y. Cofca: A step-wise counterfactual multi-hop qa benchmark, 2024. URL https://arxiv.org/abs/ 2402.11924.
- Wu, Y., Wayne, G., Graves, A., and Lillicrap, T. The kanerva machine: A generative distributed memory, 2018.
- Xiao, G., Tian, Y., Chen, B., Han, S., and Lewis, M. Efficient streaming language models with attention sinks, 2024. URL https://arxiv.org/abs/ 2309.17453.
- Yang, Z., Ishay, A., and Lee, J. Coupling large language models with logic programming for robust and general reasoning from text. In *The 61st Annual Meeting Of The Association For Computational Linguistics*, 2023.
- Zelikman, E., Wu, Y., Mu, J., and Goodman, N. D. Star: Bootstrapping reasoning with reasoning, 2022. URL https://arxiv.org/abs/2203.14465.

Appendix A. Algorithm

Algorithm 1:

```
1 Function MemReasoner (q, \{c_1, ..., c_E\}, \alpha, \tau):
         // q: query tokens,
               \{c_1, ..., c_E\}: E context lines,
               \alpha: a hyperparameter for the query update,
               \tau: a threshold hyperparameter for terminating iterations,
               P_a: the prompt given to the decoder for answer generation
         z_q \leftarrow \text{encode}(q)
 2
         for i \leftarrow 1 to E do
 3
          z_i \leftarrow \text{encode}(c_i)
 4
 5
         end
         \tilde{z}_1, ..., \tilde{z}_E \leftarrow \texttt{temporalEncoding}(z_1, ..., z_E)
 6
         \hat{M} \leftarrow \text{write}(\tilde{z}_1, ..., \tilde{z}_E)
 7
         \tilde{z}_r \leftarrow \text{queryUpdate}(z_q, \alpha, \tau, \hat{M})
 8
         (optional) \tilde{z_r}, \{z_1, \ldots, z_E\}, \{\tilde{z_1}, \ldots, \tilde{z_E}\} \leftarrow \text{InferenceTimeUpdate}(\tilde{z_r}, z_1, \ldots, z_E, \tilde{z_1}, \ldots, \tilde{z_E})
 9
10
         i^* \leftarrow \arg\min_{i \in \{1...E\}} ||\tilde{z}_i - \tilde{z}_r||_2
         return decode (z_{i^*}, W_M, P_a)
                                                                // generate the answer with the decoder, W_M is a
11
          learnable parameter which interfaces the z_{i^*} with the decoder
12
   Function queryUpdate (z_q, \alpha, \tau, M):
13
                                                                                                               // W_q is learned parameter
         \tilde{z}_r \leftarrow \text{read}(W_q z_q, M)
14
         z_q = z_q + \alpha \tilde{z}_r
                                                                                                                                     // query update
15
         \tilde{z}_{r,\text{next}} \leftarrow \text{read}\left(W_q z_q, M\right)
16
         do
17
              \tilde{z}_r \leftarrow \tilde{z}_{r,\text{next}}
18
            z_q = z_q + \gamma \tilde{z}_r
19
            \tilde{z}_{r,\text{next}} \leftarrow \text{read}(W_q z_q, M)
20
         while ||\tilde{z}_{r,next} - \tilde{z}_r||_2 > \tau
21
         return \tilde{z}_r
22
23
24
   Function InferenceTimeUpdate (\tilde{z}_r, z_1, \dots, z_E, \tilde{z}_1, \dots, \tilde{z}_E, \eta = 125):
         Index set \mathcal{I} \leftarrow gather indices i, s.t. \tilde{z}_i has the top \eta smallest distance to \tilde{z}_r
                                                                                                                      // filter out the most
25
          irrelevant contexts
         \{\tilde{z}_j\}_{j\in\mathcal{I}} \leftarrow \texttt{temporalEncoding}(\{z_j\}_{j\in\mathcal{I}})
26
         \hat{M} \leftarrow \text{write}(\{\tilde{z}_j\}_{j \in \mathcal{I}})
27
         \tilde{z}_r \leftarrow \text{queryUpdate}(z_q, \alpha, \tau, \hat{M})
28
         return \tilde{z_r}, \{z_j\}_{j \in \mathcal{I}}, \{\tilde{z}_j\}_{j \in \mathcal{I}}
29
```

B. Data Details

B.1. Additional dataset preprocessing details

In the unprocessed bAbi data, a single data instance consists of a sequence of lines representing facts to reason over with questions interspersed throughout the facts. We preprocess the bAbi data such that after pre-processing, a single training sample consists of a single question with facts for reasoning being the lines before it, with previous questions replaced by an empty line. On average, this leads to about 2 empty lines per training sample. For batches containing training samples with different lengths of context episodes, we pad shorter episodes with rows of the encoder padding token at the beginning.

During training, we also use Wikipedia samples which are chunked to a length of 64 tokens.



Babilong Task 2

Figure 4. Examples of BABILong tasks.

B.2. Generation of location change dataset

In order to test generalization to changes in location, we take each bAbi sample and map locations mentioned in the bAbi data to new out-of-distribution locations. Specifically, bAbi data contains the mention of the following 6 locations: office, garden, hallway, bathroom, bedroom, and kitchen. We replace all instances of these location names via the following mapping: office \rightarrow library, garden \rightarrow garage, kitchen \rightarrow cafe, bathroom \rightarrow attic, bedroom \rightarrow basement, and hallway \rightarrow gym.

B.3. Generation of BABILong-soft data

To generate BABILong-soft data, we begin with the bAbi test set for tasks 1 and 2. We pad the data with sentences of the form:

{entity} {verb} to the {location}.

where the entity is one of "John", "Mary", "Sandra", and "Daniel", verb is one of "moved", "went", "journeyed", "travelled", "went back", and location is one of "bedroom", "bathroom", "kitchen", "garden", "office", and "hallway". Sentences of this form naturally occur in the bAbi train and test set for these tasks. The location of the padding is randomly sampled and thus this padding can occur before, between, and after the true sentences in the context of the bAbi dataset. In order to avoid changing the answer to the bAbi question when adding padding, we keep track of the location of the last supporting fact and ensure that padding added after the last supporting fact does not mention the entity that is in the supporting fact. Meanwhile, padding added before the last supporting fact can be have any entity.

To illustrate, consider a bAbi sample with the question "Where is the football?" and context:

```
Mary travelled to the office.
Sandra went to the bedroom.
Sandra moved to the hallway.
Daniel journeyed to the garden.
Sandra discarded the football.
Daniel went back to the kitchen
```

Here, the last supporting fact in the line "Sandra moved to the hallway." and this line tells us the answer of the question is "hallway". To generate a corresponding BABILong-soft data point, we randomly sample a location at which we insert a sentence of padding. If this line is to be added before "Sandra moved to the hallway." then we sample any entity of the bAbi entities for the padding. If it is to be added after "Sandra moved to the hallway.", then we sample an entity that is not Sandra.

We use this approach to generate padding to increase context lengths to 1k, 2k, and 4k tokens.

B.4. Additional details about Variable Tracking

To generate variable tracking data for evaluation, we sample a letter of the alphabet and have that letter repeated 5 times as the variable name (ie. AAAAA). Variable tracking data has 2 parameters, the number of hops and the number of chains. The number of chains specifies the number of distinct numerical values present in the data. For 1-hop data, each line of context has a variable assigned to each numerical value (ie. "VAR AAAAA = 16438"). In 2-hop data, there are 2 variables

assigned each value, but one of the variables references the other in assignment (ie. "VAR AAAAA = 16438, VAR BBBBB = AAAAA"). Thus, the number of distinct variables is given by the number of hops times the number of chains.

We provide a data sample below with 2 hops and 2 chains with question "Find all variables that are assigned the value 13075 in the text above":

VAR DDDDD = 13075 VAR FFFFF = 19367 VAR ZZZZZ = VAR FFFFF VAR YYYYY = VAR DDDDD

For RMT and Mamba we provide the context in the prompt so that the prompt looks as follows "[INST] Memorize and track the chain(s) of variable assignment hidden in the following text. VAR DDDDD = 13075 VAR FFFFF = 19367 VAR ZZZZZ = VAR FFFFF VAR YYYYY = VAR DDDDD Question: Find all variables that are assigned the value 13075 in the text above. [/INST] Answer: According to the chain(s) of variable assignment in the text above, 2 variables are assigned the value 13075, they are:"

For MemReasoner, the query is taken to be "[INST] Question: Find all variables that are assigned the value 13075 [/INST]" and the prompt we use for obtaining the answer is "Answer: According to the chain(s) of variable assignment, 2 variables are assigned the value 13075, they are:" During the training of MemReasoner, we also insert empty lines of context, with 0 empty lines added at chain length 2, 1 empty line added at chain length 4, 2 at chain length 6, 3 at chain length 8, and 4 and chain length 10 similar to how empty lines are present in training MemReasoner on bAbi. The locations of these empty context lines are chosen randomly for variable tracking.

In order to increase the length of variable tracking data to 1k, 4k, and 16k token lengths, we follow the approach used by (Hsieh et al., 2024) in the RULER benchmark and pad by repeatedly inserting the noise: "The grass is green. The sky is blue. The sun is yellow. Here we go. There and back again." until we reach the desired token length. We note that this inserted noise can appear before, between, or after lines of variable tracking data.

C. Training Details

We always initiate MemReasoner finetuning from Larimar checkpoint pretrained on Wikitext (obtained by following the training protocol described in (Das et al., 2024)), which uses a Bert-large as the encoder and a GPT2-large as the decoder. The number of parameters in MemReasoner reported in the main paper is 1.4B. For extension to MemReasoner with a GPTJ-6B decoder, see section D.4. The slot size in the memory is 512. During finetuning, we randomly sample a batch of pretraining data (Wikipedia) of the same size as the batch of bAbi finetuning data, for computing the autoencoding loss on the pretrain dataset of 2M samples. We generate the answer to the question by passing a prompt to the decoder (i.e. in the case of bAbi Task1-2, the prompt has the from "<BOS> X is in the" where X denotes subject of the query).

bAbi training. We train MemReasoner models for 200 epochs using Adam optimizer with learning rate 5e-6. We set batch size to be 10. Additionally, we set query update parameter $\alpha = 1$. The maximum episode length varies from 14 (bAbi Task 1) to 72 (bAbi Task 2). Which means that MemReasoner has been exposed to a maximum of 90 and 573 tokens during finetuning on task 1 and task 2, respectively, whereas at test-time the model is exposed to contexts that are up to 128k tokens long. Since bAbi Task 1 is a single hop task, we do not perform query update during either training or inference. When fine-tuning on bAbi Task 2, we perform a fix number of 2 hop (equivalent to 1 query update) during the training. With bAbi Task 2 fine-tuned MemReasoner, we re-use the "2 hop" setting at inference on all tasks, including bAbi Task 2 and BABILong Task1/2. We consistently use query update parameter α =8 throughout our experiments and include an ablation study on α in the appendix. Due to the page limit, we also defer ablation studies on the episodic memory, temporal encoding schemes, use of inference time update, and the number of training epochs to Appendix D.5.

For RMT-0.77B and Mamba-1.4B finetuning, we finetune starting from off-the-shelf model checkpoints using the next token prediction loss on final answer reconstruction and optionally on supporting fact (SF) reconstruction (100% SF) on each tasks separately till the testing accuracy on the task is sufficiently high (near 100%). 100% SF models are trained to jointly reconstruct the answer given the prompt and output supporting facts when given a separate prompt asking for the supporting fact (i.e., when prompted "Where is the apple? Supporting facts:", the model is trained to follow up with the text of each supporting fact). In practice, we train for 20 epochs with batch size 10 on Mamba for the accuracy to plateau. RMT training was done with multiple segments using a curriculum learning procedure. In order to train with more segments while exposing the model to only bAbi data, we reduce the segment size to 64 for task 1 and 128 for task 2. This leads to 2

segments in training for task 1 and 2-4 segments in training for task 2. In order to mimic the curriculum learning process, we filter the data so that we train with inputs with token length up to the segment size for 10 epochs with batch size 5, up to 2 times segment size for another 10 epochs, and so on. For both RMT and Mamba, we use Adam optimizer with learning rate 1e - 5.

Variable tracking (VT) training. For the training on VT tasks, we do not use autoencoding loss on wiki samples. We train MemReasoner for 100 epochs. For VT, the episode length is at most 14 for both single hop and 2-hop tasks. Similar to bAbi, we do not perform query update for the single hop task and perform a single query update for the 2-hop task. Since VT asks for all variables with a specific value, for MemReasoner, we take all unordered readouts of the model and pass them individually to the decoder to get the variables from each reasoning hop, and then concatenate these variables in order to obtain the final answer.

For RMT and Mamba on VT, we use the same experimental setup as with training on bAbi. Due to the shorter context lengths in variable tracking compared to bAbi, we train RMT with 2 segments, with segment size set to the median length on the train dataset. Similar to bAbi training, we use a curriculum schedule of training with 1 segment for 10 epochs and with 2 segments for an additional 10 epochs and train with a batch size of 5.

D. Additional Experimental Results

D.1. Comparison of inference-time complexity

Let H_1 , H_2 and d_1 , d_2 be the number of transformer layers and hidden state dimension in the encoder and decoder, respectively. Let E denote the number of context lines in a sample, L be the max context length, L_1 be the max query length, D be the latent space dimension, and m be the memory size. The inference-time computational complexity for MemReasonr can be estimated by the encoder complexity $\mathcal{O}(H_1((EL^2 + L_1^2)d_1 + (EL + L_1)d_1^2))$, temporal encoding complexity $\mathcal{O}(Ed^2)$, memory operation complexity $\mathcal{O}(Edm^2)$, decoding complexity $\mathcal{O}(H_2(|P_a|^2d_2 + |P_a|d_2^2))$, and broadcasting complexity $\mathcal{O}(d_1dE)$ and $\mathcal{O}(d_2dH_2)$. For a typical GPT decoding, the inference-time computational complexity is $\mathcal{O}(H_2((EL + L_1)^2d_2 + (EL + L_1)d_2^2))$.

To provide a more direct comparison, we give in Table 4 the inference cost measured in seconds per input for evaluating with BABILong in comparison to the base decoder (gpt2-large). We note that gpt2-large does not support context lengths longer than 1024 tokens. Overall, we observe that the increase in inference time for both RMT and MemReasoner are very small for 0k, and MemReasoner's runtime advantage over RMT becomes clear as they process longer context lengths. This is attributed to the utilization of latent encodings of contexts, performing one-shot write to the memory, and executing multiple hops over that memory, all in the latent space.

Model type	0k	1k	2k	4k	8k	16k	32k	64k	128k
gpt2-large	0.28	1.13	-	-	-	-	-	-	-
RMT	0.35	0.35	0.69	1.46	2.97	5.96	12.25	23.92	48.40
MemReasoner	0.30	0.33	0.40	0.61	0.98	1.94	3.26	11.25	13.77

Table 4. The inference cost measured in seconds per input on BABILong.

D.2. Performance on original bAbi Test Set

Table 5 reports the performance of MemReasoner, RMT, and Mamba, each of which is independently finetuned on original bAbi task 1 and task 2, on the corresponding bAbi test set of 1k samples. If supporting fact supervision is used during fine-tuning, it is mentioned explicitly as + x% sup, where x denotes amount of training samples that have corresponding supporting facts. We will also include off-the-shelf powerful baselines GPT-3 (175 B parameters) with few-shot and chain-of-thought prompting (Yang et al., 2023). Results show that, while prompting techniques such as few-shot learning and CoT prompting work well on task 1 which requires a single hop to find the entity location, those baselines perform much poorly on task 2 that requires learning temporal dependence and performing multiple hops across facts to generate the final answer of object location. RMT and Mamba, when finetuned on bAbi, achieves near-perfect accuracy on both tasks. In contrast, MemReasoner trained with supervision on final answer, while perform comparably on task 1, it falls short on task 2. This low test accuracy of MemReasoner is due to making frequent errors at the second hop. Thus, we add supporting fact supervision on all samples, the accuracy becomes near perfect. This result suggest MemReasoner requires a small amount

Model type	Task 1	Task 2
CoT - GPT-3	97.3	72.2
Few-shot - GPT-3	98.4	60.8
RMT77B (bAbi)	97.7	97.5
Mamba-1.4B (bAbi)	100	95
MemReasoner-1.4B (bAbi)	100	39.5
MemReasoner-1.4B (bAbi) + 1% SF	-	74.4
MemReasoner-1.4B (bAbi) + 100% SF	-	99.6

Table 5. Performance on original bAbi test set. Best model is highlighted in bold. GPT-3 (=text-davinci-003) baselines are from (Yang et al., 2023). Finetuning data, if any, seen by a model is specified within parentheses.

Table 6. RMT's robustness to location changes in bAbi test set when fine-tuned on BABILong. Mamba's result is unavailable due to the absence of publicly released finetuned checkpoint.

Model type	Task 1	Task 2
RMT14B (BABILong)	12.4	1.6

of supporting fact supervision to perform two-hop reasoning in a reasonable manner.

D.3. Robustness of models finetuned on BABILong

Kuratov et al. (2024) observe that directly finetuning with long contexts following the BABILong distribution leads to improved generalization to longer contexts. We test the robustness of RMT-.14B finetuned on BABILong to unseen locations using our bAbi location change dataset (Table 6). We observe that RMT finetuned on BABILong exhibits a large drop in accuracy on these unseen locations even in the absence of padding.

D.4. Extension to GPTJ-6B

MemReasoner is a model-agnostic way to augment current decoder-only LLMs with dynamically updatable memory. Via end-to-end training, the architecture learns to write the latent encodings in a fixed-size memory, order them in their order of appearance in the context, and perform multiple hop over that context and update the latent query accordingly. The decoder learns a differentiated attention mechanism to the readout from the memory, to accurately generate the final answer and supporting facts (intermediate hops). Supervision on all supporting facts was enabled in the form of SF ordering loss and reconstruction loss. Below, we provide the results when we train a GPTJ-6B decoder with MemReasoner training protocol, suggesting more or less similar performance compared to MemReasoner-1.3B.

Table 7. Performance of MemReasoner + 100% SF with a GPTJ-6B decoder on BABILong.

Model type	0k	1k	2k	4k	8k	16k	32k	64k	128k
Task 1	98	82	77	65	60	68	70	65	67
Task 2	98	65	50	34	35	32	22	27	30

D.5. Ablation Studies

D.5.1. INFERENCE TIME UPDATE

We compare the performance of MemReasoner with and without inference time update (IU) as shown below:

D.5.2. Memory

In Table 10, we conduct the ablation study on the episodic memory module in MemReasoner on bAbi and BABILong, task 1 and 2. Specifically, MemReasoner w/o memory module uses the same architecture of encoder and decoder (BERT-Large and GPT2-Large respectively) but does not use the memory module for encoding the context. Instead, the MemReasoner w/o memory uses the encoder to encode only the question and this is passed in to the decoder as kv-cache. Additionally, the context and question are passed to the decoder as part of the prompt with the format:

Context:\n{context}\nQuestion:\n{question}\nAnswer:

Table 8. Ablation with and without IU for BABILong Task 1

		Avg.	Avg.									
Model type	+ IU	$\leq 8k$	$\geq 16k$	0k	1k	2k	4k	8k	16k	32k	64k	128k
MemReasoner-1.4B (bAbi)		77.2	62.8	97	82	73	65	69	62	66	63	60
MemReasoner-1.4B (bAbi)	\checkmark	91.6	89	97	90	89	89	93	94	94	87	81
MemReasoner-1.4B (bAbi) + 100% sup		82.2	59.3	100	91	80	70	70	62	58	58	59
MemReasoner-1.4B (bAbi) + 100% sup	\checkmark	94.4	93	100	93	93	94	92	94	94	94	90

Table 9. Ablation with and without IU for BabiLong Task 2

		Avg.	Avg.									
Model type	+ IU	$\leq 8k$	$\geq 16k$	0k	1k	2k	4k	8k	16k	32k	64k	128k
MemReasoner-1.4B (bAbi)		18.4	11.8	38	16	12	14	12	8	14	14	11
MemReasoner-1.4B (bAbi)	\checkmark	21	18.8	38	17	17	16	17	15	15	27	18
MemReasoner-1.4B (bAbi) + 1% sup		42.8	27.5	76	47	33	31	27	25	24	31	30
MemReasoner-1.4B (bAbi) + 1% sup	\checkmark	46.6	27.8	76	43	46	38	30	27	25	31	28
MemReasoner-1.4B (bAbi) + 100% sup		59.4	24.5	100	70	52	44	31	28	20	24	26
MemReasoner-1.4B (bAbi) + 100% sup	\checkmark	74.2	59.5	100	64	71	63	73	71	61	55	51

where {context} and {question} represent the context and the question for the datapoint. We train the model with reconstruction loss to ensure that the model is able to fill in the answer given this prompt and with autoencoding loss on the pretraining dataset (see last term of Equation 1) in order to reduce overfitting on bAbi data. We train MemReasoner w/o memory module for 5 epochs.

MemReasoner w/o memory module trained on bAbi task 1 obtains almost perfect accuracy on bAbi task 1 and BABILong task 1 0k. However, its generalization ability to long context (BABILong 1k and 2k) is much inferior to MemReasoner (MemReasoner\memory 0% vs. MemReasoner 91% on BABILong 1k). Similar trends can also be seen from bAbi task 2 trained MemReasoner\memory, implying the significance of the episodic memory module and the operations around it in MemReasoner.

Table 10.	Ablation	study	on the	episodic	memory
				1	2

Model type	Task 1	0k	1k	2k	Task 2	0k	1k	2k
MemReasoner\memory	100	100	0	-	99.3	100	29	-
MemReasoner	100	99	91	83	100	100	73	61

D.5.3. TEMPORAL ENCODING

The temporal encoding module is generic and allows any structure featuring sequentiality within context. In the paper, we have used *parameterized* methods such as GRUs. In practice, we can also use *un-parameterized* methods such as Sinusoidal Positional Encoding (Vaswani et al., 2017). Additionally, we experiment with positional encoding which assigns encodings starting from the last element of the episode. This structure ensures that for contexts of different length, the last lines of the contexts are encoded similarly, which is useful for QA tasks in which the most recent information is more relevant for answering the question. Finally, to convert $\{z_1, ..., z_E\}$ to $\{\tilde{z}_1, ..., \tilde{z}_E\}$ with positional encodings, we add the computed positional encodings to the input.

In Table 11, we experiment with different temporal encoding schemes, including non-parametric method (Positional Encoding) and parametric method (GRU). In the table, we show MemReasoner's accuracy on BABILong Task 1. It can be seen that GRU encoding has significant advantage over Positional Encoding, with much slower decay in the accuracy as the context length increases. Additionally, though showing higher accuracy compared with Positional Encoding, uni-directional GRU's accuracy decreases faster than bi-directional GRUs. Since 1-layer bi-directional GRU has similar performance with 2-layer bi-directional GRU, we choose the lighter model and use 1-layer bi-directional GRU throughout the experiments in this paper.

D.5.4. Query Update α

In Table 12, we exploit test-time inference hyper-parameter α and its effect in reasoning tasks' performance. We draw inspiration from (Kollias et al., 2024), where authors investigated the effect of scaling readout vectors to improve generation

Encoding scheme	0k	1k	2k
Positional Encoding	100	27	20
2-layer bi-directional GRU	100	90	80
2-layer uni-directional GRU	94	75	61
1-layer bi-directional GRU	99	91	83

Table 11. Ablation study on the temporal encoding schemes.

quality. In Line 20 of Algorithm 1, when using an $\alpha > 1$, we equivalently scale up the readout vectors which greatly help our generalization to Task 1 BABILong according to Table 12 (e.g. from 14% to 45% on 4k context token task).

Table 12. Ablation study on the query update parameter α .

Query update	Task 2 bAbi		Task 2 BABILong								Task 1 BABILong				
α	location change	0k	1k	2k	4k	8k	16k	32k	64k	128k	0k	1k	2k	4k	
1	52.6	100	46	25	18	18	13	16	12	13	78	21	17	14	
4	54.2	100	73	61	46	26	22	19	19	27	83	47	44	40	
8	52.7	100	73	61	46	23	20	19	17	20	83	58	50	45	

D.5.5. TRAINING EPOCHS

In Table 13, we evaluate MemReasoner's performance when fine-tuned on bAbi task 2 as a function of the number of training epochs. Specifically, with fewer epochs, MemReasoner demonstrates stronger robustness to location change, reaching an accuracy of 79% at the 66th epoch, which decreases to around 50% as the training continues (at 100/200th epoch). On the other side, MemReasoner's accuracy on shorter context tasks in BABILong Task 1 and 2 (i.e. 0-4k) improves as the training continues.

Table 13. Ablation study on the number of training epochs

	Task 2 bAbi		Task 2 BABILong							Task 1 BABILong				
#epochs	location change	Ok	1k	2k	4k	8k	16k	32k	64k	128k	0k	1k	2k	4k
66	78.0	99	70	54	30	27	23	17	18	17	58	51	45	37
100	47.3	100	70	57	38	28	31	25	12	19	82	58	50	46
200	52.7	100	73	61	46	23	20	19	17	20	83	58	50	45

D.6. MemReasoner with even stronger supporting fact supervision

To further boost the expandability of a decoding result, one can optionally optimize the reconstruction loss of the supporting facts using the available supervised data. Specifically, if we let P_s denote the prompts for generating the supporting fact, we can instead minimize

$$\begin{split} L &= \rho \underbrace{\mathbb{E}_{x \sim \mathcal{D}_{\text{pretrain}}} \ln p(d(e(x)))}_{\text{autoencoding of pretraining dataset}} + \mathbb{E}_{(q,C,S,a) \sim \mathcal{D}_{\text{finetune}}} \underbrace{\mathbb{E}_{z_{r}^{|S|} \sim p(z_{r}^{|S|}|q,M,\tilde{z}_{r}^{0}\dots\tilde{z}_{r}^{|S|-1})}_{\text{reconstruction of answer}} \ln p(a|z_{r}^{|S|},P_{a})}_{\text{reconstruction of answer}} \\ &+ \mathbb{E}_{(q,C,S,a) \sim \mathcal{D}_{\text{finetune}}} \left[\delta \underbrace{\sum_{i=1}^{|S|} \mathbb{E}_{\tilde{z}_{r}^{i} \sim p(\tilde{z}_{r}^{i}|q,M,\tilde{z}_{r}^{0}\dots\tilde{z}_{r}^{i-1})}_{\text{ordering loss}} \ell_{\text{ordering loss}} \right]_{\text{ordering loss}} \\ &+ \alpha \underbrace{\sum_{i=1}^{|S|} \mathbb{E}_{z_{r}^{i} \sim p(z_{r}^{i}|M,\tilde{z}_{r}^{0}\dots\tilde{z}_{r}^{i-1})}_{\text{reconstruction of supporting facts}} + \beta \underbrace{\sum_{s \in S} \underbrace{\ln p(d(e(c_{s})))}_{\text{autoencoding of supporting fact}} \right], \end{split}$$

where α and β are hyperparameters controlling regularization strength of the two additional terms - the 4th term corresponds to the reconstruction loss of the supporting fact(s) with respect to the corresponding prompt for obtaining the answer P_a and

readout; the 5th term is the autoencoding loss of the supporting fact(s). We denote this comprehensive use of supporting fact as "SF*". MemReasoners trained with additional losses perform similarly on most task except transfer task generalization as shown in Table 14. It should be mentioned that training RMT or Mamba with the ordering loss is non-trivial and is beyond the scope of current work.

Table 14	Performance on	hAbi task $2 \rightarrow$	BABIL ong task 1	generalization
14010 14.	r chlorinance on	0/101 task 2	DribiLong task i	generalization

Model type	0k	1k	2k	4k	
MemReasoner-1.4B (bAbi) + 100% SF	56	44	43	38	-
MemReasoner-1.4B (bAbi) + 100% SF*	83	58	50	45	

D.7. Additional baselines

We also add a Larimar-1.3B baseline, which is finetuned on Wikipedia and either bAbi or VT samples (indicated in parentheses for each table below), with final answer reconstruction loss and autoencoding loss. The purpose of comparing MemReasoner with respect to Larimar is to disambiguate the benefits of temporal feature learning and iterative query and read updates on top of the episodic memory. Larimar fine-tuning shares the same training setups as MemReasoner.

Table 15. BABILong Results.

	Avg.	Avg.									
Model type	$\leq 8k$	$\geq 16k$	0k	1k	2k	4k	8k	16k	32k	64k	128k
Larimar-1.3B (bAbi task 1)	44.8	14.3	63	59	55	28	19	14	16	13	14
Larimar-1.3B (bAbi task 2)	31	20.3	42	41	29	22	21	19	16	22	24

Table 16. Variable tracking results.

Model type	0k	1k	4k	16k
Larimar-1.3B (VT task 1)	92.5	92.5	94.0	93.6
Larimar-1.3B (VT task 2)	0.1	0	0.1	0

Table 17. Robustness to location changes in bAbi test set.

Model type	Task 1	Task 2
Larimar-1.3B (bAbi)	24.9	7.8

Table 18. Performance on bAbi/VT task $2 \rightarrow$ task 1 (long) generalization.

Model type	0k	1k	2k	4k
Larimar-1.3B (bAbi)	45	19	20	11
Larimar-1.3B (VT)	0.2	0.1	0.3	0.1