Thermal conductivity of the $A_x BO_2$ type layered oxides $Na_{0.77}MnO_2$ and $LiCoO_2$

Kazumi TAKAHATA¹ and Ichiro TERASAKI^{1,2} *

¹Department of Applied Physics, Waseda University,

3–4–1 Ohkubo, Shinjuku-ku, Tokyo, 169-8555, Japan

²Precursory Research for Embryonic Science and Technology,

Japan Science Technology, Tokyo 108-0075, Japan

(Dated: October 29, 2018)

We prepared polycrystalline samples of the A_xBO_2 type layered oxides $Na_{0.77}MnO_2$ and $LiCoO_2$, and measured thermal conductivity (κ) from 15 to 280 K. $Na_{0.77}MnO_2$ shows a low κ of 15 mW/cmK at 280 K, while $LiCoO_2$ shows a much higher κ of 40 mW/cmK at 280 K. By comparing them with κ of $NaCo_2O_4$, we have found that the low κ of A_xBO_2 comes essentially from the A-ion deficiency, not from the layered structure itself.

PACS numbers: PACS numbers: 72.15.Eb, 72.15.Jf, 72.80.Ga, 72.15.Lh

Recently, thermoelectric energy conversion [1] has attracted renewed interest from the viewpoint of environmental concerns. In this respect, oxides are quite desirable, because they are stable in air and mostly harmless. Owing to the low efficiency, they have been thought to be unsuitable for thermoelectric applications, but the layered cobalt oxide NaCo₂O₄ has been found to show exceptionally high thermoelectric performance [2]. Previously we found that NaCo₂O₄ has a low thermal conductivity (κ) of 15 mW/cmK at 280 K, which was attributed to the short phonon mean free path arising from the Na deficiency [3].

An open question is whether the layered structure is effective for the κ reduction in NaCo₂O₄ or not, as in the case of the thermoelectric superlattice [4, 5, 6]. Although the phonon-scattering theory [7, 8] successfully fitted the data in the previous paper [3], we did not rule out the possibility of the layered-structure effects. The best way is perhaps to measure anisotropic κ using single crystals, but the crystals are too small and thin to measure κ accurately [9]. At least we can say that there is no reason to regard NaCo₂O₄ as a superlattice on the electric properties. The resistivity is anisotropic, but quantum confinement is unlikely to occur in the c-axis conduction [2].

In order to distinguish the layered-structure effects from the Na-deficiency effects, we focus on Na_{0.77}MnO₂ and LiCoO₂, which have the same layered structure of A_xBO_2 , but have different A-ion deficiency (see Fig.1): Na ions in NaCo₂O₄ (Na_{0.5}CoO₂) and Na_{0.77}MnO₂ are 50 % and 23% deficient, while Li ions in LiCoO₂ are nominally 100% occupied. Here we report on measurement and analysis of κ of Na_{0.77}MnO₂ and LiCoO₂.

Polycrystalline samples of $Na_{0.77}MnO_2$ and $LiCoO_2$ were prepared through a solid-state reaction. For $Na_{0.77}MnO_2$, starting powders of $NaCO_3$ and Mn_3O_4 were mixed and calcined at 500°C for 12h. The product was pressed into a pellet, and sintered at 550°C for 12h [10]. For LiCoO₂, starting powders of LiCO₃ and Co₃O₄ were mixed and calcined at 450°C for 12h. The product was pressed into a pellet, and sintered at 900°C for 24h [11]. X-ray diffraction revealed no impurity phases in the obtained polycrystals, and resistivity measurement revealed that they were highly insulating. The thermal conductivity was measured using a steady-state technique described previously [3].



FIG. 1: Crystal structures of $Na_{0.5}CoO_2$ ($NaCo_2O_4$), $Na_{0.77}MnO_2$ and $LiCoO_2$. The close and open circles represent the occupied and vacant ions, respectively.

Figure 2 shows κ of Na_{0.77}MnO₂ and LiCoO₂, together with κ of NaCo₂O₄ from Ref.[3]. κ of the Na-deficient oxide Na_{0.77}MnO₂ is as low as 15 mW/cmK at 280 K, and is slightly lower than κ of NaCo₂O₄. Since κ of NaCo₂O₄ includes the electron thermal conductivity (about 10 % of total), we think that the lattice thermal conductivity is nearly equal between the two. On the contrary, the fully Li-occupied oxide LiCoO₂ shows 3-4 times higher κ than Na_{0.77}MnO₂. This clearly indicates that the A-ion deficiency effectively reduces κ .

Let us fit the data with the phonon-scattering theory [7, 8]. The lattice thermal conductivity is written as

$$\kappa_{\rm ph} = \frac{k_B}{2\pi^2 v} \left(\frac{k_B}{\hbar}\right)^3 T^3 \int_0^{\Theta_D/T} \frac{x^4 e^x}{(e^x - 1)^2} \ \tau \ dx \qquad (1)$$

where Θ_D is the Debye temperature, and v is the sound velocity, and $x = \hbar \omega / k_B T$. The total scattering rate τ^{-1}

^{*}E-mail address: terra@mn.waseda.ac.jp



FIG. 2: The thermal conductivity of $A_x BO_2$ type layered oxides plotted as a function of temperature. The theoretical fitting by the phonon-scattering theory is shown by the solid curves. Note that the theoretical curves are functions as the Debye temperature Θ_D and the boundary scattering length L (see text).

is given as the sum of three scattering rates as

$$\tau^{-1} = \tau_{pd}^{-1} + \tau_{ph-ph}^{-1} + \tau_0^{-1} = a\omega^4 + b\omega^2 + v/L \qquad (2)$$

where τ_{pd}^{-1} , τ_{ph-ph}^{-1} and τ_0^{-1} are the scattering rates for the point-defect scattering, the phonon-phonon scattering, and the boundary scattering, respectively. For a phonon frequency ω , the three scattering rates are written as $a\omega^4$, $b\omega^2$ and v/L, where a, b and L are characteristic parameters. According to Klemens [12], the coefficient a is calculated as

$$a = \Omega_0 \Sigma f_i (1 - M_i/M)^2 / 4v^3, \tag{3}$$

where Ω_0 is the unit cell volume, M_i and f_i are the mass

and the fraction of an atom, and $M = \Sigma f_i M_i$ is the average mass. Then *a* for Na_{0.07}MnO₂ can be calculated only by assuming that the Na ion and the vacancy make a solid solution, and *a* is calculated to be zero for LiCoO₂. As discussed in the previous paper [3], the temperature dependence of κ indicates negligibly small phonon-phonon scattering, and we safely assume b = 0. Consequently *v* and *L* are to be determined through fitting. Since *v* is related to Θ_D as

$$\Theta_D = \frac{\hbar v}{k_B} (6\pi^2 N)^{\frac{1}{3}}, \tag{4}$$

and thus we employed Θ_D instead of v as a fitting parameter (N is the number of atoms per unit cell).

The data fitting is satisfactory, as displayed in Fig.2 by the solid curves. Θ_D 's are fitted to be 300 K for $Na_{0.77}MnO_2$ and $LiCoO_2$, which are nearly equal to the value of 350 K for NaCo₂O₄ estimated from the specificheat measurement [13]. L's are fitted to be 0.2, 0.08, $0.003 \ \mu m$ for NaCo₂O₄, Na_{0.77}MnO₂ and LiCoO₂, respectively. It should be noted that L of LiCoO₂ is much shorter than the others. In this compound, we set a = b = 0 in Eq. (2), which means that only the boundary scattering dominates κ . Then L is reduced to be an "average" phonon mean free path ℓ in the sense of the classical argument $\kappa = Cv\ell/3$, where C is the phonon specific heat. From the very beginning, L is introduced as a phenomenological parameter, and cannot be evaluated from the first principle. The physical meaning of Lis to be explored theoretically, as other researchers also pointed out [5, 6].

In summary, polycrystalline samples of $Na_{0.77}MnO_2$ and LiCoO₂ are prepared, and the thermal conductivity is measured from 15 to 280 K. We have successfully fitted the experimental data with the phonon-scattering theory, and have found that the reduction of the thermal conductivity is mainly determined by the vacancy (point defect), not by the layered structure.

The authors appreciate Y. Iguchi, A. Satake, W. Kobayashi and R. Kitawaki for collaboration.

- For a review, see G. D. Mahan: Solid State Phys. 51 (1998) 81.
- [2] I. Terasaki, Y. Sasago, and K. Uchinokura: Phys. Rev. B 56 (1997) R12685.
- [3] K. Takahata, Y. Iguchi, D. Tanaka, T. Itoh, and I. Terasaki: Phys. Rev. B 61 (2000) 12551.
- [4] L. D. Hicks and M. S. Dresselhaus: Phys. Rev. B 47 (1993) 12727.
- [5] G. Chen: Phys. Rev. B 57 (1998) 14958.
- [6] M. V. Simkin and G. D. Mahan: Phys. Rev. Lett. 84 (2000) 927.
- [7] J. Callaway: Phys. Rev. 113 (1959) 1046.
- [8] J. Callaway and H. C. von Baeyer: Phys. Rev. **120** (1960) 1149.
- [9] Very recently Fujita, Mochida and Nakamura [Jpn. J. Appl. Phys. **40** (2001) 4644] measured κ for single crystals of NaCo₂O₄ which was unexpectedly high (400 mW/cm K at 300 K). They evaluated κ from thermal-diffusivity measurement, and other technique should be examined.
- [10] J. P. Parant, R. Olazcuaga, M. Devalette, C. Fouassier and P. Hagenmuller: J. Solid State Chem 3 (1971) 1.
- [11] C. Delmas, J-J. Braconner and P. Hagenmuller: Mat. Res. Bull. 17 (1982) 117.
- [12] P. G. Klemens: Phys. Rev. 119 (1960) 507.
- [13] Y. Ando, N. Miyamoto, K. Segawa, T. Kawata and I. Terasaki: Phys. Rev. B 60 (2000) 10580.