SUBMODELS OF THE SPECIAL COMPRESSIBLE FLUID ON TWO-DIMENSIONAL SUBALGEBRAS

1. Introduction

The differential equation of gas dynamic (EGD) are:

$$D = \partial_t + u \cdot \nabla$$
$$Du + \frac{1}{\rho} \nabla p = 0,$$
$$D\rho + \rho divu = 0,$$
(1)
$$DS = 0.$$

where u is speed, ρ is density, p is pressure, S is entrophy. These variables with the special state equation admit 11 parametrical algebra operators Lee L_{11} . In the Cartesian system of coordinates the L_{11} bases is the following [1, see also 2]:

$$\begin{split} X_1 &= \partial_x, \ X_2 = \partial_y, \ X_3 = \partial_z, X_4 = t\partial_x + \partial_u, \ X_5 = t\partial_y + \partial_v, \\ X_6 &= t\partial_z + \partial_w, \ X_7 = y\partial_z - z\partial_y + v\partial_w - w\partial_v, \\ X_8 &= z\partial_x - x\partial_z + w\partial_u - u\partial_w, \ X_9 = x\partial_y - y\partial_x + u\partial_v - v\partial_u, \ X_{10} = \partial_t, \\ X_{11} &= t\partial_t + x\partial_x + y\partial_y + z\partial_z, \end{split}$$

We considered the special state equation of the kind:

$$p = \pm \rho^{\gamma} + F(S), \tag{2}$$

where $+\rho^{\gamma}$ for $\gamma > 0$ and $-\rho^{\gamma}$ for $\gamma < 0$, $\gamma -$, F(S) is the function of entropy. It coordinates with the fixed state equation for the fluid at high pressures and high temperatures.

EGD with the equation (2) admit additional operators:

- stretching
$$X_{12} = t\partial_t - u\partial_u - v\partial_v - w\partial_w - (\overline{\gamma} - 2)\rho\partial_\rho - \overline{\gamma}p\partial_p$$
,
- carry $X_{13} = \partial_p$,

where $\overline{\gamma} = 2\gamma/(\gamma - 1), \ \gamma \neq 1.$

Together with L_{11} L they make up algebra Lee L_{13} .

In cylindrical coordinates (C) $x = (x, r, \theta), u = (U, V, W), y = r \cos \theta, z = r \sin \theta, u = U, v = V \cos \theta - W \sin \theta, w = V \sin \theta + W \cos \theta$ the basis of algebra L_{13} is the following: $X_1 = \partial_x, X_2 = \cos \theta \partial_r - \sin \theta r^{-1} (\partial_\theta + W \partial_V - V \partial_W), X_3 = \sin \theta \partial_r + \cos \theta r^{-1} (\partial_\theta + W \partial_V - V \partial_W), X_4 = t \partial_x + \partial_U, X_5 = \cos \theta (t \partial_r - \partial_V) - \sin \theta r^{-1} t (\partial_\theta + W \partial_V - (V - rt^{-1}) \partial_W), X_6 = \sin \theta (t \partial_r + \partial_V) + \cos \theta r^{-1} t (\partial_\theta + W \partial_V - (V - rt^{-1}) \partial_W), X_7 = \partial_\theta, X_8 = \sin \theta (r \partial_x - x \partial_r + V \partial_U - U \partial_V) + \cos \theta (W \partial_U - U \partial_W - xr^{-1} (\partial_\theta + W \partial_V - V \partial_W)), X_9 = -\cos \theta (r \partial_x - x \partial_r + V \partial_U - U \partial_V) + \sin \theta (W \partial_U - U \partial_W - xr^{-1} (\partial_\theta + W \partial_V - V \partial_W))$

 $X_{10} = \partial_t, X_{11} = t\partial_t + x\partial_x + r\partial_r,$

$$X_{12} = t\partial_t - U\partial_U - V\partial_V - W\partial_W - (\overline{\gamma} - 2)\rho\partial_\rho - \overline{\gamma}p\partial_p, X_{13} = \partial_p.$$

For algebra L_{13} all subalgebrus are listed [4], If

 $\gamma = -1, 1/3$ there are more subalgebrus than for any γ . We shall considers two-dimensional subalgebrus from optimum system for L_{13} , appering only when $\gamma = -1, 1/3$. We shall write out not similar two-dimensional subalgebrus for this purprose:

 $\begin{aligned} & 2.1'.X_1 + X_2, aX_4 + X_{13}, a(\overline{\gamma} - 1) = 0; \\ & 2.2'.X_{12}, aX_4 + X_{13}, a \neq 0; \\ & 2.3'.X_1 + X_{12}, aX_4 + bX_5 + X_{13}; \end{aligned}$

 $\begin{array}{l} 2.4'.-X_{11}+X_{12},X_1+aX_5+X_{13},a\neq 0;\\ 2.1''.aX_1+X_{12},X_{10}+X_{13},a\neq 0;\\ 2.5'.aX_7-bX_{11}+X_{12},X_1+X_{13},a\neq 0;\\ 2.6'.aX_7+bX_{11}+X_{12},cX_4+X_{13},c^2+(b+1)^2\neq 0\lor a^2+c^2\neq 0,c(\overline{\gamma}-1)=0;\\ 2.7'.X_1+aX_7+X_{12},bX_4+X_{13},a\neq 0;\ (3)\\ 2.8'.aX_7+X_{12},bX_4+X_{13},a\neq 0,b(\overline{\gamma}-1)=0;\\ 2.9'.aX_7-(\overline{\gamma}+1)X_{11}+X_{12},bX_4+X_{10}+X_{13},b(\overline{\gamma}-1)=0,\overline{\gamma}\neq 1;\\ 2.2''.bX_1+aX_7+X_{12},X_{10}+X_{13},b\neq 0;\\ 2.10'.aX_7+X_{10}-X_{11}+X_{12},bX_1+X_{13},b\neq 0;\\ \text{are for subalgebrus } 2.1'' \text{ and } 2.2'', \overline{\gamma}=-1\Rightarrow \gamma=1/3,\\ \text{for other subalgebrals } \overline{\gamma}=1\Rightarrow \gamma=-1,\\ \text{here parameters } a \text{ and } b \text{ which define set of series of dissimilar subalgebras.} \end{array}$

2. Proposal for the coordinates of the equation (2) with the fixed state equation

The equation (2) coordinates with the fixed state equation [5]

$$p = \Phi(\rho^{-1}) + Tf(\rho^{-1}), \tag{4}$$

for same implication functions F(S), $\Phi(\rho^{-1})$, $f(\rho^{-1})$. Where $\Phi(\rho^{-1})$ is describes the potential component of pressure, $Tf(\rho^{-1})$ is the describes the thermal components of pressure, ρ^{-1} – is the specific volume. The equation (4) describes behavior of the real environments, which by their properties approximate firm or fluid frames. It is possible with high pressure (about 10^9kg/cm^2) and high temperature (about $10^6 K$). Let us find the meanings F(S), $\Phi(\rho^{-1})$, $f(\rho^{-1})$.

Comparing $p_{-}(2)$, (4) and excluding T with the help of thermodynamics (ρ, S – are independent parameters) we receive the identity:

$$\pm \rho^{\gamma} + F(S) = \Phi(\rho^{-1}) + (G'_S - F'_S \rho^{-1}) f(\rho^{-1}), \ eqno(5)$$

where G(S) is determined by the additional experiment. After twice differenting by S:

$$0 = -F'_{S} - F''_{SS}Vf(V) + G''_{SS}f(V),$$
(6)

where $V = \rho^{-1}$.

1⁰. Let us $F_{SS} \neq 0$, then:

$$\frac{F'_S}{F'_{SS}} = -Vf(V) + \frac{G''_{SS}}{F''_{SS}}f(V).$$
(7)

Once again we differentiate on S and receive: $(\frac{F'_S}{F''_{SS}})' = (\frac{G''_{SS}}{F''_{SS}})'f(V)$. If $\frac{G''_{SS}}{F''_{SS}} \neq 0$, then, dividing by variables we have $f = \text{const} = f_0$ and after the integration we subtitle it in (7). We take the contradiction, that ρ, S are independing parameters.

Means $\frac{G_{SS}^{\prime\prime}}{F_{SS}^{\prime\prime}} = 0$, i.e.

$$G_{SS}'' = k_0 F_{SS}'', F_S' = k_1 F'' SS,$$
(8)

and from (7) follows, that $k_1 = -Vf(V) + k_0F(V)$.

The integration of (8) at $k_1 \neq 0$ and the substitution to (5) gives:

$$F(S) = k_1 k_2 e^{\frac{S}{k_1}} + k_3,$$

$$\Phi(\rho^{-1}) = \pm \rho^{\gamma} + k_3 - \frac{k_4 k_1}{k_0 - \rho^{-1}},$$

$$f(\rho^{-1}) = \frac{\rho k_1}{\rho k_0 - 1},$$

$$G(S) = k_0 k_1 k_2 e^{\frac{S}{k_1}} + k_4 S + k_5,$$
(9)

where k_j are the constants of integration.

2⁰. Let us $F_{SS} = 0$ (it is equivalent $k_1 = 0$). Then $F(S) = k_1 S + k_0$ and from (6) we receive (if $G''_{SS} \neq 0$) $\frac{k_1}{G''_{SS}} = f(V) = \text{const} = f_0$. Hence from (5) are follows:

$$\Phi(\rho^{-1}) = k_1 \rho^{-1} f_0 + k_0 - k_2 f_0 \pm \rho^{\gamma},$$

$$f(\rho^{-1}) = f_0,$$

$$G(S) = \frac{k_1}{2f_0} S^2 + G_1(S) + G_0,$$

(10)

where $G_0, G_1 = \text{const.}$

 3^0 . Let us $F_{SS} = 0$, $G_{SS} = 0$. Then from (7) follows, that $F_S = 0$, $F(S) = F_0$. And from (5) we shall receive:

$$\Phi(\rho^{-1}) = \pm \rho^{\gamma} + F_0 - G_1 f(\rho^{-1}),$$

$$G(S) = G_1(S) + G_0,$$
(11)

where F_0 , G_0 , G_1 are constants.

Thus, the state equation (2) coordinates with the equation (4), if the functions F(S), $f(\rho^{-1})$, $\Phi(\rho^{-1})$ are represents in one of kinds: (9), (10), (11).

3. Calculation of invariants

For construction the submodels of the special compressible fluid necessary to calculate invariants of the subalgebrus. [2, see also 1].

The algorithm of the calculation invariants consist in the following:

1. We select the system of coordinates, in witch calculates the invariants. If the subalgebra contains the operator X_7 of the rotation, it is convenient to choose cylindrical coordinates. If the operator of the rotation id not resent are convenient the cartesian coordinates.

2. We write out the operators of subalgebra in convenient system of coordinates from the list (3).

3. We enter the function h, which depends from 9 variables (t, x, u, ρ, p) as required invariants.

4. The function h is invariants of the subalgebra $L = \langle Y_1, Y_2 \rangle$ Only when any operators Y of subalgebra, working on invariants function, to annul it. Namely, $Y \cdot h = 0, Y \in L$. We shall work by the operator Y_1 of the basis subalgebra L on invariant function. In result we received the linear homogeneous equation with the partial derivatives of the 1-st order. For this equation we write the characteristic equation, the system of the ordinary differential equation [6]. Let us assume, that there is an obviously complete set functionally independent invariant (integrals) $I^k(t, x, u, \rho, p), k = 1..8$.

3

4. We write down the second operator of the basis through received invariants by the rule:

$$Y_2 = \xi^j \partial_{x^j} = \xi_j \frac{\partial I^k}{\partial x^j} \partial_{I^k} \tag{12}$$

5. We shall work by the stayed operator Y_2 on invariant function $h(I^k)$. We received the linear homogeneous equation with the partial derivatives of the 1-st order. We write down for it the equation of the characteristic. We find a complete set of invariants.

6. We pass to initial variable.

(

The received invariants (3) are shown into the table (see the appendix). Example:

As an example we shall consider the subalgebra 2.7' from (3): $Y_1 = X_1 + aX_7 + X_{12} = a\partial_{\theta} + t\partial_t - U\partial_U - V\partial_V - W\partial_W + \rho\partial_{\rho} - p\partial_p,$ $Y_2 = bX_4 + X_{13} = bt\partial_x + b\partial_U + \partial_p.$

Let us the invariant function $h(t, x, u, \rho, p)$, $x = (x, r, \theta)$, u = (U, V, W), satisfying to the equations $Y_1 \cdot h = 0$, $Y_2 \cdot h = 0$.

The second equation looks like $bth_x + bh_U + h_p = 0$.

Let us write down the equation of the characteristics:

$$\frac{dx}{bt} = \frac{dU}{b} = \frac{dp}{1} = \frac{dr}{0} = \frac{d\theta}{0} = \frac{dV}{0} = \frac{dW}{0} = \frac{d\rho}{0} = \frac{dt}{0}$$

We find integrals, which form a complete set functionally independent invariants : $t; \rho; W; V; \theta; r; U_1 = U - xt^{-1}; p_1 = p - x(bt)^{-1}.$

We shall receive $h_{1x} = 0$, when written down the second equation through invariants by a rule (12). Means $h = h_1(t, r, \theta, V, W, \rho, p_1, U_1)$.

The first equation looks like in new invariants for the known equations variable :

$$h_{1\theta} + th_{1t} + (-U + xt^{-1})h_{1U_1} - Vh_{1V} - Wh_{1W} + \rho h_{1\rho} + (-p + x(bt)^{-1})h_{1p_1} = 0;$$

Having written down the characteristic equation and having calculated integrals, we receive a complete set functionally independent invariants, which in initial variable look like :

$$r; \theta - a \ln|t|; Ut - x; Vt; Wt; \rho t^{-1}; pt - xb^{-1}.$$
(13)

4. Invariant submodels of the second rank

Two-dimentional subalgebra has 5 invariants. The invariant decision is exist if all required functions are defined from expressions for invariants. These invariants are nominated by new functions from others invariants for this purpose. Others invariants necessarily will be the functions of independent variables [2]. All unknown function are defined from the received equality. Thus, the representation of the invariant decision turns out, which is substituted to EGD. The system of the equations turn out which connect only invariants and new invariant functions as a result of the substitution under the theorem of the representation invariant variety [6]. The equations for invariants refers an invariant's submodel.

We shall write down an invariant submodel for the considered example.

We shall make equality from invariants (13): $\theta - a\ln|t| = \theta_1$, $Ut - x = U_1(r, \theta_1), Vt = V_1(r, \theta_1), Wt = W_1(r, \theta_1), \rho t^{-1} = \rho_1(r, \theta_1), pt - xb^{-1} = p_1(r, \theta_1).$ The representation of the invariants decision for S can be received from the state equation: $p = \pm \rho^{-1} + S \Rightarrow S = t^{-1}(x(b^{-1}) + S_1)$, where $S_1 = p_1 \pm \rho^{-1}$ replaced the state equation in the invariant submodel.

The statement in EGD results to the invariant submodel:

$$D_{1} = (W_{1}r^{-1} - a)\partial_{\theta_{1}} + V_{1}\partial_{r},$$

$$D_{1}U_{1} = -(\rho_{1}b)^{-1},$$

$$D_{1}V_{1} + p_{1r}\rho_{1}^{-1} = W_{1}^{2}r^{-1} + V_{1},$$

$$D_{1}W_{1} + p_{1\theta_{1}}(\rho_{1}r)^{-1} = W_{1} - V_{1}W_{1}r^{-1},$$

$$D_{1}\rho_{1} + \rho_{1}(V_{1r} + r^{-1}W_{1\theta_{1}}) = -\rho_{1}(2 + V_{1}r^{-1})$$

$$D_{1}S_{1} = -U_{1}b^{-1}.$$
(14)

Any invariant submodel can be resulted to the one of the two initial types by the choice invariants [7]:

- Evolutionary (time-*t* is the invariant of the subalgebra)

$$D = \partial_t + u_2 \partial_s,$$

$$Du_2 + b\rho_1^{-1} p_{1s} = a_1,$$

$$Dv_2 = a_2,$$

$$Dw_2 = a_3,$$

$$D\rho_1 + \rho_1 u_{2s} = a_4$$

$$DS_1 = a_5,$$

$$b > 0;$$

(15)

- Stationary

$$D = u_2 \partial_{x_1} + v_2 \partial y_1,$$

$$Du_2 + b_1 \rho_1^{-1} p_{1x_1} = a_1,$$

$$Dv_2 + b_2 \rho_1^{-1} p_{1y_1} = a_2,$$

$$Dw_2 = a_3,$$

$$D\rho_1 + \rho_1 (u_{2x_1} + v_{2y_1}) = a_4,$$

$$DS_1 = a_5,$$

$$b_1 > 0, : b_2 > 0;$$

(16)

here a_i, b, b_i is the coefficients of the initial types. From examining subalgebras (3) is received two submodels of the evolutionary type, and from others subalgebras is received ten submodels of the stationary type.

The canonical types of invariant submodels are tabulated (see appendix), where:

- 1-st column is the number of subalgebra,

- 2-nd column is the basic system of the coordinates in which considered the EGD,

- 3-rd column is the initial type: S is the stationary type, E is the evolutionary type,

in 4-th column are given invariants,

in 5-th column the factors of the initial type are written down.

The (14) implements to stationary initial type by replacement

 $\begin{aligned} r &= x_1, : \theta - a \ln|t|, : u_2 = V_1, : v_2 = (x_1)^{-1} W_1 + a, : w_2 = U_1 \text{ with factors: } a_1 = \\ u_2 + x_1(v_2 + a), : a_2 = (v_2 - a)(1 - 2u_2(x_1)^{-1}), : a_3 = 1 - (\rho b)^{-1}, a_4 = -\rho_1(u_2 x_1^{-1} + 2), : a_5 = (1 + w_2)b^{-1} + S_1, : b_1 = 1, : b_2 = x_1^{-2}. \end{aligned}$

The example of reduction subalgebra 2.9' to the canonical type.

The operators of the subalgebra are those:

 $Y_1 = aX_7 - 2X_{11} + X_{12},$

$$Y_2 = bx_4 + X_{10} + X_{13}, \ b(\overline{\gamma}) = 0, : \overline{\gamma} \neq -1.$$

Invariants from independent variables look like: $x_1 = (x - b2^{-1}t^2)r^{-1}$, $y_1 = \theta + a2^{-1}\ln|r|$. The representation of the invariant decision enters the name through the new invariant function: $V = V_1r^{\frac{1}{2}}$, $W = W_1r^{\frac{1}{2}}$, $\rho = \rho_1r^{-\frac{1}{2}}$, $p = p_1r^{\frac{1}{2}} + t$, $U = U_1r^{\frac{1}{2}} + bt$, where V_1, W_1, ρ, p_1, U_1 depends on x_1, y_1 .

The representation for entropy is defined from the state equation $S = S_1 r^{\frac{1}{2}} + t$, where $S_1 = p_1 \pm \rho_1^{-1}$.

The substitution to the EGD results the following invariant submodel:

$$\begin{split} D_1 &= (U_1 - x_1 V_1) \partial_{x_1} + (W_1 + a 2^{-1} V_1) \partial_{y_1}, \\ D_1 U_1 + \rho_1^{-1} &= -b - 2^{-1} V_1 U_1, \\ D_1 V_1 + \rho_1^{-1} (p_{1y_1} a 2^{-1} - p_{1x_1} x_1) &= W_1^2 - p_1 (2\rho_1)^{-1} - 2^{-1} V_1^2, \\ D_1 W_1 + \rho_1^{-1} p_{1y_1} &= W_1 V_1, \\ D_1 \rho_1 + \rho_1 (U_{1x_1} - V_{1x_1} x_1 + V_{1y_1} a (2r)^{-1} + W_{1y_1}) &= -3V_1 \rho_1 2^{-1}, \\ D_1 S_1 &= -1 - V_1 S_1 2^{-1}. \end{split}$$

The new invariant speeds are entered on expression for D_1 : $U_1 - x_1V_1 = u_2$, $: a2^{-1}V_1 + W_1 = v_2$, $W_1 - 2a^{-1}V_1 - x_1U_12a^{-1}$, with which we receive replacement: $x_2 = x_1^2 - ay_1$, $: y_2 = y_1 + 2^{-1}a \ln |x_1|, u_3 = 2x_1u_2 - av_2$, $: v_3 = (2x_1)^{-1}au_2 + v_2$. From which follows the system (16), where:

$$\begin{split} a_1 &= -2x_2b - V_1(x_2U_1 + 2x_2(U_1 - x_1V_1) - aW_1 + V_1x_2(\rho)^{-1}) + (2x_2 - a)(W_1^2 - p_1(2\rho_1)^{-1} - 2^{-1}V_1^2) + 2(U_1 - x_1V_1)^2, \\ a_2 &= (a(2x_2)^{-1} + 1)(W_1^2 - p_1(2\rho_1)^{-1} - 2^{-1}V_1^2) - ab(2x_2)^{-1} - aV_1U_1(4x_2)^{-1} + (2x_2)^{-1}a(U_1 - x_1V_1)V_1 - 2^{-1}ax_2^{-2} + W_1V_1, \\ a_3 &= W_1V_1 - 2a^{-1}(W_1^2 - p_1(2\rho)^{-1} - 2^{-1}V_1^2) + 2x_2a^{-1}(-b - 2^{-1}V_1U_1) + 2a^{-1}(U_1 - x_1V_1)U_1, \\ a_4 &= -\frac{5}{2}\rho_1V_1, \\ a_5 &= -1 - 2^{-1}V_1S_1, \\ b_1 &= (2x_2^22^{-1}a^2)^2 + 1 + 4x_2^2, \ b_2 &= \frac{a^2}{4x_2^2} + 1, \ p_1 &= \pm\rho_1^{-1} + S_1. \end{split}$$

The expressions for invariants are define the speed and the pressure, but it is impossible to define density (see table, appendix) for subalgebra 2.1" from optimum system (3) at a = 0. It is possible to build a regular partially invariant submodel in this case.

Let is give the definition to the regular partially invariant decisions generally.

Let us for algebra H are present $I_1, ..., I_k$ - invariants from independent variables and are present $J_1, ..., J_l$ - invariants from dependent variables. If from invariants

 $\mathbf{6}$

 $J_1, ..., J_l$ are defined all dependent variables, it is possible to build an invariant submodel of the rank k, nominating invariants J_j by functions from $(I_1, ..., I_k)$, i.e.

$$J_j = J_j(I_1, ..., I_k), j = 1, ..., l.$$
(17)

If it is impossible all dependent variables of invariants J_j , to define, then (17) gives the representation of the regular partially invariant decision of the rank k, and defect σ ,, which is equal to number not determined independent variables, i.e. $\sigma = m - l$, where m is the number of dependent variables.

For subalgebra 2.1'' the rank equal 3, the defect is equal 1.

Let us consider the subalgebra 2.1'' more in detail.

The operators of basis are those:

 $Y_1 = \partial_t + \partial_p,$

 $Y_2 = t\partial_t - \dot{u}\partial_u - v\partial_v - w\partial_w + 3\rho\partial_\rho + p\partial_p.$

Invariants from independent variables are : x, y, z. From others invariant, specified in the table, we receive the representation of the regular partially invariant decision.

$$u = \rho^{\frac{1}{3}} u_1(x, y, z), : p = t + \rho^{\frac{1}{3}} p_1(x, y, z), : \rho = \rho(t, x, y, z).$$
(18)

The substitution to the EGD, gives:

$$-\frac{1}{3}u_1(\rho_t + \rho^{-\frac{1}{3}}u_1 \cdot \nabla\rho) + \rho^{\frac{2}{3}}[(u_1 \cdot \nabla)u_1 + \nabla p_1] + \frac{1}{3}\rho^{-\frac{1}{3}}p_1 \cdot \nabla\rho = 0, \quad (19)$$

$$\rho_t + \frac{2}{3}\rho^{-\frac{1}{3}}u_1 \cdot \nabla \rho + \rho^{\frac{2}{3}}divu_1 = 0.$$
(20)

We shall received the representation of the decision for entrophy from the state equation $S = t + \rho^{\frac{1}{3}}S_1$, where $S_1 = p_1 - 1$.

The substitution to the equation DS = 0, gives:

$$\frac{1}{3}S_1\rho^{-\frac{2}{3}}(\rho_t + \rho^{-\frac{1}{3}}u_1 \cdot \nabla \rho) + u_1 \cdot \nabla S_1 + 1 = 0.$$
(21)

From (20) and (21) are follows:

$$\frac{u_1 \cdot \nabla \rho}{\rho} = -9 \frac{(1 + u_1 \cdot \nabla S_1)}{S_1} + 3 div u_1.$$

$$\tag{22}$$

Then it is possible to find ρ_t from the (21):

$$\frac{1}{\rho}\rho_t = 3\rho^{-\frac{1}{3}} [-divu_1 + 2S_1^{-1}(u_1 \cdot \nabla S_1 + 1)] \equiv \rho^{-\frac{1}{3}} B(x).$$
(23)

Replacing p_1 on $S_1 + 1$ and substituting (23), (22) to the (19) we receive:

$$\frac{1}{\rho} \cdot \nabla \rho = \left[-\frac{1}{S_1} u_1 (1 + u_1 \cdot \nabla S_1) - \nabla S_1 - (u_1 \cdot \nabla) u_1 \right] \frac{3}{S_1 + 1} \equiv A(x).$$
(24)

By the substitution (24) to (22), we exclude ρ :

$$\left(\frac{u_1^2}{S_1+1}-3\right)\left(u_1\cdot\nabla S_1+1\right)+\frac{S_1}{S_1+1}\left(u_1\cdot\nabla\right)\left(S_1+\frac{1}{2}{u_1}^2\right)=0.$$

Equating the mixed derivative functions $\ln \rho$ from (23), (24), we receive $\nabla B = \frac{1}{3}BA$, rotA = 0. From the last equality follows, that $A = \nabla \varphi$ and $\nabla (3\ln B - \varphi) = 0 \Rightarrow 3lnB - \varphi = 0 \Rightarrow B = e^{\frac{1}{3}\varphi}$. From (24) follows $\rho = b(t)e^{\varphi}$. Then from (21) we receive $b' = b^{\frac{2}{3}}$.

The integration gives $b = (\frac{t}{3})^3$, where constant of the integration is made by zero with the help of carries on t and on p, admitted by EGD.

So, density as $\rho = t^3 \rho_1(x, y, z)$, i.e. is the representation of the invariant decision for one-dimensional subalgebra Y_2 .

Thus, the is a reduction of the partially invariant decision to the invariants:

$$(u_{1} \cdot \nabla)u_{1} + \rho_{1}^{-1} \cdot p_{1} = u_{1},$$

$$u_{1} \cdot \nabla \rho_{1} + \rho_{1} divu_{1} = -3\rho_{1},$$

$$u_{1} \cdot S_{1} = -S_{1},$$
(25)

where $S_1 = p_1 - \rho_1^{\frac{1}{3}}, S = tS_1$.

Literature

[1] Ovsyannikov L.V. Group properties of differential equations. - Novosibirsk: SO AN SSSR, 1962. - 240 p.

[2] Ovsyannikov L.V. Group analysis of differential equations. - M.: Nauka, 1978. - 400 p.

[3] Khabirov S.V. The invariant decisions of the rank 1 in gas dynamics // Works of the international conference "Modeling, calculation, designing in conditions of uncertainty". - Ufa: USATU, 2000, P. 104-115.

[4] Khabirov S.V. The optimum systems of the subalgebras, admitted by the equations of gas dynamics. - Ufa: Institute of the mechanics USC of RAS, 1998.-33.

[5] Stanukovich K.P. The unsteady movements of continous environment. - M.: GITTL, 1955. - 804 p.

[6] Gunter N.M. The integration first order partial differential equations. - L.M.: GTTI, 1934. - 359 p.

[7] Khabirov S.V. The reduction of invariant submodel gas dynamics to canonical form // Mat. Zametki. - 1999. - V. 66. - N. 3. - pp. 439 - 444.

Appendix

2.1'. C.S.: D, Type: S; Invariants: $y, z, tv, tw, tu - x + \ln |t|, \rho t^{-1}, tS - xa^{-1} + a^{-1} \ln |t|;$ Submodel (16): $a_1 = u_2, a_2 = v_2, a_3 = 1 - (a\rho_1)^{-1}, a_4 = -2\rho_1, a_5 = S_1 + a^{-1}(1 - w_2), b_1 = b_2 = 1;$ 2.2'. C.S.: D, Type: S; Invariants: $y, z, tv, tw, tu - x, \rho t^{-1}, tS - xa^{-1};$ Submodel (16): $a_1 = u_2, a_2 = v_2, a_3 = -(a\rho_1)^{-1}, a_4 = -2\rho_1, a_5 = S_1 + a^{-1}w_2, b_1 = b_2 = 1;$ 2.3'. C.S.: D, Type: S; Invariants: $x - ayb^{-1} - \ln |t|, z, tu - ab^{-1}tv - 1, tw, ab^{-1}(tu - ayb^{-1} - 1) + tv - y, \rho t^{-1}, tS - ya^{-1};$

Submodel (16): $a_1 = u_2 + a(b^2\rho_1)^{-1} + 1, a_2 = v_2\rho_1, a_3 = ab^{-1}(u_2 + 1) - (b\rho_1)^{-1}, a_4 = -3\rho_1, a_5 = S_1 - ba^{-2}w_2 + a^{-1}u_2, b_1 = a^2b^{-2} + 1, b_2 = 1;$ 2.4'. C.S.: D, Type: E;

Invariants: $t, z^{-1}(y - atx), z^{-1}(v - ax - atu - sw), z^{-1}[(a^2t^2 + s^2)(v - ax) + atu + sw], z^{-1}((a^2t^2 + s^2)w + s(v - ax) - atsu)\rho z, z^{-1}(S - x);$

Submodel (15): $a_1 = -2(1 + a^2t^2 + S^2)^{-1}[u_2(a^2t^2 - stu_2) + w_2(tu_2 - s)] = at(\rho_1)^{-1} - sp_1(\rho_1)^{-1}, a_2 = (1 + a^2t^2 + s^2)^{-1}[2av_2 - u_2a^3t^2 - 2asw_2 + (v_2 + u_2)(2a^2t + su_2) - w_2v_2 + sv_2u_2 + w_2u_2 + s(u_2)^2] + at(\rho_1)^{-1} - sp_1(\rho_1)^{-1}, a_3 = (\rho_1)^{-1}(p_1(1 + a^2t^2 + ats) + (1 + a^2t^2 + s^2)^{-1}[2a^2t^2w_2 - (w_2 - su_2)^2t - 2sv_2 + as^2w_2] + (u_2)^2, a_4 = -2\rho((w_2 - su_2)(1 + a^2t^2 + s^2)^{-1}, a_5 = [w_2(S_1 - s) + v_2 - u_2(a^2t + S_1s)](1 + a^2t^2 + s^2)^{-1}, b = (1 + a^2t^2 + s^2), p_1 = \rho_1^{-1} + S_1;$

2.5'. C.S.: D, Type: E;

Invariants: $t, \theta + a \ln |t|, r^{-1}(aV + W), r^{-1}U, ar^{-1}(Wa - V), pr, r^{-1}(S - x);$ Submodel (15): $a_1 = -a(\rho_1)^{-1}(S_1 + (\rho_1)^{-1}) + (a(a^2 + 1))^{-1}(w_2^2 - a^2w_2^2 + 2u_2w_2, a_2 = -(\rho_1)^{-1} - v_2(a(a^2 + 1))^{-1}(au_2 - w_2), a_4 = -\rho_1(a(a^2 + 1))^{-1}(a_2u_2 - w_2), a_5 = -v_2, b = a^2 + 1;$