

A Bayesian Estimator for Linear Calibration Error Effects in Thermal Remote Sensing

J. A. Morgan
The Aerospace Corporation
P. O. Box 92957
Los Angeles, CA 90009

Abstract—

The Bayesian Land Surface Temperature estimator previously developed has been extended to include the effects of imperfectly known gain and offset calibration errors. It is possible to treat both gain and offset as nuisance parameters and, by integrating over an uninformative range for their magnitudes, eliminate the dependence of surface temperature and emissivity estimates upon the exact calibration error.

Keywords— Remote Sensing, Land Surface Temperature, Sea Surface Temperature.

I. INTRODUCTION

As a practical matter, land surface temperature (LST) estimates retrieved from radiances reported by a remote sensor will be subject to some unavoidable level of calibration error, which need not be very accurately known. While all forms of quantitative exploitation of radiometric data in remote sensing are afflicted to some degree by calibration error effects, this problem may be a special concern for the Bayesian multiband LST algorithm [1]. That is because the Bayesian algorithm iterates on a range of plausible surface temperatures, within which the estimated LST value is obtained as an expected value. Should uncompensated calibration errors lead to a temperature interval which does not bracket the true surface temperature, the algorithm in its present form has no way to recover, and may return a surface temperature estimate with degraded accuracy.

This note sketches the extension of the Bayesian approach to LST retrieval to include effects of a simple form of unknown calibration error. After a review of the Bayesian approach to LST retrieval, the calibration error is parameterized as linear in the true aperture radiance. The joint prior probability for the calibration error parameters is then obtained by imposing the requirement that two distinct observers agree on its mathematical form. Finally, the Bayesian LST estimator is extended to include linear calibration error by treating the calibration error parameters as nuisance variables, and integrating them out of the final estimators for surface temperature and emissivity.

II. ELEMENTS OF BAYESIAN LST ESTIMATOR

The Bayesian land surface temperature retrieval algorithm is developed in [1], which may be consulted for details. The approach to LST retrieval presented in that earlier paper consists of three elements:

1. The forward model for sensor aperture radiance, assumed linear in surface emissivity:

$$I_F(k) = \epsilon_k B_k(T) \exp\left(-\frac{\tau_k}{\mu}\right) + \frac{\rho_k}{\pi} F_k^\downarrow(0) \exp\left(-\frac{\tau_k}{\mu}\right) + I_k^\uparrow(\tau, \mu) \quad (1)$$

$I_k^\uparrow(\tau, \mu)$ and $F_k^\downarrow(0)$ are the upwelling diffuse radiance at nadir optical depth τ (top of the atmosphere, or TOA, for spaceborne sensors; μ is the cosine of the angle with respect to zenith) and the downwelling irradiance at the surface, respectively. $B_k(T)$ is the Planck function at surface temperature T . The emissivity is ϵ_k , and the surface reflectance $\rho_k = 1 - \epsilon_k$. Note that (1) assumes Khirchoff's law; this is done solely for simplicity. It is also assumed (at least initially) that the sensor has high spectral resolution.

2. The MAXENT form of the conditional probability of observing radiance I [2],[3],[4] in the presence of noise-equivalent radiance σ :

$$P(I | T, \epsilon_k, \sigma) = \exp\left[-\frac{(I - I_F)^2}{2\sigma^2}\right] \frac{dI}{\sigma} \quad (2)$$

3. The prior probability of surface temperature and emissivity [1]:

$$P(T, \epsilon_k | K) = \frac{\text{const.}}{T} dT d\epsilon_k \quad (3)$$

The posterior probability for the surface temperature and emissivity, given observed radiance and available knowledge, is obtained from these quantities by use of Bayes' theorem:

$$P(T, \epsilon_k | I, K) \propto P(T, \epsilon_k | K) P(I | T, \epsilon_k, \sigma). \quad (4)$$

III. CALIBRATION ERROR MODEL

By hypothesis, the physical radiance I_0 at wavenumber k is related linearly to the reported radiance I :

$$I_0 = (1 + \alpha)I + \beta \quad (5)$$

Both α and β are assumed to be small quantities;

$$\alpha \ll 1 \quad (6)$$

and

$$\beta \ll I_0 \quad (7)$$

It is the physical radiance I_0 which goes into (1). Recalling that the forward model (1) is linear in ϵ , the exponent in that expression is

$$(I_0 - I_F)^2 = (((1 + \alpha)I + \beta) - (A\epsilon + B))^2 \quad (8)$$

which is quadratic in α , β , and ϵ .

IV. PRIOR PROBABILITY FOR CALIBRATION ERROR PARAMETERS

In order to obtain a useable estimator, it is necessary to find the prior probability for the calibration error parameters α and β [5],[6],[7]. As in [1], two equally cogent observers must relate their descriptions of radiance, and of calibration error, by a Lorentz transformation [8],[9] connecting one (primed) coordinate description moving with velocity v along the observation axis with respect to the other (unprimed) one by

$$k' = \eta k \quad (9)$$

where the Doppler factor η is given in terms of the boost parameter

$$\gamma = \frac{1}{\sqrt{1 - (v/c)^2}}. \quad (10)$$

by

$$\begin{aligned} \eta &\equiv \gamma(1 - v/c) \\ &= \sqrt{\frac{1 - v/c}{1 + v/c}} \end{aligned} \quad (11)$$

The quantity η is real and nonvanishing for physical Lorentz transformations. Let

$$P(\alpha, \beta | K) = g(\alpha, \beta) d\alpha d\beta \quad (12)$$

be the prior probability assigned by Vladimir in the unprimed frame, and

$$P(\alpha', \beta' | K) = h(\alpha', \beta') d\alpha' d\beta' \quad (13)$$

be that assigned by Estragon, viewing radiance in the primed frame. The prior probabilities in the two frames are related by

$$h(\alpha', \beta') d\alpha' d\beta' = J^{-1} g(\alpha, \beta) d\alpha d\beta \quad (14)$$

where

$$J = \det \left[\frac{\partial(\alpha', \beta')}{\partial(\alpha, \beta)} \right] \quad (15)$$

is the Jacobian determinant for the transformation.

Consider first α as defined by Vladimir. Suppose that $\beta = 0$; then by the Lorentz invariance properties of spectral radiance [10] we have

$$\frac{I_0(k)}{k^3} = \text{invariant} = \frac{(1 + \alpha)I(k)}{k^3} \quad (16)$$

and also

$$\frac{I(k)}{k^3} = \text{invariant} \quad (17)$$

if Vladimir and Estragon are to agree that the quantity $I(k)$ admits interpretation as a radiance. The ratio

$$\frac{(1 + \alpha)I(k)}{I_0(k)} = \frac{\frac{(1 + \alpha)I(k)}{k^3}}{\frac{I_0(k)}{k^3}} \quad (18)$$

is likewise invariant, so that

$$1 + \alpha = \text{invariant}, \quad (19)$$

as it must be, as the ratio of two radiances evaluated in the same Lorentz frame. Thus

$$\alpha'(k') = \alpha(k) = \alpha(k') \quad (20)$$

Next consider β . We have

$$\frac{(1 + \alpha)I + \beta}{k^3} = \text{invariant} \quad (21)$$

from which

$$\frac{\beta}{k^3} = \text{invariant} \quad (22)$$

as must be for any radiance, in particular a noise radiance. By (9) we find

$$\beta'(k') = \beta'(\eta k) = \eta^3 \beta(k) \quad (23)$$

The Jacobian is therefore

$$\det \left[\frac{\partial(\alpha', \beta')}{\partial(\alpha, \beta)} \right] = \eta^3 \quad (24)$$

so Vladimir and Estragon must agree that

$$g(\alpha, \beta) d\alpha d\beta = \eta^3 h(\alpha', \beta') d\alpha' d\beta' \quad (25)$$

and, by the principle of indifference [1],[5], that

$$g(\alpha, \beta) = \eta^3 g(\alpha, \eta^3 \beta) \quad (26)$$

with solution

$$g(\alpha, \beta) d\alpha d\beta = \frac{\text{const.}}{\beta} d\beta d\alpha \quad (27)$$

Application of Bayes' theorem (4), as in [1], immediately gives the result that the joint posterior probability of T , ϵ , α , and β is proportional to the product of (2), (3), and (27):

$$P(T, \epsilon, \alpha, \beta, \sigma | I, K) \propto \exp \left[-\frac{(I - I_F)^2}{2\sigma^2} \right] d\epsilon \frac{dT}{T} d\alpha \frac{d\beta}{\beta} \frac{dI}{\sigma}. \quad (28)$$

V. EXTENDED LST ESTIMATOR

Estimators for T and ϵ may be constructed from (28) as expectation values in exactly the same manner as in [1]. The treatment of spectral quantities integrated over a pass-band follows the equivalent discussion in [1]. In practice, (28) will be unaltered for band-integrated radiances.

The calibration error parameters α and β are treated as nuisance parameters: One does not care what their actual values are, so long as they lie between specified limits. One is therefore at liberty to integrate (28) over those limits and obtain estimators for

$$\langle T \rangle = \frac{\int_{T_{min}}^{T_{max}} TP(T | I_i, \sigma) \frac{dT}{T}}{\int_{T_{min}}^{T_{max}} P(T | I_i, \sigma) \frac{dT}{T}} \quad (29)$$

and

$$\langle \epsilon_i \rangle = \frac{\int_{\epsilon_{min}}^{\epsilon_{max}} \epsilon P(\langle T \rangle, \epsilon | I_i, \sigma) d\epsilon}{\int_{\epsilon_{min}}^{\epsilon_{max}} P(\langle T \rangle, \epsilon | I_i, \sigma) d\epsilon} \quad (30)$$

in terms of

$$P(T, \epsilon | I, \sigma) = \int_{\alpha_{min}}^{\alpha_{max}} \int_{\beta_{min}}^{\beta_{max}} P(I | T, \epsilon, \alpha, \beta, \sigma) d\alpha \frac{d\beta}{\beta} \quad (31)$$

and

$$P(T | I, \sigma) = \int_{\epsilon_{min}}^{\epsilon_{max}} \int_{\alpha_{min}}^{\alpha_{max}} \int_{\beta_{min}}^{\beta_{max}} P(I | T, \epsilon, \alpha, \beta, \sigma) d\epsilon d\alpha \frac{d\beta}{\beta}. \quad (32)$$

In (29) and (30), $\langle T \rangle$ and $\langle \epsilon \rangle$ have no dependence on exactly what the calibration error parameters α and β were, for a given reported sensor aperture radiance.

It does not appear feasible to integrate moments of (28) in closed form. However, by integrating over ϵ first, it is possible to take advantage of the closed-form result for the LST posterior probability derived in [1]:

$$P(T | I, \sigma) \propto \frac{1}{\sqrt{a}} \exp \left[-\frac{[c - b^2/4a]}{2\sigma^2} \right] H(\epsilon_{max}, \epsilon_{min}) \quad (33)$$

where

$$H(\epsilon_{max}, \epsilon_{min}) = \operatorname{erf} \left[\frac{\sqrt{a/2}(\epsilon_{max} + b/2a)}{\sigma} \right] - \operatorname{erf} \left[\frac{\sqrt{a/2}(\epsilon_{min} + b/2a)}{\sigma} \right] \quad (34)$$

for each band i . As in [1],

$$a = \left[\int_{k_1}^{k_2} \left(B_k(T) - \frac{1}{\pi} F_k^\downarrow(0) \right) \exp\left(-\frac{\tau_k}{\mu}\right) dk \right]^2, \quad (35)$$

$$b = b_1 b_2 \quad (36)$$

with

$$b_1 = 2 \left[\int_{k_1}^{k_2} \left(B_k(T) - \frac{1}{\pi} F_k^\downarrow(0) \right) \exp\left(-\frac{\tau_k}{\mu}\right) dk \right] \quad (37)$$

$$b_2 = \left[\int_{k_1}^{k_2} \left(\frac{1}{\pi} F_k^\downarrow(0) \exp\left(-\frac{\tau_k}{\mu}\right) + I_k^\uparrow(\tau, \mu) \right) dk - I_i \right], \quad (38)$$

and

$$c = \left[\int_{k_1}^{k_2} \left(\frac{1}{\pi} F_k^\downarrow(0) \exp\left(-\frac{\tau_k}{\mu}\right) + I_k^\uparrow(\tau, \mu) \right) dk - I_i \right]^2 \quad (39)$$

In (33), as in (28), the sensor radiance that appear in the quantities a , b , and c is related to the physical radiance by (5).

The remaining integration over the nuisance variables α and β is now two-dimensional, and any integration over T to form the expectation value $\langle T \rangle$ makes for a third quadrature, for the full calculation. This is potentially awkward for routine evaluation, but the computational burden can be alleviated in special cases:

1. If one knows *a-priori* that one is operating in a regime dominated by either gain or offset calibration error, the less important source of error may be ignored as a first approximation.

2. In a vicarious calibration, the surface temperature may be accurately known.

3. Once a value for $\langle T \rangle$ is obtained for one pixel in a dataset, expectation values $\langle \alpha \rangle$ and $\langle \beta \rangle$ can be calculated and used in estimation of $\langle T \rangle$ for other pixels. Should calibration error be slowly varying, estimates of $\langle \alpha \rangle$ and $\langle \beta \rangle$ obtained from one dataset could be used for subsequent ones, or as initial guesses for updated estimates of $\langle \alpha \rangle$ and $\langle \beta \rangle$.

REFERENCES

- [1] Morgan, J. A., "Bayesian Estimation for Land Surface Temperature Retrieval: The Nuisance of Emissivities," arXiv:physics/0402099, 2004
- [2] Bretthorst, L., *Bayesian Spectral Analysis and Parameter Estimation*, Dissertation, Washington University, St. Louis, MO, 1987
- [3] Bretthorst, L., "Bayesian Spectrum Analysis and Parameter Estimation," in Berger, J., S. Fienberg, J. Gani, K. Krickenberg, and B. Singer, Eds, *Lecture Notes in Statistics*, **48**, Springer-Verlag, New York, 1988
- [4] Bretthorst, L., "Excerpts from Bayesian Spectrum Analysis and Parameter Estimation," in Erickson, G. J., and C. R. Smith, *Maximum-Entropy and Bayesian Methods in Science and Engineering, Volume 1: Foundations*, Kluwer, Dordrecht, 1988, pp. 75-145
- [5] Jaynes, E., "Prior Probabilities," *IEEE Trans. on Systems Science and Cybernetics*, vol. SSC-4, pp. 227-241, 1968
- [6] Jaynes, E., "The Well-Posed Problem," *Found. Physics* **3**, pp. 477-493, 1973
- [7] Jaynes, E., "Marginalization and Prior Probabilities," in *Bayesian Analysis in Econometrics and Statistics*, A. Zellner, Ed., North-Holland Publishing Co.: Amsterdam, 1980
- [8] Misner, C. W., K. S. Thorne, and J. A. Wheeler, *Gravitation*, Freeman: San Francisco, 1973
- [9] Weinberg, S., *Gravitation and Cosmology*, John Wiley and Sons: New York, 1972
- [10] Misner, C. W., K. S. Thorne, and J. A. Wheeler, *Gravitation*, Freeman: San Francisco, pp. 587-589, 1973