arXiv:q-bio/0312019v3 [q-bio.MN] 16 May 2004 [arXiv:q-bio/0312019v3 \[q-bio.MN\] 16 May 2004](http://arxiv.org/abs/q-bio/0312019v3)

Topological Generalizations of network motifs

N. Kashtan^{1,2}, S. Itzkovitz^{1,3}, R. Milo^{1,3}, U. Alon^{1,3}

¹*Department of Molecular Cell Biology*

²*Department of Computer Science and Applied Mathematics* ³*Department of Physics of Complex Systems,*

Weizmann Institute of Science, Rehovot, Israel 76100

Biological and technological networks contain patterns, termed network motifs, which occur far more often than in randomized networks. Network motifs were suggested to be elementary building blocks that carry out key functions in the network. It is of interest to understand how network motifs combine to form larger structures. To address this, we present a systematic approach to define 'motif generalizations': families of motifs of different sizes that share a common architectural theme. To define motif generalizations, we first define 'roles' in a subgraph according to structural equivalence. For example, the feedforward loop triad, a motif in transcription, neuronal and some electronic networks, has three roles, an input node, an output node and an internal node. The roles are used to define possible generalizations of the motif. The feedforward loop can have three simple generalizations, based on replicating each of the three roles and their connections. We present algorithms for efficiently detecting motif generalizations. We find that the transcription networks of bacteria and yeast display only one of the three generalizations, the multi-output feedforward generalization. In contrast, the neuronal network of *C. elegans* mainly displays the multi-input generalization. Forward-logic electronic circuits display a multi-input, multi-output hybrid. Thus, networks which share a common motif can have very different generalizations of that motif. Using mathematical modelling, we describe the information processing functions of the different motif generalizations in transcription, neuronal and electronic networks.

PACS numbers: 05, 89.75

I. INTRODUCTION

A major current challenge is to understand the function of biological information-processing networks [\[1,](#page-11-0) [2](#page-11-1), [3](#page-11-2), [4,](#page-11-3) [5](#page-11-4), [6,](#page-11-5) [7,](#page-11-6) [8](#page-11-7), [9,](#page-11-8) [10,](#page-11-9) [11](#page-11-10), [12,](#page-11-11) [13](#page-11-12)]. These networks, as well as networks from engineering, ecology, and other fields, were recently found to contain network motifs: small subgraphs that occur in the network far more often than in randomized networks [\[14](#page-11-13), [15\]](#page-11-14). Each class of networks was found to have a characteristic set of network motifs [\[16\]](#page-11-15). Information processing networks, such as gene regulation networks [\[15,](#page-11-14) [17\]](#page-11-16), neuron networks, and some electronic circuits, were found to share many of the same network motifs [\[14,](#page-11-13) [16](#page-11-15)]. Recently, in the case of the transcription network of the bacterium E. coli, network motifs were shown theoretically and experimentally to function as elementary building blocks of the network, each performing specific information-processing tasks [\[15,](#page-11-14) [18](#page-11-17), [19](#page-11-18)]. For example, one of the most significant motifs shared by biological information processing networks is the feedforward loop (FFL). In transcription networks, the feedforward loop with positive regulations was shown to act as a 'persistence detector' circuit that rejects transient activation signals yet allows rapid response to inactivation signals [\[15,](#page-11-14) [18,](#page-11-17) [19\]](#page-11-18). A second motif, the single-input module, was shown to generate a temporal order of gene expression, which correlates with the functional order of the genes in the pathway [\[21,](#page-11-19) [22](#page-11-20)]. A third major motif, the bifan, which is the building block of dense arrays of overlapping regulation,

performs hard-wired combinatorial decisions governed by the input functions of the output genes [\[23,](#page-11-21) [24](#page-11-22), [25\]](#page-11-23).

Here, we address the question of whether a given network motif appears independently in the network or whether instances of the motif combine to form larger structures [\[20\]](#page-11-24). If the latter occurs, what is the function of these larger structures? Do different networks that share a certain network motif also share the same structural combinations of that motif? These questions require analysis of large subgraphs, a computationally difficult problem [\[26,](#page-11-25) [27,](#page-11-26) [28,](#page-11-27) [29\]](#page-11-28). Recently, efficient algorithms for counting subgraphs based on sampling have been introduced [\[27\]](#page-11-26). These algorithms can at present be effectively used to detect motifs of up to 7-8 nodes. To go beyond this requires an approach to efficiently define and detect large structures whose architecture is based on a given motif.

To address these issues, we present an approach for uniting related groups of motifs of different sizes into families termed *motif generalizations*. This allows generalizing from small motifs to the larger complexes in which they appear. We present an efficient algorithm to detect motif generalizations. We find that networks that share the same motif can have different generalizations of that motif. For example, we find different generalizations of the FFL motif in transcription, neuronal and electronic networks. Using mathematical models we analyze the information-processing functions of the FFL generalization that is selected in each of these networks.

FIG. 1: a. A directed 3-node subgraph (triad) b. This triad has two roles. c. Roles in all the 13 types of connected triads. In each triad there are between one and three roles.

II. RESULTS

A. Node Roles in a subgraph

We begin by defining *roles* of nodes in a subgraph. A group of nodes in a subgraph share the same role if there is a permutation of these nodes, together with their corresponding edges, that preserves the subgraph structure (See APPENDIX A for formal definitions). For example, in the v-shaped subgraph in Fig. 1a, nodes b and c can be permuted leaving the structure intact, whereas nodes a and b cannot. Thus, this subgraph has two roles, role 1 and role 2 (Fig. 1b). The FFL has three roles (Fig. 1c, triad 6), whereas the 3-loop (Fig 1c, triad 7) has only one role (because a cyclic permutation of the three nodes preserves its structure). The thirteen possible connecteddirected triads have between one and three roles each (Fig. 1c), with a total of 30 different roles.

B. Subgraph Topological Generalizations

We now define subgraph topological generalizations based on node roles. Subgraph topological generalizations are extensions of a subgraph to a family of larger subgraphs which share its basic structure. Consider the FFL (Fig. 2a). For this 3-node subgraph we define three simple generalizations to the level of 4 nodes (Fig. 2b).

In each simple generalization a single role and its connections are duplicated. In the first simple generalization, the X role and its connections are duplicated. This generalization is termed double-X FFL or double-input FFL. The other two generalizations are obtained by duplicating the Y or Z roles. This replication process can be continued, leading to higher-order motif generalizations, the multi-X (multi-input), multi-Y and multi-Z (multioutput) FFL generalizations (Fig. 2c).

More complex generalizations can be obtained by replicating more than one of the roles. For example, duplicating both the X and Z roles yields five-node generalizations (Fig 2d). When replicating more than one role (and in some cases replicating even a single role), one can define two kinds of generalizations: in strong generalizations, every X,Y,Z triplet forms a FFL. In weak generalizations, every node participates in at least one FFL, but not all possible FFLs are formed (Fig. 2d).

This procedure of generalization can be applied to any subgraph (see formal definition in APPENDIX B). For example simple generalizations of the 4-node bi-fan are shown in Fig. 2e-g. We now describe the statisticalsignificance of the generalizations of the motifs found in various networks.

FIG. 2: a. The feedforward loop triad has three roles: X (input node), Y (internal - secondary input) node and Z (output node) b. 4-node simple generalizations of the feedforward loop. The X node is duplicated to form the double-X generalization. The Y and Z nodes are duplicated to form the double-Y and double-Z generalizations respectively. c. Simple multi-node generalizations of the FFL. d. Strong and weak generalization rules. A 5-node generalization of the FFL with two X nodes, one Y node, and two Z nodes. In the strong generalization every combination of a X,Y,Z triplet of nodes forms a FFL. e. The bi-fan, a 4-node motif with two roles X (input role) and Y (output role). f. 5-node simple generalizations of the bi-fan. In each of the two generalizations one of the two roles is duplicated. g. Simple multi-node generalization of the bi-fan: an X or Y node is replicated to form the multi-input or multi-output bi-fan generalization respectively.

FIG. 3: Statistical significance of motif generalizations. The cumulative number of multi-Z FFLs in the real network (black) and randomized networks - mean ± SD (grey) in a. *E. coli* transcription network. b. *S. cerevisiae* transcription network. c. The cumulative number of multi-X FFLs in the real and randomized networks (mean ± SD) in the *C. elegans* neuronal network.

Generalization	Subgraph size	Transcriptional Networks		Neurons	Electronic chips
		E. coli	yeast	C. elegans	S ₁₅₈₅₀
basic bi-fan	4 (2X.2Y)	$+$ (N=209)	$+$ (N=1812)	$+$ (N=126)	$+$ (N=1040)
multi output	5(2X,3Y)	$+$ (N=264)	$+$ (N=14857) $+$ (N=152)		$+$ (N=1990)
	6 $(2X, 4Y)$	$+$ (C=0.015)	$+$ (C=3.5)	$+(C=0.17)$	$+$ (C=0.28)
multi input	5(3X,2Y)	$+$ (N=20)	$+$ (N=81)	$+$ (N=25)	$+$ (N=226)
	6 $(4X, 2Y)$	$-(N=0)$	$+$ (N=14)	$+(C=0.015)$	$+$ (C=0.001)
equal multi input-outputs	6(3X.3Y)	$+$ (N=6)	$+$ (N=21)	$-$ (N=0)	$+$ (N=301)

TABLE I: Bi-fan generalizations in different networks. (aX,bY) represents the multiplicity of each of the roles in the generalization (Fig. 2g). '+': Statistically significant generalizations, '-': non-significant generalizations. Number of appearances (N), or concentration $(x10^{-3})$ (C) [\[27\]](#page-11-26) are listed.

C. Network Motifs Topological Generalizations

While enumerating all subgraphs of a given size is a difficult task, enumerating generalizations of a given subgraph can be performed efficiently by an algorithm described in APPENDIX C. The algorithm is based on using the appearances of the basic subgraph as nucleation points for a search for its generalizations. As an example, we applied this algorithm to networks in which the FFL and bi-fan are motifs, to ask whether any of the possible FFL or bi-fan generalizations occur significantly in the networks (APPENDIX C). In the transcription networks of E . *coli* [\[15\]](#page-11-14) and S . *cerevisiae* [\[14\]](#page-11-13) we find that the multi-Z FFL generalization is highly significant (Fig. 3a,b). The other two possible simple generalizations are not significant (in the E. coli network, multi-X's and multi-Y's do not occur at all, in the S. cerevisiae network both appear only twice). An example of a multi-Z FFL in the E. coli transcription network, the maltose utilization system, is shown in Fig. 4a. In each multi-Z FFL, the different genes (Z roles) share a common biological function (as shown in tables 2 and 3 that list all multi-Z FFL complexes in the E. coli and S. cerevisiae networks).

In the network of synaptic connections between

neurons in C. elegans [\[14](#page-11-13), [30,](#page-11-29) [31](#page-11-30)], we find a different FFL generalization: the multi-X FFL (Fig. 3c). This structure occurs 29 times in the network, with upto 4 inputs. Multi-Y and multi-Z FFLs are found in far smaller numbers (double-X's and double-Y's FFL appear 3 times each) [\[32\]](#page-11-31). An example of a multi-X FFL in the locomotion control circuit of C. elegans is shown in Fig. 4b.

In networks of connections between logic gates in forward-logic electronic chips [\[14,](#page-11-13) [33](#page-12-0), [34\]](#page-12-1) we find no simple generalization of the FFL. These electronic circuits do, however, show a complex FFL generalization - a structure with two Xs, a single Y and two Zs (a weak generalization, Fig. 4c). In the five forward-logic electronic chips we have analyzed, 70 percent to 100 percent of the FFLs are embedded in instances of this 5-node structure.

The most prominent 4-node network motif in these networks is the bi-fan [\[14](#page-11-13)] (Fig. 2e). The bi-fan has two roles and therefore two simple generalizations (Fig. 2g). We find that both simple generalizations of the bifan (multi-output and multi-input) are significant in the transcription, neuronal and electronic networks (Table 1). The multi-output bi-fan generalizations are more significant and the maximal Y multiplicity is higher than

FIG. 4: The FFL generalizations found in biological and technological networks. a. An example of a three-Z FFL in the transcription network of *E. coli*, maltose utilization system. The activator CRP senses glucose starvation, MalT senses maltotriose, and malEFG, malK and malS participate in maltose metabolism and transport. b. An example of a double-X FFL in the locomotion neural circuit of *C. elegans*. AVA and AVD are ventral cord command interneurons. AVD functions as modulator for backward locomotion. AVA functions as driver cell for backward locomotion. ASH and FLP are head sensory neurons sensitive to noxious chemicals and nose touch. c. A generalized form of the FFL $(2X,Y,2Z)$ found in forward-logic electronic chips. This 5-node structure appears as a part of a 6-node module, which implements XOR (Exclusive OR) using 4 NAND gates. d. Truth table of the circuit described in c (a (2X,Y,2Z) FFL generalization with additional NAND gate at the output). There are 2 input bits X1 and X2 and a single output bit which is equal to (X1 XOR X2).

the maximal X multiplicity in all these networks. In these networks we find structures of multi-output bi-fan with 10 Ys and more, while multi-input bi-fan do not exceed 6 input X nodes.

D. Functions of multi-output FFL generalization in transcription networks

The function of the FFL depends on the signs of the interactions (positive or negative regulation), on their strengths and on the functions that integrate multiple inputs into each node. In the case of positive regulation, the 3-node FFL has been shown to function as a persistence detector [\[15\]](#page-11-14): it filters out short input stimuli to X, and responds only to persistent signals. On the other hand, it responds quickly to OFF steps in the input to X [\[15,](#page-11-14) [18\]](#page-11-17). With other sign combinations, the 3-node FFL can function as a pulse-generator or response accelerator [\[18,](#page-11-17) [35\]](#page-12-2). These functions apply to a wide range of interaction strengths, and to both AND and OR-like input functions.

Here, we studied the functions of the generalizations of the FFL. We begin with the multi-output FFL, which is the generalization that is significant in transcription networks. The multi-output FFL has a single input node X, a single internal node Y (secondary input) and a number of output nodes $Z_1...Z_m$ (Fig. 2c,4a). The arrows in the FFL diagram should be assigned numbers representing the strength of the interaction of the transcription factors (TFs) X and Y with the promoters of the various Z-genes [\[21](#page-11-19)]. These numbers correspond to the activation or repression coefficients of each gene (the concentration of the TF required for 50 percent effect [\[5,](#page-11-4) [21,](#page-11-19) [36](#page-12-3)]). Here, we consider for simplicity the most common case, that of FFLs with positive regulation [\[18\]](#page-11-17). We employ a simple model of the dynamics of this circuit [\[15](#page-11-14)]. $X(t)$ is the activity of the transcription factor X, $Y(t)$ of Y, $Z_j(t)$ is the concentration of the gene product Z_j . The dynamics of transcription factor Y and the output gene products Z_i is given by

$$
dY/dt = F(X, T_{yx}) - \alpha Y
$$

$$
dZ_j/dt = F(X, T_{z_jx})F(Y, T_{z_jy}) - \alpha Z_j
$$

Where α is the protein lifetime [\[37](#page-12-4), [38\]](#page-12-5) and T_{yx} , $T_{z_1x}, T_{z_2x}, T_{z_1y}, T_{z_2y}$ are the activation thresholds of the various genes (Fig. 5a). For simplicity we use a sharp activation function, $F(U,T) = 1$ if $U > T$ and 0 otherwise. The qualitative results apply also to Michaelis-type activation functions. These equations can be solved analytically, yielding piecewise exponential dynamics in response to step like activation profiles of X. We find that the multi-output FFL can encode a temporal order of expression of the Z genes, by means of different activation thresholds $T_{z_i y}$ for each of the output genes (Fig. 5a,b). This temporal ordering feature is shared with another common network motif, the single-input module [\[15,](#page-11-14) [21](#page-11-19), [22\]](#page-11-20). Indeed, high resolution expression measurements on the flagella multi-output FFL (in $E.$ coli) showed that the class 2 flagella genes, which are regulated by a feedforward loop, are activated in a temporal order that corresponds to the functional order of the gene product in the assembly of the flagellar motor [\[39](#page-12-6), [40\]](#page-12-7).

The timing of activation of gene j following a step activation of X is

FIG. 5: Kinetics of a double-output FFL generalizations following pulses of stimuli. a. A double-output FFL with positive regulation and AND-logic input function for Z_1 and Z_2 . Numbers on the arrows are activation thresholds. b. Simulated kinetics of the double-output FFL in response to a short pulse and a long pulse of X activity. The dashed and dotted horizontal lines represent the activation thresholds T_{z_1y} and T_{z_2y} . $\alpha = 1$ was used.

$$
\tau_j = -\alpha^{-1} \ln(1 - T_{z_j y}/Y_{max})
$$

The rise time of the different genes can be tuned by T_{z_jy}/Y_{max} , where Y_{max} is the maximal concentration of Y. Note that $T_{z_j y}$ can be easily tuned during evolution , for example by mutations in the binding site of Y in the Z_j promotor [\[25](#page-11-23), [40\]](#page-12-7). The Z gene with the lowest activation threshold is turned on first after the stimulation of X. Furthermore, the multi-Z FFL can act as a persistence detector for all of the output genes (Fig. 5b): the Z genes are expressed only if the input stimulus to X is present for a long enough time. The minimal time that a saturating X stimulus needs to be present to activate gene j is equal to τ_i . Thus this FFL generalization preserves the functionality of the original FFL motif. The turn-off order of the Z genes upon a gradual decay of X activity can be separately controlled by the activation coefficients of the X TF, T_{z_ix} [\[40](#page-12-7)]. Thus different turn on and turn off orders of the Z_j genes can in principle be achieved. In summary, the multi-output FFL preserves the functionality of the simple FFL, and in addition can encode temporal expression programs among the different Z genes.

E. Functions of multi-input FFL generalization in neuronal networks

A different FFL generalization, multi-input FFL, is found in the neuronal network of C. elegans. In general, the function of this circuit depends on the signs on the arrows and on two input-functions (gates): one input function integrates the multiple X inputs to Y, and the other integrates the inputs from Y and $X_1...X_m$ to Z. (Fig. 6a)

We analyzed the dynamics of one possible two-input FFL, where the input-function governing the Y node is an OR gate, X_1 OR X_2 , and the input-function of the Z node is Y AND $(X_1 \t{OR } X_2)$ (Fig. 6a,b,c). This choice of input-functions ensure that both Y and either X_1 or X_2 are needed for Z to be activated to a level that allows activation of its downstream (post synaptic) neurons or muscle cells (as is the case, for example, in the circuit of Fig. 4b, in which ablation of the neuron AVD results in loss of sensory input to the neuron AVA [\[41\]](#page-12-8)). These input functions could in principle be implemented by simple neurons which integrate weighted inputs. The input function of Z , for example, represents strong synapses from Y and weaker ones from X_1 and X_2 . It is important to note that the simplest equations that describe transcription networks also describe neurons with graded potential and no spiking (as C. elegans neurons are thought to be [\[42,](#page-12-9) [43\]](#page-12-10)). In the case of neurons, $X_i(t)$, $Y(t)$ and $Z(t)$

FIG. 6: Kinetics of a double-input FFL generalization following pulses of stimuli. a. A double-input FFL. Input functions for Y and Z, and the activation thresholds, are shown as gates and numbers on the arrows. b. Simulated kinetics of the twoinput FFL, with short well-separated stimuli pulses of X_1 and X_2 , followed by a persistent X_1 stimulus. c. Simulated kinetics of the double-input FFL, with short X_1 stimulus followed rapidly by a short X_2 stimulus pulse. The dashed horizontal line corresponds to the activation thresholds for Y, T_{zy} . $\alpha = 1$ was used.

represent neuron membrane potentials. The activation dynamics of the circuit in Fig. 6a are

$$
dY/dt = F(X_1 + X_2, T_{yx}) - \alpha Y
$$

$$
dZ/dt = F(Y, T_{zy})[F(X_1 + X_2, T_{zx})] - \alpha Z
$$

Here α is the relaxation rate of the neurons' membrane potential, and the synaptic activation thresholds are $T_{yx}, T_{zx}, T_{zy}.$

This model shows that the circuit can act as a persistence detector for both X_1 and X_2 (Fig. 6b). In the locomotion neuronal circuit example (Fig 4b), the FFL circuit could elicit backward motion only if the stimulation of one of the sensory neurons is longer than a threshold duration τ determined by the parameters of the circuit.

$$
\tau = -\alpha^{-1} \ln(1 - T_{zy}/Y_{max})
$$

A transient stimulation would not be enough to elicit backward motion. Furthermore, we find that sufficiently closely spaced short pulses of X_1 and X_2 can elicit a response, even if each pulse alone can not (Fig. 6c). This highlights a 'memory-like' function of Y, which can store information from recent stimulations over its relaxation time. In the basic 3-node FFL, Y can store information about recurring pulses of X. In the multi-input FFL, Y can store information from multiple inputs (Fig. 6c gives an example), and increase sensitivity to one input if the other input has recently been detected. Generally, if the summed input of the input-nodes X_j to node Y is $S(t) = F(x_1 + x_2, T_{yx}),$ Z is activated when Y activity exceeds the threshold T_{zy}

$$
Y(t) = e^{-\alpha t} \int_0^t S(t') e^{\alpha t'} dt' > T_{zy}
$$

(where $Y(t = 0) = 0$), showing that node Y effectively integrates the inputs over a time scale of $1/\alpha$.

F. Function of FFL generalization in electronic chips

Forward-logic electronic chips are networks in which nodes represent logic gates. These circuits are optimized to perform a hard-wired logical function between input and output nodes. Forward-logic chips, taken from an engineering database (ISCAS89), were previously found to display the FFL network motif [\[14](#page-11-13)]. Here we find that they display a specific generalization of the FFL, with two input and two output nodes (Fig. 4c). Analyzing the appearances of this pattern, we find that this 5-node generalized FFL motif is part of a commonly used engineering module built of 4 NAND gates, which implements XOR (exclusive OR) logic on the two inputs [\[44\]](#page-12-11) (see truth table in Fig. 4d).

III. DISCUSSION

This study presented a systematic approach for defining and detecting generalizations of network motifs. Motif generalizations are families of subgraphs of different sizes which share a common structural theme, and which appear significantly more often in the network than in randomized networks. The generalizations are produced by replicating nodes in a basic motif structure. The generalizations often preserve the functionality of the network motif on which they are based, because they preserve the roles of nodes in the motif (for example, by replicating input or output nodes). We presented an efficient algorithm for detecting motif generalizations. We find that different networks which display the same motifs can show very different generalizations of these motifs. We also demonstrated using simple models that these generalized motifs can carry out specific information processing functions. These functions can in principle be tested experimentally in transcription and neuronal systems.

The two sensory transcription networks, from a prokaryote (E. coli) and a eukaryote (S. cerevisiae), showed the same generalization of the FFL: both networks display the multi-output FFL generalization [\[15,](#page-11-14) [20\]](#page-11-24). The other two generalizations, multi-input and multi-Y, are not found significantly in these transcription networks. Multi-output FFL complexes are found throughout the transcription networks in diverse systems (tables 2,3). The X role is usually a global transcription factor which controls many genes, the Y role is usually a 'local' transcription factor which controls specific systems, and the Z nodes are the regulated genes which share a specific function. Often, multi-output FFLs in E. coli that respond to specific stimuli have a non-homologous multi-output FFL counterpart in yeast which responds to similar stimuli. The fact that the genes in these circuits are not evolutionary related, whereas their connectivity patterns are the same in the two organisms, suggests convergent evolution to the same regulation pattern [\[14,](#page-11-13) [45\]](#page-12-12). Examples include systems that respond to carbon limitation, drugs, and nitrogen starvation in both organisms (tables 2,3). Multi-output FFLs can also appear in systems that make up a protein machine, for example, a multi-output FFL in E. coli controls genes whose products make up

the flagellar basal-body motor [\[39](#page-12-6)] (X=flhDC, Y=fliA, Z= class 2 flagella genes). We find that the multi-output FFL can serve as a persistence detector for all the outputs. In addition it can generate temporal orders of output gene expression [\[40\]](#page-12-7).

A different FFL generalization, the multi-input FFL, is found in the neuronal synaptic wiring of C. elegans. This network is found to chiefly display the multi-input FFL (Fig. 2c), and not the other two generalizations. The multi-input FFL has a number of input nodes $X_1...X_m$, a single internal node Y (secondary input) and a single output node Z. As an example we have mentioned the backward locomotion control circuit of the worm. This circuit is governed by two ventral-cord command interneurons AVD and AVA [\[41,](#page-12-8) [42\]](#page-12-9). These two neurons are linked in a multi-input FFL with several input neurons, such as ASH and FLP (Fig. 4b), which are head sensory neurons sensitive to nose touch and noxious chemicals [\[41](#page-12-8), [42\]](#page-12-9). This circuit implements an avoidance reflex, eliciting backward motion in response to head stimulation. We find that the multi-input FFL can serve as a persistence detector for each input. In addition, it can serve as coincidence detector for weak inputs, firing only if short stimuli from two or more different inputs occur within a certain time of each other.

A different FFL generalization, with two inputs and two outputs, appears in a class of electronic circuits. This motif generalization functions within a XOR gate. This demonstrates that network motifs and their generalizations can be used to detect basic functional building block of a network without prior knowledge.

Motif generalizations cover a substantial portion of the high-order motifs in various biological and technological networks we have studied. However, motifs generalizations in the present form do not cover all possible types of families of structures that share similar architectural themes. It would be important to find additional rules for defining families of motifs beyond the current notion of motif generalization by role replication. Motifs and their generalizations can help us understand the design principles of complex networks by defining functional building blocks whose function can be tested experimentally.

To summarize, this study presented topological generalizations of network motifs, and an efficient algorithm to detect them. We found motif generalizations in several real-world networks. Networks that share the same motif were found to exhibit different generalizations of that motif. We demonstrated theoretically that the generalized motifs in biological networks can carry out informationprocessing functions.

Acknowledgments

We thank all members of our lab for discussions. We thank NIH, Israel Science Foundation and Minerva for support. N.K. was supported by Ernst and Anni Deutsch-Promotor Stiftung foundation for an MSc fellowship. R.M. was supported by Horowitz complexity science foundation PhD fellowship.

APPENDIX A: ROLES IN A SUBGRAPH - FORMAL DEFINITION

We classify nodes in a subgraph into structurally equivalent classes. Each class represents a role. The measure of structural equivalence that we use here is automor-phic equivalence [\[46](#page-12-13), [47,](#page-12-14) [48,](#page-12-15) [49](#page-12-16), [50](#page-12-17)]. Let $S = (V_s, E_s)$ be a subgraph, then an automorphism is a one-to-one mapping, τ , from V_s to V_s , such that $(v_i, v_j) \in E_s$ if and only if $(\tau(v_i), \tau(v_j)) \in E_s$. Two nodes v_i and v_j are automorphically equivalent if and only if there is some automorphism, τ , that maps one of the nodes to the other $(\tau(v_i) = v_j)$. For each subgraph S, we classify all its n nodes into roles by examining structural equivalence of all possible pairs of the nodes. By the transitivity of automorphic equivalence, we are guaranteed to get a partition of the nodes into distinct roles. This concept can be readily generalized for networks with weights on the edges or with different types of nodes.

APPENDIX B: SUBGRAPH GENERALIZATION - FORMAL DEFINITION

Let S be the basic subgraph where $r_1..r_L$ are the set of roles of S with multiplicity $(d_1, ..., d_L)$ respectively. simple generalization of S is a subgraph which is formed by replication of a single role r_i and its edges to preserve the roles connectivity of S. Note that in a simple generalization only a single role is replicated. A generalized form of a subgraph is defined by a $\text{pair}(M, V^L)$ where M is an $L \times L$ image matrix, which describes the connectivity between roles. $M[i, j] = 1$ if there is an edge between role i and j (i is not equal to j), and $M[i, j] = 0$ otherwise. $M[i, i] = 0$ if there is no edge between every two nodes of role i, $M[i, i] = 1$ if there is a single edge, and $M[i, i] = 2$ if there is a mutual edge. $V^L \in N^L$ is an Ldimensional vector which defines the multiplicity of each role. The FFL which is an example of a basic subgraph, is represented by $(M_{FFL},(1,1,1))$ where

$$
\mathbf{M_{FFL}} = \begin{pmatrix} 0 & 1 & 1 \\ \hline 0 & 0 & 1 \\ \hline 0 & 0 & 0 \end{pmatrix}
$$

and the vector $(1, 1, 1)$ describes the roles multiplicity: in the basic FFL each of the three roles X,Y,Z appears once. A FFL with two output nodes is represented by

the pair $(M_{FFL}, (1, 1, 2))$. A FFL with m output nodes (m Z-role nodes) is represented by $(M_{FFL},(1, 1, m))$ (Fig. 2c). Such a generalization has only one degree of freedom - the multiplicity of the Z role in the structure. There are cases, such as multiplicity of more than one role, where we need additional definition in order to distinguish between different types of structures. For this we define the generalization rule r. We define two possible generalization rules: a strong generalization rule and a weak generalization rule. An example of a strong and weak $(M_{FFL}, (2, 1, 2))$ generalization is illustrated in Fig 2d. If S is the basic n-node subgraph with set of L roles represented by the multiplicity vector $(d_1, ..., d_L)$ then a basic n-node set is every set of n nodes in the structure that consists of d_i nodes of role i (for all $1 \leq i \leq L$). For example every set of three nodes in the multi output FFL, consisting of the X node, Y node and one of the Z role nodes, is a *basic n-node set*. A strong generalization rule, r_s , requires that every *basic n-node set* in the structure forms the basic subgraph S. A weak generalization rule, r_w , requires that every node in the structure participates in at least one basic n-node set (Fig. 2d). Note that weak generalization can represent more than one unique structure of a given size.

APPENDIX C: ALGORITHM FOR MOTIF GENERALIZATIONS DETECTION

We begin by finding the network motifs (significant subgraphs) of size n (usually $n=3-4$) in the network as described in [\[14,](#page-11-13) [15\]](#page-11-14)(application and source code are available at [http://www.weizmann.ac.il/mcb/UriAlon/\)](http://www.weizmann.ac.il/mcb/UriAlon/). For each motif, for each of its roles, we prepare a list of all the nodes that play that role. We perform a search for all of the generalizations of each motif using its appearances in the network as starting point. This search reduces computation time and enables the detection of significant generalization forms of the basic motifs, which are beyond reach using algorithms that attempt to enumerate all subgraphs of a given size.

In order to compute the statistical significance of a certain generalization of a motif S, we first find for each appearance of S in the network the maximal size generalization in which it appears. Then we count the cumulative number of times S appears in the union of all the maximal generalizations (up to size k). In order to verify that the generalization significance is not due to many stand-alone appearances of the basic subgraph (e.g. a single-Z FFL in the case of multi-Z FFL generalization), we subtract the number of time S appears as a stand-alone structure in the network from the cumulative results (Note that in Fig 3 we show the results before subtractions). We compare these numbers to the corresponding numbers in randomized networks (Here we used $Zscore > 2$). It is important to note that the randomized networks preserve the incoming,

Complex	Id. X		Y	Ζ	Function
size					
	$\mathbf{1}$	arcA	appY	appCBA	Anaerobic/stationary phase
	$\overline{2}$	crp	fucPIKUR	fucAO	Fucose utilization
	3	crp	$f_{\rm HF}$	cirA	Iron citrate uptake
	$\overline{4}$	crp	galS	mgIBAC	Carbon utilization
$\mathbf{1}$	5	crp	malI	malXY	Maltose utilization
	6	crp	melR	melAB	Melibiose utilization
	7	hns	fthDC	fliAZY	Flagella regulation
	8	metJ	metR	metA	Methionine biosynthesis
	9	omp R-envZ	csgDEFG	csgBA	Osmotic stress response
	10	crp	caiF	caiTABCDE	Carnitine metabolism
				fixABCX	
	11	crp	nagBACD	manXYZ	Carbon utilization
				nagE	
$\overline{2}$	12	himA	omp R-envZ $ompC$		Osmotic stress response
				ompF	
	13	rpoN	fhlA	fdhF	Formate hydrogen lyase system
				hycABCDEFGH	
	14	rpoN	glnALG	glnHPQ	Nitrogen utilization
				nac	
3	15	crp	malT	m al EFG	Maltose utilization
				$malk-lamB-malM$	
				mals	
	16	crp	arac	araBAD	Arabinose utilization
				araE	
				arafGH	
				araJ	
$\overline{4}$	17	rob	marRAB	$f \text{um} C$	Drug resistance
				nfo	
				sodA	
				zwf	
5	18	fthDC	fliAZY	flgBCDEFGHIJK	Flagella system
				flhBAE	
				fliE	
				fliFGHIJK	
				fliLMNOPQR	
$\overline{7}$	19	fnr	arcA	cydAB	Anaerobic metabolism
				cyoABCDE	
				$focA-pfIB$	
				glpACB	
				icdA	
				nuoABCDEFGHIJKLMN	
				sdhCDAB-b0725-sucABCD	

TABLE II: Feedforward loops in E. coli transcription network classified into multi-Z complexes. Complex size is the number of operons (Z-role nodes) in the FFL generalization

outgoing and mutual edge degree for each node. The networks are not constrained to have the same number of 3-node or higher subgraphs as in the real network (in [\[14\]](#page-11-13) in contrast, 4-node motifs were detected based on randomized networks that preserved 3-node subgraph counts).

The network is described by a directed interaction graph $G = (V, E)$, where V is the set of nodes and E is the set of edges. An edge $(v_i, v_j) \in E$ represents a directed link between nodes v_i and v_j . For every n-node subgraph S which is detected as a network motif [\[14,](#page-11-13) [15](#page-11-14)] we search for its simple generalizations (multiplicity

of one of the roles). We begin by building an induced graph $G' = (V', E')$. The nodes in G' are only those that act as members (nodes) of S appearances in G , and the edges are only the edges in G between these nodes. G' is usually a much smaller graph then G , but it contains all the information we need for our purpose. For each simple generalization type j (multiplicity of the j-th role of the subgraph) the following is performed: A non-directed graph $\hat{G} = (\hat{V}, \hat{E})$ is built where each node represents a specific basic subgraph S in G (a specific set of nodes in G that form a subgraph of type S). The number of nodes in \hat{G} equals the number of times S appears in the original graph G . Two nodes in \hat{G} are

Complex	Id.	Х	Y	Ζ	Function
size					
	$\mathbf{1}$	TUP1	RME1	IME1	Meiosis
	$\overline{2}$	RIM101	IME1	$\rm{DIT1}$	Sporulation
	3	MIG1	HAP2-3-4-5	CYC1	Formation of apocytochromes
	$\overline{4}$	MIG1	GAL4	GAL1	Galactokinase
$\mathbf{1}$	5	MIG1	CAT ₈	JEN1	Lactate uptake
	6	MIG2	CAT ₈	JEN1	$(2X-FFL$ complex)
	7	GAT1	DAL80-GZF3	GAP1	Nitrogen utilization
	8	TUP1	ALPHA1	MFALPHA1	Mating factor alpha
	9	GAL11	ALPHA1	MFALPHA1	$(2X-FFL$ complex)
	10	TUP ₁	ROX1	ANB1	Anaerobic metabolism
				CYC7	
	11	GLN3	GAT1	GAP1	Nitrogen utilization
				GLN1	Glutamate synthetase
$\overline{2}$	12	GLN3	GAT1	DAL ₈₀	Nitrogen utilization
				GLN1	Glutamate synthetase
	13	GLN3	DAL80-GZF3	GAP1	Nitrogen utilization
				UGA4	
	14	PDR1	YRR1	$\mathrm{SNQ2}$	Drug resistance
				YOR1	
	15	GCN4	MET4	MET16	Methionine biosynthesis
				MET17	
	16	HAP1	ROX1	ERG11	Anaerobic metabolism
				HEM13	
3				$_{\mathrm{CYC7}}$	
	17	SPT16	SWI4-SWI6		Cell cycle and
				CLN1 CLN2	
				HO	mating type switch
					Leucine and branched amino
	18	GCN4	LEU3	ILV1	
				ILV2	acid biosynthesis
				ILV5	
$\overline{4}$				LEU4	
	19	UME ₆	$INO2-INO4$	CHO ₁	Phospholipid biosynthesis
				CHO ₂	
				INO1	
				OPI3	
6	20	PDR1	PDR ₃	HXT11	Drug resistance
				HXT9	
				IPT1	
				PDR5	
				SNQ2	
				YOR1	
15	21	GLN3	DAL ₈₀	CAN1	Nitrogen utilization
				DAL1	
				DAL2	
				DAL3	
				DAL ₄	
				DAL5	
				DAL7	
				DCG1	
				DURI	
				DUR ₃	
				GDH1	
				PUT1	
				PUT2	
				PUT4	
				UGA1	

TABLE III: Feedforward loops in S. cerevisiae transcription network classified into multi-Z complexes. Complex size is the number of genes (Z-role nodes) in the FFL generalization.

connected if and only if they follow the generalization type, j, and the generalization rule (strong or weak). Setting the edges in \hat{G} is done efficiently by using the appearances of the basic subgraph in G' as starting points. For each specific 'starting point' subgraph S_1 in G' we pass through all the 'neighboring' subgraphs S_2 ('neighboring' in the sense that they share all node roles excluding j-th node roles) and check if the joint subgraph $(S_1 \cup S_2)$ in G' forms a generalization type j. After setting all edges in \hat{G} , the next step is to find all maximal cliques [\[51\]](#page-12-18) (a group of nodes in which every two are connected) in \hat{G} . Each maximal clique represents a maximal generalization type j of S (i.e. the generalization with maximal number of appearances of the basic subgraph). We store the size and the members (nodes in the original network) of all maximal generalizations. Complex generalizations (when more than one role is replicated) were detected in a similar way by appropriately changing the rules for setting the edges in \tilde{G} .

APPENDIX D: NETWORK DATABASES

- [1] L.H. Hartwell, J.J. Hopfield, S. Leibler, and A.W. Murray, Nature 402: C47-52 (1999).
- [2] C.A. Ouzounis and P.D. Karp, Genome Res. 10: 568-576 $(2000).$
- [3] H. McAdams and A. Arkin, Curr. Biol. 10: R318-320 $(2000).$
- [4] M.B. Elowitz, and S. Leibler, Nature 403:335-338 (2000).
- [5] M.A. Savageau, Chaos 11: 142-159 (2001).
- [6] C.V. Rao and A.P. Arkin, Annu. Rev. Biomed. Eng. 3: 391-419 (2001).
- $\left[7\right]$ S.H. Strogatz, Nature $\bf{410:}$ $\bf{268{\text -}276}$ $\bf{(2001)}.$
- [8] H. Bolouri and E.H. Davidson Bioessays 24:1118-1129 (2002).
- [9] J. Hasty, D. McMillen, and J.J. Collins Nature 420: 224- 230 (2002).
- [10] C.C. Guet, M.B. Elowitz, W. Hsing, and S. Leibler, Science 296: 1466-1470 (2002).
- [11] J.J. Tyson, K.C. Chen, and B. Novak, Curr. Opin. Cell Biol. 15: 221-231 (2003).
- [12] S. Maslov. K. Sneppen, Science 296(5569):910-3 (2002).
- [13] M. Newman, SIAM Review 45: 167-256 (2003).
- [14] R. Milo, S. Shen-Orr, S. Itzkovitz, N. Kashtan, D. Chklovskii, and U. Alon, Science 298: 824-827 (2002).
- [15] S. Shen-Orr, R. Milo, S. Mangan, and U. Alon, Nat. Genet. 31: 64-68 (2002).
- [16] R. Milo et. al. Science **303**: 1538-1542 (2004).
- [17] T.I. Lee et. al. Science **298**: 799-804 (2002).
- [18] S. Mangan and U. Alon, Proc. Natl. Acad. Sci. U S A. 100(21):11980-5 (2003)

[19] S. Mangan, A. Zaslaver, and U. Alon, J. Mol. Biol. 334(2):197-204 (2003).

chips in the database.

<http://www.weizmann.ac.il/mcb/UriAlon/> was based on selected data from [\[14,](#page-11-13) [52\]](#page-12-19) and literature. Transcription network of yeast (S. cere*visiae*) [\[14](#page-11-13)], version 1.3 (N=685, E=1052) available at<http://www.weizmann.ac.il/mcb/UriAlon/> was based on selected data from [\[14](#page-11-13), [53\]](#page-12-20). (N=number of nodes, E=number of edges). Self edges were excluded. The Neuronal synaptic connection network of C. elegans $(N=280, E=400)$ was based on [\[30\]](#page-11-29) as arranged in [\[31](#page-11-30)]. The network was compiled with a cutoff of at least 5 synapses for connections between neurons. Target muscle cells were excluded. Electronic forward-logic chips [\[14](#page-11-13)] were obtained by parsing the ISCAS89 benchmark data set [\[33](#page-12-0)] available at www.cbl.ncsu.edu/CBL Docs/iscas89.html . Bi-fan generalizations data (Table 1) are shown for chip S15850 $(N=10383, E=14240)$, and are representative of all logic

- [20] R. Dobrin, Q.K.Beg, A.L. Barabasi, Z.N. Oltvai, BMC Bioinformatics 5(1):10 (2004).
- [21] M. Ronen, R. Rosenberg, B.I. Shraiman, and U. Alon, Proc. Natl. Acad. Sci. U S A. 99: 10555-10560 (2002).
- [22] A. Zaslaver, A. Mayo, M. Surette, N. Rosenberg, P. Bashkin, H. Sberro, M. Tsalyuk, and U. Alon, Nat. Genet. **36**(5): 486-91 (2004).
- [23] C.H. Yuh, H. Bolouri, and E.H. Davidson Science 279: 1896-1902 (1998).
- [24] N. Buchler, U. Gerland, and T. Hwa, Proc. Natl. Acad. Sci. U S A. 100: 5136-5141 (2003).
- [25] Y. Setty, A.E. Mayo, M.G. Surette, and U. Alon, Proc. Natl. Acad. Sci. U S A. 100(13):7702-7 (2003).
- [26] S. Itzkovitz, R. Milo, N. Kashtan, G. Ziv, and U. Alon. Phys Rev. E 68: 026127 (2003).
- [27] N. Kashtan, S. Itzkovitz, R. Milo, and U. Alon, Bioinformatics, advance access '10.1093/bioinformatics/bth163' (2004).
- [28] J. Nesetril and S. Poljak, Commen. Math. Univ. Carol. 26: 415-419 (1985).
- [29] F. Harary, and E.M. Palmer, *Graphical Enumeration*. (Academic Press, NY, 1973).
- [30] J. White, E. Southgate, J. Thomson, and S. Brenner, Phil. Trans. Roy. Soc. London Ser. B 314: 1-340 (1986).
- [31] T.B. Achacoso and W.S. Yamamoto, *AY's Neuroanatomy of C.elegans for Computation*. (CRC Press, 1992).
- [32] We note that in the neuronal network where edges rep-

resent all synaptic connections (not only those with 5 or more synapses), we find numerous examples of the multi-Z and multi-Y FFLs, with the multi-X FFL the most common structure (data not shown).

- [33] F. Brglez, D. Bryan, and K. Kozminski *Combinational Profiles of Sequential Benchmark Circuits. Proc*. IEEE Int. Symposium on Circuits and Systems: 1929-1934 (1989).
- [34] R.F. Cancho, C. Janssen, and R.V. Sol Phys. Rev. E 64: 046119 (2001).
- [35] S. Basu, R. Mehreja, S. Thiberge, M.T. Chen, R. Weiss, Proc Natl Acad Sci U S A. 101(17):6355-60 (2004).
- [36] H. McAdams and A. Arkin, Annu. Rev. Biophys. Biomol. Struct. 27: 199-224 (1998).
- [37] N. Rosenfeld, M.B. Elowitz, and U. Alon, J. Mol. Biol. 323: 785-793 (2002).
- [38] N. Rosenfeld and U. alon, J. Mol. Biol. 329:645-654 (2003).
- [39] S. Kalir, J. McClure, K. Pabbaraju, C. Southward, M. Ronen, s. Leibler, M.G. Surette, U. Alon, Science 292: 2080-2083 (2001).
- [40] S. Kalir and U. Alon . Cell in press (2004).
- [41] M. Chalfie, J.E. Sulston, J.G. White, E. Southgate, J.N. Thomson, and S. Brenner, The Journal of Neuroscience 5: 956-964 (1985).
- [42] I.A. Hope *C. elegans A practical approach*. (Exford uni-

versity press, 1999).

- [43] M.B. Goodman, D.H. Hall, L. Avery, and S.R. Lockery, Neuron 20: 763-772 (1998).
- [44] M.C. Hansen, H. Yaclin, and J.P. Hayes, *Unveiling the ISCAS-85 Benchmarks: A case study in reverse engineering*. IEEE Design and Test: 72-80 (1999).
- [45] G.C. Conant, and A. Wagner, Nat. Genet. 34: 264-266 (2003).
- [46] S. Wasserman and K. Faust, . *Social Network Analysis*. (Cambridge University Press, Cambridge, 1994).
- [47] F. Lorrain and H.C.White, Journal of Mathematical Sociology 1: 49-80 (1971).
- [48] C. Winship. Social Networks **10**: 209-231 (1988).
- [49] C. Winship and M. Mandel, Sociological Methodology 1983-1984: 314-344 (1983).
- [50] M.G. Everett, J.P. Boyd, and S.P. Borgatti, Journal of Mathematical Sociology 15: 163-172 (1990).
- [51] C. Bron, J. Kerbosch, Commun. ACM. 16: 575-577 (1973).
- [52] H. Salgado, A. Santos-Zavaleta, S. Gama-Castro, D. Millan-Zarate, E. Diaz-Peredo, F. Sanchez-Solano, E. Perez-Rueda, C. Bonavides-Martinez, and J. Collado-Vides, Nucleic Acids Res. 29: 72-74 (2001).
- [53] M.C. Costanzo et. al. Nucleic Acids Res. 29: 75-79 (2001).