

UNRANKING PERMUTATIONS IN TRANSPOSITION ORDER AND LINEAR TIME.

KONSTANTINOS A. BLEKOS

ABSTRACT. An algorithm is presented for unranking permutations in transposition order: Given a seed $s \in \mathbb{N}$, the algorithm produces a permutation $\mathcal{P}(s)$ that differs from the permutation $\mathcal{P}(s + 1)$ by the transposition of two elements.

CONTENTS

1. Introduction	1
1.1. Transposition Order	1
1.2. Factoradic representation	1
2. Algorithm	2
2.1. Properties	2
3. Examples	3
References	3

1. INTRODUCTION

An algorithm $\mathcal{P}(s)$ is constructed that produces a permutation of objects in factoradic representation. All permutations of n objects can be produced, evaluating $\mathcal{P}(s)$ for every $0 \leq s \leq n! - 1$.

The key property of the algorithm is that permutations $\mathcal{P}(0), \mathcal{P}(1), \dots$ are produced in transposition order.

1.1. Transposition Order. It is an ordering of permutations in which each two adjacent permutations differ by the transposition of two elements. For the permutations of $\{1, 2, 3\}$ there are two listings which are in transposition order. One is 123, 132, 312, 321, 231, 213, and the other is 123, 321, 312, 213, 231, 132.[1]

1.2. Factoradic representation. Factoradic is a numeral system based on factorials. In factoradic, the sequence $a_n a_{n-1} \cdots a_0$ represents the number

$$\sum_{i=0}^n a_i i!$$

, where $a_i \leq i$

One can represent any permutation using factoradic as follows: Suppose we have a set of $n + 1$ objects $\{k_0, \dots, k_n\}$ and the factoradic sequence $a_n a_{n-1} \cdots a_0$. We remove the a_n -th element from the set of objects (the element with index a_n) and place it first on the permuted list. We continue with the a_{n-1} -th object of the re-indexed set, placing it second on the permuted list and proceed likewise through a_0 -th (which is always zero: the first and only element left in the set).[2]

Date: August 2007.

2. ALGORITHM

The algorithm is $O(n)$, i.e. linear in respect to the number of objects n in the set.

For a given seed s , we choose an n such that $s \leq n! - 1$. The algorithm outputs the factoradic sequence $f_{n-1}f_{n-2} \cdots f_0$ that corresponds to the s -permutation of a set of n objects.

Algorithm 1 Given seed $s \in \mathbb{N}$ calculate permutation $f_{n-1}f_{n-2} \cdots f_1$

Require: n such that $s \leq n! - 1$

- 1: $d_{n+1} = 0$
 - 2: **for** $k = n$ to 1 **do**
 - 3: $x_k = \lfloor \frac{s \pmod{k!}}{(k-1)!} \rfloor$
 - 4: $d_k = \left\lfloor \frac{\lfloor \frac{s+d_{k+1}(k+1)!}{k!} \rfloor \pmod{(k+1)^2}}{k+2} \right\rfloor$
 - 5: $f_{k-1} = (x_k - \lfloor \frac{s}{k!} \rfloor - d_k) \pmod{k}$
 - 6: **end for**
-

2.1. Properties. Defining a distance $d(s, s')$ as the minimum number of transpositions needed to reach permutation $\mathcal{P}(s')$ starting from permutation $\mathcal{P}(s)$ ¹, the following properties can be proved:

- \mathcal{P} is a bijection: $\mathcal{P}(s) \rightarrow f_{n-1}f_{n-2} \cdots f_0 \Leftrightarrow f_{n-1}f_{n-2} \cdots f_0 \rightarrow \mathcal{P}(s), \forall s \in \mathbb{N}, \forall f_{n-1}f_{n-2} \cdots f_0 \in \mathbb{P}^n$
- \mathcal{P} unrankes permutations in transposition order: $d(s \pm 1, s) = 1$

Also,

- $d(s, s') \leq \min(|s - s'|, n - 1) \Rightarrow d(s \pm 2, s) = 2$
- $d(s, 0) \leq k - 1, s < k!$
- $|d(s, 0) - d(s', 0)| \leq d(s, s')$

¹ $d(s, s')$ is a proper distance function since

- (1) $d(s, s') \geq 0$
- (2) $d(s, s') = 0 \Leftrightarrow \mathcal{P}(s) = \mathcal{P}(s')$
- (3) $d(s, s') = d(s', s)$
- (4) $d(a, b) \leq d(a, c) + d(c, b)$

3. EXAMPLES

For $s = 4$ we choose $n = 4$, so:

$$\begin{aligned}
 x_4 &= \lfloor \frac{4 \pmod{4!}}{3!} \rfloor = 0 \\
 d_4 &= \left\lfloor \frac{\left(\frac{4+(0)(5!)}{4!}\right) \pmod{5^2}}{6} \right\rfloor = 0 \\
 f_3 &= (0 - \lfloor \frac{4}{4!} \rfloor - 0) \pmod{4} = 0 \\
 x_3 &= \lfloor \frac{4 \pmod{3!}}{2!} \rfloor = 2 \\
 d_3 &= \left\lfloor \frac{\left(\frac{4+(0)(4!)}{3!}\right) \pmod{4^2}}{5} \right\rfloor = 0 \\
 f_2 &= (2 - \lfloor \frac{4}{3!} \rfloor - 0) \pmod{3} = 2 \\
 \dots & \\
 f_1 &= 0 \\
 f_0 &= 0
 \end{aligned}$$

thus $\mathcal{P}(4) \rightarrow 0_3 2_2 0_1 0_0 \rightarrow 1423$.

Similarly:

$$\begin{aligned}
 \mathcal{P}(5) &\rightarrow 0_3 2_2 1_1 0_0 \rightarrow 1432 \\
 \mathcal{P}(6) &\rightarrow 1_3 2_2 1_1 0_0 \rightarrow 2431 \\
 \mathcal{P}(7) &\rightarrow 1_3 2_2 0_1 0_0 \rightarrow 2413 \\
 \mathcal{P}(319) &\rightarrow 2_5 1_4 2_3 2_2 0_1 0_0 \rightarrow 325614 \\
 \mathcal{P}(320) &\rightarrow 2_5 1_4 2_3 0_2 1_1 0_0 \rightarrow 325164 \\
 \mathcal{P}(321) &\rightarrow 2_5 1_4 2_3 0_2 0_1 0_0 \rightarrow 325146 \\
 \mathcal{P}(322) &\rightarrow 2_5 1_4 2_3 1_2 0_1 0_0 \rightarrow 325416
 \end{aligned}$$

Using the above values, we can validate some distance relationships:

$$\begin{aligned}
 d(4, 5) &= 1 \\
 d(4, 6) &= 2 \\
 |d(319, 0) - d(5, 0)| &= |3 - 1| = 2 \\
 &\leq d(319, 5) = 2 \\
 &\leq d(319, 0) + d(0, 5) = 3 + 1 = 4 \\
 d(319, 5) &= 2 \\
 &\leq \min(|319 - 5|, 5) = 5
 \end{aligned}$$

REFERENCES

- [1] Weisstein, Eric W. "Transposition Order." From MathWorld—A Wolfram Web Resource. <http://mathworld.wolfram.com/TranspositionOrder.html>
- [2] Wikipedia contributors, "Factoradic," Wikipedia, The Free Encyclopedia, <http://en.wikipedia.org/wiki/Factoradic>