





# L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> Input Guide for Authors

CAMBRIDGE T<sub>E</sub>X-TO-TYPE†

(Received 26 July 2003)

**Abstract.** This guide is for authors who are preparing papers for the *Journal of Plasma Physics* using the L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> document preparation system and the Cambridge University Press JPP class file.

---

## CONTENTS

<b>1. Introduction</b>	2
1.1. Introduction to L <sup>A</sup> T <sub>E</sub> X	2
1.2. General style issues	2
1.3. Submission of L <sup>A</sup> T <sub>E</sub> X articles	2
1.4. The JPP document class	3
<b>2. Using the JPP class file</b>	3
2.1. Document class options	3
2.2. Additional ‘packages’ supplied with <code>jpp.cls</code>	4
<b>3. Additional facilities</b>	4
3.1. Titles, authors’ names and running headlines	4
3.2. Abstract	5
3.3. Lists	5
3.4. Theorem environments	6
3.5. Definitions	7
3.6. Proof environment	7
<b>4. Mathematics and units</b>	8
4.1. Numbering of equations	8
4.2. AMS fonts – especially if you do not have them	9
4.3. Typeface	10
4.4. Skewing of accents	11
4.5. Units of measure	12
<b>5. User-defined macros</b>	12
<b>6. Some guidelines for using standard facilities</b>	12
6.1. Sections	13
6.2. Tables	13
6.3. Illustrations (or figures)	14
6.4. Acknowledgments	15
6.5. Appendices	15
6.6. References	15
<b>Appendix A</b>	19
<b>Appendix B</b>	20

† Example of thanks

## 1. Introduction

The layout design for the *Journal of Plasma Physics* has been implemented as a L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> class file. The JPP class is based on the ARTICLE class as discussed in the L<sup>A</sup>T<sub>E</sub>X manual (2nd edition). Commands which differ from the standard L<sup>A</sup>T<sub>E</sub>X interface, or which are provided in addition to the standard interface, are explained in this guide. This guide is not a substitute for the L<sup>A</sup>T<sub>E</sub>X manual itself.

Note that the final printed version of papers will use the Monotype Modern typeface rather than the Computer Modern available to authors. Also, the measure in JPP class is different from L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> article class. For these reasons line lengths and page breaks will change and authors should not insert hard breaks in their text.

### 1.1. Introduction to L<sup>A</sup>T<sub>E</sub>X

The L<sup>A</sup>T<sub>E</sub>X document preparation system is a special version of the T<sub>E</sub>X typesetting program. L<sup>A</sup>T<sub>E</sub>X adds to T<sub>E</sub>X a collection of commands which allow the author to concentrate on the logical structure of the document rather than its visual layout.

L<sup>A</sup>T<sub>E</sub>X provides a consistent and comprehensive document preparation interface. L<sup>A</sup>T<sub>E</sub>X can automatically number equations, figures, tables, and list entries, as well as sections and subsections. Using this numbering system, bibliographic citations, page references and cross-references to any other numbered entity (e.g. section, equation, figure, list entry) are quite straightforward.

### 1.2. General style issues

Use of L<sup>A</sup>T<sub>E</sub>X defaults will result in a pleasing uniformity of layout and font selection. Authors should resist the temptation to make *ad hoc* changes to these. Also avoid use of direct formatting unless really necessary. Papers will be edited as usual, and this process may be obstructed by the use of inserted line breaks, etc.

For general style issues, authors are referred to the ‘Preparation of manuscripts’ in the back cover of the journal. The language used in the journal is British English, and spelling should conform to this.

Use should be made of symbolic references (`\ref`) in order to protect against late changes of order, etc.

### 1.3. Submission of L<sup>A</sup>T<sub>E</sub>X articles

Authors who intend to submit a L<sup>A</sup>T<sub>E</sub>X article should obtain a copy of the JPP class file. This is available by anonymous FTP from

`ftp.cup.cam.ac.uk`

You will find the class file and instructions contained in a single zip archive `jpp-cls.zip` in the directory

`pub/texarchive/journals/latex/jpp-cls`

The `readme.txt` (which is the same directory) tells you how to unzip the `jpp-cls.zip` file. There may also be an ‘unpacked’ directory containing all of the files separately, in case of difficulty. If you cannot obtain the JPP files, use the standard `article` class, with the default ‘10pt’ option.

When submitting the final article, ensure that the following are included and are clearly labelled.

(a) A hardcopy printout of the article.

- (b) The input file (exactly matching the hardcopy).
- (c) A copy of any user-defined macros.
- (d) If you have used L<sup>A</sup>T<sub>E</sub>X, the .bib, .bbl and .bst files that were used.
- (e) Any other files necessary to prepare the article for typesetting.

The files for the *final* article should be supplied on a PC or Macintosh disk. Please write on the disk what format it is, as this saves time. Submit the hardcopy and disk by post in the normal way.

#### 1.4. The JPP document class

The use of document classes allows a simple change of style (or style option) to transform the appearance of your document. The CUP JPP class file preserves the standard L<sup>A</sup>T<sub>E</sub>X interface such that any document which can be produced using the standard L<sup>A</sup>T<sub>E</sub>X ARTICLE class can also be produced with the JPP class. However, the measure (or width of text) is slightly different from that for ARTICLE; therefore line breaks will change and it is possible that equations may need re-setting.

## 2. Using the JPP class file

First, copy the file `jpp.cls` and `upmath.sty` (see §2.2) into the correct subdirectory on your system. The JPP document style is implemented as a complete document class, and *not* a document class option. In order to use the JPP class, replace `article` by `jpp` in the `\documentclass` command at the beginning of your document:

```
\documentclass{article}
```

is replaced by

```
\documentclass{jpp}
```

Some of the standard document class options should be used. Author-defined macros should be inserted before `\begin{document}`, or in a separate file and should be included with the submission, see §5. Authors must not change any of the macro definitions or parameters in `jpp.cls`.

### 2.1. Document class options

In general, the following standard document class options should *not* be used with the JPP class file:

- `10pt`, `11pt` and `12pt` – unavailable;
- `twoside` is the default (`oneside` is disabled);
- `onecolumn` is the default (`twocolumn` is disabled);
- `titlepage` is not required and is disabled;
- `fleqn` and `leqno` should not be used, and are disabled.

The standard document class options should *not* be used with the JPP class:

- `10pt`, `11pt`, `12pt` – unavailable.
- `draft`, `twoside` (no associated class file) – `twoside` is the default.
- `fleqn`, `leqno`, `titlepage`, `twocolumn` – unavailable.

## 2.2. Additional ‘packages’ supplied with `jpp.cls`

The following additional package (`.sty`) files are supplied in the JPP distribution:

- `upmath` – provides ‘upright’ Greek math characters. Requires the AMS `amsbsy` and `amsgen` packages.

If your site does not have the AMS Fonts and AMS L<sup>A</sup>T<sub>ε</sub>X packages installed, we strongly recommend that your site installs them. With them, you can produce output which is much closer to the final result. The latest AMS Fonts/AMS L<sup>A</sup>T<sub>ε</sub>X distributions can be found on your nearest CTAN (Comprehensive T<sub>ε</sub>X Archive Network) site.

*2.2.1. The UPMATH package* The `upmath` package defines the macros `\mathup` and `\mathbup`, which allow access to the symbols in the AMS Euler fonts.

The `upmath` package provides macros for upright lower-case Greek (`\ualpha`–`\uxi`), and for bold lower-case Greek (`\ubalpha`–`\ubxi`). The bold upright symbol `\eta` has to be treated differently, in this case use `\uboldeta`. The `upmath` package also provides `\upartial` and `\ubpartial`.

To use the `upmath` package, you need to have the AMS `eurm/b` fonts installed.

## 3. Additional facilities

In addition to all the standard L<sup>A</sup>T<sub>ε</sub>X design elements, the JPP class file includes the following features:

- Extended commands for specifying a short version of the title and author(s) for the running headlines.
- Abstract environment
- Control of enumerated lists.
- An extended `theorem` environment, enabling you to also typeset unnumbered theorems, etc.
- Ability to create new theorem-like environments for claims, conjectures, examples, problems, remarks, etc.
- The `subequations` and `subeqnarray` environments for sub-numbering equations.
- A `proof` environment.
- A `acknowledgements` environment.

Once you have used these additional facilities in your document, it can be processed only with `jpp.cls`.

### 3.1. Titles, authors’ names and running headlines

In the JPP class, the title of the article and the author’s name (or authors’ names) are used both at the beginning of the article for the main title and throughout the article as running headlines at the top of every page. The title is used on odd-numbered pages (rectos) and the author’s name (with initials only for first names) appears on even-numbered pages (versos). The `\pagestyle` and `\thispagestyle` commands should *not* be used. Similarly, the commands `\markright` and `\markboth` should not be necessary.

Although the article title can run to several lines of text, the running headline must be a single line. Moreover, the title can also incorporate new line commands (e.g. `\`) but these are not acceptable in a running headline. To enable you to specify an alternative short title and author’s name, the standard `\title` and `\author`

commands have been extended to take an optional argument to be used as the running headline:

```
\title[A short title]{The full title which can be as long
                        as necessary}
\author[Initials and last names of all authors]{The full names of
        all the authors, using letterspacing and \and before
        the last name in the list}
\affiliation{Author's affiliation}
```

Unlike most other document classes, `jpp.cls` does not follow the convention of using the second line of the `\author` command to write the author's affiliation. Rather, this must be entered using the `\affiliation` command as shown above. The `\and` command does not produce separate author/affiliation pairs, but only generates the word 'and' in small caps as required by the JPP class. Use the predefined macro `\ls` to get the letterspacing between the letters of the author's name. If there is more than one affiliation, use `\\[\affilskip]` between lines of the `\affiliation`, inserting footnote numbers manually.

An example will make all this clearer. To produce

## Interesting title

ALAN N. OTHER<sup>1</sup> and J. Q. PUBLIC<sup>2</sup>

<sup>1</sup>University of Moscow, Moscow, Russia

<sup>2</sup>Ngonga University, Nairobi, Kenya

(Received 12 June 1992)

you would type

```
\title[Short title]{Interesting title}
\author[A. N. Other and J. Q. Public]
        {A\ls L\ls A\ls N\ls N.\ns O\ls T\ls H\ls E\ls R$^1$\ns
         \and\ns J.\,Q.\ns P\ls U\ls B\ls L\ls I\ls C$^2$}
\affiliation{$^1$University of Moscow, Moscow, Russia\\[\affilskip]
             $^2$Ngonga University, Nairobi, Kenya}
\date{12 June 1992}
```

The L<sup>A</sup>T<sub>E</sub>X `\thanks` command can be used inside the `\author` command to insert an authors 'Current address' information as a footnote, appearing at the bottom of the title page.

### 3.2. Abstract

The JPP class provides for an abstract, produced by

```
\begin{abstract}
...
\end{abstract}
```

This should appear just *before* the first `\section` command.

### 3.3. Lists

The JPP style provides the three standard list environments plus an additional unnumbered list:

- Numbered lists, created using the `enumerate` environment.

- Bulleted lists, created using the `itemize` environment.
- Labelled lists, created using the `description` environment.

The `enumerate` environment numbers each list item with an italic letter in parentheses; alternative styles can be achieved by inserting a redefinition of the number labelling command after the `\begin{enumerate}`. For example, a list numbered with roman numerals inside parentheses can be produced by the following commands:

```
\begin{enumerate}
\renewcommand{\theenumi}{\roman{enumi}}
\item first item
:
\end{enumerate}
```

This produces the following list:

- (i) first item
- (ii) second item
- (iii) etc.

In the last example, the item alignment is uneven because the standard list indentation is designed to be sufficient for arabic numerals rather than the wider roman numerals. In order to enable different labels to be used more easily, the `enumerate` environment in the JPP style can be given an optional argument which (like a standard `thebibliography` environment) specifies the *widest label*. For example,

- (i) first item
- (ii) second item
- (iii) etc.

was produced by the following input:

```
\begin{enumerate}[(iii)]
\renewcommand{\theenumi}{\roman{enumi}}
\item first item
:
\end{enumerate}
```

Once you have used the optional argument on the `enumerate` environment, do not process your document with a standard L<sup>A</sup>T<sub>E</sub>X class file.

### 3.4. Theorem environments

The `\newtheorem` command works as described in the L<sup>A</sup>T<sub>E</sub>X manual, but produces spacing and caption typefaces required to the JPP style. The preferred numbering scheme is for theorems to be numbered within sections, as 1.1, 1.2, 1.3, etc., but other numbering schemes are permissible and may be implemented as described in the L<sup>A</sup>T<sub>E</sub>X manual. In order to allow authors maximum flexibility in numbering and naming, *no* theorem-like environments are defined in `jpp.cls`. Rather, you have to define each one yourself. Theorem-like environments include Theorem, Definition, Lemma, Corollary, and Proposition. For example,

```
\newtheorem{lemma}{Lemma}[section]
```



```
\renewcommand{\thelemma}{\Roman{lemma}}
```

The new macro which follows can also produce numbered and unnumbered environments.

### 3.5. Definitions

The `\newdefinition` command can be used to create environments for claims, conjectures, examples, problems, remarks, etc. These are typeset in the way as theorems, except the text is typeset in roman instead of italic.

You can have an environment created by `\newdefinition` number in the same sequence as a ‘Theorem’ by adding the optional `[theorem]` argument as below:

```
\newdefinition{definition}[theorem]{Definition}
:
\begin{definition}
This is a definition.
\end{definition}
\begin{definition*}
This is an unnumbered definition.
\end{definition*}
```

which produces the following:

*Definition 3.1.* This is a definition.

*Definition.* This is an unnumbered definition.

### 3.6. Proof environment

The standard L<sup>A</sup>T<sub>E</sub>X constructs do not include a proof environment to follow a theorem, lemma etc. (see also §3.4), and so one has been added for the JPP style.

Note the use in the following examples of an optional argument in square braces which may contain any information you may wish to add. For example,

```
\begin{theorem}[2]\label{thenv}
Let the scalar function  $T(x,y,t,\mathbf{\omega})$  be a conserved
density for solutions of  $(9)$ . Then the two-component function
\begin{equation}
\mathbf{P} = \mathbf{J} \mathcal{E} T
\end{equation}
represents the infinitesimal generator of a symmetry group
for  $(9)$ .
\end{theorem}
\begin{proof}[Proof of Theorem~\ref{thenv}]
The assumption about  $T$  means that
\[
0 \sim \frac{\partial T}{\partial t} + \mathcal{E} T \mathbf{\omega}_t
= \frac{\partial T}{\partial t} + \{ T, H \},
\]
where  $\frac{\partial T}{\partial t}$  refers to explicit
dependence on  $t$ . The skew symmetry of  $\mathbf{J}$  hence implies
\begin{equation}
```

```
\frac{\partial T}{\partial t} \sim \{ H, T\},
\end{equation}
```

whereupon the operation  $\mathcal{J}$ , which commutes with  $\partial_t$  in its present sense, gives

```
\[
\frac{\partial \mathbf{P}}{\partial t}
= \mathcal{J}\{ H, T\}.
\]
```

This equation reproduces the characterisation of symmetries that was expressed by (19), thus showing  $\mathbf{P}$  to represent a symmetry group.

```
\end{proof}
```

produces the following text:

**THEOREM 3.2 (2).** *Let the scalar function  $T(x, y, t, \omega)$  be a conserved density for solutions of (9). Then the two-component function*

$$\mathbf{P} = \mathcal{J}T \tag{3.1}$$

*represents the infinitesimal generator of a symmetry group for (9).*

*Proof.* [Proof of Theorem 3.2] The assumption about  $T$  means that

$$0 \sim \frac{\partial T}{\partial t} + \mathcal{E}T\omega_t = \frac{\partial T}{\partial t} + \{T, H\},$$

where  $\partial T/\partial t$  refers to explicit dependence on  $t$ . The skew symmetry of  $\mathcal{J}$  hence implies

$$\frac{\partial T}{\partial t} \sim \{H, T\}, \tag{3.2}$$

whereupon the operation  $\mathcal{J}\mathcal{E}$ , which commutes with  $\partial_t$  in its present sense, gives

$$\frac{\partial \mathbf{P}}{\partial t} = \mathcal{J}\mathcal{E}\{H, T\}.$$

This equation reproduces the characterisation of symmetries that was expressed by (19), thus showing  $\mathbf{P}$  to represent a symmetry group.  $\square$

The final  $\square$  will not be included if the `proof*` environment is used.

## 4. Mathematics and units

The JPP class file will insert the correct space above and below displayed maths if standard L<sup>A</sup>T<sub>E</sub>X commands are used; for example use `\[ ... \]` and *not* `$$ ... $$`. Do not leave blank lines above and below displayed equations unless a new paragraph is really intended.

### 4.1. Numbering of equations

The `subequations` and `subeqnarray` environments have been incorporated into the JPP class file. Using these two environments, you can number your equations (1.1a), (1.1b) etc. automatically. For example, you can typeset

$$a_1 \equiv (2\Omega M^2/x)^{\frac{1}{4}}y^{\frac{1}{2}} \tag{4.1a}$$

and

$$a_2 \equiv (x/2\Omega)^{\frac{1}{2}} k_y / M. \quad (4.1b)$$

by using the `subequations` environment as follows:

```
\begin{subequations}
\begin{equation}
a_1 \equiv (2\Omega M^2/x)^{\frac{1}{4}} y^{\frac{1}{2}}
\end{equation}
and
\begin{equation}
a_2 \equiv (x/2\Omega)^{\frac{1}{2}} k_y / M.
\end{equation}
\end{subequations}
```

You may also typeset an `array` such as:

$$\dot{X} = \gamma X - \gamma \delta \eta, \quad (4.2a)$$

$$\dot{\eta} = \frac{1}{2} \delta + 2X\eta. \quad (4.2b)$$

by using the `subeqnarray` environment as follows:

```
\begin{subeqnarray}
\dot{X} & = & \gamma X - \gamma \delta \eta , \\
\dot{\eta} & = & \frac{1}{2} \delta + 2X\eta .
\end{subeqnarray}
```

#### 4.2. AMS fonts – especially if you do not have them

If you need AMS symbols but do not have the AMS fonts you can ensure that they will be correctly typeset by taking the following steps. Set up user-defined macros that can be redefined by the typesetter to use the correct AMS macros. For example, the blackboard bold symbols, sometimes called shell or outline characters, are obtained with the AMS macro `\mathbb{. .}`. Instead, use a macro definition such as:

```
% replace font!
\newcommand\BbbE{\ensuremath{\mathsf{E}}} % Blackboard bold E
```

This substitutes a sans serif character where you want blackboard bold. You can typeset the input file and the typesetter is alerted to do the substitution.

The following example (which uses the `\providecommand` macro) will work without modification by the typesetter, because the `\providecommand` macro will not overwrite any existing `\mathbb` definition.

```
\providecommand\mathbb[1]{\ensuremath{\mathsf{#1}}}
...
\newcommand\BbbE{\mathbb{E}} % Blackboard bold E
```

Plain T<sub>E</sub>X provides only `\leq` and `\geq` which typeset the Computer Modern symbols  $\leq$  and  $\geq$ , respectively. These will be redefined at typesetting to use the AMS symbols `\leqslant` and `\geqslant`, to give the slanted symbols.

If you wish to use AMS fonts with L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> you must be using at least version 2.0. Earlier versions are not supported.

### 4.3. Typeface

Sometimes, non-italic symbols are required in maths. This section describes how these may be obtained using L<sup>A</sup>T<sub>E</sub>X and `jpp.cls`.

*4.3.1. Roman symbols* The mathematical operators and constants, such as `\sin`, `\cos`, `\log` and `\exp` (and many others) are covered by L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> macros which ensure that they are typeset in roman text, even in math mode: `\sin`, `\cos`, `\log`, `\exp`. Where single letters are concerned (e.g. `d`, `i`, `e`) just use `\mathrm` in math mode, i.e. `\$E=m\mathrm{c}^2\$` which typesets as  $E = mc^2$ , giving the correct roman character but with math spacing. When the term involves more than one character (e.g. `Re` or `Im`) text-character spacing is required:

```
\$ \mbox{Re} \; x \$
```

which typesets as  $\text{Re } x$ .

Where such expressions are used repeatedly, macro definitions can reduce typing and editing. The following examples are included in the preamble of the input files for this document, `jppguide.tex`, and of the sample article `jppsampl.tex`. Authors are encouraged to use them and others like them.

```
\newcommand\Real{\mbox{Re}} % do not confuse with TeX's \Re
\newcommand\Imag{\mbox{Im}} % do not confuse with TeX's \Im
\newcommand\Ai{\mbox{Ai}}
\newcommand\Bi{\mbox{Bi}}
```

*4.3.2. Multiletter italic symbols* If multiletter symbols are used in maths mode, for example Reynolds, Prandtl numbers, etc. the standard maths mode spacing between them is too large and text-character spacing is required. As described in §4.3.1 (but here for italic letters) use for example

```
\newcommand\Rey{\mbox{\textit{Re}}}
\newcommand\Pran{\mbox{\textit{Pr}}}
```

*4.3.3. Upright and sloping Greek symbols* Like the italic/roman fonts described above, Greek letters for math variables are printed in the Journal in sloping type, whereas constants, operators and units are upright. However, L<sup>A</sup>T<sub>E</sub>X normally produces sloping lowercase Greek and upright capitals. The upright lowercase required for example for ‘`\pi`’ and ‘`\mu`’ (micro) are provided by the `upmath` package (from the AMS Euler fonts). If you don’t have the AMS font set, you will have to use the normal math italic symbols and the typesetter will substitute the corresponding upright characters.

You will make this much easier if you can use the macros `\upi` and `\umu` in your text to indicate the need for the upright characters, together with the following definitions in the preamble, where they can easily be redefined by the typesetter.

```
\providecommand\upi{\pi}
\providecommand\umu{\mu}
```

Notice the use of `\providecommand`, this stops your definitions overwriting the ones used by the typesetter.

Sloping uppercase Greek characters can be obtained by using the `\varGamma` etc. macros (which are built into the class file). The few required upright Greek capital letters (e.g. capital delta for ‘difference’) are given by the relevant L<sup>A</sup>T<sub>E</sub>X macro, e.g. `\Delta`.

*4.3.4. Sans serif symbols* The `\textsf` and `\mathsf` commands change the typeface to sans serif, giving upright characters. Occasionally, bold-sloping sans serif is needed. You should use the following supplied macros to obtain these fonts.

<code>\textsf{text}</code>	→	text	<code>\mathsf{math}</code>	→	math
<code>\textsf{i{text}</code>	→	<i>text</i>	<code>\mathsf{i{math}</code>	→	<i>math</i>
<code>\textsf{b{text}</code>	→	<b>text</b>	<code>\mathsf{b{math}</code>	→	<b>math</b>
<code>\textsf{bi{text}</code>	→	<i>text</i>	<code>\mathsf{bi{math}</code>	→	<i>math</i>

You can use them like this:

```
\newcommand\ssC{\mathsf{C}} % for sans serif C
\newcommand\sfsP{\mathsf{i{P}} % for sans serif slanted P
\newcommand\sfbSX{\mathsf{b{X}} % for sans serif bold slanted X
```

Note that the bold-slanted font `\textsf{bi}` and `\mathsf{bi}` use the slanted sans serif font `cmssi` – because there is no bold-slanted maths sans serif font in Computer Modern! If you use the supplied sans-serif text and math commands the typesetter will be able to substitute the fonts automatically.

*4.3.5. Bold math italic symbols* If you require bold math italic symbols/letters, L<sup>A</sup>T<sub>E</sub>X provides several ways of getting them. Firstly, L<sup>A</sup>T<sub>E</sub>X’s `\boldmath` switch which can be used like this:

```
$ \mbox{\boldmath $P$} = \mathsf{J}\mathcal{E} T $
```

As you can see it takes quite a lot of typing to achieve a bold math italic P. Another problem is that you can’t use `\boldmath` in math mode, thus the `\mbox` forces the resulting text into text style (which you may not want).

You can cut down on the typing by defining the following macro (which is in the preamble of this guide):

```
\providecommand\boldsymbol[1]{\mbox{\boldmath $1$}}
```

Then for the above example you can define:

```
\newcommand\bldP{\boldsymbol{P}}
```

to achieve the same result. This still doesn’t remove the default to text style problem.

If you have the `amsbsy` package on your system, then you can remove this limitation as well by placing a `\usepackage{amsbsy}` after the `\documentclass` line in your document, and then use `\boldsymbol` for bold math italic symbols (don’t define `\boldsymbol` yourself when using `amsbsy`).

*4.3.6. Script characters* Script characters should be typeset using L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>’s `\mathcal` command. This produces the Computer Modern symbols such as  $\mathcal{E}$  and  $\mathcal{F}$  in your hard copy but the typesetter will substitute the more florid script characters normally seen in the journal.

#### 4.4. Skewing of accents

Accents such as hats, overbars and dots are normally centred over letters, but when these are italic or sloping greek the accent may need to be moved to the right so that it is centred over the top of the sloped letter. For example, `\newcommand\hatp{\skew3\hat{p}}` will produce  $\hat{p}$ .

#### 4.5. Units of measure

Numbers and their units of measure should be typeset with fixed spaces that will not break over two lines. This is easily done with user-defined macros. For example, `52\dynpercm` typesets as 52 dynes cm<sup>-1</sup>, providing the following macro definition has been included in the preamble.

```
\newcommand\dynpercm{\nobreak\mbox{\;$\;$dynes\,cm$^{-1}$}}
```

### 5. User-defined macros

If you define your own macros you must ensure that their names do not conflict with any existing macros in plain T<sub>E</sub>X or L<sup>A</sup>T<sub>E</sub>X (or AMS L<sup>A</sup>T<sub>E</sub>X if you are using this). You should also place them in the preamble to your input file, between the `\documentclass` and `\begin{document}` commands.

Apart from scanning the indexes of the relevant manuals, you can check whether a macro name is already used in plain T<sub>E</sub>X or L<sup>A</sup>T<sub>E</sub>X by using the T<sub>E</sub>X command `show`. For instance, run L<sup>A</sup>T<sub>E</sub>X interactively and type `\show<macro_name>` at the T<sub>E</sub>X prompt. (Alternatively, insert the `\show` command into the preamble of an input file and T<sub>E</sub>X it.)

```
* \show\Re
```

produces the following response from T<sub>E</sub>X:

```
> \Re=\mathchar"23C.
<*> \show\Re
```

By contrast `\Real` is not part of plain T<sub>E</sub>X or L<sup>A</sup>T<sub>E</sub>X and `\show\Real` generates:

```
> \Real=undefined
<*> \show\Real
```

confirming that this name can be assigned to a user-defined macro.

Alternatively, you can just use `\newcommand`, which will check for the existence of the macro you are trying to define. If the macro exists L<sup>A</sup>T<sub>E</sub>X will respond with:

```
! LaTeX Error: Command ... already defined.
```

In this case you should choose another name, and try again.

Such macros must be in a place where they can easily be found and modified by the journal's editors or typesetter. They must be gathered together in the preamble of your input file, or in a separate `macros.tex` file with the command `\input{macros}` in the preamble. Macro definitions must not be scattered about your document where they are likely to be completely overlooked by the typesetter.

The same applies to font definitions that are based on Computer Modern fonts. These must be changed by the typesetter to use the journal's T<sub>E</sub>X typefaces. In this case, you should draw attention to these font definitions on the hard copy that you submit for publication and by placing a comment in your input file just before the relevant definitions, for example `% replace font!`

### 6. Some guidelines for using standard facilities

The following notes may help you achieve the best effects with the standard L<sup>A</sup>T<sub>E</sub>X facilities that remain in the JPP style.

**Table 1.** An example table

Figure	$hA$	$hB$	$hC$
2	$\exp(\pi ix)$	$\exp(\pi iy)$	0
3	-1	$\exp(\pi ix)$	1
4	$-4 + 3i$	$-4 + 3i$	1.6
5	-2	-2	1.2i

### 6.1. Sections

$\LaTeX$  provides five levels of section headings, only four of which are defined in the JPP class file:

Heading A – `\section{...}`  
 Heading B – `\subsection{...}`  
 Heading C – `\subsubsection{...}`  
 Heading D – `\paragraph{...}`

There is no `subparagraph` in the JPP style.

To obtain non-bold in a bold heading use the usual  $\LaTeX_{2\epsilon}$  commands for changing typeface; for example `\section{Fluctuations in Ca\textsc{ii}}`.

### 6.2. Tables

The `table` environment is implemented as described in the  $\LaTeX$  manual to provide consecutively numbered floating inserts for tables.

JPP class will cope with most table positioning problems and you should not normally use the optional positional qualifiers `t`, `b`, `h` on the `table` environment, as this would override these decisions. Table captions should appear at the bottom of the table; therefore you should place the `\caption` command before the `\begin{tabular}`.

The JPP `table` environment will insert rules above and below the table as required by the JPP style, so you should not attempt to insert these yourself. The only time you need to intervene with the rules is when two or more tables fall one above another. When this happens, you will get two rules together and too much space between the tables; the solution is to add `\norule` before the end of upper table and `\followon` between tables as shown here:

```

...
\end{center}
\caption{Dimensionless parameters}\label{dimensionless_p}
\norule
\end{table}
\followon
\begin{table}
\begin{center}
...

```

The JPP style dictates that vertical rules should never be used within the body of the table, and horizontal rules should be used only to span columns with the same headings. Extra space can be inserted to distinguish groups of rows or columns.

As an example, table 1 is produced using the following commands:

```

\begin{table}
\caption{An example table} \label{sample-table}

```

```

\begin{center}
\begin{tabular}{cccc}
\hline
{Figure} & {$hA$} & {$hB$} & {$hC$}\\
\hline
2 & $\exp\;(\uparrow \mathrm{i} x)$ & & \\
& $\exp\;(\uparrow \mathrm{i} y)$ & & $0$\\
3 & $-1$ & $\exp\;(\uparrow \mathrm{i} x)$ & $1$\\
4 & $-4+3\mathrm{i}$ & $-4+3\mathrm{i}$ & $1.6$\\
5 & $-2$ & $-2$ & $1.2 \mathrm{i}$
\end{tabular}
\end{center}
\end{table}

```

The `tabular` environment has been modified for the JPP style in the following ways:

- (a) Additional vertical space is inserted above and below a horizontal rule produced by `\hline`
- (b) Tables are centred, and span the full width of the page; that is, they are similar to the tables that would be produced by `\begin{tabular*}{\textwidth}`.
- (c) As with normal L<sup>A</sup>T<sub>E</sub>X, if a footnote needs to be inserted into the body of the table, the `tabular` environment should be enclosed in a `minipage` environment of width `\textwidth`. e.g.

```

\begin{minipage}{\textwidth}
\begin{tabular}{cccc}
\hline
{Figure} & {$hA$} & {$hB$} & \footnote{A table must be
inside a \verb"minipage" environment if it includes
table footnotes.}
& {$hC$}\\
...
\end{tabular}
\end{minipage}

```

Commands to redefine quantities such as `\arraystretch` should be omitted. If the original tabular facilities are needed, there is a new environment ‘`oldtabular`’, which has none of the reformatting; it should be used in exactly the same way.

### 6.3. Illustrations (or figures)

Artwork for all figures must be supplied separately, to be processed by the Printer, and so L<sup>A</sup>T<sub>E</sub>X’s `picture` environment, for example, cannot be used. An approximate amount of space should be left, using the `\vspace` command.

The JPP style will cope with most figure positioning problems and you should not normally use the optional positional qualifiers `t`, `b`, `h` on the `figure` environment, as this would override these decisions. Figure captions should be below the figure itself, therefore the `\caption` command should appear after the space left for the illustration within the `figure` environment. For example, figure 1 is produced using the following commands:



**Figure 1.** An example figure with space for artwork.

```

\begin{figure}
  \vspace{3cm}
  \caption{An example figure with space for artwork.}
  \label{sample-figure}
\end{figure}

```

If a figure caption is too long to fit on the same page as its illustration, the caption may be typeset as ‘FIGURE X. For caption see facing page.’, and the longer caption typeset at the bottom of the facing page. Authors should not concern themselves unduly with such details, and may leave pages long.

#### 6.4. Acknowledgments

Acknowledgments should appear at the close of your paper, just before the list of references and any appendices. Use the `acknowledgments` environment, which simply inserts an ‘Acknowledgments’ subsection heading.

There is also an `acknowledgment` (or `acknowledgement`) environment for typesetting a single acknowledgment.

#### 6.5. Appendices

You should use the standard L<sup>A</sup>T<sub>E</sub>X `\appendix` command to place any Appendices, normally, just before the references. This numbers appendices as A, B etc. , equations as (A1), (B1) etc. , and figures and tables as A1, B1 etc.

If you have only one Appendix, you should use the `\oneappendix` command (instead of `\appendix`). This command does the same as `\appendix`, except it allows `jpp.cls` to typeset a single Appendix correctly.

#### 6.6. References

As with standard L<sup>A</sup>T<sub>E</sub>X, there are two ways of producing a list of references; either by compiling a list (using a `thebibliography` or `thereferences` environment), or by using Bib<sub>T</sub>E<sub>X</sub> with a suitable bibliographic database.

References in the text should follow either the Harvard (name/date) or Vancouver (numbered) system. In the Harvard system, each reference should be cited in the text as ‘author(s) (date)’ or ‘(author(s) date)’, and the reference list at the end of the paper should be in *alphabetical order*. In the Vancouver system, references should be indicated in the text by numbers in square brackets (e.g. [1], [1,2], [1–4], etc.), and should be listed at the end of the paper in *numerical order of citation*. For details of the style of entries within the reference list, please see any recent issue of the journal.

**6.6.1. References in the text** References in the text are given by author and date like Dennis (1985) or numbered system [12]. Each entry has a key, which is assigned by the author and used to refer to that entry in the text.

6.6.2. *Harvard (name/date)* The following listing shows some references prepared in author (date) style of the journal; the code produces the references at the end of this guide.

```

\begin{thebibliography}{}
  \bibitem[Abramowitz and Stegun (1965)]{AS65}
    {Abramowitz, M. and Stegun, I.\,A.} 1965
    {\em Handbook of Mathematical Functions}. Dover.
  \bibitem[Dennis (1985)]{Den85}
    {Dennis, S.\,C.\,R.} 1985
    Compact explicit finite difference approximations to the
    Navier--Stokes equation. In {\em Ninth Intl Conf. on
    Numerical Methods in Fluid Dynamics\} (ed. Soubbaramayer
    and J.\,P. Boujot). Lecture Notes in Physics, vol. 218,
    pp. 23--51. Springer.
  \bibitem[Jones (1976)]{Jon1976}
    {Jones, O.\,C.} 1976
    An improvement in the calculation of turbulent friction in
    rectangular ducts. {\em Trans. ASME\} J:
    {\em J.\,Fluids Engng\} {\bf 98}, 173--181.
  \bibitem[Saffman (1990)]{Saf1990}
    {Saffman, P.\,G.} 1990
    A model vortex reconnection. {\em J.\,Fluid Mech.}
    {\bf 212}, 395--402.
  \bibitem[Saffman and Schatzman (1982)]{SS1982}
    {Saffman, P.\,G. and Schatzman, J.\,C.} 1982
    Stability of a vortex street of finite vortices.
    {\em J.\,Fluid Mech.} {\bf 117}, 171--185.
  \bibitem[Saffman and Yuen (1980)]{SY1980}
    {Saffman, P.\,G. and Yuen, H.\,C.} 1980
    A new type of three-dimensional deep-water wave of permanent
    form. {\em J.\,Fluid Mech.} {\bf 101}, 797--808.
  \bibitem[Shaqfeh and Koch (1990)]{SK1990}
    {Shaqfeh, E.\,S.\,G. and Koch, D.\,L.} 1990
    Orientational dispersion of fibres in extensional flow.
    {\em Phys. Fluids\} A {\bf 2}, 1077--1081.
  \bibitem[Wijngaarden (1968)]{Wij1968}
    {Wijngaarden, L. van} 1968
    On the oscillations near and at resonance in open pipes.
    {\em J.\,Engng Maths\} {\bf 2}, 225--240
  \bibitem[Williams (1964)]{Wil64}
    {Williams, J.\,A.} 1964
    A nonlinear problem in surface water waves. PhD thesis,
    University of California, Berkeley.
\end{thebibliography}

```

Each entry takes the form

```

\bibitem[Author(s) (Date)]{tag}
  Bibliography entry

```

where **Author(s)** should be the author names as they are cited in the text, **Date** is the date to be cited in the text, and **tag** is the tag that is to be used as an argument for the `\cite{}` command. **Bibliography entry** should be the material that is to appear in the bibliography, suitably formatted.

## References

- Abramowitz, M. and Stegun, I. A. 1965 *Handbook of Mathematical Functions*. Dover.
- Dennis, S. C. R. 1985 Compact explicit finite difference approximations to the Navier–Stokes equation. In *Ninth Intl Conf. on Numerical Methods in Fluid Dynamics* (ed. Soubbaramayer and J. P. Boujot). Lecture Notes in Physics, vol. 218, pp. 23–51. Springer.
- Jones, O. C. 1976 An improvement in the calculation of turbulent friction in rectangular ducts. *Trans. ASME J: J. Fluids Engng* **98**, 173–181.
- Saffman, P. G. 1990 A model vortex reconnection. *J. Fluid Mech.* **212**, 395–402.
- Saffman, P. G. and Schatzman, J. C. 1982 Stability of a vortex street of finite vortices. *J. Fluid Mech.* **117**, 171–185.
- Saffman, P. G. and Yuen, H. C. 1980 A new type of three-dimensional deep-water wave of permanent form. *J. Fluid Mech.* **101**, 797–808.
- Shaqfeh, E. S. G. and Koch, D. L. 1990 Orientational dispersion of fibres in extensional flow. *Phys. Fluids A* **2**, 1077–1081.
- Wijngaarden, L. van 1968 On the oscillations near and at resonance in open pipes. *J. Engng Maths* **2**, 225–240
- Williams, J. A. 1964 A nonlinear problem in surface water waves. PhD thesis, University of California, Berkeley.

*6.6.3. Vancouver (numbered) system* The following listing shows some references prepared in Vancouver (numbered) system style of the journal; the code produces the references at the end of this guide.

```
\begin{thereferences}{9}
  \bibitem{Jon76}
    {Jones, O.\,C.},
    An improvement in the calculation of turbulent friction in
    rectangular ducts. {\em Trans. ASME\}/ J:
    {\em J.\,Fluids Engng\}/ {\bf 98}, 173--181 (1976).
  \bibitem{Saf90}
    {Saffman, P.\,G.},
    A model vortex reconnection. {\em J.\,Fluid Mech.}
    {\bf 212}, 395--402 (1990).
  \bibitem{SS82}
    {Saffman, P.\,G. and Schatzman, J.\,C.},
    Stability of a vortex street of finite vortices.
    {\em J.\,Fluid Mech.} {\bf 117}, 171--185 (1982).
  \bibitem{SY80}
    {Saffman, P.\,G. and Yuen, H.\,C.},
    A new type of three-dimensional deep-water wave of permanent
    form. {\em J.\,Fluid Mech.} {\bf 101}, 797--808 (1980).
  \bibitem{SK90}
    {Shaqfeh, E.\,S.\,G. and Koch, D.\,L.}
    Orientational dispersion of fibres in extensional flow.
    {\em Phys. Fluids\}/ A {\bf 2}, 1077--1081 (1990).
```

```

\bibitem{Wij68}
  {Wijngaarden, L. van},
  On the oscillations near and at resonance in open pipes.
  {\em J.\,Engng Maths\} {\bf 2}, 225--240 (1968).
\end{thereferences}

```

Each entry takes the form

```

\bibitem{tag}
  Bibliography entry

```

where `tag` is the tag that is to be used as an argument for the `\cite{}` command. `Bibliography entry` should be the material that is to appear in the bibliography, suitably formatted.

## References

- [1] Jones, O. C., An improvement in the calculation of turbulent friction in rectangular ducts. *Trans. ASME J: J. Fluids Engng* **98**, 173–181 (1976).
- [2] Saffman, P. G., A model vortex reconnection. *J. Fluid Mech.* **212**, 395–402 (1990).
- [3] Saffman, P. G. and Schatzman, J. C., Stability of a vortex street of finite vortices. *J. Fluid Mech.* **117**, 171–185 (1982).
- [4] Saffman, P. G. and Yuen, H. C., A new type of three-dimensional deep-water wave of permanent form. *J. Fluid Mech.* **101**, 797–808 (1980).
- [5] Shaqfeh, E. S. G. and Koch, D. L. Orientational dispersion of fibres in extensional flow. *Phys. Fluids A* **2**, 1077–1081 (1990).
- [6] Wijngaarden, L. van, On the oscillations near and at resonance in open pipes. *J. Engng Maths* **2**, 225–240 (1968).

## Appendix A. Special commands in `jpp.cls`

The following is a summary of the new commands, optional arguments and environments which have been added to the standard L<sup>A</sup>T<sub>E</sub>X user-interface in creating the JPP class file.

### *New commands*

<code>\affiliation</code>	use after <code>\author</code> to typeset an affiliation.
<code>\affilskip</code>	use immediately after <code>\</code> in <code>\affiliation</code> to give correct vertical spacing between separate affiliations.
<code>\author</code>	do not use <code>\</code> in <code>\author</code> to start an affiliation.
<code>\followon</code>	to remove space between adjacent tables.
<code>\ls</code>	to letter space the author's name.
<code>\newtheorem</code>	this is enhanced so that you can produce unnumbered versions of the environments by using the <code>*</code> form. e.g. <code>\begin{theorem*}</code> .
<code>\newdefinition</code>	this environment works like the <code>\newtheorem</code> command, except it produces environments which are typeset in roman instead of italic. Again unnumbered 'definitions' can be typeset using the <code>*</code> forms.
<code>\norule</code>	to remove the rule below a table.
<code>\ns</code>	to insert space between an author's names.
<code>\oneappendix</code>	does the same as <code>\appendix</code> , except it allows <code>jpp.cls</code> to typeset a single Appendix correctly.

### *New optional arguments*

<code>[&lt;short title&gt;]</code>	in the <code>\title</code> command: to define a right running headline that is different from the article title.
<code>[&lt;short author&gt;]</code>	in the <code>\author</code> command: to define a left running headline that is different from the authors' names as typeset at the article opening.
<code>[&lt;widest label&gt;]</code>	in <code>\begin{enumerate}</code> : to ensure the correct alignment of numbered lists.

### *New environments*

<code>acknowledg(e)ment(s)</code>	to typeset acknowledgements.
<code>proof</code>	to typeset mathematical proofs.
<code>proof*</code>	to typeset mathematical proofs without the terminating proofbox.
<code>remark</code>	this environment works like the <code>theorem</code> environment; it typesets an italic heading and roman text to contrast with <code>theorem</code> 's small caps heading and italic text.
<code>subeqnarray</code>	enables equation numbers in an array to be numbered as (6.1a), (6.2b), etc.
<code>subequation</code>	enables consecutive equations to be numbered (6.1a), (6.1b), etc.
<code>tabular</code>	has been modified to insert additional space above and below an <code>\hrule</code> and the table caption and body is centred with rules full out across the text measure.

**Appendix B. Notes for editors**

This appendix contains additional information which may be useful to those who are involved with the final production stages of an article. Authors, who are generally not typesetting the final pages in the journal's typeface (Monotype Modern), do not need this information.

*B.0.1. Catchline commands* To be placed in the preamble:

- `\date{}`
- `\pagerange{}`
- `\part{}`
- `\pubyear{}`
- `\volume{}`
- `\doi{}`

*B.0.2. Footnotes* If a footnote falls at the bottom of a page, it is possible for the footnote to appear on the following page (a feature of T<sub>E</sub>X). Check for this.

*B.0.3. Rules between tables* If two or more tables fall one above another, add the commands `\norule` and `\followon` as described in this guide.

*B.0.4. Font substitution* Check for use of AMS fonts, bold slanted sans serif, and bold math italic and alter preamble definitions to use the appropriate AMS/CUP/Monotype fonts for phototypesetter output.

*B.0.5. Font sizes* The JPP class file defines all the standard L<sup>A</sup>T<sub>E</sub>X font sizes. For example:

- `tiny` – This is tiny text.
- `scriptsize` – This is scriptsize text.
- `\indexsize` – This is indexsize text.
- `\footnotesize` – This is footnotesize text.
- `\small` – This is small text.
- `\qsmall` – This is qsmall text (quotations).
- `\normalsize` – This is normalsize text (default).
- `\large` – This is large text.
- `\Large` – This is Large text.
- `\LARGE` – This is LARGE text.

All these sizes are summarized in Table B.1.

**Table B.1.** Type sizes for L<sup>A</sup>T<sub>E</sub>X size-changing commands

<i>Size</i>	<i>Size/Baseline</i>	<i>Usage</i>
<code>\tiny</code>	5pt/6pt	–
<code>\scriptsize</code>	7pt/8pt	–
<code>\indexsize</code>	8pt/9pt	catchline.
<code>\footnotesize</code>	9pt/10pt	index, footnotes.
<code>\small</code>	9pt/10pt	‘AND’ in authors’ names, received date, affiliation, figure and table captions.
<code>\qsmall</code>	9.75pt/10.75pt	quote, quotations.
<code>\normalsize</code>	10pt/12pt	main text size, abstract, B and C heads.
<code>\large</code>	11pt/13pt	A head, part no.
<code>\Large</code>	14pt/18pt	part title.
<code>\LARGE</code>	17pt/19pt	article title.
<code>\huge</code>	20pt/25pt	–
<code>\Huge</code>	25pt/30pt	–

## An interesting and seminal work on various phenomena in fluid mechanics

ALAN N. OTHER<sup>1†</sup>,  
 H.-C. SMITH<sup>1</sup> and J.Q. PUBLIC<sup>2</sup>

<sup>1</sup>Department of Chemical Engineering, University of America, Somewhere, IN 12345, USA

<sup>2</sup>Department of Aerospace and Mechanical Engineering, University of Camford, Academic Street, Camford, CF3 5QL, UK

(Received 1 July 1994 and in revised form 30 October 1998)

**Abstract.** Using Stokes flow between eccentric counter-rotating cylinders as a prototype for bounded nearly parallel lubrication flow, we investigate the effect of a slender recirculation region within the flow field on cross-stream heat or mass transport in the important limit of high Péclet number  $Pe$  where the enhancement over pure conduction heat transfer without recirculation is most pronounced. The steady enhancement is estimated with a matched asymptotic expansion to resolve the diffusive boundary layers at the separatrices which bound the recirculation region. The enhancement over pure conduction is shown to vary as  $\epsilon^{\frac{1}{2}}$  at infinite  $Pe$ , where  $\epsilon^{\frac{1}{2}}$  is the characteristic width of the recirculation region. The enhancement decays from this asymptote as  $Pe^{-\frac{1}{2}}$ .

---

### 1. Introduction

The use of integral equations to solve exterior problems in linear acoustics, i.e. to solve the Helmholtz equation  $(\nabla^2 + k^2)\phi = 0$  outside a surface  $S$  given that  $\phi$  satisfies certain boundary conditions on  $S$ , is very common. A good description is provided by 9. Integral equations have also been used to solve the two-dimensional Helmholtz equation that arises in water-wave problems where there is a constant depth variation. The problem of wave oscillations in arbitrarily shaped harbours using such techniques has been examined (see for example Hwang & Tuck 1970; Lee 1971).

In a recent paper 8 have shown how radiation and scattering problems for vertical circular cylinders placed on the centreline of a channel of finite water depth can be solved efficiently using the multipole method devised originally by Ursell (1950). This method was also used by 2 to prove the existence of trapped modes in the vicinity of such a cylinder at a discrete wavenumber  $k < \pi/2d$  where  $2d$  is the channel width.

Many water-wave/body interaction problems in which the body is a vertical cylinder with constant cross-section can be simplified by factoring out the depth dependence. Thus if the boundary conditions are homogeneous we can write the

† Present address: Plasma Physics Inc., 24 The Street, Lagos, Nigeria



velocity potential  $\phi(x, y, z, t) = \text{Re}\{\phi(x, y) \cosh k(z + h)e^{-i\omega t}\}$ , where the  $(x, y)$ -plane corresponds to the undisturbed free surface and  $z$  is measured vertically upwards with  $z = -h$  the bottom of the channel.

Subsequently Callan *et al.* (1991) proved the existence of, and computed the wavenumbers for, the circular cross-section case. It should be noted however that experimental evidence for acoustic resonances in the case of the circular cylinder is given by Bearman & Graham (1980, pp. 231–232).

6 provided a theory for determining the trapped-mode frequencies for the thin plate, based on a modification of the Wiener–Hopf technique.

The use of channel Green’s functions, developed in §2, allows the far-field behaviour to be computed in an extremely simple manner, whilst the integral equation constructed in §3 enables the trapped modes to be computed in §4 and the scattering of an incident plane wave to be solved in §5. Appendix A contains comparisons with experiments.

## 2. Green’s functions

### 2.1. Construction of equations

We are concerned with problems for which the solution,  $\phi$ , is either symmetric or antisymmetric about the centreline of the waveguide,  $y = 0$ . The first step is the construction of a symmetric and an antisymmetric Green’s function,  $G_s(P, Q)$  and  $G_a(P, Q)$ . Thus we require

$$(\nabla_P^2 + k^2)G_s = (\nabla_P^2 + k^2)G_a = 0 \quad (2.1)$$

in the fluid, where  $\nabla_\rho$  is a gradient operator, except when  $P \equiv Q$ ,

$$G_s, G_a \sim 1/(2\pi) \ln r \quad \text{as } r \equiv |P - Q| \rightarrow 0, \quad (2.2)$$

$$\frac{\partial G_s}{\partial y} = \frac{\partial G_a}{\partial y} = 0 \quad \text{on } y = d, \quad (2.3)$$

$$\frac{\partial G_s}{\partial y} = 0 \quad \text{on } y = 0, \quad (2.4)$$

$$G_a = 0 \quad \text{on } y = 0, \quad (2.5)$$

and we require  $G_s$  and  $G_a$  to behave like outgoing waves as  $|x| \rightarrow \infty$ .

One way of constructing  $G_s$  or  $G_a$  is to replace (2.1) and (2.2) by

$$(\nabla_P^2 + k^2)G_s = (\nabla_P^2 + k^2)G_a = -\delta(x - \xi)\delta(y - \eta) \quad (2.6)$$

and to assume initially that  $k$  has a positive imaginary part.

### 2.2. Further developments

Using results from 8 we see that this has the integral representation

$$-\frac{1}{2\pi} \int_0^\infty \gamma^{-1} [e^{-k\gamma|y-\eta|} + e^{-k\gamma(2d-y-\eta)}] \cos k(x - \xi)t \, dt, \quad 0 < y, \quad \eta < d, \quad (2.7)$$

where

$$\gamma(t) = \begin{cases} -i(1 - t^2)^{\frac{1}{2}}, & t \leq 1 \\ (t^2 - 1)^{\frac{1}{2}}, & t > 1. \end{cases}$$

In order to satisfy (2.4) we add to this the function

$$-\frac{1}{2\pi} \int_0^\infty B(t) \frac{\cosh k\gamma(d-y)}{\gamma \sinh k\gamma d} \cos k(x-\xi)t dt$$

which satisfies (2.1), (2.3) and obtain

$$B(t) = 2e^{-k\gamma d} \cosh k\gamma(d-\eta). \quad (2.8)$$

Thus the function

$$G = -\frac{1}{4}i(H_0(kr) + H_0(kr_1)) - \frac{1}{\pi} \int_0^\infty \frac{e^{-k\gamma d}}{\gamma \sinh k\gamma d} \cosh k\gamma(d-y) \cosh k\gamma(d-\eta) \quad (2.9)$$

satisfies (2.1)–(2.4). By writing this function as a single integral which is even in  $\gamma$ , it follows that  $G$  is real.

### 3. The trapped-mode problem

The unit normal from  $D$  to  $\partial D$  is  $\mathbf{n}_q = (-y'(\theta), x'(\theta))/w(\theta)$ . Now  $G_a = \frac{1}{4}Y_0(kr) + \widetilde{G}_a$  where  $r = \{[x(\theta) - x(\psi)]^2 + [y(\theta) - y(\psi)]^2\}^{\frac{1}{2}}$  and  $\widetilde{G}_a$  is regular as  $kr \rightarrow 0$ . In order to evaluate  $\partial G_a(\theta, \theta)/\partial n_q$  we note that

$$\frac{\partial}{\partial n_q} \left( \frac{1}{4}Y_0(kr) \right) \sim \frac{\partial}{\partial n_q} \left( \frac{1}{2\pi} \ln r \right) = \frac{1}{2\pi r^2 w(\theta)} [x'(\theta)(y(\theta) - y(\psi)) - y'(\theta)(x(\theta) - x(\psi))]$$

as  $kr \rightarrow 0$ . Expanding  $x(\psi)$  and  $y(\psi)$  about the point  $\psi = \theta$  then shows that

$$\begin{aligned} \frac{\partial}{\partial n_q} \left( \frac{1}{4}Y_0(kr) \right) &\sim \frac{1}{4\pi w^3(\theta)} [x''(\theta)y'(\theta) - y''(\theta)x'(\theta)] \\ &= \frac{1}{4\pi w^3(\theta)} [\rho'(\theta)\rho''(\theta) - \rho^2(\theta) - 2\rho'^2(\theta)] \quad \text{as } kr \rightarrow 0. \end{aligned} \quad (3.1)$$

#### 3.1. Computation

For computational purposes we discretize (3.1) by dividing the interval  $(0, \pi)$  into  $M$  segments. Thus we write

$$\frac{1}{2}\phi(\psi) = \frac{\pi}{M} \sum_{j=1}^M \phi(\theta_j) \frac{\partial}{\partial n_q} G_a(\psi, \theta_j) w(\theta_j), \quad 0 < \psi < \pi, \quad (3.2)$$

where  $\theta_j = (j - \frac{1}{2})\pi/M$ . Collocating at  $\psi = \theta_i$  and writing  $\phi_i = \phi(\theta_i)$  etc. gives

$$\frac{1}{2}\phi_i = \frac{\pi}{M} \sum_{j=1}^M \phi_j K_{ij}^a w_j, \quad i = 1, \dots, M, \quad (3.3)$$

where

$$K_{ij}^a = \begin{cases} \partial G_a(\theta_i, \theta_j)/\partial n_q, & i \neq j \\ \partial \widetilde{G}_a(\theta_i, \theta_i)/\partial n_q + [\rho'_i \rho''_i - \rho_i^2 - 2\rho_i'^2]/4\pi w_i^3, & i = j. \end{cases} \quad (3.4)$$

For a trapped mode, therefore, we require the determinant of the  $M \times M$  matrix whose elements are

$$\delta_{ij} - \frac{2\pi}{M} K_{ij}^a w_j,$$

to be zero. Table 1 shows a comparison of results obtained from this method using

**Table 1.** Values of  $kd$  at which trapped modes occur when  $\rho(\theta) = a$ 

$a/d$	$M = 4$	$M = 8$	Callan <i>et al.</i>
0.1	1.56905	1.56905	1.56904
0.3	1.50484	1.50484	1.50484
0.5	1.39128	1.39131	1.39131
0.7	1.32281	1.32287	1.32288
0.9	1.34479	1.35160	1.35185

**Figure 1.** Trapped-mode wavenumbers,  $kd$ , plotted against  $a/d$  for three ellipses: -----,  $b/a = 0.5$ ; —,  $b/a = 1$ ; - · -,  $b/a = 1.5$ .

two different truncation parameters with accurate values obtained using the method of Callan *et al.* (1991).

An example of the results that are obtained from our method is given in figure 1. Figure 2 (*a,b*) shows shaded contour plots of  $\phi$  for these modes, normalized so that the maximum value of  $\phi$  on the body is 1.

### 3.2. Basic properties

Let

$$\rho_l = \lim_{\zeta \rightarrow Z_l^-(x)} \rho(x, \zeta), \quad \rho_u = \lim_{\zeta \rightarrow Z_u^+(x)} \rho(x, \zeta) \quad (3.5a,b)$$

be the fluid densities immediately below and above the cat's-eyes. Finally let  $\rho_0$  and  $N_0$  be the constant values of the density and the vorticity inside the cat's-eyes, so that

$$(\rho(x, \zeta), \phi_{\zeta\zeta}(x, \zeta)) = (\rho_0, N_0) \quad \text{for } Z_l(x) < \zeta < Z_u(x). \quad (3.6)$$

The Reynolds number  $Re$  is defined by  $u_\tau H/\nu$  ( $\nu$  is the kinematic viscosity), the length given in wall units is denoted by  $(\ )_+$ , and the Prandtl number  $Pr$  is set equal to 0.7. In (2.1) and (2.2),  $\tau_{ij}$  and  $\tau_j^\theta$  are

$$\tau_{ij} = \overline{(\bar{u}_i \bar{u}_j)} - \bar{u}_i \bar{u}_j + \overline{(\bar{u}_i u_j^{SGS} + u_i^{SGS} \bar{u}_j)} + \overline{u_i^{SGS} u_j^{SGS}}, \quad (3.7a)$$

$$\tau_j^\theta = \overline{(\bar{u}_j \bar{\theta})} - \bar{u}_j \bar{\theta} + \overline{(\bar{u}_j \theta^{SGS} + u_j^{SGS} \bar{\theta})} + \overline{u_j^{SGS} \theta^{SGS}}. \quad (3.7b)$$

**Figure 2.** Shaded contour plots of the potential  $\phi$  for the two trapped modes that exist for an ellipse with  $a/d = 1.5$ ,  $b/d = 0.75$ . (a) Symmetric about  $x = 0$ ,  $kd = 0.96$ ; (b) antisymmetric about  $x = 0$ ,  $kd = 1.398$ .

*3.2.1. Calculation of the terms* The first terms in the right-hand side of (3.5a) and (3.5b) are the Leonard terms explicitly calculated by applying the Gaussian filter in the  $x$ - and  $z$ -directions in the Fourier space.

The interface boundary conditions given by (2.1) and (2.2), which relate the displacement and stress state of the wall at the mean interface to the disturbance quantities of the flow, can also be reformulated in terms of the transformed quantities. The transformed boundary conditions are summarized below in a matrix form that is convenient for the subsequent development of the theory:

$$Q_C = \begin{bmatrix} -\omega^{-2}V'_w & -(\alpha^t\omega)^{-1} & 0 & 0 & 0 \\ \frac{\beta}{\alpha\omega^2}V'_w & 0 & 0 & 0 & i\omega^{-1} \\ i\omega^{-1} & 0 & 0 & 0 & 0 \\ iR_\delta^{-1}(\alpha^t + \omega^{-1}V''_w) & 0 & -(i\alpha^t R_\delta)^{-1} & 0 & 0 \\ \frac{i\beta}{\alpha\omega}R_\delta^{-1}V''_w & 0 & 0 & 0 & 0 \\ (i\alpha^t)^{-1}V'_w & (3R_\delta^{-1} + c^t(i\alpha^t)^{-1}) & 0 & -(\alpha^t)^{-2}R_\delta^{-1} & 0 \end{bmatrix}. \quad (3.8)$$

$\mathbf{S}^t$  is termed the displacement-stress vector and  $Q_C$  the flow-wall coupling matrix. Subscript  $w$  in (3.8) denotes evaluation of the terms at the mean interface. It is noted that  $V''_w = 0$  for the Blasius mean flow.

*3.2.2. Wave propagation in anisotropic compliant layers* From (2.1), the fundamental wave solutions to (3.1) and (3.2) for a uniformly thick homogeneous layer in the transformed variables has the form of

$$\boldsymbol{\eta}^t = \hat{\boldsymbol{\eta}}^t \exp[i(\alpha^t x_1^t - \omega t)], \quad (3.9)$$

where  $\hat{\boldsymbol{\eta}}^t = \mathbf{b} \exp(i\gamma x_3^t)$ . For a non-trivial wave, the substitution of (1.7) into (1.3) and (1.4) yields the following determinantal equation:

$$\text{Det}[\rho\omega^2\delta_{ps} - C_{pqrs}^t k_q^t k_r^t] = 0, \quad (3.10)$$

where the wavenumbers  $\langle k_1^t, k_2^t, k_3^t \rangle = \langle \alpha^t, 0, \gamma \rangle$  and  $\delta_{ps}$  is the Kronecker delta.

#### 4. Torus translating along an axis of symmetry

Consider a torus with axes  $a, b$  (see figure 2), moving along the  $z$ -axis. Symmetry considerations imply the following form for the stress function, given in body coordinates:

$$\mathbf{f}(\theta, \psi) = (g(\psi) \cos \theta, g(\psi) \sin \theta, f(\psi)). \quad (4.1)$$

Because of symmetry, one can integrate analytically in the  $\theta$ -direction obtaining a pair of equations for the coefficients  $f, g$  in (4.1),

$$f(\psi_1) = \frac{3b}{\pi(2(a+b\cos\psi_1))^{\frac{3}{2}}} \int_0^{2\pi} \frac{(\sin\psi_1 - \sin\psi)(a+b\cos\psi)^{\frac{1}{2}}}{(1-\cos(\psi_1-\psi))(2+\alpha)^{\frac{1}{2}}}, \quad (4.2)$$

$$\begin{aligned} g(\psi_1) = & \frac{3}{\pi(2(a+b\cos\psi_1))^{\frac{3}{2}}} \int_0^{2\pi} \left( \frac{a+b\cos\psi}{2+\alpha} \right)^{\frac{1}{2}} \left\{ f(\psi)[(\cos\psi_1 - \cos\psi - b\beta_1)S + \beta_1 P] \right. \\ & \times \frac{\sin\psi_1 - \sin\psi}{1-\cos(\psi_1-\psi)} + g(\psi) \left[ \left( 2+\alpha - \frac{(\sin\psi_1 - \sin\psi)^2}{1-\cos(\psi-\psi_1)} - b^2\gamma \right) S \right. \\ & \left. \left. + \left( b^2 \cos\psi_1\gamma - \frac{a}{b}\alpha \right) F\left(\frac{1}{2}\pi, \delta\right) - (2+\alpha)\cos\psi_1 E\left(\frac{1}{2}\pi, \delta\right) \right] \right\} d\psi, \quad (4.3) \end{aligned}$$

$$\alpha = \alpha(\psi, \psi_1) = \frac{b^2(1-\cos(\psi-\psi_1))}{(a+b\cos\psi)(a+b\cos\psi_1)}; \quad \beta - \beta(\psi, \psi_1) = \frac{1-\cos(\psi-\psi_1)}{a+b\cos\psi}. \quad (4.4)$$

#### 5. Conclusions

We have shown how integral equations can be used to solve a particular class of problems concerning obstacles in waveguides, namely the Neumann problem for bodies symmetric about the centreline of a channel, and two such problems were considered in detail.

##### *Acknowledgements*

We would like to acknowledge the useful comments of a referee concerning the solution procedure used in §5. A. N. O. is supported by SERC under grant number GR/F/12345.

#### Appendix A. Boundary conditions

It is convenient for numerical purposes to change the independent variable in (4.1) to  $z = y/\tilde{v}_T^{\frac{1}{2}}$  and to introduce the dependent variable  $H(z) = (f - \tilde{y})/\tilde{v}_T^{\frac{1}{2}}$ . Equation (4.1) then becomes

$$(1-\beta)(H+z)H'' - (2+H')H' = H'''. \quad (A1)$$

Boundary conditions to (4.3) follow from (4.2) and the definition of  $H$ :

$$\left. \begin{aligned} H(0) &= \frac{\epsilon \bar{C}_v}{\tilde{v}_T^{\frac{1}{2}}(1-\beta)}; & H'(0) &= -1 + \epsilon^{\frac{2}{3}} \bar{C}_u + \epsilon \hat{C}'_u; \\ H''(0) &= \frac{\epsilon u_*^2}{\tilde{v}_T^{\frac{1}{2}} u_P^2}; & H'(\infty) &= 0. \end{aligned} \right\} \quad (\text{A } 2)$$

### Appendix B

A simple sufficient condition for the method of separation of variables to hold for the convection problem is derived. This criterion is then shown to be satisfied for the ansatz described by (3.27), thus justifying the approach used in §3. The basic ingredient of our argument is contained in the following estimate for a Rayleigh Ritz ratio:

LEMMA 1. *Let  $f(z)$  be a trial function defined on  $[0, 1]$ . Let  $\Lambda_1$  denote the ground-state eigenvalue for  $-d^2g/dz^2 = \Lambda g$ , where  $g$  must satisfy  $\pm dg/dz + \alpha g = 0$  at  $z = 0, 1$  for some non-negative constant  $\alpha$ . Then for any  $f$  that is not identically zero we have*

$$\frac{\alpha(f^2(0) + f^2(1)) + \int_0^1 \left(\frac{df}{dz}\right)^2 dz}{\int_0^1 f^2 dz} \geq \Lambda_1 \geq \left(\frac{-\alpha + (\alpha^2 + 8\pi^2\alpha)^{\frac{1}{2}}}{4\pi}\right)^2. \quad (\text{B } 1)$$

Before proving it, we note that the first inequality is the standard variational characterization for the eigenvalue  $\Lambda_1$ .

COROLLARY 1. *Any non-zero trial function  $f$  which satisfies the boundary condition  $f(0) = f(1) = 0$  always satisfies*

$$\int_0^1 \left(\frac{df}{dz}\right)^2 dz. \quad (\text{B } 2)$$

### References

- Bearman, P. W. & Graham, J. M. R. 1980 Vortex shedding from bluff bodies in oscillating flow: A report on Euromech 119. *J. Fluid Mech.* **99**, 225–245.
- Callan, M., Linton, C. M. & Evans D. V. 1991 Trapped modes in two-dimensional waveguides. *J. Fluid Mech.* **229**, 51–64.
- Dennis, S. C. R. 1985 Compact explicit finite difference approximations to the Navier–Stokes equation. In *Ninth Intl Conf. on Numerical Methods in Fluid Dynamics* (ed. Soubbaramayer & J. P. Boujot). Lecture Notes in Physics, vol. 218, pp. 23–51. Springer.
- Hwang, L.-S. & Tuck, E. O. 1970 On the oscillations of harbours of arbitrary shape. *J. Fluid Mech.* **42**, 447–464.
- Keller, H. B. 1977 Numerical solution of bifurcation and nonlinear eigenvalue problems. In *Applications of Bifurcation Theory* (ed. P. H. Rabinovich), pp. 359–384. Academic.
- Koch, W. 1983 Resonant acoustic frequencies of flat plate cascades. *J. Sound Vib.* **88**, 233–242.

- Lee, J.-J. 1971 Wave-induced oscillations in harbours of arbitrary geometry. *J. Fluid Mech.* **45**, 375–394.
- Linton, C. M. & Evans, D. V. 1992 The radiation and scattering of surface waves by a vertical circular cylinder in a channel. *Phil. Trans. R. Soc. Lond. A* **338**, 325–357.
- Martin, P. A. 1980 On the null-field equations for the exterior problems of acoustics. *Q. J. Mech. Appl. Maths* **33**, 385–396.
- Rogallo, R. S. 1981 Numerical experiments in homogeneous turbulence. *NASA Tech. Mem.* 81835.
- Wijngaarden, L. van 1968 On the oscillations near and at resonance in open pipes. *J. Engng Maths* **2**, 225–240.
- Williams, J. A. 1964 A nonlinear problem in surface water waves. PhD thesis, University of California, Berkeley.

## References

- [1] Bearman, P. W. & Graham, J. M. R. 1980 Vortex shedding from bluff bodies in oscillating flow: A report on Euromech 119. *J. Fluid Mech.* **99**, 225–245.
- [2] Callan, M., Linton, C. M. & Evans D. V. 1991 Trapped modes in two-dimensional waveguides. *J. Fluid Mech.* **229**, 51–64.
- [3] Dennis, S. C. R. 1985 Compact explicit finite difference approximations to the Navier–Stokes equation. In *Ninth Intl Conf. on Numerical Methods in Fluid Dynamics* (ed. Soubbaramayer & J. P. Boujot). Lecture Notes in Physics, vol. 218, pp. 23–51. Springer.
- [4] Hwang, L.-S. & Tuck, E. O. 1970 On the oscillations of harbours of arbitrary shape. *J. Fluid Mech.* **42**, 447–464.
- [5] Keller, H. B. 1977 Numerical solution of bifurcation and nonlinear eigenvalue problems. In *Applications of Bifurcation Theory* (ed. P. H. Rabinovich), pp. 359–384. Academic.
- [6] Koch, W. 1983 Resonant acoustic frequencies of flat plate cascades. *J. Sound Vib.* **88**, 233–242.
- [7] Lee, J.-J. 1971 Wave-induced oscillations in harbours of arbitrary geometry. *J. Fluid Mech.* **45**, 375–394.
- [8] Linton, C. M. & Evans, D. V. 1992 The radiation and scattering of surface waves by a vertical circular cylinder in a channel. *Phil. Trans. R. Soc. Lond. A* **338**, 325–357.
- [9] Martin, P. A. 1980 On the null-field equations for the exterior problems of acoustics. *Q. J. Mech. Appl. Maths* **33**, 385–396.
- [10] Rogallo, R. S. 1981 Numerical experiments in homogeneous turbulence. *NASA Tech. Mem.* 81835.
- [11] Wijngaarden, L. van 1968 On the oscillations near and at resonance in open pipes. *J. Engng Maths* **2**, 225–240.
- [12] Williams, J. A. 1964 A nonlinear problem in surface water waves. PhD thesis, University of California, Berkeley.

