

Multiple-scattering method applied to gyrotropic media

Wojciech Śmigaj, Boris Gralak*

March 16, 2009

In the following, we present the modifications of the multiple-scattering method [1, 2, 3] necessary for handling two-dimensional systems of scatterers characterised by tensor (relative) permittivity $\hat{\epsilon}$ of the form

$$\hat{\epsilon} = \begin{bmatrix} \epsilon_t & ig & 0 \\ -ig & \epsilon_t & 0 \\ 0 & 0 & \epsilon_z \end{bmatrix}. \quad (1)$$

For simplicity, we assume all media to be nonmagnetic ($\mu \equiv 1$). We assume that the direction of invariance coincides with the z axis.

With the permittivity given by eq. (1), the Maxwell's curl equations

$$\nabla \times \mathbf{E} = i\omega\mu_0\mathbf{H}, \quad (2a)$$

$$\nabla \times \mathbf{H} = -i\omega\hat{\epsilon}\epsilon_0\mathbf{E} \quad (2b)$$

decouple into the equations corresponding to the E polarization ($\mathbf{E} \parallel \hat{z}$),

$$\frac{\partial E_z}{\partial y} = i\omega\mu_0 H_x, \quad (3a)$$

$$-\frac{\partial E_z}{\partial x} = i\omega\mu_0 H_y, \quad (3b)$$

$$\frac{\partial H_y}{\partial x} - \frac{\partial H_x}{\partial y} = -i\omega\epsilon_0\epsilon_z E_z, \quad (3c)$$

and the H polarization ($\mathbf{H} \parallel \hat{z}$),

$$\frac{\partial E_y}{\partial x} - \frac{\partial E_x}{\partial y} = i\omega\mu_0 H_z, \quad (4a)$$

$$\frac{\partial H_z}{\partial y} = -i\omega\epsilon_0(\epsilon_t E_x + igE_y), \quad (4b)$$

$$-\frac{\partial H_z}{\partial x} = -i\omega\epsilon_0(-igE_x + \epsilon_t E_y). \quad (4c)$$

In the following, we restrict our attention to the case of the H polarization, where the effects of anisotropy are present. From eqs. (4) we obtain

$$E_x = \frac{1}{i\omega\epsilon_0(g^2 - \epsilon_t^2)} \left(ig \frac{\partial H_z}{\partial x} + \epsilon_t \frac{\partial H_z}{\partial y} \right), \quad (5a)$$

$$E_y = \frac{1}{i\omega\epsilon_0(g^2 - \epsilon_t^2)} \left(-\epsilon_t \frac{\partial H_z}{\partial x} + ig \frac{\partial H_z}{\partial y} \right) \quad (5b)$$

*Institut Fresnel, UMR CNRS 6133, 13397 Marseille Cedex 20, France.

and

$$\frac{\partial^2 H_z}{\partial x^2} + \frac{\partial^2 H_z}{\partial y^2} + \epsilon_0 \mu_0 \left(\epsilon_t - \frac{g^2}{\epsilon_t} \right) \omega^2 H_z = 0. \quad (6)$$

Evidently, the H_z field fulfils the Helmholtz equation $\nabla^2 H_z + k^2 H_z = 0$ with $k^2 = \epsilon_0 \mu_0 (\epsilon_t - g^2/\epsilon_t)$. This is the basic assumption of the multiple-scattering formalism, which we can therefore apply to the analysis of the considered system. With respect to the multiple-scattering method as described in Ref. [3], we need to make only two changes: (1) replacement of the formula $n = \sqrt{\epsilon_t}$ for the refractive index of a medium by $n = \sqrt{\epsilon_t - g^2/\epsilon_t}$, (2) modification of the formula for the scattering matrix of a cylinder. This formula can be derived easily by imposing the conditions of continuity of the tangential components of the electric and magnetic fields on the surface of a cylinder, which we do in the following.

For the case of H polarization, the tangential components in question are H_z and E_ϕ , so we need to impose that

$$\left. \begin{aligned} H_z^{\text{int}}(R, \phi) &= H_z^{\text{ext}}(R, \phi) \\ E_\phi^{\text{int}}(R, \phi) &= E_\phi^{\text{ext}}(R, \phi) \end{aligned} \right\} \quad \text{for all } \phi \in [0, 2\pi), \quad (7)$$

where R denotes the radius of the cylinder and the superscripts ‘‘int’’ and ‘‘ext’’ refer to field expansions in the cylinder interior and exterior, respectively. Equations (5) imply that

$$E_\phi = \frac{1}{i\omega\epsilon_0(g^2 - \epsilon_t^2)} \left(-\epsilon_t \frac{\partial H_z}{\partial r} + \frac{ig}{r} \frac{\partial H_z}{\partial \phi} \right). \quad (8)$$

From the multiple-scattering theory we know that the magnetic field H_z inside and outside the cylinder is given by appropriate Fourier-Bessel expansions,

$$H_z^{\text{int}}(r, \phi) = \sum_m c_m \underbrace{J_m(k_{\text{int}} r)}_{\equiv C_m^H} e^{im\phi}, \quad (9a)$$

$$H_z^{\text{ext}}(r, \phi) = \sum_m [a_m \underbrace{J_m(k_{\text{ext}} r)}_{\equiv A_m^H} + b_m \underbrace{H_m^{(1)}(k_{\text{ext}} r)}_{\equiv B_m^H}] e^{im\phi}, \quad (9b)$$

hence

$$E_\phi^{\text{int}}(R, \phi) = -\frac{1}{i\omega\epsilon_0} \sum_m c_m \underbrace{\frac{(mg_{\text{int}}/R)J_m(k_{\text{int}}R) + \epsilon_{t,\text{int}}k_{\text{int}}J'_m(k_{\text{int}}R)}{g_{\text{int}}^2 - \epsilon_{t,\text{int}}^2}}_{\equiv C_m^E} e^{im\phi}, \quad (10a)$$

$$E_\phi^{\text{ext}}(R, \phi) = -\frac{1}{i\omega\epsilon_0} \left\{ \sum_m a_m \underbrace{\frac{(mg_{\text{ext}}/R)J_m(k_{\text{ext}}R) + \epsilon_{t,\text{ext}}k_{\text{ext}}J'_m(k_{\text{ext}}R)}{g_{\text{ext}}^2 - \epsilon_{t,\text{ext}}^2}}_{\equiv A_m^E} + \sum_m b_m \underbrace{\frac{(mg_{\text{ext}}/R)H_m^{(1)}(k_{\text{ext}}R) + \epsilon_{t,\text{ext}}k_{\text{ext}}H_m^{(1)'}(k_{\text{ext}}R)}{g_{\text{ext}}^2 - \epsilon_{t,\text{ext}}^2}}_{\equiv B_m^E} \right\} e^{im\phi}. \quad (10b)$$

Substituting these formulas to eqs. (7) and solving for b_m and c_m , we obtain

$$b_m = -\frac{A_m^H C_m^E - A_m^E C_m^H}{B_m^H C_m^E - B_m^E C_m^H} a_m, \quad (11a)$$

$$c_m = -\frac{A_m^H B_m^E - A_m^E B_m^H}{B_m^H C_m^E - B_m^E C_m^H} a_m. \quad (11b)$$

We conclude that the scattering matrix \mathbf{S} of a cylinder of circular cross-section is diagonal and its elements are given by

$$S_{ij} = -\frac{A_m^H C_m^E - A_m^E C_m^H}{B_m^H C_m^E - B_m^E C_m^H} \delta_{ij}, \quad (12)$$

where δ_{ij} is the Kronecker delta and the symbols A_m^E etc. are defined in eqs. (9) and (10).

References

- [1] D. Felbacq, G. Tayeb, and D. Maystre, J. Opt. Soc. Am. A **11**, 2526 (1994).
- [2] G. Tayeb and D. Maystre, J. Opt. Soc. Am. A **14**, 3323 (1997).
- [3] D. Maystre, S. Enoch, and G. Tayeb, in *Electromagnetic theory and applications for photonic crystals*, edited by K. Yasumoto (CRC Press, Boca Raton, 2005), chap. 1, pp. 1–46.