A uni-directional optical pulse propagation equation for materials with both electric and magnetic responses

Paul Kinsler*

Blackett Laboratory, Imperial College London, Prince Consort Road, London SW7 2AZ, United Kingdom.

(Dated: November 1, 2018)

I derive uni-directional wave equations for fields propagating in materials with both electric and magnetic dispersion and nonlinearity. The derivation imposes no conditions on the pulse profile except that the material modulates the propagation only slowly: i.e. that loss, dispersion, and nonlinearity have only a small effect over the scale of a wavelength. It also allows a direct term-to-term comparison of the exact bi-directional theory with its approximate uni-directional counterpart.

I. INTRODUCTION

In the past few years, composite materials ("metamaterials") that demonstrate both an electric and magnetic response have been the subject of both experimental and theoretical investigation. Often the motivation for this research is the potential for exotic applications: for example, superresolution [1], or the possibility of "trapped rainbow" light storage [2]. Despite these interesting possibilities, there is also the more basic need for efficient methods for propagating optical pulses in such metamaterials, in particular in one-dimensional (1D) waveguide geometries. Indeed, methods for doing so have already led to interesting predictions (see, e.g., [3-5]). However, these methods, and earlier ones, (e.g. [6-9]) tend to rely on mechanisms such as the introduction of a co-moving frame, and assumptions that the pulse profile has negligible second-order temporal or spatial derivatives. Assuming second-order derivatives are small may well be reasonable, but it means that the pulse profile must remain well behaved. This approximation therefore might well become poorly controlled [6, 10], particularly for ultrashort or otherwise ultrawideband pulses, or exotic or extreme material parameters. Ideally we would prefer to make approximations based solely on the material parameters of our device, so as to avoid making assumptions about the state of an ever-changing propagating pulse.

Here I derive 1D wave equations for a waveguide with both electric and magnetic dispersion, and electric and magnetic nonlinearity. I use the directional fields approach [11, 12], which allows us to directly write down a first-order wave equation for pulse propagation without complicated derivation or approximation. We simply look at the coupled forward and backward wave equations that are a direct re-expression of Maxwell's curl equations, and substitute in the appropriate dispersion and nonlinearity. I also show separate examples for second- and third-order nonlinearities in both electric and magnetic responses, although the effects can be combined if desired. Note that these directional fields are applicable to more than just pulse propagation, as they have been used to simplify Poynting-vector-based approaches to electromagnetic continuity equations [13]. The derivation makes only a single, well-defined approximation to reduce the bi-directional forward-backward coupled model down to a single first-order wave equation – that of assuming small changes over the scale of a wavelength. This approximation is remarkably robust for all physically realistic parameter values – see [14] for an analysis focused on nonlinear effects; more general considerations have been dealt with in terms of factorized wave equations [15]. The resulting wave equation retains all the usual intuitive and analytical simplicity of ordinary wave propagation equations, unlike the computationally intensive approach of a direct numerical solution of Maxwell's equations (see, e.g., [7?????)].

This paper is structured as follows: Directional fields and their re-expression of the Maxwell curl equations is outlined in Section II, followed by the reduction of the bi-directional wave equation into a uni-directional form in Section III. Section IV shows wave equations for a doubly-nonlinear thirdorder nonlinearity material, and Section V does the same for a second-order case. In Section VI propagation under the influence of typical metamaterial responses is discussed, and I conclude in Section VII.

II. DIRECTIONAL FIELDS

The directional fields approach [11] allows us to write down wave equations for hybrid electromagnetic fields \mathbf{G}^{\pm} . Note that here I define \mathbf{G}^{\pm} with an alternate (and more sensible) sign convention than previously. Further, I also allow for more general types of polarization and magnetization in such a way as to provide a *simpler* presentation. For propagation along the unit vector \mathbf{u} , the propagation (curl) equation for \mathbf{G}^{\pm} is written in the frequency domain as¹

$$\nabla \times \mathbf{G}^{\pm} = \pm \iota \omega \alpha_r \beta_r \mathbf{u} \times \mathbf{G}^{\pm} \pm \iota \omega \beta_r \mathbf{u} \times \mathbf{P}_c + \iota \omega \alpha_r \mu_0 \mathbf{M}_c$$
(1)

with

$$\mathbf{G}^{\pm}(\boldsymbol{\omega}) = \boldsymbol{\alpha}_{r}(\boldsymbol{\omega})\mathbf{E}(\boldsymbol{\omega}) \pm \boldsymbol{\beta}_{r}(\boldsymbol{\omega})\mathbf{H}(\boldsymbol{\omega}) \times \mathbf{u}.$$
 (2)

Here the electric response of the material is encoded in two parts: a spatially invariant linear response component α_r , and

^{*}Electronic address: Dr.Paul.Kinsler@physics.org

¹ See derivation in Appendix A.

the remaining contributions (of any type) in \mathbf{P}_{c} . Similarly, the magnetic response is divided up in the same way between β_r and $\mu_0 \mathbf{M}_c$. Generally we will put the entire non-lossy linear response of the medium (i.e. the dispersion) into the reference parameters α_r and β_r , although it may also be convenient to specify only that the product $\alpha_r \beta_r$ is real (cf. [?]). All the nonlinear responses and other complications ("corrections"), such as spatial variations in the material parameters, remain in \mathbf{P}_c and \mathbf{M}_c . As an example, in [11] this approach was applied to second-harmonic generation in a periodically poled dielectric crystal. The time derivatives of these corrections \mathbf{P}_c and \mathbf{M}_c correspond to bound electric and magnetic currents respectively [13]. These P_c and M_c are functions of both fields **E** and **H**, i.e. $\mathbf{P}_c \equiv \mathbf{P}_c(\mathbf{E}, \mathbf{H})$ and $\mathbf{M}_c \equiv \mathbf{M}_c(\mathbf{E}, \mathbf{H})$. If we choose instead to have frequency-independent α_r and β_r , then the remaining linear response can simply be included in \mathbf{P}_c and \mathbf{M}_c ; in this case the "weak loss and nonlinearity" condition I use later to decouple forward and backward fields would then need to be broadened to include weak dispersion as well (also see [11] for more discussion). However, neither version imposes any requirements on the pulse profile.

It is useful to give a simple example of the directional fields to provide some insight into their nature. In the pure transverse plane-polarized case, with fields propagating along the z direction, and frequency-independent (material parameters) permitivity ε_r and permeability μ_r , we can write

$$G_x^{\pm} = \sqrt{\varepsilon_r} E_x \pm \sqrt{\mu_r} H_y, \qquad (3)$$

$$G_{y}^{\pm} = \sqrt{\varepsilon_{r}} E_{y} \mp \sqrt{\mu_{r}} H_{x}, \qquad (4)$$

where this simple G_x^{\pm} definition matches the original proposal of Fleck [16].

It is worth considering how reflections arise in this picture based on spatially invariant reference parameters augmented by corrections terms. Leaving aside for now the distinctions between spatially propagated fields and temporally propagated ones (see the discussion in [15]), transition to a new media can be handled in two ways. First, we could map the existing fields \mathbf{G}^{\pm} onto new ones \mathbf{G}_n^{\pm} based on new reference parameters α_{rn} and β_{rn} . Here a pure \mathbf{G}^+ field would separate into two pieces, one a forward propagating \mathbf{G}_n^+ , and the other a "reflected" backward propagating \mathbf{G}_n^- . Second, we might retain the existing reference parameters, and have modified corrections \mathbf{P}'_{c} and \mathbf{M}'_{c} . These altered correction terms then couple the forward and backward directed fields, inducing the necessary reflection in G^- ; although as a side-effect of our now no longer optimal α_r and β_r , the forward evolving field is made up of coupled G^+ and G^- components [11].

A. Material response

We define the electric and magnetic material response in the frequency domain, as it greatly simplifies the description of the linear components. Let us chose a *reference* behaviour given by $\varepsilon_r(\omega), \mu_r(\omega)$, and use them to define reference parameters $\alpha_r(\omega) = \sqrt{\varepsilon_r(\omega)}$ and $\beta_r(\omega) = \sqrt{\mu_r(\omega)}$. Note that these are allowed to have a frequency dependence [11], and that $\alpha_r \beta_r$ is just the reciprocal of the (reference) speed of light in the medium (i.e. n_r/c). We therefore have that the electric displacement and magnetic fields are

$$\mathbf{D}(\boldsymbol{\omega}) = \boldsymbol{\varepsilon}_0 \mathbf{E}(\boldsymbol{\omega}) + \mathbf{P}(\boldsymbol{\omega}) = \boldsymbol{\varepsilon}_r(\boldsymbol{\omega}) \mathbf{E}(\boldsymbol{\omega}) + \mathbf{P}_c(\boldsymbol{\omega}), \quad (5)$$

$$\mathbf{B}(\boldsymbol{\omega}) = \mu_0 \mathbf{H}(\boldsymbol{\omega}) + \mathbf{M}(\boldsymbol{\omega}) = \mu_r(\boldsymbol{\omega}) \mathbf{H}(\boldsymbol{\omega}) + \mu_0 \mathbf{M}_c(\boldsymbol{\omega}).$$
(6)

To give a specific example, we can define frequencydependent loss and dispersive corrections by $\kappa_{\varepsilon}(\omega)$ and $\kappa_{\mu}(\omega)$, along with (e.g.) independent third-order nonlinearities $\chi_{\varepsilon}, \chi_{\mu}$ to both the material responses; although any appropriate expression can be used – even magneto-electric or other types. Thus we can write the frequency domain expressions

$$\mathbf{P}_{c}(\boldsymbol{\omega}) = \boldsymbol{\alpha}_{r}^{2} \kappa_{\varepsilon} \mathbf{E} + \varepsilon_{0} \mathcal{F} \left[\boldsymbol{\chi}_{\varepsilon} E^{2}(t) \right] \star \mathbf{E}$$
(7)

$$\mu_0 \mathbf{M}_c(\boldsymbol{\omega}) = \beta_r^2 \kappa_\mu \mathbf{H} + \mu_0 \mathcal{F} \left[\chi_\mu H^2(t) \right] \star \mathbf{H}, \tag{8}$$

where $\mathcal{F}[...]$ takes the Fourier transform (which is necessary because nonlinear effects are defined in the time domain as powers of the field) and \star denotes a convolution [i.e., $a \star b = \int a(\omega)b(\omega - \omega')d\omega'$]. If the nonlinearity is time dependent, then the simple $\chi_{\varepsilon}E^2$ type terms can be replaced with the appropriate convolution. In general, it is best to pick α_r , β_r subject to the condition that the sizes of \mathbf{P}_c and \mathbf{M}_c are minimised.

In a double-negative material (with both ε , $\mu < 0$) we would get imaginary α_r , β_r , changing the complex phase of $\mathbf{G}^{\pm}(\omega)$ away from that given by the original **E** and **H**. Since this is in the frequency domain, it converts into a phase shift in the time domain, so although imaginary-valued α_r , β_r might seem inconvenient, it does not give unphysical results.

III. WAVE EQUATIONS

Starting with the vectorial curl equation (1), I first take the 1D, but bi-directional, limit, and describe the approximation necessary to produce a simpler uni-directional form. After this, I discuss how the common transformations used in optical wave equations can be applied in this context. All equations and field quantities are in the frequency (ω) domain, unless explicitly noted otherwise.

A. Bi-directional wave equations

Here we set **u** along the *z* axis without loss of generality, and consider just an *x* polarized wave (i.e., consisting of E_x, H_y). This means we use the *y* component of eqn. (1) with $\partial_z = d/dz$, so that the wave equations for the *full spectrum* fields $G_x^{\pm}(\omega)$, coupled by corrections $P_x \equiv P_{c,x}(\omega)$ and $M_y \equiv M_{c,y}(\omega)$ are

$$\partial_z G_x^{\pm} = \pm \iota \omega \alpha_r \beta_r G_x^{\pm} \quad \pm \iota \omega \beta_r P_x \quad + \iota \omega \alpha_r M_y. \tag{9}$$

Following the detailed discussion in $[15]^2$, we say that this wave equation *propagates* ("steps") the fields forward along the *z* direction using oppositely *directed* fields G_x^+ and G_x^- . These fields can be written as functions of either time or frequency, and pulses they describe therefore *evolve* (travel) forward or backward in time.

Consider the example case with parameters $\kappa_{\varepsilon}(\omega)$ and $\kappa_{\mu}(\omega)$, and $\chi_{\varepsilon}, \chi_{\mu}$ in eqns. (7) and (8). Defining $k_r(\omega) = \omega \alpha_r(\omega) \beta_r(\omega)$, we get

$$\partial_{z}G_{x}^{\pm} = \pm ik_{r}G_{x}^{\pm} \pm \frac{ik_{r}\kappa_{\varepsilon}}{2} \left(G_{x}^{+}+G_{x}^{-}\right) + \frac{ik_{r}\kappa_{\mu}}{2} \left(G_{x}^{+}-G_{x}^{-}\right)$$
$$\pm \frac{ik_{r}}{2}\frac{\varepsilon_{0}}{\varepsilon_{r}}\mathcal{F}\left[\chi_{\varepsilon}E^{2}\right] \star \left(G_{x}^{+}+G_{x}^{-}\right)$$
$$+ \frac{ik_{r}}{2}\frac{\mu_{0}}{\mu_{r}}\mathcal{F}\left[\chi_{\mu}H^{2}\right] \star \left(G_{x}^{+}-G_{x}^{-}\right). \tag{10}$$

Note that even for a frequency-independent choice of the reference parameters α_r and β_r , the reference wave vector k_r retains a (linear) frequency dependence. Also, the dispersion and/or loss parameters κ_{ε} , κ_{μ} are directly related to ε and μ respectively, and not to a refractive index *n* or wavevector *k*. This is why there is a factor of 1/2 associated with their appearance in eqn. (10) and subsequently.

If written in the time domain, these wave equations are seen to propagate the full temporal history of a field forward in space. There, the reference propagation given by $\pm \iota k_r G_x^{\pm}$ becomes a convolution if k_r retains a nontrivial frequency dependence. However, if we expand $k_r(\omega)$ around a central frequency ω_1 in powers of $\omega - \omega_1$, we can instead convert it (in the time domain) into a Taylor series in time derivatives, which is a popular alternative to the frequency domain form used here. However, if implementing a split-step Fourier method of solving these wave equations, dispersion is applied in the frequency domain, so that in general such an expansion is an unnecessary complication.

B. Uni-directional approximation

Now we apply the approximation: that the effect of any correction terms is small over propagation distances of one wavelength – or, if you prefer, over time intervals of one optical period. This translates into a weak loss and nonlinearity assumption; and if the correction terms \mathbf{P}_c and \mathbf{M}_c include dispersion, a weak dispersion assumption is also made. These are rarely very stringent approximations. If $|\mathbf{P}_c| << |\mathbf{D}|$ and $|\mu_0\mathbf{M}_c| << |\mathbf{B}|$, then a forward \mathbf{G}^+ has minimal copropagating \mathbf{G}^- [11]. Further, the forward field has a wave vector k_r evolving as $\exp(+ik_r z)$, but any generated backward component will evolve as $\exp(-ik_r z)$. This gives a very rapid relative oscillation $\exp(-2ik_r z)$, which will quickly average to zero. Nevertheless, although achievable optical nonlinearity coefficients fall well within this approximation, care may

need to be taken with the dispersion, particularly if near a band edge or in the vicinity of a narrow resonance.

A directly comparable approximation is treated exhaustively in [15], where although applied to bi-directional factorizations of the second-order wave equation, the physical considerations are exactly the same: Deviations from the reference behaviour over a propagation distance of one wavelength should be small. Note that the slow evolution approximation applied here is not the same as other "slowly varying" types of approximation [e.g., the slowly varying envelope approximation (SVEA)] – although the physical motivation is similar, the approach used here is far less restrictive.

After we apply this weak correction or "slow evolution" approximation, we set the initial value of $G_x^- \equiv 0$, and can be sure that it will stay negligible. Thus eqn. (9) for the full spectrum, forward directed field $G_x^+(\omega)$ can be written as

$$\partial_z G_x^+ \simeq +\iota \omega \alpha_r \beta_r G_x^+ + \iota \omega \beta_r P_x + \iota \omega \alpha_r \mu_0 M_y.$$
(11)

Alternatively, we can scale the G_x^+ field so that it has the same units and scaling as the electric field, using $F_x^+(\omega) = G_x^+(\omega)/2\alpha_r(\omega)$. This gives

$$\partial_z F_x^+ \simeq +\iota \omega \alpha_r \beta_r F_x^+ + \iota \frac{\omega \beta_r}{2\alpha_r} P_x^+ + \iota \frac{\omega}{2} \mu_0 M_y^+.$$
(12)

Note that $E_x^+ = G_x^+/2\alpha_r \equiv F_x^+$ and $H_y^+ = G_x^+/2\beta_r \equiv F_x^+\alpha_r/\beta_r$, since $G_x^- = 0$. In either version of these uni-directional equations, $P_x^+ \equiv P(E_x^+, H_y^+)$ and $M_y^+ \equiv M(H_y^+, E_x^+)$ – the uni-directional (residual) polarization P_x^+ and (residual) magnetization M_y^+ should not be written as functions of the total fields E_x and H_y .

C. Modifications

Either of eqns. (11) or (12) by themselves are sufficient to model the propagation of the electric and magnetic fields. However, there are many traditional simplifications which can be applied, and which in other treatments are even sometimes *required* in order obtain a simple evolution equation. In particular, the various envelope equations [6–8, 17] all use comoving and/or envelopes as a preparation for discarding inconvenient derivatives: Here such steps are optional extras.

These are all considered in more detail for a factorised wave equation approach in [15], but here I have adapted them for this context.

- 1. A *co-moving frame* can now be added, using $t' = t z/v_f$. This is a simple linear process that causes no extra complications; the leading right-hand side (RHS) $\iota \alpha_r \beta_r \omega = \iota k_r$ term is replaced by $\iota (\alpha_r \beta_r \omega \mp k_f)$, for frame speed $v_f = \omega_0/k_f$. Setting $k_f = k_r(\omega_0)$ will cancel the phase velocity v_p of the pulse at ω_0 , not the group velocity.
- 2. The *field can be split up* into pieces localized at certain frequencies, as done in descriptions of optical parametric amplifiers or Raman combs (as in, e.g., [6, 18, 19]).

² Section III

The wave equation can then be separated into one equation for each piece, coupled by the appropriate frequency-matched polarization terms (see, e.g., [20]).

- 3. A *carrier-envelope* description of the field can easily be implemented with the usual prescription of [21, 22] $F_x^+(t) = A(t) \exp[\iota(\omega_1 t - k_1 z)] + A^*(t) \exp[-\iota(\omega_1 t - k_1 z)]$ defining an envelope A(t) with respect to carrier frequency ω_1 and wave vector k_1 ; this also provides a built-in a co-moving frame $v_f = \omega_1/k_1$. Multiple envelopes centred at different carrier frequencies and wave vectors (ω_i, k_i) can also be used [20, 21].
- 4. Bandwidth restrictions might be added (see below), either to ensure a smooth envelope or to simplify the wave equations; in addition they might be used to separate out or neglect frequency mixing terms or harmonic generation. As it stands, no bandwidth restrictions were applied when deriving eqns. (11) or (12) there are only the limitations introduced by the dispersion and/or polarization models to consider. Typically we would expand the model parameters to the first few orders about some convenient reference frequency ω_0 .
- 5. *Mode averaging* is where the transverse extent of a propagating beam is not explicitly modeled, but is subsumed into a description of a transverse mode profile; as such it is typically applied to situations involving optical fibres or other waveguides. Thus we could use mode averaging when calculating the effective dispersion or nonlinear parameters. See, for example, [23] for a recent approach, which goes beyond a simple addition of a frequency dependence to the "effective area" of the mode, and generalizes the effective area concept itself.

D. Diffraction

One important feature lacking in this approach is the handling of transverse effects such as diffraction, although they can be inserted by hand (at least in the paraxial limit) by adding the term $\iota(\partial_x^2 + \partial_y^2)F_x^+/2k_r$ to the RHS [12]. However, no treatment of transverse effects has been achieved in a native directional fields description on the basis of the firstorder equations – although transverse terms arise naturally in the second-order equation resulting from taking the curl of eqn. (1). Treating nonlinear diffraction [24] suffers the same difficulties, although presumably it might be incorporated in an analogous way as to ordinary diffraction.

IV. THIRD-ORDER NONLINEARITY

Third-order nonlinearities are common in many materials, for example in the silica used to make optical fibres (see, e.g., [9]). There are many applications of significant scientific interest, for example, white light supercontinua [25–27], optical rogue waves [28]; or filamentation [29, 30].

Here we study propagation through such a material, with non-reference linear responses $\kappa_{\varepsilon}, \kappa_{\mu}$ (describing e.g. loss and dispersion), and instantaneous magnetic third-order nonlinearity χ_{μ} [?] along with the more common electric type χ_{ε} . For such a system, and for plane-polarized fields, the propagation equation is

$$\partial_{z}F_{x}^{+} = +\imath k_{r} \left[1 + \frac{\kappa_{\varepsilon}}{2} + \frac{\kappa_{\mu}}{2}\right]F_{x}^{+} + \frac{\imath k_{r}}{2}\frac{\varepsilon_{0}}{\varepsilon_{r}} \left[\chi_{\varepsilon} + \frac{\mu_{0}}{\varepsilon_{0}}\frac{\varepsilon_{r}^{2}}{\mu_{r}^{2}}\chi_{\mu}\right]\mathcal{F}\left[F_{x}^{+2}(t)\right] \star F_{x}^{+}.$$
(13)

This is a generalized nonlinear Schrödinger (NLS) equation, and it retains both the full field (i.e. uses no envelope description) and the full nonlinearity (i.e. includes third-harmonic generation). The only assumptions made are that of transverse fields and weak dispersive and nonlinear responses; these latter assumptions allow us to decouple the forward and backward wave equations. This decoupling allows us, without any extra approximation, to reduce our description to one of forward-only pulse propagation. The specific example chosen here is for a cubic nonlinearity, but it is easily generalized to the noninstantaneous case or even other scalar nonlinearities.

We can transform eqn. (13) into one closer to the ordinary NLS equation by representing the field in terms of an envelope and carrier

$$F_x^+(t) = A(t) \exp[\iota(\omega_0 t - k_0 z)] + A^*(t) \exp[-\iota(\omega_0 t - k_0 z)],$$
(14)

where we choose the carrier wave vector to be $k_0 = k_r(\omega_0) = \omega_0 \alpha_r(\omega_0) \beta_r(\omega_0)$. After separating into a pair of complexconjugate equations (one for *A* and one for *A**), and ignoring the off-resonant third-harmonic generation term, this gives us the expected NLS equation without diffraction. The chosen carrier effectively moves us into a frame that freezes the carrier oscillations, but this phase velocity ($v_p = \omega/k$) frame differs from one that is co-moving with the pulse envelope (i.e., one moving at the group velocity $v_g = \partial \omega/\partial k$). After we transform into a frame co-moving with the group velocity at ω_0 , where $\Delta_g = \omega_0 [v_g^{-1}(\omega_0) - v_p^{-1}(\omega_0)]$, the wave equation for $A(\omega)$ is

$$\partial_{z}A = +\imath K(\omega)A + \frac{\imath k_{r}}{2}\frac{\varepsilon_{0}}{\varepsilon_{r}}\mathcal{F}\left[2\chi|A(t)|^{2}A(t)\right], \qquad (15)$$

where $K(\omega) = k_r [\kappa_{\varepsilon}(\omega) + \kappa_{\mu}(\omega)]/2 + \Delta_g$; and $\chi = \chi_{\varepsilon} - (\mu_0 \varepsilon_r^2 / \varepsilon_0 \mu_r^2) \chi_{\mu}$. All that has been assumed to derive this standard envelope NLS equation is uni-directional propagation and negligible third-harmonic generation. The self-steepening term, often seen in (or added to) NLS equations arises from the frequency dependence of k_r . This self-steepening has both electric and magnetic contributions, which can be adjusted independently, as has been pointed out by Wen *et al.* [4] for the case of the SVEA limit. In Section VI, I discuss how the importance of each contribution varies with frequency for both a double-plasmon model (as in [4]), and a wire-array and splitring model more typical of practical metamaterials.

It is worth comparing this eqn. (15) to D'Aguanno *et al.*'s [5] eqn. (5) [hereafter eqn. (DMB5)]. Although in many respects they appear to be the same, mine is far more general

and can be applied (at least in principle) to an arbitrarily wide pulse bandwidth, whereas theirs is subject to the rather restrictive SVEA. For example, my eqn. (15) results from only one "slow evolution" approximation, as opposed to the numerous steps, substitutions, and approximations in Section 2 of [5]. I also retain the possibility of arbitrary dispersion $K(\omega)$, whereas theirs retains only the second-order part (i.e. as $\propto \partial_t^2$, which in the frequency domain would be $\propto \omega^2$). Indeed, with the dispersion and nonlinear factors in my eqn. (13) combined, that full-spectrum wave propagation equation is scarecly more complicated than eqn. (DMB5). Similar remarks also hold when comparing eqn. (15) to Wen et al.'s [4]: but although Wen et al.'s result is also restricted by the SVEA, it does at least allow for diffraction. Both, however, along with Scalora et al.'s form [3], cannot model the full non-envelope field, nor revert to an exact and explicitly bi-directional form, as in my eqn. (9) or (10).

V. SECOND-ORDER NONLINEARITY

Treating a second-order nonlinearity is more complicated than the third-order case, since it typically couples the two possible polarization states of the field together. Such interactions occur in materials used for optical parametric amplification, and have long been used for a wide variety of applications (see, e.g., [21, 31, 32]). To model the cross-coupling between the orthogonally polarised fields, it is necessary to solve for both field polarizations; and to allow for the birefringence we need two pairs of (non-reference) linear responses, i.e. $\kappa_{\varepsilon x}$, $\kappa_{\varepsilon y}$ and $\kappa_{\mu x}$, $\kappa_{\mu y}$.

As an example, I choose a magnetic nonlinearity that couples H_y and H_x in the same way as the electric nonlinearity couples E_x and E_y , although other configurations are possible. This means that the $\beta_r \mathbf{u} \times \mathbf{P}$ term in eqn. (1), which represents the non-reference part of the electric response, needs to include those for the standard second-order nonlinear terms (here $P_x \propto E_x E_y$ and $P_y \propto E_x^2$). Similarly, the $\alpha_r \mu_0 \mathbf{M}$ term has ones for the complementary second-order nonlinear magnetic response. Note that second-order nonlinear magnetic effects have been measured in split ring resonators by Klein *et al.* [?].

Since it is convenient, I split the vector form of the \mathbf{G}^{\pm} wave equation up into its transverse *x* and *y* components. By noting that the definition of G_y^{\pm} means that $H_x^+ = -F_y^+ \alpha_r / \beta_r$, the 1D wave equations can be written as

$$\partial_{z}F_{x}^{+} = +\iota k_{r}\left[1 + \frac{\kappa_{\varepsilon x}}{2} + \frac{\kappa_{\mu y}}{2}\right]F_{x}^{+} + 2\frac{\iota k_{r}}{2}\frac{\varepsilon_{0}}{\varepsilon_{r}}\left[\chi_{\varepsilon} - \frac{\mu_{0}}{\varepsilon_{0}}\left(\frac{\varepsilon_{r}}{\mu_{r}}\right)^{\frac{3}{2}}\chi_{\mu}\right]\mathcal{F}\left[F_{y}^{+}(t)F_{x}^{+}(t)\right]$$
(16)

$$\partial_{z}F_{y}^{+} = +\iota k_{r} \left[1 + \frac{\kappa_{\varepsilon y}}{2} + \frac{\kappa_{\mu x}}{2}\right]F_{y}^{+} + \frac{\iota k_{r}}{2}\frac{\varepsilon_{0}}{\varepsilon_{r}}\left[\chi_{\varepsilon} + \frac{\mu_{0}}{\varepsilon_{0}}\left(\frac{\varepsilon_{r}}{\mu_{r}}\right)^{\frac{3}{2}}\chi_{\mu}\right]\mathcal{F}\left[F_{x}^{+}(t)^{2}\right].$$
(17)

These wave equations for the field are strikingly similar to the usual SVEA equations used to propagate narrowband pulses; the main differences are the addition of terms for magnetic dispersion ($\kappa_{\mu x}, \kappa_{\mu y}$) and nonlinearity (χ_{μ}), and the lack of a co-moving frame.

We can transform eqns. (16) and (17) into a form close to the usual equations for a parametric amplifier by representing the x and y polarized fields in terms of three envelope and carrier pairs:

$$F_{x}^{+}(t) = A_{1}(t) \exp[\iota(\omega_{1}t - k_{1}z)] + A_{1}^{*}(t) \exp[-\iota(\omega_{1}t - k_{1}z)] + A_{2}(t) \exp[\iota(\omega_{2}t - k_{2}z)] + A_{2}^{*}(t) \exp[-\iota(\omega_{2}t - k_{2}z)] (18) F_{y}^{+}(t) = A_{3}(t) \exp[\iota(\omega_{3}t - k_{3}z)] + A_{3}^{*}(t) \exp[-\iota(\omega_{3}t - k_{3}z)], (19)$$

where $\omega_3 = \omega_1 + \omega_2$. After separating into pairs of complexconjugate equations (one each for all A_i and A_i^*), and ignoring the off-resonant polarization terms, we transform into a frame co-moving with the group velocity, although here we select the group velocity of a preferred frequency component, with $\Delta_g = \omega (v_g^{-1} - v_p^{-1})$. The wave equations for the $A_i(\omega)$ are then

$$\partial_{z}A_{1} = +\iota K_{1}(\omega)A_{1} + \frac{\iota k_{0}^{2}}{2k_{1}}\chi^{-}\mathcal{F}[2A_{3}(t)A_{2}^{*}(t)]e^{-\iota\Delta kz} \quad (20)$$

$$\partial_z A_2 = +\iota K_2(\omega) A_2 + \frac{\iota k_0^2}{2k_2} \chi^- \mathcal{F}[2A_3(t)A_1^*(t)] e^{-\iota \Delta kz}$$
(21)

$$\partial_{z}A_{3} = +\iota K_{3}(\omega)A_{3} + \frac{\iota k_{0}^{2}}{2k_{3}}\chi^{+} \mathcal{F}[A_{1}(t)A_{2}(t)]e^{+\iota\Delta kz}.$$
 (22)

Here $K_{1,2}(\omega) = k_{1,2}[\kappa_{\varepsilon x}(\omega) + \kappa_{\mu y}(\omega)]/2 + \Delta_g$ and $K_3(\omega) = k_3[\kappa_{\varepsilon y}(\omega) + \kappa_{\mu x}(\omega)]/2 + \Delta_g$; we choose k_r for each equation differently (i.e., with $k_r \in \{k_1, k_2, k_3\}$); also the phase mismatch term is $\Delta k = k_3 - k_2 - k_1$. The combined nonlinear coefficient is $\chi^{\pm} = \chi_{\varepsilon} \pm (\mu_0/\varepsilon_0)(\varepsilon_r/\mu_r)^{3/2}\chi_{\mu}$.

VI. DISCUSSION

Examining the respective roles of the reference permittivity ε_r and permeability μ_r in eqns. (13) and (16), (17), we see that as far as dispersion and other linear effects are concerned, the two components simply add. In contrast, their effect on nonlinear terms is more dramatic: with the ratio $Y^2 = \varepsilon_r/\mu_r$ scaling the nonlinear corrections to the magnetization into the electric field units of \mathbf{F}^{\pm} . This is because Y^2 determines how much of a given directional field \mathbf{F}^{\pm} is electric field and how much magnetic field; large values of Y^2 correspond to cases where the magnetic field is most prominent. Indeed, Y is just the reciprocal of the electromagnetic impedance of our chosen



FIG. 1: Normalised electromagnetic field ratio and ε, μ curves for Drude responses in both permittivity ε_r and permeability μ_r . The magnetic resonance at $\omega_{\mu} = \omega_{\varepsilon}/\sqrt{2}$ is lower than the (dielectric) plasma frequency ω_{ε} , and $\gamma_{\varepsilon} = \gamma_{\mu} = 0.01 \omega_{\varepsilon}$. Large |Y| corresponds to mostly magnetic \mathbf{G}^{\pm} fields, small |Y| corresponds to mostly electric \mathbf{G}^{\pm} . The frequency ranges of propagating negative phase velocity (NPV) and positive phase velocity (PPV) light are shown.

reference medium, and only if *Y* is real-valued do propagating fields exist, since otherwise the fields become evanescent.

Figures 1 and 2 show how *Y* varies with frequency for two different metamaterial types, with the dispersions encoded on ε_r and μ_r and scaled by ω^2 to moderate the low-frequency singularity of the Drude response. The extreme limits of large *Y* occur when $|\mu_r| \ll |\varepsilon_r|$, that is, usually just at an edge of a non-propagating band, where μ_r is about to change sign. In such a region, it would be better to revert to the \mathbf{G}^{\pm} fields, or to rescale the propagation equations into units of magnetic field (e.g., with some $\mathbf{K}^{\pm} = \mathbf{G}^{\pm}/2\beta_r$).

In previous work [3–5], a Drude type response for both ε and μ was assumed, where $\varepsilon_r, \mu_r \propto 1 - \omega_{\varepsilon,\mu}^2 / (\omega^2 - \iota \gamma_{\varepsilon,\mu} \omega);$ and this situation is shown on Fig. 1. However, although the dielectric response in metamaterials (e.g., a wire grid array [? ?]) often has this behaviour, the magnetic response of split ring resonators (SRRs) differs. SRR magnetization is best described by a pseudo-Lorentz model³ [?] with $\mu_r \propto 1 +$ $F_{\mu}\omega^2/(\omega^2-\omega_{\mu}^2-i\gamma_{\mu}\omega)$, although sometimes a true Lorentz response is used instead, $\mu_r \propto 1 + F_\mu \omega_\mu^2 / (\omega^2 - \omega_\mu^2 - \iota \gamma_\mu \omega)$. Note the difference between the numerators in these latter two expressions: a frequency-dependent ω^2 versus a constant material parameter ω_{μ}^2 . The pseudo-Lorentz model has an incorrect high-frequency behaviour, and so it is incompatible with the Kramers-Kronig relations that enforce causality. However, at low and medium frequency it is a better match to the physical response of SRRs, and so I use it for Figs. 2 and 3.

There are frequency ranges over which the linear material responses vary dramatically, and in particular on Fig. 3 (which uses the same model as Fig. 2) this is evident for both the refractive index *n* and group velocity v_g . If we aim to operate in such regions, this leads to two potential complications. First, if we have chosen reference parameters that do not match the



FIG. 2: Normalised electromagnetic field ratio and ε, μ curves for Drude response permittivity ε_r (dot-dashed line), with a pseudo-Lorentz response for the permeability μ_r (dashed line). The magnetic resonance at $\omega_{\mu} = \omega_{\varepsilon}/\sqrt{2}$ is lower than the (dielectric) plasma frequency ω_{ε} , and $\gamma_{\varepsilon} = \gamma_{\mu}/5 = 0.01 \omega_{\varepsilon}$, $F_{\mu} = 5$. The high-frequency behaviour of the pseudo-Lorentz model "illegally" increases faster than that of the Drude model, whereas a properly causal form should match it. Apart from detail, and the high-frequency behaviour, replacing the pseudo-Lorentz model with the (causal) Lorentz one gives a figure of similar appearance. The frequency ranges of propagating NPV and PPV light are shown.



FIG. 3: Normalised refractive index *n* (solid line) and group velocity $v_g = dk/d\omega$ (dashed line) for the system defined in fig. 2, for only those frequencies where the field propagates. By comparing with fig. 2, we can see that the edges of the NPV band are dominated by the magnetic field, whereas the lower edge of the PPV band is dominated by the electric field. Note that in the NPV band, the sign of the group velocity is not tied to the sign of the phase velocity.

linear material responses exactly, then the correction terms will become large, meaning that our wavelength-scale "slow evolution" approximation may come under threat. Second, even if our reference parameters do match the linear material responses exactly, our wavelength-scale will have become frequency dependent, and so again our "slow evolution" approximation may be threatened. In either case the solution is simple – we just need to revert to the bi-directional wave equations [i.e., eqns. (9) or (10)]. However, this does not necessarily mean that any backward evolving fields are generated (as explained in [11], and following a different approach in [15]), so that in principle one could optimize the propagation by reinstating it only over those frequency ranges where it becomes necessary.

³ Also known as the "F-model"

VII. CONCLUSIONS

I have derived a uni-directional optical pulse propagation equation for media with both electric and magnetic responses, based on the directional fields approach [11]. This involved a re-expression of Maxwell's equations, and required only a single approximation to reduce a one dimensional bi-directional model, to a uni-directional first-order wave equation. The simplicity of this approach makes it very convenient in waveguides, optical fibres, or other collinear situations. The important approximation is that the pulse evolves only slowly on the scale of a wavelength; and indeed this is a valid assumption in a wide variety of cases – note in particular that nonlinear effects have to be unrealizably strong to violate it [14]. The result has no intrinsic bandwidth restrictions, makes no demands on the pulse profile, and does not require a co-moving

- J. B. Pendry, Phys. Rev. Lett. 85, 3966 (2000), doi:10.1103/PhysRevLett.85.3966.
- [2] K. L. Tsakmakidis, A. D. Boardman, and O. Hess, Nature 450, 397 (2007), doi:10.1038/nature06285.
- [3] M. Scalora, M. S. Syrchin, N. Akozbek, E. Y. Poliakov, G. D'Aguanno, N. Mattiucci, M. J. Bloemer, and A. M. Zheltikov, Phys. Rev. Lett. **95**, 013902 (2005), doi:10.1103/PhysRevLett.95.013902.
- [4] S. Wen, Y. Xiang, X. Dai, Z. Tang, W. Su, and D. Fan, Phys. Rev. A 75, 033815 (2007), doi:10.1103/PhysRevA.75.033815.
- [5] G. D'Aguanno, N. Mattiucci, and M. J. Bloemer, J. Opt. Soc. Am. B 25, 1236 (2008), doi:10.1364/JOSAB.25.001236.
- [6] P. Kinsler and G. H. C. New, Phys. Rev. A 67, 023813 (2003), doi:10.1103/PhysRevA.67.023813, arXiv:physics/0212016.
- [7] T. Brabec and F. Krausz, Phys. Rev. Lett. **78**, 3282 (1997), doi:10.1103/PhysRevLett.78.3282.
- [8] M. Geissler, G. Tempea, A. Scrinzi, M. Schnürer, F. Krausz, and T. Brabec, Phys. Rev. Lett. 83, 2930 (1999), doi:10.1103/PhysRevLett.83.2930.
- [9] G. P. Agrawal, Nonlinear Fiber Optics (Academic Press, Boston, 2007), 4th ed., ISBN 978-0-12-369516-1.
- [10] P. Kinsler (2002), arXiv:physics/0212014.
- [11] P. Kinsler, S. B. P. Radnor, and G. H. C. New, Phys. Rev. A **72**, 063807 (2005), doi:10.1103/PhysRevA.72.063807, arXiv:physics/0611215.
 [12] P. Kinsler (2007),
- "Pulse propagation methods in nonlinear optics", arXiv:0707.0982.
- [13] P. Kinsler, A. Favaro, and M. W. McCall, Eur. J. Phys. 30, 983 (2009), doi:10.1088/0143-0807/30/5/007, arXiv:0908.1721.
- [14] P. Kinsler,

frame – unlike other common types of derivation [6–9].

The resulting equations have the advantage that they are straightforward to write down, despite containing the complications of *both* electric and magnetic responses, and that a carrier-envelope representation or co-moving frames are easy to apply if desired, requiring no further approximation. In this, they match the clarity and flexibility of factorized second-order wave equations [15, 33, 34], but they can more easily incorporate the effects of magnetic material responses – albiet at the cost of being restricted to one dimensional propagation.

Acknowledgments

I acknowledge financial support from the Engineering and Physical Sciences Research Council (EP/E031463/1).

- J. Opt. Soc. Am. B 24, 2363 (2007),
- doi:10.1364/JOSAB.24.002363, arXiv:0707.0986. [15] P. Kinsler,
- Phys. Rev. A **81**, 013819 (2008), doi:10.1103/PhysRevA.81.013819, arXiv:0810.5689.
- [16] J. A. Fleck,Phys. Rev. B 1, 84 (1970),doi:10.1103/PhysRevB.1.84.
- [17] M. Scalora and M. E. Crenshaw, Opt. Commun. **108**, 191 (1994), doi:10.1016/0030-4018(94)90647-5.
- [18] P. Kinsler and G. H. C. New, Phys. Rev. A 69, 013805 (2004), doi:10.1103/PhysRevA.69.013805, arXiv:physics/0411120.
- [19] P. Kinsler and G. H. C. New, Phys. Rev. A 72, 033804 (2005), doi:10.1103/PhysRevA.72.033804, arXiv:physics/0606111.
- [20] P. Kinsler, G. H. C. New, and J. C. A. Tyrrell (2006), arXiv:physics/0611213.
- [21] R. W. Boyd, *Nonlinear Optics* (Academic Press, New York, 2003), 2nd ed., 1st ed. 1994.
 [22] D. Gabor,
- J. Inst. Electr. Eng. (London) **93**, 429 (1946).
- [23] J. Laegsgaard, Opt. Express 15, 16110 (2007), doi:10.1364/OE.15.016110.
- [24] A. D. Boardman, K. Marinov, D. I. Pushkarov, and A. Shivarova, Optical and Quantum Electronics 32, 49 (2000),
- doi:10.1023/A:1007045304098.
 [25] R. R. Alfano and S. L. Shapiro, Phys. Rev. Lett. 24, 584 (1970), doi:10.1103/PhysRevLett.24.584.
- [26] R. R. Alfano and S. L. Shapiro, Phys. Rev. Lett. 24, 592 (1970), doi:10.1103/PhysRevLett.24.592.
- [27] J. M. Dudley, G. Genty, and S. Coen, Rev. Mod. Phys. 78, 1135 (2006), doi:10.1103/RevModPhys.78.1135.
- [28] D. R. Solli, C. Ropers, P. Koonath, and B. Jalali,

Nature **450**, 1054 (2007), doi:10.1038/nature06402.

- [29] A. Braun, G. Korn, X. Liu, D. Du, J. Squier, and G. Mourou, Opt. Lett. 20, 7375 (1995), doi:10.1364/OL.20.000073.
- [30] L. Berge and S. Skupin,
 Discrete and Continuous Dynamical Systems (DCDS-A) 23, 1099 (2009),
 doi:10.3934/dcds.2009.23.1099.
- [31] Various, J. Opt. Soc. Am. B 10, 1656–1791 (1993),
 "Special Issue on optical parametric oscillation and amplification",
 URL http://www.opticsinfobase.org/josab/issue.cfm?volume=10&issue=9.
- [32] R. Danielius, A. Piskarskas, A. Stabinis, G. P. Banfi, P. D. Trapani, and R. Righini,
 J. Opt. Soc. Am. B 10, 2222 (1993), doi:10.1364/JOSAB.10.002222.
- [33] G. Genty, P. Kinsler, B. Kibler, and J. M. Dudley, Opt. Express 15, 5382 (2007), doi:10.1364/OE.15.005382.
- [34] A. Ferrando, M. Zacares, P. F. de Cordoba, D. Binosi, and A. Montero, Phys. Rev. E 71, 016601 (2005),
- doi:10.1103/PhysRevE.71.016601. [35] P. Kinsler, (2006), arXiv:physics/0611216.

Appendix A: Derivation of eqn. (1)

The derivation in this paper is simpler, more general, and defines G^{\pm} using a better sign convention than those in [11, 35]. I start with the Maxwell curl equations, and transform into frequency space:

$$\nabla \times \mathbf{H}(t) = +\partial_t \varepsilon_r \star \mathbf{E}(t) + \mathbf{J}(t),$$

$$\nabla \times \mathbf{E}(t) = -\partial_t \mu_r \star \mathbf{H}(t) - \mu_0 \mathbf{K}(t)$$
(A1)

$$\nabla \times \mathbf{H}(\boldsymbol{\omega}) = -\iota \boldsymbol{\omega} \ \boldsymbol{\alpha}_r(\boldsymbol{\omega})^2 \mathbf{E}(\boldsymbol{\omega}) + \mathbf{J}(\boldsymbol{\omega}),$$

$$\nabla \times \mathbf{E}(\boldsymbol{\omega}) = +\iota \boldsymbol{\omega} \, \boldsymbol{\beta}_r(\boldsymbol{\omega})^2 \mathbf{H}(\boldsymbol{\omega}) - \boldsymbol{\mu}_0 \mathbf{K}(\boldsymbol{\omega}). \tag{A2}$$

V

Continuing the derivation,

$$\nabla \times \alpha_r \mathbf{E} \pm \mathbf{u} \times (\nabla \times \beta_r \mathbf{H}) = +\iota \omega \alpha_r \beta_r^2 \mathbf{H} \mp \iota \omega \beta_r \alpha_r^2 (\mathbf{u} \times \mathbf{E}) \pm \mathbf{u} \times \beta_r \mathbf{J} - \alpha_r \mu_0 \mathbf{K}, \tag{A10}$$

$$\nabla \times \alpha_r \mathbf{E} \pm \nabla \times (\mathbf{u} \times \beta_r \mathbf{H}) \pm \nabla (\mathbf{u} \cdot \beta_r \mathbf{H}) = +\iota \omega \alpha_r \beta_r^2 \mathbf{H} \mp \iota \omega \beta_r \alpha_r^2 (\mathbf{u} \times \mathbf{E}) \pm \mathbf{u} \times \beta_r \mathbf{J} - \alpha_r \mu_0 \mathbf{K}$$
(A11)

$$\nabla \times [\alpha_r \mathbf{E} \pm (\mathbf{u} \times \beta_r \mathbf{H})] = +\iota \omega \alpha_r \beta_r^2 \mathbf{H} \mp \iota \omega \beta_r \alpha_r^2 (\mathbf{u} \times \mathbf{E}) \mp \nabla (\mathbf{u} \cdot \beta_r \mathbf{H}) \pm \mathbf{u} \times \beta_r \mathbf{J} - \alpha_r \mu_0 \mathbf{K}$$
(A12)

$$\times \mathbf{G}^{\mp} = \iota \omega \left\{ \alpha_r \beta_r^2 \mathbf{H} \ \mp \ \beta_r \alpha_r^2 \left(\mathbf{u} \times \mathbf{E} \right) \right\} \mp \nabla \left(\mathbf{u} \cdot \beta_r \mathbf{H} \right) \ \pm \mathbf{u} \times \beta_r \mathbf{J} - \alpha_r \mu_0 \mathbf{K}$$
(A13)

I now rearrange eqn. (A13) to give the final form, in which I substitute $\partial_t \mathbf{P} = \mathbf{J}(t)$ and $\partial_t \mathbf{M} = \mathbf{K}(t)$ to match eqn. (1). Thus

$$\nabla \times \mathbf{G}^{\mp} = \iota \omega \left\{ \alpha_r \beta_r \mathbf{u} G^{\circ} - \alpha_r \beta_r^2 \left(\mathbf{u} \times [\mathbf{u} \times \mathbf{H}] \right) \quad \mp \beta_r \alpha_r^2 \left(\mathbf{u} \times \mathbf{E} \right) \right\} \mp \nabla G^{\circ} \quad \pm \mathbf{u} \times \beta_r \mathbf{J} - \alpha_r \mu_0 \mathbf{K}$$
(A14)

$$= \pm \iota \omega \left\{ \beta_r \alpha_r^2 \left(\mathbf{u} \times \mathbf{E} \right) \pm \alpha_r \beta_r^2 \left(\mathbf{u} \times \left[\mathbf{u} \times \mathbf{H} \right] \right) \right\} + \iota \omega \alpha_r \beta_r \mathbf{u} G^\circ \equiv \nabla G^\circ \pm \mathbf{u} \times \beta_r \mathbf{J} - \alpha_r \mu_0 \mathbf{K},$$
(A15)

and finally

$$\nabla \times \mathbf{G}^{\pm} = \pm \iota \omega \ \alpha_r \beta_r \mathbf{u} \times \mathbf{G}^{\pm} + \iota \omega \alpha_r \beta_r \mathbf{u} G^{\circ} \ \pm \nabla G^{\circ} \ \mp \mathbf{u} \times \beta_r \mathbf{J} - \alpha_r \mu_0 \mathbf{K}$$
(A16)

$$= \pm \iota \omega \, \alpha_r \beta_r \mathbf{u} \times \mathbf{G}^{\pm} + \iota \omega \alpha_r \beta_r \mathbf{u} \mathbf{G}^{\circ} \pm \nabla \mathbf{G}^{\circ} \pm \iota \omega \beta_r \mathbf{u} \times \mathbf{P} + \iota \omega \alpha_r \mu_0 \mathbf{M}.$$
(A17)

Note that for $\mathbf{J}(t) = \partial_t \mathbf{P} = \partial_t \kappa_{\varepsilon} \mathbf{E}(t)$, where κ_{ε} is some com-

plicated but scalar dielectric response function, we have

8
$$\mp \mathbf{u} \times \beta_r \mathbf{J}(\boldsymbol{\omega}) = \pm \imath \boldsymbol{\omega} \beta_r \mathbf{u} \times \mathbf{P} = \pm \imath \boldsymbol{\omega} \alpha_r^2 \beta_r \kappa_{\varepsilon} \star \mathbf{u} \times \mathbf{E}$$
(A18)

$$= \pm \iota \omega \frac{\alpha_r^2 \beta_r}{2} \kappa_{\varepsilon} \star \left(\mathbf{u} \times \left[\mathbf{G}^+ + \mathbf{G}^- \right] \right), \quad (A19)$$

I now rotate the $\nabla \times {\boldsymbol{H}}$ equation by taking the cross product with ${\boldsymbol{u}},$

$$\mathbf{u} \times (\nabla \times \mathbf{H}) = -\iota \omega \ \alpha_r^2 \left(\mathbf{u} \times \mathbf{E} \right) + \mathbf{u} \times \mathbf{J}, \qquad (A3)$$

scale each part by β_r and α_r respectively, while insisting that these parameters do not depend on position. Thus,

$$\mathbf{u} \times (\nabla \times \beta_r \mathbf{H}) = -\iota \omega \ \beta_r \alpha_r^2 (\mathbf{u} \times \mathbf{E}) + \mathbf{u} \times \beta_r \mathbf{J},$$

$$\nabla \times \alpha_r \mathbf{E} = +\iota \omega \ \alpha_r \beta_r^2 \mathbf{H} - \alpha_r \mu_0 \mathbf{K},$$
 (A4)

and then take the sum and difference –

$$\nabla \times \alpha_r \mathbf{E} \pm \mathbf{u} \times (\nabla \times \beta_r \mathbf{H})$$

= $+\iota \omega \ \alpha_r \beta_r^2 \mathbf{H} \mp \iota \omega \ \beta_r \alpha_r^2 (\mathbf{u} \times \mathbf{E})$
 $\pm \mathbf{u} \times \beta_r \mathbf{J} - \alpha_r \mu_0 \mathbf{K}.$ (A5)

The vector \mathbf{G}^{\pm} fields are defined in eqn. (2), but that neglects the longitudinal part of **H**. Thus, for completeness, we also need to define $G^{\circ} = \mathbf{u} \cdot \boldsymbol{\beta}_r \mathbf{H}$ (as in [11, 35]). Their form means that I need to convert both the second term on the LHS of the sum-and-difference equation above, as well as the RHS. It is most important for the LHS to be simple, because this will define the type of propagation specified by the RHS. In the following I use the vector identity.

$$\mathbf{u} \times (\nabla \times \mathbf{H}) - \nabla (\mathbf{u} \cdot \mathbf{H}) = \nabla \times (\mathbf{u} \times \mathbf{H}), \quad (A6)$$

along with $\mathbf{u} \times [\mathbf{u} \times \mathbf{H}] = [\mathbf{u} \cdot \mathbf{H}]\mathbf{u} - \mathbf{H}$, so that

$$\mathbf{u} \times \mathbf{G}^{\mp} = \mathbf{u} \times \alpha_r \mathbf{E} \pm \mathbf{u} \times [\mathbf{u} \times \beta_r \mathbf{H}]$$
(A7)

$$= \mathbf{u} \times \alpha_r \mathbf{E} \mp \beta_r \mathbf{H} \pm [\mathbf{u} \cdot \beta_r \mathbf{H}] \mathbf{u}$$
 (A8)

$$= \mathbf{u} \times \alpha_r \mathbf{E} \mp \beta_r \mathbf{H} \pm \mathbf{u} G^{\circ}. \tag{A9}$$

and for $\mathbf{K}(t) = \partial_t \mathbf{M} = \partial_t \kappa_{\mu} \mathbf{H}(t)$, where κ_{μ} is some complicated but scalar magnetic response function, we have

$$-\alpha_{r}\mu_{0}\mathbf{K}(\boldsymbol{\omega}) = +\iota\boldsymbol{\omega}\mu_{0}\alpha_{r}\mathbf{M} = +\iota\boldsymbol{\omega}\mu_{0}\alpha_{r}\kappa_{\mu}\star\mathbf{H} \quad (A20)$$
$$= +\iota\boldsymbol{\omega}\mu_{0}\alpha_{r}\kappa_{\mu}\star(\mathbf{u}[\mathbf{u}\cdot\mathbf{H}]-\mathbf{u}\times\mathbf{u}\times\mathbf{H}) \quad (A21)$$

$$= +\iota\omega\mu_{0}\frac{\alpha_{r}}{\beta_{r}}\kappa_{\mu}\star(\mathbf{u}G^{\circ}-\mathbf{u}\times[\mathbf{u}\times\beta_{r}\mathbf{H}])$$
(A22)
$$= -\iota\omega\mu_{0}\frac{\alpha_{r}}{2\beta_{r}}\kappa_{\mu}\star(\mathbf{u}\times[\mathbf{G}^{+}-\mathbf{G}^{-}]-2\mathbf{u}G^{\circ}).$$
(A23)

Finally, when generating eqn. (A3), we lost the longitudinal part of $\nabla \times \mathbf{H} = \partial \varepsilon_r \mathbf{E} + \mathbf{J}$ (i.e. that parallel to **u**). This is

$$\mathbf{u} \cdot \nabla \times \mathbf{H} = -\iota \omega \alpha_r^2 \mathbf{u} \cdot \mathbf{E} + \mathbf{u} \cdot \mathbf{J} \quad (A24)$$
$$\mathbf{u} \cdot \nabla \times (\mathbf{G}^+ - \mathbf{G}^- + 2\mathbf{u}G^\circ) = -\iota \omega \alpha_r \beta_r \mathbf{u} \cdot (\mathbf{G}^+ - \mathbf{G}^-)$$
$$+ 2\beta_r \mathbf{u} \cdot \mathbf{J} \qquad (A25)$$

$$2\mathbf{u} \cdot (\nabla G^{\circ} - \mathbf{u} \times \nabla G^{\circ}) = -\iota \omega \alpha_r \beta_r \mathbf{u} \cdot (\mathbf{G}^+ - \mathbf{G}^-) + 2\beta_r \mathbf{u} \cdot \mathbf{J}$$
(A26)

$$2\mathbf{u} \cdot \nabla G^{\circ} = -\iota \omega \alpha_r \beta_r \mathbf{u} \cdot \left(\mathbf{G}^+ - \mathbf{G}^- \right) + 2\beta_r \mathbf{u} \cdot \mathbf{J}, \qquad (A27)$$

since $\nabla \times G^{\circ} \mathbf{u} = G^{\circ} \nabla \times \mathbf{u} - \mathbf{u} \times \nabla G^{\circ} = -\mathbf{u} \times \nabla G^{\circ}$, and

$$\mathbf{u} \cdot \nabla \times (\mathbf{G}^{+} - \mathbf{G}^{-}) = \iota \omega \alpha_{r} \beta_{r} \mathbf{u} \cdot \mathbf{u} \times (\mathbf{G}^{+} + \mathbf{G}^{-}) + 2\mathbf{u} \cdot \nabla G^{\circ} + 2\iota \omega \beta_{r} \mathbf{u} \cdot \mathbf{u} \times \mathbf{P} \quad (A28) = 2\mathbf{u} \cdot \nabla G^{\circ}. \qquad (A29)$$

Appendix B: Correction terms

In this appendix I work through the details of how the polarization and magnetization terms scale with respect to one another. To simplify matters, I assume all corrections are scalar since when ε_r and μ_r are not field-polarization or orientation sensitive, the scalings remain the same, even if the specific field terms may vary (e.g. $E_x E_y$ instead of E_x^2). Consider the general unidirectional equation for F_x^{\pm} (i.e. eqn. (10)), and replace the polarization and magnetization terms with dimensionless response parameters q_{ε} and q_{μ} multiplied by the appropriate field E_x or H_y . Then replace E_x and H_y with their representation in terms of F_x^+ , so that

$$\frac{\iota\omega}{2}\frac{\beta_r}{\alpha_r}P_x + \frac{\iota\omega}{2}\mu_0M_y = \frac{\iota\omega}{2}\frac{\beta_r}{\alpha_r}q_{\varepsilon}\varepsilon_0E_x + \frac{\iota\omega}{2}q_{\mu}\mu_0H_y \quad (B1)$$

$$= \frac{\iota\omega}{2}\left[\frac{\beta_r}{\alpha_r}q_{\varepsilon}\varepsilon_0F_x^+ + q_{\mu}\mu_0\frac{\alpha_r}{\beta_r}F_x^+\right] \quad (B2)$$

$$= \frac{\iota\omega\alpha_r\beta_r}{2}\left[\frac{q_{\varepsilon}\varepsilon_0}{\alpha_r^2}F_x^+ + \frac{q_{\mu}\mu_0}{\beta_r^2}F_x^+\right] \quad (B3)$$

$$= \frac{\iota k_r}{2} \frac{\varepsilon_0}{\varepsilon_r} \left[q_{\varepsilon} + q_{\mu} \frac{\mu_0}{\varepsilon_0} \frac{\varepsilon_r}{\mu_r} \right] F_x^+, \quad (B4)$$

remembering that $\mathbf{F}^+ = \mathbf{E} = (\beta_r / \alpha_r) \mathbf{H}$, and that $\varepsilon_r = \alpha_r^2$, and $\mu_r = \beta_r^2$.

Since we consider the electric-field-like field F^+ , the polarization corrections are trivial to write down; as for an *m*-th order nonlinear term, $q_{\varepsilon} = \chi_{\varepsilon}F^{+(m-1)}$. This means we need only concentrate on the magnetization correction. If q_{μ} is that for an *m*-th order nonlinear term, then $q_{\mu} = \chi_{\mu}H^{n-1} =$ $\chi_{\mu}(\alpha_r/\beta_r)^{(m-1)}F^{+(m-1)}$. Writing down only the term in square brackets from eqn. (B4) gives us

$$\left[q_{\varepsilon} + \chi_{\mu} \frac{\mu_{0}}{\varepsilon_{0}} \frac{\varepsilon_{r}}{\mu_{r}} \left(\frac{\alpha_{r}}{\beta_{r}}\right)^{m-1} F_{x}^{+(m-1)}\right] F_{x}^{+}$$
(B5)

$$= \left[q_{\varepsilon} + \chi_{\mu} \frac{\mu_{0}}{\varepsilon_{0}} \left(\frac{\varepsilon_{r}}{\mu_{r}}\right)^{\frac{m+1}{2}} F_{x}^{+(m-1)}\right] F_{x}^{+}.$$
 (B6)

Note that corrections for linear loss or gain are first-order processes (i.e. with m = 1), where for loss we need $q \sim t\gamma$, with $\gamma > 0$; Thus for loss the whole correction term will be proportional to $-\gamma F_x^+$, as would be expected.