## Laser cooling with a single laser beam and a planar diffractor

Matthieu Vangeleyn, Paul F. Griffin, Erling Riis and Aidan S. Arnold<sup>\*</sup>

Department of Physics, SUPA, University of Strathclyde, Glasgow G4 0NG, UK \* Corresponding author: a.arnold@phys.strath.ac.uk

Compiled July 13, 2021

A planar triplet of diffraction gratings is used to transform a single laser beam into a four-beam tetrahedral magneto-optical trap. This 'flat' pyramid diffractor geometry is ideal for future microfabrication. We demonstrate the technique by trapping and subsequently sub-Doppler cooling <sup>87</sup>Rb atoms to  $30 \,\mu$ K. © 2021 Optical Society of America

OCIS codes: 020.1335, 140.3320.

A magneto-optical trap (MOT) [1] is the starting point for the vast majority of cold and ultracold atomic physics experiments. Atoms are trapped and cooled to sub-milliKelvin temperatures using light scattering modified by the Zeeman and Doppler effects, respectively. MOTs are typically formed at the center of a spherical quadrupole magnetic field, in the overlap region of six (or less commonly four [2]) appropriately polarised red-detuned laser beams. The original pyramid MOT (PMOT) [3], utilising a square-based pyramidal reflector with 90  $^{\circ}$  apex angle between opposite sides, was devised as a means to turn a single laser beam into the six appropriately polarised beams required for a MOT. The PMOT simplifies optical alignment, saves a large number of optical components, and can also be modified to produce a beam source of cold atoms [4]. The original PMOT has since been used to make a compact gravimeter [5], and a millimetre scale chip trap [6].

Recently we demonstrated a new kind of pyramid MOT, based on a four-beam tetrahedral geometry [7] originating from a single beam interacting with a triangular pyramid reflector. This geometry has many advantages over the original design: MOT formation outside the pyramid is possible which simplifies optical access to the atoms and the apex region of the pyramid is noncritical (the latter feature is also present in the PMOT design in Ref. [8]). The apex and mirror edges in the original PMOT will generate diffraction and incorrect apex angle will also generate intensity irregularities in the doubly-reflected beams counterpropagating with the input beam. As these irregularities pass directly through the MOT, they can hinder further cooling in optical molasses. Moreover although sub-Doppler cooling is possible with small atom number [5], for larger PMOTs the counterpropagating beam will contain a shadow of the atoms from the input beam, creating an intensity imbalance that will hinder molasses [9]. This problem is obviated in the tetrahedral PMOT.

In this letter we have experimentally realized our proposal to extend the tetrahedral PMOT [7] to a 'flat' geometry using diffraction gratings. The grating magnetooptical trap (GMOT) has a very similar working principle to the tetrahedral PMOT, and its properties are again largely the result of intensity balance and polarisation decomposition [7]. One major difference is due to the fact that gratings spatially compress beams with a corresponding intensity increase (Fig. 1 a). The relationship between the intensities  $I_i$  and  $I_1$  of the vertical incident beam and the first-order diffracted beam, respectively, is determined by the corresponding beam widths  $w_i$  and  $w_1$ , and the first order diffraction efficiency  $R_1$ :

$$I_1/I_i = R_1 w_i/w_1 = R_1 \sec \alpha,$$
 (1)

where the Bragg condition yields the first order diffraction angle  $\alpha = \arcsin(\lambda/d)$  for light with wavelength  $\lambda$ normally incident on a grating with groove spacing d. Note the relation  $\alpha = 2\theta$  allows direct comparison with mirror declination angle  $\theta$  in our previous work [7].

The condition for balanced optical molasses from beams with intensities  $I_j$  and wavevectors  $\mathbf{k}_j$  is:

$$\sum I_j \mathbf{k}_j = \mathbf{0}.$$
 (2)

If we consider the configuration depicted in Fig. 1 b), where all but one beam are provided by diffraction from



Fig. 1. a) Side view of a first-order diffracted beam, illustrating geometric beam compression. b) Top view of three gratings and the circular vertical incident beam. The arrows show the blaze direction. c) A design for improved use of the laser beam area. Tomographic movies of the beam overlap volume for b) and c) are shown in Media 1, Media 2.

n identical gratings, then Eq. (2) is *radially* always satisfied, given the symmetry of the problem. Substituting Eq. (1) into Eq. (2) and projecting onto the vertical axis yields the very simple condition for balanced optical molasses:

$$R_1 = 1/n, \tag{3}$$

which is completely independent of diffraction angle and hence grating period. For three beams this corresponds to first order diffraction efficiency of  $R_1 = 1/3$ .

We consider only gratings for which second order diffraction is absent (i.e. first-order angles  $\alpha > 30^{\circ}$ ), as they are simpler to model and additionally small  $\alpha = 2\theta$ leads to drastically reduced trapping and cooling properties [7]. To create the maximum trap volume for a given beam size, the geometry in Fig. 1c) could be used. Unlike the system corresponding to our experimental realization (Fig. 1b) the zeroth grating order (a retroreflection with efficiency  $R_0$ ) has to be considered as it is present in the beam overlap volume. This modifies the balanced molasses condition Eq. (3) to  $R_1 = (1 - R_0)/n$ , and all cooling forces are reduced by the factor  $1 - R_0$ . The effect on the vertical trapping force depends on the relative zeroth order reflection phase shift between S and P polarizations, tending only to improve with non-zero relative phase.

A critical point in the achievement of a tetrahedral magneto-optical trap is the circular polarization of the first order diffracted beams. Grating efficiency is usually specified in terms of S and P polarization, and can vary dramatically with wavelength and polarisation. However, the difference in phase accumulation between S and P components  $\phi_{SP}$  also has to be taken into consideration. For our configuration, optimal cooling and trapping is achieved when the handedness (direction of circular polarization relative to beam propagation) of the incident vertical beam is reversed [7] and the total power drops by a factor 3 (i.e. all beams have equal intensity).

One can show that the radial trapping constant of the GMOT, relative to the tetrahedral PMOT is reduced by a correction factor

$$\zeta_{\rm SP} = 2\sqrt{I_{\rm SP}} \sin \phi_{\rm SP} / (1 + I_{\rm SP}) \tag{4}$$

if the S and P linear components of the first order grating beams have an intensity ratio of  $I_{\rm SP}$  and a relative phase shift of  $\phi_{\rm SP}$  respectively. The effect of relative S:P intensity ratio and phase is shown in Fig. 2 and is surprisingly robust. For an ideal  $\pi/2$  phase shift between S and P even an intensity ratio  $I_{\rm SP} \sim 0.07$  still yields  $\sim 1/2$  the trapping strength (black curve in Fig. 2). We measured the efficiency of our gratings for a circularly polarized incident beam to be  $R_1 = 45.3\%$ , of which 90% has the correct circular handedness. If we consider the ensemble made of the grating and the quartz plate of the vacuum chamber (Fig. 3), overall diffraction efficiency drops to a near-optimal  $R_1 = 32.2\%$ , with 85% having the correct handedness, i.e.  $\zeta_{\rm SP} = 70\%$  (red curve in Fig. 2).

In the experiment, trapping and repumping light are provided by two independent external cavity diode lasers



Fig. 2. Relative grating MOT radial trapping strength compared to the tetrahedral PMOT [7],  $\eta_{\rm SP}$ , as a function of the intensity ratio  $I_{\rm SP}$  and relative phase  $\phi_{\rm SP}$  between the S and P components of the first order beams at the MOT location. The black and red curves indicate 50% and 70% trapping reduction, respectively.

[10]. The lasers are overlapped and then spatially filtered by a  $30\,\mu\text{m}$  pinhole to remove rapid spatial intensity variation before and after diffraction from the gratings, which degrades the trap loading and can prevent sub-Doppler molasses. The beam is also over-expanded such that the intensity profile is as flat as possible within the 23 mm diameter apertured laser beam, to reduce intensity gradients in the three diffracted beams. A quarterwave plate changes the polarization to circular just before the vacuum chamber. We used inexpensive Edmund Optics gratings NT43-752. These 1200 grooves/mm gratings deflect a normally incident 780 nm beam at an angle  $\approx 69.4^{\circ}$ , close to the ideal tetrahedron PMOT angle  $(\arccos(1/3) \approx 70.5^{\circ})$ . This yields maximum trapping and cooling [7] albeit with a decreased capture volume using the grating geometry.

The grating triplet is positioned below the glass vacuum cell, the gratings forming a triangle with the blazed direction pointing towards the center (Fig. 1 a). The gratings have dimensions 12.7 mm by 12.7 mm and thus are not completely illuminated by the 23 mm diameter laser beam. After diffraction, the beams are vertically squeezed to about  $w_1 = 2.7 \,\mathrm{mm}$ , due to compression on the gratings, and the overlap region, where atoms can be trapped, is approximately a flattened rhombohedron [7]. The overlap volume is  $\sim 60 \,\mathrm{mm^3}$  and entirely above the 3 mm thick quartz vacuum window (Fig. 3). By deliberately tilting the gratings beyond the flat geometry to increase the beam overlap region, we found we could collect more atoms, indicating that the atom number is indeed overlap-volume limited. Ideally gratings with a longer period could be used, however for commercial gratings the variety in blaze angle (and hence polarization-dependent diffraction efficiency) is limited unless the spatial period is a multiple of 600 grooves/mm.

With intensities of  $1.3 \,\mathrm{mW/cm^2}$  in both the vertical and diffracted beams, a magnetic field gradient of  $17 \,\mathrm{G/cm}$  and  $7 \,\mathrm{MHz}$  red-detuning, we trap  $10^5 \ ^{87}\mathrm{Rb}$  atoms in our GMOT (Fig. 3), consistent with the beam



Fig. 3. Photograph of the experimental setup from the side. The MOT forms in the overlap of the downward incident beam (dashed white lines) and the three first-order grating beams. The path of the diffracted beam (dotted white lines) from one grating (yellow schematic) refracts through the 3 mm thick quartz vacuum cell (blue), then propagates at the expected  $\alpha \sim 69^{\circ}$ .

overlap volume reduction from our previous work [7]. For our experimental parameters the atom number should only enter the volume-squared scaling regime [6] for beam diameters less than 2 mm.

After initial MOT loading, the light frequency is further red-detuned for 20 ms to achieve sub-Doppler  $(< 140 \,\mu\text{K})$  MOT temperatures. The cloud temperature is measured using the sizes of background-subtracted fluorescence images after 0 and 10 ms time of flight. Fig. 4 shows the evolution of temperature as a function of extra in-MOT detuning, reaching significantly sub-Doppler temperatures of  $30 \pm 10 \,\mu\text{K}$  for red-detunings > 30 MHz. For a fixed 30 MHz extra red-detuning we investigated optical molasses formation by reducing the MOT magnetic field gradient to a fixed value in the range  $0 - 17 \,\mathrm{G/cm}$  for the last 10 ms of the 20 ms in-MOT cooling phase. Although the temperature remains approximately constant, as the final magnetic field gradient reaches zero the 1/e diameter of the Gaussian cloud prior to time of flight imaging reaches a size ( $\sim 4 \,\mathrm{mm}$ ) comparable to the beam overlap volume.

It appears that deeper molasses cooling is largely prevented by spatial intensity variation in our small beam overlap volume, particularly near the edge of the cloud. Under optimal conditions we have seen preliminary evidence for optical molasses, however future experiments would be better performed in an optimized setup – with larger beam overlap and less dramatic diffracted beam compression. Both goals can be achieved using diffraction gratings with a larger groove period. A particularly appealing aspect of the GMOT is that it lends itself to custom microfabricated planar optical elements, with arbitrary groove spacing in a stand-alone planar element.

In conclusion we have demonstrated a pyramid magneto-optical trap with 'flat' optics, extending our



Fig. 4. Temperature in the MOT as a function of the 20 ms extra detuning. For red-detuning jumps larger than 30 MHz, the temperature drops to  $30 \pm 10 \,\mu\text{K}$ .

work on the tetrahedral pyramid MOT [7]. A single beam is split into three new beams by a planar diffractor. This diffractor is well-suited to microfabrication, as technically challenging deep etching is not required. Additionally, MOT formation above the plane of the gratings has clear advantages for detection and further manipulation of the atoms. One can envisage applications in portable MOT-based devices. Moreover, we have demonstrated sub-Doppler temperatures in our grating MOT, and like the tetrahedral PMOT, sub-Doppler optical molasses should be achievable even with large atom number, suitable for applications requiring Bose-Einstein condensation formation.

We are grateful for stimulating discussions with Joseph Cotter and Ed Hinds. PFG received support from the RSE/Scottish Government Marie Curie Personal Research fellowship program.

## References

- E. L. Raab, M. Prentiss, A. Cable, S. Chu, and D. E. Pritchard, Phys. Rev. Lett. 59, 2631 (1987).
- F. Shimizu, K. Shimizu, and H. Takuma, Opt. Lett. 16, 339 (1991).
- K. I. Lee, J. A. Kim, H. R. Noh, and W. Jhe, Opt. Lett. 21, 1177 (1996).
- J. J. Arlt, O. Maragò, S. Webster, S. Hopkins and C. J. Foot, Opt. Commun. 157, 303 (1998).
- Q. Bodart, S. Merlet, N. Malossi, F. Pereira Dos Santos, P. Bouyer, and A. Landragin, Appl. Phys. Lett. 96, 134101 (2010).
- S. Pollock, J. P. Cotter, A. Laliotis, and E. A. Hinds, Opt. Express 17, 14109 (2009).
- M. Vangeleyn, P. F. Griffin, E. Riis, and A. S. Arnold, Opt. Express 17, 13601 (2009).
- B. M. Xu, X. Chen, J. Wang, and M. S. Zhan, Opt. Commun. 281, 5819 (2008).
- P. D. Lett, W. D. Phillips, S. L. Rolston, C. E. Tanner, R. N. Watts, and C. I. Westbrook J. Opt. Soc. Am. B 6, 2084 (1989).
- A. S. Arnold, J. S. Wilson, and M. G. Boshier, Rev. Sci. Instrum. 69, 1236 (1998).