

Heat engine model exhibit super-universal feature and capture the efficiencies of different power plants

M. Ponnmurugan

Department of Physics, School of Basic and Applied Sciences,
Central University of Tamilnadu, Thiruvavur - 610 005,
Tamilnadu, India. e-mail:ponphy@cutn.ac.in

August 30, 2019

Abstract

We propose a generalized model of a heat engine and calculate the minimum and maximum bounds on the efficiency at maximum power. We obtain a universal form of generalized extreme bounds on the efficiency at maximum power. Our model unifies the bounds on the efficiency and the universality features are observed for various heat engine models. Even though our model is a direct generalization of low-dissipation heat engines, the bounds on the efficiency obtained at a single target function capture those observed in the actual power plants working at different dissipation levels.

1 Introduction

In the study of non-equilibrium thermodynamics, the universal features of the heat engine efficiency at maximum target function have attracted much attention in the past few years [1, 2, 3]. Heat engine is a thermodynamic system operating between hot and cold heat reservoirs. The engine performs useful work W by absorbing Q_h amount of heat from the hot reservoir at a higher temperature T_h and delivers Q_c amount of heat to the cold reservoir at a lower temperature T_c . The efficiency of the heat engine operating between two reservoirs is defined as $\eta = W/Q_h$, which is bounded below the Carnot efficiency, $\eta_C = 1 - T_c/T_h$.

In equilibrium thermodynamics, the Carnot efficiency is the maximum efficiency reached by the heat engine when it is operating in the quasi-static process of infinitely long time duration in which the power delivered by the engine is zero. The quasi-static process can also be realized in a finite time for micro-sized heat engines kept in optical or bacterial reservoirs and operated at a single molecule level [4, 5, 6]. However, the actual power plants are macroscopic engines which are operating in the regime of near equilibrium or completely in the non-equilibrium regime. The efficiency observed by the macroscopic heat engines should be less than η_C since the engines are operating in the finite time duration of non-zero power output.

Most of finite time thermodynamics studies focus on maximizing different target functions [1, 2, 3] to analyze the heat engine performances in the linear and non-linear regimes [7]. The most frequently used target functions are the efficiency at maximum power, η_P [1, 8], the efficiency at maximum figure of merit or efficient power, η_χ (a product of η and power P) [9, 10, 11] and the efficiency at maximum Ω (ecological criterion), η_Ω , which accounts both for useful energy and losses [3, 12, 13].

The salient feature of heat engine efficiency at maximum target function is that one can obtain the universal form of efficiency up to quadratic order in η_C , irrespective of the different models such as stochastic heat engine [14], low-dissipation heat engine [8], minimally nonlinear heat engine [15], etc. In other words, the efficiency at maximum target function displays the universality up to quadratic order when the system deviates from equilibrium. For different target functions, different upper and lower bounds on the efficiency at maximum target function and different universality classes of the efficiency up to quadratic order in η_C can be obtained.

For the efficiency at maximum power, the upper and lower bounds on the efficiency are given by $\frac{\eta_C}{2} \leq \eta_P \leq \frac{\eta_C}{2-\eta_C}$ and the universal form of the efficiency up to quadratic order in η_C is [8],

$$\eta_P = \frac{1}{2}\eta_C + \frac{1}{8}\eta_C^2 + O(\eta_C^3). \quad (1)$$

The efficiency at maximum power of an optimized thermal engine in the endoreversible limit given by $\eta_{CA} = 1 - \sqrt{\frac{T_c}{T_h}} = 1 - \sqrt{1-\eta_C}$ [16, 17] is usually called as the Curzon-Ahlborn efficiency. When the temperature difference between the two reservoirs is small, the Taylor expansion of η_{CA} gives Eq.(1) [18, 19], which is bounded below the Carnot efficiency of the reversible heat engines. However, this model does not represent a universal bound on the efficiency at maximum power [7, 20].

Whereas, in the case of efficient power, the upper and lower bounds on the efficiency are given by $\frac{2}{3}\eta_C \leq \eta_\chi \leq \frac{3-\sqrt{9-8\eta_C}}{2}$ and the universal form of the efficiency up to quadratic order in η_C is [11],

$$\eta_\chi = \frac{2}{3}\eta_C + \frac{2}{27}\eta_C^2 + O(\eta_C^3) \quad (2)$$

and in the case of maximum Ω criterion, the upper and lower bounds on the efficiency are given by $\frac{3}{4}\eta_C \leq \eta_\Omega \leq \frac{3-2\eta_C}{4-3\eta_C}\eta_C$ and the universal form of the efficiency up to quadratic order in η_C is [3],

$$\eta_\Omega = \frac{3}{4}\eta_C + \frac{1}{32}\eta_C^2 + O(\eta_C^3). \quad (3)$$

The above results are obtained for different heat engine models under the assumption that T_c is very close to T_h . Further, in the study of a minimal model of information (I) based heat engine [21], another universality class for efficiency at maximum power up to quadratic order in η_C has been observed:

$$\eta_{PI} = \frac{1}{2}\eta_C + \frac{1}{12}\eta_C^2 + O(\eta_C^3). \quad (4)$$

Recent studies on heat engines showed the break down of such universality in the case of the efficiency at maximum power [22, 23]. In particular, a recent

study on a quantum dot engine reveals that the universal and non-universal form of efficiency at maximum target function depends on the imposed constraint on the control parameter of the heat engine [22]. Few other heat engine studies showed the importance of constraint relations between the efficiency and power and the optimal finite time protocol to achieve the efficiency at maximum power [24, 25].

The simplest model, which is believed to capture the features of various physical systems is, the low-dissipation Carnot engine [8]. There are extensive studies on low-dissipation Carnot engine model and its performance under maximizing different target functions [8, 11, 13]. Some of the industrial power plants [8, 10, 13, 26] does not operate in the low-dissipation regime [27]. Our proposed model, which is a direct generalization of the low-dissipation model, is found to be valid for any dissipation levels in which the heat engines might operate. It also unifies the different universal form of efficiency at a single target function (maximum power). Even though the operation regimes are completely different for different target functions, the minimum and maximum bounds on the efficiency at maximum power for different dissipation levels encompass all the extreme bounds on the efficiency at different target functions studied so far. Below, we will briefly summarize the existing low-dissipation model and give a detailed explanation of our generalized model.

2 Low-dissipation model

The considered low-dissipation model describes a heat engine undergoing Carnot cycle, consisting of two isothermal processes of finite time duration and two instantaneous adiabatic processes. In the isothermal expansion (compression), the working substance is in contact with the hot (cold) reservoir at temperature T_h (T_c) during the time interval t_h (t_c). The amount of heat Q_h (Q_c) exchanged between the hot (cold) reservoir and the working substance is modeled as [8]

$$Q_h = T_h (\Delta S - \Sigma_h/t_h), \quad (5)$$

$$Q_c = T_c (-\Delta S - \Sigma_c/t_c), \quad (6)$$

where Σ_h, Σ_c are the dissipation coefficients, describing the irreversibility present in the model, and $\pm\Delta S$ is the change in entropy of the working substance during isothermal expansion (+) and compression (-), such that the total change in entropy of the working substance is zero [11].

The work performed by the engine during the total time period $t = t_h + t_c$ is $-W = Q_h + Q_c$. Here, we used the convention that work and heat absorbed by the system are positive [8]. The power (P) generated during the Carnot cycle is given by,

$$P = \frac{-W}{t_h + t_c} = \frac{(T_h - T_c)\Delta S - T_h\Sigma_h/t_h - T_c\Sigma_c/t_c}{t_h + t_c}. \quad (7)$$

Using Eq.(5), Q_c can be rewritten as

$$Q_c = -T_c (Q_h/T_h + \Sigma_h/t_h + \Sigma_c/t_c). \quad (8)$$

Then the engine efficiency during the Carnot cycle is given by

$$\eta = \frac{Q_h + Q_c}{Q_h} = \eta_C - T_c \left(\frac{\Sigma_h/t_h + \Sigma_c/t_c}{Q_h} \right). \quad (9)$$

From the above equation, it is observed that the relation between the efficiency and the entropy production per engine cycle is similar to what is stated in Ref.[32]. Here, $Q_h + Q_c = \eta_C Q_h - T_c (\Sigma_h/t_h + \Sigma_c/t_c)$. Using Eq.(5), Eq.(9) can be rewritten as

$$\eta = \eta_C - \frac{T_c}{T_h} \left(\frac{1 + \frac{\Sigma_c t_h}{\Sigma_h t_c}}{\frac{\Delta S t_h}{\Sigma_h} - 1} \right). \quad (10)$$

The values of t_h and t_c , at which the power is maximum, as given by [8], are, $t_h = 2 \frac{T_h \Sigma_h}{(T_h - T_c) \Delta S} \left(1 + \sqrt{\frac{T_c \Sigma_c}{T_h \Sigma_h}} \right)$ and $t_c = 2 \frac{T_c \Sigma_c}{(T_h - T_c) \Delta S} \left(1 + \sqrt{\frac{T_h \Sigma_h}{T_c \Sigma_c}} \right)$. Their ratio obeys the relation, $\frac{t_c}{t_h} = \sqrt{\frac{T_c \Sigma_c}{T_h \Sigma_h}}$. By using the above equations, the efficiency at maximum power can be obtained and is given by

$$\eta_P = \eta_C - \frac{\eta_C}{2} \left[\frac{1 - \frac{\eta_C}{1 + \sqrt{\frac{T_c \Sigma_c}{T_h \Sigma_h}}}}{1 - \frac{\eta_C}{2(1 + \sqrt{\frac{T_c \Sigma_c}{T_h \Sigma_h}})}} \right]. \quad (11)$$

The above equation showed that η_P , in general, does not exhibit any universal form [22]. However, in the asymmetric dissipation limits, $\Sigma_c/\Sigma_h \rightarrow \infty$ and $\Sigma_c/\Sigma_h \rightarrow 0$, η_P converges respectively to the lower bound $\eta_C/2$ and the upper bound $\eta_C/(2 - \eta_C)$. In the symmetric dissipation, $\Sigma_c = \Sigma_h$, the above equation can be expanded in terms of η_C as, $\eta_P = \frac{\eta_C}{2} + \frac{\eta_C^2}{8} + O(\eta_C^3)$. This universal form of the efficiency at maximum power up to quadratic order in η_C is thus obtained only under the assumption that the temperature difference between T_c and T_h is small [8].

The inverse proportionality relation between the irreversible entropy production and time for the low-dissipation model may be a reasonable assumption for many systems operating in finite time. Different control schemes are utilized to tune the efficiency at the maximum power of the low-dissipation heat engine models [10, 14, 28]. Recent study also showed that the efficiency at the maximum power of a heat engine can be optimized by tuning the system's energy levels [24]. This can be done in low-dissipation heat engine model by incorporating the control scheme on the coefficients $\Sigma_{h,c}$ in the isothermal process [14, 24, 25]. Underlying this control scheme and using the low-dissipation assumption as a base model, three different types (normal, sub and super) of dissipative heat engines and its bounds were proposed earlier [29]. However, the significance of implementing such a control scheme have not yet been discussed more elaborately in general for heat engines operating in different dissipation regimes [29]. Therefore, it is worthwhile to investigate the different dissipation behaviors of such heat engines [27, 29] in a generalized case.

3 Generalized model

Even though the low-dissipation model is a well-founded model for many heat engines [10, 14], it might not be suitable for real heat engines [10, 27, 29].

Below, following Ref.[29], we generalize the low-dissipation model of the heat engine and calculate the minimum and maximum bounds on the efficiency at maximum power.

The amount of heat Q_h (Q_c) exchanged between the hot (cold) reservoir and the working substance is modeled as

$$Q_h = T_h \left\{ \Delta S - \alpha_h \left(\frac{\sigma_h}{t_h} \right)^{\frac{1}{\delta}} \right\}, \quad (12)$$

$$Q_c = T_c \left\{ -\Delta S - \alpha_c \left(\frac{\sigma_c}{t_c} \right)^{\frac{1}{\delta}} \right\}, \quad (13)$$

where $\sigma_h = \lambda_h \Sigma_h$, $\sigma_c = \lambda_c \Sigma_c$, $\delta \geq 0$ is a real number, which represents the level of dissipation, and $\lambda_{h/c}$ & $\alpha_{h/c}$ are the dimensionality-preserving tuning parameters such that the quantity inside the parenthesis (possibly having a nonlinear power $1/\delta$) is dimensionless. Note that the parameter δ departs this model from the first approximation in the entropy generation of irreversible heat devices. Under the assumption that $\sigma_{h/c} < t_{h/c}$, $\delta \rightarrow 0$ implies no dissipation, $\delta = 1$ low-dissipation and $\delta \rightarrow \infty$ high dissipation.

In recent years, the heat engine studies are primarily focused on mesoscopic systems, which require more sophisticated microscopic models [30, 31]. Using the Markovian master equation approach, the study of generalized framework of quantum mechanical heat engines provided the solid microscopical basis to the low-dissipation theory [31]. The phenomenological approach used in our work makes a general impression that some previously derived performance bounds can be recovered, since the employed model contains three additional fitting parameters compared to the standard low-dissipation model. The main physical motivation of our proposed model is that the coefficient δ , which is not necessarily an integer, might capture a non-Markovian dynamics of the system [31]. Similarly to Ref.[29], $\lambda_{h/c}$ are related with some external controlled parameter that drives the system during the isothermal processes in a given time interval. Further, our model has an additional parameter $\alpha_{h/c}$, which might be related to the control scheme that tune the system energy levels during the isothermal processes [24]. These tuning parameters allow to control the irreversible entropy generation by choosing a suitable combination of control schemes. Using Eq.(12), Q_c can be rewritten as

$$Q_c = -T_c \left[Q_h/T_h + \alpha_h(\sigma_h/t_h)^{\frac{1}{\delta}} + \alpha_c(\sigma_c/t_c)^{\frac{1}{\delta}} \right]. \quad (14)$$

Then,

$$Q_h + Q_c = \eta_C Q_h - T_c \left[\alpha_h(\sigma_h/t_h)^{\frac{1}{\delta}} + \alpha_c(\sigma_c/t_c)^{\frac{1}{\delta}} \right]. \quad (15)$$

The engine efficiency for the Carnot cycle is

$$\eta = \eta_C - T_c \left[\frac{\alpha_h(\sigma_h/t_h)^{\frac{1}{\delta}} + \alpha_c(\sigma_c/t_c)^{\frac{1}{\delta}}}{Q_h} \right]. \quad (16)$$

As mentioned above, this equation, relating the efficiency and the entropy production per engine cycle, is similar to the relation given in Ref.[32]. Further, using Eq.(12), the above equation can be rewritten as

$$\eta = \eta_C - \frac{T_c}{T_h} \left(\frac{1 + \frac{\alpha_c}{\alpha_h} \left(\frac{\sigma_c t_h}{\sigma_h t_c} \right)^{\frac{1}{\delta}}}{\frac{\Delta S}{\alpha_h} \left(\frac{t_h}{\sigma_h} \right)^{\frac{1}{\delta}} - 1} \right) \quad (17)$$

and the power generated during the Carnot cycle is given by

$$P = \frac{(T_h - T_c)\Delta S - T_h \alpha_h (\sigma_h/t_h)^{\frac{1}{\delta}} - T_c \alpha_c (\sigma_c/t_c)^{\frac{1}{\delta}}}{t_h + t_c}. \quad (18)$$

The values of t_h and t_c at which the power becomes maximum are given by,

$$t_h = \left\{ \left(1 + \frac{1}{\delta} \right) \alpha_h \frac{T_h \sigma_h^{\frac{1}{\delta}}}{(T_h - T_c)\Delta S} \left[1 + \left(\frac{\alpha_c T_c}{\alpha_h T_h} \right)^{\frac{\delta}{\delta+1}} \left(\frac{\sigma_c}{\sigma_h} \right)^{\frac{1}{\delta+1}} \right] \right\}^{\delta}, \quad (19)$$

$$t_c = \left\{ \left(1 + \frac{1}{\delta} \right) \alpha_c \frac{T_c \sigma_c^{\frac{1}{\delta}}}{(T_h - T_c)\Delta S} \left[1 + \left(\frac{\alpha_h T_h}{\alpha_c T_c} \right)^{\frac{\delta}{\delta+1}} \left(\frac{\sigma_h}{\sigma_c} \right)^{\frac{1}{\delta+1}} \right] \right\}^{\delta}, \quad (20)$$

and the ratio between the two obeys the relation

$$\left(\frac{t_c}{t_h} \right)^{\frac{1}{\delta}+1} = \frac{\alpha_c T_c}{\alpha_h T_h} \left(\frac{\sigma_c}{\sigma_h} \right)^{\frac{1}{\delta}}. \quad (21)$$

By using Eqs.(17), (19) and (21), the efficiency at maximum power can be obtained as,

$$\eta_P = \left(\frac{1}{\delta + 1} \right) \frac{\eta_C}{1 - \frac{\eta_C}{(1 + \frac{1}{\delta})\zeta}}, \quad (22)$$

where,

$$\zeta = 1 + \varsigma \left(\frac{T_c}{T_h} \right)^{\frac{\delta}{\delta+1}} = 1 + \varsigma (1 - \eta_C)^{\frac{\delta}{\delta+1}} \quad (23)$$

and

$$\varsigma = \left(\frac{\alpha_c}{\alpha_h} \right)^{\frac{\delta}{\delta+1}} \left(\frac{\sigma_c}{\sigma_h} \right)^{\frac{1}{\delta+1}}.$$

Note that the efficiency at maximum power does not depend on the individual parameters but only on their ratios σ_c/σ_h and α_c/α_h . The above equation shows that η_P in general does not exhibit any universal form. However, in the asymmetric dissipation limits, $\sigma_c/\sigma_h \rightarrow \infty$ or $\zeta \rightarrow \infty$ and $\sigma_c/\sigma_h \rightarrow 0$ or $\zeta \rightarrow 1$, η_P converges respectively to its lower bound $\eta_P^- = \frac{1}{\delta+1} \eta_C$ and its upper bound $\eta_P^+ = \frac{\eta_C}{(\delta+1) - \delta \eta_C}$ and thus it is bounded as

$$\frac{1}{\delta + 1} \eta_C \leq \eta_P \leq \frac{\eta_C}{(\delta + 1) - \delta \eta_C}. \quad (24)$$

Table 1: Expansion of the efficiency at maximum power $\eta_P = \left(\frac{1}{\delta+1}\right)\eta_C + \frac{\delta}{(\delta+1)^2(1+\varsigma)}\eta_C^2 + O(\eta_C^3)$ up to quadratic order in η_C for $\varsigma = 1$ to 5 and for three dissipation levels δ .

| ς | $\delta = 1$ | $\delta = 1/2$ | $\delta = 1/3$ |
|-------------|--|--|--|
| 1 | $\frac{1}{2}\eta_C + \frac{1}{8}\eta_C^2$ | $\frac{2}{3}\eta_C + \frac{1}{9}\eta_C^2$ | $\frac{3}{4}\eta_C + \frac{3}{32}\eta_C^2$ |
| 2 | $\frac{1}{2}\eta_C + \frac{1}{12}\eta_C^2$ | $\frac{2}{3}\eta_C + \frac{2}{27}\eta_C^2$ | $\frac{3}{4}\eta_C + \frac{1}{16}\eta_C^2$ |
| 3 | $\frac{1}{2}\eta_C + \frac{1}{16}\eta_C^2$ | $\frac{2}{3}\eta_C + \frac{1}{18}\eta_C^2$ | $\frac{3}{4}\eta_C + \frac{3}{64}\eta_C^2$ |
| 4 | $\frac{1}{2}\eta_C + \frac{1}{20}\eta_C^2$ | $\frac{2}{3}\eta_C + \frac{2}{45}\eta_C^2$ | $\frac{3}{4}\eta_C + \frac{3}{80}\eta_C^2$ |
| 5 | $\frac{1}{2}\eta_C + \frac{1}{24}\eta_C^2$ | $\frac{2}{3}\eta_C + \frac{1}{27}\eta_C^2$ | $\frac{3}{4}\eta_C + \frac{1}{32}\eta_C^2$ |

This result was obtained earlier in Ref.[29] by using power law profile control scheme. Nevertheless, the significance of the above relation have not yet discussed more elaborately. In what follows, we will discuss the universal form of the above relation for different dissipation levels in detail.

When $\delta = 1$, one can recover the results of low-dissipation heat engines [8] with $\alpha_c = \alpha_h = 1$ and $\lambda_c = \lambda_h = 1$. As mentioned earlier, the operation regimes are entirely different for different target functions. Nevertheless, we find that the minimum and maximum bounds on the efficiency at maximum power span the extreme bounds on the efficiency of different target functions with a proper choice of δ .

For $\delta = 1/2$, one gets $\eta_P^- = (2/3)\eta_C$ and $\eta_P^+ = 2\eta_C/(3 - \eta_C)$, we obtain the same lower bound on the efficiency at maximum efficient power of low-dissipation Carnot like engines and other models of nonlinear irreversible heat engines [11, 33]. Similarly, for $\delta = 1/3$, $\eta_P^- = (3/4)\eta_C$ and $\eta_P^+ = 3\eta_C/(4 - \eta_C)$, we obtain the same lower bound on the efficiency at maximum Ω criterion for low-dissipation Carnot like engines and different models of linear and nonlinear irreversible heat engines [13, 33]. However, the upper bounds calculated here are different from (in fact, higher than) those generally observed for other target functions.

The generalized minimum and maximum bounds on the efficiency at a single target function (maximum power) was obtained that covers the extreme bounds obtained for other target functions [11, 13, 33]. It should be emphasized that in our generalized model, the extreme bounds on the efficiency at maximum power for $\delta < 1$ clearly indicate that the heat engines dissipate in those regimes less than in the low-dissipation regime.

In the symmetric dissipation $\sigma_c = \sigma_h$, the efficiency at maximum power (Eq.22) becomes,

$$\eta_P^s = \frac{\eta_C}{(\delta + 1) - \frac{\delta\eta_C}{\zeta_s}}, \quad (25)$$

Table 2: The minimum (η_P^-) and the maximum (η_P^+) bounds on the efficiency at maximum power capture the observed efficiency (η_o) of industrial power plants for different dissipation levels δ . η_C is the Carnot efficiency.

| Thermal plant | η_C | η_o | δ | η_P^- | η_P^+ |
|----------------------------|----------|----------|----------|------------|------------|
| CANDU, (Nuclear, Canada) | 0.48 | 0.30 | 0.6 | 0.30 | 0.36 |
| Calder Hall, (Nuclear, UK) | 0.49 | 0.19 | 1.6 | 0.19 | 0.27 |
| Steam, UK | 0.57 | 0.28 | 1.04 | 0.28 | 0.39 |
| Gas turbine, (Switzerland) | 0.69 | 0.32 | 1.16 | 0.32 | 0.51 |

where $\zeta_s = 1 + \left(\frac{\alpha_c T_c}{\alpha_h T_h}\right)^{\frac{\delta}{\delta+1}}$. From the above relation, another interesting generalized expression for efficiency at maximum power is also obtained. Under the tuning condition, $\alpha_c/\alpha_h = T_h/T_c$, and $\zeta_s = 2$, Eq.(25) becomes

$$\eta_P^s = \frac{\eta_C}{(\delta + 1) - \frac{\delta \eta_C}{2}}. \quad (26)$$

In the low-dissipation level of $\delta = 1$, the above equation further reduces to $\frac{\eta_C}{2 - \frac{\eta_C}{2}}$, as obtained earlier in the stochastic heat engine model [14]. These results show that our generalized model comprises the universal expression of the efficiency at maximum power for various heat engine models. In the following section, we will investigate the universal form of the efficiency at maximum power obtained from the proposed model.

4 Universal form

In order to find the universal form of the optimized efficiency, we expand Eq.(22) in terms of η_C as,

$$\eta_P = \left(\frac{1}{\delta + 1}\right) \eta_C + \frac{\delta}{(\delta + 1)^2(1 + \varsigma)} \eta_C^2 + \frac{\delta^2}{(\delta + 1)^3(1 + \varsigma)^2} \eta_C^3 + \dots \quad (27)$$

The above result shows that the generalized model does not exhibit a universal form of the efficiency at maximum power in general. However, it shows the universal form for some specific conditions, namely for $\sigma_c/\sigma_h \rightarrow 0$, $\varsigma \rightarrow 0$ and $\sigma_c/\sigma_h \rightarrow \infty$, $\varsigma \rightarrow \infty$. The expansions of η_P for different values of ς and δ is given in Table.1.

For $\delta = 1$, the universal form of efficiency at maximum power up to quadratic order (Eq.(1)) is obtained for $\varsigma = 1$. The present model also captures the universal form of efficiency at maximum power up to quadratic order (Eq.(4)) for $\varsigma = 2$ at the same value of δ for the minimal model of information based heat engine [21]. For $\delta < 1$, the universal form of efficiency for different target functions (Eqs.(2) and (3)) holds for different values of ς as seen in Table.1. That is, for different dissipation levels, $\delta = 1/2$ and $1/3$, other universal form of efficiency at maximum power can be obtained which are similar to those for the efficient power, multi-parameter target functions [33] and Ω , or ecological criterion, respectively, for $\varsigma = 2, 3$, and 5 . Since our model unifies the different universal form of the efficiency at a single target function (maximum power) for different dissipation regimes, we can say that Eq.(27) exhibits a super-universal feature.

5 Efficiency of industrial power plants

In order to see whether the generalized model captures efficiencies of the various industrial power plants, we compared the corresponding observed efficiencies η_o [8, 10, 13, 26, 27] with the extreme bounds (24) on the efficiency at maximum power. The efficiencies of some power plants are actually captured by the extreme bounds for the low-dissipation heat engine corresponding to different target functions [8, 10, 13]. However, η_o of few power plants (UK: Calder Hall, Steam and Switzerland: Gas turbine) does not fall within these extreme bounds. This indicates that the above power plants are either not operated in the low-dissipation regime or they are not optimized with respect to the considered target functions.

The extreme generalized bounds on efficiency at maximum power (24), capture the observed efficiencies of actual thermal plants with different values of δ given in Table 2. The value of δ at which the minimum bound $\eta_P^- = \eta_o$ is calculated is given by $\delta = \frac{\eta_C}{\eta_o} - 1$. From Table 2, it is clear that δ larger than one is observed for three different power plants. This indicates that these engines might operate in the region with higher dissipation than the low-dissipation regime ($\delta = 1$). Whereas, for δ less than one, the engines may operate in a regime with smaller dissipation than the low-dissipation regime.

The most important factor affecting the parameter δ for different power plants is the way in which the machines exchange heat with the surroundings [27]. In the case of nuclear plants, the coolant inlet/outlet temperature and pressure also play a significant role in the machine's performance [34]. For example, in Table 2, the steam generating heavy water reactor in UK is similar to the pressurized heavy water reactor CANDU in Canada. Heavy water is used as a moderator for both the reactors and coolant for CANDU, while ordinary light water is used as a coolant for Steam [34]. Further, the operating conditions namely, coolant inlet/outlet temperature and pressure are also different for both reactors. For Calder Hall Magnox reactor in UK, graphite is used as a moderator and carbon dioxide is used as a coolant for heat transfer [35, 36]. Hot gas converts water to steam in a steam generator and four heat exchangers generate high and low pressure steam at the same time. Apart from changing the cladding in the Magnox reactor, the cooling gas pressure also needs to be increased for better performance. Finally, the Gas turbine in Switzerland is different from the nuclear reactors. The highly efficient axial compressor used in the gas turbine absorbs nearly seventy percent of the power from an air inlet at a particular temperature. The heat of the exhaust gases is utilized for the production of steam in exhaust boiler which in turn operates with low efficiency and high dissipation [27]. However, the cycle efficiency increases with the increase in turbine inlet temperature.

6 Conclusion

We generalized the low-dissipation model of a heat engine and obtained the minimum and maximum bounds on the efficiency at maximum power. Extreme bounds on the efficiency at a single target function of maximum power capture the efficiency at the maximum power of various heat engine models and also efficiencies corresponding to other target functions.

Also the bounds on the efficiency obtained in our generalized model capture the efficiency observed in the actual power plants. In the high dissipation case of $\delta \rightarrow \infty$, the efficiency η_P at maximum power (22) vanishes, and for no dissipation, $\delta \rightarrow 0$, $\eta_P \rightarrow \eta_C$. The study of attainability of η_C at non zero power in the irreversible region attracted much interest in recent years [37]. The high values of efficiency obtained by the practical heat engines are not necessarily in the region of maximum power output [10]. Hence this model requires further study of the optimal efficiency at arbitrary power [38].

It should be noted that the universal relation (1) at maximum power is valid not only for heat engine models having strong coupling with left-right symmetry but also for models (Curzon- Ahlborn heat engine and the Feynman ratchet) without having such symmetry [39]. The previous study showed that the energy-matching condition is sufficient for obtaining Eq.(1) for different heat engine models [39]. Obtaining such an energy matching condition for our generalized model will be a part of our future work.

Acknowledgment:

I would like to thank the anonymous referees for their critical comments and supportive suggestions.

References

- [1] C. Van den Broeck, Phys. Rev. Lett. **95**, 190602 (2005).
- [2] C. De. Tomas, A. C. Hernandez and J. M. M. Roco, Phys. Rev. E **85**, 010104 (R) (2012).
- [3] N. Sanchez-Salas, L. Lopez-Palacios, S. Velasco and A. C. Hernandez, Phys. Rev. E **82**, 051101 (2010); Y. Zhang, C. Huang, G. Lin and J. Chen, Phys. Rev. E **93**, 032152 (2016).
- [4] I. A. Martinez, E. Rolden, L. Dinis, D. Petrov, J. M. R. Parrondo and R. A. Rica, Nature Phy. **12**, 67 (2016).
- [5] S. Krishnamurthy, S. Ghosh, D. Chatterji, R. Ganapathy and A. K. Sood, Nature Phy. **12**, 1134 (2016).
- [6] V. Holubec and A. Ryabov, Phys. Rev. Lett. **109**, 269 (1980).
- [7] R. S. Berry, V. A. Kazakov, S. Sieniutycz, Z. Szwast and A. M. Tsirlin, *in Thermodynamics optimization of Finite-Time process* (John Wiley and Sons, Chichester, 2000).
- [8] M. Esposito, R. Kawai, K. Lindenberg and C. Van den Broeck, Phys. Rev. Lett. **105**, 150603 (2010).
- [9] J. W. Stucki, Eur. J. Biochem. **109**, 269 (1980).
- [10] V. Holubec and A. Ryabov, Phys. Rev. E **92**, 052125 (2015).
- [11] V.Singh and R.S. Johal, Phys. Rev. E **98**, 062132 (2018).

- [12] F. Angulo-Brown, J. Appl. Phys. **69**, 7465 (1991); A. C. Hernandez, A. Medina, J. M. M. Roco, J. A. White and S. Velasco, Phys. Rev. E **82**, 051101 (2001).
- [13] C. De. Tomas, J. M. M. Roco, A. C. Hernandez, Y. Wang and Z. C. Tu, Phys. Rev. E **87**, 012105 (2013).
- [14] T. Schmiedl and U. Seifert, Europhys. Lett. **81**, 20003 (2008).
- [15] Y. Izumida and K. Okuda, Europhys. Lett. **97**, 10004 (2012).
- [16] I. I. Novikov, J. Nucl. Energy **7**, 125 (1958).
- [17] F. L. Curzon and B. Ahlborn, Am. J. Phys. **43**, 22 (1975).
- [18] S. Sheng and Z. C. Tu, Phys. Rev. E **91**, 022136 (2015).
- [19] J. P. Palao, L. A. Correa, G. Adesso and D. Alonso, Braz. J. Phys. **46**, 282 (2016).
- [20] K. H. Hoffmann, J. M. Burzler and S. Schubert, J. Non-Equilib. Thermodyn. **22**, 311 (1997).
- [21] Y. Zhou and D. Segal, Phys. Rev. E **82**, 011120 (2010).
- [22] S. H. Lee, J. Um and H. Park, Phys. Rev. E **98**, 052137 (2018).
- [23] U. Seifert, Phys. Rev. Lett. **106**, 020601 (2011).
- [24] Y. H. Ma, D. Xu, H. Dong and C. Sun, Phys. Rev. E **98**, 022133 (2018).
- [25] Y. H. Ma, D. Xu, H. Dong and C. Sun, Phys. Rev. E **98**, 042112 (2018).
- [26] R. S. Johal, Eur. Phys. J. Special Topics, **226**, 489 (2017).
- [27] S. L. Medina, G. V. Ortega and L. A. A. Hernandez, arXiv:1812.0936, (2018).
- [28] F. Giazotto, T. T. Heikkila, A. Luukanen, A. M. Savin and J. P. Pekola, Rev. Mod. Phys. **78**, 217 (2006); S. An et.al., Nature Phys. **11**, 193 (2014); J. Gonzalez-Ayala, A. C. Hernandez and J. M. M. Roco, J. Stat. Mech. Theory Exp. 073202 (2016).
- [29] W. Yang and T. Zhan-Chun, Commun. Theor. Phys. **59**, 175 (2013).
- [30] L. A. Correa, J. P. Palao, G. Adesso and D. Alonso, Phys. Rev. E **90**, 062124 (2014).
- [31] V. Cavina, A. Mari and V. Giovannetti, Phys. Rev. Lett. **119**, 050601 (2017).
- [32] J. S. Lee, H. Park, Scientific Reports **7**, 10725 (2017).
- [33] Y. Zhang, J. Guo, G. Lin and J. Chen, J. Non-Equilib. Thermodyn. **42**, 253 (2017).

- [34] Nuclear reactor Types : an Environment and Energy FactFile; The Institution of Electrical Engineers (IEE), London, UK, 2005; <https://www.eea.europa.eu/data-and-maps/indicators/nuclear-energy-and-waste-production/iee-2005-nuclear-reactor-types>
- [35] N. E. Todreas, M. S. Kazimi, Nuclear Systems I: Thermal Hydraulic Fundamentals, (Taylor and Francis, 1990).
- [36] S. Glasstone and A. Sesonske, Nuclear Reactor Engineering, Reactor Systems Engineering, Vol. 1 and 2 (Chapman and Hall, Inc. 1994).
- [37] M. Ponmurugan, J. Non-Equilib. Thermodyn. **44**, 143 (2019); J. S. Lee, S. H. Lee, J. Um and H. Park, arXiv:1812.10651.
- [38] V. Holubec and A. Ryabov, J. Stat. Mech. 073204 (2016).
- [39] S. Sheng and Z. C. Tu, Phys. Rev. E **91**, 022136 (2015).