Evolutionary Stochastic Policy Distillation

Hao Sun, Xinyu Pan, Bo Dai, Dahua Lin, Bolei Zhou The Chinese University of Hong Kong sh018@ie.cuhk.edu.hk

Abstract

Solving the Goal-Conditioned Reward Sparse (GCRS) task is a challenging reinforcement learning problem due to the sparsity of reward signals. In this work, we propose a new formulation of GCRS tasks from the perspective of the drifted random walk on the state space, and design a novel method called Evolutionary Stochastic Policy Distillation (ESPD) to solve them based on the insight of reducing the First Hitting Time of the stochastic process. As a self-imitate approach, ESPD enables a target policy to learn from a series of stochastic variants through the technique of policy distillation (PD). The learning mechanism of ESPD can be considered as an Evolution Strategy (ES) that applies perturbations upon policy directly on the action space, with a SELECT function to check the superiority of stochastic variants and then use PD to update the policy. The experiments based on the MuJoCo robotics control suite show the high learning efficiency of the proposed method.¹

1 Introduction

Although Reinforcement Learning (RL) has been applied to various challenging tasks and outperforms human in most cases [Mnih et al., 2015; Silver et al., 2016; Lillicrap et al., 2015; Vinyals et al., 2019; Pachocki et al., 2018], human effort is always needed to provide sufficient learning signals beside the original *Win or Loss* reward signal [Vinyals et al., 2019]. On the one hand, such reward sparsity hinders the learning process, on the other hand, it also provides the flexibility of learning different policies as different solutions to a certain task in order to get rid of deceptive sub-optimal solutions produced by manually designed rewards [Plappert et al., 2018].

Among many of real-world reinforcement learning tasks with extremely sparse rewards, an important class is the Goal-Conditioned Reward Sparse (GCRS) task. In those tasks, the goal is combined with the current state as the input of policy, and the agent is able to receive a positive reward only when the goal is achieved. In most cases, the GCRS task is also associated with the Multi-Goal task: in which the goal is not fixed and can be anywhere in the state space. Therefore the policy has to learn a general solution that can be applied to a set of similar tasks. For example, robotic object grasping is such a GCRS task: the target object could be anywhere on the table, the robot has to adjust its arm to reach the object and grasp it. The learning objective of a policy is to find a feasible path from the current state toward the goal [Tamar et al., 2016]. Similar tasks include the Multi-Goal benchmarks in robotics control [Plappert et al., 2018].

In previous work, reward shaping [Ng et al., 1999], hierarchical reinforcement learning [Dietterich, 2000; Barto & Mahadevan, 2003], curriculum learning [Bengio et al., 2009] and leaning from demonstrations [Schaal, 1997; Atkeson & Schaal, 1997; Argall et al., 2009; Hester et al., 2018; Nair et al., 2018] are proposed to tackle the challenge of learning through sparse reward. Those approaches provide manual guidance from different perspectives. Besides, the Hindsight Experience Replay (HER) [Kaelbling , 1993; Andrychowicz et al., 2017] was proposed to relabel the failed trajectories

Preprint. Under review.

¹Code is available at https://github.com/decisionforce/ESPD



Figure 1: An illustration figure shows how our proposed method work

and assign hindsight credit as complementary to the primal sparse rewards, which is still a kind of Temporal Difference learning and relies on the value of the reward. Recently the Policy Continuation with Hindsight Inverse Dynamics (PCHID) [Sun et al., 2019] is proposed to learn with hindsight experience in a supervised learning manner, but the learning efficiency is still limited by the explicit curriculum setting.

In this work, we intend to further improve the learning efficiency and stability in those GCRS tasks with an alternative approach based on supervised learning. Specifically, by formulating the exploration of GCRS problems as random walk in state space, solving the GCRS is equivalent to decreasing the first hitting time (FHT) in the random walk. And as successful trajectories which have short FHT are more likely from a good policy, learning to reproduce such trajectories can improve the target policy if the target policy itself perform poorly at present. Therefore, we can apply self-imitate learning to reproduce the success of reaching a *hindsight goal* [Andrychowicz et al., 2017], *i.e.*, distilling knowledge from the subset of random samples that conform to certain hindsight target. Based on this intuition, we propose a new approach for the GCRS tasks, which is purely based on self-imitate learning and is independent of the value of rewards. Our agent learns from its own success to be executed in a much more efficient supervised learning manner. To sum up our contributions:

- 1. By modeling the GCRS problems as random walk in the state space, we provide a Stochastic Differential Equation (SDE) formulation of policy learning and show the link between policy improvement and reduction of FHT.
- 2. To reduce the FHT from the SDE perspective, we propose the Evolutionary Stochastic Policy Distillation (ESPD) method, which combines the insight of evolutionary strategies and Policy Distillation, as a self-imitate approach for the GCRS problems.
- 3. We demonstrate the proposed method on the MuJoCo robotics control benchmarks and show our method can work in isolation to solve GCRS tasks with prominent learning efficiency.

2 Preliminaries

2.1 Markov Decision Process

We consider a Markov Decision Process (MDP) denoted by a tuple \mathcal{M} containing: a state space \mathcal{S} , action space \mathcal{A} , start state distribution $d(s_0)$, transition distribution $\mathcal{P}(s_{t+1}|s_t, a_t)$, reward function r(s) and discount factor $\gamma \in [0, 1]$. Let $T : \mathcal{S} \times \mathcal{A} \to \mathcal{S}$ model the dynamics if the transition is deterministic. Given a policy $\pi(a|s)$, let $J(\pi) = \mathbb{E}_{\mathcal{M}}[\sum_{t=0}^{\infty} \gamma^t r(s_t)]$ denote the discounted expected return, and an optimal policy $\pi^* = \arg \max_{\pi} J(\pi)$ maximizes that return.

2.2 Universal Value Function Approximator and Multi-Goal RL

The Universal Value Function Approximator [Schaul et al., 2015] extends the state space of Deep Q-Networks [Mnih et al., 2015] to include goal state as part of the input, which is useful in the setting where there are multiple goals to achieve. Moreover, Schaul et al. [2015] show that in such a setting, the learned policy can be generalized to previous unseen state-goal pairs. Specifically, let $Q = S \times G$ denote the *extended state space* of \mathcal{M} where \mathcal{G} is a goal space. Since the goal is fixed

within an episode, the transition function $T' : \mathcal{Q} \times \mathcal{A} \to \mathcal{Q}$ on the extended state space can be induced from the original transition T as T'((s, g), a) = (T(s, a), g). Besides, a representation mapping $m(\cdot) : \mathcal{S} \to \mathcal{G}$ is assumed to be known in such multi-goal RL frameworks [Plappert et al., 2018]. Hence, in order to achieve the goal g, the agent must reach a certain state s_q such that $g = m(s_q)$.

We say \mathcal{M}' is a sub-task of \mathcal{M} if \mathcal{M}' is obtained by restricting the start state distribution d'(q) onto a subset \mathcal{Q}' of the extended state space \mathcal{Q} , denoted by $\mathcal{M}' = \mathcal{M}_{\mathcal{Q}'} \subset \mathcal{M}$. In particular, let $\mathcal{M}_{(s,g)}$ denote the sub-task with fixed start state s and goal state g. A partition of \mathcal{M} is a sequence of subtasks $\{\mathcal{M}_k\}_{k=1}^K$ such that $\mathcal{M}_k \subset \mathcal{M}_{k+1}$ and $\mathcal{M}_K = \mathcal{M}$.

2.3 Policy Continuation

Most multi-goal RL tasks have sparse rewards. In order to motivate the agent to reach the goal efficiently, the reward function r(s,g) is usually set non-negative if g = m(s) while there is a *negative* penalty otherwise. Such reward distribution can exhibit optimal substructure of the policy.

Definition 1. Policy Continuation Given a policy π defined on the sub-task $\mathcal{M}_{\mathcal{Q}'}$ and a policy Π defined on the sub-task $\mathcal{M}_{\mathcal{Q}''} \supset \mathcal{M}_{\mathcal{Q}'}$, we call Π is a policy continuation of π , if $\Pi(q) = \pi(q), \forall q \in \mathcal{Q}'_{\pi}$, where \mathcal{Q}'_{π} is the set of all extended states reachable by π within task $\mathcal{M}_{\mathcal{Q}'}$

Theorem 1. If π is an optimal policy of sub-task $\mathcal{M}_{Q'}$, then there exists an optimal policy Π of $\mathcal{M}_{Q''} \supset \mathcal{M}_{Q'}$ such that Π is a policy continuation of π .

Proof. Let Π' be an optimal policy of $\mathcal{M}_{\mathcal{Q}''}$ and construct Π as follows:

$$\Pi(q) = \begin{cases} \pi(q) & \text{if } q \in \mathcal{Q}'_{\pi} \\ \Pi'(q) & \text{otherwise.} \end{cases}$$
(1)

It is straightforward to see that Π is the optimal policy continuation of π .

The above theorem is simple yet powerful. It enables the agent to perform supervised learning from experience replay as long as the trajectory is optimal for some sub-tasks. Nevertheless, in general given a trajectory $\{(s_0, g), a_0, r_0, \dots, (s_T, g), a_T, r_T\}$ generated by the policy π , it is not easy to decide whether π is optimal for the sub-task $\mathcal{M}_{(s_0,m(s_T))}$. If we further assume the negative reward is a *constant* value, *i.e.* the agent should learn to achieve the goal with minimum actions, Sun et al. [2019] proposed to use the partition induced from the *k*-step solvability to help decide the sub-task optimality.

Definition 2. *k*-Step Solvability Given a sub-task $\mathcal{M}_{(s,g)}$ of a certain system with deterministic dynamics, we call $\mathcal{M}_{(s,g)}$ is *k*-step solvable with a policy π if the goal g can be achieved from (s,g) within k steps under π , *i.e.*, set $q_0 = (s,g)$ and $q_{t+1} = T'(q_t, \pi(q_t)) = (s_{t+1},g)$ for $t \ge 0, \exists i \le k$ such that $m(s_i) = g$. We call a sub-task \mathcal{M}' is *k*-step solvable with π if any $\mathcal{M}_{(s,g)} \subset \mathcal{M}'$ is *k*-step solvable. Solvable with π . Specifically, if π is the optimal policy of \mathcal{M}' , we simply call \mathcal{M}' is *k*-step solvable.

Consider the partition $\{\mathcal{M}_k\}_{k=1}^K$ of \mathcal{M} where for any k < K, \mathcal{M}_k is the maximal k-solvable subtask. Suppose the agent has learnt the optimal policy π_k of \mathcal{M}_k , it can decide whether a trajectory of length (k + 1) is optimal by testing whether the corresponding sub-task is k-step solvable. And those trajectories passing the TEST can serve as supervised training samples for extending π_k to an optimal policy continuation π_{k+1} on \mathcal{M}_{k+1} .

3 Method

3.1 Problem Formulation

In a given goal-oriented reinforcement learning task, we assume there exists an unknown metric $\mathcal{D}(s_t, g)$ that represents the distance between the current state s_t and the desired goal state g. For example, $\mathcal{D}(s, g)$ is the Euclidean distance in barrier-free navigation tasks; or the Manhattan distance in navigation tasks with obstacles.

A feasible solution of the task should be a policy $\pi(s_t, g)$ that outputs an action a_t , such that the distance $\mathcal{D}(s_{t+1}, g) \leq \mathcal{D}(s_t, g)$ for deterministic dynamics, or $\mathbb{E}[\mathcal{D}(s_{t+1}, g)] \leq \mathbb{E}[\mathcal{D}(s_t, g)]$ for stochastic dynamics.

Assume $\mathcal{D}(s,g)$ is continuous and differentiable on s, and $\delta s = -\xi \frac{\partial \mathcal{D}(s,g)}{\partial s} dt$ is a feasible direction, as it decreases the distance between s and g when ξ is sufficiently small.

As the state transition $\Delta s_t = s_{t+1} - s_t$ is determined by both the dynamics $\phi_s(\cdot) : S \times A \to \Delta S$ and the action provided by the policy by $a_t = \pi(s_t, g)$. We may write a sufficient condition for a feasible policy:

$$\phi_s(\pi(s,g)) = -\xi \frac{\partial \mathcal{D}(s,g)}{\partial s} \mathrm{d}t,\tag{2}$$

we further assume $\phi_s^{-1}(\cdot)$ exists², *i.e.* $\forall a \in \mathcal{A}, \phi_s^{-1}(\phi_s(a)) = a$. Hence, by parameterizing the policy $\pi(s, g)$ with θ , we have

$$\pi_{\theta}(s,g) = \phi_s^{-1} \left(-\xi \frac{\partial \mathcal{D}(s,g)}{\partial s} \right), \tag{3}$$

is a feasible policy, *i.e.*, it tends to solve the GCRS task by as it continuously minimizes the distance between the current state and goal.

The above equation tells us, in order to learn a well-performing policy, the policy should learn two unknown functions: the inverse dynamics $\phi_s^{-1}(\cdot)$ and the derivatives of distance metric $\mathcal{D}(\cdot, \cdot)$ over s and g with regard to state s.

The work of Sun et al. [2019] proposed PCHID to use Hindsight Inverse Dynamics (HID) as a practical policy learning method in such GCRS tasks. Specifically, in Inverse Dynamics, a model parameterized by θ is optimized by minimizing the mean square error of predicted action \hat{a}_t and executed action a_t between adjacent states s_t and s_{t+1} , *i.e.* $\theta = \arg \min_{\theta} (a_t - \hat{a}_t)^2 = \arg \min_{\theta} (a_t - \pi_{\theta}(s_t, s_{t+1}))^2$. The HID revises the latter s_{t+1} with its goal correspondence $g_{t+1} = m(s_{t+1})$, where the mapping m is assumed to be known in normal GCRS task settings. $m : S \to G$ s.t. $\forall s \in S$ the reward function r(s, m(s)) = 1. In the single step transition setting, the learning objective of the policy is to learn HID by

$$\theta = \operatorname*{arg\,min}_{\theta} (a_t - \hat{a}_t)^2 = \operatorname*{arg\,min}_{\theta} (a_t - \pi_{\theta}(s_t, g_{t+1}))^2, \tag{4}$$

The Eq.4 shows the HID can be used to train a policy with supervised learning by minimizing the prediction error. However, to get more capable policy that is able to solve harder cases, training the policy only with 1-step HID is not enough. The work of PCHID then proposed to check the optimality of multi-step transitions with a TEST function and learn multi-step HID recursively. Such explicit curriculum learning is not efficient as multi-step transitions can only be collected after the convergence of previous sub-policies.

Here we try to interpret how PCHID works from the SDE perspective. Practically, a policy is always parameterized as a neural network trained from scratch to solve a given task. At beginning the policy will not be fully goal-oriented as a feasible policy should be. With random initialization, the policy network will just perform random actions regardless of what state and goal are taken as inputs. We use a coefficient ϵ to model the goal awareness of the policy, e.g., $\epsilon = 0$ denotes a purely random policy, and $\epsilon = 1$ denotes a better policy. In order to collect diverse experience and improve our target policy, We follow traditional RL approaches to assume a random noise term denoted by N with coefficient σ to execute exploration. Hence, the behavioral policy becomes:

$$\pi_{\text{behave}} = \pi_{\theta}(s, g) + \sigma N = \epsilon \phi_s^{-1} \left(-\xi \frac{\partial \mathcal{D}(s, g)}{\partial s} \right) + \sigma N, \tag{5}$$

the behavioral policy above combines a deterministic term and a stochastic term, which in practice can be implemented as a Gaussian noise or OU-noise [Lillicrap et al., 2015]. Although we assume a deterministic policy $\pi_{\theta}(s, g)$ here, the extension to stochastic policies is straightforward, e.g., the network can predict the mean values and standard deviations of an action to form a Gaussian policy family and Mixture Density Networks [Bishop, 1994] can be used for more powerful policy representation.

With such a formulation, the PCHID can be regarded as a method that *explicitly* learns the inverse dynamics with HID, and progressively learns the geometry $\mathcal{D}(s, g)$ with Policy Continuation (PC). In this work, we justify that the approach can be extended to a more efficient synchronous setting

²The assumption can be released to a existence of pseudo inverse: $\phi_s^{-1}(\phi_s(a)) \in A'$, where A' is a set s.t. $\forall a' \in A', \phi_s(a') = \phi_s(a)$



Subtask(s_{t+1} , $m(s_{t+k+1})$) is **NOT** selected as π_T can finish within k steps

Subtask $(s_t, m(s_{t+k}))$ is **selected** as π_T can not finish within k steps

Figure 2: An illustrative on how the selection process works: first we generate episodes with the stochastic behavior policy π_B , which is composed of the deterministic target policy π_T and a noise term drawn from Gaussian, then we check the superiority of generated transitions over the target policy. If π_T can not find a shorter path for a transition generated by π_B , the select function will return True and the transition will be stored for Stochastic Policy Distillation. Therefore, π_T will learn to evolve to solve more sub-task, *i.e.*, transitions, continuously.

that *implicitly* learns the inverse dynamics $\phi_s^{-1}(\cdot)$ and the derivatives of distance metric $\mathcal{D}(\cdot, \cdot)$ with regard to state *s* simultaneously. The key insight of our proposed method is to *minimizing the First Hitting Time [Alili et al., 2005] of a drifted random walk* (Eq.5).

Concretely, the simplest case of Eq.5 is navigating in the Euclidean space, where the distance metric is $\mathcal{D}(s,g) = ||g-s||_2$ and the transition dynamics is an identical mapping, *i.e.*, $\phi_s(a) = a \in \mathcal{A} \subset \mathcal{S}$, and by applying Gaussian noise on the action space, we have

$$\pi(s,g) = ds = \epsilon \frac{g-s}{||g-s||_2} dt + \sigma dW_t, \tag{6}$$

which is a Stochastic Differential Equation. As our learning objective is to increase the possibility of reaching the goal in a finite time horizon, the problem can be formulated as minimizing the FHT $\tau = \inf\{t > 0 : s_t = g | s_0 > g\}$, *i.e.* hitting the goal in the state space. In practice, the goal state is always a region in the state space [Plappert et al., 2018], and therefore the task is to cross the region as soon as possible.

3.2 Evolutionary Stochastic Policy Distillation

Our proposed method combines evolutionary strategies with policy distillation to minimize FHT. Specifically, ESPD maintains a target deterministic policy π_T , parameterized as a policy network, and a behavioral stochastic policy π_B

$$\pi_B = \pi_T + \tilde{\eta}, \tilde{\eta} \sim \mathcal{N}(0, \sigma^2), \tag{7}$$

according to Eq.5, *i.e.*, the behavior policy comes from adding a Gaussian exploration noise upon the target policy π_T , as in previous deterministic policy learning literature [Lillicrap et al., 2015; Fujimoto et al., 2018b]. For the policy update step, ESPD use the evolutionary idea by distilling the well-performed behavior policies, in terms of FHT, to the target policy, instead of applying policy gradient or the zeroth-order approximation of policy gradient [Salimans et al., 2017] to the present target policy.

Concretely, during training, π_B first interacts with the environment and collects a batch of transition samples, permitting us to generate a batch of HIDs, regardless of their optimality. Those HIDs contain a set of transition pairs (s, g', a), where g' denotes the hindsight goals. *i.e.*, the starting points, final achieved goals, and the corresponding actions are included in those transition pairs. From an oracle-perspective, those HIDs can be regarded as generated from a series of *unknown deterministic policies* instead of a known stochastic policy π_B , each provides individual solutions for the state-goal pair task (s, g', a). Among those unknown oracle-policies, some are better than our current target policy π_T in terms of FHT, which means they are able to solve the certain state-goal pair task in fewer steps, or they are able to solve some sub-tasks while the π_T is not. Although we are not able to access those well-performing oracle-policies directly, we can distill the useful knowledge from those oracle-policies to π_T through their corresponding HIDs.

In practice, we use a SELECT function to distinguish the HIDs from oracle-policies that outperform π_T and store those well-performing HIDs in a buffer $\mathcal{B} = \{(s_i, g'_i, a_i)\}_{i=1,2,...,n}$. The SELECT function can be implemented in different ways, (1) reset the environment to a given previous state, which is always tractable in simulation [Nair et al., 2018], (2) use classifier, dynamic models or

Algorithm 1 ESPD

Require

• a target policy $\pi_T(s,g)$ parameterized by neural network: $\pi_T(s,g) = \pi_{\theta}(s,g)$ • a reward function r(s, g) = 1 if g = m(s) else 0 • a buffer for ESPD \mathcal{B} • a Horizon list $\mathcal{K} = [1, 2, ..., K]$ • a noise e.g., $\mathcal{N}(0, \sigma^2)$ Initialize π_T , $\pi_B = \pi_T + \tilde{\eta}, \tilde{\eta} \sim \mathcal{N}(0, \sigma^2), \mathcal{B}$ for episode = 1, M do generate s_0, g by the environment for t = 0, T - 1 do Select an action by the behavior policy $a_t = \pi_B(s_t, g)$ Execute the action a_t and get the next state s_{t+1} end for for t = 0, T - 1 do for k = 1. K do calculate additional goal according to s_{t+k} by $g' = m(s_{t+k})$ if $SELECT(s_t, g') = True$ then Store (s_t, g', a_t) in \mathcal{B} end if end for end for Sample a minibatch B from buffer \mathcal{B} Optimize target policy $\pi_T(s_t, g')$ to predict a_t according to Eq.8 Update behavior policy $\pi_B = \pi_T + \tilde{\eta}, \tilde{\eta} \sim \mathcal{N}(0, \sigma^2)$ end for

heuristics [Sun et al., 2019]. In this work we use (1) and leave the usage of model-based SELECT function to the future work. To implement (1), the SELECT function takes in an episode generated by π_B . Suppose the episode $(s_t, a_t, s_{t+1}, a_{t+1}, ..., s_{t+k})$ is of length k, the SELECT function reset the environment to the starting state of this episode s_t and run π_T for up to k steps, trying to reach the final achieved state s_{t+k} . *i.e.*, at every timestep, an action of $\pi_T(s, m(s_{t+k}))$ is performed. If π_T is **NOT** able to reach s_{t+k} within k steps, the corresponding transition $(s_t, m(s_{t+k}), a_t)$ will be collected in the buffer \mathcal{B} and π_T will learn from those transitions later. Such procedure is illustrated in Fig.2.

Then, we can apply Stochastic Policy Distillation (SPD) to distill the knowledge from the wellperforming oracle-policies to π_T so that π_T may evolve to be more capable to tackle the same sub-tasks. To be specific, we use supervised learning to minimize the difference between the action stored in the HID buffer and the action π_T predicted. The SPD is conducted as

$$\pi_T = \underset{\pi_T}{\arg\min} \frac{1}{N} \sum_{i=1}^{N} (\pi_T(s_i, g'_i) - a_i)^2,$$
(8)

where (s_i, g'_i, a_i) are sampled from the HID buffer \mathcal{B} . From this point of view, the ESPD method is composed of the evolution strategies and policy distillation, where a stochastic behavior policy π_B performs as perturbation on the target policy and produce diverse strategies (*a population*), and we choose those well-performed strategies to distill their knowledge into a target policy π_T (selection). Fig.1 provides an illustration of the learning pipeline and Algorithm 1 presents the detailed learning procedure of ESPD.

4 Experiments

4.1 Experiments on the Fetch Benchmarks

We demonstrate the proposed method on the Fetch Benchmarks. Specifically, we evaluate our method on the FetchPush, FetchSlide and FetchPickAndPlace environments, as shown in Fig.3. We compare



Figure 3: From left to right: the FetchPush. FetchSlide and FetchPickAndPlace environment



Figure 4: The test success rate comparison on the FetchPush-v1, FetchSlide-v1 and FetchPickAndPlace-v1 among our proposed method (ESPD), HER and Evolution Strategy (ES).

our proposed method with the HER [Andrychowicz et al., 2017; Plappert et al., 2018] released in OpenAI Baselines [Dhariwal et al., 2017] and the Evolution Strategy [Salimans et al., 2017] which is a counterpart of our method with parameter noise. As PCHID [Sun et al., 2019] can be regarded as a special case of ESPD if we gradually increase the hyper-parameter Horizon in ESPD from 1 to K, the performance of PCHID is upper-bounded by ESPD and we do not include it as a baseline. Such result can be infered from our ablation study on the Horizon K in the next section, which shows smaller K limits the performance, and achieves worse learning efficiency than K = 8, the default hyper-parameter used in ESPD².

Fig.4 shows the comparison of different approaches. For each environment, we conduct 5 experiments with different random seeds and plot the averaged learning curve. Our method shows superior learning efficiency and can learn to solve the task in fewer episodes in all the three environments.

4.2 Ablation Studies

Exploration Factor The exploration factor σ controls the randomness of behavior policy and therefore determines the behavior of generated samples. While larger σ helps the agents to benefit exploration by generating samples with large variance, smaller σ helps to generate a biased sample with little variance. Here we need to select a proper σ to balance the variance and bias. Fig.5 shows our ablation study on the selection of different exploration factors. The results are generated with 5 different random seeds. We find in all environments, the exploration factor $\sigma = 1$ provides sufficient exploration and relatively high learning efficiency.

Horizon K In our proposed method, the parameter of Horizon K determines the maximal length of sample trajectories the policy can learn from. Intuitively, smaller K decreases the learning efficiency as the policy is limited by its small horizon, making it hard to plan for the tasks that need more steps to solve. On the other hand, larger K will provide a better concept of the local as well as global geometry of the state space, and thus the agent may learn to solve more challenging tasks. However, using large K introduces more interactions with the environment, and needs more computation time. Moreover, as the tasks normally do not need lots of steps to finish, when the Horizon is getting too large, more noisy actions will be collected and be considered as better solutions and hence impede the learning performance. Fig.6 shows our ablation studies on the selection of Horizon K. The results are generated with 5 different random seeds. We find that K = 8 provides satisfying results in all of the three environments.

²In FetchSlide, our ablation studies in the next section shows K = 12 outperforms K = 8.



Figure 5: The test success rate comparison on the FetchPush-v1, FetchSlide-v1 and FetchPickAndPlace-v1 with different scale of exploration factors. Experiments are repeated with 5 random seeds.



Figure 6: The test success rate comparison on the FetchPush-v1, FetchSlide-v1 and FetchPickAndPlace-v1 with different scale of Horizon K. The results are generated with 5 different random seeds

5 Related Work

Learning with Experts and Policy Distillation Imitation Learning (IL) approaches introduce expert data in the learning of a agent [Pomerleau, 1991; Ross et al., 2011], while similar techniques are used in the literature of Learning from Demonstrations (LfD) [Atkeson & Schaal, 1997; Schaal, 1997; Argall et al., 2009], where experience of human expert will be collected to help the learning of an agent. Those methods are further extended in the setting of Deep Q-learning [Mnih et al., 2015; Hester et al., 2018], combined with DDPG [Lillicrap et al., 2015; Nair et al., 2018] or to learn from imperfect expert data [Gao et al., 2018].

Policy Distillation was proposed to extract the policy of a trained RL agent with a smaller network to improve the efficiency as well as the final performance or combine several task-specific agents together [Rusu et al., 2015]. Latter extensions proposed to improve the learning efficiency [Schmitt et al., 2018], enhance multi-task learning [Teh et al., 2017; Arora et al., 2018].

All of those methods start from a trained expert agent or human expert experience that can solve a specific task [Czarnecki et al., 2019]. As a comparison, our proposed method focus on extracting knowledge from stochastic behaviors, which is capable to act as a feasible policy itself with regard to the primal task.

Evolution Strategies and Parameter Noise The Evolution Strategy (ES) was proposed by Salimans et al. [2017] as an alternative to standard RL approaches, where the prevailing temporal difference based value function updates or policy gradient methods are replaced as perturbations on the parameter space to resemble the evolution. Later on, Campos et al. [2018] improved the efficiency of ES by means of importance sampling. Besides, the method was also extended to be combined with Novelty-Seeking to further improve the performance [Conti et al., 2018].

Thereafter, Plappert et al. [2017] proposed to use Parameter Noise as an alternative to the action space noise injection for better exploration. They show such a perturbation on the parameter space can be not only used for ES methods, but also collected to improve the sample efficiency by combining it with traditional RL methods.

While previous ES algorithms apply perturbations on the parameter noise and keep the best-performed variates, our approach implicitly execute the policy evolution by distilling better behaviors, therefore our approach can be regarded as an Evolutiaon Strategy based on action space perturbation.

Supervised and Self-Imitate Approaches in RL Recently, several works put forward to use supervised learning to improve the stability and efficiency of RL. Zhang et al. [2019] propose to utilize supervised learning to tackle the overly large gradients problem in policy gradient methods. In order to improve sample efficiency, the work chose to first design a target distribution proposal and then used supervised learning to minimize the distance between present policy and the target policy distribution. The Upside-Down RL proposed by Schmidhuber [2019] used supervised learning to mapping states and rewards into action distributions, and therefore acted as a normal policy in RL. Their experiments show that the proposed UDRL method outperforms several baseline methods [Srivastava et al., 2019]. In the work of Sun et al. [2019], a curriculum learning scheme is utilized to learn policies recursively. The self-imitation idea behind ESPD is also discussed by the concurrent work of Ghosh et al. [2019], but ESPD further uses the SELECT function to improve the quality of collected data for self-imitation learning.

6 Conclusion

In this work, we focus on developing a practical algorithm that can evolve to solve the GCRS problem by distilling knowledge from a series of its stochastic variants. The key insight behind our proposed method is based on our SDE formulation of the GCRS tasks: we solve such tasks by the learning to reduce the FHT. Our experiments on the OpenAI Fetch Benchmarks show that the proposed method, Evolutionary Stochastic Policy Distillation, has high learning efficiency as well as stability with regard to two benchmark methods, the Evolution Strategies and Hindsight Experience Replay.

References

- Alili, L., Patie, P., and Pedersen, J. L. Representations of the first hitting time density of an ornsteinuhlenbeck process. *Stochastic Models*, 21(4):967–980, 2005.
- Kaelbling, Leslie Pack. Learning to achieve goals In the 13th International Joint Conferences on Artificial Intelligence, pp. 1094–1099. Citeseer, 1993.
- Andrychowicz, M., Wolski, F., Ray, A., Schneider, J., Fong, R., Welinder, P., McGrew, B., Tobin, J., Pieter Abbeel, O., and Zaremba, W. Hindsight experience replay. In Guyon, I., Luxburg, U. V., Bengio, S., Wallach, H., Fergus, R., Vishwanathan, S., and Garnett, R. (eds.), Advances in Neural Information Processing Systems 30, pp. 5048–5058. Curran Associates, Inc., 2017. URL http://papers.nips.cc/paper/7090-hindsight-experience-replay.pdf.
- Argall, B. D., Chernova, S., Veloso, M., and Browning, B. A survey of robot learning from demonstration. *Robotics and autonomous systems*, 57(5):469–483, 2009.
- Arora, H., Kumar, R., Krone, J., and Li, C. Multi-task learning for continuous control. *arXiv preprint arXiv:1802.01034*, 2018.
- Atkeson, C. G. and Schaal, S. Robot learning from demonstration. In *ICML*, volume 97, pp. 12–20. Citeseer, 1997.
- Barto, A. G. and Mahadevan, S. Recent advances in hierarchical reinforcement learning. *Discrete* event dynamic systems, 13(1-2):41–77, 2003.
- Bengio, Y., Louradour, J., Collobert, R., and Weston, J. Curriculum learning. In *Proceedings of the* 26th annual international conference on machine learning, pp. 41–48, 2009.
- Bishop, C. M. Mixture density networks. 1994.
- Bracewell, R. N. and Bracewell, R. N. *The Fourier transform and its applications*, volume 31999. McGraw-Hill New York, 1986.
- Campos, V., Giro-i Nieto, X., and Torres, J. Importance weighted evolution strategies. *arXiv preprint arXiv:1811.04624*, 2018.
- Conti, E., Madhavan, V., Such, F. P., Lehman, J., Stanley, K., and Clune, J. Improving exploration in evolution strategies for deep reinforcement learning via a population of novelty-seeking agents. In Advances in neural information processing systems, pp. 5027–5038, 2018.
- Czarnecki, W. M., Pascanu, R., Osindero, S., Jayakumar, S. M., Swirszcz, G., and Jaderberg, M. Distilling policy distillation. *arXiv preprint arXiv:1902.02186*, 2019.
- Dhariwal, P., Hesse, C., Klimov, O., Nichol, A., Plappert, M., Radford, A., Schulman, J., Sidor, S., Wu, Y., and Zhokhov, P. Openai baselines. https://github.com/openai/baselines, 2017.
- Dietterich, T. G. Hierarchical reinforcement learning with the maxq value function decomposition. *Journal of artificial intelligence research*, 13:227–303, 2000.
- Fujimoto, S., Meger, D., and Precup, D. Off-policy deep reinforcement learning without exploration. *arXiv preprint arXiv:1812.02900*, 2018a.
- Fujimoto, S., Van Hoof, H., and Meger, D. Addressing function approximation error in actor-critic methods. arXiv preprint arXiv:1802.09477, 2018b.
- Gao, Y., Lin, J., Yu, F., Levine, S., Darrell, T., et al. Reinforcement learning from imperfect demonstrations. *arXiv preprint arXiv:1802.05313*, 2018.
- Ghosh, D., Gupta, A., Fu, J., Reddy, A., Devine, C., Eysenbach, B., and Levine, S. Learning to reach goals without reinforcement learning. arXiv preprint arXiv:1912.06088, 2019.

Ha, D. and Schmidhuber, J. World models. arXiv preprint arXiv:1803.10122, 2018.

- Hester, T., Vecerik, M., Pietquin, O., Lanctot, M., Schaul, T., Piot, B., Horgan, D., Quan, J., Sendonaris, A., Osband, I., et al. Deep q-learning from demonstrations. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.
- Kakutani, S. 143. two-dimensional brownian motion and harmonic functions. *Proceedings of the Imperial Academy*, 20(10):706–714, 1944.
- Lillicrap, T. P., Hunt, J. J., Pritzel, A., Heess, N., Erez, T., Tassa, Y., Silver, D., and Wierstra, D. Continuous control with deep reinforcement learning. *arXiv preprint arXiv:1509.02971*, 2015.
- Mnih, V., Kavukcuoglu, K., Silver, D., Rusu, A. A., Veness, J., Bellemare, M. G., Graves, A., Riedmiller, M., Fidjeland, A. K., Ostrovski, G., et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.
- Nair, A., McGrew, B., Andrychowicz, M., Zaremba, W., and Abbeel, P. Overcoming exploration in reinforcement learning with demonstrations. In 2018 IEEE International Conference on Robotics and Automation (ICRA), pp. 6292–6299. IEEE, 2018.
- Ng, A. Y., Harada, D., and Russell, S. Policy invariance under reward transformations: Theory and application to reward shaping. In *ICML*, volume 99, pp. 278–287, 1999.
- Pachocki, J., Brockman, G., Raiman, J., Zhang, S., Pondé, H., Tang, J., Wolski, F., Dennison, C., Jozefowicz, R., Debiak, P., et al. Openai five, 2018. URL https://blog. openai. com/openai-five, 2018.
- Plappert, M., Houthooft, R., Dhariwal, P., Sidor, S., Chen, R. Y., Chen, X., Asfour, T., Abbeel, P., and Andrychowicz, M. Parameter space noise for exploration. arXiv preprint arXiv:1706.01905, 2017.
- Plappert, M., Andrychowicz, M., Ray, A., McGrew, B., Baker, B., Powell, G., Schneider, J., Tobin, J., Chociej, M., Welinder, P., et al. Multi-goal reinforcement learning: Challenging robotics environments and request for research. arXiv preprint arXiv:1802.09464, 2018.
- Pomerleau, D. A. Efficient training of artificial neural networks for autonomous navigation. *Neural computation*, 3(1):88–97, 1991.
- Ross, S., Gordon, G., and Bagnell, D. A reduction of imitation learning and structured prediction to no-regret online learning. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pp. 627–635, 2011.
- Rusu, A. A., Colmenarejo, S. G., Gulcehre, C., Desjardins, G., Kirkpatrick, J., Pascanu, R., Mnih, V., Kavukcuoglu, K., and Hadsell, R. Policy distillation. arXiv preprint arXiv:1511.06295, 2015.
- Salimans, T., Ho, J., Chen, X., Sidor, S., and Sutskever, I. Evolution strategies as a scalable alternative to reinforcement learning. *arXiv preprint arXiv:1703.03864*, 2017.
- Schaal, S. Learning from demonstration. In Advances in neural information processing systems, pp. 1040–1046, 1997.
- Schaul, T., Horgan, D., Gregor, K., and Silver, D. Universal value function approximators. In Bach, F. and Blei, D. (eds.), *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pp. 1312–1320, Lille, France, 07–09 Jul 2015. PMLR. URL http://proceedings.mlr.press/v37/schaul15.html.
- Schmidhuber, J. Reinforcement learning upside down: Don't predict rewards–just map them to actions. *arXiv preprint arXiv:1912.02875*, 2019.
- Schmitt, S., Hudson, J. J., Zidek, A., Osindero, S., Doersch, C., Czarnecki, W. M., Leibo, J. Z., Kuttler, H., Zisserman, A., Simonyan, K., et al. Kickstarting deep reinforcement learning. arXiv preprint arXiv:1803.03835, 2018.
- Silver, D., Huang, A., Maddison, C. J., Guez, A., Sifre, L., Van Den Driessche, G., Schrittwieser, J., Antonoglou, I., Panneershelvam, V., Lanctot, M., et al. Mastering the game of go with deep neural networks and tree search. *nature*, 529(7587):484, 2016.

- Srivastava, R. K., Shyam, P., Mutz, F., Jaśkowski, W., and Schmidhuber, J. Training agents using upside-down reinforcement learning. arXiv preprint arXiv:1912.02877, 2019.
- Sun, H., Li, Z., Liu, X., Lin, D., and Zhou, B. Policy continuation with hindsight inverse dynamics. In Advances in Neural Information Processing Systems, pp. 10265–10275, 2019.
- Sutton, R. S., Barto, A. G., et al. *Introduction to reinforcement learning*, volume 135. MIT press Cambridge, 1998.
- Tamar, A., Wu, Y., Thomas, G., Levine, S., and Abbeel, P. Value iteration networks. In Advances in Neural Information Processing Systems, pp. 2154–2162, 2016.
- Teh, Y., Bapst, V., Czarnecki, W. M., Quan, J., Kirkpatrick, J., Hadsell, R., Heess, N., and Pascanu, R. Distral: Robust multitask reinforcement learning. In Advances in Neural Information Processing Systems, pp. 4496–4506, 2017.
- Vinyals, O., Babuschkin, I., Czarnecki, W. M., Mathieu, M., Dudzik, A., Chung, J., Choi, D. H., Powell, R., Ewalds, T., Georgiev, P., et al. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *Nature*, 575(7782):350–354, 2019.
- Zhang, C., Li, Y., and Li, J. Policy search by target distribution learning for continuous control. *arXiv* preprint arXiv:1905.11041, 2019.



Figure 7: The numerical result with different values of bias b and goal awareness factor ϵ .

On the Selection of Exploration Factor Α

In Algorithm 1, the behavior policy π_B is composed of the deterministic target policy $\pi_T = \pi_{\theta}(s, g)$, and an exploration term $\mathcal{N}(0, \sigma^2)$. During the learning process, π_T provides a biased estimation of the feasible policy $\pi_{\theta}(s,g)$ without variance, while the exploration term $\mathcal{N}(0,\sigma^2)$ provides unbiased exploration with variance. The Eq.5 becomes

$$\pi_B = \pi_\theta(s,g) + \tilde{\eta} = \epsilon \phi_s^{-1} \left(-\xi \frac{\partial \mathcal{D}(s,g)}{\partial s} + b \right) + \tilde{\eta}, \tilde{\eta} \sim \mathcal{N}(0,\sigma^2), \tag{9}$$

where b is an unknown bias introduced by function approximation error or extrapolation error [Fujimoto et al., 2018a] due to the limited number of samples in Algorithm 1.

Intuitively, a large exploration factor, *i.e.* large σ , will lead to better exploration thus can help reduce the bias introduced by the π_T , while smaller σ can reduce the variance, but expose the bias. This is exactly the dilemma of Exploration-Exploitation (E&E) [Sutton et al., 1998]. We further introduce an effective annealing method to adjust σ , the exploration factor to tackle the E&E challenge.

In the following section, we provide analysis and numerical experiment result based on the special case we have mentioned above to interpret how the exploration factor helps to correct the bias.

Revisit the Special Case: Navigation in the Euclidean Space A.1

At the beginning of learning, the policy π_T is initialized randomly. The only way to cross the target region at this moment is to utilize large exploration term, *i.e.* with large σ . As the learning continues with limited experience, bias might be introduced into Eq.6

$$\pi(s,g) = ds = \epsilon \left(\frac{g-s}{||g-s||_2} + b\right) dt + \sigma dW_t,$$
(10)

where b denotes the bias. One the one hand, such bias may lead to extremely bad solutions if we do not keep a exploration term for bias correction [Fujimoto et al., 2018a]. On the other hand, while the policy becomes more capable of navigating in the state space to reach the goal, large exploration term will hinder the agent to step into the goal region. Here we conduct a numerical simulation to show the dependencies of Success Rate, *i.e.* the proportion that successfully hit the goal region in a 2-D Euclidean space navigation task, on the value of σ .

A.2 Numerical Result

According to the previous analysis, the exploration with a random behaved policy in a GCRS task is like a random walk in the state space. Distinguished from the well known fact that a drunk man will find his way home, but a drunk bird may get lost forever [Kakutani, 1944; Bracewell & Bracewell, 1986], in most cases, the systems we are concerned about have finite boundaries, and the goal, instead of a single point in the state space, always has a non-trivial radius. Therefore, in known dynamics, we can simulate the behavior of policy at different learning state, e.g., with different bias b, goal-awareness ϵ , and investigate how the exploration factor affects the learning outcomes.



Figure 8: The test success rate comparison on the FetchPush-v1, FetchSlide-v1 and FetchPickAndPlace-v1 with different scale of noise applied in policy evaluation. The results are generated with 5 different random seeds

Our simulation is based on a bounded region of size $N \times N$, for each episode, a current state and goal are generated randomly in the region. At each timestep, the state updates according to Eq.10, with normalized step length. The success rate shows the probability of hitting the goal within a finite time horizon T. In our simulation, we apply tabular fixed random bias with different scale (*i.e.*, U(0, 0.2) and U(0, 0.5)), and set T = 100, N = 100, maximal step length 10 and goal radius r = 1.

The result is shown in Fig.7. Smaller bias enables success rate increases when the goal-awareness is small. As goal awareness increase, the performance of success rate relies on the selection of exploration factor. For small exploration factors, the performance of biased policy will drastically be hindered, while proper exploration factor value will fix such a problem. Such imperfectness, e.g., the bias is unavoidable when parameterizing the policy with a neural network, hence we maintain a small exploration factor even when evaluating a policy for bias correction. The detailed comparison with different exploration factor in both training and testing phase is discussed in the experiment section.

A.3 Evaluation Noise

As we have shown in the numerical simulation, the bias of learned deterministic policy reduces the success rate. Such bias can be attributed to the extrapolation error [Fujimoto et al., 2018a]. Consequently, we introduce a Gaussian noise term in the learned policy to form a stochastic policy for robustness. Our ablation studies on the selection of different scales of such noise terms are shown in Fig.8. The results are generated with 5 different random seeds, showing proper noise terms can help to overcome the extrapolation error and therefore improve the evaluation performance. It worths noting that applying larger noise in the game of FetchSlide will lead to performance decay, as the game relies on precise manipulation: after the robotic arm hitting the block, the block will become out of reach, and therefore the agent can not correct the error anymore.

B Future Work

Our method, as a novel backbone for GCRS tasks, can be combined with other RL techniques for further improvements, and is promising to be extended to more general settings such as non-GCRS tasks. Here we list some possible future extensions.

Forward Dynamics Modeling The evolutionary part of ESPD is based on the SELECT function, which evaluates the superiority between π_T and π_B , and plays the role of sorting function in evolution strategies. In this work, the SELECT function is implemented by resetting the environment. Other approaches include using dense reward and model-based approximation [Sun et al., 2019]. In our experiments, we observed great robustness on the selection step: the proposed method can still learn feasible solutions even when the action selected in the selection step is off-policy, e.g., a random policy. Such robustness indicates that approximating the dynamics model needed in the SELECT with model-based RL approaches [Ha & Schmidhuber, 2018] is a promising future direction.

Combination with Other RL Algorithms As we have shown in the paper, our ESPN method can work well in isolation and perform competitively with previous approaches. In the future, combining ESPD and other off-policy algorithms might provide further improvements in the performance as

well as higher sample efficiency. Furthermore, the evolutionary step can be coupled with different algorithms, other than stochastic variants to achieve better exploration efficiency.

Extension to non-GCRS tasks While our work focuses on GCRS tasks, it is possible to extend our framework to the non-GCRS tasks, such as the locomotion tasks. The UDRL method proposed by Schmidhuber [2019] provides the idea to take the reward as input, which can be understood as taking reward as the goal and therefore any non-GCRS task can be formulated as a similar GCRS form by taking *getting high reward* as a goal. In that case our work can be applied.