# QUANTUM ILLUMINATION WITH MULTIPLE ENTANGLED PHOTONS

Ricardo Gallego Torromé¹

Department of Mathematics

Faculty of Mathematics, Natural Sciences and Information Technologies

University of Primorska, Koper, Slovenia

Nadya Ben Bekhti-Winkel<sup>2</sup>

FHR, Fraunhofer-Institut für Hochfrequenzphysik und Radartechnik, Fraunhoferstr. 20, 53343 Wachtberg, Germany

Peter Knott<sup>3</sup>

FHR, Fraunhofer-Institut für Hochfrequenzphysik und Radartechnik, Fraunhoferstr. 20, 53343 Wachtberg, Germany

Chair of Radar Systems Engineering Institute of High Frequency Technology RWTH Aachen University Melatener Strae 25 52074 Aachen Germany

ABSTRACT. A generalization of Lloyd's quantum illumination to signal beams described by two entangled photon states is developed. The protocol offers a method to find the range of target, reduces the size of the required time bandwidth product and it is resilient against noise and loses.

Keywords: Quantum Radar, Quantum Illumination, Quantum Entanglement.

### 1. Introduction

Lloyd's Quantum illumination is a type 3 quantum sensing protocol that has open a new research area, quantum illumination, that promises to outperform efficiency in target detection with respect to non-entangled and classical illumination schemes [8, 7]. Lloyd's quantum illumination was the first of type 3 quantum sensing protocol robust against total loss of entanglement. The protocol relies on several heritage correlations between the idler and the signal state that survive the annihilation of entanglement, together with specific characteristic of the signal state (large time band-width product).

However, also from its inception, many important limitations and problems with the practical and theoretical stand have been understood to happen generically in quantum illumination protocols [12, 14]. Such investigations have raised doubts on the possibilities of realistic implementations of quantum radar using quantum illumination protocols. Let us mention that among the several problems of the implementation in realistic radar technological scenarios, a fundamental problem is the range problem: quantum illumination requires previous knowledge of the target

Date: September 21, 2020.

<sup>&</sup>lt;sup>1</sup>Email: rigato39@gmail.com

<sup>&</sup>lt;sup>2</sup>Email: nadya.ben.bekhti-winkel@fhr.fraunhofer.de

<sup>&</sup>lt;sup>3</sup>Email: peter.knott@fhr.fraunhofer.de

range, limiting the applicability of the theory in the ambit of target detection to scanning prototypes.

Several interesting suggestions to overcome the range problem have been considered. For instance, L. Maccone and C. Ren have suggested the use of beams composed by N-photon entangled states as signal beams. In this way, a maximum advantage that depends on  $\sqrt{N}$  respect to non-entangled light is obtained [11]. Although the protocol provides a method to solve the range problem, the current form of the protocol is very sensitive to environmental noise and to loses.

We discuss in this paper a theoretical generalization of Lloyd's protocol to the case where the signal beam is composed by two entangled photon states. A three entangled photon state is created by three generation through a four photon nonlinear interaction [6]. The state is divided in an idler state, that contains one photon, and a signal state, that contains two photons. The three photons in each state are correlated in time of generation (ideally), in frequencies and in linear momentum. Then the signal is sent to explore a given region and the idler is retained in the receiver system. When the returned signal is detected, it is correlated with the still retained idler. Since there are two photons that are detected at the same time, one has a higher precision of when the photons coming from the scattering arrive to the target, instead of arriving noise photons. This higher sensitivity serves to identify the possible brother idler photon from the original entangled state with higher precision too.

The protocol is robust against entanglement loss, because it only uses the heritage correlations in time and energy from the original three photon states. The protocol is robust against environmental noise, for the same reasons than Lloyd's quantum illumination. Furthermore, the method of Maccone and Ren to obtain the range of the target can also be applied, providing a theoretical solution for the range problem. A similar method (coincidence detection) to obtain the range of the target has been used by England et al. [5] in their experiments on Lloyd's quantum illumination under related assumptions.

Finally, let us mention that our protocol requires a shorter time bandwidth product to effectively produce the same quantum enhancement in signal to noise ratio than in Lloyd's quantum illumination, in the domain of low signal to noise ratios.

### 2. QUANTUM ILLUMINATION WITH MULTIPLE ENTANGLED PHOTONS

We describe below a new protocol for a quantum radar which is resilient to thermal noise and provides a method for obtaining the target range.

## 2.1. Lloyd's quantum illumination using multiple entangled signal beams.

We will consider here the case where the back-ground noise  $N_B$  is small and the time-bandwidth product M is large, as in the original analysis from Lloyd [8]. This has the advantage of simplifying the treatment.

The generation of the idler and signal beams are as follows. We first consider a state of the form

$$(2.1) \qquad |\psi\rangle_3 = \frac{1}{\sqrt{M}} \sum_{\alpha=1}^M \hat{a}^{\dagger}(\omega_1(\alpha), \vec{k}_1(\alpha)) \, \hat{a}^{\dagger}(\omega_2(\alpha), \vec{k}_2(\alpha)) \, \hat{a}^{\dagger}(\omega_3(\alpha), \vec{k}_3(\alpha)) \, |0\rangle,$$

where  $\alpha=1,...,M$  indicates the modes of the states. This photon state can be obtained by four interaction linear optics. The photons 1, 2, 3 are correlated in time (they are generated at the same time), but they also are correlated in frequencies by the relation  $\omega_0=\omega_1+\omega_2+\omega_3$  and in momentum, by the relation  $\hbar\vec{k}_0=\hbar\vec{k}_1+\hbar\vec{k}_2+\hbar\vec{k}_3$  (see for instance, [6], section 13.4), where  $(\omega_o,\hbar\vec{k}_0)$  are the frequency and momentum of the pump beam.

The initial beam can be transformed by an unitary operator  $\mathcal{U} = I_1 \otimes I_2 \otimes U_3$  that sends  $\frac{\vec{k}_3}{\|\vec{k}_3\|}$  to  $\vec{k}' = \frac{\vec{k}_2}{\|\vec{k}_2\|}$ ) to prepare the sates in the form

$$(2.2) \qquad |\widetilde{\psi}\rangle_3 = \frac{1}{\sqrt{M}} \sum_{\alpha=1}^M \hat{a}^{\dagger}(\omega_1(\alpha), \vec{k}_1(\alpha)) \, \hat{a}^{\dagger}(\omega_2(\alpha), \vec{k}_2(\alpha)) \, \hat{a}^{\dagger}(\omega_3(\alpha), \vec{k}_2'(\alpha)) \, |0\rangle,$$

where two of the photons have parallel momenta  $\vec{k}_2 \parallel \vec{k}_2'$ , but were the frequencies  $\omega_2$  and  $\omega_3$  can be different. After this preparation, the beam is splitted into two beams: the idler beam, which is composed by photons with momentum  $(\omega_1, \vec{k}_1)$ , and the signal beam, which is composed by states with two photons with momentum  $(\omega_3, \parallel \vec{k}_3 \parallel \vec{k}_2')$ .

Independently of the methodology followed for the preparation of the beams in the required form, after the preparation and splitting of the beam, none of the photon states composing the idler beam and none of the states composing the signal beam are entangled anymore. However, the following correlations persists even after the loss of entanglement:

- Time correlation in the generation of the three photons,
- The photons on each state exhibit correlations in energy,

(2.3) 
$$\omega_0 = \omega_1(\alpha) + \omega_2(\alpha) + \omega_3(\alpha), \quad \alpha = 1, ..., M$$

and correlation in momentum,

as follows:

(2.4) 
$$\hbar \vec{k}_0 = \hbar \vec{k}_1(\alpha) + \hbar \vec{k}_2(\alpha) + \hbar ||\vec{k}_3|| \vec{k}_2'(\alpha), \quad \alpha = 1, ..., M.$$

Assuming the above framework for the generation and preparation of the idler and signal beams, let us analyze the case of detection for quantum illumination and single photon state illumination. The signal state is denoted by  $\tilde{\rho}_2$ , while the idler state is denoted by  $\tilde{\rho}_1$ . They can be both mixed states. The noise is described by the state  $\rho_0$  given by

$$\rho_0 \approx \left\{ (1 - M_B N_B) |0\rangle\langle 0| + N_B \sum_{\beta=1}^{M_B} |a^{\dagger}(\omega(\beta), \vec{k}(\beta))|0\rangle\langle 0|a(\omega(\beta), \vec{k}(\beta))| \right\}.$$

where the index  $\beta=1,...,M_B$  indicates the possible noise spectra  $spectNoise:=\{\vec{k}\in Noise\};\,M_B$  is the number of modes of the noise. This is the noise quantum state used in Lloyd's theory (see the expression (A.1) in Appendix A). Let us remark here that for the signal beam it is collimated such that the wavevectors of the photons 2 and 3 are in the spectra of the noise,

$$\vec{k}_2(\alpha),\,\vec{k}_2'(\alpha)\in\{\vec{k}\in\,Noise\},\quad \, \alpha=1,...,M.$$

Thus for all practical purposes, one can take the index  $\alpha$  and the index  $\beta$  as identical. Given the structure of the signal beam and the underlying correlations keep with the idler beam, the criteria that we can follow for a positive detection is formulated Criterion for positive detection: We declare that the target is present if two photons in the spectrum range of the signal are detected back within an established time window at the same time than an idler photon is detected together in a joint measurement of the idler and signal beam and if the correlation relations (2.3) and (2.4) hold good.

By joint measurement we mean here the following: once two photons are detected, one should compare the possible measurement (ideally, in a short time after the measurement is performed) with the corresponding idler photon. This requires to track when the idler photons are generated and for how long they stay in the receiver. Note that we are speaking of a theoretical protocol. This does not excludes that other methods for reception can be used, as for instance hybrid methods, that do not require to keep the idler alive [2, 10].

The notion of time window must be adapted to the particularities of the given experimental situations. It cannot be too large to avoid confusion with uncorrelated photons. This imposes a constrain on the operation characteristics of the direct photo detection device used and the available maximal range of detection. On the other hand, the time window detection cannot be too short to miss entangled photons. Indeed, the generation process of three entangled photons imply a lower value for the time window of detection precision: if the generation time is within an interval  $\delta t$  and the time of exposition is  $\Delta t$ , then it is necessary that  $\Delta t > \delta t$ . Also, corrections due to the pass by media with different refraction index for the idler and signal beam must be considered.

2.2. Enhancement of the signal to noise ratio. In the following paragraphs we evaluate the signal to noise ratio for non-entangled illumination and for quantum illumination with multiple entangled photon states as signal. The procedure what we will follow mimics the treatment as in LLoyd's theory [8].

**A.** Illumination with non-entangled light. When the target is not there and the illumination is done with non-entangled light, the quantum states are described by the density matrix  $\rho_0$ . The probability of false positive can be read directly from the structure of the state and, by the criteria of detection discussed above, it is the probability of detecting two photons in the same time window. Therefore, in the case of low brightness environment  $(N_B << 1)$ , the probability of false positive is determined by the criteria of detection of two photons with the required energies  $\omega_2$ ,  $\omega_3$  and momenta  $\vec{k}_2$ ,  $\vec{k}_2' \in spect\ Noise$  and is given by the expression

$$(2.5) p_0(+) = (N_B)^2,$$

where independent detection of two photons has been considered.

When the target is there, and under the same assumptions, the state is given by the density matrix

$$\rho_{1} = (1 - \eta)\rho_{0} + \eta\tilde{\rho}$$

$$\approx (1 - \eta) \left\{ (1 - M_{B} N_{B})|0\rangle\langle 0| + N_{B} \sum_{\beta=1}^{M_{B}} |a^{\dagger}(\omega(\beta), \vec{k}(\beta))|0\rangle\langle 0|a(\omega(\beta), \vec{k}(\beta))| \right\} + \eta\,\tilde{\rho},$$

where  $\tilde{\rho}$  stands for the state describing the signal when using non-entangled light. The probability for the detection the arrival of two simultaneous photons is in this case of the form

(2.6) 
$$p_1(+) = ((1 - \eta)N_B + \eta)^2$$

The signal to noise ratio (SNR) in quantum illumination with two signal state photons when the illumination is performed with non-entangled light is given by the expression

(2.7) 
$$SNR_{CI2P} = \frac{p_1(+)}{p_0(+)} = \left(\frac{(1-\eta)N_B + \eta}{N_B}\right)^2.$$

One observes that this signal to noise ratio  $SNR_{CI2P}$  is given by the square of the signal to noise ratio  $SNR_{CI}$  in Lloyd's theory (expression (A.8) in Appendix A). This is a natural consequence of the methodology followed. Therefore, when the signal to noise ratio is low  $(SNR_{CI2P})$  is small than 1), then there is a reduction in sensitivity respect to the original Lloyd's theory in the regime  $SNR_{CI} < 1$ .

**B.** Illumination with three photons entangled light. When there is no target there, the state noise-idler is described by the density matrix  $\tilde{\rho}_0^e$  and it has the form

$$\tilde{\rho}_0^e \approx \left\{ (1 - M_B N_B) |0\rangle\langle 0| + N_B \sum_{\beta=1}^{M_B} |a^{\dagger}(\omega(\beta), \vec{k}(\beta))|0\rangle\langle 0|a(\omega(\beta), \vec{k}(\beta))| \right\} \otimes \tilde{\rho}_1.$$

The probability of a false positive is the probability to attribute to the presence of the target and the detection of two simultaneous returned photons. Within the scope of the approximations that we are considering, such a probability is independent of the details of the signal state and given by the expression

$$(2.8) p_0^e(+) = \left(\frac{N_B}{M}\right)^2.$$

This relation shows an enhancement respect to the analogous relation in Lloyd's quantum illumination protocol (eq. (A.10) in Appendix).

When the target is there, the state after decoherence and interaction signal-target is of the form

$$\tilde{\rho}_1^e = (1 - \eta) \cdot \tilde{\rho}_0^e + \eta \, \tilde{\rho}_2.$$

By a similar argument as in Lloyd's theory, the probability of detection using entangled light signal states when the target is there for one trial is

(2.9) 
$$p_1^e(+) = \left( (1 - \eta) \frac{N_B}{M} + \eta \right)^2.$$

The signal to noise ratio is of the form

(2.10) 
$$SNR_{QI2R}^e = \frac{p_1^e(+)}{p_0^e(+)} = \left(\frac{M}{N_B}\right)^2 \left((1-\eta)\frac{N_B}{M} + \eta\right)^2,$$

which is the square of the signal to noise ratio obtained for Lloyd's quantum illumination in the analogous case, equation (A.15).

In the regime when the signal to noise ratio is low, expression (2.10) implies two different types of phenomena. The first is an enhancement from the use of quantum entangled states respect to non-entangled states, analogous result to Lloyd's theory. The second phenomenon is a reduction of enhancement respect to Lloyd's quantum illumination in the low sinal to noise ratio regime.

Furthermore, in the regime of low signal to noise ratio, in the sense that it is less than 1, there could be a reduction in the time bandwidth product needed to reach the same advantage in SNR than in Lloyd's quantum illumination. Let us compare the  $SNR_{QI2R}^e$  of multiple entangle photon illumination (2.10) with the  $SNR_{QI}^e$  in Lloyd's quantum illumination (A.15). If both are to be of the same order, then we will have the expression

$$SNR_{QI2R}^{e} = \left(\frac{M}{N_B}\right)^2 \left((1-\eta)\frac{N_B}{M} + \eta\right)^2 = \frac{M'}{N_B} \left((1-\eta)\frac{N_B}{M'} + \eta\right) = SNR_{QI}^{e},$$

where M and M' are a priori different. In Lloyd's theory, the condition of low SNR is  $\eta M'/N_B < 1$ . Thus the comparison between  $SNR^e_{QI2R}$  and  $SNR^e_{QI2R}$  in the regime  $\eta << 1$  leads to the relations

$$\left(\frac{M}{N_B}\right)\left((1-\eta)+\eta\,\frac{M}{N_B}\right)^2 = \left((1-\eta)+\eta\,\frac{M'}{N_B}\right) \approx \left(1+\eta\,\frac{M'}{N_B}\right) \geq \,2\eta\,\frac{M'}{N_B},$$

or comparing the first and last expressions,

$$(2.11) M\left(1+\eta\frac{M}{N_B}\right)^2 \ge 2\eta M'.$$

If this condition is consistent with a reduction of the time band-width product in the sense that M' > M, then the condition becomes

$$2^{2} M \ge M \left(1 + \eta \frac{M}{N_{B}}\right)^{2} \ge M \left(1 + \frac{M'}{N_{B}}\right) \ge 2 \eta M' \ge 2 \eta M,$$

which is equivalent to the condition

$$1 \geq \frac{\eta}{2}$$
.

This condition, in the low reflective regime  $\eta << 1$ , always hold. This proves the existence of a regime where the comparison (2.11) holds good and where there is a reduction M' < M in the required time band-with product when using multiple entangled photons quantum illumination with respect to Lloyd's protocol.

2.3. Determination of the range and transverse position using quantum illumination with two signal photons states. If the target is small enough in the sense that the surface can be considered smooth and regular without drastic changes, by the criterion for the detection discussed above, the target is declared detected if two individual photons with the same frequency and momenta are detected within the same detection time window. Under the further assumption that there is only a pair of photons on fly, the detection of a pair of correlated photons provides a measure also of  $t-t_0$  in an analogous way to Maccone-Ren's theory and hence, it determines the range by the expression

(2.12) 
$$r_z = c \frac{1}{2} (t_1 - t_0 + t_2 - t_0))$$

where  $t_1$  and  $t_2$  are arrival times and  $t_0$  is the time of emission. The measurement of the location of the two photons determines the transverse location of the target as the average location of the photons arrivals.

The reduction in the probability of error is enhanced by the correlation with the idler beam.

### 3. Discussion

This paper is a first step towards a more complete theory of quantum illumination with signal beams described by quantum states with two photons correlated with an idler states of one photon. As such first step, we have discussed in the most basic form the protocol, showing two fundamental benefits respect to the equivalent protocol in quantum illumination, namely, 1. The requirement of a lower time bandwidth product in the bad regime respect to Lloyd's quantum illumination and 2. A methodology to obtain the target range.

Regarding the implementation of the protocol for radar systems, several problems remain to be addressed. The first one to mention is the difficulty in the generation of the required states for the protocol. Three photons generation is an arduous task [3, 4, 6]. However, the fact that it is possible to generate usable beams for quantum illumination by means of four wave mixing generation as demonstrated by [5], provides arguments in favour of the possibility of the related three photon generation from four photon interactions [6]. Many details should be clarified before to have a pertinent source of states.

Second, in order to be able to use quantum illumination with two photon states signal beams, the signal beam must be in the microwave regime. However, the original generated entangled state  $|\psi_3\rangle$  does not need to correspond to a microwave photon state, because existing current frequency conversion methods (electro-optomechanical converter [1]) can be applied from optical to microwave. The use of Josephson parametric amplification (JPA) is an alternative to the laboratory generation of microwave entangled photons, but currently it is difficult to find a JPA mechanism capable to generate three photons entangled states. Furthermore, the application of such methods will reduce the efficiency.

In order to treat the storage of the idler and the recognition of the beam, a combination of the methods in quantum illumination as introduced in [2, 10, 9] can provide alternative solution to the problem.

Lloyd's quantum illumination did not offer theoretical advantage in sensitivity over theoretical protocols based upon coherent light illumination [13]. However, the important benefits that the new protocol discussed here has makes it potentially useful for future implementations. Better understanding of the protocol advantages is required. A natural next step in the development of the theory is to consider the Gaussian version of the protocol, on the lines as Gaussian quantum illumination [15]. In particular, we expect that, as in the case of Gaussian quantum illumination, the new protocol will show advantage in probability of detection over coherent light detection protocols.

# APPENDIX A. ENHANCEMENT OF SENSITIVITY IN LLOYD'S QUANTUM ILLUMINATION: AN ILLUSTRATIVE EXAMPLE

In the following lines we discus in detail some aspects of Lloyd's theoretical protocol [8]. We partially follow the exposition described in [7]. As it is commonly used, hypothesis 0 means that the target is not there, while when the target is there, the hypothesis is labeled by 1.

A. Non-entangled light illumination. When the light used for experiments is

described by non-entangled photons, the density matrix of the system idler-signalnoise, when the target is not there (hypothesis 0) is

(A.1) 
$$\rho_0 \approx \left\{ (1 - M N_B) |0\rangle\langle 0| + N_B \sum_{n=1}^M |k\rangle_n \langle k|_n \right\},\,$$

where  $|k\rangle_n$  stands for a noise photon mode. Hence the probability of a false positive is

(A.2) 
$$p_0(+) = N_B$$
,

while the probability to be correct in the forecast that the target is not there is

(A.3) 
$$p_0(-) = 1 - p_0(+) = 1 - N_B.$$

If we repeat the experiment m times, the probability of a false positive is

$$p_0(+,M) = (N_B)^M$$
.

If the target is there (hypothesis 1), then the density matrix is given by

$$(A.4) \rho_1 = (1 - \eta)\rho_0 + \eta \tilde{\rho}$$

(A.5) 
$$\approx (1 - \eta) \left\{ (1 - MN_B)|0\rangle\langle 0| + N_B \sum_{n=1}^{M} |k\rangle_n \langle k|_n \right\} + \eta |\psi\rangle_s \langle \psi|_s,$$

where  $|\psi\rangle_s$  stands for the state describing the signal, that one can assume first is a pure state, while  $\eta$  is the reflective index. It follows that the probability to measure the arrival of photon is

(A.6) 
$$p_1(+) = (1 - \eta)N_B + \eta$$

and that consequently, the probability of false negative is

(A.7) 
$$p_1(-) = 1 - p_1(+) = 1 - ((1 - \eta)N_B + \eta) = (1 - \eta)(1 - N_B).$$

The signal to noise ratio is given by the expression

(A.8) 
$$SNR_{CI} = \frac{p_1(+)}{p_0(+)} = \frac{((1-\eta)N_B + \eta)}{(N_B)}.$$

**B. Entangled light illumination**. Let us now consider the case when the illumination is made using entangled states. For the case when there is no target there, the density matrix is given by the expression

$$(A.9) \qquad \rho_0^e \approx \left\{ (1-MN_B)|0\rangle\langle 0| + N_B \sum_{n=1}^M |k\rangle_n\langle k|_n \right\} \otimes \left(\frac{1}{M} \sum_{n=1}^M |k\rangle_A\langle k|_A\right),$$

where  $\frac{1}{M} \sum_{k=1}^{M} |k\rangle_A \langle k|_A$  is the state of the idler. The state

$$\rho_0 = \left\{ (1 - MN_B)|0\rangle\langle 0| + N_B \sum_{n=1}^{M} |k\rangle_n\langle k|_n \right\}$$

is the state that will describe the absence of the target. It determines the probability distributions to detect one photon due to noise only. The modes determining the idler k=1,...,M are selected to coincide with the modes of the noise. In this context, it is remarkable that the false positive probability for one individual detection,

(A.10) 
$$p_0^e(+) = \frac{N_B}{M}$$

is dramatically reduced with the number of modes M. This was first highlighted by S. Lloyd in his seminal work [8]. The probability of forecasting correctly the absence of the target is given by the probability of the complement,

(A.11) 
$$p_0^e(-) = 1 - \frac{N_B}{M}.$$

Note than when the experiment is repeated a number m of times in a independent way, the probability of a false positive after detecting m independent photons is

$$p_0^e(+,m) = \left(\frac{N_B}{M}\right)^m.$$

In the case that the target is there, for entangled states, the system idler-noisesignal is described by a density matrix of the form

(A.12) 
$$\rho_1^e = (1 - \eta) \cdot \rho_0^e + \eta \, \rho_s,$$

where  $\rho_s$  is the density matrix of the signal photon system. From this expression, one can extract the probability of detecting the target is

(A.13) 
$$p_1^e(+) = (1 - \eta) \frac{N_B}{M} + \eta.$$

The probability of no detection (interpreted as a false negative) is of the form

(A.14) 
$$p_1^e(-) = 1 - p_1^e(+) = \left(1 - \frac{N_B}{M}\right)(1 - \eta).$$

When applied m independent experiments, the probability of right detection is

$$p_1^e(+,m) = \left( (1-\eta) \frac{N_B}{M} + \eta \right)^m$$

For the case of false negative,

$$p_1^e(-,m) = 1 - p_1^e(+) = (1 - \frac{N_B}{M})^m (1 - \eta)^m.$$

(A.15) 
$$SNR_{QI}^{e} = \frac{p_{1}^{e}(+)}{p_{0}^{e}(+)} = \left(\frac{M}{N_{B}}\right) \left((1-\eta)\frac{N_{B}}{M} + \eta\right),$$

From the above formulae and comparing the probabilities of false positive and detection using quantum enhancement respect to classical light, one observes a clear enhancement in sensitive when using quantum illumination [8]. Further details of the analysis of how the sensitivity enhancement arises using Lloyd's protocol can be found summarized in [8] and in [7], section 5.5.3.

**Acknowledgements**. We would like to thank L. Maccone and C. Ren for the reading of a previous version of the manuscript and raise critical comments and point out several errors. This work has been financed by *Fraunhofer Institute for High Frequency Physics and Radar Techniques FHR*.

### References

- S. Barzanjeh, S. Guha, C. Weedbrook, D. Vitale, J. H. Shapiro and S. Pirandola, *Microwave quantum illumination*, Phys. Rev. Lett. 114, 080503 (2015).
- [2] S. Barzanjeh, S. Pirandola, D. Vitali and J. M. Fink, Microwave Quantum Illumination using a digital receiver, Science Advances Vol. 6, no. 19, eabb0451 (2020).
- [3] K. Bencheikh, F. Gravier, J. Douady, A. Levenson and B. Boulanger, *Triple photons: a challenge in nonlinear and quantum optics*, C. R. Physique **8**, 206 (2007).

- [4] N. A. Borshchevskaya, K. G. Katamadze, S. P. Kulik, M. V. Fedorov, Three-photon generation by means of third-order spontaneous parametric down-conversion in bulk crystals, Laser Phys. Lett. 12, 115404 (2015).
- [5] D. G. England, B. Balaji, and B. J. Sussman1, Quantum-enhanced standoff detection using correlated photon pairs, Phys. Rev. A 99, 023828 (2019).
- [6] J. C. Garrison and R. Y. Chiao, Quantum Optics, Oxford University Press (2007).
- [7] M. Lanzagorta, Quantum Radar, Synthesis Lectures on Quantum Computing n. 5, Morgan and Claypool publishers (2011).
- [8] S. Lloyd, Enhanced Sensitivity of Photodetection via Quantum Illumination, Sicence 321, 1463 (2008).
- [9] D. Luong, S. Rajan and B. Balaji Quantum Two-Mode Squeezing Radar and Noise Radar: Correlation Coefficients for Target Detection, IEEE Sensors Journal, Vol. 20, Issue: 10, May15, 15 (2020).
- [10] D. Luong, C. W. Sandbo Chang, A. M. Vadiraj, A. Damini, C. M. Wilson and B. Balaji, Receiver Operating Characteristics for a Prototype Quantum Two-Mode Squeezing Radar, https://arxiv.org/abs/1903.00101.
- [11] L. Maccone and C. Ren, Quantum Radar, Phys. Rev. Lett. 124, 200503 (2020).
- [12] S. Pirandola, B. Roy Bardham, T. Gehring, C. Weedbrook and S. Lloyd, Advances in photonic quantum sensing, Nature Photonics 12, 724(2018).
- [13] J. H. Shapiro and S. Lloyd, Quantum illumination versus coherent-state target detection, New Journal of Physics 11 063045 (2009).
- [14] J. H. Shapiro, The Quantum Illumination Story, IEEE Aerospace and Electronic Systems Magazine35, Issue: 4, April 1 (2020).
- [15] S.-H. Tan et al., Quantum Illumination with Gaussian States, Phys. Rev. Lett. 101, 253601 (2008).