# Detecting of a Patient's Condition From Clinical Narratives Using Natural Language Representation

Thanh-Dung Le, *Member, IEEE*, Jérôme Rambaud, Guillaume Sans, Philippe Jouvet, and Rita Noumeir, *Member, IEEE* 

Abstract—This paper proposes a joint clinical natural language representation learning and supervised classification framework based on machine learning for detecting concept labels in clinical narratives at CHU Sainte Justine Hospital (CHUSJ). The novel framework jointly discovers distributional syntactic and latent semantic (representation learning) from contextual clinical narrative inputs and, then, learns the knowledge representation for labeling in the contextual output (supervised classification). First, for having an effective representation learning approach with a small data set, mixing of numeric values and texts. Four different methods are applied to capture the numerical vital sign values. Then, different representation learning approaches are using to discover the rich structure from clinical narrative data. Second, for an automatic encounter with disease prediction, in this case, cardiac failure. The binary classifiers are iteratively trained to learn the knowledge representation of processed data in the preceding steps. The multilayer perceptron neural network outperforms other discriminative and generative classifiers. Consequently, the proposed framework yields an overall classification performance with accuracy, recall, and precision of 89% and 88%, 89%, respectively. Furthermore, a generative autoencoder (AE) learning algorithm is then proposed to leverage the sparsity reduction. Affirmatively, the AE algorithm is overperforming other sparsity reduction techniques. And, the classifier performances can successfully achieve up to 91%, 91%, and 91%, respectively, for accuracy, recall, and precision.

*Index Terms*—clinical NLP, cardiac failure, machine learning, feature selection.

### I. INTRODUCTION

**C**URRENTLY, an abundance of data is available in the clinical domain. Taking advantage of this opportunity, clinicians have successfully combined the informative and structured data, which includes laboratory test results and medical imaging [1]. However, clinical narrative sources are

Partial content has been submitted in: T. D. Le, R. Noumeir, J. Rambaud, G. Sans, and P. Jouvet, "Machine Learning Based on Natural Language Processing to Detect Cardiac Failure in Clinical Narratives," 2021 IEEE 34<sup>th</sup> International Symposium on Computer-Based Medical Systems (CBMS).

Thanh-Dung Le is with the Biomedical Information Processing Lab, École de Technologie Supérieure, University of Québec, Montréal, Québec, Canada, and also with with the CHU Sainte-Justine Research Center, CHU Sainte-Justine Hospital, University of Montreal, Montréal, Québec, Canada (Email: thanh-dung.le.1@ens.etsmtl.ca).

Rita Noumeir is with the Biomedical Information Processing Lab, École de Technologie Supérieure, University of Québec, Montréal, Québec, Canada.

Jérôme Rambaud, Guillaume Sans, and Philippe Jouvet are with the CHU Sainte-Justine Research Center, CHU Sainte-Justine Hospital, University of Montreal, Montréal, Québec, Canada. imposed considerable constraints, which are short notes on patients written initially by physicians. Although the notes are continuously provided and stored in electronic medical records (EMR), they are underutilized in clinical decision support systems. The limitation comes from their unstructured or semistructured format [2].

1

Since 2013, the Pediatric Critical Care Unit at CHU Sainte-Justine (CHUSJ) has used an EMR. The patients' information, including vital signs, laboratory results, ventilator parameters, is updated every 5 minutes to 1 hour according to the variable sources [3]. Mostly, a significant data source of French clinical notes is currently stored. There are 7 caregiver notes/patient/day from 1386 patients (containing a dataset of more than  $2.5 \times 10^7$  words). These notes are scribed extensively from admission notes and evaluation notes. Admission notes outline reasons for admission to intensive care units, historical progress of the disease, medication, surgery, and the patient's baseline status. Daily ailments and test results are described in evaluation notes, from which patient condition is evaluated and diagnosed later by doctors. However, these information sources are being used as clinical documentation for reporting and billing instead of clinical knowledge for predicting disease conditions or for decision support.

## A. Problem Statement

One of the targets of the clinical decision support system in CHUSJ is to early diagnose acute respiratory distress syndromes (ARDS). Theoretically, it endeavors to improve the respiratory disease diagnosis for children by detecting the absence of "cardiac failure" as suggested by a board of experts in pediatric acute lung injury in [4]. Therefore, in such standard criteria for age, timing, the origin of edema, and chest imaging with an acute deterioration in oxygenation can be well explained by underlying cardiac disease. Then, correctly identifying cardiac failure is vital in the diagnosis and treating ARDS. This linked syndrome is diagnosed using many clinical information and exams, including laboratory tests or echocardiography tests. However, the patient cardiac condition can be virtually found based on the stored clinical notes that synthesized all this information.

Generally, there is a list of golden indicators to classify the patient with cardiac failure. Those indicators could be either from the medical history, clinical exam, chest X-Ray interpretation, recent cardiovascular performance evaluation, or laboratory test results. Medication, such as Levosimendan, Milrinone, Dobutamine, is a surrogate to the gold standard.

This work was supported in part by the Natural Sciences and Engineering Research Council (NSERC), in part by the Institut de Valorisation des données de l'Université de Montréal (IVADO), in part by the Fonds de la recherche en sante du Quebec (FRQS), and in part by the Fonds de recherche du Québec – Nature et technologies (FRQNT).

Label	
	Cardiac failure
[Attributes	
1) Adm	ission notes:
a)	Medical history: Levosimendan, Milrionone or Dobutamine.
b)	<b>History of diagnosed terms</b> : cardiomyopathie dilatee, choc cardiogenique, defaillance cardiaque gauche aigue, defaillance cardiaque gauche chronique, defaillance cardiaque post-operatorie (LCOS), surcharge liquidienne (hypervolemie), myocardite.
2) Eval	uation notes:
a) b)	<b>Evolution par systeme</b> (Cardiovascular): FE (ejection fraction $< 50\%$ ) and/or FR (shortening ratio $< 25\%$ ). <b>Laboratory test result</b> : pro-BNP ng/L (> 1000)

Its list can be retrieved from syringe pump data, prescriptions, and notes. If any medication from the three is present, there is certainly a cardiac failure. Besides, cardiovascular performance evaluation also highly contributes to indicate the cardiac failure diagnosis. One of the evaluations is ejection fraction (FE) < 50%. EF refers to the percentage of blood pumped (or ejected) out of the ventricles with each contraction. It is a surrogate for left ventricular global systolic function, defined as the left ventricular stroke volume divided by the end-diastolic volume. The other indicator for cardiovascular performance evaluation is shortening fraction (FR) < 25%. FR is the length of the left ventricle during diastole and systole. It measures diastolic/systolic changes for inter-ventricular septal dimensions and posterior wall dimensions. Finally, brain natriuretic peptide, known as pro-BNP ng/L > 1000, comes from laboratory test results being useful in the acute settings for differentiation of cardiac failure from pulmonary causes of respiratory distress. Pro-BNP is continually produced in small quantities in the heart and released in more substantial quantities when the heart needs to work harder.

Consequently, the clinical knowledge representation summarizes detail attributes, which are the main essential contribution to detect cardiac failure, shown in Table I. All notes are taken into account if they are encompassed by the information of the prescription history of Milrinone (mcg/kg/min), measurement notes of pro-BNP (ng/L), dilated cardiomyopathy, acute left cardiac failure, chronic cardiac failure, postoperative cardiac failure, coronary microvascular disorder history notes, notes of a measurement result of either FE-ejection fraction(%) or FR-shortening fraction (%). As a result, a patient is considered to have a cardiac failure if he/she has one of the criteria. Unfortunately, as all the mentioned information above that helps diagnose cardiac failure is not readily available electronically, we will develop a machine learning algorithm based on natural language processing (NLP) that automatically detects this desired concept label from clinical notes. Specifically, the algorithm can automatically see whether a patient has a cardiac failure or a healthy condition lacking gold indicators from the notes. Technically, in such a situation, the proposed algorithm can effectively learn a latent representation of clinical notes, which cannot be depicted by traditionally rule-based approaches.

# B. Related Works

Within a decade, there is a 9 times increase in EMR system adoption in hospitals in 2018 compared to 2008 [5]. Because of increasing EMR, the stored data in EMR also proportionally increased, however, not all data is directly used to analyze health management improvement. The data must be preprocessed before use, and there are different preprocessing methods in conjunction with varying limitations for various data types. For example, clinical notes have a lack of standardization [6]. Therefore, it increases the complexity of the knowledge extraction from clinical text data. That is why there is limited clinical text adoption in real practice, although clinical notes are holding a developing position in clinical research priority.

Fortunately, there has been a outstanding achievement of machine learning-based NLP for clinical text knowledge extraction [7], [8]. However, significant concerns are remaining in the trajectory of clinical NLP deployment. First, one limitation is how to learn the semantic and syntactic structure of feature extraction for clinical texts. The information combination (semantic and syntactic structure) will lead to conflation deficiency when a word level is tightened to the semantic and syntactic level. Especially in cases of the clinical notes in language other than English, the challenge is more difficult to combat [9]. Hence, the target is cognizance enrichment during the combination process instead of losing crucial information. Second, supervised learning algorithms for classification have reached their highest potentiation because they only learn the discrepancy between instances from actual data distribution and synthesized instances generated by the learning rules. However, the underlying probability distribution of clinical text is not known; thus, the solution to the classification is deficient [10].

Currently, all the state-of-the-art for machine learning-based NLP are focusing on deep learning for clinical notes to solve the two limitations above [11], [12]. For example, to predict the cardiac failure, deep learning (Convolution Neural Network-based) shows its exceptional performance, F1 score of 0.756, to the conventional approach (Random Forest) with F1 score of 0.674 [13]. And, study [14] shows the best performance to predict multiple chronic diseases (cerebral infraction, pulmonary infection and coronary atherosclerotic heart disease) by the combination of word2vec and deep learning with the average accuracy and F1 score exceeded



Fig. 1: The two objectives to learn clinical notes for detecting the desirable label.

90%. However, deep learning architectures generally work well for large scale data sets with short texts, while do not outperform conventional approaches (BoW) on smaller corpus with long texts in clinical note corpus [15]. In addition, automatic methods to extract New York heart association classification from clinical notes [16] confirm that machine-learning method, support vector machine with n-gram features, achieve the best performance at 93% F-measure. Also, study [17] proved the extraordinary achievement by the combination of BoW and Naive Bayes classifier on clinical notes classification for acessing hospital readmission offering an area under the curve (AUC) of 0.690. This study again confirms that with the small dataset TF-IDF and BoW have better performance than other techniques on coronary microvascular dysfunction classification [18].

To sum up, a large enough amount of data is needed to have a good generalization capability of deep learning, while this data availability requirement is not always provided [19]. Even, this study propose an alternative approach to deal with both large and small amount of dataset [20]. However, the limitations from these studies include: (i) the authors either remove all of the vital sign numeric values or they did not mention how to deal with numeric values and (ii) they ignore the sparsity from the learning representation feature space, although some studies extensively perform various features selections.

## II. MOTIVATION AND CONTRIBUTIONS

# A. Motivation

As proven in the recent study [21], the feasibility of employing machine learning for cardiac failure was extensively analyzed and confirmed. However, in our case, we are dealing with two challenges from clinical notes in French, and a limited amount of dataset size. Fig. 1. shows the main objective consisting of two sub-objectives which aim to overcome the mentioned limitations, as follows:

• Which representation learning approach should be used? The representation learning approach, which can retain the words' semantic and syntactic analysis in critical



Fig. 2: An overview of the proposed methodology to detect cardiac failure from clinical notes at CHUSJ.

care data, enriches the mutual information for the word representation by capturing word to word correlation not only from statistically but also semantically distributional learning of word appearance.

• Which machine learning classifier should be employed? The machine classifier, which can influentially avoid the overfitting associated with machine learning rule by marginalizing over the model parameters instead of making point estimates of its values, would be assuredly accomplished to draw a high classification accuracy, recall, and precision for the desired labeling concept.

# B. Methodology

The methodology consists in empirical experiments of a learning algorithm to learn the hidden interpretation and presentation of the French clinical note data. Technically, an optimal learning algorithm will be achieved by minimizing the empirical loss during the learning process of supervised learning. Generally, a detection algorithm based on supervised learning follows the same steps, including data collection, data pre-processing, feature extraction, classification, and prediction. Nevertheless, the performance of the detection techniques strongly depends on the details of each step above. As shown in Fig. 2, it is divided into four steps as follows:

- Categories of clinical notes, including admission and evaluation notes from CHUSJ databases are collected in the data integration process.
- 2) Data pre-processing is performed to pre-process raw text data. Notably, the information of the data is tightened by applying lowercase conversion, stop words removal and tokenization.
- 3) Representation learning model is built-in feature extraction. The model is trained to compress a text sequence into a low-dimensional vector space, learn the word representation, and integrate relation from lexical resources into the learning process.
- 4) Machine learning classifier is iteratively trained to learn the knowledge representation of processed data in preceding steps. Consequently, the final result must obtain high accuracy in cardiac failure prediction.

## C. Contributions

The main contributions of this work are as follows.

- We formulate automatic label detection as a joint representation learning and binary classification problem. The new formulation avoids the shortcomings of the common classification scheme while improving modelling performance. Usually, other studies are immediately applying different learning representation with machine learning classifiers without any analysis and comparison. This study shows a conceptual framework from the input contextual to the output contextual downstream.
- 2) Four different experiments of numeric values decoding are proposed for the clinical note preprocessing, instead of losing crucial information from the vital numeric values by removing them, then, we can find the best way to treat numeric values.
- 3) we present and employ a simple and efficient TF-IDF with a MLP-NN to conduct joint representation learning and classification. To that end, with the limited amount of data, a TF-IDF and MLP-NN have provided the best performance for solving the joint problem with an overall performance.
- We further propose a generative learning approach, namely an autoencoder, to leverage the sparsity reduction in the proposed framework.

Section III will discuss the data preparation including data collection, data pre-processing from CHUSJ. Then, to solve the first sub-objective, section IV will explore the possibilities of various clinical note representation learning employing different techniques. From then, we will continue to solve the second sub-objectives, section V will show the results from different machine learning classifier performance for

	notes	label	len_notes
2884	1- Urgence de trois-rivière : \t- arrivée lét	yes	3473
414	* grossesse : G1 P1 Mère sans ATCD ou médicati	yes	3414
781	Enfant né le 27-06-2018 DAN hypoVG, atrésie Ao	yes	3402
1559	<ul> <li>\tCardiomyopathie restrictive en insuffisanc</li> </ul>	yes	3380
754	Ex 35 sem PN =3.1kg Cardiopathie complexe type	yes	3347
690	Admis au SIP le 06/03/2017 pour défaillance ca	yes	3289
395	Nce à terme (39 +1) - AVB avec brady per partu	yes	3280
2679	Patiente de Kujjuaq. S'est présenté dispensair	no	3204
3239	Était auprès d'un feu à l'extérieur en famille	yes	3167
207	Cardiopathie complexe avec physiologie univent	no	3153

Fig. 3: An examples of clinical notes from CHUSJ sorted by the longest length (number of characters).

the binary classifier. The results and discussion then will be discussed in section VI. In addition, another improvement for the classifier performance is also illustrated with the employing of autoencoder to reduce the sparsity from the first sub-objective output in section VII. Finally, section VIII provides concluding remarks.

## III. CLINICAL NARRATIVE DATA AT CHUSJ

# A. Data Collection

The data integration process has been successfully completed at the Pediatric Intensive Care Unit, CHUSJ, for more than 1300 patients. We only took information from two types of notes, including admission and evaluation notes. Primarily, we focused on medical background, history of the disease to admission, and cardiovascular evaluation. Furthermore, we only used notes for each patient's first stay within the first 24h since the admission. If a patient had more than one ICU stay, we only analyzed the first one. Two doctors from the CHUSJ (Dr. Jérôme Rambaud and Dr. Guillaume Sans) separately reviewed each patient's notes; then, each note was manually labeled "YES" or "NO" for positively cardiac failure or under a healthy condition, respectively. Finally, to avoid data contamination, we checked both the "patientID" and "careproviderID" to ensure that there were not any notes being present in the training cohort and the testing cohort at the same time.

Totally, we have 5444 single line of notes with 1941 positive cases (35.65% of total) and 3503 negative cases. Fig. 3 shows an example of clinical notes with labels, which are sorted as the top 10 longest length in total number of characters. Besides, average length of number of characters is 601, and 704 for the positive cases, and negative case, respectively. And, average length of number of digits is 25 and 26 for the positive cases, and negative case, and negative case, and negative cases, negative cases, and negative cases, negative cases,

# B. Data Pre-Processing

Generally, it is proven that if the preprocessing steps are well done, the result for the end-task will be improved [22]. Therefore, there are steps that were used as case lowering, and stop words removing. Fig. 4 shows the statistics for the

Positive freq Negative freq pos\_precision pos\_freq\_pct pos\_hmean

term					
de	11460	13500	0.459135	0.043645	0.079712
et	5180	5519	0.484157	0.019728	0.037911
à	4437	6803	0.394751	0.016898	0.032409
avec	3818	4680	0.449282	0.014541	0.028169
pas	3449	5335	0.392646	0.013135	0.025420
d	3381	4191	0.446513	0.012876	0.025031
en	2957	3250	0.476398	0.011262	0.022003
la	2577	3404	0.430864	0.009814	0.019191
1	2425	3655	0.398849	0.009235	0.018053
0	2343	1055	0.689523	0.008923	0.017618

Fig. 4: Clinical notes analyzing for stop words removing.

list of top words removed. From the list, all these words are the definition in French, therefore, they do not contribute to the learning representation. Besides, all the notes are short narratives and the n-gram length distribution is shown in Fig. 5, the longest n-gram is over 400 words, but most of the ngram length distribution is between 50 and 125 words. Then, the ratio of the number of samples/number of words per sample is much smaller than 1500, as given by a tutorial for small text classification from [23].

In addition, in medical expression, it is very important to pay attention to negation. First, the negation criteria from study [24] was used for detecting the negative meaning from French notes. Then, a negation technique is applied [25]: a term "neg\_" will is added as a prefix for a term. For example, a original notes as "Patiente *ne suivi pas* pour une cmd en attente d'une greffe cardiaque. Respiration plus rapide, mais état général préservé, parents *n'étaient pas* inquiets." will be tagged with a negation transform as: "Patiente *neg\_suivi* pour une CMD en attente d'une greffe cardiaque. Respiration plus rapide, mais état général préservé, parents *neg\_étaient* inquiets."

For the vital numeric values (heart rate, blood pressure, etc...) cannot the representation learning accommodate the numeric values effectively. Actually, most NLP models treat numeric values in text in the same way as other tokens, and it has proven that the pretrained token representations (word2vec) can naturally encode the numeric values [26]. Unfortunately, it is required a large amount of data with specific labelling progress for this tasks, while the numerical reasoning results are less better (47%) compared with the expert human performance (96.4%) for F1 score metric [27]. There is an study which only focus how to extract the number not dealing with representation learning [28]. In our case, because we have a limited data, we decide to keep all numeric value for vital sign values (nearly 4% of the notes), and to apply the decoding for those number values. We manually performed four experiment to see the contribution from the numeric value into the feature space and the classifiers. Table II summarizes the four different approaches to decode the numeric values including (i) keeping all of the original numeric values and their units, (ii) removing all of the numeric values



Fig. 5: The distribution of length of notes in CHUSJ dataset.

and their units, (iii) encoding the decimal into a string named dot, and (iv) decomposing into digits. Finally, we tokenized the narratives into a vector of tokens.

For the note visualization, we apply the ScatterText [29]. Totally, we have more than 580000 (n-grams) word count from the data shown in Fig. 6. The figure shows the most frequent words for the positive case in the upper right corner; the most frequent words for the negative cases in the lower left corner; and, all less frequent words for both cases are in the center. Besides, the top 20 words from the the positive cases and negative cases are presented in the right hand side. Their frequency distribution are also illustrated in Fig. 7 and Fig. 8, respectively. In cases of positive, we easily see that, most these terms following positively related to the cardidac malfuction: milrinone (milri), aorte, aortique, and valve. In contrast, such terms: urgence, ad, respiratorie, vers, toux, ivrs are relatively contributed to the respiratory syndromes.

There are also medical terms, whose descriptions and characteristics are summerized in Table III, and they are compatible with the clinical diagnosis mentioned from Table I. For example, there are CIV (Communication intraventriculaire), CEC (Circulation extra-corporelle), CIA (Communication intra-auriculaire) and FC (fréquence cardiaque), and IVRS (Infection des voies respiratoires supérieures).

# IV. CLINICAL NATURAL LANGUAGE REPRESENTATION LEARNING

There is no doubt about the effectiveness of neural word embedding. In this study [14], the author confirm that word2vec representation for various disease classification from medical notes. Especially for the French clincal notes, the study [30] show that word2vec and GloVec were effective on embedding the clinical notes. And, the word2vec had the highest score on 3 out of 4 rated tasks (analogy-based operations, odd one similarity, and human validation), particularly regarding the skipgram architecture. In addition, as mentioned before from the studies [15]–[18] confirm that conventional approaches (BoW, TF-IDF) are better performance than other deep learning







Positive document count: 2,830; word count: 277,563 Negative document count: 2,923; word count: 310,617

Fig. 6: Clinical note illustration.

FABLE III: Important Ab	breviations for 1	Medical Terms
-------------------------	-------------------	---------------

Abbreviations	Descriptions	Characteristics
CIV	Communication intraventriculaire	Cardiac malformation
CEC	Circulation extracorporelle	Treatment for cardiac failure
CIA	Communication intraauriculaire	Cardiac malformation
FC	Fréquence cardiaque	Cardiac frequency
IVRS	Infection des voies respiratoires supérieures	Virus responsible for respiratory distress
SOP	Salle d'opération	Operations
PO	Per os (by mouth)	Feeding

techniques on smaller corpus with long texts in clinical note corpus. Therefore, this study we will evaluate the effectiveness of two conventional representation approaches including BoW, TF-IDF and the word2vec neural word embedding model.

## A. Bag-of-Words

A bag-of-words model [31], or BoW for short, is a representation of text that describes the occurrence of words within a document. Technically, if documents have similar content, they will be similar. It extracts features from the text by considering each word count as a feature from a vocabulary of known words. There is a theoretical analysis for understanding the BoW model [32], it prove that the success of BoW representation is not by using a heuristic clustering process but by are generated by a statistical process and based on statistical consistency. However, in the BoW representation, any two different words drawn from the vocabulary are treated equal if they are assigned with the same topic; in reality, it is neglecting much correlation information among words. Then, there are many variants to improve the limitation of BoW models such as: collects high-level structural and semantic meaning of the words by a network-based bag-of-words model to reflect the relationship between nodes [33], construct more predictive representation for each document by deliberating the



Fig. 7: Frequency distribution of n-grams for positive cases (Top 20 n-grams).



Fig. 8: Frequency distribution of n-grams for negative cases (Top 20 n-grams).

identification of the objectively or subjectively discriminative power of the words [34].

# B. TF-IDF

The TF-IDF, first introduced in [35], stands for term frequency (TF) × inverse document frequency (IDF). TF-IDF weighting is commonly used in information retrieval for text mining. The intuition is that term importance increases with the term's frequency in the text, but the term's frequency neutralizes it in the domain of interest. Given a collection of terms  $t \in T$  that appear in a set of N documents  $d \in D$ , each of length  $n_d$ , tf-idf weighting is computed as follows:

$$tf_{t,d} = \frac{f_{t,d}}{n_d} \tag{1}$$

$$idf_t = \log \frac{N}{df_t} \tag{2}$$

$$W_{t,d} = tf_{t,d} \times idf_t \tag{3}$$

where  $f_{t,d}$  is the frequency of term t in document d, and  $df_t$  is the document frequency of term t, that is, the number

of documents in which term t appears. Several variations and adjustments were offered including normalizing  $tf_{t,d}$  and optional weighting schemes.

Actually, TF-IDF and other its variations not only focuses on the basic statistical relation of note representation. Its theoretical arguments as [36], as well as, a probabilistic theoretical are explained [37] for its heuristic. And, it is shown that if TF-IDF is treated carefully with the bias, it will manifest the best performance of TF-IDF. [38].

#### C. Neural Word Embeddings

The neural word embedding was introduced in [39], and named word2vec model. The central target word vector  $w_c$ and context word vector  $w_0$  for each word  $w_i$  are the neural word embedding parameters.

$$p(w_o \mid w_c) = \frac{\exp(u_o^\top v_c)}{\sum_{i \in V} \exp(u_i^\top v_c)}$$
(4)

where  $v_i \in R^d$  is the vector of the word  $w_i$  when it is the central target word, and  $u_i \in R^d$  is the vector of the word  $w_i$  when it is a context word.

The key to the success of word2vec is that it can compute the logarithmic conditional probability for the central word vector and the context word vector. Consequently, its computation obtains the conditional likelihood for all the words in the dictionary given the central target word  $w_c$ , and trained by a neural network.

$$\log p(w_o \mid w_c) = u_o^\top v_c - \log \left( \sum_{i \in V} \exp(u_i^\top v_c) \right)$$
(5)

where  $V = \{0, 1, ..., |V| - 1\}$  is the vocabulary index. After the training, for any word in the dictionary with index  $w_i$ , we are going to get its two word vector sets  $v_i$  and  $u_i$ . In applications of natural language processing, the central target word vector in the skip-gram model is generally used as the representation vector of a word.

In this study, we adapted the instruction of how to generate a good neural word embeddings [40]. Especially, the three critical components in training word embeddings including the model, corpus, and training parameters are well customized. In addition, hyper-parameter choices are very important in neural word embedding systems; therefore, we also controlled the effects of data size and frequency range on distributional semantic models based on the recommendations from [41].

## V. MACHINE LEARNING CLASSIFIERS

Deep learning has proven its superiority to representation learning and classification problems from various data structured such as medical imgaing, time seris data, clinical natural language [42]. Unfortunately, not all cases can apply the deep learning, especially, with the limited amount of data.

Fortunately, when the ratio value for the number of samples/number of words per sample is small (< 1500), a small MLP-NN that take n-grams as input perform better or at least as well as deep learning-based sequence models [23]. Besides, a MLP-NN is simple to define and understand, and it take much less compute time than sequence models. There is a detail explanation of using a MLP-NN in medical analysis for small dataset [43].

Furthermore, study [44] observed in particularly small datasets with discriminative and generative learning approach. And, it confirms that the discriminative logistic regression algorithm has a lower asymptotic error, while the generative Naive Bayes classifier converges more quickly. Therefore, in this study, we decide to go with three different machine learning classifiers logistic regression, Gaussian Naive Bayes, and MLP-NN.

Here we consider a binary classification problem. Given n training samples  $D = (x_1, y_1)..., (x_n, y_n)$  where  $x_i \in \mathbb{R}^p$  is a p-dimensional column vector and label  $y_i \in \{0, 1\}$ .

### A. Logistic Regression (LR)

LR uses a logistic function to model the probability of a binary dependent variable (particular class or event existing) such as unhealthy/healthy. Therefore, it is widely used in most medical fields [45]. We first write the logistic function as follows:

$$p(x;w) = p(y=1 \mid x;w) = \frac{1}{1 + \exp(-w^T x)}$$
(6)

where w is the weight vector of coefficients, and p() is a sigmoid function. Here we assume that the n training examples are generated independently. We thus can obtain the following log-likelihood.

$$\ell(w) = \sum_{i=1}^{n} \log p(y_i \mid x_i; w) = \sum_{i=1}^{n} \{ y_i w^T x_i - \log (1 + \exp (w^T x_i)) \}$$
(7)

#### B. Gaussian Naive Bayes (GaussianNB)

GaussianNB algorithm for classification is a set of supervised learning algorithms based on applying Bayes' theorem with the "naive" assumption of conditional independence between every pair of features given the value of the class variable. Bayes' theorem states the following relationship, given class variable Y and dependent feature vector  $x_1$  through  $x_n$ :

$$p(y \mid x_1, \dots, x_n) = \frac{p(y)p(x_1, \dots, x_n \mid y)}{p(x_1, \dots, x_n)}$$
(8)

Using the naive conditional independence assumption that

$$p(x_i|y, x_1, \dots, x_{i-1}, x_{i+1}, \dots, x_n) = p(x_i|y),$$
 (9)

for all i, this relationship is simplified to

$$p(y \mid x_1, \dots, x_n) = \frac{p(y) \prod_{i=1}^n p(x_i \mid y)}{p(x_1, \dots, x_n)}$$
(10)

Since  $p(x_1, \ldots, x_n)$  is constant given the input, we can use the following classification rule:  $P(y \mid x_1, \ldots, x_n) \propto p(y) \prod_{i=1}^n p(x_i \mid y)$ . Then

$$\hat{y} = \arg\max_{y} p(y) \prod_{i=1}^{n} P(x_i \mid y)$$
(11)

and we can use the maximum a posteriori estimation to estimate p(y) and  $p(x_i | y)$ ; the former is then the relative frequency of class y in the training set. However, the difference between GaussianNB and naive Bayes classifiers is mainly based on the distribution of  $p(x_i | y)$ . The likelihood of the features is assumed to be Gaussian with mean  $\mu$  and variance  $\sigma^2$  for GaussianNB [46]:

$$p(x_i \mid y) = \frac{1}{\sqrt{2\pi\sigma_y^2}} \exp\left(-\frac{(x_i - \mu_y)^2}{2\sigma_y^2}\right)$$
(12)



Fig. 9: An mathematical model for a biologically inspired neural network [47].

## C. Multilayer Perceptron Neural Network (MLP-NN)

The earliest work in the field of "neural network" is founded and attempted to understand, model and emulate neurological function and learning in brains [48]. Since then, a commonly used neural network is the MLP-NN. In an MLP-NN, the neurons are structured into layers, consisting of at least three layers, namely the input layer, hidden layer or layers, and an output layer [49]. Typical MLP-NN networks are feedforward neural networks where the computation is carried out in a single direction from input to output.

As shown in Fig. 9,  $x_i$  is the  $i^{th}$  input (axon from a neuron) to an input neuron, and a weight  $w_i$  is the effect of the  $i^{th}$  synapse on neural network. Then, the total effect of the input on the synapse from the cell body is:

$$\sum_{i}^{n} w_i x_i + b \tag{13}$$

Following this affine transformation of the weighted sum of its input, a nonlinear activation function  $f(\cdot)$  is defined for the cell output. In general, this nonlinear activation function  $f(\cdot)$ enables the MLP-NN to learn and solve nonlinear problems. It is proven that ReLU activation in combination with stochastic gradient descent optimization algorithm shows a better convergence and gives a better optimization in small MLP-NN [50]. Therefore, we apply the ReLU activation for the hidden layer as shown below:

$$f(\cdot) = ReLU(\alpha) = \max(\alpha, 0) \tag{14}$$

Besides, based on the analysis for the selection of proper neural network sizes and architectures [51], the structure of an MLP-NN is used in this study with L = 3 layers where layer 1 is the input layer, layer 3 is the output layer, and layer 2 is the hidden layer. The total number of neuron in the hidden layer is  $N_t = 100$  neurons. In addition, we also applied dropout [52] (p=0.25) and GlorotNormal kernel initializer [53] to prevent neural networks from overfitting.

# VI. EXPERIMENTAL RESULTS AND DISCUSSIONS

To implement, we used the scikit-learn library [54] and Keras [55] in Python. The data was divided into 70% training and 30% testing. To make our results more consistent, we used the k-fold cross validation (k = 5) [56]; each dataset was divided into k subsets called folds, the model was trained on k - 1 of them and tested on the last left out. This process was repeated k times and the results were averaged to get the final results. Furthermore, we also employed the univariate feature selection with sparse data from the learning representation feature space. This selection process works by selecting the best features based on univariate statistical tests named SelectKBest algorithms, which removes all but the K highest scoring features.

To deal with the imbalance, we apply the balance technique Bayes Imbalance Impact Index  $(BI^3)$  for the classifiers [57]. We decide to do that because we do not support the sampling data as well as data augmentation. An extensive evaluation of different sampling techniques and neural network architectures recently confirm that the effect of sampling methods and the architecture of the neural network on the results strongly depend on the dataset, and the results become less consistent [58]. Consequently, there are two reasons that encouraging we are not interested in sampling approaches (i) there are presence of characteristics in our clinical notes data, namely small training example size, large number of features, and correlations between features. And, it is concluded that there is no clear winner between oversampling and undersampling to compensate for the class imbalance, if we do not carefully take into account factors such as class distribution, class prevalence and features correlations in medical decision making [59]; (ii) it has been focused only on the imbalance ratio when dealing with imbalance problems, but ignored the lack of information for the minority class, overlap, and disjuncts. In addition, the lack of representation, which cannot be learned because of not present in the training, is also suffered from the imbalance [60]. And, the  $BI^3$  was proposed to overcome those challenges in the imbalance. In summary, the  $BI^3$  for the whole data set  $\mathcal{D}$  is calculated by averaging over all Individual Bayes Imbalance Impact Index  $IBI^3$  on the minority class.

$$BI^{3}(\mathcal{D}) = \frac{1}{N_{p}} \sum_{(x_{i}, y_{i}) \in \mathcal{D}, y_{i} = +1} IBI^{3}(x_{i})$$
(15)

 $N_p$  is the numbers of samples in the positive class, and the  $IBI^3$  is the difference between the normalized posterior probabilities of the imbalance case and the estimated balanced case.

$$IBI^{3} = \frac{f'_{p}(x)}{f_{n}(x) + f'_{p}(x)} - \frac{f_{p}(x)}{f_{n}(x) + f_{p}(x)}$$
(16)

 $f_p(x)$  and  $f_n(x)$  are the posterior scores for positive class and negative class, respectively. And,  $f'_p(x)$  is proportional to the minority class posterior probability under the estimated balance case. If  $IBI^3$  is small, the influence of the imbalance on x is irrelevant. Therefore, it can measure how much a single minority class sample is influenced by the imbalance.

To effectively assess the performance of our method, some metrics including accuracy, precision, recall (or sensitivity), and F1 score were used [61]. These metrics are defined as follows:

Accuracy (acc) = 
$$\frac{TP + TN}{TP + TN + FP + FN}$$
  
Precision (pre) =  $\frac{TP}{TP + FP}$   
Recall/Sensitivity (rec) =  $\frac{TP}{TP + FN}$   
F1-Score (f1) =  $\frac{2^*Precision^*Recall}{Precision + Recall}$ 

where TN and TP stands for true negative and true positive, and they are the number of negative and positive patients that are classified correctly. Whereas FP and FN represents false positive and false negative and they represent the number of positive and negative patients that was wrongly predicted.

Table IV presents the results of our method. First, among four experiments for dealing with numeric values, the experiment 3 yields better performance than others. By encoding the decimal point into a string "DOT", it has helped the learning representation process retain the information from numeric values from clinical notes. It is also interesting to mention that in cases of keep all numeric values and do nothing (experiment 1), the results is worse than we remove all the numbers and their units (experiment 2). Experiment 4 confirms that if the numbers are extensively encoded, it will have the opposite effect of the result, which lowers the performance. In short, from these observations, our findings again confirms that the value of conducting human centered evaluative research might impact the prospective evaluations of model accuracy, as recently reported in a clinical experiment study [62].

The combination of TF-IDF and MLP-NN always outperforms other combinations with all overall performance, and are the most stable in all circumstances. In the case without any feature selection, the proposed framework yielded an overall classification performance with acc, pre, rec, and f1 of 85% and 84%, 85%, and 84%, respectively. Also, the representation matrix from the TF-IDF above is sparse because every word is treated separately. Hence, the semantic relationship between separated entity is ignored, which would cause information loss. Therefore, if the feature selection (SelectKBest) was well applied and tuned, it could accomplish the improvement up to 3-4% for each evaluation in the overall performance. Consequently, it achieves the best performance with 89%, 89%, 88%, 88% for acc, pre, rec, and f1, respectively.

Furthermore, with the limited amount of data, the BoW and TF-IDF have proven their capacity to better retain for the information retrieval in clinical note representation. Especially, the TF-IDF could exhibit a better performance when used on short narratives (approximately 80 words per each example in our case). While the neural word embeddings also showed their potentiality to deal with learning representation for clinical notes. Although the difference between these performances was not significant, it may be more effective when the corpus size is scale-up. When the data is small, neural networkbased models can underperform, but they are more reliable in cases of increasing sizes and frequency ranges as proved by [63]. Meanwhile, it is required that the corpus must correctly represents the use of specific words in domain-specific when increasing the corpus size [64].

Besides, with the same learning presentation approach (BoW, TF-IDF, or neural word embeddings), the LR classifiers had better performance than GaussianNB classifiers. The results align with the theoretical and experimental analysis from [44], [65], LR performs better with smaller data size because it effectively approaches its lower asymptotic error from the initial learning steps. However, MLP-NN models always dominated with their best generalization. They have achieved their capacity of generalization because the misclassification probability can be reduced and can be trained closer to optimal points which cannot be trained with simple algorithms [66].

We also tested with the model CamemBERT, which is specifically a transformer-based language models for French languages [67]. It is motivated by the success of a Bidirectional Encoder Representations from Transformers (BERT) for natural language understanding [68]. Unfortunately, the result was not as good as expected, where we could only achieved the accuracy less than 60%. Even though, we applied the drop-out technique as recommended from the study [69]. We continued investigating with the simpler Transformer, which solely based on attention mechanisms through the connection of the encoder and decoder [70], and implemented by Keras block from [71]. The result has achieved a decent performance in comparison with advanced and complicated BERT-based models. However, it is still far below the performance from the simple MLP-NN, when the highest precision and recall are continually fluctuating at around 80% as shown in Fig. 10, and 11, respectively. It is again confirm the limitation of transformer for clinical natural language processing classification task. One of the limitation is correctly identifying labels in clinical text depend more on identifying a few key words or phrases rather than understanding the contextual meaning of sequences of text as given in [72].



Fig. 10: Precision performance based on the Transformer configuration.

# VII. AUTOENCODER LEARNING ALGORITHM FOR SPARSITY REDUCTION

In numerical analysis, a sparse matrix or sparse array is a matrix in which most of the elements are zero [73]. The number of zero-valued elements divided by the total number of elements (e.g.,  $m \times n$  for an  $m \times n$  matrix) is called the

Representation		мі	Exp_1			Exp_2				Exp_3				Exp_4				
		NIL NIL	acc	pre	rec	f1	acc	pre	rec	f1	acc	pre	rec	f1	acc	pre	rec	f1
election	BoW	LR	0.80	0.77	0.81	0.79	0.81	0.80	0.82	0.81	0.82	0.80	0.83	0.81	0.82	0.80	0.81	0.8
		GaussianNB	0.77	0.72	0.80	0.76	0.78	0.76	0.81	0.78	0.79	0.78	0.81	0.79	0.79	0.76	0.80	0.78
		MLP-NN	0.81	0.78	0.81	0.79	0.81	0.80	0.82	0.81	0.81	0.81	0.84	0.82	0.81	0.81	0.82	0.81
Ň		LR	0.81	0.79	0.82	0.8	0.78	0.76	0.79	0.77	0.81	0.78	0.81	0.79	0.77	0.75	0.77	0.76
W/o Feature	TF-IDF	GaussianNB	0.79	0.75	0.81	0.78	0.77	0.74	0.80	0.77	0.78	0.75	0.81	0.78	0.76	0.74	0.80	0.77
		MLP-NN	0.81	0.80	0.82	0.81	0.84	0.82	0.85	0.83	0.85	0.84	0.85	0.84	0.82	0.81	0.81	0.81
	Embedding	LR	0.74	0.72	0.79	0.75	0.76	0.74	0.79	0.76	0.78	0.75	0.82	0.78	0.76	0.73	0.77	0.75
		GaussianNB	0.72	0.71	0.77	0.74	0.76	0.71	0.79	0.75	0.76	0.73	0.80	0.76	0.75	0.72	0.72	0.72
		MLP-NN	0.74	0.74	0.76	0.75	0.77	0.76	0.78	0.77	0.79	0.77	0.80	0.78	0.77	0.73	0.78	0.75
W/ Feature Selection	BoW	LR	0.80	0.81	0.78	0.79	0.81	0.81	0.79	0.80	0.78	0.78	0.77	0.77	0.80	0.80	0.79	0.79
		GaussianNB	0.80	0.81	0.78	0.79	0.80	0.78	0.79	0.78	0.78	0.79	0.77	0.78	0.80	0.81	0.78	0.79
		MLP-NN	0.80	0.79	0.80	0.79	0.82	0.82	0.81	0.81	0.83	0.82	0.83	0.82	0.84	0.83	0.84	0.83
		LR	0.76	0.71	0.79	0.75	0.82	0.81	0.83	0.82	0.83	0.82	0.83	0.82	0.78	0.78	0.80	0.79
	TF-IDF	GaussianNB	0.80	0.78	0.80	0.79	0.81	0.82	0.79	0.80	0.81	0.81	0.82	0.81	0.79	0.78	0.79	0.78
		MLP-NN	0.84	0.84	0.85	0.84	0.87	0.86	0.88	0.87	0.89	0.89	0.88	0.88	0.85	0.84	0.84	0.84
	Embedding	LR	0.80	0.78	0.80	0.79	0.80	0.79	0.80	0.79	0.82	0.82	0.83	0.82	0.81	0.78	0.79	0.78
		GaussianNB	0.77	0.76	0.78	0.77	0.79	0.79	0.79	0.79	0.81	0.81	0.80	0.8	0.79	0.78	0.78	0.78
		MLP-NN	0.80	0.79	0.80	0.79	0.80	0.80	0.80	0.80	0.82	0.81	0.81	0.81	0.80	0.79	0.80	0.79

TABLE IV: Summarization of experiments performance evaluation



Fig. 11: Recall performance based on the Transformer configuration.

sparsity of the matrix (which is equal to 1 minus the density of the matrix). Using those definitions, a matrix will be sparse when its sparsity is greater than 0.5.

Fortunately, with the high sparsity ratio from the representation feature space of TF-IDF, the SelectKBest shows its effectiveness to increase the performance of the classifier by reducing the sparsity, as discussed from the previous Section VI. Therefore, we continue to explore the possibilities of dealing to data sparsity. The motivation is how we can compress the sparse, high-dimensional data to lower dimensional space by reducing the dimension from the feature space of TF-IDF.

## A. Data Sparsity Challenging

To dealing with the sparsity, many researches simply focus on dimension reduction. Especially, when the training data set is small, supervised discriminative approach Principal Component Analysis (PCA) can outperform and it is also less sensitive to different training data sets. [74]. For example, study [75] proves that the PCA can increase the performance from different machine classifiers for the cardiac failure prediction. Besides, another possible way is primarily employing an unsupervised generative Latent Dirichlet allocation (LDA) used for estimating topic distribution (topics) by using observed variables (words). For example, LDA shows the effectiveness of overcoming the sparsity from feature space matrix of TF-IDF [76]. However, the feature selection LDA is not much improve with very small amount of data [18].

Then, we explored the possibility of PCA for the sparsity reduction. The training was tuned and performed, and the best performance was achieved with reduction to 2 principal dimensions. Unfortunately, the test accuracy achieved 88%, and it is lower than the the performance from SelectKBest with 89%. Furthermore, as recommendation from [77], we also tested with a statistical method Neighbourhood Components Analysis (NCA) to reduce the dimensions of the dataset. NCA has proven that it work well on a small dataset for medical domain. However, the result is only slightly better than PCA, when NCA only draws a accuracy at 89% (the same with SelecKBest). As seen in Fig. 12, 13 we easily see that the overlapping of the features, hence the classification task hardly separate the boundary for the binary classification. As consequently, either PCA or NCA cannot improve the classification accuracy. The results confirmed the limitation of these approaches by linearly approximate a feature subspace to maximize class separability.



Fig. 12: Visualization of the representation space for 2 components from Principle Component Analysis (PCA).



Fig. 13: Visualization of the representation space for 2 components from Neighborhood Component Analysis (NCA).

## B. Autoencoder Learning Algorithm

In contrast with PCA or NCA, an autoencoder (AE) was originated by [78] to solve a Nonlinear PCA in dimensional reduction, and later famously promoted by training a MLP-NN with a small central layer to reconstruct high-dimensional input vectors [79]. Technically, AE takes an input  $x \in \mathcal{R}^D$  and, first, maps it to a latent representation  $z \in \mathcal{R}^M$  via a nonlinear mapping:

$$z = g(Wx + b) \tag{17}$$

Where W is a weight matrix to be estimated during training, b is a bias vector, and g stands for a nonlinear function, such as the logistic sigmoid function or a hyperbolic tangent function. The encoded feature representation z is then used to reconstruct the input x by a reverse mapping, leading to the reconstructed input x':

$$x' = f(W'z + b') \tag{18}$$

where W' is usually constrained to be the form of  $W' = W^T$ , i.e., the same weight is used for encoding the input and decoding the latent representation. And, f is also a nonlinear function. Then, the reconstruction error is defined as the Eucliden distance between x and x' that is constrained to approximate the input data x (i.e, minimizing  $||x - x'||^2$ ). Then, the conventional AE relies on the dimension of the latent representation z being smaller than of input x (M < D) which means that it tends to learn a low-dimensional, compressed representation.

It has been proven that training a neural network-based by increasing number of hidden layers (in combination with an increased number of units per layer), the results are less consistent [58]. Therefore, in our case, we aim to use a small, and simple AE. We employ an AE with three layer (one input layer, one hidden layer, and one output layer). Especially, to reducing the parameters from the latent space of the AE, we applied the regularization technique to remove redundant parameters from study [80]. After training, we use the weight



Fig. 14: Schematic structure of an autoencoder-based for compression and prediction.



Fig. 15: Loss for training and validation for AE algorithm.

matrix from the hidden layer as a pre-train tool. This pre-train latent space representation is subsequently used by a classifier to perform the binary classification, as shown in Fig. 14. Fig. 15 shows the loss during the training and the validation process for training the AE, it shows that the loss perfectly converges.

As a result, Fig. 16 show the comparison of box plot of the 5-fold cross validation for classifiers. Instead of performing on MLP-NN, LR, and GaussianNB, we also tested with other classifier as Random Forest, Multinomial Naive Bayes, and Support Vector Machine. Again, the MLP-NN gives the best performances; LR comes right after; GaussianNB is comparatively similar performance with LR. And, all other classifiers are less effective. The best performance from MLP-NN was achieved at 91%, 91%, 91%, and 91%, respectively for acc, pre, rec, and f1. The experimental result shows that the proposed method improves the performance of the MLP-NN classifier, and is more robust as compared to other methods, and the result is similar to a recent work [81].

Further analysis, it is confirmed by [44] that as the number of training examples is increased, one would expect generative Naive Bayes-based to initially do better. However, Fig. 17 confirms that the training score and validation score of MLP-NN is better than the GaussianNB in cases of increasing the number of training examples. Especially, with the same size of dataset, the GaussianNB have reached a plateau of performance after around 2000 training examples, and the



Fig. 16: A comparison evaluation of the box plot 5-fold crossvalidation results for classifiers performance.

cross validation score cannot improve. The MLP-NN shows its potential improvement in cases of the increasing size of dataset. Its cross validation score gradually increases, and does not show any signs of achieve the maximum points. It is also one of the limitation for GaussianNB, namely linear discrimination characteristic for a real world dataset, which is explained and comments from the study [82].

# VIII. CONCLUSION

This paper has employed both learning representation and machine learning algorithms to tackle the French clinical natural language processing for detecting a cardiac failure in children at CHUSJ. This study extensively conducted and analyzed a conceptual framework from the input contextual to the output contextual downstream in detecting a patient's health condition. Our numerical results have confirmed that the feasibility of the proposed design by combining TF-IDF and MLP-NN compared to others scenario can be achieved; the proposed mechanism could also be improved with the feature selection from the learning representation vector space.

We assumed that the vital sign numeric values are not significant contribution to the classifier. Instead of losing them, we address the different decoding approaches for numeric values in our future work. By encoding the decimal point into a string "DOT", it has helped the learning representation process retain the information from numeric values from clinical notes. This basic adjustment confirms that the value of conducting human centered explanation impact the machine learning classifier model accuracy.

With MLP-NN learning algorithm, we can train closer to optimal architectures which cannot be trained with simple algorithms (LR, GaussianNB, Random Forest, Multinomial Naive Bayes, and Support Vector Machine). However, BERTbased models are known that they are not a good solution for our problems (limited data, short narratives per each sample). The final results suggest that while these Transformer-based



Fig. 17: Performance comparison between GaussianNB classifier (Top) and MLP-NN classifier (Bottom) in case of increasing the training size.

methods perform less effective than existing alternatives, further work may allow this to be used as part of an ensemble for future models.

Finally, it has been proved that the sparsity reduction for the feature space strongly affects the task-end classifier performance. Especially, it has been proven that the first stage involves training an AE to compress the feature space from TF-IDF. The second stage involves using an MLP-NN to predict the health status based on the compressed feature space. Then, this efficient model can outperform all alternative approaches. It concludes that AE can learn the best representation of the training data because of it lossless compression capacity.

#### ACKNOWLEDGMENT

The clinical data was provided by the CHU Sainte-Justine Research Center, University of Montreal. The authors thank Dr. Sally Al Omar, Dr. Michaël Sauthier, Dr. Rambaud Jérôme and Dr. Sans Guillaume for their data support of this research.

#### REFERENCES

- S. Abhyankar and et. al., "Combining structured and unstructured data to identify a cohort of icu patients who received dialysis," *Journal of the American Medical Informatics Association*, vol. 21, no. 5, pp. 801–807, 2014.
- [2] A. E. Johnson and et. al., "Machine learning and decision support in critical care," *Proceedings of the IEEE. Institute of Electrical and Electronics Engineers*, vol. 104, no. 2, p. 444, 2016.

- [3] M.-P. Matton and et. al., "Databases and computerized systems in picu: Electronic medical record in pediatric intensive care: Implementation process assessment," *Journal of pediatric intensive care*, vol. 5, no. 3, p. 129, 2016.
- [4] P. A. L. I. C. C. Group *et al.*, "Pediatric acute respiratory distress syndrome: consensus recommendations from the pediatric acute lung injury consensus conference," *Pediatric critical care medicine: a journal* of the Society of Critical Care Medicine and the World Federation of Pediatric Intensive and Critical Care Societies, vol. 16, no. 5, p. 428, 2015.
- [5] F. Jiang and et. al., "Artificial intelligence in healthcare: past, present and future," *Stroke and vascular neurology*, vol. 2, no. 4, pp. 230–243, 2017.
- [6] K. Kreimeyer and et. al., "Natural language processing systems for capturing and standardizing unstructured clinical information: a systematic review," *Journal of Biomedical Informatics*, vol. 73, pp. 14–29, 2017.
- [7] T. Young and et. al., "Recent trends in deep learning based natural language processing," *IEEE Computational Intelligence Magazine*, vol. 13, no. 3, pp. 55–75, 2018.
- [8] S. Sheikhalishahi and et. al., "Natural language processing of clinical notes on chronic diseases: systematic review," *JMIR Medical Informatics*, vol. 7, no. 2, p. e12239, 2019.
- [9] A. Névéol and et. al., "Clinical natural language processing in languages other than english: opportunities and challenges," *Journal of biomedical semantics*, vol. 9, no. 1, pp. 1–13, 2018.
- [10] I. Spasic and et. al., "Clinical text data in machine learning: Systematic review," *JMIR Medical Informatics*, vol. 8, no. 3, p. e17984, 2020.
- [11] T. Pham, T. Tran, D. Phung, and S. Venkatesh, "Predicting healthcare trajectories from medical records: A deep learning approach," *Journal* of biomedical informatics, vol. 69, pp. 218–229, 2017.
- [12] A. Rajkomar, E. Oren, K. Chen, A. M. Dai, N. Hajaj, M. Hardt, P. J. Liu, X. Liu, J. Marcus, M. Sun, *et al.*, "Scalable and accurate deep learning with electronic health records," *NPJ Digital Medicine*, vol. 1, no. 1, p. 18, 2018.
- [13] X. Liu and et. al., "Predicting heart failure readmission from clinical notes using deep learning," in 2019 IEEE International Conference on Bioinformatics and Biomedicine (BIBM). IEEE, 2019, pp. 2642–2648.
- [14] X. Shi and et. al., "Multiple disease risk assessment with uniform model based on medical clinical notes," *IEEE Access*, vol. 4, pp. 7074–7083, 2016.
- [15] Y. Li and et. al., "Early prediction of acute kidney injury in critical care setting using clinical notes," in 2018 IEEE International Conference on Bioinformatics and Biomedicine (BIBM). IEEE, 2018, pp. 683–686.
- [16] R. Zhang and et. al., "Automatic methods to extract new york heart association classification from clinical notes," in 2017 ieee international conference on bioinformatics and biomedicine (bibm). IEEE, 2017, pp. 1296–1299.
- [17] A. Agarwal and et. al., "A natural language processing framework for assessing hospital readmissions for patients with copd," *IEEE journal of biomedical and health informatics*, vol. 22, no. 2, pp. 588–596, 2017.
- [18] S. J. Fodeh and et. al., "Classification of patients with coronary microvascular dysfunction," *IEEE/ACM transactions on computational biology and bioinformatics*, vol. 17, no. 2, pp. 704–711, 2019.
- [19] A. Paleyes and et. al., "Challenges in deploying machine learning: a survey of case studies," arXiv preprint arXiv:2011.09926, 2020.
- [20] V. Kumar and et. al., "Ensembling classical machine learning and deep learning approaches for morbidity identification from clinical notes," *IEEE Access*, 2020.
- [21] C. R. Olsen, R. J. Mentz, K. J. Anstrom, D. Page, and P. A. Patel, "Clinical applications of machine learning in the diagnosis, classification, and prediction of heart failure," *American Heart Journal*, 2020.
- [22] S. Kannan and et. al., "Preprocessing techniques for text mining," *International Journal of Computer Science & Communication Networks*, vol. 5, no. 1, pp. 7–16, 2014.
- [23] Google, "Machine learning guides text classification," https://developers. google.com/machine-learning/guides/text-classification/step-2-5, 2019-10-21, online; accessed 2020-09-30.
- [24] L. Deléger and et. al., "Detecting negation of medical problems in french clinical notes," in *Proceedings of the 2nd ACM sight international health informatics symposium*, 2012, pp. 697–702.
- [25] S. Dubois and et. al., "Learning effective representations from clinical notes," *stat*, vol. 1050, p. 15, 2017.
- [26] E. Wallace, Y. Wang, S. Li, S. Singh, and M. Gardner, "Do nlp models know numbers? probing numeracy in embeddings," in *Proceedings* of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP), 2019, pp. 5310–5318.

- [27] D. Dua, Y. Wang, P. Dasigi, G. Stanovsky, S. Singh, and M. Gardner, "Drop: A reading comprehension benchmark requiring discrete reasoning over paragraphs," in *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, 2019, pp. 2368–2378.
- [28] T. Cai, L. Zhang, N. Yang, K. K. Kumamaru, F. J. Rybicki, T. Cai, and K. P. Liao, "Extraction of emr numerical data: an efficient and generalizable tool to extend clinical research," *BMC medical informatics* and decision making, vol. 19, no. 1, p. 226, 2019.
- [29] J. Kessler, "Scattertext: a browser-based tool for visualizing how corpora differ," in *Proceedings of ACL 2017, System Demonstrations*, 2017, pp. 85–90.
- [30] E. Dynomant and et. al., "Word embedding for the french natural language in health care: comparative study," *JMIR medical informatics*, vol. 7, no. 3, p. e12310, 2019.
- [31] T. Joachims, "Text categorization with support vector machines: Learning with many relevant features," in *European conference on machine learning*. Springer, 1998, pp. 137–142.
- [32] Y. Zhang, R. Jin, and Z.-H. Zhou, "Understanding bag-of-words model: a statistical framework," *International Journal of Machine Learning and Cybernetics*, vol. 1, no. 1-4, pp. 43–52, 2010.
- [33] D. Yan, K. Li, S. Gu, and L. Yang, "Network-based bag-of-words model for text classification," *IEEE Access*, vol. 8, pp. 82641–82652, 2020.
- [34] Y. Zhuang, H. Wang, J. Xiao, F. Wu, Y. Yang, W. Lu, and Z. Zhang, "Bag-of-discriminative-words (bodw) representation via topic modeling," *IEEE Transactions on Knowledge and Data Engineering*, vol. 29, no. 5, pp. 977–990, 2017.
- [35] G. Salton and C.-S. Yang, "On the specification of term values in automatic indexing," Cornell University, Tech. Rep., 1973.
- [36] S. Robertson, "Understanding inverse document frequency: on theoretical arguments for idf," *Journal of documentation*, 2004.
- [37] L. Havrlant and V. Kreinovich, "A simple probabilistic explanation of term frequency-inverse document frequency (tf-idf) heuristic (and variations motivated by this explanation)," *International Journal of General Systems*, vol. 46, no. 1, pp. 27–36, 2017.
- [38] I. Yahav, O. Shehory, and D. Schwartz, "Comments mining with tf-idf: the inherent bias and its removal," *IEEE Transactions on Knowledge* and Data Engineering, vol. 31, no. 3, pp. 437–450, 2018.
- [39] T. Mikolov, I. Sutskever, K. Chen, G. S. Corrado, and J. Dean, "Distributed representations of words and phrases and their compositionality," in *Advances in neural information processing systems*, 2013, pp. 3111–3119.
- [40] S. Lai, K. Liu, S. He, and J. Zhao, "How to generate a good word embedding," *IEEE Intelligent Systems*, no. 6, pp. 5–14, 2016.
- [41] O. Levy, Y. Goldberg, and I. Dagan, "Improving distributional similarity with lessons learned from word embeddings," *Transactions of the Association for Computational Linguistics*, vol. 3, pp. 211–225, 2015.
- [42] D. W. Otter, J. R. Medina, and J. K. Kalita, "A survey of the usages of deep learning for natural language processing," *IEEE Transactions on Neural Networks and Learning Systems*, 2020.
- [43] A. Pasini, "Artificial neural networks for small dataset analysis," *Journal of thoracic disease*, vol. 7, no. 5, p. 953, 2015.
- [44] A. Jordan et al., "On discriminative vs. generative classifiers: A comparison of logistic regression and naive bayes," Advances in neural information processing systems, vol. 14, no. 2002, p. 841, 2002.
- [45] J. Tolles and et. al., "Logistic regression: relating patient characteristics to outcomes," *Jama*, vol. 316, no. 5, pp. 533–534, 2016.
- [46] T. Hastie, R. Tibshirani, and J. Friedman, *The elements of statistical learning: data mining, inference, and prediction.* Springer Science & Business Media, 2009.
- [47] A. Karparthy, "Neural networks 1," https://cs231n.github.io/ neural-networks-1, 2020-04-01, online; accessed 2020-09-30.
- [48] W. S. McCulloch and W. Pitts, "A logical calculus of the ideas immanent in nervous activity," *The bulletin of mathematical biophysics*, vol. 5, no. 4, pp. 115–133, 1943.
- [49] H. B. Demuth, M. H. Beale, O. De Jess, and M. T. Hagan, *Neural network design*. Martin Hagan, 2014.
- [50] Y. Li and Y. Yuan, "Convergence analysis of two-layer neural networks with relu activation," *Advances in Neural Information Processing Systems*, vol. 30, pp. 597–607, 2017.
- [51] D. Hunter, H. Yu, M. S. Pukish III, J. Kolbusz, and B. M. Wilamowski, "Selection of proper neural network sizes and architectures—a comparative study," *IEEE Transactions on Industrial Informatics*, vol. 8, no. 2, pp. 228–240, 2012.

- [52] N. Srivastava, G. Hinton, A. Krizhevsky, I. Sutskever, and R. Salakhutdinov, "Dropout: a simple way to prevent neural networks from overfitting," *The journal of machine learning research*, vol. 15, no. 1, pp. 1929–1958, 2014.
- [53] X. Glorot and Y. Bengio, "Understanding the difficulty of training deep feedforward neural networks," in *Proceedings of the thirteenth international conference on artificial intelligence and statistics*. JMLR Workshop and Conference Proceedings, 2010, pp. 249–256.
- [54] F. Pedregosa and et. al, "Scikit-learn: Machine learning in Python," *Journal of Machine Learning Research*, vol. 12, pp. 2825–2830, 2011.
   [55] F. Chollet *et al.*, "keras," 2015.
- [56] R. Kohavi *et al.*, "A study of cross-validation and bootstrap for accuracy estimation and model selection," in *Ijcai*, vol. 14, no. 2. Montreal, Canada, 1995, pp. 1137–1145.
- [57] Y. Lu, Y.-M. Cheung, and Y. Y. Tang, "Bayes imbalance impact index: A measure of class imbalanced data set for classification problem," *IEEE transactions on neural networks and learning systems*, vol. 31, no. 9, pp. 3525–3539, 2019.
- [58] C. Steinmeyer and L. Wiese, "Sampling methods and feature selection for mortality prediction with neural networks," *Journal of Biomedical Informatics*, vol. 111, p. 103580, 2020.
- [59] M. A. Mazurowski, P. A. Habas, J. M. Zurada, J. Y. Lo, J. A. Baker, and G. D. Tourassi, "Training neural network classifiers for medical decision making: The effects of imbalanced datasets on classification performance," *Neural networks*, vol. 21, no. 2-3, pp. 427–436, 2008.
- [60] S. Visa and A. Ralescu, "Issues in mining imbalanced data sets-a review paper," in *Proceedings of the sixteen midwest artificial intelligence and cognitive science conference*, vol. 2005. sn, 2005, pp. 67–73.
- [61] C. Goutte and E. Gaussier, "A probabilistic interpretation of precision, recall and f-score, with implication for evaluation," in *European conference on information retrieval*. Springer, 2005, pp. 345–359.
- [62] E. Beede, E. Baylor, F. Hersch, A. Iurchenko, L. Wilcox, P. Ruamviboonsuk, and L. M. Vardoulakis, "A human-centered evaluation of a deep learning system deployed in clinics for the detection of diabetic retinopathy," in *Proceedings of the 2020 CHI conference on human factors in computing systems*, 2020, pp. 1–12.
- [63] M. Sahlgren and A. Lenci, "The effects of data size and frequency range on distributional semantic models," in *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, 2016, pp. 975–980.
- [64] E. Dusserre and M. Padró, "Bigger does not mean better! we prefer specificity," in *Iwcs 2017—12th international conference on computational semantics—short papers*, 2017.
- [65] C. Perlich, F. Provost, and J. Simonoff, "Tree induction vs. logistic regression: A learning-curve analysis," 2003.
- [66] P. L. Bartlett, "The sample complexity of pattern classification with neural networks: the size of the weights is more important than the size of the network," *IEEE transactions on Information Theory*, vol. 44, no. 2, pp. 525–536, 1998.
- [67] L. Martin, B. Muller, P. J. O. Suárez, Y. Dupont, L. Romary, É. V. de la Clergerie, D. Seddah, and B. Sagot, "Camembert: a tasty french language model," in *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, 2020, pp. 7203–7219.
- [68] J. Devlin, M.-W. Chang, K. Lee, and K. Toutanova, "Bert: Pre-training of deep bidirectional transformers for language understanding," in Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), 2019, pp. 4171–4186.
- [69] K. Pasupa and W. Sunhem, "A comparison between shallow and deep architecture classifiers on small dataset," in 2016 8th International Conference on Information Technology and Electrical Engineering (ICI-TEE). IEEE, 2016, pp. 1–6.
- [70] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin, "Attention is all you need," in *Proceedings* of the 31st International Conference on Neural Information Processing Systems, 2017, pp. 6000–6010.
- [71] A. Nandan, "Text classification with transformer," https://keras.io/ examples/nlp/text\_classification\_with\_transformer/, 2020-05-10, online; accessed 2020-09-30.
- [72] S. Gao, M. Alawad, M. T. Young, J. Gounley, N. Schaefferkoetter, H.-J. Yoon, X.-C. Wu, E. B. Durbin, J. Doherty, A. Stroup, *et al.*, "Limitations of transformers on clinical text classification," *IEEE journal of biomedical and health informatics*, 2021.
- [73] N. Hurley and S. Rickard, "Comparing measures of sparsity," *IEEE Transactions on Information Theory*, vol. 55, no. 10, pp. 4723–4741, 2009.

- [74] A. M. Martinez and A. C. Kak, "Pca versus Ida," *IEEE transactions on pattern analysis and machine intelligence*, vol. 23, no. 2, pp. 228–233, 2001.
- [75] A. K. Gárate-Escamila and et. al., "Classification models for heart disease prediction using feature selection and pca," *Informatics in Medicine Unlocked*, vol. 19, p. 100330, 2020.
- [76] S.-W. Kim and J.-M. Gil, "Research paper classification systems based on tf-idf and lda schemes," *Human-centric Computing and Information Sciences*, vol. 9, no. 1, p. 30, 2019.
- [77] S. Laghmati, B. Cherradi, A. Tmiri, O. Daanouni, and S. Hamida, "Classification of patients with breast cancer using neighbourhood component analysis and supervised machine learning techniques," in 2020 3rd International Conference on Advanced Communication Technologies and Networking (CommNet). IEEE, 2020, pp. 1–6.
- [78] M. A. Kramer, "Nonlinear principal component analysis using autoassociative neural networks," *AIChE journal*, vol. 37, no. 2, pp. 233–243, 1991.
- [79] G. E. Hinton and R. R. Salakhutdinov, "Reducing the dimensionality of data with neural networks," *science*, vol. 313, no. 5786, pp. 504–507, 2006.
- [80] Y. Shi, M. Lei, R. Ma, and L. Niu, "Learning robust auto-encoders with regularizer for linearity and sparsity," *IEEE Access*, vol. 7, pp. 17195– 17206, 2019.
- [81] I. D. Mienye, Y. Sun, and Z. Wang, "Improved sparse autoencoder based artificial neural network approach for prediction of heart disease," *Informatics in Medicine Unlocked*, vol. 18, p. 100307, 2020.
- [82] J.-H. Xue and D. M. Titterington, "Comment on "on discriminative vs. generative classifiers: A comparison of logistic regression and naive bayes"," *Neural processing letters*, vol. 28, no. 3, pp. 169–187, 2008.