Automating insect monitoring using unsupervised near-infrared sensors

- 2 Klas Rydhmer^{1,2*}, Emily Bick^{1,3}, Laurence Still¹, Alfred Strand¹, Rubens Luciano¹, Salena Helmreich¹,
- 3 Brittany Beck¹, Christoffer Grønne¹, Ludvig Malmros¹, Knud Poulsen¹, Frederik Elbæk¹, Mikkel
- 4 Brydegaard^{1,4,5,6}, Jesper Lemmich¹, Thomas Nikolajsen¹
- *¹ FaunaPhotonics APS, Støberigade 14, DK-2450, Copenhagen SV, Denmark.*
- *² Department of Geosciences and Natural Resource Management, University of Copenhagen, Rolighedsvej*
- *23,1958 Frederiksberg C, Denmark*
- *³ Department of Plant and Environmental Sciences, University of Copenhagen, Frederiksberg C, Denmark*
- *⁴ Lund laser Centre, Department of Physics, Lund University, Sölvegatan 14, SE-223 62 Lund, Sweden.*
- *⁵ Center for Animal Movement Research, Department of Biology, Lund University, Sölvegatan 35, SE-223 62 Lund, Sweden.*
- *⁶ Norsk Elektro Optikk AS, Østensjøveien 34, 0667 Oslo, Norway*
- **corresponding author[: klry@faunaphotonics.com](mailto:klry@faunaphotonics.com)*
-

Abstract

- Insect monitoring is critical to improve our understanding and ability to preserve and restore
- biodiversity, sustainably produce crops, and reduce vectors of human and livestock disease.
- However, conventional monitoring methods of trapping and identification are time consuming and
- thus expensive.
- Here, we present a network of distributed wireless sensors, recording backscattered near-infrared
- modulation signatures from insects. The instrument is a compact sensor based on dual-wavelength
- 22 infrared light emitting diodes and is capable of unsupervised, autonomous long-term insect
- 23 monitoring over weather and seasons. The sensor records the backscattered light at kHz pace from
- each insect transiting the measurement volume. Insect observations are automatically extracted
- and transmitted with environmental metadata over cellular connection to a cloud-based database.
- The recorded features include wing beat harmonics, melanisation and flight direction.
- To validate the sensor's capabilities, we tested the correlation between daily insect counts from an
- oil seed rape field measured with six yellow water traps and six sensors during a 4-week period. A
- comparison of the methods found a Spearman's rank correlation coefficient of 0.61 and a p-
- value=0.0065, with the sensors recording approximately 19 times more insect observations and
- demonstrating a larger temporal dynamic than conventional trapping.
-

Introduction

- Insecta is the most speciose class of terrestrial fauna¹ and the majority of the world's biodiversity is
- 35 composed of this class². In epidemiological and agricultural ecosystems, insects serve as both
- 36 beneficial organisms^{3–5} and economic pests^{6,7}. Data on insects can support biodiversity
- 37 conservation^{8,9}, human health protection¹⁰ and increased food production¹¹.
- Insects are monitored via established sampling methods including trapping, sweep netting, and
- 39 portable aspiration $12-14$. These methods are imperfect resulting in biases towards size¹⁵⁻¹⁷ and
- 40 stage¹⁸. Additionally, conventional methods may be time-consuming, costly and prone to human
- 41 error such as person-to-person variation in sampling execution $19-21$. New methods, like insect
- 42 anesthetization sampling²², are being implemented to minimize these biases. Regardless of sampling
- method, insect identification is time consuming and requires specialized training.
- In order to reduce the cost of insect monitoring and identification, automation of insect trapping ²³⁻
- 45 and identification $27-31$ has been developed. While these methods could greatly improve
- monitoring via traps, they are unsuitable for monitoring a general insect population since trap
- designs and baits are generally biased in regard to species.
- Automation of insect monitoring without traps could reduce species bias of conventional methods
- and human error, thus greatly improving the state of the art. Insect identification has been
- 50 automated as early as 1973 using wingbeat frequency $32-34$, and today remote insect sensing includes
- 51 acoustic detection³⁵, radar observations^{36–38} and lidar^{39–41}. Acoustic methods work best with a solid
- 52 medium^{26,42}, though acoustic monitoring of free flying insects has been demonstrated^{43–45}. While
- 53 radar technologies have much larger monitoring range^{16,38,46-48}, they are unsuitable for monitoring
- small insects, or insects around vegetation, such as a crop canopy. Lidar can be used to record a
- 55 large number of observations in a long transect^{49–53} and distinguish between species groups by
- 56 wingbeat frequency (WBF)^{50,54}. However, lidar equipment requires a trained operator and requires
- constant supervision due to eye safety restrictions.
- Here we present an autonomous near-infrared sensor for monitoring of flying insects in the field.
- The sensor aims to minimize human biases, be usable by non-technical personnel, and be capable of
- weatherproof long-term monitoring.

Instrument design

- The sensor is weatherproof, compact, and intended for field use by non-technicians. Like
- entomological lidar instrumentation, an air volume is illuminated, and light backscattered from
- insects entering the measurement volume is recorded by a high-speed photodetector. In addition,
- the instrument is equipped with a satellite navigation device, a camera for situational photos, and an
- environmental sensor monitoring temperature, humidity, and light intensity. An internal Global
- System for Mobile Communications (GSM) modem allows for communication and data transfer. The
- sensor can be powered by any 12V power supply, including utility power, batteries, or solar power,
- and has a maximum power consumption of 30W during monitoring. A photo of the sensor is shown
- in Figure 1.

Figure 1: As insects fly into the measurement volume, the backscattered light is recorded by the

receiver. Insect observations are automatically extracted and transmitted along with environmental

data, location, and situational photos, to the cloud via a GSM connection. Using a solar panel and

battery, the sensor is capable of unsupervised, long-term monitoring in remote locations.

Emitter

- The emitter module consists of a rectangular array of LEDs emitting two spectral bands at 808 nm
- and 980 nm with total output of 1.6 W and 1.7 W, respectively. The two wavelengths are modulated
- in a square wave at 118.8 kHz and 79.2 kHz respectively. The LEDs are mounted in a checkerboard
- pattern to achieve a homogeneous beam profile. The total area of the checkerboard, and thus the
- 81 beam size at the source, is 82 $cm²$. The light emitted from each diode is partially collimated by an
- 82 asymmetrical lens and expands with 20° and 4° diverging angles (θ_F) . The full width half maximum
- (FWHM) of the emitted light is 26 nm for the 808 nm band and 47 nm for the 970 band.

Receiver

- The backscattered light from insects entering the overlap between the beam and the receiver's field
- 86 of view (FoV) is collected by a near infrared coated aspheric lens (60 mm focal length, ø 76.2 mm
- 87 aperture) onto a silicon quadrant photodiode (QPD) with a total area of 1 cm². The receiver is
- 88 focused at 1 m and has a 4° divergence angle (θ_R) . Quadrant detection of insects allow for basic
- 89 range and size estimation^{55,56} and can differentiate ascending and descending insects as well as
- migrating insects with tailwind or host- or scent-seeking insects with headwind.

Signal processing

- Each quadrant of the QPD is amplified by a dedicated trans-impedance amplifier (TIA) with a
- 93 bandwidth of 10 Hz to 1 MHz and a gain of 0.75V/ μ A around 100kHz. The amplified signals are
- sampled by four analogue-digital converters (ADC) with 14-bit output at a rate of 6 MHz. The digital
- data-streams are sent into a field-programmable gate array (FPGA) where eight digital lock-in
- amplifiers are implemented in VHDL (Very High-Speed Integrated Circuit Hardware Description
- Language). This allows the two spectral bands to be recorded independently on each quadrant,
- resulting in an 8-channel data stream. The data is then filtered by a low-pass filter with a cut-off at
- 5kHz and down-sampled to a 20 kHz, 16-bit data stream before it is sent to a microcontroller unit
- (MCU) for event extraction and further processing. The increase in bit depth is possible due to the oversampling of the unfiltered signal.
-
-

-
- *Figure 2. Light is emitted and collimated from the LED board at 808 nm and 980nm and modulated at*
- *different carrier frequencies. The backscattered light from an insect entering the measurement*
- *volume is collected by a lens and focused onto a QPD. The four QPD-quadrants are independently*
- *amplified by a TIA and sampled. The digital data streams are sent to the FPGA, where 8 digital lock-in*
- *amplifiers individually amplify each wavelength in the digital signal processing (DSP) unit. The*
- *resulting 8-channel data stream is analyzed by the MCU which extracts events from the data stream.*
- *The events can then be stored locally or sent via GSM modem to a cloud database.*

112

113 *Figure 3. The wide beam yields long insect transit times, and the corresponding frequency resolution*

114 *is high enough to accurately capture most species. The frequency response curve (red) is flat in the*

115 *wingbeat frequency region and the effect of the LP filter at 5 kHz is indicated. The 5kHz bandwidth*

116 *allows a minimum of 4 harmonic overtones to be recorded even for mosquitoes with very high*

117 *wingbeat frequencies.*

118 Measurement volume

119 The measurement volume is defined by the overlap between the beam and the FoV. Its size and

120 shape can be adjusted by changing the angle (θ_S) between the emitter and receiver.

121 The beam, FoV and the measurement volume have been mapped by a custom-built 3-axis robot

122 covering a volume of 2 m x 1.5 m x 1.5 m. The robot is equipped with a photodetector, an

123 illumination source, and a sphere dropping mechanism. By measuring the intensity of the emitted

124 beam and the sensitivity of the FoV in the volume, the signal response from an arbitrary target can

125 be estimated. The volumes were measured at 20 planes along the Z axis, from 30 to 1655 mm, each

126 plane consisting of 56 x 56 measurement points in a 12 mm grid. The calculated signals were then

127 compared to actual measurement values by dropping black and white spheres. The white spheres

128 were assumed to be 100% reflective and the black spheres had a 5% reflectivity.

129 The measurement volume properties for targets with various optical cross sections (OCS) at different

130 angles are shown in Table 1. The size of the measurement volume is dependent on the minimum

131 acceptable sensitivity, which is related to the noise in the instrument. In the following results, the

132 edge of the volume is defined as the limit where the signal to noise ratio (SNR) is larger than 10 for

133 typical noise levels in a field installation. The volumes for a 10 mm² target are shown in Figure 4.

Table 1: Measurement volume parameters at different angles for different target OCS. The target

OCS values correspond roughly to a small midge, a small beetle, and a honeybee.

Figure 4. Measured FoV, beam, and measurement volume for the three angles. Each volume is

mapped at 20 planes along the Z axis and each plane consists of 56 x 56 measurement points with 12

mm spacing. For the FoV and beam, all measurement points below 2% of the maximum value are

excluded. For the measurement volume all points with a SNR < 10 for a 10 mm² target are excluded.

A low angle yields a longer and larger, but less sensitive, measurement volume. The FoV is identical in

all configurations.

144 Data processing

145 Automated event extraction

 The sensor records intervals of 10 minutes (4 quadrants, 2 spectral bands, 16 bit and 20 kHz sample rate after demux of carrier frequency) and automatically extracts insect observations from each

recording. The event extraction is inspired by earlier work but modified to reduce computational

149 load^{40,41,54,57}. In each channel, the signal was downsampled to 2 kHz and a rolling median filter with a

- width of 2 s and 50% overlap was used to estimate the quasi-static baselines (the baselines can
- change with environmental conditions, static objects in the beam etc.) Similarly, a standard
- deviation filter with identical properties was applied to all datapoints below the median. This
- reduces the influence of rare events, such as insects, on the noise level estimation.

The interpolated median signals were removed from the full resolution data and we employed a

- Boolean condition for insect detection when the time series exceed 10 times the estimated standard deviation. The Boolean time series were eroded by 500 µs and dilated by 30 ms. The erosion rejects
- short spikes which could not be interpreted and dilation includes insect observation flanks. The
- logical OR function was applied across all QPD-quadrants and spectral channels. Extracted
- observations are transmitted to a cloud database along with metadata such as baseline and noise
- level, via GSM connection or stored locally until a connection is available. An example of the event
- extraction process is shown in Figure 5, and the insect event is shown in greater detail in Figure 6.
-

Figure 5. An example of the event extraction process in a single channel for visibility. a) The data, in

the 810 nm band of a single QPD segment after the rolling median has been removed. The part of the

signal above the event threshold is marked in grey, and the final insect event after erosion and

dilation of the binary map is marked in green. b) Intensity distribution of the data.

Each insect observation, along with its associated timestamp and device identifier, is automatically

uploaded to the cloud via one-way AMQP (Advanced Message Queuing Protocol), with unique

connections for each device. Virtual computing is then used to further process, analyze, and securely

171 store data for further use and aggregation.

172 Events and Features

Figure 6: a) The 810 nm signal for a single insect event in of one of the QPD segments. The insect

wingbeats appear as undulating spikes. The minimum envelope of the signal is interpreted as the

 insect body contribution to the signal. b) The Welch spectral density of the event. The fundamental wingbeat frequency and harmonics are seen in the event signal. This event has a fundamental

wingbeat frequency of 160 Hz and an average body-to-wing ratio of 0.4.

179 Feature extraction / Data interpretation

- The QPD segments collect backscattered light from different sections of the measurement volume.
- For a single object passing through the measurement volume, the signal strength within each QPD-

quadrant is related to the object's OCS as well as its position. As the OCS varies with each wingbeat,

the wingbeat frequency can be resolved. Many methods have been used to extract the wingbeat

184 frequency from insect observations^{57–59} and most are based on identifying the fundamental

- frequency in the frequency domain, as shown in Figure 6 b).
- In addition to the wingbeat frequency, the body and wing contribution can be measured from each
- time signal which allows calculation of additional features such as body-to-wing ratio. Additional
- features can be calculated by comparing the relative intensity of the body and wing signals in the
- two spectral bands. These bands differentially index melanin absorption^{60–62} and may yield some
- 190 sensitivity to wing interference patterns^{61,63,64}, although not enough to uniquely determine wing
- membrane thickness. Together these features can be used to quantify the morphology of different
- insect groups and allow remote classification of insects according to order, family, genus or
- 193 species^{59,64-66}.

Field validation

Methodology

The sensor was field-tested against a conventional insect monitoring method, yellow water traps (22

cm diameter)67,68 , in an organic oilseed rape (*Brassica napus* L.) field in Sorø, Denmark (55°29'04.3"N

11°29'34.6"E). During a four-week period (04/22/19 - 05/22/19), insects were monitored with six

sensors and six yellow water traps. Sensors and traps were placed in a grid pattern, consisting of

- four linear transects 30 m from and perpendicular to the field's southern-most edge. Each transect
- consisted of three monitoring points (either sensors or traps) with 45 m spacing, and a separation of
- 22.5 m between transects. The first and third transect consisted of sensors and the second and
- 203 fourth were yellow water traps. During the field study presented in this work, θ_s was set to 20° in
- 204 order to maximize the signal strength of small targets at close range.
- Fundamentally the two methods observe different insect behaviors. While the sensor looks at
- insects flying above the crop canopy, the yellow water traps look at insects that occur within it.
- 207 Further confounding the comparison, yellow is attractive to some insects⁶⁸. Therefore, some
- proportion of insects will be attracted to the yellow water traps, resulting in overrepresentation of
- 209 some species $69,70$.
- 210 Data analysis
- The water traps were emptied daily, and sensor data was recorded continuously. All insects in the
- traps were collected, but to allow for a more direct comparison of methods, non-flying insects and
- 213 thrips found in water traps were excluded from further analysis.
- 214 The sensor data was aggregated according to the collection time of the water traps but one day,
- 215 April 30th, was excluded due to instrument malfunction. The average number of recorded insect
- observations per sensor per day and per hour was calculated. The calculated numbers were
- normalized by sensor uptime, which was on average 90% throughout the measurement period.
- Results
- The insect activity recorded by the sensors and traps respectively are shown in Figure 7. Insect
- counts from sensors and traps cannot be directly equated due to differences in measurement
- subject (insect flights vs insect landings) and non-homogeneous insect distribution; however, they
- serve to visualize similarities in gross changes in insect activity over the sample period. The results
- demonstrate a significant correlation between the sensor and trap results, specifically with a
- 224 Spearman's rank correlation coefficient of 0.61 and a p-value=0.0065 71 . Over the course of the
- 225 season, an average of 1122 ± 242 (SE) insect observations per day were collected per sensor
- 226 (excluding downtime), compared to an average of 63 ± 6 (SE) insects caught per water trap per day
- over the same period.

Discussion

- Here we present a sensor for automated unsupervised field monitoring of insect flight activity. The
- sensor illuminates an air volume and records the backscattered light from insects that fly through
- 235 the measurement volume. Discrete insect observations are automatically extracted from the
- continuous raw data flow and transmitted over a cellular connection to a database in the cloud. Field
- validation showed the number of recorded insect observations correlates with the number of
- individual insects trapped by a conventional insect monitoring method. Furthermore, the sensor
- recorded an order of magnitude more insects than the conventional method over the same time
- period.
- The automation of insect monitoring has the potential to reduce monitoring bias, cost, and human
- labor, potentially resulting in an increased ability to collect large quantities of biodiversity, public
- health, and economically relevant insect data. Additionally, the observations from the sensors were
- available in real time, whereas emptying and counting insects from traps required a significant
- amount of labor. While this work was limited to comparing total insect counts from the traps, it is possible for a skilled expert to identify these insects to the sub-species level. This is an area were the
- traps have a strong advantage over this sensor and similar instrumentation. However, we expect
- significant progress with species identification from sensor observations.
- 249 One of the most striking differences in monitoring methods is the day-to-day variability in the
- number of data points collected (Figure 7). While the yellow traps catch a similar number of insects
- each day, the difference between low and high flight activity days were more visible in the sensor.
- Early analysis of the trap and sensor data indicates that the peak recorded during May 7-11 is due to
- a pollen beetle (*Brassicogethes aeneus*) activity spike. This will be the subject of further studies.
- Another marked difference between the sensor and the water traps is the number of data points 255 collected over the same collection period. Each sensor observed \sim 19 x more insect observations than insects collected in the water trap. While in general the correlation between the two values is considered more relevant than the absolute number, one advantage of a much higher observation 258 rate in the sensors is an increased probability of recording rare species. Further work is required to successfully identify rare species from sensor signals, but if realized, sensors could provide a method
- to monitor rare species across large areas with lower labor costs.
- Insect observations recorded by the sensor are precisely timestamped at the point of occurrence,
- allowing variable aggregation over time as well as higher time granularity in measurements. This
- may have advantages in standardization compared to conventional trapping periods which may be
- affected by variable intra-collection times due to human factors (e.g. missed or delayed collections
- due to weekends or public holidays). Furthermore, the higher granularity and continuous monitoring
- during unsociable hours allows for the comparatively easy and low-labor collection of data on insect
- circadian rhythms, as well as direct weather interactions.
- We hypothesize that the sensors observe different insect behaviors compared to conventional
- monitoring methods since only airborne (flying or jumping) insects are recorded. Therefore, we did not expect a perfect correlation between the sensors and the conventional methods. Sweep netting
- 271 is likely the most similar monitoring method since it also catches insects in flight above the crop.
- However, sweep netting, which also collects insects on plants, occurs at a point measurement in
-
- 273 time and is typically performed along a transect, rather than at a fixed point in the field¹⁹. Also, each 274 trapping method is biased towards different insects, influencing catch^{15,17}.
- Trapping methods, such as the water traps used in this study, monitor insects landing, walking, or
- jumping to a specific point and do not record insects in flight. Also, each trapping method is biased
- 277 towards different insects, with the trap color influencing the trap catch⁶⁸. Although we do not yet
- know in what manner, the sensor is also most likely biased towards certain species groups. Most
- 279 primarily, its only capable of recording airborne insects. Insect vision is focused towards the visual or
- ultraviolet spectrum and not capable of resolving infrared light and we believe the emitted beam has
- 281 very little influence on insect behavior⁷². However, in a homogeneous landscape such as an
- agricultural field, any foreign object could serve as an attractant and the placement above the
- canopy could attract insects. Finally, the size of the measurement volume varies with the OCS of the insects and larger insects will be over-represented. To provide a complete picture of the insect
- 285 population, this should be considered. Along with species specific observations, this is an area where
- we expect significant progress.
- The automated unsupervised field sensor has the potential to facilitate pest prevention, public health studies and biodiversity monitoring. In further work we will explore the possibilities of
- unsupervised long-term monitoring of insect activity and species recognition.
-

Conclusions

- In this work, we have introduced an unsupervised automated sensor for insect monitoring. The
- measurement principle is similar to entomological lidar setups but is optimized for near-field
- measurements. This simplifies the installation process and increases the robustness of the sensor,
- 295 allowing it to be operable by non-technical experts and enables long-term unsupervised monitoring.
- The sensor automatically extracts insect events from the raw data and transmits these via a built-in
- modem for further processing. From the recorded observations, features such as the wingbeat
- frequency, body-wing ratio, and melanisation factor are computed and used to predict the insect
- classification down to species. During a 4-week deployment in an oilseed rape field, the detected
- flight activity was shown to be correlated with a conventional monitoring method.
- The capabilities and scalability of this sensor-based method has the potential to improve the state of
- the art in insect monitoring. The sensor can be used to explore areas such as biodiversity
- assessment, insecticide resistance, and long-term monitoring of remote areas, facilitating research
- studies currently difficult or impossible to conduct with conventional methods.

Acknowledgments

- The authors want to thank Jakob Dyhr for kindly making his organic oilseed rape field in Sorø,
- Denmark, available for the field experiments. Thanks to Lene Sigsgaard, Samuel Jansson and Sam
- Cook for helpful discussions.

Funding

 This work was supported by Innovation Fund Denmark under grant no. 9078-00183B and the Danish Environmental Protection Agency under grant no. MST-667-00253.

Author contributions:

- KR Wrote the first draft, produced figures, and conducted data analysis. KR, EB, and LS developed
- paper outline and structure. EB contributed to the introduction, field validation, discussion, and
- conclusion. LS contributed to the data processing section and discussion. KP and LM contributed to
- the instrument software development. AS, RL, and FE contributed to the instrument development
- and instrument characterization section.
- MS contributed with editing and contributed to figures.
- SH, BB, CG & JL collected and counted insects during the field trials.
- TN led the development of the instrumentation. JL took over development leadership in 2020.
- Competing Interests
- All authors are or were (partly) affiliated with FaunaPhotonics, the company that developed the sensor described in this study.
-
- 1. Stork, N. E. How Many Species of Insects and Other Terrestrial Arthropods Are There on Earth? (2017) doi:10.1146/annurev-ento-020117.
- 2. Scudder, G. *Insect Biodiversity: Science and Society - Google Books*. (Wiley-Blackwell, 2009).
- 3. Lami, F., Boscutti, F., Masin, R., Sigura, M. & Marini, L. Seed predation intensity and stability in agro-ecosystems: Role of predator diversity and soil disturbance. *Agric. Ecosyst. Environ.* **288**, 106720 (2020).
- 4. Gallai, N., Salles, J. M., Settele, J. & Vaissière, B. E. Economic valuation of the vulnerability of world agriculture confronted with pollinator decline. *Ecol. Econ.* **68**, 810–821 (2009).
- 5. Egg Parasitoids in Agroecosystems with Emphasis on Trichogramma Google Books. https://books.google.dk/books?hl=en&lr=&id=jtlhlYFH9RgC&oi=fnd&pg=PR5&dq=parasitoids +in+agroecosystems&ots=UFPabmkmym&sig=VQQ9h6LD_0sBJvGcll9E8wpHPG8&redir_esc=y #v=onepage&q=parasitoids in agroecosystems&f=false.
- 6. Sánchez-Guillén, R. A., Córdoba-Aguilar, A., Hansson, B., Ott, J. & Wellenreuther, M. Evolutionary consequences of climate-induced range shifts in insects. *Biol. Rev.* **91**, 1050– 1064 (2016).
- 7. Zalucki, M. P. *et al.* Estimating the economic cost of one of the world's major insect pests, Plutella xylostella (Lepidoptera: Plutellidae): just how long is a piece of string? *J. Econ. Entomol.* **105**, 1115–1129 (2012).
- 8. Dornelas, M. & Daskalova, G. N. Nuanced changes in insect abundance. *Science (80-.).* **368**, 368–369 (2020).
- 9. Didham, R. K. *et al.* Interpreting insect declines: seven challenges and a way forward. *Insect Conserv. Divers.* **13**, 103–114 (2020).
- 10. Greenwood, B. M., Bojang, K. & Whitty, C. J. M. Target GAT. *Lancet* **365**, 98 (2005).
- 11. Dangles, O. & Casas, J. Ecosystem services provided by insects for achieving sustainable development goals. *Ecosyst. Serv.* **35**, 109–115 (2019).
- 12. Burkholder, W. E. & Ma, M. Pheromones for monitoring and control of stored-product insects. *Annu. Rev. Entomol.* **30**, 257–272 (1985).
- 13. Morris3, R. F. *SAMPLING INSECT POPULATIONS1,2*.
- 14. Strickland, A. H. *SAMPLING CROP PESTS AND THEIR HOSTSl*.
- 15. Bannerman, J. A., Costamagna, A. C., McCornack, B. P. & Ragsdale, D. W. Comparison of Relative Bias, Precision, and Efficiency of Sampling Methods for Natural Enemies of Soybean Aphid (Hemiptera: Aphididae). *J. Econ. Entomol.* **108**, 1381–1397 (2015).
- 16. Osborne, J. L. *et al.* Harmonic radar: a new technique for investigating bumblebee and honey

 34. Reed, S. C., Williams, C. M. & Chadwick, L. E. *FREQUENCY OF WING-BEAT AS A CHARACTER FOR SEPARATING SPECIES RACES AND GEOGRAPHIC VARIETIES OF DROSOPHILA*. 35. Mankin, R. W., Hagstrum, D. W., Smith, M. T., Roda, A. L. & Kairo, M. T. K. *Perspective and Promise: a Century of Insect Acoustic Detection and Monitoring*. https://academic.oup.com/ae/article/57/1/30/2462094 (2011). 36. Drake, V. A. & Reynolds, D. R. *Radar entomology: observing insect flight and migration*. (Cabi, 2012). 37. Long, T. *et al.* Entomological Radar Overview: System and Signal Processing. *IEEE Aerosp. Electron. Syst. Mag.* **35**, 20–32 (2020). 38. Drake, V. A., Hatty, S., Symons, C. & Wang, H. Insect monitoring radar: Maximizing performance and utility. *Remote Sens.* **12**, (2020). 39. Brydegaard, M. & Jansson, S. Advances in entomological laser radar. *IET Int. Radar Conf.* 2–5 (2018) doi:10.1049/joe.2019.0598. 40. Jansson, S. *Entomological lidar : target characterization and field applications*. (Division of Combustion Physics, Department of Physics, Lund University, 2020). 41. Malmqvist, E. *From Fauna to Flames : remote sensing with Scheimpflug-Lidar*. (Division of Combustion Physics, Department of Physics, Lund University, 2019). 42. Mankin, R. W., Hagstrum, D. W., Smith, M. T., Roda, A. L. & Kairo, M. T. K. Perspective and promise: A century of insect acoustic detection and monitoring. *Am. Entomol.* **57**, 30–44 (2011). 43. Miller-Struttmann, N. E., Heise, D., Schul, J., Geib, J. C. & Galen, C. Flight of the bumble bee: Buzzes predict pollination services. *PLoS One* **12**, 1–14 (2017). 44. Li, Y. *et al.* Mosquito detection with low-cost smartphones: data acquisition for malaria research. (2017). 45. Mukundarajan, H., Hol, F. J. H., Castillo, E. A., Newby, C. & Prakash, M. Using mobile phones as acoustic sensors for high-throughput mosquito surveillance. *Elife* **6**, 1–26 (2017). 46. Osborne, J. L. *et al.* A landscape-scale study of bumble bee foraging range and constancy, using harmonic radar. *J. Appl. Ecol.* **36**, 519–533 (1999). 47. Radar, L., Smith, A. D., Riley, J. R. & Gregory, R. D. *A Method for Routine Monitoring of the Aerial Migration of Insects by Using a Vertical*. *Source: Philosophical Transactions: Biological Sciences* vol. 340 (1993). 48. Chapman, J. W., Smith, A. D., Woiwod, I. P., Reynolds, D. R. & Riley, J. R. *Development of vertical-looking radar technology for monitoring insect migration*. *Computers and Electronics in Agriculture* vol. 35 www.elsevier.com/locate/compag (2002). 49. Malmqvist, E. & Brydegaard, M. Applications of KHZ-CW Lidar in Ecological Entomology. *EPJ Web Conf.* **119**, (2016). 50. Brydegaard, M. *et al.* Lidar reveals activity anomaly of malaria vectors during pan-African eclipse. *Sci. Adv.* **6**, eaay5487 (2020). 51. Malmqvist, E. *et al.* The bat–bird–bug battle: Daily flight activity of insects and their predators over a rice field revealed by high-resolution scheimpflug lidar. *R. Soc. Open Sci.* **5**, (2018). 52. Fristrup, K. M., Shaw, J. A. & Tauc, M. J. Development of a wing-beat-modulation scanning

- lidar system for insect studies. *Lidar Remote Sens. Environ. Monit. 2017* 15 (2017) doi:10.1117/12.2274656.
- 53. Hoffman, D. S., Nehrir, A. R., Repasky, K. S., Shaw, J. A. & Carlsten, J. L. Range-resolved optical detection of honeybees by use of wing-beat modulation of scattered light for locating land mines. *Appl. Opt.* **46**, 3007–3012 (2007).
- 54. Jansson, S., Malmqvist, E. & Mlacha, Y. Real-time dispersal of malaria vectors in rural Africa monitored with lidar. *PLoS ONE* (2020).
- 55. Jansson, S. & Brydegaard, M. Passive kHz lidar for the quantification of insect activity and dispersal. *Anim. Biotelemetry* **6**, 6 (2018).
- 56. Jansson, S. P. & Sørensen, M. B. An optical remote sensing system for detection of aerial and aquatic fauna. (2019).
- 57. Malmqvist, E., Jansson, S., Török, S. & Brydegaard, M. Effective parameterization of laser radar observations of atmospheric fauna. *IEEE J. Sel. Top. Quantum Electron.* **22**, 1 (2015).
- 58. Drake, V. A., Wang, H. K. & Harman, I. T. Insect Monitoring Radar: Remote and network operation. *Comput. Electron. Agric.* **35**, 77–94 (2002).
- 59. Kirkeby, C. *et al.* Advances in automatic identification of flying insects using optical sensors and machine learning. *Sci. Rep.* **11**, 1555 (2021).
- 60. Jacques, S. L. Erratum: Optical properties of biological tissues: A review (Physics in Medicine and Biology (2013) 58). *Phys. Med. Biol.* **58**, 5007–5008 (2013).
- 61. Li, M. *et al.* Bark beetles as lidar targets and prospects of photonic surveillance. *J. Biophotonics* 1–16 (2020) doi:10.1002/jbio.202000420.
- 62. Brydegaard, M. Advantages of shortwave infrared LIDAR entomology. in *Laser Applications to Chemical, Security and Environmental Analysis* LW2D-6 (Optical Society of America, 2014).
- 63. Brydegaard, M., Jansson, S., Schulz, M. & Runemark, A. Can the narrow red bands of dragonflies be used to perceive wing interference patterns? *Ecol. Evol.* **8**, (2018).
- 64. Gebru, A. *et al.* Multiband modulation spectroscopy for the determination of sex and species of mosquitoes in flight. *J. Biophotonics* **11**, (2018).
- 65. Potamitis, I. Classifying insects on the fly. *Ecol. Inform.* **21**, 40–49 (2014).
- 66. Silva, D. F., De Souza, V. M. A., Batista GEAPA, K. E. & Ellis, D. P. W. Applying machine learning and audio analysis techniques to insect recognition in intelligent traps. Proceedings—2013 12th International Conference on Machine Learning and Applications, ICMLA 2013. 2013. (2013).
- 67. Heathcote, G. D. THE COMPARISON OF YELLOW CYLINDRICAL, FLAT AND WATER TRAPS, AND OF JOHNSON SUCTION TRAPS, FOR SAMPLING APHIDS. *Ann. Appl. Biol.* **45**, 133–139 (1957).
- 68. Capinera, J. L. & Walmsley, M. R. *Visual Responses of Some Sugarbeet Insects to Sticky Traps and Water Pan Traps of Various Colors 1*.
- 69. VAISHAMPAYAN, S. M., KOGAN, M., WALDBAUER, G. P. & WOOLLEY, J. T. SPECTRAL SPECIFIC RESPONSES IN THE VISUAL BEHAVIOR OF THE GREENHOUSE WHITEFLY, TRIALEURODES VAPORARIORUM (HOMOPTERA: ALEYRODIDAE). *Entomol. Exp. Appl.* **18**, 344–356 (1975).
- 70. Mound, L. A. Studies on the olfaction and colour sensitivity of Bemisia tabaci (Genn.) (Homoptera, Aleyrodidae). *Entomol. Exp. Appl.* **5**, 99–104 (1962).
- 71. Virtanen, P. *et al.* SciPy 1.0: fundamental algorithms for scientific computing in Python. *Nat. Methods* **17**, 261–272 (2020).
- 72. Van Der Kooi, C. J., Stavenga, D. G., Arikawa, K., Belušič, G. & Kelber, A. Evolution of Insect Color Vision: From Spectral Sensitivity to Visual Ecology. *Annu. Rev. Entomol.* **66**, 435–461 (2021).