The Tensor Brain: A Unified Theory of Perception, Memory and Semantic Decoding

Volker Tresp

Ludwig Maximilian University of Munich Siemens, Corporate Technology, Munich

Sahand Sharifzadeh* Ludwig Maximilian University of Munich

Hang Li^{*}

Ludwig Maximilian University of Munich Siemens, Corporate Technology, Munich

Dario Konopatzki Ludwig Maximilian University of Munich

Yunpu Ma Ludwiq Maximilian University of Munich

Editor:

VOLKER.TRESP@LMU.DE

SAHAND.SHARIFZADEH@GMAIL.COM

HANG.LI@SIEMENS.COM

DK@DKONOPATZKI.DE

COGNITIVE.YUNPU@GMAIL.COM

Abstract

We present a unified computational theory of an agent's perception and memory. In our model, perception, episodic memory, and semantic memory are realized by different functional and operational modes of the oscillating interactions between an index layer and a representation layer in a bilayer tensor network (BTN). The memoryless representation layer broadcasts information and reflects the cognitive brain state. In cognitive neuroscience, it would be the "mental canvas", or the "global workspace". The symbolic index layer represents concepts and past episodes, whose semantic embeddings are implemented in the connection weights between both layers. In addition, we propose a working memory layer as a processing center and information buffer. Episodic and semantic memory realize memory-based reasoning, i.e., the recall of relevant past information to enrich perception, and are personalized to an agent's current state, as well as to an agent's unique memories. Episodic memory stores and retrieves past observations and provides provenance and context. Recent episodic memory enriches perception by the retrieval of perceptual experiences, which provide the agent with a sense about the here and now: to understand its own state, and the world's semantic state in general, the agent needs to know what happened recently, in recent scenes, and on recently perceived entities. Remote episodic memory retrieves relevant past experiences, contributes to our conscious self, and, together with semantic memory, to a large degree defines who we are as individuals. With semantic memory, quite specific information on entities can be retrieved, which supplements perception for those entities. Semantic memory compresses past observations, enables multimodal integration, and represents a restricted sufficient statistics and a prior for the unobserved. We argue that it is important for the agent to represent specific entities, like Jack and Sparky, and not just attributes and classes, like Person, Dog and Tall, to analyze visual scenes, spatial and social networks, and as a prerequisite for an explicit episodic

^{*.} Equal contributions

and semantic memory. We test our model on a standard benchmark data set, which we expanded to contain richer representations for attributes, classes, and individuals. From our experimental results, we conclude the following. Fast perception is an integrated scene analysis and requires the representation layer, without specific attention to scene entities. Simple perception, an elementary form of perception, is quite sufficient for labeling novel visual entities with attributes and classes. Indices for time instances and individual entities are required for the labeling of known entities in perception, and for the realization of episodic and semantic recall, which enrich perception with past experiences and background knowledge. For the labeling of relationships, an additional memory buffer, i.e., a working memory, is required. The paper demonstrates that a form of self-supervised learning by pseudo-labeling can learn new concepts and refine existing ones. We propose that our model can be related to some of the aspects of perception and memory in the human brain. In particular, we suggest that —in evolution and during development— episodic memory and semantic memory evolved as emergent properties in a development to gain a deeper understanding of sensory information, to provide a context, and to provide a sense of the current state of the world.

1. Introduction

With an increase in higher animals' abilities to move and act came a growing demand for high-performing perceptual systems, beyond simple labeling of entities with attributes and classes (Hommel et al., 2001). This might have been a driving force to develop episodic and semantic memory. Episodic engrams permit the recall of recent and remote memories and provide guidance for acting right. Semantic engrams provide background information and complement perceived information with background knowledge.

Episodic memories recall previous events. *Recent episodic memory* permits the agent to remember the immediate past since some state information cannot be directly derived from perceptual input. A recall is triggered by nearness in time and relevance. Recent episodic memory has evolved to be able to remember where an agent had been before, why it is where it is, and what the general context is, beyond the here and now. For instance, the agent needs to remember that, even though perception does not give a clue, it is still in the hide-out, because the bear had been chasing it and might still be lurking outside. *Remote episodic memory* can remind an agent about past situations, similar to the current, and imminent danger and favorable actions associated with the memory. Recall in remote episodic memory is triggered by closeness in episodic representation.

Semantic memory represents a restricted sufficient statistics, enables multimodal integration, and provides information from the prior. For example, if Sparky is discovered in a scene, semantic memory provides background information, e.g., that Sparky is a young dog and is owned by Jack; and although dogs, in general, might be aggressive, Sparky is a friendly dog. Semantic memory support can be essential for survival: an agent simply knows that bears are dangerous, even when a bear looks cozy and sleepy and even if an individual did not yet have an unpleasant encounter with a bear.

We emphasize the importance of relationships between entities, which enable, e.g., rich scene descriptions and reasoning in social and spatial networks. An agent can understand not only that there is a bear and a person in a scene, but that, in fact, the bear is chasing the person. We propose that basic facts are expressed as triple sentences of the form *(subject, pred-icate, object)*. In most languages, basic facts are expressed in this format and thus triple sentences are arguable of fundamental relevance to communicate perception, episodic memory, and semantic memory, all of which humans can easily describe by language. Triples might have been the basis from which agents developed the ability to communicate, e.g., they could inform peers that a bear is lurking outside the hide-out. In computer science, triples are the basis for knowledge graphs (KGs), where the concepts are represented as nodes and predicates become labeled directed links pointing from subject node to object node. KGs are universal in the sense that statements involving predicates with an arity larger than two can be reduced to triple formats. Knowledge graphs currently have a large impact in applications and industry.

In our approach, we are motivated by Occam's quest for simplicity, i.e., we are interested in the simplest biologically plausible probabilistic model explaining the computational features we are interested in. We propose a very simple architecture, which contains two basic layers, i.e., the *index layer* and the *representation layer*. Operations are supported by a third layer, the working memory layer, for the modeling of relationships. The index layer contains indices, i.e., symbolic representations, for the individual's acquired concepts and time instances. The representation layer is the main communication platform. In cognitive neuroscience, if would correspond to, what authors call, the "mental canvas", the "theater of the brain", or the "global workspace" and reflects the cognitive brain state. The connection matrix between both consists of the index embeddings, which are the semantic representations of the symbols; if one index is activated, the representation layer reflects the index embedding. The representation layer is subsymbolic and conveys the gist of perception or of a specific memory. An index represents a concept whose embedding is a point in semantic embedding space, formed by the representation layer. In cognitive neuroscience, this layer is sometimes referred to as the conceptual space (Gärdenfors, 2016).

We will show that perception, episodic memory, and semantic memory can all be performed by an interplay between the two basic layers, supported by working memory. Mathematically, these operations can be described by a bilayer tensor network (BTN) and assume a form of alternating activations of the two layers.

If translated into the working of the human brain, we propose that the index layer might be realized by the medial temporal lobe (MTL) and the representation layer might be part of the posterior hot zone, which, as it has been argued, is the minimal neural substrate essential for conscious perception (Koch et al., 2016). In conjunction with working memory, one might also relate it to the prefrontal parietal network (PPN), (Bor and Seth, 2012), and the global workspace (Baars, 1997; Dehaene, 2014). As these authors argue, both are candidates for foundations of consciousness, as well.

The paper is organized as follows. In the next section, we cover related work. Section 3 provides theoretical background on ontologies. Section 4 defines semantic state variables and a semantic state space. It introduces the temporal KG, the episodic KG, the probabilistic KG, and the semantic KG and their models. In Section 5 we present our proposed bilayer tensor network (BTN) and demonstrate how it realizes the different KGs of the agent. Section 6 describes how our model functions in perception. The following sections present experimental results and discuss potential relationships to cognitive computational neuroscience. Section 7 covers perception and a path towards language and consciousness.

Section 8 discusses concept representations and conceptual maps. Section 9 covers episodic memory and Section 10 semantic memory. Using social network data, we demonstrate multimodal integration in semantic memory. In Section 11 we demonstrate that a form of self-supervised learning by pseudo-labeling can learn new concepts and refine existing concepts. Section 12 contains our conclusions.

2. Related Work

2.1 Tensor Networks for Modeling Knowledge Graphs

The bilayer tensor network (BTN) is an example of a tensor network. RESCAL was the first tensor-based embedding model for triple prediction in relational data sets and knowledge graphs (Nickel et al., 2011, 2012). Embedding learning for knowledge graphs evolved into a sprawling research area (Bordes et al., 2013; Socher et al., 2013; Yang et al., 2014; Nickel et al., 2015b; Trouillon et al., 2016; Dettmers et al., 2018). (Nickel et al., 2015a) provides an overview and PyKEEN (Ali et al., 2021) a comprehensive software library. In contrast to previous approaches, the BTN can be implemented as an interaction between the index layer and the representation layer and thus is more suitable for brainware implementations.

2.2 Cognitive Tensor Networks and Related Models

The line of work described in this paper started with (Tresp et al., 2015). That paper introduced tensor networks with index embeddings for perception, as well as semantic and episodic memory. The paper did not explicitly consider scene bounding boxes and did not contain experimental results.

(Tresp and Ma, 2016; Tresp et al., 2017a,b; Ma et al., 2018b) analyzed the connection between temporal and semantic tensor networks. In those papers, the temporal knowledge graph was modeled by a Bernoulli likelihood function, from which semantic memory was derived by an integration step, performed in latent space. In this paper, we replace the integration by an attention approximation that leads to an explicit semantic memory model.

Tensors and tensor decompositions have been used previously as memory models but the main focus was on simple associations (Hintzman, 1984; Kanerva, 1988; Humphreys et al., 1989; Osth and Dennis, 2015) and compositional structures (Smolensky, 1990; Pollack, 1990; Plate, 1997; Halford et al., 1998; Ma et al., 2018a). In the tensor product approach (Smolensky, 1990), encoding or binding is realized by a tensor product (generalized outer product), and composition by tensor addition. In the STAR model (Halford et al., 1998), predicates are represented as tensor products of the components of the predicates. The early approaches often had some form of factor design, e.g., by using random vectors as embeddings.

Tensor network theory evolved in the 1980s and follows the idea of geometrization of biology. It is a theory of brain function (particularly that of the cerebellum) that provides a mathematical model of the transformation of sensory space-time coordinates into motor coordinates and vice versa by cerebellar neuronal networks (Pellionisz and Llinás, 1980).

2.3 Visual Relationship Detection and Scene Graphs

In 2016, the Stanford Visual Relationship dataset was published which contained images annotated with triple sentences (Lu et al., 2016) and (Krishna et al., 2017). The two papers made their annotated data available, which spawned an explosion of research activity in visual relationship detection (VRD). The background information in (Lu et al., 2016) was extracted from a text corpus. Recent work in this direction is (Luo et al., 2019).

VRD with KG models was proposed by (Baier et al., 2017; Zhang et al., 2017; Baier et al., 2018). (Baier et al., 2017) showed how a prior distribution derived from triple occurrences could significantly improve on pure vision-based approaches and on approaches that used prior distributions derived from language models. (Sharifzadeh et al., 2019) showed further improvements by including 3-D image information. (Tresp et al., 2019, 2020) describes more recent publications in this tradition. The presented work introduces more clearly the different operational modes and also provides more extensive experimental results.

Triple sentences generated from an image form a scene graph (Johnson et al., 2015). Work on scene graphs attempts to find a unique, globally optimal, interpretation of an image. State-of-the-art scene graph models are described in (Yang et al., 2018; Zellers et al., 2018; Hudson and Manning, 2019). (Sharifzadeh et al., 2020) captures the interplay between perception and semantic knowledge by introducing schema representations and implementing the classification as an attention layer between image-based representations and the schema. Our paper is based on visual relationship detection, which we extend to also permit information propagation in the underlying scene graph.

2.4 Related Modern Technical Models for Memory

(Hochreiter and Schmidhuber, 1997) convincingly demonstrated the importance of memory systems in recurrent neural networks. Important later extensions are the neural Turing machine (NTMs) (Graves et al., 2014) and the memory networks (Weston et al., 2014; Sukhbaatar et al., 2015). In those papers, episodic memory acts as an instance buffer. Both use a recurrent neural network in combination with attention mechanisms.

In our approach, working memory is part of a (non-standard) recurrent neural network, as part of the BTN. The attention mechanisms in our model, i.e., episodic attention and semantic attention, are quite different from the attention mechanisms in those papers. Also, our goal is to derive triple statements, whereas, in those models, the task is query answering.

In experience replay (Mnih et al., 2015; Schaul et al., 2015; Botvinick et al., 2019), relevant episodic experiences are repeatedly presented to speed up and improve reinforcement learning.

2.5 Dual Process Theory and Complementary Learning Systems (CLS)

In psychology, dual process theory concerns the interplay in the mental processing of an implicit, automatic, unconscious process (shared with animals) and an explicit, controlled, conscious process (uniquely human). See (Evans, 2003) for a review.

In our model, the implicit side would be on the level of embeddings and representations, whereas the explicit side is on the level of the concept indices and the extracted triple sentences. An index represents a concept whose embedding is a point in semantic embedding space, formed by the representation layer, in cognitive neuroscience sometimes referred to as conceptual space. Conceptual spaces are the core of the approach by Gärdenfors (Gärdenfors, 2016). In a conceptual space, points denote objects, and regions denote concepts.

One instance of a dual process theory is Kahneman's system-1 / system-2 dichotomy (Kahneman, 2011). Although most of our model is on the level of system 1, the triple generation, while still rather effortless, might form the transition to system 2.

CLARION is a dual-process model of both implicit and explicit learning (Sun and Peterson, 1996). It is based on one-shot explicit rule learning (i.e., explicit learning) and gradual implicit tuning (i.e. implicit learning).

A related dichotomy can be found in the complementary learning systems (CLS) theory (McClelland et al., 1995; Kumaran et al., 2016), where the formation of the time index and its embedding would be part of a nonparametric learning system centered on the hippocampus, which allows rapid learning of the specifics of individual items and experiences (Kumaran et al., 2016). Slow training would be part of a parametric learning system, which serves as the basis for the gradual acquisition of structured knowledge about the environment to neocortex (Kumaran et al., 2016). In our paper, we introduce self-supervised learning by pseudo-labeling for rapid learning and discuss the consolidation process of learned knowledge.

2.6 The Bayesian Brain

Our approach can be related to the tradition of Bayesian approaches to brain modeling (Dayan et al., 1995; Rao and Ballard, 1999; Knill and Pouget, 2004; Körding et al., 2004; Tenenbaum et al., 2006; Griffiths et al., 2008; Friston, 2010).

In (Baier et al., 2017) an explicit semantic prior distribution was used, describing *a priori* probabilities for triple sentences. For inference, Bayes' formula is used. The great improvement in performance after integrating the prior information is an indication that triple representations might be a powerful abstraction level for formulating prior information, in general. In (Sharifzadeh et al., 2020) it was shown that the probabilistic KG acts as an inductive bias in perception. Here, we emphasize the role of a prior as an integrator of multimodal information and in its role to fill in nonperceptual background information.

3. An Ontology to Organize the World

You only see what you know. —Johann Wolfgang von Goethe

To understand what is perceived, an agent needs to have an understanding of the things in the world and their relationships. In the information sciences, an ontology encompasses a representation, formal naming, and definition of the concepts and relations between concepts. In this section we review some ontological basics, in as much they are relevant for further discussion in the paper.

3.1 An Upper Ontology

We assume that the agent's world consists of a set of N_C concepts $\mathcal{C} = \{c_1, \ldots, c_{N_C}\}$ and a set of N_P relation types or predicates $\mathcal{P} = \{p_1, \ldots, p_{N_P}\}$. We orient ourselves on basic components of upper ontologies¹ and define that a concept can either denote an individual or instance $e \in \mathcal{E} \subset \mathcal{C}$, or a class $k \in \mathcal{K} \subset \mathcal{C}$, which stands for a collection of entities, or an attribute $b \in \mathcal{B} \subset \mathcal{C}$. Examples for entities are Jack, Sparky, and Munich, for classes are Person, Dog, Mammal, LivingBeing, City, and Country, and for attributes are Tall, Black, Dangerous and Young.

We formulate facts as triple sentences of the form (s, p, o) where $s \in C$ is the identifier for the subject concept (also called *head* or *source node*), $p \in \mathcal{P}$ is the identifier for the predicate, and $o \in C$ is the identifier for the object concept (also called *tail* or *target node*). Examples for predicates are *knows*, *likes*, *loves*, *ownedBy*, *nextTo*, *type* and *subClass*. We roughly follow the RDF standard, developed in the Semantic Web community (Klyne and Carroll, 2004). Examples for triple sentences are: (Munich, partOf, Bavaria), (Sparky, looksAt, Jack), (AkiraKurosawa, directorOf, SevenSamurai), and (Jack, knows, Mary).

Predicates often come with type constraints on domains (applied to the subject in a triple) and ranges (applied to the object of a triple). In our basis ontology, we enforce that the subject s, for most predicates, must be an entity, i.e., $s \in \mathcal{E}$. An exception is the predicate *subClass*, where both subject and object are classes, as in (Mammal, subClass, LivingBeing). As will be discussed in Subsection 4.7, we reserve the case that the subject is not an entity for generalized statements, which are probabilistic summary statements, i.e., to represent approximate rules.

We assume a strong default predicate *hasAttribute*, which, depending on the subject type and the object type, can stand for certain other predicates from the set $\mathcal{P}^d \subseteq \mathcal{P}$:

- If both subject and object are entities, the implicit predicate is *sameAs*; thus (Jack, hasAttribute, John) stands for (Jack, sameAs, John).
- If the subject is an entity and the object is an attribute, the implicit predicate is attribute-specific but should be obvious; thus (Jack, hasAttribute, Tall) stands for (Jack, height, Tall).
- If the subject is an entity and the object is a class, the implicit predicate is *type*, as in (Sparky, type, Dog).
- If both subject and object are classes, the implicit predicate is *subClass*, as in (*Dog*, *subClass*, *Mammal*); note that the transitive *subClass* predicate permits the modeling of deep ontologies.

Triple sentences involving the hasAttribute predicate (and its substitutes) we call unary statements. The remaining N_B predicates from $\mathcal{P}^B \subseteq \mathcal{P}$ form binary statements. We will refer to the object in a unary statement also simply as a unary label of the subject entity, and to the predicate in a binary statement as the binary label. Binary statements are required when the default unary interpretation is not applicable, as in (Jane, motherOf,

^{1.} Wikipedia, The Free Encyclopedia, s.v. "Ontology components," (accessed February 10, 2021), https://en.wikipedia.org/wiki/Ontology_components

Jack) (the default would be *(Jane, sameAs, Jack)*). Higher-order relations can be reduced to a set of binary statements, e.g., by using blank concepts, which are represented as blank nodes in a graphical representation (Noy et al., 2006).

3.2 Reasoning

First-order logic is a well-established foundation for logical reasoning. An important form of reasoning is the transitive subclass reasoning: if $(k_i, subClass, k_j)$ is true, then $(s, type, k_j) \leftarrow (s, type, k_i)$, where $s \in \mathcal{E}$, $k_i, k_j \in \mathcal{K}$. This will be important in the derivation of parent and grandparent class labels in Section 7. We also perform sameAs reasoning; for example, $(Sparky, looksAt, Jack) \leftarrow (s', looksAt, o')$, (s', sameAs, Sparky), (o', sameAs, Jack). Otherwise, logical reasoning is not a focus of this paper.

In a way, all of perception, episodic and semantic memory perform some form of probabilistic reasoning. We refer to the former as perceptual reasoning and the latter two as memory-based reasoning. We will also discuss the derivation of probabilistic rules in the context of generalized statements.

4. Semantic State and Knowledge Graph Models

4.1 Semantic State Variables and the Semantic State

Some statements are always true, as (Munich, partOf, Bavaria), but the truth values of other statements can change in time, as (Munich, weather, Sunny). Thus, with each triple sentence, we associate a semantic state variable $Y_{s,p,o,t}$. If (s, p, o) is true at time instance t, then $Y_{s,p,o,t} = 1$ and if (s, p, o) is false at time instance t, then $Y_{s,p,o,t} = 0$. The semantic state at time instance t is defined as the states of all semantic state variables. We assume that the agent is concerned with N_T past time instance $\mathcal{T} = \{t_1, \ldots, t_{N_T}\}^2$.

4.2 Knowledge Graphs

An agent is only aware of parts of the world, sometimes called the "projected world" (Gärdenfors, 2016). We define an agent's knowledge graph (KG) to consist of all the concepts and predicates the agent is aware of, i.e., the agent's universe. A knowledge graph (KG) is a graphical representation where concepts are represented as nodes. A link from subject node s to object node o, labeled by p, refers to the triple sentence (s, p, o). An agent's KG can be considered as a personalized view of the semantic state.

KGs have become quite popular as a means for knowledge and information representation in many applications. Maybe the most prominent technical KG is the Google KG (Singhal, 2012). As of 2022, it contains over 500 billion facts about five billion entities (Sullivan, 2020). Further popular large-scale knowledge graphs are DBpedia (Auer et al., 2007), YAGO (Suchanek et al., 2007), Freebase (Bollacker et al., 2008), and NELL (Carlson et al., 2010).

^{2.} In RDF, all statements belonging to one time instance form a namespace.



Figure 1: Left: pKG and sKG. The grey nodes indicate categorical variables (for random variables S and O, one state per concept) and represent the "inputs". The pink nodes represent "outputs" describing the unary statements (one node per concept). The orange nodes represent "outputs" describing the binary statements (one node per binary label). In the SPM for the pKG, we condition on S, and O and predict the unary labels and the binary labels. In the sKG, we include an IPM, which predicts O from S. Center: tKG and eKG. We add a categorical random variable T to model time instances. In the SPM for the tKG, we condition on T, S, and O and predict the unary labels and predict the unary labels. In the sKG, we include an IPM, which predicts S from T and O from T and S. Right: In perception, all nodes become dependent on perceptual input. The models for perception, episodic and semantic memory are coupled by parameter sharing, motivated by an attention approach, which we see as an approximation to a probabilistic mixture model. More details in Section 5 and in the Appendix.

4.3 Temporal KG

In an agent's temporal KG (tKG), the link from s to o labeled by p exists at time t, if $Y_{s,p,o,t} = 1$. Thus it summarizes the semantic states for all time steps considered. An agent's statement prediction model (SPM) provides the probability $\mathbb{P}(Y_{s,p,o,t} = 1)$.³ As random variables, all $Y_{s,p,o,t}$ are mutually independent, although they will become dependent in training by a shared parameterization (see Section 5).

In our approach, we represent $\mathbb{P}(Y_{s,p,o,t})$ as a conditional probability. The SMP for binary statements becomes, $\forall p \in \mathcal{P}^B$,

$$\mathbb{P}(Y_{s,p,o,t}) \equiv \mathbb{P}(Y_p|s,o,t).$$
(1)

^{3.} Temporal knowledge graph models were introduced in (Tresp et al., 2015) and explored in (Ma et al., 2018b). Note, that in some works, the term tKG is used to describe novelty such as singular events, like (*Sparky, bites, John*) and events describing state changes, like, (*Jack, statusChange, Married*) (Han et al., 2020). Novelty is especially relevant for forecasting.

Here, $Y_p \in \{0, 1\}$. Thus we are defining N_B probabilistic functions. For unary statements, this simplifies to $\mathbb{P}(Y_{s, hasAttribute, \underline{o}, t}) \equiv \mathbb{P}(Y_{\underline{o}}|s, t)$. Here $Y_{\underline{o}} \in \{0, 1\}$ and $\underline{o} \in \mathcal{C}$. Thus, for the unary statements, we are defining N_C probabilistic functions.

In our probabilistic notation, we refer to the agent's personal belief, i.e., Bayesian probabilities, in contrast to objective frequentist probabilities.

4.4 Episodic KG

Whereas the SPM represents $N_B + N_C$ different functions, the instance prediction model (IPM) models the input distributions to those functions, where we decompose

$$\mathbb{P}(s, o, t) = \mathbb{P}(o|s, t)\mathbb{P}(s|t)\mathbb{P}(t).$$
⁽²⁾

Here, $\mathbb{P}(s|t)$ is the probability that at time t, information on statements were acquired, where s was the subject, and $\mathbb{P}(o|s,t)$ is the probability that at time t, information on statements were acquired, where o was the object, given that s was the subject.

In an agent's eKG, we generate samples s^* and o^* from these distributions and then predict triple probabilities using the SPM. An agent's eKG is our mathematical model for episodic memory. Figure 1 visualizes the dependencies between the IPM and the SPM.

4.5 Probabilistic KG

A probabilistic KG (pKG) labels each link with the expectation that it is true, independent of any particular time instance or perceptual input. It represents a restricted sufficient statistics and a prior for future observations. An agent's SPM provide

$$\mathbb{P}(Y_{s,p,o}) \equiv \mathbb{P}(Y_p|s,o) = \sum_t \mathbb{P}(Y_p|s,o,t)\mathbb{P}(t|s,o).$$
(3)

The weighting $\mathbb{P}(t|s, o)$ takes care that the average is only over time indices, for which data on s and o had actually been acquired. In the pKG, a statement, which is always true, has an annotation $\mathbb{P}(Y_p|s, o) = 1$, such as *(Munich, partOf, Bavaria)*, a statement that is always false has an annotation $\mathbb{P}(Y_p|s, o) = 0$, such as *(Munich, partOf, Belgium)*. A statement like *(Munich, hasAttribute, Sunny)* would get annotated with a probability somewhere between 0 and 1. Similarly, for unary statements, we get

$$\mathbb{P}(Y_{s,hasAttribute,\underline{o}}) \equiv \mathbb{P}(Y_{\underline{o}}|s) = \sum_{t} \mathbb{P}(Y_{\underline{o}}|s,t)\mathbb{P}(t|s).$$
(4)

The execution of those summations would be very expensive in an actual implementation. Instead, we learn parameterized models, coupled by parameter sharing. This approach is derived from an attention approach (see Appendix).

4.6 Semantic KG

The semantic KG (sKG) is the pKG with an IPM. The IPM models

$$\mathbb{P}(s,o) = \sum_{t} \mathbb{P}(s,o,t).$$
(5)

In an agent's sKG, we generate samples o^* from these distributions and then predict triple probabilities using the SPM. An agent's sKG is our mathematical model for a semantic memory. Figure 1 illustrates the relationships between the tKG, eKG, pKG, and sKG.

4.7 Generalized Statements

As discussed, for most predicates, the subject s is assumed to be an entity. We now generalize to the case that the subject can be a general concept $c \in C$. In particular, we define that $\mathbb{P}(Dog, hasAttribute, Black)$ stands for the probability that a randomly selected entity that belongs to the class Dog has the attribute Black.

We get, with $\underline{o} \in \mathcal{C}$ and $c \in \mathcal{B} \cup \mathcal{K}$ for the pKG

$$\mathbb{P}(Y_{c, hasAttribute, \underline{o}}) \equiv \mathbb{P}(Y_{\underline{o}}|c) = \frac{1}{\sum_{s' \in \mathcal{E}} \mathbb{P}(Y_c|s') \mathbb{P}(s')} \sum_{s' \in \mathcal{E}} \mathbb{P}(Y_{\underline{o}}|s') \mathbb{P}(Y_c|s') \mathbb{P}(s').$$

This would, e.g., define what is meant by $\mathbb{P}(Y_{\underline{o}}|c)$, i.e., an average over observations and entities. In an analog way we can derive $\mathbb{P}(Black, hasAttribute, Dog)$, indicating that if something is "Black" it might be a dog, with some probability. Thus generalized statements permit the description of what it means to be a dog or what it means that something is black. Similarly, we can define and formulate (*Dog, looksAt, Person*). Generalized statements are important for perception, but also for semantic memory, as will be discussed in Section 10. Again, the execution of the summations in the last equation will be replaced by a parameterized model, using an attention approach. In Figure 1, this would mean that the states of S and O include all concepts and not just entities.

Note, that a generalized statement corresponds to a probabilistic rule. Thus, the above expression is the probability that $\forall s : (s, hasAttribute, Black) \leftarrow (s, hasAttribute, Dog)$ is true.

5. A Bilayer Tensor Network (BTN)

5.1 Introduction

We describe now how the operations described in the last section can be implemented by an interaction of two layers (see Figure 2). One layer is the *r*-dimensional representation layer \mathbf{q} , where $r \in \mathbb{N}$ is the embedding dimension, i.e., the rank of the BTN approximation. \mathbf{q} reflects the cognitive state of the brain. The other one is the index layer \mathbf{n} with dimension $N_C + N_P + N_T$. The index layer contains one dimension or unit for each concept, for each predicate, and for each time instance. We also introduce a working memory layer \mathbf{h} , which supports the operations. In the following, we describe the implementations of layers and operations using the unfolded view in Figure 3. From a mathematical perspective, the models we are considering are generalized tensor networks.

5.2 The Bilayer Tensor Network (BTN): a Generalized Tensor Network

The probability tables from the last section, e.g., $\mathbb{P}(Y_{s,p,o,t})$ and $\mathbb{P}(s, o, t)$ can be represented by tensors. In many application domains, one works with reduced-rank tensor factorization models, e.g., to reduce parameter size, computational complexity, and generalization



Figure 2: Our model architecture consists of two main layers, the representation layer q and the index layer n. The working memory layer h realizes a short-term memory supporting the operations. The activation pattern of q reflects the cognitive state of the brain.

(Hackbusch, 2012). In standard approaches, tensor products of index embedding vectors are used, as in the Tucker model (a.k.a. tensor subspace approximation) or RESCAL (Nickel et al., 2011). In the canonical polyadic decomposition (CPD) and the tensor train models (a.k.a. matrix product states) only a small number of elements in the tensor product are considered and one achieves approximations with complexity linear in the order of the tensor (Hackbusch, 2012). Another way to reduce complexity is to employ neural networks, replacing the tensor products and leading to generalized tensor models. These approaches are known as Neural Tensor Networks (Socher et al., 2013), E-MLPs, ER-MLPs (Dong et al., 2014; Nickel et al., 2015a), and multiway neural networks (Baier et al., 2018). Our Bilayer Tensor Network (BTN) is another instance, where a recurrent neural network and an attention mechanism are employed.

5.3 The BTN for the tKG and the eKG

As other tensor networks, the BTN relies on embedding vectors $\mathbf{a}_s, \mathbf{a}_o, \mathbf{a}_t, \mathbf{a}_p \in \mathbb{R}^r$. Also, $t \in \mathcal{T}, s, o \in \mathcal{C}$, and $p \in \mathcal{P}^B$.

The SPM equations for predicting binary statements in the tKG are

$$\mathbb{P}(Y_{s,p,o,t}) \equiv \mathbb{P}(Y_p|s,o,t) = \operatorname{sig}\left(\mathbf{a}_p^{\top} \mathbf{g}(\mathbf{a}_o + \mathbf{g}(\mathbf{a}_s + \mathbf{g}(\mathbf{a}_t)))\right)$$
(6)

and for unary statements

$$\mathbb{P}(Y_{s,hasAttribute,\underline{o},t}) \equiv \mathbb{P}(Y_{\underline{o}}|s,t) = \operatorname{sig}\left(\mathbf{a}_{\underline{o}}^{\top}(\mathbf{a}_s + \mathbf{g}(\mathbf{a}_t))\right).$$
(7)

The eKG also requires an IPM. Assume, the agent queries time instance t^* . We get

$$\mathbb{P}(S=s|t^*) = \operatorname{softmax}_s^\beta \left(\mathbf{a}_s^\top \mathbf{g}(\mathbf{a}_{t^*}) \right).$$
(8)

Let s^* be a sample from that distribution. Then, for the object entity

$$\mathbb{P}(O = o|t^*, s^*) = \operatorname{softmax}_o^\beta \left(\mathbf{a}_o^\top \mathbf{g}(\mathbf{a}_{s^*} + \mathbf{g}(\mathbf{a}_{t^*})) \right).$$
(9)

Here, $\mathbf{g}(\cdot)$ is a nonlinear function. In our approach, we use

$$\mathbf{g}(\mathbf{q}) = W \operatorname{sig}(B \operatorname{sig}(V \mathbf{q}))$$

which performs computations in the hidden layer \mathbf{h} of the recurrent network. W, B, V are learned matrices.

Also, sig $(x) = 1/(1 + \exp(-x))$ is the logistic function and

$$\operatorname{softmax}_{i}^{\beta}(\mathbf{x}) = \frac{\exp\beta x_{i}}{\sum_{i'}\exp\beta x_{i'}}.$$
(10)

Here, β is an inverse temperature and can be used for making the response more or less selective.

5.4 The BTN for the pKG and the sKG

In the previous equations, we replace the time instance specific embedding \mathbf{a}_t by a constant embedding $\mathbf{\bar{a}}$. Thus, for the SPM, we get for binary statements

$$\mathbb{P}(Y_{s,p,o}) \equiv \mathbb{P}(Y_p|s,o) = \operatorname{sig}\left(\mathbf{a}_p^{\top}\mathbf{g}(\mathbf{a}_o + \mathbf{g}(\mathbf{a}_s + \mathbf{g}(\mathbf{\bar{a}})))\right)$$
(11)

and for unary statements

$$\mathbb{P}(Y_{s,hasAttribute,\underline{o}}) \equiv \mathbb{P}(Y_{\underline{o}}|s) = \operatorname{sig}\left(\mathbf{a}_{\underline{o}}^{\top}(\mathbf{a}_{s} + \mathbf{g}(\bar{\mathbf{a}}))\right).$$

This replaces the mixture models described in Section 4 and can be derived from the attention approach used in deep learning (Vaswani et al., 2017) (see the Appendix). One can think of $\bar{\mathbf{a}}$ as the embedding for some "neutral" time index. The IPM equations are modified accordingly. Given a query s^* , an object is sampled from $\mathbb{P}(O = o|s) =$ softmax^{β}_o ($\mathbf{a}_o^{\top} \mathbf{g}(\mathbf{a}_s + \mathbf{g}(\bar{\mathbf{a}}))$).

5.5 Algorithmic Implementation and Triple Serialization

Figure 3 illustrates the unfolded processing steps of the architecture shown in Figure 2. Algorithm 1 shows the implementations for the tKG and the pKG and Algorithm 2 for the eKG and the sKG. Here, \mathbf{q}_T , $\mathbf{\tilde{q}}_S$, \mathbf{q}_S , $\mathbf{\tilde{q}}_O$, \mathbf{q}_O , $\mathbf{\tilde{q}}_P$, and \mathbf{q}_P , are the activations of the representation layer at different processing steps.

Algorithm 1 describes the SPMs and produces triple probabilities for the unary and binary statements involving the queried entities, and, for the tKG, time instance. Algorithm 2 includes the IPMs and also produces a sample o^* for the object, and, in the case of the eKG, also a sample s^* for the subject. In line 6 and line 16 we generate categorical distributions, from which we sample. We call this transformation from a logistic transfer function to a softmax transfer function softmax-transformation. For example, $s^* = Sparky$ and and $o^* = Jack$ might be samples produced by the IPM, The outputs \mathbf{n}_O and \mathbf{n}_P are summary activation patterns describing the results. To produce likely triple statements, we can apply again the softmax-transformation. Let *Black*, and *looksAt* be samples produced in the softmax-transformation of the unary and binary labels. Then the generated triples might be (Sparky, hasAttribute, Dog), (Sparky, hasAttribute, Black), and (Sparky, looksAt, Jack).

A	Algorithm 1: The SPM for the tKG and the pKG.	
	Input: t, s, o for the tKG or only s, o for the pKG	
	Output: Probabilistic predictions for unary and binary statements	
1	switch tKG do	
2	$\mathbf{q}_T \leftarrow \mathbf{a}_t$	
3	end	
4	switch pKG do	
5	$\mathbf{q}_T \leftarrow \mathbf{ar{a}}$	
6	end	
7	$\tilde{\mathbf{q}}_S \leftarrow \mathbf{g}(\mathbf{q}_T)$	
8	$\mathbf{n}_S \leftarrow \mathbf{e}^s$	
9	$\mathbf{q}_S \leftarrow \mathbf{a}_s + \mathbf{ ilde{q}}_S$	
10	$\forall \underline{o} \in \mathcal{C} : n_{\underline{O}}(\underline{o}) \leftarrow \operatorname{sig}\left(\mathbf{a}_{\underline{o}}^{\top} \mathbf{q}_{S}\right)$	⊳ Unary labels
11	$\mathbf{\tilde{q}}_O \leftarrow \mathbf{g}(\mathbf{q}_S)$	
12	$\mathbf{n}_O \leftarrow \mathbf{e}^o$	
13	$\mathbf{q}_O \leftarrow \mathbf{a}_o + \mathbf{ ilde{q}}_O$	
14	$\mathbf{\tilde{q}}_P \leftarrow \mathbf{g}(\mathbf{q}_O)$	
15	$\mathbf{q}_P \leftarrow \mathbf{ ilde q}_P$	
16	$\forall p \in \mathcal{P}^B : n_P(p) \leftarrow \operatorname{sig}\left(\mathbf{a}_p^\top \mathbf{q}_P\right) \qquad \triangleright$	Binary labels
17	$\mathbf{return} \ \forall \underline{o} \in \mathcal{C} : n_{\underline{O}}(\underline{o}), \forall p \in \mathcal{P}^B : n_P(p)$	

5.6 Discussion

An important property of the BTN is that, in the algorithmic implementation and at any iteration step, only a fixed-sized vector needs to be applied to the representation layer. We can relate this to brain function: Since the representation layer might occupy a significant portion of the brain, leaving no space for a second concurrent representation, we call this property the "single brain hypothesis" (discussed in more detail in Section 7). Also, due to the nonlinearity of $\mathbf{g}(\mathbf{a})$, one breaks the symmetry between subject and object embedding. When we replace the nonlinearity by a linear function, the model cannot distinguish between subject and object. Simpler models, like TransE (Bordes et al., 2013) or DistMult (Yang et al., 2014) have limited expressibility. We did not select more standard models for several reasons. First, most tensor factorizations, such as CPD, the Tucker decomposition, the

Algorithm 2: The BTN for the eKG and the sKG.

Input: t^* for the eKG) or s^* for the sKG **Output:** s^* and o^* and probabilistic predictions for unary and binary statements 1 switch eKG do $\mathbf{n}_T \leftarrow \mathbf{e}^{t^*}$ $\mathbf{2}$ \triangleright Initialization of time index $\mathbf{q}_T \leftarrow \mathbf{a}_{t^*}$ 3 $\tilde{\mathbf{q}}_S \leftarrow \mathbf{g}(\mathbf{q}_T)$ $\mathbf{4}$ $\forall s \in \mathcal{E} : n_S(s) \leftarrow \operatorname{sig}(\mathbf{a}_s^\top \tilde{\mathbf{q}}_S)$ $\mathbf{5}$ Sample $s^* \sim \operatorname{softmax}_s^\beta(\operatorname{logit}(\mathbf{n}_S(s)))$ 6 \triangleright Sample a subject 7 end 8 switch sKG do $\mathbf{q}_T \leftarrow \mathbf{\bar{a}}$ 9 10 end 11 $\mathbf{n}_S \leftarrow \mathbf{e}^{s^*}$ 12 $\mathbf{q}_S \leftarrow \mathbf{a}_{s^*} + \tilde{\mathbf{q}}_S$ **13** $\forall \underline{o} \in \mathcal{C} : n_O(\underline{o}) \leftarrow \operatorname{sig} \left(\mathbf{a}_{o}^{\top} \mathbf{q}_S \right)$ \triangleright Unary labels 14 $\tilde{\mathbf{q}}_O \leftarrow \mathbf{g}(\mathbf{q}_S)$ 15 $\forall o \in \mathcal{E} : n_O(o) \leftarrow \operatorname{sig}\left(\mathbf{a}_o^\top \tilde{\mathbf{q}}_O\right)$ 16 sample $o^* \sim \operatorname{softmax}_o^{\beta}(\operatorname{logit}(\mathbf{n}_O(o)))$ \triangleright Sample an object 17 $\mathbf{n}_{O} \leftarrow \mathbf{e}^{o^{*}}$ 18 $\mathbf{q}_O \leftarrow \mathbf{a}_{o^*} + \mathbf{\tilde{q}}_O$ 19 $\tilde{\mathbf{q}}_P \leftarrow \mathbf{g}(\mathbf{q}_O)$ 20 $\mathbf{q}_P \leftarrow \tilde{\mathbf{q}}_P$ **21** $\forall p \in \mathcal{P}^B : n_P(p) \leftarrow \operatorname{sig}\left(\mathbf{a}_n^\top \mathbf{q}_P\right)$ \triangleright Binary labels **22 return** $s^*, o^*, \forall \underline{o} \in \mathcal{C} : n_O(\underline{o}), \forall p \in \mathcal{P}^B : n_P(p)$

tensor train, and RESCAL, require the excessive multiplication of factors; multiplication is an operation that is not easily implemented in biological hardware. Second, standard tensor networks are functions of several embedding vectors which would need to be presented concurrently; this would violate our single brain hypothesis. Also, our model clearly is compositional (in the sense of (Poggio et al., 2020)), which is a property that is used to explain the superior performance of deep architectures.

Another important point to notice is that, although statements are initially assumed to be independent (see Section 4), by a shared parameterization —as in most embedding models for KGs— they become dependent in training. Since we are using regularizers, one can interpret the training as finding parameters that correspond to Bayesian MAP (maximum a posteriori) parameter estimates.

A detailed analysis of our KG models in the context of current discussions in cognitive computational neuroscience follows in Sections 7, 8, 9, 10, and 11.



Figure 3: **tKG**: For the tKG's SPM, we set $\mathbf{n}_T = \mathbf{e}^{(t)}$, $\mathbf{n}_S = \mathbf{e}^{(s)}$, and $\mathbf{n}_O = \mathbf{e}^{(o)}$ (orthonormal basis vectors, i.e., one-hot vectors). **eKG**: As in the tKG, but only $\mathbf{n}_T = \mathbf{e}^{(t)}$ is set; *s* and *o* are not set but sampled from the IPM. **pKG**: As the tKG, only that we set $\mathbf{n}_T = \mathbf{e}^{(0)}$ and thus $\mathbf{q}_T = \bar{\mathbf{a}}$. **sKG**: As the pKG, but *s* and *o* are not set but sampled from the IPM. **pKG**: how the structures in orange are added. In episodic attention, instead of sampling, we marginalize *t* and in semantic attention, we marginalize *s*, resp. *o*.

6. The Perception Experience

6.1 The IPM and the SPM for Perception

We consider the following setting: At a new time instance t' the agent encounters a new $scene_{t'}$. Then a bounding box BB_{sub} is segmented whose content describes a visual entity s'. The visual entity s' might be a known entity, or it might be a novel entity, not yet known to the agent. The agent might also detect a second entity o' with bounding box BB_{obj} in the scene and might be interested in its relationship to s'. The content of a third bounding box BB_{pred} describes the predicate. The goal is now to produce statements that are likely true, considering the context of the scene. Algorithm 3 describes the processing steps. See also Figure 3.

We first consider the IPM. For the time instance, we get

$$\mathbb{P}(T = t | scene_{t'}) = \operatorname{softmax}_{t}^{\beta} \left(\mathbf{a}_{t}^{\top} \mathbf{f}(scene_{t'}) \right).$$

Here, $\mathbf{f}(\cdot)$ are representation vectors derived from visual inputs realized by a deep convolutional neural network (DCNN) (see the Appendix). Let t^* be a sample from that distribution (Algorithm 3, line 4).

For the subject, we get

$$\mathbb{P}(S = s | t^*, scene_{t'}, BB_{sub}) = \operatorname{softmax}_s^\beta \left(\mathbf{a}_s^\top (\mathbf{f}(BB_{sub}) + \mathbf{g}(\mathbf{a}_{t^*} + \mathbf{f}(scene_{t'}))) \right).$$

Let s^* be a sample from that distribution (line 15). For the object, we get

$$\mathbb{P}(O = o|t^*, s^*, scene_{t'}, BB_{sub}, BB_{obj}) =$$

softmax_o^β
$$\left(\mathbf{a}_{o}^{\top} (\mathbf{f}(BB_{obj}) + \mathbf{g}(\mathbf{a}_{s^{*}} + \mathbf{f}(BB_{sub}) + \mathbf{g}(\mathbf{a}_{t^{*}} + \mathbf{f}(scene_{t'})))) \right).$$

Let o^* be a sample from that distribution (line 27). A scene is analyzed by repeating the sampling process for a fixed set of bounding boxes and then for all bounding boxes in a scene.

The SPM formulas for unary prediction are (line 23)

$$\mathbb{P}(Y_{s^*,hasAttribute,\underline{o},t^*}|BB_{sub},scene_{t'}) \equiv \mathbb{P}(Y_{\underline{o}}|s^*,t^*,BB_{sub},scene_{t'})$$
$$= \operatorname{sig}\left(\mathbf{a}_{\underline{o}}^{\top}(\mathbf{a}_{s^*} + \mathbf{f}(BB_{sub}) + \mathbf{g}(\mathbf{f}(scene_{t'}) + \mathbf{a}_{t^*}))\right)$$

and for binary prediction are (line 37)

$$\mathbb{P}(Y_{s^*,p,o^*,t^*}|BB_{sub}, BB_{obj}, BB_{pred}, scene_{t'}) \equiv \mathbb{P}(Y_p|s^*, o^*, t^*, BB_{sub}, BB_{obj}, BB_{pred}, scene_{t'}) =$$

sig $\left(\mathbf{a}_p^{\top} \left[\mathbf{f}(BB_{pred}) + \mathbf{g}\left(\mathbf{a}_{o^*} + \mathbf{f}(BB_{obj}) + \mathbf{g}\left(\mathbf{a}_{s^*} + \mathbf{f}(BB_{sub}) + \mathbf{g}\left(\mathbf{a}_{t^*} + \mathbf{f}\left(scene_{t'}\right)\right)\right)\right]\right).$

Essentially the processing is analog to Algorithm 2, except that we also integrate visual inputs from the overall scene and from the contents of the bounding boxes. See also Figure 3. It is important to realize that the visual inputs only makes predictions about visual predicates (e.g., *nextTo*, *on*, ...).

6.2 Episodic and Semantic Attention

Motivated by the attention approach used in deep learning (Vaswani et al., 2017), we can derive predictions that do not commit to particular instances. With parallel hardware, e.g, brainware, the serial sampling process can be replaced by a computational step, which can be executed in parallel.

The attention approach for the time instance (episodic attention) (Algorithm 3, line 9), becomes

$$\mathbf{a}_T(scene) = \sum_{t=1}^{N_T} \mathbf{a}_t \mathbb{P}(t|scene) = \sum_{t=1}^{N_T} \mathbf{a}_t \operatorname{softmax}_t^\beta(\operatorname{logit}(\mathbf{n}_T)).$$
(12)

Similarly, we can use the attention approach for entities (semantic attention). The semantic attention for the subject (line 20) is

$$\mathbf{a}_{S}(BB_{sub}, scene) = \sum_{s} \mathbf{a}_{s} \mathbb{P}(s|t, scene, \mathbf{f}(BB_{sub})) = \sum_{s} \mathbf{a}_{s} \operatorname{softmax}_{s}^{\beta} \left(\operatorname{logit}(\mathbf{n}_{S}) \right).$$
(13)

Similarly, We can marginalize over o^* .

Algorithm 3: The BTN for Perception

Input: scene, BB_{sub} , BB_{obj} , BB_{pred} **Output:** t^*, s^*, o^* and probabilistic predictions for unary and binary statements 1 $\tilde{\mathbf{q}}_T \leftarrow \mathbf{f}(scene)$ 2 $\forall t \in \mathcal{T} : n_T(t) \leftarrow \operatorname{sig}(\mathbf{a}_t^\top \tilde{\mathbf{q}}_T)$ 3 switch SamplingMode do Sample $t^* \sim \operatorname{softmax}_t^\beta(\operatorname{logit}(\mathbf{n}_T))$ $\mathbf{4}$ $\mathbf{n}_T \leftarrow \mathbf{e}^{t^*}$ 5 6 $\mathbf{q}_T \leftarrow \mathbf{a}_{t^*} + \tilde{\mathbf{q}}_T$ 7 end 8 switch EpisodicAttention do $\mathbf{a}_T(scene) \leftarrow \sum_{t=1}^{N_T} \mathbf{a}_t \mathbb{P}(t|scene) = \sum_{t=1}^{N_T} \mathbf{a}_t \text{softmax}_t^\beta \left(\text{logit}(\mathbf{n}_T) \right)$ 9 $\mathbf{q}_T \leftarrow \mathbf{a}_T(\mathit{scene}) + \mathbf{\tilde{q}}_T$ 10 11 end 12 $\tilde{\mathbf{q}}_S \leftarrow \mathbf{f}(BB_{sub}) + \mathbf{g}(\mathbf{q}_T)$ 13 $\forall s \in \mathcal{E} : n_S(s) \leftarrow \operatorname{sig}\left(\mathbf{a}_s^\top \tilde{\mathbf{q}}_S\right)$ 14 switch SamplingMode do Sample $s^* \sim \operatorname{softmax}_s^\beta(\operatorname{logit}(\mathbf{n}_S))$ $\mathbf{15}$ $\mathbf{n}_S \leftarrow \mathbf{e}^{s^*}$ $\mathbf{16}$ $\mathbf{q}_S \leftarrow \mathbf{a}_{s^*} + \mathbf{\tilde{q}}_S$ $\mathbf{17}$ 18 end 19 switch SemanticAttention do $\mathbf{a}_{S}(BB_{sub}, scene) \leftarrow \sum_{s} \mathbf{a}_{s} \mathbb{P}(s|t, scene, \mathbf{f}(BB_{sub})) = \sum_{s} \mathbf{a}_{s} \operatorname{softmax}_{s}^{\beta}(\operatorname{logit}(\mathbf{n}_{S}))$ $\mathbf{20}$ $\mathbf{q}_{S} \leftarrow \mathbf{a}_{S}(BB_{sub}, scene) + \mathbf{\tilde{q}}_{S}$ $\mathbf{21}$ 22 end **23** $\forall \underline{o} \in \mathcal{C} : n_O(\underline{o}) \leftarrow \operatorname{sig}\left(\mathbf{a}_o^\top \mathbf{q}_S\right) = \mathbb{P}(Y_o | s^*, t^*, BB_{sub}, scene)$ \triangleright Unary labels 24 $\tilde{\mathbf{q}}_O \leftarrow \mathbf{f}(BB_{obj}) + \mathbf{g}(\mathbf{q}_S)$ **25** $\forall o \in \mathcal{E} : n_O(o) \leftarrow \operatorname{sig}\left(\mathbf{a}_o^{\top} \tilde{\mathbf{q}}_O\right)$ 26 switch SamplingMode do Sample $o^* \sim \operatorname{softmax}_o^\beta(\operatorname{logit}(\mathbf{n}_O))$ $\mathbf{27}$ $\mathbf{n}_{O} \leftarrow \mathbf{e}^{o^{*}}$ $\mathbf{28}$ $\mathbf{q}_O \leftarrow \mathbf{a}_{o^*} + \mathbf{\tilde{q}}_O$ $\mathbf{29}$ 30 end 31 switch SemanticAttention do $\mathbf{a}_O(BB_{sub}, BB_{obj}, scene) \leftarrow \sum_o \mathbf{a}_o \operatorname{softmax}_o^\beta(\operatorname{logit}(\mathbf{n}_O))$ 32 $\mathbf{q}_O \leftarrow \mathbf{a}_O(BB_{sub}, BB_{obj}, scene) + \mathbf{\tilde{q}}_O$ 33 34 end **35** $\tilde{\mathbf{q}}_P \leftarrow \mathbf{f}(BB_{pred}) + \mathbf{g}(\mathbf{q}_O)$ **36** $\mathbf{q}_P \leftarrow \tilde{\mathbf{q}}_P$ **37** $\forall p \in \mathcal{P}^B : n_P(p) \leftarrow \operatorname{sig}\left(\mathbf{a}_n^\top \tilde{\mathbf{q}}_P\right)$ \triangleright Binary labels **38 return** $t^*, s^*, o^*, \forall \underline{o} \in \mathcal{C} : n_O(\underline{o}), \forall p \in \mathcal{P}^B : n_P(p)$

Attention is fast and parallel, whereas sampling is a serial process. The main difference to previous approaches to attention (Weston et al., 2014; Sukhbaatar et al., 2015; Vaswani et al., 2017) is that in our approach, attention is evaluated with respect to *stored* embeddings from episodic and semantic memory. For a derivation of the attention approximations, see the Appendix. The attention approach is the default in all perception experiments.

6.3 Triple Serialization and sameAs Reasoning

Triple serialization with semantic attention —using the activation in $\mathbf{n}_{\underline{O}}$ and the softmaxtransformation— would generate triples like (s', sameAs, Sparky), (s', type, Dog), (s', color, Black), (s', looksAt, o'), (o', sameAs, Jack).

In sampling, the model makes a clear commitment to a hypothesis in \mathbf{n}_S , e.g., that (s', sameAs, Sparky), (o', sameAs, Jack) are true. Then, with sameAs-reasoning we can generate (Sparky, type, Dog), (Sparky, color, Black), (Sparky, looksAt, Jack). These are statements that can be recalled in episodic and semantic memory. If an entity is novel and relevant, a new index is formed.

6.4 Generalized Statements

The index layer **n** contains indices for concepts (entities, classes, attributes), and time instances. These subsets are activated at different processing steps. So far, we assumed that entities were activated as \mathbf{n}_S (Algorithm 3, line 13) and unary labels at \mathbf{n}_Q (line 23). We now consider that all concepts can be activated at both \mathbf{n}_S and \mathbf{n}_Q .

This allows us, e.g., to obtain maps from a concept or index in \mathbf{n}_S to concepts in \mathbf{n}_Q . The resulting triples would correspond to the generalized statements discussed in Subsection 4.7. In perception, this permits us to generate not just the triples (Sparky, hasAttribute, Black) and (Sparky, looksAt, Jack), but also (Dog, hasAttribute, Black) and (Dog, looksAt, Person). In the sKG, the agent can now evaluate a statement such as $\mathbb{P}(Y_{Dog, \ color, \ Black})$ indicating how many dogs are black. We will illustrate the usefulness of generalized statements in the sKG in Section 10.

7. Perception, Language and a Foundation for Consciousness

In this and the following sections, we present experimental results. Here, we focus on perception, and in the following sections on engrams, episodic memory, semantic memory, and learning. Intertwined with the experiments, we make the link to cognitive computational neuroscience and formulate concrete hypotheses as propositions.

In discussions relating to neuroscience, we do not focus on *anatomical architectures* — beyond relating our model to discussions about the operations of different brain regions (Figure 4)— but on potentially biologically plausible *functional architectures*. For example, it is unclear how, anatomically, direct connections between the index layer and the representation layer could instantaneously be realized in the memorization of a new episode. There is a long tradition in cognitive computational neuroscience to make this distinction between anatomical brain structure, e.g., the actual anatomical structure of the biological neural network, and functional architectures of the cortex, where the latter might be quickly



Figure 4: Hypotheses about the locations of functions in the brain: Indices are formed in the medial temporal lobe (MLT). Indices for concepts might be consolidated in hubs like the anterior temporal lobe (ATL) including the temporal pole and time indices in the prefrontal cortex. Some papers also see a greater role of the posterior parietal cortex, as part of a parietal memory network (PMN). MTL and other structures, like the medial prefrontal cortex (mPFC), are involved in the consolidation of episodic memories. The brain's working memory involves the prefrontal parietal network (PPN). The representation layer is distributed across the neocortex, including sensory and motor centers.

adaptable (Friston et al., 1995; van den Heuvel and Sporns, 2013; Bassett and Sporns, 2017; Sporns, 2018; Leopold et al., 2019).

7.1 Data Set

We tested our approach experimentally using an augmented version of the VRD dataset (Lu et al., 2016). In the past, the VRD dataset has been the basis for many research works on visual relationship detection. Each visual entity is labeled as belonging to one out of 100 classes. Binary statements are annotated with 70 labels with 37,993 binary statements in total. We followed other works and assigned 4000 images to the training set and 1000 images to the test set. The training images contain overall 26,430 bounding boxes, thus on average 6.60 per image.

We generated a first derived dataset, VRD-E (for VRD-Entity), with additional labels for each visual entity. First, each entity in each image obtains an individual entity index (or name). The 26,430 bounding boxes in the training images describe 26,430 entity indices. Second, we used concept hierarchies from WordNet (Fellbaum, 2010), see Figure 5. Each



Figure 5: Ontologies. Top: Class ontology. Bottom: Attribute ontology.

entity is assigned exactly one basis class (or *B-Class*) from VRD, e.g., *Dog*, one parent class (or *P-Class*), e.g., *Mammal*, and one grandparent class (or *G-Class*), e.g., *LivingBeing*. At any level, we use the default class *Other* for entities that cannot be assigned to a WordNet concept. We perform subclass reasoning in the training data and label an entity with its entity index, its *B-Class*, *P-Class*, and *G-Class*. Thus a visual entity might be Sparky, which is a *Dog*, a *Mammal* and a *LivingBeing*.

In addition, we used pretrained attribute classifiers (Anderson et al., 2018), (Tan, 2021) to label visual entities using the attribute ontology shown in Figure 5. Each visual entity obtains exactly one color (including the color *Other*), and exactly one activity attribute, e.g., a person can be standing or running. We also introduce the attribute labels *Young* and *Old* which are randomly assigned, such that these can only be predicted for test entities that already occurred in training, but not for novel entities.

Furthermore, we introduce the nonvisual, or hidden, attribute label *Dangerous* to all living things and *Harmless* to all nonliving things. We do not use these labels in perceptual training; we use them instead to demonstrate the effect of semantic memory on label prediction for entities and for attribute labels.

In summary, every visual entity receives one entity index and 8 positive attribute labels (entity index, *B-Class*, *P-Class*, G-Class (*LivingBeing*), Age(Y/O), *Dangerous/Harmless*, Color, Activity).

Based on the VRD-E dataset, we generate the VRD-EX dataset. Here, we distort each image in the training data set, which generates another 4000 training images⁴. We utilized an open library to distort the image (Jung et al., 2020). To obtain a distorted image, we apply a sequence of transformations including translation, rotation, shearing, and horizontal flipping of the original image (Bloice et al., 2017). Each transformation is associated with a probability of actually using it. When the operation has coefficients, e.g., the displacement of translation, a random value within a reasonable range is generated for the operation. Thus VRD-EX has 8000 training images. Then we perform another distortion on each



Figure 6: Generation of VRD-EX images. Left: an original VRD image. Center: a distorted VRD-EX image that is assigned to the training set. Right: a distorted VRD-EX image that is assigned to the test set.

original image and generate a set of another 4000 test images⁴. Note that in these new 4000 test images, every visual entity has already occurred in the training set twice. See Figure 6.

All entities that occur in the images, as well as all other concepts, form the nodes in the KGs. In addition, we introduce nonvisual entities, i.e., entities which are only part of the KGs but do not occur in any image. In the experiments, we relate visual entities to those hidden entities, e.g., by the predicate ownedBy or the predicate lovedBy. For example, each visual dog is owned by a person who is not in any scene. Table 1 shows the overall statistics.

Dataset	Training	Test	#BB	# VisEnt	#BinStat	# Attr/Ent
	Images	Images	Train	Train	Train	Train
VRD (Lu et al., 2016)	4000	1000	26430	26430	30355	1
VRD-E ntity	4000	1000	26430	26430	30355	8
$\mathbf{VRD}\text{-}\mathbf{EX}$ tended	7737	3753	50910	26430	59095	8

Table 1: Statistics of the datasets VRD-E and VRD-EX. Attr/Ent stands for the average number of unary labels per instance. Overall, 15% of the lables are "Others".

We used Faster R-CNN for the object detection backbone employed before the representation layer. The VGG-19 architecture within this framework (Simonyan and Zisserman, 2014) is pre-trained on ImageNet (Russakovsky et al., 2015) and fine-tuned to our data. In all of our experiments, we used rank r = 4096 as the dimension of the representation layer. The training was performed using the Adam optimizer (Kingma and Ba, 2014). For evaluation, we consider top-1 accuracy for unary labels and Hits@k for binary labels and sampling of entities. Hits@k is defined as the fraction of true entities that appear in the top k ranked entities.

^{4.} Due to distortion, some objects and images are discarded, resulting in a reduced number of samples.



Figure 7: Scene on a starship. The captain and Spooky observe the scene on the left. The right images stands for a recent episodic memory. Episoidc memories are displayed with soft edges.

7.2 Fast and Simple Perception

Captain: Spooky, what is that in front of us? — Spooky: Captain, it is an unidentified object, no wait, it is a dog. It is a brown dog. It is huge. (See Figure 7)

Proposition 1 Fast Perception: Fast perception analyses a scene as a global pattern and might trigger an action without the explicit analysis of regions of interests (i.e., bounding box content). It requires the representation layer but might not require an index layer.

In our model, it would be a scene analysis, solely based on $\mathbf{f}(scene_{t'})$. As an example, if the overall scene appears dangerous, the agent might react quickly, without a deeper analysis of bounding box content and possibly without involving the index layer.

Proposition 2 Simple Perception: Simple perception infers unary labels for attributes and classes, describing the entities in a scene, purely based on scene inputs. Simple perception does not have a notion of a permanent individual entity or of a past time instance and is completely perceptual. Simple perception requires indices for attributes and classes in the index layer, together with their associated embeddings.

Simple perception is about the prediction of unary labels for attributes and classes. Simple perception concerns the processing path $BB_{sub} \rightarrow \tilde{\mathbf{q}}_S \rightarrow \mathbf{q}_S \rightarrow \mathbf{n}_{\underline{O}}$. and is about the attribute and concept indices in layer $\mathbf{n}_{\underline{O}}$. In our model, simple perception would be realized by the direct connection from scene input, via the representation layer, to the indices for attributes and classes. $\mathbf{n}_{\underline{O}}$ provides a holistic view. Triple serialization would enable triples like (s', type, Dog), (s', color, Black). Thus simple perception might be the perception of a rather primitive, non-social animal. Simple perception is about the here and now, is neither supported by episodic nor semantic memory. A complete scene can be analyzed by sequentially and individually analyzing all entities in the scene. Due to this sequential process, simple perception is slower than fast perception.

Our perception experiments are all based on Algorithm 3. Simple perception is labeled as "P-Simple" in the following tables. The third and the sixth rows in Table 2 show results on simple perception. The results on VRD-E are quite competitive. The performance is improved in VRD-EX, likely due to some form of memorization by overfitting since the same entities occur in the training set and in the test set.

			Unary labels (accuracy)						
	Model	Entity	B-Class	P-Class	G-Class	Y/O	Color	Activity	Average
VRD-E	Р	-	80.96	87.90	94.62	49.67	68.57	83.40	77.52
	P-Max	-	80.47	88.01	94.50	49.14	68.55	83.12	77.30
	P-Simple	-	80.03	86.86	94.04	49.93	68.03	83.63	77.09
VRD-EX	Р	88.42	95.30	96.71	98.27	92.84	94.06	97.33	95.75
	P-Max	88.60	95.57	96.92	98.27	93.60	94.43	97.42	96.03
	P-Simple	-	92.83	94.12	96.82	79.74	86.40	93.06	90.50

Table 2: Unary label prediction in perception $(\mathbf{n}_{\underline{O}})$. The column labeled "Entity" evaluates if the right entity is recognized. The columns labeled "B-Class, P-Class, G-Class" are class labels and the columns labeled "Y/O, Color, Activity" are attribute labels. Average refers to the average over all columns. "P" indicates standard perception which uses semantic attention. "P-Max" stands for the sampling approach using the index with maximum activation, instead of semantic attention. "P-Simple" does not have instance representations. On the <u>VRD-E</u> data set, where each entity is novel, "P" shows the best results. Not surprisingly, "P-Simple" is also quite competitive. On the <u>VRD-EX</u> data set, where each entity is known, "P-Max" shows the best results, since it can recognize specific entities. In particular the attribute label "Y/O" can only be learned for already known entities. Not surprisingly, "P-Simple" is significantly worse, since it does not have a notion of an individual entity, although overfitting leads to better results than with the VRD-E data.

7.3 Unary Perception

Captain: Spooky, do we know that dog? — Spooky: Captain, yes, of course, it is Sparky!

Proposition 3 Unary Perception: The introduction of indices for entities in the index layer permits the recognition of specific known entities and this permits the retrieval of specific background information. The sampling of entity indices is the basis for the semantic memory experience (see Section 10).

Unary perception adds processing step \mathbf{n}_S , which contains the entity indices, and also adds entity indices in \mathbf{n}_Q . Also, unary perception adds the processing path $\tilde{\mathbf{q}}_S \to \mathbf{n}_S \to \mathbf{q}_S$.

If relevant, the visual entities s' and o' can be related to existing entity indices, in the example, with the index for *Sparky*. With (s', sameAs, Sparky), sameAs-reasoning can generate (*Sparky*, type, Dog), (*Sparky*, color, Black). These statements can be retrieved in episodic and semantic memory. If an entity is novel and relevant, a new index can be formed.

The results in Table 2 show that on the VRD-E data set with novel entities in the test set, perception with instance representations ("P") shows the best results, although simple perception ("P-Simple") is quite competitive.

On the VRD-EX data set with known entities in testing, "P-Max" is best, where the algorithm could "remember" past encounters of the same entities. Here, "P-Simple" is not competitive.

7.4 Binary Perception and Working Memory

Captain: Spooky, I can see that there is more! — Spooky: Captain, Sparky is on a surfboard, and a person is grabbing Sparky!

As the example demonstrates, to really capture the content of a scene, it is important to understand the relationships between the scene entities.

Proposition 4 Visual Relationship Perception: In visual relationship perception, indices for binary labels are introduced in the index layer. To decode binary statements, visual relationship perception requires the repeated activation of the index layer and representation layer in synchrony with foci of attention and enables the agent to analyze relationships between concepts. With a working memory, relationship perception improves considerably.

The indices for binary labels are represented in \mathbf{n}_P . When analyzing the relationships between entities, one needs an additional storage facility, since, following our single brain hypothesis, the brain only possesses one representation layer. As illustrated in Figure 2 and Figure 3, we propose that this functionality is represented by working memory.

Table 3 shows results from visual relationship perception. For the binary labeling with novel entities on the VRD-E data, the approach without specific entity representations shows best results. The performance of the latter is even quite competitive for the VRD-EX data set, which indicates that it is not as important to represent individual entities in this task. An explanation might be that visual binary labels are more varying than unary labels and can well be predicted from class labels.

In Table 4 we compare our model with other visual relationship detection methods. In the methods from literature, only binary labels are tested, with one class label for each entity. In a zero-shot situation, where the triple *(subject-class, predicate, object-class)* never occurred in training, our approach achieved a recall score of 81.61%, which is much better than the result from the BFM with 76.05%. In summary, our approach gives competitive results overall and gives superior results for zero-shot binary labeling.

Figure 8 illustrates perception with unary labels and visual and nonvisual binary statements.

		Binary	labels
	Model	@10	@1
VRD-E	Р	92.45	47.94
	P-Max	92.33	47.98
	P-noI	92.96	48.43
	P-noWM	85.45	31.68
VRD-EX	Р	98.96	75.94
	P-noI	98.65	67.36

Table 3: Visual relationship perception. Prediction of the binary labels. As the results for "P-noWM" indicate, working memory is essential for binary label prediction. In "P-noI", we have representations for attributes and classes in \mathbf{n}_S but not for entities. For the VRD-E data, entity representations do not improve results. For known entities (VRD-EX), entity indices permit some memorization and improve performance.

Model	ph	z-s-ph	rl	z-s-rl
Р	24.26	8.47	93.31	81.09
P-noI	23.54	9.41	93.15	80.84
P-noInoWM	14.22	6.50	84.16	67.75
P -no $scene_t$	24.19	8.55	93.03	79.98
BFM (Baier et al., 2017)	25.11	7.96	93.81	76.05
Approach in (Tresp and Ma, 2016)	23.45	10.95	93.32	78.79

Table 4: Visual relationship perception. We compare binary labeling with methods published in literature using the original <u>VRD</u> data set. *Phrase (ph)* shows the recall of binary labels, where also the extracted bounding box contents are evaluated. The *binary relational label (rl)* shows the recall of the binary label given the ground truth class of subject and object. *z-s-ph* and *z-s-rl* denote zero-shot performance for triples that did not occur in the training set. Our proposed model "P" is superior in the last task. Also obvious is the importance of a working memory. In "P-no*scenet*" we only used bounding box content but no overall scene information. Clearly, overall scene information is important for a good performance.



Figure 8: Illustration of perception with known entities (<u>VRD-EX</u>). The left bounding box is identified (sampled) as s' = s* = 24470 = Sparky (n_S). Highly ranked unary labels are: Dog, Mammal, LivingBeing, Young, White, OtherActivity (n_O). Highly ranked unary labels for the second bounding box (24471) are: Bench, Furniture, NonLivingBeing, Old, OtherColor, OtherActivity. Sampled binary statements are: (Dog, sitsOn, Bench), (LivingBeing, on, Furniture), (Mammal, sitsOn, Old), (White, sitsOn, Bench). We also indicate how perception can be supported by the semantic memory experience. The latter adds binary statements to entities, not in the scene: (Sparky, ownedBy, Jack(26675)), (Sparky, lovedBy, Mary(26676)), where Jack and Mary are not on the scene, but in the agent's sKG. The semantic memory experience will be further discussed in Section 10.

7.5 Bi-directional Modeling

The visual entities in a scene form a multi-relational graph and message passing might be employed to improve direct and binary labeling. We implement a simple form of message passing, where we generate samples s^* for visual entity s' when s' assumes the role of the subject and o^* when it assumes the role of an object. Figure 9 illustrates the concept and Table 5 shows numerical results, which demonstrates that message passing, the key to graph neural network approaches for scene graph modeling (Sharifzadeh et al., 2020), can be performed within our framework.

Figure 9 shows an example where our bi-directional message passing improves entity recognition. Experimental numerical results are shown in Table 5, showing an advantage of bi-directional message passing.

Proposition 5 Entity Indices and Scene Graph Labeling: To analyze the visual scene graph, one needs indices for the entities in the scene; for perception, these indices only need to live as long as the scene input persisted, but then might have evolved into permanent indices and embeddings for entities.

As we will discuss later, unique identifiers for scene inputs are prerequisites for both episodic and semantic memory. .

			Unary labels (top-1 accuracy)						
Data	Method	Entity	B-Class	P-Class	G-Class	Y/O	Color	Activity	Avg
VRD-E*	Uni-dir.	-	72.59	83.46	94.24	50.41	64.16	92.56	76.23
	Bi-dir.	-	73.50	84.53	95.04	50.56	64.37	92.75	76.79
VRD-EX*	Uni-dir.	87.61	87.26	90.93	95.53	78.46	79.86	93.66	89.05
	Bi-dir.	88.25	88.04	91.80	96.37	79.10	80.38	93.83	90.18

Table 5: Bi-directional message passing in perception. We use a trained perception model and evaluate its classification performance under two different settings. The first row (uni-directional) corresponds to the case that each entity only assumes a role of the subject (standard). The second row (bi-directional) is based on aggregated predictions of an entity when it assumes both the role of the subject and the object (in different samples). <u>VRD-E*</u> is a richer version of VRD-E that completes the missing inverse relationships in the test set (but not in the training set). Similarly for <u>VRD-EX*</u>. On all experiments, the bi-directional results are up to a percentage point better.

7.6 Representation Layer

Proposition 6 The Representation Layer Acts as a Communication Platform: The representation layer represents the cognitive brain state. In cognitive neuroscience, it is referred to as "global workspace", "communication platform", "communication bus", "blackboard", or the shared "canvas" and it enables a global information exchange.

We propose that it has a distributed representation involving large parts of the brain. (Binder and Desai, 2011) states: "The neural systems specialized for storage and retrieval

$s^* = sBB,$	$o^* = lBB$	$s^* = lBB,$	$, o^* = sBB$	
label (s^*)	label (o^*)	label (s^*)	label (o^*)	
Person 0.58	Person 1.00	Person 1.00	Shirt 0.53	
Mammal 0.50	Mammal 1.00	Mammal 1.00	Clothing 0.64	
NonLivB 0.65	LivB 1.00	LivB 1.00	NonLivB 0.84	
Old 0.53	Old 0.60	Old 0.59	Old 0.52	
Red 0.46	Other 0.94	Other 0.95	Red 0.46	
Other 0.92	Other 0.68	Other 0.67	Other 0.96	

Figure 9: Context scene graph for perception using <u>VRD-E*</u> data. Shown are unary labels. When the smaller bounding box (*sBB*, containing the shirt) assumes the role of the subject, it is incorrectly labeled as being a person (column 1, blue). The larger bounding box (*lBB*, containing the player), assuming the role of the object, then is correctly labeled as being a person, as well (column 2). In contrast, when the larger bounding box assumes the role of the subject, it is correctly labeled as being a person, as well (column 2). In contrast, when the larger bounding box assumes the role of the subject, it is correctly labeled as being a person (column 3). The smaller bounding box, assuming the role of the object, now is correctly labeled as being a shirt (column 4).

of semantic knowledge are widespread and occupy a large proportion of the cortex in the human brain", which would refer to the representation layer in our model.

If we look at the path from visual input to the index layer as one deep neural network, then the representation layer would be the last hidden layer. As discussed, we use a deep convolutional neural network (DCNN) for the mapping $\mathbf{f}(\cdot)$ from scene and bounding box content to the representation layer. Our approach can be generalized in a way such that several upper layers in the DCNN form the representation layer. (Kriegeskorte and Douglas, 2018) and others have discussed how DCNNs might represent functional modules in the brain. This is not the topic of this paper.

The representation layer is activated by perceptual input (e.g., in states $\tilde{\mathbf{q}}_T, \tilde{\mathbf{q}}_S$ in perception) and forms visual representations. Thus some dimensions might represent, e.g., the different colors. At the same time it might get activated by the embeddings of concepts (e.g., $\mathbf{q}_S \leftarrow \mathbf{a}_s$ in a semantic memory experience). In perception it can represent and a concept in context as $\mathbf{q}_S \leftarrow \tilde{\mathbf{q}}_S + \mathbf{a}_s$. The representation layer is partially compositional, e.g., in that a red ball might activate both the dimensions in the representation layer for redness and for roundness.

From another perspective, the representation layer assumes the role of the central layer in an autoencoder, if we look at the path, e.g., from \mathbf{n}_S to \mathbf{n}_Q . As in the restricted Boltzmann machine (Smolensky, 1986; Hinton, 2010), the dimension of the central layer can be rather high-dimensional.

7.7 Working Memory and a Foundation for Consciousness

Since the representation layer assumes a distributed presence in the brain, to realize a memory buffer, the brain needs a storage site.

Proposition 7 Single Brain Hypothesis and Working Memory: The representation layer is memoryless and can only present one semantic state at a time; any information that needs to be stored for later processing requires a separate working memory layer.

In comparison to episodic and semantic memory, the working memory is short-lived and does not extend beyond the lifetime of a scene. Long-term working memory is considered to be essentially the same thing as the portion of episodic and semantic memory activated in a decision process.

Working memory, of course, realizes many more functions and is not limited to storing intermediate processing results in complex semantic decoding, as in our approach. In general, working memory is associated with decision making and cognitive control (Baddeley, 1992) and is necessary for keeping task-relevant information active as well as manipulating that information to accomplish behavioral tasks. There is an emerging consensus that most working memory tasks recruit a network of the prefrontal cortex (PFC) and parietal areas in the prefrontal parietal network (PPN). A modern view is that working memory is distributed across the cortex (Buschman and Miller, 2020) and we do not argue for any specific brain region for the working memory function discussed in the paper.

PPN activity is consistently reported in both attention and consciousness studies (Bor and Seth, 2012). The latter publication proposes that the PPN can be viewed as a "core correlate" of consciousness. (Dehaene, 2014) defines consciousness as "global information sharing" where information has entered into a specific storage area that makes it available to the rest of the brain. Christof Koch and colleagues argue that the posterior hot zone (PHZ) is the minimal neural substrate essential for conscious perception (Koch et al., 2016). The PHZ includes sensory cortical areas in the parietal, temporal, and occipital lobes. We would relate to these discussions with the following proposition.

Proposition 8 Foundation of Consciousness: The interactions between the index layer, the representation layer, and the working memory layer might be a foundation from which evolution eventually generated human consciousness. The three layers might be a basis for the PPN and the PHZ.

Thus, the agent's awareness of the state of the world, which includes perception and the agent's episodic and semantic memory, defines who the agent is, and might be a prerequisite of a conscious mind.

7.8 Triple Serialization and the Central Bottleneck

Proposition 9 Sequences of Parallel Processing: In perception, processing is executed as a sequence of steps where the computations executed at each step are highly parallel.

Thus, it is this mixture of parallel and sequential processing exhibited in our model, which also makes up the brain's operation. Serial processing is a consequence of the single brain hypothesis and we suggest that it also applies to perception. Consider, that in a first step, we map $scene_{t'}$ to $\mathbf{f}(scene_{t'})$, and this representation can be analyzed rapidly and might trigger action, with a limited understanding of scene content (see fast perception). Only then, bounding box content is analyzed in detail, which might be supported by saccadic eye movements, and is a slower serial process. It requires N_V steps, where N_V is the number of visual entities in the scene. The number of generated triples in triple serialization is even greater but permits a path to language, as discussed in the next subsection. Maybe not surprisingly, language makes thoughts explicit and maybe clearer but, at the same time, slows down thinking.

Sequential processing is also a core concept in the theory of a global workspace (Baars, 1997; Bor and Seth, 2012; Dehaene, 2014; Goyal et al., 2021): (Koch, 2014) discusses that Dehaene's workspace has extremely limited capacity ("the central bottleneck") and that the mind can be conscious of only one or a few items or events, although these might be quickly varying. In cognitive computational neuroscience, the general notion is that parallel multitasking likely is an illusion. Even working memory is assumed to be able to only store three to four items at a time (Awh and Vogel, 2020). The sequential processing would also contribute to a potential solution of the binding problem (Singer, 2001), since the decoding focuses on concepts in a serial fashion and associations between activities in the representation layer and the index layer are well defined. The importance of sampling is also recognized in (Dehaene, 2014) in the context of conscious perception. For example, the author states that "... consciousness is a slow sampler".

Another interesting point is that both (Dehaene, 2014) and (Koch et al., 2016) assume mental states, well-delineated from all the other states. Such a process is going on in our sampling approach if one interprets a sample as a decision on an interpretation: "It's a bird, or a plane, or it's Superman, but not all of them at the same time" (Dehaene 2017) Dehaene talks about a similar process of "... collapsing all unconscious probabilities into a single conscious sample ...". His model assumes a "winning neural coalition" whereas our sampling approach is much simpler, but maybe based on a similar computational need.

In the semantic decoding of our model, the representation layer is periodically activated, which might be reflected in neural signals and could be related to some of the neural oscillations found in the brain. A candidate is the beta rhythm (13-35 Hz) considered to be related to consciousness, perception, and motor behavior. Also of interest is the gamma wave (25-140 Hz), which is correlated with large-scale brain network activity and cognitive phenomena such as working memory, attention, and perceptual grouping.

7.9 Language of Thought

Captain: Spooky, repeat what we know, in triple format — Spooky: (s', sameAs, Sparky), (Sparky', type, Dog), (Sparky, color, Brown), (Sparky, size, Huge), (o", sameAs, Surf-Board), (o', type, Person), (Person, grabs, SurfBoard), (s", type, Bear), (Bear, lurks, Nearby), (t* = 42, sameAs, t'), t*: (Bone, beamedTo, Sparky), t*: (t*, hasEnding, Happy) (Dog, subClass, Mammal), (Dog, hasAbility, Bite), (Sparky, hasAttribute, Friendly), (Sparky, bites, Klingons)

Humans differ from other animals in their ability to express themselves in the form of natural languages. Human language is the basis for communication but also a means to argue and reason. The *language of thought hypothesis* is the hypothesis that mental representation has a linguistic structure, as well: thoughts are sentences in the mind. (Fodor, 1975) describes the nature of thought as possessing "language-like" or compositional structure (sometimes referred to as mentalese). In this view, simple concepts combine in systematic ways (akin to the rules of grammar in language) to build thoughts.

Proposition 10 Inner Speech: The triple sentences generated in perception and memory recall by triple serialization are a basis for a language of thought and might be related to a form of an "inner speech".

The translation of information from perceived images to language is called the translation problem (Gärdenfors, 2016). Perception, episodic memory, and semantic memory are all declarative, or explicit, and can produce an inner speech. Or simply put: humans can verbally report about perception, episodic and semantic memory. In our model, working memory is involved in the generation of binary statements. Indeed, individuals with aphasia (language impairments due to damage to specific brain regions) can demonstrate deficits in short-term memory, working memory, attention, and the executive function (Murray and Ramage, 2000). It is generally assumed that language generation involves working memory but also several other areas, such as Broca's area (Hickok and Poeppel, 2007).

Triple sentences can drive communication, argumentation, and logical reasoning (Richardson and Domingos, 2006; Hildebrandt et al., 2020). There is a clear advantage to communicate with other agents about the part of the agent's world, which is not perceived here and now. Thus an agent can tell another agent not to leave the hide-out since there is a bear lurking outside.

An interesting question is: what came first? Did we develop semantic decoding to develop language and to communicate —and improved perception and logical reasoning were by-products, which enabled us to act better— or did we develop improved perception first, with language and reasoning as by-products? (Gärdenfors, 2016) argues in favor of the latter, whereas others argue for the former.

The abstraction generated by triples and language also demonstrates great invariances both in cognition and in our model. Significantly different scene input might generate identical scene descriptions! Another issue is that the "firework" of triples might generate statements that are contradictory, like (s', type, Cat) and (s', type, Dog); it might be a more pronounced ability of human beings to recognize and resolve contradicting triples. The relationship between images, KG-triples, and language has been studied in (Schmitt et al., 2020).

8. Concept Engrams and Their Organisation

Engrams are memory traces in the brain. In this section, we focus on engrams for concepts such as entities, attributes and classes, representing conceptual knowledge (Ralph et al., 2017). Engrams for episodic memory are discussed in Section 9.

Proposition 11 Concept Engrams: In the brain, concept engrams are memory traces, e.g., for entities, attributes, and classes. We propose that an engram for a concept consists of a concept index, realized by a unit in the index layer, and its concept embedding, which is realized as a connection vector, connecting an entity index with the representation layer.

An index is a symbol for a concept, whereas embeddings are part of an implicit concept memory. The latter have a subsymbolic semantic interpretation reflecting the gist of a concept and provide a grounding. We are here in agreement with a number of cognitive theories on semantic engrams. For example, in (Binder and Desai, 2011) it is stated that semantic engrams consist of both modal and amodal representations, supported by the "gradual convergence of information throughout large regions of temporal and inferior parietal association cortex". Translated to our model, the embedding has a modal, distributed character, and grounds the concept, whereas the concept index has an amodal, local, symbolic character and is a high-level convergence zone.

The relationship between the index layer and the representation layer reminds one of the hub-and-spoke model (Ralph et al., 2017). The hub is supposed to be located in the anterior temporal lobes (ATLs), which might be where concept indices are consolidated. The hub is connected to several different areas (e.g., visual cortex, auditory cortex, orbitofrontal cortex), which might be part of the biological realization of the representation layer. Other hubs might be located in the parietal and the temporal lobe (Binder and Desai, 2011) and maybe in the frontal lobe (Tomasello et al., 2017).

Some works propose that an anatomical distinction between the representation layer and the index layer might be blurred in the brain. One should rather assume an "interactive continuum of hierarchically ordered neural ensembles, supporting progressively more combinatorial and idealized representations" (Binder and Desai, 2011).

8.1 The Index Layer

The debate about localized representations in the brain is ongoing. Specific concept cells have been found in the medial lobe (MTL) region of the brain. MTL includes the hippocampus, along with the surrounding hippocampal region consisting of the perirhinal ("what"path), parahippocampal ("where"-path), and entorhinal neocortical regions. Researchers have reported on a remarkable subset of MTL neurons that are selectively activated by strikingly different pictures of given individuals, landmarks, or objects, and in some cases even by letter strings with their names (Quiroga, 2012; Quiroga et al., 2005). Naturally, locality of representation is probably only discovered in well-designed experiments: In our model, an activated concept index activates many units in the representation layer, and a unit in the representation layer, in turn, activates many indices. Since index activations might change rapidly, the general appearance might be that of a globally activated system, hiding the locality of representation.

Each index s corresponds to a point \mathbf{a}_s in the semantic vector space defined by the representation layer \mathbf{q} . Since an embedding is optimized for a concept's role in perception and memory, it implicitly reflects all background that is known about it. Figure 10 shows an analysis of the entity embeddings, based on the t-SNE visualization (Van der Maaten and Hinton, 2008). The plot clearly shows a schema-like organization of concept embeddings in semantic embedding space, also known as a cognitive map (Tolman, 1948). In cognitive neuroscience, the semantic embedding space is sometimes referred to as conceptual space (Gärdenfors, 2016), where points denote objects, and regions denote concepts.

Following the theory of a conceptual space, the different dimensions of the representation, i.e., units in the representation layer, should have semantic meaning, as well, but maybe less specific, compared to the representation of a concept in the index layer. Whereas the index layer would be similar to the output layer of a technical deep neural network, the



Figure 10: We show t-SNE visualization of embeddings of seven classes and randomly selected entity concepts from these classes, based on their respective embedding vectors in semantic embedding space. A dot stands for an entity, e.g., a specific dog, *Sparky*. The color of a dot marks the basis class of that entity. A cross stands for a class, e.g., *Dog*, which is labeled by the same color as entities belonging to the class. We find that the embedding of a class concept lies approximately in the center of their corresponding entities. Recall that we are not indicating cluster centers, but the embeddings that happened to be learned for the classes in learning. In cognitive neuroscience, the semantic embedding space is sometimes referred to as conceptual space, where points denote objects, and regions denote concepts (Gärdenfors, 2016).

representation layer is more similar to the last hidden layers: one can find some semantic meanings in their activations, but not as specialized as the neurons in the output layer. The output layer represents symbols and words, the representation layer their subsymbolic gist.

(Gärdenfors, 2016) discusses the conceptual space as basic features, or an embodiment or grounding (Binder and Desai, 2011), by which concepts and objects can be compared. In neuroscience, this is supported by the fact that, in different brain regions, maps have been discovered that code, e.g., for visual appearance, sound, and function. For instance, the concept "cat" includes the information that a cat has four legs, is furry, meows, can move, or can be petted (Kiefer and Pulvermüller, 2012). As another example, consider the recall of the concept "hammer", represented in the index layer. This might excite brain areas indicating a typical hammer appearance, the sound of hammering, and the required motor movement of hammering, all represented in the biological equivalence of representation layer (Rueschemever et al., 2010). In our model, since the representation layer is activated by visual input, the embeddings will mostly be visually grounded. In terms of (Binder and Desai, 2011), the embeddings are modality-specific (here: visual), and the indices represent (supramodal, multimodal, polymodal) convergence zones. As (Dehaene, 2014) puts it: "Every cortical site holds its own specialized piece of knowledge".

Evidence for distributed semantic activation has also been described by (Huth et al., 2016; de Heer et al., 2017). That paper developed a detailed atlas of semantic categories and their topographic organization by extensive fMRI studies, showing the involvement of the lateral temporal cortex, the ventral temporal cortex, the lateral parietal cortex, the medial parietal cortex, the medial prefrontal cortex, the superior prefrontal cortex, and the inferior prefrontal cortex (Huth et al., 2016).

Recently, it has been proposed that embeddings are context-dependent (Popp et al., 2019). Our model suggests that a concept embedding is rather stable but that the activations of the representation layer are highly context-dependent as discussed throughout the paper. In our model, the representation layer is activated by sensory input and by concept indices, so the model is informed about a concept in context, even with the connection weights between index and representation layer being fixed. The feedback from the working memory layer also represents context which affects representations. On the other hand, since the embeddings represent latent information, e.g., concept embeddings, the assignment of meaning to units in this layer might not be stable and can easily change in time, as supported by the great plasticity of brain maps after injury.

8.2 Functional and Structural Connectivity

Indices are explicit concept representations, i.e., an index is a symbol for a concept and functionally could be implemented by a single neuron. We are purposely imprecise about how exactly an index is represented anatomically, i.e., structurally, in brainware. In the one extreme, it might be single neurons, realizing localist codes, where neurons respond highly selectively to single entities ("grandmother cells"). In the other extreme are densely distributed codes where items are encoded through the activity of many (e.g., 50%) neurons (Kumaran et al., 2016). Most researchers favor a sparse population of cells realizing a population code.

In our model, we have a bipartite relationship between the concept index layer and the representation layer. The advantage of an effective or functional bipartite architecture is interpretability and speed of operation. The cortical network, in general, is anatomically not strictly bipartite and contains extensive local connectivity, realizing an interplay of synaptic excitation and synaptic inhibition (Isaacson and Scanziani, 2011). The hub-and-spoke model also assumes recurrent connections within the hub layers, which functionally, would not be required in our approach, i.e., we do not need to assume direct index-to-index connections. Our model would also support that indices show correlation patterns: If an index is activated, indices that represent similar entities are activated as well, even without direct index-to-index connections.

In our approach, we implemented symmetric connections between the index layer and the representation layer. Thus we have connection weights A and A^{\top} in Figures 2 and 3, and, e.g., the vectors \mathbf{a}_s are identical in Equations 6 and 8. The hub-and-spoke model contains strong connections between the hub modules and the spoke modules as well. Although backward connections are common in the brain, symmetry is not commonly found. We did extensive experiments where we removed that constraint. The result was that the performance dropped by about 1% in basically all experiments, so we stayed with symmetric connections in our work.

The representation layer is high-dimensional, although embeddings might be sparse and a given index only activates a small number of components of the representation layer. Naturally, the index that represents the color "red" is likely to mostly connect to components of the representation layer that is excited by red images. Another advantage of sparse distributed representations (Rolls, 2016) is that this might lead to increased memory capacity (Ma et al., 2018a). Sparsity in the embedding vectors can be achieved in technical models, e.g., by using appropriate regularization terms, like LASSO (Tibshirani, 1996). In our experiments, we use L2 regularization ("weight decay") on all parameters. With Lasso, we obtained comparable results with 70% sparsity.

9. Episodic Memory

9.1 Episodic Memories Enhance Perception

Proposition 12 *Episodic Memory in Perception:* The introduction of indices for time instances in the index layer permits the reactivation of a previous —either recent or remote—episodic memory. The sampling of time indices is the basis for an episodic memory experience.

We propose that an agent first performs episodic attention and semantic attention, which can be executed fast and in parallel. Only in a second step, associations with past time instances and known entities are made. This is a slower serial sampling process, which improves performance and can trigger episodic and semantic memory experiences. As an illustration: If the agent is chased by a dog, it might at first not be as relevant, that the dog is Sparky and that Sparky is owned by Jack.

The episodic and semantic memory experiences are about using the not-perceived to support the agent here and now. The goal is to provide information that makes the agent act right! Semantic memory, covered in the next section, provides information from the prior and recalls relevant information which is true for the involved concepts in general.

9.2 Background on Episodic Memory

(Tulving, 1985) describes episodic memory as a memory that, in contrast to semantic memory, requires a recollection of a prior experience. It is considered to be the result of rapid associative learning in that a single episode and its context become associated and bound together and can be retrieved from memory after a single episode. Episodic memory stores information of general and personal events (Tulving, 1972, 1985, 2002; Gazzaniga et al., 2013) and concerns information we "remember" including the spatiotemporal context of events (Gluck et al., 2013).

Episodic memories are first formed in the hippocampus. The idea that episodic memory is index-based is by now a well-accepted theory (Tonegawa et al., 2018). It goes back to the hippocampal memory indexing theory (Teyler and DiScenna, 1986; Teyler and Rudy, 2007), which was long controversial. The indices have a relational memory function in the sense that they bind together different pieces of experience. Evidence for time cells in the hippocampus (CA1) have recently been found (Eichenbaum et al., 2012; Eichenbaum, 2014; Kitamura et al., 2015b,a).

There is some evidence that indices might be quickly formed in the hippocampus by a process termed neurogenesis. Neurogenesis by special stem cells has been discovered in the dentate gyrus (part of the hippocampal formation) and is active throughout adult life; these new neurons may be preferentially recruited in the formation of memories. In fact, it has been observed that the adult macaque monkey forms a few thousand new neurons daily (Gluck et al., 2013; Gould et al., 1999), possibly to encode new information (Becker, 2005).

The establishment of new time indices together with their embeddings, as well as the establishment of new concept indices and their embeddings, are the most demanding learning tasks in the brain. Functionally, our model assumes that a new episodic memory is quickly stored by the establishment of a new index and its connections to the representation layer, copying the episodic memory trace. Although there exist several theories, little is known about how exactly new time indices are formed in the brain anatomically and how they quickly set up the connection patterns to the representation layer, forming a hippocampal–cortical network (Frankland and Bontempi, 2005), maybe building on already existing networks. A structural intra-hub-connectivity might facilitate this process (see discussion in Section 8).

In our work, we consider episodic memory to be related to instances in time. Other theories emphasize more the sequential nature of episodic memory and the memory process. (Moscovitch et al., 2016) considers an episodic memory experience to be an active process that involves details of the event and its location. Sometimes the reconstruction is considered a Bayesian process of reconstructing the past as accurately as possible based on available engram information. We would support the idea that the reconstruction of a complex spatial or narrative episodic memory might involve the MTL.



Figure 11: t-SNE visualization of embeddings for time instances, based on $\{\mathbf{a}_t\}_{t=1}^{N_T}$. From the figure, we can see similar scenes are often clustered together. As examples, the circled areas show images of playgrounds (bottom) and of groups of people having dinner (right).

9.3 Episodic Memory Experience and Episodic Engrams

Proposition 13 *Episodic Memory Experience:* An episodic memory experience activates the index for the past time instance, which leads to the activation of the representation layer with the embedding vector of the time instance. This then initiates an approximate reconstruction of the past perceptual event.

The establishment of a new episodic engram for time instance t' consists of the generation of a novel time index and its embedding $\mathbf{a}_{t'}$, i.e., its connection vectors between the time index and the representation layer. Thus, an episodic memory engram represents all information that has been conveyed to the agent at a past time instance t, in particular in reference to the observed entities. Episodic memory provides context to a previous encounter with an entity. Figure 11 shows that the embedding vectors of episodic memories form meaningful maps, and also are organized as a conceptual space.

Simply speaking, episodic memory recalls a past data point, which is relevant to current perception. In (Duncan and Shohamy, 2016) this is referred to as the "sampling of one-hot episodes". Episodic memory activates the past time index t^* and its embedding vector and then semantically decodes the embedding vector by forming a set of triple statements describing the past scene. We would argue that this mechanism is very simple and easy to implement in the brainware, in comparison to alternative approaches requiring more complex mechanisms.

	s	*	Unary labels					Binary	labels	
Model	@50	@10	B-Class	P-Class	G-Class	Y/O	Color	Act.	@10	@1
Episodic recall	82.75	59.34	98.07	99.51	99.99	94.55	92.93	97.61	97.08	60.90
P-noI	0.0	0.0	41.19	20.83	51.76	49.03	12.97	71.05	39.34	7.79

Table 6: Top row: Episodic memory experience using <u>VRD-E</u> data. For randomly selected past time instances t^* as input, we determine the highest-ranked entity instances (first two columns) (\mathbf{n}_S). For the other columns, we set ("teacher-force") the correct entity instances (s^* and o^*) and predict unary labels and binary labels (\mathbf{n}_O). The performance is quite good. Thus an agent might recall seeing a black dog, but the reconstruction that it was Sparky, might require more effort. Considering the large number of entities in the data set, the performance on entity prediction is impressive, as well. Bottom row: In comparison, we show results where the model does not contain representations for time instances and entities. Entity recall is now impossible and unary and binary labels are not well predicted.

Proposition 14 Binding Problem: Episodic memory requires entity indices to solve the binding problem!

Without entity representations it would be impossible for episodic memory to link information: e.g., it would not be possible to recall if the dog was black and the cat was white, but not vice versa. Our approach proposes an elegant approach to addressing the well-known binding problem in episodic memory (Singer, 2001). Episodic memories are inherently contextualized.



Figure 12: Episodic memory experience using <u>VRD-E</u> data. The first row shows, first, the original scene t' and then extracted bounding boxes for entities in the scene (Algorithm 3). In the second row, we show an episodic recall of this same scene $(t^* = t')$, Algorithm 2. We show the bounding boxes of the scene entities, which were recalled. We see that, in sampling, episodic recall recovers entities with correct bounding box content (fire hydrant, sky, car, etc.) (\mathbf{n}_S). Meanwhile, similar entities which are not associated with this time instance can be wrongly predicted, e.g., the second car (column 6) in the second row. Note, this incorrect recall would still be quite plausible for the scene. This figure shows that, most often, relevant entities are recovered in an episodic recall.

There is some evidence that, in the brain, MTL might reconstruct spatial memories permitting complex spatial reasoning. A similar reconstruction of complex relational networks for episodic and semantic memories into a narrative might be realized in MTL, as well (Whittington et al., 2020). MTL might not always be the storage place for memories, but it is essential for establishing memory and for spatial and relational reasoning.

Figure 12 illustrate an episodic memory experience. Table 6 provides numerical results. In the experiments on episodic memory, we use Algorithm 2.

We want to emphasize the importance of the IPM for episodic memory (Algorithm 2 (eKG) (sampling the subject s^* in line 6 and sampling the object o^* in line 16). IPM takes care, that only entities are considered in the episodic memory experience, which actually occurred in the past scene.

9.4 Recent Episodic Memories for Context

Captain: Spooky, what is our status? — Spooky: Captain, we still have Sparky in front of us. But, don't forget, a bear is still lurking outside our hideout, even if we cannot see it right now!

Proposition 15 Recent Episodic Memory: Recent episodic memory can provide the agent with information on recent perceptional experiences. It contributes to an agent's sense of the world state. A recall is triggered by closeness in time and relevance.

Recent episodic memory is recalled because it is relevant and close in time, not primarily because it is similar. This emphasis on temporal closeness can be implemented as "time encoding" (Ma et al., 2018b), in a similar way as "position encoding" is used in the attention literature (Vaswani et al., 2017). An example is, what we refer to as the lurking-bear situation (Figure 13): "There was a bear strolling around outside the hide-out, Remember: it might still be there, although the agent cannot see it from the hide-out". An agent needs to know about the state of the world, even for parts that are not currently being perceived. Figure 14 shows another example of a recent episodic memory recall.



Figure 13: Recent episodic memory experience: An illustration of the effect of a recent episodic memory experience using <u>VRD-E</u> data. The left image shows a harmless garden scene, but due to a recall of a recent episodic memory $t^* = 684$ (Algorithm 3), the agent is aware of the lurking bear close by (right scene). Labels for visual entity recovered in the episodic recall (Algorithm 2) (right scene) are *Bear, Mammal, LivingBeing, Old, Black, OtherActivity, Dangerous*. Note that episodic recall is not triggered by closeness in a scene but by recency and relevance.

9.5 Remote Memories for Decision Support

Captain: Spooky, have we been in a similar situation before, what did we do last time, and how did it end? — Spooky: Captain, yes, this is similar to episode 42; we beamed up a bone to Sparky and the episode had a happy end!

Proposition 16 Remote Episodic Memory: Remote episodic memory can provide the agent with information on similar remote perceptional experiences and that can contribute to decision making! A recall is triggered by closeness in representations of the current scene representation with past scene representations, and relevance.

Remote episodic memory is retrieved because it is relevant and similar to the current situation. An important capability for an agent is the comparison of the current situation to previous experiences: If a current event is very similar to a past event, and that past event triggered a certain action, it makes sense that the current event should trigger the same action — if it led to a good outcome— or an alternative action, if not. As an example: the



s*	Unary labels	0*	Binary label
346	Person, 1.00, Mammal, 1.00, LivingBeing, 1.00	345	on
	Young, 1.00, Other, 1.00, Other 1.00		
348	Shirt, 1.00, Clothing, 1.00, NonLivingBeing, 1.00	347	on
	Young, 1.00, Orange, 1.00, Other, 1.00		
347	Person, 1.00, mammal, 1.00, LivingBeing, 1.00	348	wear
	Young, 1.00, Other, 1.00, Playing, 1.00		
345	Grass, 1.00, Plant, 1.00 LivingBeing, 1.00	346	under
	Old, 1.00, Green, 1.00, Other, 1.00		

Figure 14: Recent episodic memory experience. Top: The left image shows the visual input $scene_{t'}$ using <u>VRD-EX</u> data. Then a recent t^* is sampled. The right image shows the image belonging to t^* . The table shows results from this episodic memory experience, without the image for t^* being available. The first column shows s^* . The second column shows unary labels. The third column shows sampled objects o^* . The fourth column shows the most likely binary label.

agent finds the current situation very similar to a previous one where the next thing was an attack by a bear, so better watch out! "I was in this situation before. I walked towards the bear and almost got attacked. I should not do this again!".

Thus memory guides behavior. (Duncan and Shohamy, 2016) describes this process as an integration across relational events by imaging possible rewards in the future. Thus the value associated with a memory (e.g., reward, thread) might be an integral aspect of episodic memory. The paper also states that there is now extensive empirical data supporting the prevalent use of episodic memory across a variety of decision making tasks in humans.

Figure 15 shows that a perceptual scene indeed can activate memories of quite similar scenes in remote episodic memory.



Figure 15: Top: Remote episodic memory experience using <u>VRD-E</u> data. The figures on the left show the visual input to perception (Algorithm 3). Then we sample t^* , representing past episodic memories. The images of the scenes associated with the t^* show that, indeed, recalled past episodic memories are related. Bottom: visual entity representation of s' on the left and bounding box images corresponding to sampled s^* .

10. Semantic Memory

Captain: Spooky, we need to know more. Please, check our database for anything on dogs, and Sparky, in particular! — Spooky: Captain, dogs are mammals, dogs can bite, Sparky is owned by Jack. Captain, we are lucky: Sparky only bites Klingons!

10.1 The Semantic Memory Experience

Proposition 17 Semantic Memory: The semantic memory describes the (quasi-) stationary statistics of the agent's world and assigns prior probabilities to all statements. Semantic memory summarizes information from different modalities, e.g., vision, and can represent, e.g., social and spatial networks.

According to (Tulving, 1985), the semantic memory experience is independent of a particular episodic experience. It developed out of perception as an emerging property where the semantic enrichment became independent of perceptual input. Thus, in the transition from episodic memory to semantic memory, provenance is lost. It is the longest-lasting and most stable memory since it is about the stable statistics in the world.

Some researchers consider semantic memory simply as being consolidated episodic memory. Our model would support a very close relationship between both. After all, the only difference in our model is that an episodic memory experience requires the activation of the embedding vector \mathbf{a}_t , whereas a semantic memory experience requires the activation of the semantic memory representation $\bar{\mathbf{a}}$, which can be interpreted as the embedding of some "neutral" time index. In comparison to an episodic recall, a semantic recall can be fast since it does not involve a sampling of relevant past episodes!

Nevertheless, a semantic memory experience might be *triggered by* perception. Thus if perception poses the hypothesis that an entity in the image is identical to "Sparky", then the semantic memory experience would supplement background information on Sparky, that cannot necessarily be derived from the visual input. Semantic memory reconstructs what is known about the concept (i.e., the prior), both the subsymbolic reconstruction of the experience and the semantic decoding.

Table 8 shows that, in our model, semantic memory can realize a very precise memory recall and performs better than RESCAL. (Ruffinelli et al., 2019) showed in a recent study that RESCAL is a competitive approach for KG modeling.

Table 7 illustrates the semantic memory experience, which is triggered by either by an entity, a class, or an attribute. The latter two correspond to a recall of generalized statements (see Subsections 4.7). For example, it is shown that semantic memory can recall general information on dogs, mammals, and the color black.

We want to emphasize the importance of the IPM for semantic memory. IPM takes care, that, in the semantic memory experience, only entities are considered as objects o^* which are likely to have a binary statement involving the subject s^* .

10.2 Social Networks and Multimodality

Semantic memory serves as a site of multimodal integration. Table 9 shows how multimodality enters in perception. The unary label *Dangerous* was not trained in perception but just in semantic memory. The table shows that information from the semantic memory is integrated with perception and episodic memory, even without an explicit semantic memory experience. Thus an entity embedding truly integrates information from different modalities.

We derived a social network involving all persons in the data set by linking entities representing persons with the predicate knows. Each person is linked with 5 other persons.

s^* (ID)	Unary attribute/	Unary entity labels	Binary statements
	class labels	(p: sameAs)	$(s^*, \ p, \ o^*)$
10830[Person]	Person, 0.96	10830[Person]	(10830, wears, Shirt)
	Mammal, 0.97		(10830, wears, 3495[Glasses])
	LivingBeing, 0.98		
	Old, 0.98		
	Other, 0.98		
	Walking, 0.96		
Dog	Dog, 0.99	3537[Dog]	(Dog, on, Grass)
	Mammal, 1.0	602[Dog]	(Dog, behind, Person)
	LivingBeing, 1.0	5976[Dog]	
	Young, 0.52		
	Brown 0.35		
	Other 0.99		
Mammal	Dog, 0.38	3901[Cat]	(Mammal, on, Street)
	Mammal 1.0	9100[Horse]	
	LivingBeing, 1.0		
	Young 0.6		
	Brown 0.31		
	Other 0.96		
Black	Person 0.24	9812[Bag]	(Black, on, Person)
	Other 0.43	3634[Keyboard]	(Black, under, Sky)
	NonLivingBeing 0.95		
	Old 0.59		
	Black 0.99		
	Other 0.99		

Table 7: Semantic memory experience with generalized statements on <u>VRD-EX</u> data. The first column shows the queried s^* (an entity, a class, or an attribute), i.e, the input to the algorithm. The second column shows highly rated attribute and class labels describing s^* . The third column shows highly-ranked (sampled) entities for the *sameAs* predicate. The fourth column shows binary statements. We see that person [10830] is a mammal and often wears shirts and glasses. But we also see that the model "explains" what the class "Dog" stands for, what the class "Mammal" stands for, what the attribute "Black" stands for: We see that a dog is a mammal, is brown with 35% probability, and is often on the grass or behind a person. We see that if something is black, it is often a person (24%), often a bag, and black entities are often on persons and under the sky.

In addition, we define social network perception by a time instance at which the agent learns about the social contacts of one person. Our social network dataset has 4987 person entities (along with their attribute labels), 24953 *knows* statements, and 4987 episodes of social events. We refer to this data set as VRD-S. More details on the generation of the social network data can be found in the Appendix.

	Binary	labbel		Unary la	bels: attrib	outes/cl	asses	
Model	@10	@1	B-Class	P-Class	G-Class	Y/O	Color	Act.
SM-wTFC	98.20	57.62						
RESCAL-wTFC	89.95	26.06						
SM-wTFE	100.0	90.32	100.0	100.0	100.0	100.0	100.0	100.0
RESCAL-TFE	100.0	90.12						

Table 8: Semantic memory experience. For the models trained on the <u>VRD-E</u> data set, we teacher-force the class labels for s^* and o^* and predict the binary labels. Our results are better than a state-of-the-art model (RESCAL). In the third and fourth row, we teacher-force the entity instances. In this memorization, the performance is boosted with entity representations. We randomly select class labels for the subject and the object (input s and o to the algorithm) and predict the binary label (\mathbf{n}_P). The results are competitive to the equivalent RESCAL model (second row). Recall that we are testing memory retrieval and not generalization, which explains the high scores, in particular for the attributes and classes.

	Classification Accuracy
Model	Dangerous
Р	52.01
P-wSM	99.99
P-crosstalk	94.98

Table 9: Semantic memory experience integrated with perception. The task is the prediction of the unary label *Dangerous* with or without semantic memory. "P" in the first line is the perceptual system, where the label *Dangerous* was not provided in training. It can only predict by chance if an entity is dangerous or not. We trained the label *Dangerous* as part of semantic memory. In "P-wSM", the semantic memory experience is activated which supplements the information from semantic memory if a visual entity is dangerous. "P-crosstalk" shows that, when the semantic memory is trained with the *Dangerous* label, this information is also automatically integrated with perception, without an extra activation of a semantic memory experience. "Crosstalk" works well with not-perceptual information, like social network background, which is, in a way, orthogonal to the visual scene input and is an indication that statements become dependent in training by embedding sharing.

Table 10 shows numerical results on VRD-S. Given a person of interest, the semantic memory can recover the friends (object o^*) and predict unary labels. Table 11 illustrates episodic and semantic memory, including social network data recall. Social relationships are also illustrated in Figure 10.

The agent's world is not just a sum of its individuals: it is a network of individuals! By the social network context, agents learn that it is not all about them and this recognition can be a basis for the *theory of mind* (Gazzaniga et al., 2013); functioning well in a social network is essential for social beings.

Model	s*		0	*	Unary labels of s^*					
	@10	@1	@10	@1	B-Class	P-Class	G-Class	Y/O	Color	Activity
Episodic Memory	100	51.47	99.97	65.80	100.0	100.0	100.0	100.0	100.0	100.0
Semantic Memory	-	-	97.39	18.25	100.0	100.0	100.0	100.0	100.0	100.0
RESCAL	-	-	95.76	17.96						

Table 10: Episodic and semantic memory experience for <u>VRD-S</u>. The first row shows the performance of an episodic recall, with t^* given. For columns 3-10, the subject s^* is teacher-forced. The second row shows the semantic memory experience where the subject s^* is given. The unary labels have perfect recall. Since each person has 5 friends, the recall@1 shows close to 20% performance. For columns 5-10, the subject is teacher-forced. As a comparison, we show the performance of RESCAL.

10.3 The Agent's World State

Proposition 18 Agent's World State: The mind estimates the world's state by using perception, recent and remote episodic memories, and semantic memory.

It is of great interest for an agent to know the state of the world at a new time instance t', in particular, if it concerns the agent's immediate environment.

Consider the example in Figure 16. If the agent is at the office, <u>perception</u> will produce triples describing the situation there. By using <u>recent episodic memory</u>, the agent might recall that Mary is visiting the office that day and that Mary is a good friend (<u>semantic memory</u>). The agent recognizes that Sparky is in the office (<u>perception</u>) and <u>semantic memory</u> adds triples describing semantic background on Sparky, e.g., that Sparky is owned by Jack. The agent might also recall that a while ago, Sparky was at the office and behaved well (<u>remote episodic memory</u>). If the agent is thinking about its home it might recall that people are repairing the heater (<u>episodic memory</u>, not triggered by perception). Also, the agent recalls that its home is close to the airport <u>semantic memory</u>. If someone asks the agent what it knows about cats, it might again, use <u>semantic memory</u> with generalized statements to produce triples describing typical cat properties. The example nicely visualizes that it is important for the agent to know what it knows: The SPM can predict anything at any time index; the IPM conveys to the agent, where it can be certain since statements are associated with actual observations.

Note that perception can be modality-specific; so in a visual experience, the agent only learns about triples with visual predicates, e.g., *nextTo*, *Black*, whereas in a social network experience, the agent learns about *knows* triples. See Figure 16 for an illustration.

Since embeddings are shared across triple statements, we obtain generalization to unseen triples. For example, the pKG can make statements on triples that never occurred in any perceptual experience. Another effect of the shared embeddings is the crosstalk observed in Table 9.



t*	s^*	Unary labels	0*	Binary labels
	14518	Person, Mammal, LivB	14511	on
2177	[Person]	Young, Other, Sitting	[Bus]	
	14515	Building, Other, NonLivB	14516	has
	[Building]	Old, White, Other	[Roof]	
	14511	Bus, Vehicle, NonLivB	14512	next to
	[Bus]	Old, Other, Other	[Road]	
	14518	Person, Mammal, LivB	10669	knows
		Young, Other, Sitting		
6662	18010	Person, Mammal, LivB	14518	knows
0002		young, other, other		
	8318	Person, Mammal, LivB	14518	knows
		Old, Other, Other		
-		Person, Mammal, LivB	10669	knows
	14518	Young, Other, Sitting	25066	knows
			12825	knows

Table 11: Episodic and semantic memory experience that includes multimodal data, i.e., data from a social network. The figure shows the original visual scene which is not available at the time of episodic recall. The scene index of the image is $t^* = 2177$. The top segment shows sampled subject entities (s^*) , highly ranked unary labels, a sampled object o^* , and the top predicted binary label. All labels are correct except for one binary label (blue). The second segment shows an episodic recall of an episodic social event with index $(t^* = 6662)$. At that instance, social network information (binary labels knows) was provided which is recovered in the episodic recall. Shown are 3 correct triples that were recovered in the sampling of the episodic memory. The bottom block segment shows knows statements recovered from semantic memory for $s^* = 14518$ (thus without a recall of a special episodic memory). Two binary statements are correct and one is incorrect (blue).



Figure 16: The horizontal axis stands for time and the vertical for some abstract KGdimension. The current instance is t' on the right. The light orange background box stands for the tKG. The IPM of the eKG is represented by the horizontal gray bars; they indicate, where, in the past, information was acquired. The left vertical gray bar is the pKG, an average over the eKG. The blue bars represent the IPM of the sKG and indicate where the pKG is reliable. At time instance t', the agent learns about some statements by perception (orange) and these become part of the eKG (recent episodic memory). There might be an association with another portion of the eKG, i.e., the remote episodic memory (red dotted arrow). If the agent considers information not related to current perception, it relies on remote episodic (eKG) and semantic memory (sKG) (blue dotted lines).

11. Learning

There is nothing in the mind that was not first in the senses. —John Locke

11.1 Fast Self-supervised Learning

Self-supervised learning concerns the learning without teacher-provided explicit training labels. It is biologically highly relevant: During most of life, an individual has to learn without explicit supervision. In our approach, self-supervised learning works exactly as supervised training; the difference is that the agent's predicted labels become the training labels. This is a type of bootstrap learning, where model predictions are used as targets for learning, see the bootstrap Widrow-Hoff rule (Hinton and Nowlan, 1990) and learning with pseudo labels (Lee et al., 2013).

Training	Test	Unary labels (accuracy)						
Regime	\mathbf{Set}	B-Class	P-Class	G-Class	Y/O	Color	Activity	Average
SL	Κ	100.0	100.0	100.0	100.0	100.0	100.0	100.0
\mathbf{SSL}	Κ	100.0	100.0	100.0	100.0	100.0	99.99	100.0
SSL	Ν	85.51	88.36	93.16	48.32	59.42	79.78	75.76
SL	Η	77.43	85.79	92.63	49.08	62.35	81.39	74.78
SSL	Η	77.54	86.15	92.83	48.58	62.62	82.78	75.08

Table 12: Self-supervised learning on the <u>VRD-E</u> data. "SL" stands for supervised learning, "SSL" for self-supervised learning. We first trained the model ("SL") with only 50% of the training images (i.e., 2000 images) in a supervised way. The entities in those images are denoted by K. Then we continued to train the model (SSL) with the other 50% of the training images (i.e., 2000 images). The entities in those images are denoted by N. In the first three rows we show performance on the semantic memory experience. We see perfect performance for the known entities (K) for SL in the first row; the second row shows that SSL does not "forget" the known entities. The third row shows that the performance on N is quite good, but of course not as good as on K, since predicted labels are noisier than training labels. <u>Row four and five</u> show performance in perception on new entities (holdout test set, H). The performance of SSL is better than SL, which shows that self-supervised learning also improves the detection of classes and attributes.

The self-supervised training for a novel time index and a novel entity is fast, with little interference with the remaining network. Table 12 shows our results. We can draw the following conclusions. Firstly, from row 3, we see that information of novel entities is absorbed into the semantic memory by self-supervision. Even when the visual cues are not present, the model can recover attributes related to those entities. Moreover, after self-supervised training, the knowledge on known entities is retained during the semantic recall (row 1 and row 2). Furthermore, self-supervised learning improves general perception with semantic attention, when compared to a model that was just trained on the labeled training data set (row 5 and row 6). As a conclusion, the model improves from unlabeled data, and the overall system remains stable during training.

11.2 Replay for Slow Training

The basic idea behind the complementary learning systems (CLS) theory (McClelland et al., 1995; Kumaran et al., 2016) is, first, an MTL-based fast nonparametric learning system, which roughly corresponds to the establishment of episodic memory in our approach, i.e., the forming of the \mathbf{a}_t , and, second, a parametric learning system, where the neocortex is trained in a slow process from data from the nonparametric learning system by replay. Slow training serves as the basis for the gradual acquisition of structured knowledge about the environment to neocortex (Kumaran et al., 2016).

Challenging is the absorption of new information without losing existing information, in particular, if the new information is inconsistent with the previous one and might lead to catastrophic forgetting (Kumaran et al., 2016). Our results indicate that, for the learning of new time instances and concepts, learning is quite stable in SSL. A fine-tuning of established concepts, like attribute and class representations, is much more challenging since the modification of the embedding of an established concept would affect many unary and binary statements.

11.3 Replay for Memory Consolidation

As self-supervised learning adds information, the required memory capacity grows. For each time instance associated with a salient event, a new time index with its embedding vector is added. Similarly, for each new entity, a new concept index with its embedding vector is added, as well. The current thinking is that this requires a consolidation from MTL, with a limited capacity, to the neocortex, with an essentially unlimited capacity. Systems consolidation of memory (SCM) concerns this consolidation of memory into the neocortex.

Let's first consider episodic memory. Episodic memory will mostly consolidate in longterm memory those events that are memorable, unexpected or attached with emotion. Associated with those memories might be past decisions and actions, potentially with attached outcomes. The standard theory assumes that, at some point, episodic memory becomes independent of hippocampus and MTL over a period of weeks to years (Squire and Alvarez, 1995; Frankland and Bontempi, 2005). In contrast, the multiple trace theory assumes that both hippocampus and MTL remain involved (Nadel and Moscovitch, 1997; Jonides et al., 2008; Greenberg and Verfaellie, 2010). From our work, we would propose that indices and embeddings become independent of MTL, but that MTL remains the manager of complex spatial and relational memories (Whittington et al., 2020). In particular, the hippocampus is considered to be at the center of a memory system that organizes and reconstructs complex experiences according to their spatiotemporal context. In general, it is assumed that consolidation involves both MTL and the medial prefrontal cortex (mPFC) (Tonegawa et al., 2018), where the transferred indices might be established (Frankland and Bontempi, 2005). After consolidation, episodic memories might be organized in temporal order or according to a similarity in representation (see, Figure 11). It is assumed that consolation might be a process executed completely or partially during sleep (Stickgold, 2005).

Consolidation by replay in our model can be executed as follows: an index $n_{MTL}(i)$ in MTL is activated which activates the representation layer with $\mathbf{q} \leftarrow \mathbf{a}_i$; this activation is then learned in the connection weights of a newly formed index $n_{NEO}(i)$ in the neocortex, e.g., by a form of Hebbian learning. Thus, these index-duplicates in the neocortex would inherit the connection weights. If the index in the neocortex becomes more distributed, this would lead to greater robustness of memories after consolidation. For a while, both representations exist in parallel, but gradually, the index representation in the neocortex might become dominant. Consolidation by replay has the advantage that there is no need for direct interactions of indices in both storage sites, but there are only indirect interactions by a shared activation of the representation layer. Replay might play a role in memory reconsolidation and might also be one way of how the brain implements large-scale structural changes in the brain, in general, e.g., as a consequence of brain damage or as a consequence of a changing world with new statistics. Replay might also be the way of operation for reconstructing a complex episode in the hippocampus. Here, a consolidated index would be activated and an index in MTL copies the embedding pattern. For our model, the location of the index is irrelevant; in either case, decoding relies on the same machinery (Figure 3).

Training by episodic memory replay might be also important for the gradual transition from episodic to semantic memory, in which episodic memory reduces its sensitivity and association to particular events so that the information can be generalized as semantic memory. Some theories speculate that episodic memory may be the "gateway" to semantic memory (Baddeley and Hitch, 1974; Squire, 1987; Baddeley, 1988; Steyvers et al., 2004; Socher et al., 2009; McClelland et al., 1995; Yee et al., 2014; Kumar et al., 2015). In our model, episodic and semantic memory are both trained during perception; replay might correspond to the repeated presentation of a pattern during gradient-based learning.

Now, let's consider new entities. When consolidated in neocortex, concept indices might find representations in the inferior parietal cortex, large parts of the middle and inferior temporal gyri, and anterior portions of the fusiform gyrus (Binder and Desai, 2011). Concepts indices are thought to be slowly induced in the neocortex by a gradual recruitment of neocortical memory circuits in long-term storage of hippocampal memories (McClelland et al., 1995; Squire and Alvarez, 1995; Frankland et al., 2001; Moser et al., 2015).

During the course of consolidation, memories need to become interleaved into a network of existing related memories in the neocortex (Edgell and Piaget, 1929; Bartlett, 1995). Figure 10 indicates a possible two-dimensional map of concept organization and Figure 11 of episodic organization. This interleaving process requires modifications of the preexisting network structure (Preston and Eichenbaum, 2013). Cognitive maps might be more pronounced after consolidation in the neocortex with similar memories being close.

12. Summary, Conclusions and Future Work

We have shown how perception, episodic memory, and semantic memory can be realized by different functional and operational modes describing the oscillating interactions between an index layer and a representation layer in the BTN.

Table 13 gives an overview of some of our main experimental results. Fast perception permits the execution of fast reactions and only requires a representation layer. Simple perception is sufficient for the labeling of entities with attributes and classes, which can be presented holistically as the activation pattern $\mathbf{n}_{\underline{O}}$, or in serial triple formats. Representations for individual entities and time instances enrich perception by unary perception and are essential for realizing episodic and semantic memory. For relationship detection, binary indices and working memory are required. Generalized statements permit inference on the class and attribute level.

We have emphasized the role of episodic and semantic memory in perception. Essentially, we realize an associative memory where recency is key for the recall of recent episodic memories, closeness in scene representation for remote episodic memory, and closeness in concept representations for semantic memory.

The brain operates both at the symbolic index level and the subsymbolic embedding level and there is no recall of an entity, class, attribute, or time instance, without a tied recall of their subsymbolic associations. This is also a feature of our model with symbolic indices

Added Com-	Perception	Episodic Mem-	Semantic Mem-
nonont		ory Experience	ory Experience
ponent		(-VO)	ory Experience
		(eKG))	
Representation	Fast perception for quick ac-	Required	Required
layer	tions: feed, flee,		
Indices for	Simple perception; holistic	Required	Required
attributes and	understanding by the activa-		
classes in $\mathbf{n}_{\underline{O}}$	tion pattern $\mathbf{n}_{\underline{O}}$		
Triple serial-	Enables triples like $(s', type,$	Required	Required
ization	Dog), (s', color, Black)		
Entity indices	Unary perception; enables	Required for	Enables recall of
in \mathbf{n}_S and $\mathbf{n}_{\underline{O}}$	recognition and labeling	episodic mem-	detailed informa-
	of known entities; enables	ory (binding	tion on individual
	triples like $(s', sameAs,$	problem)	entities
	Sparky), (Sparky, color,		
	Black), (Sparky, type, Dog)		
Time indices	Episodic attention	Enables the recall	-
		of recent and	
		remote episodic	
		memory	
Working mem-	Enables triples like (s', look-	\leftarrow (same)	\leftarrow (same)
ory and binary	sAt, o') and, with sameAs		
indices	reasoning, (Sparky, looksAt,		
	Jack)		
Triple serial-	Enables a variety of triples	\leftarrow (same)	Defines
ization and	like (Dog, hasAttribute,		$\mathbb{P}(Y_{Dog, \ color, \ Black}),$
generalized	Black), (Dog, looksAt, Per-		i.e., the probabil-
statements	son)		ity that an entity
			is black, if it is a
			dog

Table 13: Overview: Added components and enabled functionalities

and subsymbolic embeddings. Statement probabilities associated with observed entities are represented either in a distributed way, e.g., as vectors $\mathbf{n}_{\underline{O}}$ and \mathbf{n}_{P} , or in a serial way as a sequence of triples. This becomes important in communication by spoken language.

Our work suggests that perception, episodic and semantic memory all rely on the same brainware. It also provides an explanation, why the brain is robust towards brain damage. Assuming that the index layer has a distributed representation after consolidation, the two important layers, i.e., the index layer and the representation layer, and their interconnections should be robust against disturbances. The most sensitive phases are likely, first, the formation of new memories, second, the memory consolidation process, and, third, the reconstruction of complex spatial or episodic memories. All these functions are associated with MTL, and are known to be affected by a deterioration of MTL, e.g., by brain damage and old age.

As discussed, a big open question is how some of the proposed functionalities could be implemented anatomically, e.g., the rapid establishment of a novel episodic memory. A technical implementation is quite simple: A new index is formed, together with a connection vector copying the episodic memory trace. How this is done in brainware is still largely unknown (Quiroga et al., 2013).

As part of future work, we will explore to what fidelity a past scene can be reconstructed visually (Johnson et al., 2018), i.e., the question of how strong an agent's visual recall really is. Another future project is to generalize our approach to videos, taking into account temporal continuity. After all, an agent lives in a continuous world, and visual inputs do not arrive in the form of discrete images. Although we argue that the interpretation of episodic memory as a set of images with timestamps is quite convincing, video data permits the exploration of episodic memory as a set of sequences of scenes.

Furthermore, we plan to explore how our approach can be extended to permit forecasting and how it can be related to decision making, e.g., reinforcement learning and control.

In this paper, we did not focus on spatial representations. It is well known that MTL is not only responsible for forming novel episodic memories but also for forming spatial representations, e.g., in the form of grid cells and place cells and for representing and reasoning in relational networks. The integration of spatial information and spatial reasoning is part of future work, including the navigation in the connected graphs formed by the spatial and relational networks (Whittington et al., 2020).

It goes without saying, that our paper only presents a hopefully useful view on cognitive and neural processing and by no means neither a complete picture of all intricate aspects of perception and memory, nor the only way that the brain analysis perceptual input.

References

- Mehdi Ali, Max Berrendorf, Charles Tapley Hoyt, Laurent Vermue, Sahand Sharifzadeh, Volker Tresp, and Jens Lehmann. Pykeen 1.0: A python library for training and evaluating knowledge graph embeddings. *Journal of Machine Learning Research*, 22(82):1–6, 2021.
- Peter Anderson, Xiaodong He, Chris Buehler, Damien Teney, Mark Johnson, Stephen Gould, and Lei Zhang. Bottom-up and top-down attention for image captioning and visual question answering. In CVPR, 2018.
- Sören Auer, Christian Bizer, Georgi Kobilarov, Jens Lehmann, Richard Cyganiak, and Zachary Ives. *DBpedia*. Lecture Notes in Computer Science. Springer, 2007.
- E Awh and EK Vogel. Online and off-line memory states in the human brain. the Cognitive Neurosciences, 2020.
- Bernard J Baars. In the theater of consciousness: The workspace of the mind. Oxford University Press, USA, 1997.

- Alan Baddeley. Cognitive psychology and human memory. Trends in neurosciences, 11(4): 176–181, 1988.
- Alan Baddeley. Working memory. Science, 255(5044):556–559, 1992.
- Alan D Baddeley and Graham Hitch. Working memory. The psychology of learning and motivation, 8:47–89, 1974.
- Stephan Baier, Yunpu Ma, and Volker Tresp. Improving visual relationship detection using semantic modeling. In ISWC. Springer, 2017.
- Stephan Baier, Yunpu Ma, and Volker Tresp. Improving information extraction from images with learned semantic models. In *Proceedings of the 27th International Joint Conference* on Artificial Intelligence, pages 5214–5218. AAAI Press, 2018.
- Frederic C Bartlett. Remembering: A study in experimental and social psychology, volume 14. Cambridge University Press, 1995.
- Danielle S Bassett and Olaf Sporns. Network neuroscience. *Nature neuroscience*, 20(3):353, 2017.
- Suzanna Becker. A computational principle for hippocampal learning and neurogenesis. *Hippocampus*, 15(6):722–738, 2005.
- Jeffrey R Binder and Rutvik H Desai. The neurobiology of semantic memory. *Trends in cognitive sciences*, 15(11):527–536, 2011.
- Marcus D Bloice, Christof Stocker, and Andreas Holzinger. Augmentor: an image augmentation library for machine learning. arXiv preprint arXiv:1708.04680, 2017.
- Kurt Bollacker, Colin Evans, Praveen Paritosh, Tim Sturge, and Jamie Taylor. Freebase. In ACM SIGMOD. ACM, 2008.
- Daniel Bor and Anil K Seth. Consciousness and the prefrontal parietal network: insights from attention, working memory, and chunking. *Frontiers in Psychology*, 3:63, 2012.
- Antoine Bordes, Nicolas Usunier, Alberto Garcia-Duran, Jason Weston, and Oksana Yakhnenko. Translating Embeddings for Modeling Multi-relational Data. In Advances in Neural Information Processing Systems 26, 2013.
- Mathew Botvinick, Sam Ritter, Jane X Wang, Zeb Kurth-Nelson, Charles Blundell, and Demis Hassabis. Reinforcement learning, fast and slow. *Trends in cognitive sciences*, 2019.
- Timothy J Buschman and Earl K Miller. How working memory works. The Cognitive Neurosciences, page 357, 2020.
- Andrew Carlson, Justin Betteridge, Bryan Kisiel, Burr Settles, Estevam R. Hruschka Jr., and Tom M. Mitchell. Toward an Architecture for Never-Ending Language Learning. In AAAI, AAAI'10, 2010.

- Peter Dayan, Geoffrey E Hinton, Radford M Neal, and Richard S Zemel. The helmholtz machine. *Neural computation*, 7(5):889–904, 1995.
- Wendy A de Heer, Alexander G Huth, Thomas L Griffiths, Jack L Gallant, and Frédéric E Theunissen. The hierarchical cortical organization of human speech processing. *Journal* of Neuroscience, 37(27):6539–6557, 2017.
- Stanislas Dehaene. Consciousness and the brain: Deciphering how the brain codes our thoughts. Penguin, 2014.
- Tim Dettmers, Pasquale Minervini, Pontus Stenetorp, and Sebastian Riedel. Convolutional 2d knowledge graph embeddings. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.
- Xin Dong, Evgeniy Gabrilovich, Geremy Heitz, Wilko Horn, Ni Lao, Kevin Murphy, Thomas Strohmann, Shaohua Sun, and Wei Zhang. Knowledge Vault: A Web-scale Approach to Probabilistic Knowledge Fusion. In *Proceedings of the 20th ACM SIGKDD International* Conference on Knowledge Discovery and Data Mining, 2014.
- Katherine D Duncan and Daphna Shohamy. Memory states influence value-based decisions. Journal of Experimental Psychology: General, 145(11):1420, 2016.
- Beatrice Edgell and Jean Piaget. The child's conception of the world, 1929.
- Howard Eichenbaum. Time cells in the hippocampus. *Nature Reviews Neuroscience*, 15 (11), 2014.
- Howard Eichenbaum, Magdalena Sauvage, Norbert Fortin, Robert Komorowski, and Paul Lipton. Towards a functional organization of episodic memory in the medial temporal lobe. *Neuroscience & Biobehavioral Reviews*, 36(7):1597–1608, 2012.
- Jonathan St BT Evans. In two minds: dual-process accounts of reasoning. Trends in cognitive sciences, 7(10):454–459, 2003.
- Christiane Fellbaum. Wordnet. In *Theory and applications of ontology: computer applications*, pages 231–243. Springer, 2010.
- Jerry A Fodor. The language of thought, volume 5. Harvard university press, 1975.
- Paul W Frankland and Bruno Bontempi. The organization of recent and remote memories. Nature Reviews Neuroscience, 6(2):119–130, 2005.
- Paul W Frankland, Cara O'Brien, Masuo Ohno, Alfredo Kirkwood, and Alcino J Silva. α -camkii-dependent plasticity in the cortex is required for permanent memory. *Nature*, 411(6835):309–313, 2001.
- Karl Friston. The free-energy principle: a unified brain theory? Nature Reviews Neuroscience, 11(2):127–138, 2010.
- Karl J Friston, G Tononi, O Sporns, and GM Edelman. Characterising the complexity of neuronal interactions. *Human Brain Mapping*, 3(4):302–314, 1995.

- Peter Gärdenfors. The Geometry of Meaning: Semantics Based on Conceptual Spaces. MIT Press, 2016.
- Michael S Gazzaniga, Richard B Ivry, and George Ronald Mangun. *Cognitive Neuroscience: The biology of the mind.* New York: WW Norton, fourth edition edition, 2013.
- Mark A Gluck, Eduardo Mercado, and Catherine E Myers. *Learning and memory: From brain to behavior*. Palgrave, 2013.
- Elizabeth Gould, Alison J Reeves, Michael SA Graziano, and Charles G Gross. Neurogenesis in the neocortex of adult primates. *Science*, 286(5439):548–552, 1999.
- Anirudh Goyal, Aniket Didolkar, Alex Lamb, Kartikeya Badola, Nan Rosemary Ke, Nasim Rahaman, Jonathan Binas, Charles Blundell, Michael Mozer, and Yoshua Bengio. Coordination among neural modules through a shared global workspace. arXiv preprint arXiv:2103.01197, 2021.
- Alex Graves, Greg Wayne, and Ivo Danihelka. Neural turing machines. arXiv preprint arXiv:1410.5401, 2014.
- Daniel L Greenberg and Mieke Verfaellie. Interdependence of episodic and semantic memory: evidence from neuropsychology. *Journal of the International Neuropsychological society*, 16(05):748–753, 2010.
- Thomas L Griffiths, Charles Kemp, and Joshua B Tenenbaum. Bayesian models of cognition. In *The Cambridge Handbook of Computational Psychology*. Cambridge University Press, 2008.
- Wolfgang Hackbusch. *Tensor spaces and numerical tensor calculus*, volume 42. Springer, 2012.
- Graeme S. Halford, William H. Wilson, and Steven Phillips. Processing capacity defined by relational complexity: Implications for comparative, developmental, and cognitive psychology. *Behavioral and Brain Sciences*, 21(06):803-831, 1998. URL http: //journals.cambridge.org/abstractS0140525X98001769.
- Zhen Han, Yunpu Ma, Yuyi Wang, Stephan Guennemann, and Volker Tresp. Graph hawkes neural network for forecasting on temporal knowledge graphs. In *Automated Knowledge Base Construction*, 2020.
- Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In Proceedings of the IEEE international conference on computer vision, pages 1026–1034, 2015.
- Gregory Hickok and David Poeppel. The cortical organization of speech processing. *Nature reviews neuroscience*, 8(5):393, 2007.
- Marcel Hildebrandt, Jorge Andres Quintero Serna, Yunpu Ma, Martin Ringsquandl, Mitchell Joblin, and Volker Tresp. Reasoning on knowledge graphs with debate dynamics. AAAI, 2020.

- Geoffrey E Hinton. A practical guide to training restricted boltzmann machines. *Momentum*, 9(1):926, 2010.
- Geoffrey E Hinton and Steven J Nowlan. The bootstrap widrow-hoff rule as a clusterformation algorithm. *Neural Computation*, 2(3):355–362, 1990.
- Douglas L Hintzman. Minerva 2: A simulation model of human memory. Behavior Research Methods, Instruments, & Computers, 16(2):96–101, 1984.
- Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. Neural computation, 9(8):1735–1780, 1997.
- Bernhard Hommel, Jochen Müsseler, Gisa Aschersleben, and Wolfgang Prinz. The theory of event coding (tec): A framework for perception and action planning. *Behavioral and brain sciences*, 24(5):849–878, 2001.
- Drew Hudson and Christopher D Manning. Learning by abstraction: The neural state machine. In Advances in Neural Information Processing Systems, pages 5901–5914, 2019.
- Michael S Humphreys, John D Bain, and Ray Pike. Different ways to cue a coherent memory system: A theory for episodic, semantic, and procedural tasks. *Psychological Review*, 96 (2):208, 1989.
- Alexander G. Huth, Wendy A. de Heer, Thomas L. Griffiths, Frédéric E. Theunissen, and Jack L. Gallant. Natural speech reveals the semantic maps that tile human cerebral cortex. *Nature*, 2016.
- Jeffry S Isaacson and Massimo Scanziani. How inhibition shapes cortical activity. *Neuron*, 72(2):231–243, 2011.
- Justin Johnson, Ranjay Krishna, Michael Stark, Li-Jia Li, David Shamma, Michael Bernstein, and Li Fei-Fei. Image retrieval using scene graphs. In *Proceedings of the IEEE* conference on computer vision and pattern recognition, pages 3668–3678, 2015.
- Justin Johnson, Agrim Gupta, and Li Fei-Fei. Image generation from scene graphs. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1219–1228, 2018.
- John Jonides, Richard L Lewis, Derek Evan Nee, Cindy A Lustig, Marc G Berman, and Katherine Sledge Moore. The mind and brain of short-term memory. Annual review of psychology, 59:193, 2008.
- Alexander B. Jung, Kentaro Wada, Jon Crall, Satoshi Tanaka, Jake Graving, Christoph Reinders, Sarthak Yadav, Joy Banerjee, Gábor Vecsei, Adam Kraft, Zheng Rui, Jirka Borovec, Christian Vallentin, Semen Zhydenko, Kilian Pfeiffer, Ben Cook, Ismael Fernández, François-Michel De Rainville, Chi-Hung Weng, Abner Ayala-Acevedo, Raphael Meudec, and Matias Laporte. imgaug. https://github.com/aleju/imgaug, 2020. Online; accessed 01-Feb-2020.

Daniel Kahneman. Thinking, fast and slow. Macmillan, 2011.

Pentti Kanerva. Sparse distributed memory. MIT press, 1988.

- Markus Kiefer and Friedemann Pulvermüller. Conceptual representations in mind and brain: theoretical developments, current evidence and future directions. *cortex*, 48(7): 805–825, 2012.
- Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. arXiv preprint arXiv:1412.6980, 2014.
- Takashi Kitamura, Christopher J Macdonald, and Susumu Tonegawa. Entorhinal– hippocampal neuronal circuits bridge temporally discontiguous events. Learning & memory (Cold Spring Harbor, NY), 22(9):438–443, 2015a.
- Takashi Kitamura, Chen Sun, Jared Martin, Lacey J Kitch, Mark J Schnitzer, and Susumu Tonegawa. Entorhinal cortical ocean cells encode specific contexts and drive contextspecific fear memory. *Neuron*, 87(6):1317–1331, 2015b.
- Graham Klyne and Jeremy J. Carroll. Resource Description Framework (RDF): Concepts and Abstract Syntax, February 2004. URL http://www.w3.org/TR/2004/REC-rdf-concepts-20040210/.
- David C Knill and Alexandre Pouget. The bayesian brain: the role of uncertainty in neural coding and computation. *Trends in Neurosciences*, 27(12):712–719, 2004.
- Christof Koch. Keep it in mind. Scientific American Mind, 25(3):26–29, 2014.
- Christof Koch, Marcello Massimini, Melanie Boly, and Giulio Tononi. Neural correlates of consciousness: progress and problems. *Nature Reviews Neuroscience*, 17(5):307, 2016.
- Konrad P Körding, Shih-pi Ku, and Daniel M Wolpert. Bayesian integration in force estimation. Journal of Neurophysiology, 92(5):3161–3165, 2004.
- Nikolaus Kriegeskorte and Pamela K Douglas. Cognitive computational neuroscience. Nature neuroscience, 21(9):1148–1160, 2018.
- Ranjay Krishna, Yuke Zhu, Oliver Groth, Justin Johnson, Kenji Hata, Joshua Kravitz, Stephanie Chen, Yannis Kalantidis, Li-Jia Li, and David A Shamma. Visual genome: Connecting language and vision using crowdsourced dense image annotations. *Interna*tional Journal of Computer Vision, 123(1):32–73, 2017.
- Ankit Kumar, Ozan Irsoy, Jonathan Su, James Bradbury, Robert English, Brian Pierce, Peter Ondruska, Ishaan Gulrajani, and Richard Socher. Ask me anything: Dynamic memory networks for natural language processing. arXiv preprint arXiv:1506.07285, 2015.
- Dharshan Kumaran, Demis Hassabis, and James L McClelland. What learning systems do intelligent agents need? Trends in Cognitive Sciences, 20(7):512–534, 2016.
- Dong-Hyun Lee et al. Pseudo-label: The simple and efficient semi-supervised learning method for deep neural networks. In Workshop on challenges in representation learning, *ICML*, 2013.

- David A Leopold, Peter L Strick, Danielle S Bassett, Randy M Bruno, Hermann Cuntz, Kristen M Harris, Marcel Oberlaender, and Marcus E Raichle. Functional architecture of the cerebral cortex. In *The Neocortex*, pages 141–164. MIT Press, 2019.
- Cewu Lu, Ranjay Krishna, Michael Bernstein, and Li Fei-Fei. Visual relationship detection with language priors. In *ECCV*. Springer, 2016.
- Ruotian Luo, Ning Zhang, Bohyung Han, and Linjie Yang. Context-aware zero-shot recognition. arXiv preprint arXiv:1904.09320, 2019.
- Yunpu Ma, Marcel Hildebrandt, Stephan Baier, and Volker Tresp. Holistic representations for memorization and inference. UAI, 2018a.
- Yunpu Ma, Volker Tresp, and Erik A Daxberger. Embedding models for episodic knowledge graphs. Journal of Web Semantics, 2018b.
- James L McClelland, Bruce L McNaughton, and Randall C O'Reilly. Why there are complementary learning systems in the hippocampus and neocortex: insights from the successes and failures of connectionist models of learning and memory. *Psychological review*, 102 (3):419, 1995.
- Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, and Georg Ostrovski. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.
- Morris Moscovitch, Roberto Cabeza, Gordon Winocur, and Lynn Nadel. Episodic memory and beyond: the hippocampus and neocortex in transformation. *Annual review of psychology*, 67:105–134, 2016.
- May-Britt Moser, David C Rowland, and Edvard I Moser. Place cells, grid cells, and memory. *Cold Spring Harbor perspectives in biology*, 7(2):a021808, 2015.
- Laura L Murray and Amy E Ramage. Assessing the executive function abilities of adults with neurogenic communication disorders. In *Seminars in speech and language*, volume 21. Copyright© 2000 by Thieme Medical Publishers, Inc., 333 Seventh Avenue, New ..., 2000.
- Lynn Nadel and Morris Moscovitch. Memory consolidation, retrograde amnesia and the hippocampal complex. *Current opinion in neurobiology*, 7(2):217–227, 1997.
- Maximilian Nickel, Volker Tresp, and Hans-Peter Kriegel. A three-way model for collective learning on multi-relational data. In *Proceedings of the 28th International Conference on International Conference on Machine Learning*, pages 809–816, 2011.
- Maximilian Nickel, Volker Tresp, and Hans-Peter Kriegel. Factorizing YAGO: scalable machine learning for linked data. In *Proceedings of the 21st International Conference on* World Wide Web, WWW '12, pages 271–280, 2012.

- Maximilian Nickel, Kevin Murphy, Volker Tresp, and Evgeniy Gabrilovich. A review of relational machine learning for knowledge graphs. *Proceedings of the IEEE*, 2015a.
- Maximilian Nickel, Lorenzo Rosasco, and Tomaso Poggio. Holographic embeddings of knowledge graphs. arXiv preprint arXiv:1510.04935, 2015b.
- Natasha Noy, Alan Rector, Pat Hayes, and Chris Welty. Defining n-ary relations on the semantic web. *W3C working group note*, 12(4), 2006.
- Adam F Osth and Simon Dennis. Sources of interference in item and associative recognition memory. *Psychological review*, 122(2):260, 2015.
- András Pellionisz and Rodolfo Llinás. Tensorial approach to the geometry of brain function: Cerebellar coordination via a metric tensor. *Neuroscience*, 5(7):1125–1136, 1980.
- Tony Plate. A common framework for distributed representation schemes for compositional structure. Connectionist systems for knowledge representation and deduction, pages 15–34, 1997.
- Tomaso Poggio, Andrzej Banburski, and Qianli Liao. Theoretical issues in deep networks. Proceedings of the National Academy of Sciences, 117(48):30039–30045, 2020.
- Jordan B Pollack. Recursive distributed representations. Artificial Intelligence, 46(1):77–105, 1990.
- Margot Popp, Natalie M Trumpp, and Markus Kiefer. Processing of action and sound verbs in context: An fmri study. *Translational Neuroscience*, 10(1):200–222, 2019.
- Alison R Preston and Howard Eichenbaum. Interplay of hippocampus and prefrontal cortex in memory. *Current Biology*, 23(17):R764–R773, 2013.
- R Quian Quiroga, Leila Reddy, Gabriel Kreiman, Christof Koch, and Itzhak Fried. Invariant visual representation by single neurons in the human brain. *Nature*, 435(7045):1102–1107, 2005.
- Rodrigo Quian Quiroga. Concept cells: the building blocks of declarative memory functions. Nat Rev Neurosci, 13(8), 2012.
- Rodrigo Quian Quiroga, Itzhak Fried, and Christof Koch. Brain cells for grandmother. Scientific American, 308(2):30–35, 2013.
- Matthew A Lambon Ralph, Elizabeth Jefferies, Karalyn Patterson, and Timothy T Rogers. The neural and computational bases of semantic cognition. *Nature Reviews Neuroscience*, 18(1):42, 2017.
- Rajesh PN Rao and Dana H Ballard. Predictive coding in the visual cortex: a functional interpretation of some extra-classical receptive-field effects. *Nature neuroscience*, 2(1): 79–87, 1999.
- M. Richardson and P. Domingos. Markov logic networks. *Machine Learning*, 62(1):107–136, 2006. ISSN 0885-6125.

Edmund T Rolls. Cerebral cortex: principles of operation. Oxford University Press, 2016.

- Shirley-Ann Rueschemeyer, Daan van Rooij, Oliver Lindemann, Roel M Willems, and Harold Bekkering. The function of words: Distinct neural correlates for words denoting differently manipulable objects. *Journal of cognitive neuroscience*, 22(8):1844–1851, 2010.
- Daniel Ruffinelli, Samuel Broscheit, and Rainer Gemulla. You can teach an old dog new tricks! on training knowledge graph embeddings. In *International Conference on Learning Representations*, 2019.
- Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, and Michael Bernstein. Imagenet large scale visual recognition challenge. *International journal of computer vision*, 115(3):211– 252, 2015.
- Tom Schaul, John Quan, Ioannis Antonoglou, and David Silver. Prioritized experience replay. arXiv preprint arXiv:1511.05952, 2015.
- Martin Schmitt, Sahand Sharifzadeh, Volker Tresp, and Hinrich Schütze. An unsupervised joint system for text generation from knowledge graphs and semantic parsing. In Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP), pages 7117–7130, 2020.
- Sahand Sharifzadeh, Max Berrendorf, and Volker Tresp. Improving visual relation detection using depth maps. arXiv preprint arXiv:1905.00966, 2019.
- Sahand Sharifzadeh, Sina Moayed Baharlou, and Volker Tresp. Classification by attention: Scene graph classification with prior knowledge, 2020.
- Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. arXiv preprint arXiv:1409.1556, 2014.
- Wolf Singer. Consciousness and the binding problem. Annals of the New York Academy of Sciences, 929(1):123–146, 2001.
- Amit Singhal. Introducing the Knowledge Graph: things, not strings. Official Google Blog, 2012.
- Paul Smolensky. Information processing in dynamical systems: Foundations of harmony theory. Technical report, Colorado Univ at Boulder Dept of Computer Science, Colorado Univ at Boulder Dept of Computer Science, 1986.
- Paul Smolensky. Tensor product variable binding and the representation of symbolic structures in connectionist systems. *Artificial intelligence*, 46(1):159–216, 1990. URL http://www.sciencedirect.com/science/article/pii/000437029090007M.
- Richard Socher, Samuel Gershman, Per Sederberg, Kenneth Norman, Adler J Perotte, and David M Blei. A bayesian analysis of dynamics in free recall. In Advances in neural information processing systems, pages 1714–1722, 2009.

- Richard Socher, Danqi Chen, Christopher D Manning, and Andrew Ng. Reasoning With Neural Tensor Networks for Knowledge Base Completion. In Advances in Neural Information Processing Systems 26, 2013.
- Olaf Sporns. Graph theory methods: applications in brain networks. *Dialogues in clinical* neuroscience, 20(2):111, 2018.
- Larry R Squire. Memory and brain. Oxford UP, 1987.
- Larry R Squire and Pablo Alvarez. Retrograde amnesia and memory consolidation: a neurobiological perspective. *Current opinion in neurobiology*, 5(2):169–177, 1995.
- Mark Steyvers, Richard M Shiffrin, and Douglas L Nelson. Word association spaces for predicting semantic similarity effects in episodic memory. Experimental cognitive psychology and its applications: Festschrift in honor of Lyle Bourne, Walter Kintsch, and Thomas Landauer, pages 237–249, 2004.
- Robert Stickgold. Sleep-dependent memory consolidation. *Nature*, 437(7063):1272–1278, 2005.
- Fabian M. Suchanek, Gjergji Kasneci, and Gerhard Weikum. Yago: A Core of Semantic Knowledge. In WWW, WWW '07, 2007.
- Sainbayar Sukhbaatar, Jason Weston, and Rob Fergus. End-to-end memory networks. In Advances in neural information processing systems, pages 2440–2448, 2015.
- Danny Sullivan. A reintroduction to our knowledge graph and knowledge panels. *Google* product updates, 2020.
- Ron Sun and Todd Peterson. Learning in reactive sequential decision tasks: The clarion model. In *Proceedings of International Conference on Neural Networks (ICNN'96)*, volume 2, pages 1073–1078. IEEE, 1996.
- Hao Tan. Bottom-up attention with detectron2, 2021. URL https://github.com/ airsplay/py-bottom-up-attention.
- Joshua B Tenenbaum, Thomas L Griffiths, and Charles Kemp. Theory-based bayesian models of inductive learning and reasoning. *Trends in cognitive sciences*, 10(7):309–318, 2006.
- Timothy J Teyler and Pascal DiScenna. The hippocampal memory indexing theory. *Behavioral neuroscience*, 1986.
- Timothy J Teyler and Jerry W Rudy. The hippocampal indexing theory and episodic memory. *Hippocampus*, 2007.
- Robert Tibshirani. Regression shrinkage and selection via the lasso. Journal of the Royal Statistical Society: Series B (Methodological), 58(1):267–288, 1996.
- Edward C Tolman. Cognitive maps in rats and men. Psychological review, 55(4):189, 1948.

- Rosario Tomasello, Max Garagnani, Thomas Wennekers, and Friedemann Pulvermüller. Brain connections of words, perceptions and actions: A neurobiological model of spatiotemporal semantic activation in the human cortex. *Neuropsychologia*, 98:111–129, 2017.
- Susumu Tonegawa, Mark D Morrissey, and Takashi Kitamura. The role of engram cells in the systems consolidation of memory. *Nature Reviews Neuroscience*, 19(8):485, 2018.
- Volker Tresp and Yunpu Ma. The tensor memory hypothesis. In NIPS Workshop on Representation Learning, 2016.
- Volker Tresp, Cristóbal Esteban, Yinchong Yang, Stephan Baier, and Denis Krompaß. Learning with memory embeddings. arXiv preprint arXiv:1511.07972, 2015.
- Volker Tresp, Yunpu Ma, and Stephan Baier. Tensor memories. In Conference on Cognitive Computational Neuroscience, 2017a.
- Volker Tresp, Yunpu Ma, Stephan Baier, and Yinchong Yang. Embedding learning for declarative memories. In *European Semantic Web Conference*, pages 202–216. Springer, 2017b.
- Volker Tresp, Sahand Sharifzadeh, and Dario Konopatzki. A model for perception and memory. In *Conference on Cognitive Computational Neuroscience*, 2019.
- Volker Tresp, Sahand Sharifzadeh, Dario Konopatzki, and Yunpu Ma. The tensor brain: Semantic decoding for perception and memory, 2020.
- Théo Trouillon, Johannes Welbl, Sebastian Riedel, Éric Gaussier, and Guillaume Bouchard. Complex embeddings for simple link prediction. In *International Conference on Machine Learning*, pages 2071–2080. PMLR, 2016.
- Endel Tulving. Episodic and semantic memory 1. Organization of Memory. London: Academic, 381(e402):4, 1972.
- Endel Tulving. *Elements of episodic memory*. Oxford University Press, 1985.
- Endel Tulving. Episodic memory: from mind to brain. Annual review of psychology, 53(1): 1–25, 2002.
- Martijn P van den Heuvel and Olaf Sporns. Network hubs in the human brain. Trends in cognitive sciences, 17(12):683–696, 2013.
- Laurens Van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. Journal of machine learning research, 9(11), 2008.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In Advances in neural information processing systems, pages 5998–6008, 2017.
- Jason Weston, Sumit Chopra, and Antoine Bordes. Memory networks. arXiv preprint arXiv:1410.3916, 2014.

- James CR Whittington, Timothy H Muller, Shirley Mark, Guifen Chen, Caswell Barry, Neil Burgess, and Timothy EJ Behrens. The tolman-eichenbaum machine: Unifying space and relational memory through generalization in the hippocampal formation. *Cell*, 183(5): 1249–1263, 2020.
- Bishan Yang, Wen-tau Yih, Xiaodong He, Jianfeng Gao, and Li Deng. Embedding entities and relations for learning and inference in knowledge bases. arXiv preprint arXiv:1412.6575, 2014.
- Jianwei Yang, Jiasen Lu, Stefan Lee, Dhruv Batra, and Devi Parikh. Graph r-cnn for scene graph generation. In Proceedings of the European Conference on Computer Vision (ECCV), pages 670–685, 2018.
- Eiling Yee, Evangelia G Chrysikou, and Sharon L Thompson-Schill. *The Cognitive Neuroscience of Semantic Memory*. Oxford Handbook of Cognitive Neuroscience, Oxford University Press, 2014.
- Rowan Zellers, Mark Yatskar, Sam Thomson, and Yejin Choi. Neural motifs: Scene graph parsing with global context. In *Proceedings of the IEEE Conference on Computer Vision* and Pattern Recognition, pages 5831–5840, 2018.
- Hanwang Zhang, Zawlin Kyaw, Shih-Fu Chang, and Tat-Seng Chua. Visual translation embedding network for visual relation detection. In *Proceedings of the IEEE conference* on computer vision and pattern recognition, pages 5532–5540, 2017.

13. Appendix

13.1 Attention Approximation

Consider episodic attention. Let Y stand for all unary and binary statements associated with s, o, t. We want to eliminate the sampling for the time index and calculate

$$\mathbb{P}(Y, s, o | scene_{t'}) = \sum_{t=1}^{N_T} \mathbb{P}(Y, s, o | \mathbf{f}(scene_{t'}) + \mathbf{a}_t) \mathbb{P}(t | scene_{t'}).$$

 N_T is the number of past episodes. Under the attention approximation, this becomes

$$\mathbb{P}(Y, s, o | scene_{t'}) \approx \mathbb{P}(Y, s, o | \mathbf{f}(scene_{t'}) + \mathbf{a}_T(scene_{t'}))$$

with

$$\mathbf{a}_T(scene_{t'}) = \mathbb{E}(\mathbf{a}|scene_{t'}) = \sum_{t=1}^{N_T} \mathbf{a}_t \mathbb{P}(t|scene_{t'}) = \sum_{t=1}^{N_T} \mathbf{a}_t \operatorname{softmax}_t^{\beta} \left(\mathbf{a}_t^{\top} \mathbf{f}(scene_{t'}) \right).$$

This is Equation 12. For the past episodes, we can initialize $\mathbf{a}_t = \mathbf{f}(scene_t)$, by a form of Hebbian learning, but actually we write more explicitly $\mathbf{a}_t(data_t)$ to indicate that \mathbf{a}_t is optimized to fit the data from the observations at time t. The advantage of this local

optimization is that our attention mechanism is more modular than the classical attention approximation and that the embeddings of past episodes are fixed, after optimization, and can be stored as connection weights. We propose that this is more biologically plausible than the end-to-end training in classical transformer attention (Vaswani et al., 2017). Similarly, we can obtain the semantic approximation. For the transition from episodic to semantic memory, we can use the same equations, but without the scene input and notation $\bar{\mathbf{a}}$ instead of \mathbf{a}_T . We have

$$\mathbb{P}(Y, s, o) = \sum_{t=1}^{N_T} \mathbb{P}(Y, s, o | \mathbf{a}_t) \mathbb{P}(t)$$

Under the attention approximation, this becomes $\mathbb{P}(Y, s, o) \approx \mathbb{P}(Y, s, o | \bar{\mathbf{a}})$, with

$$\bar{\mathbf{a}} = \mathbb{E}(\mathbf{a}) = \frac{1}{N_T} \sum_{t=1}^{N_T} \mathbf{a}_t.$$

13.2 Social Network

We consider all 4987 persons in the data set and link a person s to persons s', if the score $\mathbf{a}_s^{\top} \mathbf{a}_{s'}$ is in the top 5 of all scores related to s. Thus links exist between persons with similar embeddings, simulating homophily. We then determine the link direction. Considering two entities s and s', $\exp \beta ||\mathbf{a}_s|| / (||\mathbf{a}_s + \mathbf{a}_{s'}||)$ is proportional to the probability that we determine that (s, knows, s'), otherwise, (s', knows, s). At a social network episodic time step t, all links to one person s are added. This defines 4987 episodes for the tKG. The pKG then aggregates the tKG. Overall, we have 24953 knows statements. In summary, our social network dataset has 4987 person entities (along with their attribute labels), 24953 friendship statements, and 4987 episodes of social events.

13.3 Implementation

In this section, we focus on the implementation aspects and provide some details about the network architecture and training hyperparameters. Our program is written in Python and utilizes PyTorch.

13.3.1 Network Architecture

Our model mainly consists of two layers. The representation layer \mathbf{q} has 4096 neurons. The index layer \mathbf{n} has $N_T + N_C + N_P$ neurons. We use VGG-19 backbone as the deep neural network $\mathbf{f}(\cdot)$ which takes as input a scene or a bounding box and outputs a 4096dimensional feature vector. The VGG-19 network consists of a sequence of convolutional blocks followed by two fully connected hidden layers. Each convolutional block is a sequence of 2 convolution layers with 3x3 filters, a max-pooling layer, and another two convolution layers with the same parameters. We use the activations from the last hidden layer and copy them over to \mathbf{q} . The index layer \mathbf{n} is then activated by \mathbf{q} via connection weights \mathbf{A} . At different decoding steps, \mathbf{n} covers different sets of indices, namely \mathbf{n}_T has N_T units for time instances, \mathbf{n}_S , \mathbf{n}_O , \mathbf{n}_O , \mathbf{n}_Q all have N_C concepts units (entities, classes, attributes), and \mathbf{n}_P has N_P units for predicate. The index layer in turn activates the representation layer via the same weights \mathbf{A}^{\top} . To calculate the enhanced representation \mathbf{q}_T , \mathbf{q}_S , and \mathbf{q}_O , we add corresponding activations from \mathbf{n} and $\tilde{\mathbf{q}}$, which at this moment contains raw visual features and information from previous step $\mathbf{g}(\cdot)$, followed by ReLU activation. To obtain \mathbf{n}_S and \mathbf{n}_O we apply softmax on the output with an inverse temperature $\beta = 1$. For \mathbf{n}_O and $\mathbf{n}_{\underline{O}}$, we split the concepts into 8 sets and apply softmax on each set. Alternatively, we could also use the sigmoid function as stated in our algorithm. However, softmax fits here as our labels are mutually exclusive, and in practice, softmax leads to faster convergence and slightly better performance. The working memory layer \mathbf{h} contains 500 neurons with a self-connection via weight matrix \mathbf{B} . There is a direct path for the hidden layer between different decoding steps (the dotted line between \mathbf{h} blocks in figure 3), which stores the state of the working memory and leads to a slight improvement (1%) in relationship prediction. We apply ReLU nonlinearity after each linear projection. For $\bar{\mathbf{a}}$, we use a learnable embedding vector of length 4096.

13.3.2 TRAINING SCHEME

Unless specifically mentioned, we set the batch size to 16, the learning rate to 0.0001, weight decay of all learnable weights to 1e-5, dropout p=0.5 for all the experiments. We optimize the network using an SGD optimizer for 30 epochs. Following the common practice of finetuning, we freeze the transferred weights in the initial training epochs. Except for the VGG backbone, we initialize our network using Kaiming uniform initialization proposed in (He et al., 2015). We optimize the summed cross-entropy loss on \mathbf{n}_T , \mathbf{n}_S , \mathbf{n}_O , \mathbf{n}_O , \mathbf{n}_O , and \mathbf{n}_P for the perception and memory experience. For \mathbf{n}_S and \mathbf{n}_O , we only activate entity instances, with the exception of extending to class/attribute labels for generalized statements (See 4.7). For \mathbf{n}_O and \mathbf{n}_O , we apply cross-entropy loss on each subset. For instance perception, we use a learning rate of 0.001. During the training of memory experience (table 6, table 8), we optimize our model directly on triples without any visual input. The training converges after 20 epochs with an Adam optimizer (Kingma and Ba, 2014). We train two semantic models to predict relationships between classes and relationships between entities, respectively. For RESCAL, we use the implementation of PvKeen (Ali et al., 2021) and set the rank of entity embeddings and predicate embeddings to 1000, which gives a comparable number of learnable parameters as our model. For the social network, we train the model for attribute prediction and relationship prediction on the social network dataset. Concretely, we minimize the cross-entropy loss for \mathbf{n}_S , \mathbf{n}_O , \mathbf{n}_O , \mathbf{n}_O , and \mathbf{n}_P . For SSL, we use a batch size of 128, a learning rate of 1e-5, and total training epochs of 10. Except for the embeddings for time and entities, other weights are frozen. All experiments are conducted on an Nvidia GTX 1089 Ti GPU with a 4 core CPU of 16G memory.