Comparative Study of Coupling and Autoregressive Flows through Robust Statistical Tests

Andrea Coccaro^{1*}, Marco Letizia^{1,2*}, Humberto Reyes-González^{1,3,4*} and Riccardo Torre^{1*}

^{1*}INFN, Sezione di Genova, Via Dodecaneso 33, Genova, 16146, Italy.

^{2*}MaLGa - DIBRIS, University of Genova, Via Dodecaneso 35, Genova, 16146, Italy.

^{3*}Department of Physics, University of Genova, Via Dodecaneso 33, Genova, 16146, Italy.

^{4*}Institut für Theoretische Teilchenphysik und Kosmologie, RWTH Aachen, Aachen,

52074, Germany.

*Corresponding author(s). E-mail(s): andrea.coccaro@ge.infn.it; marco.letizia@edu.unige.it; humberto.reyes@rwth-aachen.de; riccardo.torre@ge.infn.it;

Abstract

Normalizing Flows have emerged as a powerful brand of generative models, as they not only allow for efficient sampling of complicated target distributions, but also deliver density estimation by construction. We propose here an in-depth comparison of coupling and autoregressive flows, both of the affine and rational quadratic spline type, considering four different architectures: Real-valued Non-Volume Preserving (RealNVP), Masked Autoregressive Flow (MAF), Coupling Rational Quadratic Spline (C-RQS), and Autoregressive Rational Quadratic Spline (A-RQS). We focus on a set of multimodal target distributions of increasing dimensionality ranging from 4 to 400. The performances are compared by means of different test-statistics for two-sample tests, built from known distance measures: the sliced Wasserstein distance, the dimension-averaged one-dimensional Kolmogorov-Smirnov test, and the Frobenius norm of the difference between correlation matrices. Furthermore, we include estimations of the variance of both the metrics and the trained models. Our results indicate that the A-RQS algorithm stands out both in terms of accuracy and training speed. Nonetheless, all the algorithms are generally able, without too much fine-tuning, to learn complicated distributions with limited training data and in a reasonable time, of the order of hours on a Tesla A40 GPU. The only exception is the C-RQS, which takes significantly longer to train, does not always provide good accuracy, and becomes unstable for large dimensionalities. All algorithms have been implemented using TENSORFLOW2 and TENSORFLOW PROBABILITY and made available on GITHUB Q.

Keywords: Machine Learning, Generative Models, Density Estimation, Normalizing Flows

Contents

1	Introduction							
2	Normalizing Flows	3						
	2.1 Coupling flows	4						
	2.2 Autoregressive flows	5						
3	Architectures	5						
	3.1 The RealNVP	6						
	3.2 The MAF	6						
	3.3 The RQS bijector	6						
	3.4 The C-RQS	7						
	3.5 The A-RQS \ldots \ldots \ldots \ldots	7						
4	Non-parametric quality metrics	8						
5	Testing the Normalizing Flows							
6	Conclusions and Outlook	12						
A	Implementation of NF architectures							
	A.1 The RealNVP	13						
	A.2 The MAF	14						
	A.3 The C-RQS	15						
	A.4 The A-RQS \ldots	15						
в	Hyperparameters							
С	Results summary tables							
D	Corner plots							

1 Introduction

The modern data science revolution has opened a great window of opportunities for scientific and societal advancement. In particular, Machine Learning (ML) technologies are being applied in a wide variety of fields from finance to astrophysics. It is thus crucial to carefully study the capabilities and limitations of ML methods in order to ensure their systematic usage. This is particularly pressing when applying ML to scientific research, for instance in a field like High Energy Physics (HEP), where one often deals with complex highdimensional data and high levels of precision are needed.

In this paper we focus on Normalizing Flows (NFs) [1–4], a class of neural density estimators that, on one side offers a competitive approach to generative models, such as Generative Adversarial

Networks (GAN) [5] and Variational AutoEncoders (VAE) [6, 7], for the generation of synthetic data, and, on the other side, opens up a wide range of applications due to its ability to directly perform density estimation. Even though we have in mind applications of NFs to HEP, in this paper we remain agnostic with respect to the applications and only perform a general comparative study of the performances of coupling and autoregressive NFs when used to learn high dimensional multi-modal target distributions. Nevertheless, it is worth mentioning some of the applications of NFs to HEP, which could also be extended to several other fields of scientific research.

While applications of the generative direction of NFs is rather obvious in a field like HEP, which poses its foundations on Monte Carlo simulations, it is interesting to mention some of the possible density estimation applications. The ability to directly learn the likelihood, or the posterior in a Bayesian framework, has applications ranging from analysis, inference, reinterpretation, and preservation, to simulation-based likelihood-free inference [8–13], unfolding of HEP analyses [14], generation of effective priors for Bayesian inference [15-20], systematic uncertainty estimation and parametrization, generation of effective proposals for sequential Monte Carlo [21–28], numerical integration based on importance sampling algorithms [29–32], and probabilistic programming applied to fast inference [33, 34].

The basic principle behind NFs is to perform series of invertible bijective transformations on a simple base Probability Densiti Function (PDF) to approximate a complicated PDF of interest. The optimal parameters of the transformations, often called bijectors, are derived from training Neural Networks (NNs) that directly take the negative log-likelihood of the true data computed with the NF distribution as the loss function. As it turns out, PDFs are everywhere in HEP: from the likelihood function of an experimental or phenomenological result, to the distribution that describes a particle-collision process. Furthermore, it has been shown that directly using the likelihood as loss function, leads to a more stable learning process, making NFs very efficient sample generators. Thus, NFs have found numerous applications in HEP: they have been used for numerical integration and event generation [35–42], anomaly detection [43–45], detector unfolding [46, 47], etc. This growing interest in NFs implies the urgency of testing state-of-the-art NF architectures against complicated high-dimensional data to ensure their systematic usability and to assess their expected performances, which is the purpose of the present study. By testing NFs against generic complicated distributions of increasing dimensionality, we aim to make a step forward in the general understanding of the performances and properties of NFs applied to high-dimensional data. This work comprises a substantial upgrade with respect of our early study of Ref. [48], as we now include more NF architectures, extend the dimensionality of the distributions and significantly improved the testing strategy.

Our strategy is the following. We implemented in PYTHON, using TENSORFLOW2 with TENSOR-FLOW PROBABILITY, four of the mostly used NF architectures of the coupling and autoregressive type: Real-valued Non-Volume Preserving (Real-NVP) [49], Masked Autoregressive Flow (MAF) [50], Coupling Rational Quadratic Spline (C-RQS) [51], and Autoregressive Rational Quadratic Spline (A-RQS) [51].

We tested these NF architectures considering Correlated Mixture of Gaussian (CMoG) multimodal distributions with dimensionalities ranging from 4 to 400. We also performed a small-scale hyperparameter scan, explicitly avoiding to finetune the models, and provide the best result for each NF architecture and target distribution.

The performances were measured by means of different test-statistics for two-sample tests built from known distance measures: the sliced Wasserstein distance, the dimension-averaged onedimensional Kolmogorov-Smirnov statistic, and the Frobenius norm of the difference between correlation matrices. These statistics were used in two-sample tests between a test sample, drawn from the original distribution, and an NFgenerated one. Moreover, all test-statistics calculations have been cross-validated and an error has been assigned both to the evaluation procedure, with repeated calculations of the metrics on different instances of the test and NF-generated samples, and to the training procedure, with repeated calculations on models trained with different instances of the training sample.

The paper is organized as follows. In Section 2 we describe the concept of NFs in more detail,

focusing on the coupling and autoregressive types. In Section 3 we introduce the specific NF architectures under investigation. In Section 4 we present the metrics used in our analysis and in Section 5 we discuss our results. Finally, we provide our concluding remarks in Section 6, with emphasis on the several prospective research avenues that we plan to follow.

2 Normalizing Flows

Normalizing Flows are made of series of bijective, continuous, and invertible transformations that map a simple *base* PDF to a more complicated target PDF. The purpose of NFs is to estimate the unknown underlying distribution of some data of interest and to allow the generation of samples approximately following the same distribution. Since the parameters of both the base distribution and the transformations are known, one can *generate* samples from the target distribution by drawing samples from the base distribution and then applying the proper transformation. This is known as the generative direction of the flow. Furthermore, since the NF transformations are invertible, one can also obtain the probability density of the true samples, via inverse transformations from the target to the base PDF. This is known as the *normalizing direction* of the flow. It is called "normalizing" because the base distribution is often Gaussian, even though this is not a requirement, and this is also the origin of the name Normalizing Flows.

The basic idea behind NFs is the change of variable formula for a PDF. Let $X, Y \in \mathbb{R}^D$ be random variables with PDFs $p_X, p_Y : \mathbb{R}^D \to \mathbb{R}$. Let us define a bijective map $\mathbf{g} : X \to Y$, with inverse $\mathbf{f} = \mathbf{g}^{-1}$.¹ The two densities are then related by the well known formula

$$p_Y(y) = p_X(\mathbf{g}^{-1}(y)) | \det \mathbf{J}_g |^{-1} = p_X(\mathbf{f}(y)) | \det \mathbf{J}_f |,$$
(1)

where $J_f = \frac{\partial \mathbf{f}}{\partial y}$ is the Jacobian of $\mathbf{f}(y)$ and $J_g = \frac{\partial \mathbf{g}}{\partial x}$ is the Jacobian of $\mathbf{g}(x)$.

¹Throughout the paper we always interpret X as the base distribution and Y as the target distribution, i.e. the data. We also always model flows in the generative direction, from base to data.

Let us now consider a set of parameters $\{\phi\}$ characterizing the chosen base density p_X (typically the mean vector and covariance matrix of a multivariate Gaussian) and parametrize the map **g** by another set of parameters $\{\theta\}$. One can then perform a maximum likelihood estimation of the parameters $\Phi = \{\phi, \theta\}$ given some measured data $\mathcal{D} = \{y^I\}_{I=1}^N$ distributed according to the unknown PDF p_y . The log-likelihood of the data is given by the following expression

$$\log p(\mathcal{D} \mid \Phi) = \sum_{i=1}^{N} \log p_Y(y^I \mid \Phi)$$

$$= \sum_{I=1}^{N} \log p_X(\mathbf{f}_{\theta}(y^I) \mid \theta, \phi) + \log \mid \det \mathbf{J}_f \mid,$$
(2)

where we made the dependence of \mathbf{f} on θ explicit through the notation \mathbf{f}_{θ} . Then, the best estimate of the parameters Φ is given by

$$\hat{\Phi} = \operatorname*{arg\,max}_{\Phi} \log p(\mathcal{D} \mid \Phi) \,. \tag{3}$$

Once the parameters $\hat{\Phi}$ have been estimated from the data, the approximated target distribution can be sampled by applying the generative map **g** to samples obtained from the base PDF. The normalizing direction **f** can instead be used to perform density evaluation by transforming the new data of interest into sample generated by the base PDF, which is easier to evaluate.

Beside being invertible, the map \mathbf{g} should satisfy the following properties:

- it should be sufficiently expressive to appropriately model the target distribution;
- it should be computationally efficient, that means that both f (for training, that means computing the likelihood) and g (for generating samples), as well as their Jacobian determinants must be easily calculable.

The composition of invertible bijective functions is also an invertible bijective function. Thus, \mathbf{g} can be generalized to a set of N_t transformations as $\mathbf{g} = g_{N_t} \circ g_{N_t-1} \circ \dots g_1$ with inverse $\mathbf{f} = f_1 \circ \dots f_{N_t-1} \circ f_{N_t}$ and det $\mathbf{J}_f = \prod_{n=1}^{N_t} \det \mathbf{J}_{f_n}$, where each \mathbf{f}_n depends on a y_n intermediate random variable. This is a standard strategy to increase the flexibility of the overall transformation.

Typically, but not mandatorily, NF models are implemented using NNs to determine the parameters of the bijectors. The optimal values are obtained by minimizing a loss function corresponding to minus the log-likelihood defined as in Eq. $2.^2$ This makes the models extremely flexible, with a usually stable training, at the cost of a potentially large number of parameters. Nonetheless, the flow transformation must be carefully designed, for instance, even if a given map and its inverse, with their respective Jacobians, are computable, one direction might be more efficient than the other, leading to models that favor sampling over evaluation (and training) or vice-versa. Among the wide and growing variety of NF architectures available, see Ref. [58] for an overview, we focus in this work on *coupling* [4] and *autore*gressive flows [59], arguably the most widely used implementations of NFs, particularly in HEP.

2.1 Coupling flows

Coupling flows, originally introduced in Ref. [4], are made of stacks of so-called coupling layers, in which each sample with dimension D, is partitioned into two samples A and B with dimensions d and D - d, respectively. The parameters of the bjiector transforming the sample A are modeled by a NN that uses B as input, effectively constructing the $p(y_d|x_{d-D})$ conditional probability distributions. At each coupling layer in the stack, different partitionings are applied, usually by shuffling the dimensions before partitioning, so that all dimensions are properly transformed.

In other words, starting from a disjoint partition of a random variable $Y \in \mathbb{R}^D$ such that $(y^A, y^B) \in \mathbb{R}^d \times \mathbb{R}^{D-d}$ and a bijector $\mathbf{h}(\cdot; \theta) :$ $\mathbb{R}^d \to \mathbb{R}^d$, a coupling layer maps $\mathbf{g} : X \to Y$ as follows

$$y^{A} = \mathbf{h}(x^{A}; \Theta(x^{B})),$$

$$y^{B} = x^{B},$$
(4)

where the parameters θ are defined by a generic function $\Theta(x^B)$ only defined on the \mathbb{R}^{D-d} partition, generally modeled by a NN. The function $\Theta(x^B)$ is called a *conditioner*, while the bijectors **h** and **g** are called *coupling function* and *coupling*

 $^{^{2}}$ Approaches beyond maximum likelihood, which use different loss functions, have also been considered in the literature, such as in Ref.s [52–57]. In this paper we always use the maximum likelihood approach and minus the log-likelihood as loss function.

flow, respectively. The necessary and sufficient condition for the coupling flow \mathbf{g} to be invertible is that the coupling function \mathbf{h} is invertible. In this case the inverse transformation is given by

$$x^{A} = \mathbf{h}^{-1}(y^{A}; \Theta(x^{B})),$$

$$x^{B} = y^{B}.$$
(5)

Notice that, despite the presence of a NN, whose inverse is unknown, to parametrize the conditioner, the invertibility of \mathbf{h} is guaranteed by the fact that such conditioner is a function of the unchanged dimensions only. The Jacobian of \mathbf{g} is then a two block triangular matrix. For the dimensions $\{1:d\}$, is given by the Jacobian of \mathbf{h} , and for dimensions $\{d:D\}$ is the identity matrix. Thus, the Jacobian determinant is just

$$\det \mathbf{J}_g = \prod_{i=1}^d \frac{\partial h_i}{\partial x_i^A}.$$
 (6)

Note that the choice of the partition is arbitrary. The most common choice is to split the dimensions in half, but other partitions are possible [58].

2.2 Autoregressive flows

Autoregressive flows, first introduced in Ref. [59], can be viewed as a generalization of coupling flows. Now, the transformations of each dimension i are modeled by an autoregressive DNN according to the previously transformed dimensions of the distribution, resulting in the $p(y_i|y_{1:i-1})$ conditional probability distributions, where $y_{1:i-1}$ is a shorthand notation to indicate the list of variables y_1, \ldots, y_{i-1} . After each autoregressive layer, the dimensions are permuted, to ensure the expressivity of the bijections over the full dimensionality of the target distribution.

Let us consider a bijector $\mathbf{h}(\cdot; \theta) : \mathbb{R} \to \mathbb{R}$, parametrized by θ . We can define an autoregressive flow function \mathbf{g} such that

$$y_1 = x_1, y_i = \mathbf{h}(x_i; \, \Theta_i(y_{1:i-1})), \quad i = 2, \dots, D.$$
(7)

The resulting Jacobian of \mathbf{g} is again a triangular matrix, whose determinant is easily computed as

$$\det \mathbf{J}_g = \prod_{i=1}^D \frac{\partial h_i}{\partial x_i}.$$
 (8)

where $\partial h_i / \partial x_i$ are the diagonal terms of the Jacobian.

Given the structure of the bijector similar to the coupling flow, also in this case the bijector is referred to as a *coupling function*. Note that Θ_j can also be alternatively determined with the precedent untransformed dimensions of X [59], such that

$$y_1 = x_1, y_i = \mathbf{h}(x_i; \,\Theta_i(x_{1:i-1})), \quad i = 2, \dots, D.$$
(9)

The choice of variables used to model the conditioner may depend on whether the NF is intended for sampling or density estimation. In the former case, Θ is usually chosen to be modeled from the base variable X, so that the transformations in the generative direction would only require one forward pass through the flow. The transformations in the normalizing direction would instead require D iterations trough the autoregressive architecture. This case is referred to as inverse autoregressive $flow^3$ [59] and corresponds to the transformations in Eq. (9). Conversely, in the case of density estimation, it is convenient to parametrize the conditioner using the target variable Y, since transformations would be primarily in the normalizing direction. This case is referred to as *direct autoregressive flow* and corresponds to the transformations in Eq. (7). In any case, when training the NFs one always needs to perform the normalizing transformations to estimate the log-likelihood of the data, as in Eq. 2. In our study, we only consider the direct autoregressive flow described by Eq. (7).

3 Architectures

In the previous section we have described NFs, focusing on the two most common choices for

³Notice that Ref. [58], parametrizing the flow in the normalizing direction (the opposite of our choice), apparently uses the inverse of our formulas for direct and inverse flows. Our notation (and nomenclature) is consistent with Ref. [50].

parametrizing the bijector \mathbf{g} in terms of the coupling function \mathbf{h} . The only missing ingredient to make NFs concrete, remains the explicit choice of \mathbf{h} . For this study, we have chosen four of the most popular implementations of coupling and autoregressive flows: the Real-valued Non-Volume Preserving (RealNVP) [49], the Masked Autoregressive Flow (MAF) [50], and the Coupling and Autoregressive Rational-Quadratic Neural Spline Flows (C-RQS and A-RQS) [51].⁴ We discuss them in turn in the following subsections and give additional details about our specific implementation in Appendices A.1-A.4.

3.1 The RealNVP

The RealNVP [49] is a type of coupling flow whose coupling functions \mathbf{h} are affine functions with the following form:

$$y_i = x_i, \qquad i = 1, \dots, d,$$

$$y_i = x_i e^{s_{i-d}(x_{1:d})} + t_{i-d}(x_{1:d}), \quad i = d+1, \dots, D,$$
(10)

where the s and t functions, defined on $\mathbb{R}^{d} \to \mathbb{R}^{D-d}$, respectively correspond to the scale and translation transformations modeled by NNs. The product in Eq. (10) is intended elementwise for each i so that, x_{d+1} is multiplied by s_1 , x_{d+2} by s_2 , and so on, up to x_D , which is multiplied by s_{D-d} . The Jacobian of this transformation is a triangular matrix with diagonal diag(\mathbb{I}_d , diag(exp($s_{i-d}(x_{1:d})$))) with $i = d + 1, \ldots, D$, so that its determinant is independent of t and simply given by

$$\det \mathbf{J} = \prod_{i=1}^{D-d} e^{s_i(x_{1:d})} = \exp\left(\sum_{i=1}^{D-d} s_i(x_{1:d})\right).$$
(11)

The inverse of Eq. 10 is given by

$$x_{i} = y_{i}, \qquad i = 1, \dots, d,$$

$$x_{i} = (y_{i} - t_{i-d}(y_{1:d})) e^{-s_{i-d}(y_{1:d})}, \quad i = d+1, \dots, D.$$
(12)

A crucial property of the affine transformation (10) is that its inverse (12) is again an affine transformation depending only on s and t, and not on their inverse. This implies that the s and t

functions can be arbitrarily complicated (indeed they are parametrized by a DNN), still leaving the RealNVP equally efficient in the forward (generative) and backward (normalizing) directions.

3.2 The MAF

The MAF algorithm was developed starting from the Masked Autoencoder for Distribution Estimation (MADE) [60] approach for implementing an autoregressive Neural Network through layers masking (see Appendix A.2).

In the original MAF implementation [50], the bijectors are again affine functions described as

$$y_1 = x_1,$$

$$y_i = x_i e^{s_{i-1}(y_{1:i-1})} + t_{i-1}(y_{1:i-1}), \quad i = 2, \dots, D.$$
(13)

The functions s and t are now defined on $\mathbb{R}^{D-1} \to \mathbb{R}^{D-1}$. The determinant of the Jacobian is simply

$$\det \mathbf{J} = \prod_{i=1}^{D-1} e^{s_i(y_{1:i})} = \exp\left(\sum_{i=1}^{D-1} s_i(y_{1:i})\right) \quad (14)$$

and the inverse transformation is

$$x_1 = y_1$$
,
 $x_i = (y_i - t_{i-1}(y_{1:i-1})) e^{-s_{i-1}(y_{1:i-1})}$, $i = 2, \dots, D$.
(15)

As in the case of the RealNVP, the affine transformation guarantees that the inverse transformation only depends on s and t and not on their inverse, allowing for the choice of arbitrarily complicated functions without affecting computational efficiency.

3.3 The RQS bijector

The bijectors in a coupling or masked autoregressive flow are not restricted to affine functions. It is possible to implement more expressive transformations as long as they remain invertible and computationally efficient. This is the case of the so-called Rational-Quadratic Neural Spline Flows [51].

The spline bijectors are made of K bins, where in each bin one defines a monotonicallyincreasing rational-quadratic function. The binning is defined on an interval $\mathbb{B} = [-B, B]$, outside of which the function is set to the identity transformation. The bins are defined by a set of K + 1 coordinates $\{(x_i^{(k)}, y_i^{(k)})\}_{k=0}^K$, called *knots*,

⁴Reference [51] refers to coupling and autoregressive RQS flows as RQ-NSF (C) and RQ-NSF (AR), where RQ-NSF stands for Rational-Quadratic Neural Spline Flows, and A and C for autoregressive and coupling, respectively.

monotonically increasing between $\{(x_i^{(0)}, y_i^{(0)}) =$ (-B, -B) to $\{(x_i^{(K)}, y_i^{(K)}) = (B, B)\}$. We use the bracket index notation to denote knots coordinates, which are defined for each dimension of the vectors x_i and y_i . It is possible to construct a rational-quadratic spline bijector with the desired properties with the following procedure [61].

Let us define the quantities

$$\begin{aligned} h_i^{(k)} &= x_i^{(k+1)} - x_i^{(k)} ,\\ \Delta_i^{(k)} &= (y_i^{(k+1)} - y_i^{(k)}) / h_i^{(k)} . \end{aligned} \tag{16}$$

Obviously, $\Delta_i^{(k)}$ represents the variation of y_i with respect to the variation of x_i within the k-th bin. Moreover, since we assumed monotonically increasing coordinates, $\Delta_i^{(k)}$ is always positive or zero. We are interested in defining a bijector $\mathbf{g}(x_i)$, mapping the \mathbb{B} interval to itself, such that $\mathbf{g}(x_i^{(k)}) = y_i^{(k)}$, and with derivatives $d_i^{(k)} = dy_i^{(k)}/dx_i^{(k)}$ satisfying the conditions

$$\begin{aligned} d_i^{(k)} &= d_i^{(k+1)} = 0 \quad \text{for } \Delta_i^{(k)} = 0 , \\ d_i^{(k)}, d_i^{(k+1)} &> 0 \quad \text{for } \Delta_i^{(k)} > 0 , \end{aligned}$$
(17)

necessary, and also sufficient, in the case of a rational quadratic function, to ensure monotonicity [61]. Moreover, for the boundary knots, we set $d_i^{(0)} = d_i^{(K)} = 1$ to match the linear behavior outside the \mathbb{B} interval. For $x_i \in [x_i^{(k)}, x_i^{(k+1)}]$ we define

$$\theta_i = (x_i - x_i^{(k)}) / h_i^{(k)},$$
(18)

such that $\theta_i \in [0, 1]$. Then, for x_i in each of the intervals $[x_i^{(k)}, x_i^{(k+1)}]$ with k = 0, ..., K - 1, we define

$$y_i = P_i^{(k)}(\theta_i) / Q_i^{(k)}(\theta_i),$$
 (19)

with the functions P and Q defined by

$$P_{i}^{(k)}(\theta_{i}) = \Delta_{i}^{(k)} y_{i}^{(k+1)} \theta_{i}^{2} + \Delta_{i}^{(k)} y_{i}^{(k)} (1-\theta_{i})^{2} + (y_{i}^{(k)} d_{i}^{(k+1)} + y_{i}^{(k+1)} d_{i}^{(k)}) \theta_{i} (1-\theta_{i}), Q_{i}^{(k)}(\theta_{i}) = \Delta_{i}^{(k)} + (d_{i}^{(k+1)} + d_{i}^{(k)} - 2\Delta_{i}^{(k)}) \theta_{i} (1-\theta_{i}).$$
(20)

The ratio in Eq. (19) can then be written in the simplified form

$$y_{i} = y_{i}^{(k)} + \frac{(y_{i}^{(k+1)} - y_{i}^{(k)})(\Delta_{i}^{(k)}\theta_{i}^{2} + d_{i}^{(k)}\theta_{i}(1 - \theta_{i}))}{\Delta_{i}^{(k)} + (d_{i}^{(k+1)} + d_{i}^{(k)} - 2\Delta_{i}^{(k)})\theta_{i}(1 - \theta_{i})}$$
(21)

The Jacobian $J_{\mathbf{g}} = \partial y_i / \partial x_j$ is then diagonal, with entries given by

$$\frac{(\Delta_i^{(k)})^2 (d_i^{(k+1)} \theta_i^2 + 2\Delta_i^{(k)} \theta_i (1-\theta_i) + d_i^{(k)} (1-\theta_i)^2)}{(\Delta_i^{(k)} + (d_i^{(k+1)} + d_i^{(k)} - 2\Delta_i^{(k)}) \theta_i (1-\theta_i))^2},$$
(22)

for $i = 1, \ldots, D$. The inverse of the transformation (19) can also be easily computed by solving the quadratic Eq. (19) with respect to x_i .

In practice, B and K are fixed variables (hyperparameters), while $\{(x_i^{(k)}, y_i^{(k)})\}_{k=0}^K$ and ${d_i^{(k)}}_{k=1}^{K-1}$ are 2(K+1) plus K-1 parameters, modeled by a NN, which determine the shape of the spline function. The different implementations of the RQS bijector, in the context of coupling and autoregressive flows, are determined by the way in which such parameters are computed. We briefly describe them in turn in the following two subsections.

3.4 The C-RQS

In the coupling flow case (C-RQS), one performs the usual partitioning of the D dimensions in the two sets composed of the first d and last D-ddimensions. The first d dimensions are then kept unchanged $y_i = x_i$ for $i = 1, \ldots, d$, while the parameters describing the RQS transformations of the other D-d dimensions are determined from the inputs of the first d dimensions, denoted by $x_{1:d}$. Schematically, we could write

$$\begin{aligned} x_i^{(k)} &= x_i^{(k)}(x_{1:d}), \\ y_i^{(k)} &= y_i^{(k)}(x_{1:d}), \\ d_i^{(k)} &= d_i^{(k)}(x_{1:d}), \end{aligned}$$
(23)

for i = d + 1, ..., D.

A schematic description of our implementation of the C-RQS is given in Appendix A.3.

3.5 The A-RQS

The RQS version of the MAF, that we call A-RQS, is instead obtained leaving unchanged the first dimension $y_1 = x_1$ and determining the parameters of the transformation of the *i*-th dimension from the output of all preceding dimensions, denoted by $y_{1:i-1}$. Schematically, this is given by

$$\begin{aligned} x_i^{(k)} &= x_i^{(k)}(y_{1:i-1}), \\ y_i^{(k)} &= y_i^{(k)}(y_{1:i-1}), \\ d_i^{(k)} &= d_i^{(k)}(y_{1:i-1}), \end{aligned}$$
(24)

for i = 2, ..., D.

4 Non-parametric quality metrics

We assess the performance of our trained models using three distinct metrics: the dimensionaveraged 1D Kolmogorov-Smirnov (KS) twosample test-statistic $\overline{D}_{u,z}$, the sliced Wasserstein distance (SWD) $\overline{W}_{y,z}$, and the Frobenius norm (FN) of the difference between the correlation matrices of two samples $||C||_F$. With a slight abuse of nomenclature, we refer to these three different distance measures, with vanishing optimal value, simply as KS, SWD, and FN. Each of these metrics serves as a separate test-statistic in a two-sample test, where the null hypothesis assumes that both samples originate from the same target distribution. For each metric, we establish its distribution under the null hypothesis by drawing both samples from the target distribution. We then compare this distribution with the test-statistic calculated from a two-sample test between samples drawn from the target and NF distributions to assign each model a *p*-value for rejecting the null hypothesis.

To quantify the uncertainty on the teststatistics computed for the test vs NF-generated samples, we perform the tests 10 times using differently seeded target- and NF-generated samples. We calculate p-values based on the mean test-statistic and its ± 1 -standard deviation.

For model comparison, and to assess the uncertainty on the training procedure, we train 10 instances of each model configuration, defined by a set of hyperparameter values. Rather than selecting the single best-performing instance to represent the best architecture, we average the performances across these instances and identify the architecture with the best average performance. After selecting this top-performing model, that we call "best" model, we report both its average and peak performances.

When computing the test-statistics distributions under the null hypothesis, and evaluating each model *p*-values, we see that the discriminative power of the KS metric is larger than that of the SWD and FN ones. For this reason, we use the result of the KS-statistic to determine the best model and then show results also for the other two statistics. Nevertheless, even though the best model may vary depending on the metric used, no qualitative difference in the conclusions would arise choosing FN or SWD as the ranking metric, i.e. results are not identical, but consistent among the three metrics.

It is important to stress that, despite we insist in using non-parametric quality metrics, we actually know the target density, and we use this information for bootstrapping uncertainties and computing p-values. In real-world examples the target density is generally not known and depending on the number of available samples, our procedure for evaluation needs to be adapted or may even end up being unusable. Nevertheless, this well-defined statistical approach is crucial for us, since we aim at drawing rather general conclusions, which strongly depend on the ability to estimate the uncertainties and should rely on robust statistical inference.

In the following we briefly introduce the three aforementioned metrics. To do so we employ the following notation: we indicate with N the number of D-dimensional points in each sample and use capital indices I, J to run over N and lower-case indices i, j to run over D.⁵ We also use greek letters indices α, β to run over slices (random directions).

• Kolmogorov-Smirnov test

The KS test is a statistical test used to determine whether or not two 1D samples are drawn from the same *unknown* PDF. The null hypothesis is that both samples come from the same PDF. The KS test-statistic is given by

$$D_{y,z} = \sup_{x} |F_{y}(x) - F_{z}(x)|,$$
 (25)

⁵We warn the reader not to confuse the dimensionality D with the KS test-statistic $D_{x,y}$.

where $F_{y,z}(x)$ are the empirical distributions of each of the samples $\{y_I\}$ and $\{z_I\}$, and **sup** is the supremum function. For characterizing the performances of our results, we compute the KS test-statistic for each of the 1D marginal distributions along the *D* dimensions and take the average

$$\overline{D}_{y,z} = \frac{1}{D} \sum_{i=1}^{D} D^{i}_{y,z} \,. \tag{26}$$

The actual test-statistic that we consider in this paper is the scaled version of $\overline{D}_{y,z}$, given by

$$t_{\rm KS} = \sqrt{\frac{N}{2}} \overline{D}_{y,z} \tag{27}$$

The $\sqrt{N/2}$ factor comes from the known $\sqrt{m \cdot n/(m+n)}$ factor in the scaled KS statistic with different-size samples, of sizes m and n, respectively.

Notice that, even though the test-statistic

$$\sqrt{\frac{m \cdot n}{m+n}} D_{y,z} \tag{28}$$

is asymptotically distributed according to the Kolmogorov distribution [62–66], the same is not true for our $t_{\rm KS}$ statistic, due to correlations among dimensions. Nevertheless, our results seem to suggest that the asymptotic distribution of $t_{\rm KS}$ for large D (that means when the average is taken over many dimensions), has a reasonably universal behavior, translating into almost constant rejection lines (solid gray lines with different thickness) in the upper panels of Figure 1.

• Sliced Wasserstein Distance

The SWD [67, 68] is a distance measure to compare two multidimensional distributions based on the 1D Wasserstein distance [69, 70]. The latter distance between two univariate distributions is given as a function of their respective empirical distributions as

$$W_{y,z} = \int_{\mathbb{R}} dx \mid F_y(x) - F_z(x) \mid .$$
 (29)

Intuitively, the difference between the WD and the KS test-statistic is that the latter considers the maximum distance, while the former is based on the integrated distance. Our implementation of the SWD is defined as follows. For each model and each dimensionality D, we draw 2D random directions \hat{v}^i_{α} , with $i = 1, \ldots D$ and $\alpha = 1, \ldots, 2D$, uniformly distributed on the surface of the unit N-sphere.⁶ Given two D-dimensional samples $\{\mathbf{y}_I\} = \{y^i_I\}$ and $\{\mathbf{z}_I\} = \{z^i_I\}$, we consider the 2D projections

$$\{y_I^{\alpha}\} = \left\{\sum_{i=1}^D y_I^i \hat{v}_i^{\alpha}\right\}, \qquad \{z_I^{\alpha}\} = \left\{\sum_{i=1}^D z_I^i \hat{v}_i^{\alpha}\right\},\tag{30}$$

and compute the corresponding 2D Wasserstein distances

$$W_{y,z}^{\alpha} = \int_{\mathbb{R}} dx \mid F_{y^{\alpha}}(x) - F_{z^{\alpha}}(x) \mid .$$
 (31)

The SWD is then defined as the average of the latter over the random projections

$$\overline{W}_{y,z} = \frac{1}{2D} \sum_{\alpha=1}^{2D} W_{y,z}^{\alpha} \,. \tag{32}$$

In analogy with the scaled KS test-statistic, we defined the scaled SWD test-statistic

$$t_{\rm SWD} = \sqrt{\frac{N}{2}} \overline{W}_{y,z} \,. \tag{33}$$

• Frobenius norm

The FN of a matrix M is given by

$$||M||_F = \sqrt{\sum_{i,j} |m_{ij}|^2}, \qquad (34)$$

where m_{ij} are the elements of M. By defining $C = C_y - C_z$, where C_y, C_z are the two $N \times N$ correlation matrices of the samples $\{\mathbf{y}_I\} = \{y_I^i\}$ and $\{\mathbf{z}_I\} = \{z_I^i\}$, its FN, given by

$$|C||_F = \sqrt{\sum_{i,j} |c_{y,ij} - c_{z,ij}|^2}, \qquad (35)$$

is a distance measure between the two correlation matrices. In analogy with the previously

⁶This can be done by normalizing the *D*-dimensional vector obtained by sampling each components from an independent standard normal distributions [71].

defined test-statistics, we defined the scaled FN test-statistic

$$t_{\rm FN} = \sqrt{\frac{N}{2}} \frac{\|C\|_F}{D},$$
 (36)

where we also divided by the number of dimensions D to remove the approximately linear dependence of the FN distance on the dimensionality of the samples.

5 Testing the Normalizing Flows

We tested the four architectures discussed above on CMoG distributions defined as a mixture of n = 3 components and D= 4, 8, 16, 32, 64, 100, 200, 400 dimensional multivariate Gaussian distributions with diagonal covariance matrices, parametrised by means randomly generated in the [0, 10] interval and standard deviations randomly generated in the [0,1] interval⁷. The components are mixed according to an ndimensional categorical distribution (with random probabilities). This means that a different probability is assigned to each component, while different dimensions of the same component multivariate Gaussian are assigned the same probability. The resulting multivariate distributions have random (order one) off-diagonal elements in the covariance matrix and multi-modal 1D marginal distributions (see, for illustration, Fig. 2).

In our analysis, we consider a training set of 10^5 points, a validation set of 3×10^4 points, and a test set equal in size to the training set, with 10^5 points. It is important to note that the chosen size of the test set corresponds to the most stringent condition for evaluating the NF models. This is because the NF can not be expected to approximate the real target distribution more accurately than the uncertainty determined by the size of the training sample.

In practical terms, the most effective NF would be indistinguishable from the target distribution when tested on a sample size equivalent to the training set. In our analysis, we find that models tested with 10^5 samples often lead to rejection at the $2\sigma/3\sigma$ level, at least with the most powerful KS test. However, this should not be viewed as a poor outcome. Rather, it suggests that one needs to utilize a test set as large as the training set to efficiently discern the NF from the true model, while smaller samples are effectively indistinguishable from those generated with the target distribution.

An alternative approach, which we do not adopt here due to computational constraints, involves calculating the sample size required to reject the null hypothesis at a given confidence level. This approach offers a different but equally valid perspective, potentially useful for various applications. Nevertheless, our approach is efficient for demonstrating that NFs can perform exceptionally well on high-dimensional datasets and for comparing, among each others, the performances of different NF architectures.

For each of the four different algorithms described above and for each value of N we perform a small scan over some of the free hyperparameters. Details on the choice of the hyperparameters are reported in Appendix B. All models have been trained on Nvidia A40 GPUs.

The performances of the best NF architectures are reported in Fig. 1 and Tables 2 and 3.

The Figure shows the values of the three teststatistics (vertical panels) for the average (left panels) and absolute (right panels) best models obtained with the four different architectures. The three gray lines with different thickness represent the values of the test-statistics corresponding to 1σ , 2σ , and 3σ rejection (*p*-values of 0.68, 0.95, and 0.99) of the null hypothesis that the two samples (test and NF-generated) are drawn from the same PDF. These rejection lines have been obtained through 10^4 pseudo-experiments. The curve for the best C-RQS models stops at 64D, since the training becomes unstable and the model does not converge. The situation could likely be improved by adding reguralization and fine-tuning the hyperparameters. However, to allow for a fair comparison with the other architectures, where regularization and fine-tuning are not necessary for a reasonable convergence, we avoid pushing C-RQS beyond 64D. Also notice that the uncertainty shown in the point at 64D for the C-RQS is artificially very small, since only a small fraction of the differently seeded runs converged.

 $^{^7\}mathrm{The}$ values for the means and standard deviations are chosen so that the different components can generally be resolved.



64 100

Reject at 1σ

Reject at 2σ

Reject at 3σ

64 100



Fig. 1 Performance comparison between the average (left panel) and abslute (right panel) best models obtained with RealNVP, MAF, C-RQS, and A-RQS architectures when learning the CMoG distributions. The figures show the value of the test-statistic with its uncertainty, computed as explained in the text. The KS, SWD, and FN test statistics, as defined in Section 4, are shown in the upper, middle, and lower panel, respectively. The gray lines with different widths represent, from thinner to ticker, the $1, 2, 3\sigma$ thresholds for the test-statistics, as obtained from the test-statistics distributions under the null hypothesis, evaluated with 10^4 pseudo-experiments.

This uncertainty should therefore be considered unreliable.

32

Number of dimensions

All plots in Fig. 1 include uncertainties. As already mentioned, the best model is chosen as the one with best architecture in average, and therefore, over 10 different trainings performed with differently seeded training samples. Once the best model has been selected, the left plots

Number of dimensions

10¹

4

---MAF

4

FN test-statistic *t*_{FN} 00

8

RealNVP

C-RQS

A-RQS

8

16

16

32

Number of dimensions

show their performances averaged over the 10 trainings, with error bands representing the corresponding standard deviations, while the right plots show the performances of the absolute best instance among the 10 trained replicas, with error band representing the standard deviation over the 10 replicas generated for testing (test and NFgenerated samples). In other words, we can say that the uncertainties shown in the left plots are the standard deviations due to repeated training, while the uncertainties shown in the right plots are the standard deviations due to repeated generation/evaluation (testing).

Figure 1 clearly highlights the distinct characteristics that establish the A-RQS as the topperforming algorithm:

- its performances are almost independent of the data dimensionality;
- the average best model is generally not rejected at 3σ level when evaluated with a number of points equal to the number of training points;
- the absolute best model is generally not reject at 2σ level when evaluated with a number of points equal to the number of training points;
- the uncertainties due to differently seeded training and testing are generally comparable, while for all other models, the uncertainty from training is generally much larger than the one from evaluation.

All values shown in Fig. 1 are reported in Tables 2 and 3, for the average and absolute best models, respectively. In the Tables we also show the average number of epochs, training time, and prediction time. It is interesting to look at the training and prediction times. Indeed, while for the coupling flows, even though training time is much larger than prediction time, both times grow with a similar rate, for the autoregressive flows, the prediction time grows faster than the training time, which is almost constant. This is because, as we already mentioned, the MAF is a "direct flow", very fast for density estimation, and therefore for training (single pass through the flow), and slower for generation, and therefor for testing (Npasses through the flow, with N the dimensionality of the target distribution). Still, testing was reasonably fast, considering that each test actually consisted of 10 tests with three metrics and 10^5 points per sample. All trainings/tests took less than a few hours (sometimes, especially in small dimensionality, a few minutes), which means that all models, but the C-RQS in large dimensionalities, are pretty fast both in training and inference.⁸

6 Conclusions and Outlook

Normalizing Flows have shown many potential applications in a wide variety of research fields including HEP, both in their normalizing and generative directions. However, to ensure a standardized usage and to match the required precision, their application to high-dimensional datasets need to be properly evaluated. This paper makes a step forward in this direction by quantifying the ability of coupling and autoregressive flow architectures to model distributions of increasing complexity and dimensionality.

Our strategy consisted in performing statistically robust tests utilizing different figures of merits, and including estimates of the variances induced both by the training and the evaluation procedures.

We focused on the most widely used NF architectures in HEP, the coupling (RealNVP and C-RQS) and the autoregressive flows (MAF and A-RQS), and compared them against generic multimodal distributions of increasing dimensionality.

As the main highlight, we found that the A-RQS is greatly capable of precisely learning all the high-dimensional complicated distributions it was tested against, always within a few hours of training on a Tesla A40 GPU and with limited training data. Moreover, the A-RQS architecture, shows great generalization capabilities allowing to obtain almost constant results over a very wide range of dimensionalities, ranging from 4 to 400.

As of the other tested architectures, our results show that reasonably good results can be obtained with all of them but the C-RQS, which ended up being the least capable to generalize to large dimensionality, with unstable and longer trainings, especially in high dimensionality.

⁸Notice that, even though, the training/testing times do not go beyond a few hours, we have trained and tested 10 replicas of 4 architectures in 8 different dimensionalities (apart from C-RQS) and with a few different values of the hyperparameters, for a total of about 1360 runs (see Table 1). This took several months of GPU time, showing how resource demanding is to reliably estimate uncertainties of ML models, even in relatively simple cases.

Our analysis was performed implementing all architectures in TENSORFLOW2 with TENSOR-FLOW PROBABILITY using PYTHON. The code is available in Ref. [72], while a general-purpose user-friendly framework for NFs in TensorFlow2 named NF4HEP is under development and can be found in Ref. [73]. Finally, a code for statistical inference and two-sample tests, implementing the metrics considered in this paper (and others) in TENSORFLOW2 is available in Ref. [74].

We stress that the intention of this study is to secure generic assessments of how NFs perform in high dimensions. For this reason the target distributions were chosen independently of any particular experimentally-driven physics dataset. An example of application to a physics dataset, in the direction of building an un-supervised DNN-Likelihood [75], has been presented in Ref. [76]. Nonetheless, these studies represent the firsts of a series to come. Let us briefly mention, in turn, the research directions we aim to follow starting from the present paper.

- Development of reliable multivariate quality metrics, including approaches based on machine learning [77, 78]. We note the importance of performing statistically meaningful tests on generative models, ideally including uncertainty estimation. A thorough study of different quality metrics against high dimensional data is on its way. Moreover, new results [79–81] suggests that classifier-based two-sample tests have the potential to match the needs of the HEP community when paired with a careful statistical analysis. These tests can leverage different ML models to provide high flexibility and sensitivity together with short training times, especially when based on kernel methods [81]. On the other hand, further studies are needed to investigate their efficiency and scalability to high dimensions.
- Study of the dependence of the NF performances on the size of the training sample [82]. In the present paper we always kept the number of training points to 10^5 . It is clear that such number is pretty large in small dimensionality, like N = 4 dimensions, and undersized for large dimensionality, like $N \ge 100$. It is important to study the performances of the considered NF architectures in the case of scarce or very abundant data, assessing the dependence

of the final precision on the number of training samples. This can also be related to developing techniques to infer the uncertainty of the NF models.

- Study how NF can be used for statistical augmentation, for instance using them in the normalizing direction to build effective priors and proposals to enhance (in terms of speed and convergence time) known sampling techniques, such as Markov Chain Monte Carlo, whose statistical properties are well established.
- A final issue that needs to be addressed to ensure a widespread use of NFs in HEP is the ability to preserve and distribute pre-trained NF-based models. This is, for the time being, not an easy and standard task and support from the relevant software developers community is crucial to achieve this goal.

Acknowledgments

We thank Luca Silvestrini for pushing us towards the study of NFs and for fruitful discussions. We are thankful to the developers of TENSOR-FLOW2, which made possible to perform this analysis. We thank the IT team of INFN Genova, and in particular Mirko Corosu, for useful support. We are thankful to OpenAI for the development of ChatGPT and to ChatGPT itself for useful discussions. H.R.G. acknowledges the hospitality of Sabine Kraml at LPSC Grenoble and the discussions on Normalizing Flows held there with the rest of the SModelS Collaboration. This work was partially supported by the Italian PRIN grant 20172LNEEZ. M.L. acknowledges the financial support of the European Research Council (grant SLING 819789). H.R.G. is supported by the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) under grant 396021762 - TRR 257: Particle Physics Phenomenology after the Higgs Discovery

A Implementation of NF architectures

A.1 The RealNVP

We are given a collection of vectors $\{y_i^I\}$ with i = 1, ..., D representing the dimensionality and I = 1, ..., N the number of samples representing

the unknown PDF p_Y . For all samples \mathbf{y}^I we consider the half partitioning given by the two sets $\hat{\mathbf{y}}^{I} = \{y_{1}^{I}, \dots, y_{D/2}^{I}\}$ and $\tilde{\mathbf{y}}_{I} = \{y_{D/2+1}^{I}, \dots, y_{D}^{I}\}.^{9}$ We then use the $\hat{\mathbf{y}}^I$ samples as inputs to train a fully connected MLP (a dense DNN) giving as output the vectors of t_i and s_i , with $i = 1, \ldots, D/2$ in Eq. (10). These output vectors are provided by the DNN through two output layers, which are dense layers with linear and tanh activation functions for t_i and s_i , respectively, and are used to implement the transformation in Eq. (12), which outputs the (inversely) transformed samples. Moreover, in order to transform all dimensions and to increase the expressivity of the model, we use a series of such RealNVP bijectors, feeding the output of each bijector as input for the next one, and inverting the role of the two partitions at each step. After the full transformation is performed, one obtains the final $\{x_i^I\}$ with $i = 1, \ldots, D$ vectors and the transformation Jacobian (the product of the inverse of Eq. (11) for each bijector). With these ingredients, and assuming a normal base distribution p_X , one can compute the negative of the log-likelihood in Eq. (2), which is used as loss function for the DNN optimization.

As it is clear from the implementation, the RealNVP NF, i.e. the series of RealNVP bijectors, is trained in the normalizing direction, taking data samples as inputs. Nevertheless, since the s_i and t_i vectors only depend, at each step, on untransformed dimensions, once the DNN is trained, they can be used both to compute the density, by using Eq. (12) and to generate new samples, with equal efficiency, by using Eq. (10). This shows that the RealNVP is equally efficient in both the normalizing and generative directions.

A.2 The MAF

As in the case of the RealNVP, also for the MAF, the forward direction represents the normalizing direction. In this case the vectors s_i and t_i , of dimension D - 1 describing the affine bijector in Eq. (13) are parametrized by an autoregressive DNN with D inputs and 2(D - 1) outputs, implemented through the MADE [60] masking procedure, according to the TENSORFLOW PROB-ABILITY implementation (see Ref. [83]). The procedure is based on binary mask matrices defining which connections (weights) are kept and which are dropped to ensure the autoregressive property.¹⁰ Mask matrices are determined from numbers (degrees) assigned to all nodes in the DNN: each node in the input layer is numbered sequentially from 1 to D; each node in each hidden layer is assigned a number between 1 and D, possibly with repetition; the first half output nodes (representing s_i) are numbered sequentially from 1 to D-1 and the same for the second half (representing t_i). Once all degrees are assigned, the matrix elements of the mask matrices are 1 if two nodes are connected and 0 if they are "masked", i.e. not connected. The mask matrices are determined connecting the nodes of each layer with index k with all nodes in the preceding layer having an index smaller or equal than k. As for the RealNVP, a series of MAF bijectors is used, by feeding each with the $\{x_i^I\}$, with $i = 1, \ldots, D$, according to Eq. (15) computed from the previous one. The last bijector computes the final $\{x_i^I\}$, with $i = 1, \ldots, D$, according to Eq. (15) and the transformation Jacobian (the product of the inverse of Eq. (14) for each bijector), used to compute and optimize the log-likelihood as defined in Eq. (2).

The efficiency of the MAF in the normalizing and generative directions is not the same, as in the case of the RealNVP. Indeed, computing the log-likelihood for density estimation, requires a single forward pass of $\{y_i\}$ through the NF. However, generating samples requires to start from $\{x_i\}$, randomly generated from the base distribution. Then one needs the following procedure to compute the corresponding $\{y_i\}$:

- define the first component of the required y_i^{input} as $y_1^{\text{output}} = y_1^{\text{input}} = x_1$ where y_i^{input} is the NF input;
- start with a $y_i^{\text{input}} = x_i$ and pass it through the NF to determine y_2^{output} as function of y_1^{output} ;

⁹For simplicity, we assume D is even and therefore D/2 integer. In case D = 2d + 1 is odd the "half-partitioning" could be equally done by taking the first d+1 and the last d dimensions, or vice-versa. This does not affect our implementation.

¹⁰The binary mask matrices are simple transition matrices between pairs of layers of dimension (K', K) with K' the number of nodes in the forward layer (closer to the output) and K the number of nodes in the backward layer (closer to the input). Obviously K = D for the input layer and K' = 2(D-1)for the output layer.

Hyperparameters values							
Hyperpar.	MAF	RealNVP	A-RQS	C-RQS			
number of bijectors	5, 10	5, 10	2	5, 10			
number of hidden layers	$\begin{array}{c} 3\times128\\ 3\times256 \end{array}$						
number of spline knots	_	_	8,12	8,12			
total number of runs	320	320	320	400			

Table 1Hyperparameter values used in our analysis.The last row shows the total number of runs for eacharchitecture, taking into account the 10 replicas and thedifferent dimensionalities.

- update y_i^{input} with $y_2^{\text{input}} = y_2^{\text{output}}$ and pass through the NF to determine y_3^{output} as function of y_1^{output} and y_2^{output} ;
- iterate until all the y_i^{output} components are computed.

It is clear to see that the procedure requires D passes through the NF to generate a sample, so that generation in the MAF is D times less efficient than density estimation. The Inverse Autoregressive Flow (IAF) [59] is an implementation similar to the MAF that implements generation in the forward direction (obtained by exchanging x and y in Eq.s (13) and (15). In the case of IAF, computing the log-likelihood (which is needed for training) requires D steps, while generation only requires a single pass through the flow. The IAF is therefore much slower to train and much faster to generate new samples.

A.3 The C-RQS

The C-RQS parameters are determined by the following procedure [51].

- 1. A dense DNN takes x_1, \ldots, x_d as inputs, and outputs an unconstrained parameter vector θ_i of length 3K - 1 for each $i = d + 1, \ldots, D$ dimension.
- 2. The vector θ_i is partitioned as $\theta_i = [\theta_i^w, \theta_i^h, \theta_i^d]$, where θ_i^w and θ_i^h have length K, while θ_i^d has length K - 1;
- 3. The vectors θ_i^w and θ_i^h are each passed through a softmax and multiplied by 2B; the outputs are interpreted as the widths and heights of

the K bins, which must be positive and span the B interval. Then, the cumulative sums of the K bin widths and heights, each starting at -B, yield the K + 1 knots parameters $\{(x_i^{(k)}, y_i^{(k)})\}_{k=0}^K$; 4. The vector θ_i^d is passed through a softplus func-

4. The vector θ_i^d is passed through a softplus function and is interpreted as the values of the derivatives $\{d_i^{(k)}\}_{k=1}^{K-1}$ at the internal knots.

As for the RealNVP, in order to transform all dimensions, a series of RQS bijectors is applied, inverting the role of the two partitions at each step.

A.4 The A-RQS

In the autoregressive implementation, we follow the same procedure used in the MAF implementation and described in Section A.2, but instead of obtaining the 2(D-1) outputs determining the affine parameters, we obtain the 3K - 1 parameters needed to compute the values of the knots parameters and derivatives. Once these are determined the procedure follows the steps 2 to 4 of the C-RQS implementation described in the previous subsection.

B Hyperparameters

For all models we used a total of 10^5 training, $3 \cdot 10^4$ validation, and 10^5 test points. We employed ReLu activation function with no regularization. All models were trained for up to 1000 epochs with initial learning rate set to 10^{-3} .¹¹ The learning rate was then reduced by a factor of 0.5 after 50 epochs without improvement better than 10^{-4} on the validation loss. Early stopping was used to terminate the learning after 100 epochs without the same amount of improvement. The batch size was set to 256 for RealNVP and to 512 for the other algorithms. For the two neural spline algorithms we also set the range of the spline equal to [-16, 16]. The values of all hyperparameters on which we performed a scan are reported in Table 1.

¹¹For unstable trainings in large dimensionality, when the training with this initual learning rate failed with a "nan" loss, we have reduced the learning rate by a factor 1/3 and re-tried, until either the training succeded, or the learning rate was smaller than 10^{-6} .

C Results summary tables

Results for Average Best models									
hidden layers	# of bijec.	algorithm	spline knots	$\begin{array}{l} \text{KS-test} \\ p\text{-value} \end{array}$	Sliced WD	Frobenius Norm	# of epochs	training time (s)	prediction time (s)
4D									
$3 \times 128 3 \times 256 3 \times 128 3 \times 128 3 \times 128$	$ \begin{array}{c} 10 \\ 5 \\ 2 \\ 5 \end{array} $	MAF RealNVP A-RQS C-RQS	- - 8 8	$\begin{array}{c} 1.5 \pm 0.4 \\ 1.6 \pm 0.5 \\ 1.2 \pm 0.1 \\ 1.4 \pm 0.2 \end{array}$	$\begin{array}{c} 3.1 \pm 0.7 \\ 3.7 \pm 0.9 \\ 2.6 \pm 0.4 \\ 3.3 \pm 0.3 \end{array}$	$\begin{array}{c} 0.9 \pm 0.3 \\ 1.0 \pm 0.4 \\ 0.7 \pm 0.2 \\ 1.0 \pm 0.5 \end{array}$	$\begin{array}{c} 442 \\ 616 \\ 670 \\ 483 \end{array}$	$5301 \\ 8777 \\ 7606 \\ 12346$	17 8 54 26
8D									
$\begin{array}{c} 3\times128\\ 3\times128\\ 3\times128\\ 3\times128\\ 3\times128\end{array}$	$5 \\ 10 \\ 2 \\ 5$	MAF RealNVP A-RQS C-RQS	$\begin{array}{c} -\\ -\\ 12\\ 8\end{array}$	$\begin{array}{c} 1.3 \pm 0.2 \\ 2.2 \pm 0.5 \\ 1.6 \pm 0.5 \\ 2.4 \pm 0.6 \end{array}$	$\begin{array}{c} 3.3 \pm 0.7 \\ 5.2 \pm 1.1 \\ 4.7 \pm 2.1 \\ 6.1 \pm 1.9 \end{array}$	$\begin{array}{c} 0.8 \pm 0.3 \\ 1.4 \pm 0.4 \\ 1.0 \pm 0.4 \\ 1.6 \pm 0.5 \end{array}$	713 340 477 294	$5757 \\ 8242 \\ 5516 \\ 11500$	$11 \\ 12 \\ 315 \\ 27$
16D									
$3 \times 128 \\ 3 \times 128 \\ 3 \times 128 \\ 3 \times 128 \\ 3 \times 128$	$5 \\ 5 \\ 2 \\ 10$	MAF RealNVP A-RQS C-RQS	$\begin{array}{c} -\\ -\\ 12\\ 8\end{array}$	$\begin{array}{c} 1.6 \pm 0.2 \\ 2.6 \pm 0.3 \\ 1.8 \pm 0.3 \\ 2.0 \pm 0.6 \end{array}$	$\begin{array}{c} 3.7 \pm 0.6 \\ 6.4 \pm 1.3 \\ 3.1 \pm 0.5 \\ 3.9 \pm 1.3 \end{array}$	$\begin{array}{c} 7.1 \pm 1.9 \\ 12 \pm 3 \\ 2.2 \pm 1.0 \\ 4.6 \pm 2.0 \end{array}$	479 366 327 558	$3410 \\ 4263 \\ 3705 \\ 64056$	$ \begin{array}{r} 16 \\ 8 \\ 65 \\ 53 \\ \end{array} $
32D									
$\begin{array}{c} 3\times128\\ 3\times128\\ 3\times128\\ 3\times256\end{array}$	$5 \\ 10 \\ 2 \\ 10$	MAF RealNVP A-RQS C-RQS	- 8 12	$\begin{array}{c} 1.7 \pm 0.3 \\ 2.6 \pm 0.5 \\ 1.9 \pm 0.3 \\ 2.0 \pm 0.5 \end{array}$	$\begin{array}{c} 4.5 \pm 0.9 \\ 6.8 \pm 1.6 \\ 4.4 \pm 1.0 \\ 5.2 \pm 1.7 \end{array}$	$\begin{array}{c} 2.1 \pm 0.6 \\ 3.0 \pm 0.8 \\ 1.7 \pm 0.4 \\ 2.3 \pm 0.8 \end{array}$	595 676 375 750	$\begin{array}{r} 4193 \\ 16946 \\ 4705 \\ 75606 \end{array}$	24 12 97 83
64D									
$3 \times 128 3 \times 256 3 \times 128 3 \times 256$	$ \begin{array}{c} 10 \\ 10 \\ 2 \\ 5 \end{array} $	MAF RealNVP A-RQS C-RQS	- 8 12	$\begin{array}{c} 2.1 \pm 0.6 \\ 2.3 \pm 0.4 \\ 1.5 \pm 0.2 \\ 2.4 \pm 0.9 \end{array}$	7 ± 3 6.5 ± 1.7 4.0 ± 0.7 6.4 ± 2.7	$\begin{array}{c} 1.3 \pm 0.5 \\ 1.5 \pm 0.3 \\ 0.9 \pm 0.1 \\ 2.6 \pm 0.8 \end{array}$	$537 \\ 711 \\ 523 \\ 813$	$5289 \\ 13871 \\ 6197 \\ 36608$	$89 \\ 16 \\ 332 \\ 53$
100D									
$\begin{array}{c} 3\times128\\ 3\times256\\ 3\times128 \end{array}$	$\begin{array}{c}10\\10\\2\end{array}$	MAF RealNVP A-RQS	 12	$\begin{array}{c} 2.2 \pm 0.8 \\ 3.2 \pm 1.3 \\ 1.4 \pm 0.2 \end{array}$	7 ± 4 10 ± 6 4.0 ± 0.9	$\begin{array}{c} 2.1 \pm 1.2 \\ 2.9 \pm 1.9 \\ 1.0 \pm 0.2 \end{array}$	778 991 588	$7824 \\ 23500 \\ 6219$	$144 \\ 19 \\ 1027$
200D									
$\begin{array}{c} 3\times128\\ 3\times256\\ 3\times128\end{array}$	$\begin{array}{c}10\\10\\2\end{array}$	MAF RealNVP A-RQS	 12	3.7 ± 1.4 6.3 ± 2.3 1.3 ± 0.2	11 ± 6 19 ± 11 3.3 ± 1.1	3.4 ± 2.4 5.4 ± 2.2 1.0 ± 0.5	612 1000 703	$6149 \\ 22704 \\ 9943$	$393 \\ 25 \\ 4900$
400D									
$\begin{array}{c} 3\times128\\ 3\times256\\ 3\times128 \end{array}$	$\begin{array}{c}10\\10\\2\end{array}$	MAF RealNVP A-RQS	- - 8	$\begin{array}{c} 4.3 \pm 1.8 \\ 8.4 \pm 2.4 \\ 2.2 \pm 0.9 \end{array}$	14 ± 8 21 ± 11 6.9 ± 1.8	$8 \pm 6 \\ 24 \pm 10 \\ 11 \pm 4$	600 824 796	$4612 \\ 23705 \\ 9970$	$1242 \\ 38 \\ 9738$

Table 2 Values of the most relevant hyperparameters and metrics for the average best models obtained for the CMoG distributions. The number of training epochs, and the training and prediction times are averages. The values of the test-statistics are those shown in the left panes of Fig. 1.

Results for Absolute Best models									
hidden layers	# of bijec.	algorithm	$_{ m knots}^{ m spline}$	$\begin{array}{c} \text{KS-test} \\ p\text{-value} \end{array}$	Sliced WD	Frobenius Norm	# of epochs	training time (s)	prediction time (s)
4D									
$ \begin{array}{r} 3 \times 128 \\ 3 \times 256 \\ 3 \times 128 \\ 3 \times 128 \end{array} $	$ \begin{array}{c} 10 \\ 5 \\ 2 \\ 5 \end{array} $	MAF RealNVP A-RQS C-RQS	- - 8 8	$\begin{array}{c} 1.1 \pm 0.1 \\ 1.1 \pm 0.2 \\ 1.1 \pm 0.2 \\ 1.2 \pm 0.2 \end{array}$	2.0 ± 0.5 2.3 ± 0.6 2.2 ± 0.6 2.8 ± 0.7	$\begin{array}{c} 0.5 \pm 0.1 \\ 0.7 \pm 0.3 \\ 0.5 \pm 0.2 \\ 0.6 \pm 0.2 \end{array}$	442 616 670 483	$5301 \\ 8777 \\ 7606 \\ 12346$	$\begin{array}{c} 17\\8\\54\\26\end{array}$
8D									
$3 \times 128 \\ 3 \times 128 \\ 3 \times 128 \\ 3 \times 128 \\ 3 \times 128$	$5\\10\\2\\5$	MAF RealNVP A-RQS C-RQS	$\begin{array}{c} -\\ -\\ 12\\ 8\end{array}$	$\begin{array}{c} 1.1 \pm 0.2 \\ 1.3 \pm 0.2 \\ 1.1 \pm 0.1 \\ 1.4 \pm 0.1 \end{array}$	$\begin{array}{c} 2.7 \pm 0.4 \\ 3.2 \pm 1.0 \\ 2.6 \pm 0.8 \\ 3.1 \pm 0.8 \end{array}$	$\begin{array}{c} 0.6 \pm 0.1 \\ 0.6 \pm 0.1 \\ 0.6 \pm 0.2 \\ 1.0 \pm 0.2 \end{array}$	713 340 477 294	5757 8242 5516 11500	$ 11 \\ 12 \\ 315 \\ 27 $
16D									
$3 \times 128 \\ 3 \times 128 \\ 3 \times 128 \\ 3 \times 128 \\ 3 \times 128$	$5 \\ 5 \\ 2 \\ 10$	MAF RealNVP A-RQS C-RQS	$\begin{array}{c} -\\ -\\ 12\\ 8\end{array}$	$\begin{array}{c} 1.3 \pm 0.1 \\ 2.2 \pm 0.1 \\ 1.4 \pm 0.1 \\ 1.1 \pm 0.1 \end{array}$	$\begin{array}{c} 2.8 \pm 0.9 \\ 4.6 \pm 0.6 \\ 2.4 \pm 0.5 \\ 2.3 \pm 0.3 \end{array}$	$\begin{array}{c} 2.4 \pm 0.9 \\ 6.3 \pm 0.9 \\ 1.1 \pm 0.2 \\ 1.9 \pm 0.3 \end{array}$	$479 \\ 366 \\ 327 \\ 558$	$3410 \\ 4263 \\ 3705 \\ 64056$	$ \begin{array}{r} 16 \\ 8 \\ 65 \\ 53 \\ \end{array} $
32D									
$3 \times 128 \\ 3 \times 128 \\ 3 \times 128 \\ 3 \times 256$	$5\\10\\2\\10$	MAF RealNVP A-RQS C-RQS	- 8 12	$\begin{array}{c} 1.2 \pm 0.1 \\ 1.7 \pm 0.2 \\ 1.3 \pm 0.1 \\ 1.4 \pm 0.2 \end{array}$	$\begin{array}{c} 2.8 \pm 0.7 \\ 4.0 \pm 1.4 \\ 2.9 \pm 0.4 \\ 2.9 \pm 0.5 \end{array}$	$\begin{array}{c} 0.9 \pm 0.2 \\ 1.8 \pm 0.5 \\ 1.2 \pm 0.2 \\ 1.2 \pm 0.1 \end{array}$	595 676 375 750	$\begin{array}{r} 4193 \\ 16946 \\ 4705 \\ 75606 \end{array}$	24 12 97 83
64D									
$3 \times 128 \\ 3 \times 256 \\ 3 \times 128 \\ 3 \times 256$	$\begin{array}{c}10\\10\\2\\5\end{array}$	MAF RealNVP A-RQS C-RQS	- 8 12	$\begin{array}{c} 1.5 \pm 0.1 \\ 1.8 \pm 0.1 \\ 1.1 \pm 0.2 \\ 1.5 \pm 0.1 \end{array}$	$\begin{array}{c} 3.1 \pm 0.7 \\ 3.7 \pm 0.8 \\ 3.1 \pm 0.8 \\ 3.7 \pm 0.5 \end{array}$	$\begin{array}{c} 0.8 \pm 0.1 \\ 1.1 \pm 0.2 \\ 0.6 \pm 0.1 \\ 1.8 \pm 0.1 \end{array}$	537 711 523 813	$5289 \\ 13871 \\ 6197 \\ 36608$	89 16 332 53
100D									
$\begin{array}{c} 3\times128\\ 3\times256\\ 3\times128 \end{array}$	$\begin{array}{c}10\\10\\2\end{array}$	MAF RealNVP A-RQS	- - 12	$\begin{array}{c} 1.3 \pm 0.1 \\ 1.9 \pm 0.1 \\ 1.1 \pm 0.2 \end{array}$	3.7 ± 0.7 3.1 ± 0.5 2.8 ± 0.8	$\begin{array}{c} 0.8 \pm 0.2 \\ 1.4 \pm 0.1 \\ 0.8 \pm 0.3 \end{array}$	778 991 588	$7824 \\ 23500 \\ 6219$	$144 \\ 19 \\ 1027$
200D									
$\begin{array}{c} 3\times128\\ 3\times256\\ 3\times128 \end{array}$	$\begin{array}{c}10\\10\\2\end{array}$	MAF RealNVP A-RQS	$^{-}_{-}$ 12	$\begin{array}{c} 2.2 \pm 0.3 \\ 4.0 \pm 0.2 \\ 1.0 \pm 0.1 \end{array}$	5.9 ± 1.3 8.8 ± 1.2 2.3 ± 0.7	$\begin{array}{c} 1.0 \pm 0.1 \\ 2.9 \pm 0.2 \\ 0.6 \pm 0.1 \end{array}$	$612 \\ 1000 \\ 703$	$\begin{array}{c} 6149 \\ 22704 \\ 9943 \end{array}$	$393 \\ 25 \\ 4900$
400D									
$\begin{array}{c} 3\times128\\ 3\times256\\ 3\times128 \end{array}$	$\begin{array}{c}10\\10\\2\end{array}$	MAF RealNVP A-RQS		$1.7 \pm 0.2 \\ 5.3 \pm 0.1 \\ 1.2 \pm 0.1$	13.2 ± 1.3 10.1 ± 0.2 3.3 ± 0.7	12.0 ± 0.7 8.3 ± 0.1 2.7 ± 0.6	600 824 796	4612 23705 9970	$1242 \\ 38 \\ 9738$

Table 3 Values of the most relevant hyperparameters and metrics for the absolute best models obtained for the CMoG distributions. The number of training epochs, and the training and prediction times are averages. The values of the test-statistics are those shown in the right panes of Fig. 1.

D Corner plots



Fig. 2 Visual representation of the 1D and 2D marginal distributions for 25 randomly chosen dimensions of the N = 100 dimensional CMoG distribution obtained with 10⁵ points. Red and blue curves and points represent the test samples and the NF-generated samples obtained with the A-RQS best model, respectively. Considering the high dimensionality, the non-trivial structure of the distribution, the limited number of training samples, and the low level of tuning of the hyperparameters, the result can be considered very accurate.

References

- E. Tabak and E. Vanden-Eijnden, "Density estimation by dual ascent of the loglikelihood", Communications in Mathematical Sciences 8 (2010) 217 [SEMANTIC SCHOLAR].
- [2] E. Tabak and C. Turner, "A family of nonparametric density estimation algorithms", Communications on Pure and Applied Mathematics 66 (2013) 145 [SEMANTIC SCHOLAR].
- [3] D. J. Rezende and S. Mohamed, "Variational Inference with Normalizing Flows", in International Conference on Machine Learning, 2015, arXiv:1505.05770 [SEMAN-TIC SCHOLAR].
- [4] L. Dinh, D. Krueger and Y. Bengio, "NICE: Non-linear Independent Components Estimation", arXiv:1410.8516 [SEMANTIC SCHOLAR].
- [5] I. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair et al., "Generative Adversarial Nets", in Advances in Neural Information Processing Systems, Z. Ghahramani, M. Welling, C. Cortes, N. Lawrence and K. Weinberger, eds., vol. 27, Curran Associates, Inc., 2014, arXiv:1406.2661 [SEMANTIC SCHOLAR].
- [6] D. P. Kingma and M. Welling, "Auto-Encoding Variational Bayes", in 2nd International Conference on Learning Representations, ICLR 2014, Banff, AB, Canada, April 14-16, 2014, Conference Track Proceedings, 2014, arXiv:1312.6114 [SEMANTIC SCHOLAR].
- [7] D. J. Rezende, S. Mohamed and D. Wierstra, "Stochastic Backpropagation and Approximate Inference in Deep Generative Models", in Proceedings of the 31st International Conference on Machine Learning, E. P. Xing and T. Jebara, eds., vol. 32 of Proceedings of Machine Learning Research, pp. 1278– 1286, PMLR, Bejing, China, 22–24 jun, 2014, arXiv:1401.4082 [SEMANTIC SCHOLAR].

- [8] Y. Fan, D. J. Nott and S. A. Sisson, "Approximate Bayesian computation via regression density estimation", Stat 2 (2013) 34, arXiv:1212.1479 [SEMANTIC SCHOLAR].
- [9] G. Papamakarios and I. Murray, "Fast εfree Inference of Simulation Models with Bayesian Conditional Density Estimation", in Advances in Neural Information Processing Systems, D. Lee, M. Sugiyama, U. Luxburg, I. Guyon and R. Garnett, eds., vol. 29, Curran Associates, Inc., 2016, arXiv:1605.06376 [SEMANTIC SCHOLAR].
- [10] J. Brehmer, G. Louppe, J. Pavez and K. Cranmer, "Mining gold from implicit models to improve likelihood-free inference", Proc. Nat. Acad. Sci. 117 (2020) 5242, arXiv:1805.12244 [SEMANTIC SCHOLAR].
- [11] S. R. Green, C. Simpson and J. Gair, "Gravitational-wave parameter estimation with autoregressive neural network flows", Phys. Rev. D 102 (2020) 104057, arXiv:2002.07656 [SEMANTIC SCHOLAR].
- [12] V. A. Villar, "Amortized Bayesian Inference for Supernovae in the Era of the Vera Rubin Observatory Using Normalizing Flows", in 36th Conference on Neural Information Processing Systems, 11, 2022, arXiv:2211.04480 [SEMANTIC SCHOLAR].
- [13] J.-E. Campagne, F. Lanusse, J. Zuntz, A. Boucaud, S. Casas, M. Karamanis et al., "JAX-COSMO: An End-to-End Differentiable and GPU Accelerated Cosmology Library", arXiv:2302.05163 [SEMANTIC SCHOLAR].
- [14] M. Bellagente, "Go with the Flow: Normalising Flows applications for High Energy Physics", PhD Thesis, U. Heidelberg (2022) [SEMANTIC SCHOLAR].
- [15] D. Zoran and Y. Weiss, "From learning models of natural image patches to whole image restoration", in Proceedings of the 13rd International Conference on Computer Vision, pp. 479–486, 2011 [SEMANTIC SCHOLAR].

- [16] S. R. Green and J. Gair, "Complete parameter inference for GW150914 using deep learning", Mach. Learn. Sci. Tech. 2 (2021) 03LT01, arXiv:2008.03312 [SEMAN-TIC SCHOLAR].
- [17] T. Glüsenkamp, "Unifying supervised learning and VAEs – automating statistical inference in (astro-)particle physics with amortized conditional normalizing flows", arXiv:2008.05825 [SEMANTIC SCHOLAR].
- [18] D. Kodi Ramanah, R. Wojtak, Z. Ansari, C. Gall and J. Hjorth, "Dynamical mass inference of galaxy clusters with neural flows", Mon. Not. Roy. Astron. Soc. 499 (2020) 1985, arXiv:2003.05951 [SEMANTIC SCHOLAR].
- [19] D. H. T. Cheung, K. W. K. Wong, O. A. Hannuksela, T. G. F. Li and S. Ho, "Testing the robustness of simulation-based gravitationalwave population inference", Phys. Rev. D 106 (2022) 083014, arXiv:2112.06707 [SEMAN-TIC SCHOLAR].
- [20] D. Ruhe, K. Wong, M. Cranmer and P. Forré, "Normalizing Flows for Hierarchical Bayesian Analysis: A Gravitational Wave Population Study", arXiv:2211.09008 [SEMANTIC SCHOLAR].
- [21] S. S. Gu, Z. Ghahramani and R. E. Turner, "Neural Adaptive Sequential Monte Carlo", in Advances in Neural Information Processing Systems, C. Cortes, N. Lawrence, D. Lee, M. Sugiyama and R. Garnett, eds., vol. 28, Curran Associates, Inc., 2015, arXiv:1506.03338 [SEMANTIC SCHOLAR].
- [22] B. Paige and F. Wood, "Inference Networks for Sequential Monte Carlo in Graphical Models", in Proceedings of the 33rd International Conference on International Conference on Machine Learning - Volume 48, ICML'16, p. 3040–3049, JMLR.org, 2016, arXiv:1602.06701 [SEMANTIC SCHOLAR].
- [23] S. Foreman, T. Izubuchi, L. Jin, X.-Y. Jin, J. C. Osborn and A. Tomiya, "HMC with Normalizing Flows", PoS LATTICE2021 (2022) 073, arXiv:2112.01586 [SEMANTIC

SCHOLAR.

- [24] D. C. Hackett, C.-C. Hsieh, M. S. Albergo, D. Boyda, J.-W. Chen, K.-F. Chen et al., "Flow-based sampling for multimodal distributions in lattice field theory", arXiv:2107.00734 [SEMANTIC SCHOLAR].
- [25] A. Singha, D. Chakrabarti and V. Arora, "Conditional normalizing flow for Markov chain Monte Carlo sampling in the critical region of lattice field theory", Phys. Rev. D 107 (2023) 014512 [SEMANTIC SCHOLAR].
- [26] M. Caselle, E. Cellini, A. Nada and M. Panero, "Stochastic normalizing flows for lattice field theory", PoS LATTICE2022 (2023) 005, arXiv:2210.03139 [SEMANTIC SCHOLAR].
- [27] A. G. D. G. Matthews, M. Arbel, D. J. Rezende and A. Doucet, "Continual Repeated Annealed Flow Transport Monte Carlo", in International Conference on Machine Learning, 1, 2022, arXiv:2201.13117 [SEMANTIC SCHOLAR].
- [28] K. Cranmer, G. Kanwar, S. Racanière, D. J. Rezende and P. Shanahan, "Advances in machine-learning-based sampling motivated by lattice quantum chromodynamics", Nature Rev. Phys. 5 (2023) 526, arXiv:2309.01156 [SEMANTIC SCHOLAR].
- [29] G. Papamakarios and I. Murray, "Distilling Intractable Generative Models", in Probabilistic Integration Workshop at the Neural Information Processing Systems Conference, 2015, 2015 [SEMANTIC SCHOLAR].
- [30] M. Gabrié, G. M. Rotskoff and E. Vanden-Eijnden, "Adaptive Monte Carlo augmented with normalizing flows", Proc. Nat. Acad. Sci. 119 (2022) e2109420119, arXiv:2105.12603 [SEMANTIC SCHOLAR].
- [31] S. Pina-Otey, V. Gaitan, F. Sánchez and T. Lux, "Exhaustive neural importance sampling applied to Monte Carlo event generation", Phys. Rev. D 102 (2020) 013003, arXiv:2005.12719 [SEMANTIC SCHOLAR].

- [32] C. Gao, S. Höche, J. Isaacson, C. Krause and H. Schulz, "Event Generation with Normalizing Flows", Phys. Rev. D 101 (2020) 076002, arXiv:2001.10028 [SEMANTIC SCHOLAR].
- [33] T. A. Le, A. G. Baydin and F. Wood, "Inference Compilation and Universal Probabilistic Programming", in Proceedings of the 20th International Conference on Artificial Intelligence and Statistics, A. Singh and J. Zhu, eds., vol. 54 of Proceedings of Machine Learning Research, pp. 1338–1348, PMLR, 20– 22 apr, 2017, arXiv:1610.09900 [SEMANTIC SCHOLAR].
- [34] G. Papamakarios, E. Nalisnick, D. J. Rezende, S. Mohamed and B. Lakshminarayanan, "Normalizing Flows for Probabilistic Modeling and Inference", J. Mach. Learn. Res. 22 (2022) 1, arXiv:1912.02762 [SEMANTIC SCHOLAR].
- [35] A. Butter, T. Heimel, S. Hummerich, T. Krebs, T. Plehn, A. Rousselot et al., "Generative Networks for Precision Enthusiasts", arXiv:2110.13632 [SEMANTIC SCHOLAR].
- [36] R. Verheyen, "Event Generation and Density Estimation with Surjective Normalizing Flows", SciPost Phys. 13 (2022) 047, arXiv:2205.01697 [SEMANTIC SCHOLAR].
- [37] C. Krause and D. Shih, "CaloFlow: Fast and Accurate Generation of Calorimeter Showers with Normalizing Flows", arXiv:2106.05285 [SEMANTIC SCHOLAR].
- [38] C. Krause and D. Shih, "CaloFlow II: Even Faster and Still Accurate Generation of Calorimeter Showers with Normalizing Flows", arXiv:2110.11377 [SEMANTIC SCHOLAR].
- [39] C. Gao, J. Isaacson and C. Krause, "i-flow: High-dimensional Integration and Sampling with Normalizing Flows", Mach. Learn. Sci. Tech. 1 (2020) 045023, arXiv:2001.05486 [SEMANTIC SCHOLAR].
- [40] T. Heimel, R. Winterhalder, A. Butter, J. Isaacson, C. Krause, F. Maltoni et al., "MadNIS - Neural multi-channel importance

sampling", SciPost Phys. **15** (2023) 141, arXiv:2212.06172 [SEMANTIC SCHOLAR].

- [41] T. Heimel, N. Huetsch, F. Maltoni, O. Mattelaer, T. Plehn and R. Winterhalder, "The MadNIS Reloaded", arXiv:2311.01548 [SEMANTIC SCHOLAR].
- [42] F. Ernst, L. Favaro, C. Krause, T. Plehn and D. Shih, "Normalizing Flows for High-Dimensional Detector Simulations", arXiv:2312.09290 [SEMANTIC SCHOLAR].
- [43] B. Nachman and D. Shih, "Anomaly Detection with Density Estimation", Phys. Rev. D 101 (2020) 075042, arXiv:2001.04990 [SEMANTIC SCHOLAR].
- [44] T. Golling, S. Klein, R. Mastandrea and B. Nachman, "FETA: Flow-Enhanced Transportation for Anomaly Detection", arXiv:2212.11285 [SEMANTIC SCHOLAR].
- [45] S. Caron, L. Hendriks and R. Verheyen, "Rare and Different: Anomaly Scores from a combination of likelihood and out-of-distribution models to detect new physics at the LHC", SciPost Phys. 12 (2022) 077 [SEMANTIC SCHOLAR].
- [46] M. Bellagente, A. Butter, G. Kasieczka, T. Plehn, A. Rousselot, R. Winterhalder et al., "Invertible Networks or Partons to Detector and Back Again", SciPost Phys. 9 (2020) 074, arXiv:2006.06685 [SEMANTIC SCHOLAR].
- [47] M. Backes, A. Butter, M. Dunford and B. Malaescu, "An unfolding method based on conditional Invertible Neural Networks (cINN) using iterative training", arXiv:2212.08674 [SEMANTIC SCHOLAR].
- [48] H. Reyes-Gonzalez and R. Torre, "Testing the boundaries: Normalizing Flows for higher dimensional data sets", J. Phys. Conf. Ser. 2438 (2023) 012155, arXiv:2202.09188 [SEMANTIC SCHOLAR].
- [49] L. Dinh, J. Sohl-Dickstein and S. Bengio, "Density estimation using Real NVP", in International Conference on Learning

Representations, 2017, arXiv:1605.08803 [SEMANTIC SCHOLAR].

- [50] G. Papamakarios, T. Pavlakou and I. Murray, "Masked Autoregressive Flow for Density Estimation", in Advances in Neural Information Processing Systems, I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan et al., eds., vol. 30, Curran Associates, Inc., 2017, arXiv:1705.07057 [SEMANTIC SCHOLAR].
- [51] C. Durkan, A. Bekasov, I. Murray and G. Papamakarios, "Neural Spline Flows", in Proceedings of the 33rd International Conference on Neural Information Processing Systems, Curran Associates Inc., Red Hook, NY, USA, 2019, arXiv:1906.04032 [SEMANTIC SCHOLAR].
- [52] F. Noé, J. Köhler and H. Wu, "Boltzmann generators: Sampling equilibrium states of many-body systems with deep learning", Science 365 (2018) [SEMANTIC SCHOLAR].
- [53] L. I. Midgley, V. Stimper, G. N. C. Simm, B. Scholkopf and J. M. Hernández-Lobato, "Flow annealed importance sampling bootstrap", ArXiv abs/2208.01893 (2022) [SEMANTIC SCHOLAR].
- [54] A. Grover, M. Dhar and S. Ermon, "Flowgan: Combining maximum likelihood and adversarial learning in generative models", in AAAI Conference on Artificial Intelligence, 2017 [SEMANTIC SCHOLAR].
- [55] C. Villani, "Topics in optimal transportation (graduate studies in mathematics 58)", . American Mathematical Soc., 2003. [SEMAN-TIC SCHOLAR].
- [56] M. Arjovsky, S. Chintala and L. Bottou, "Wasserstein generative adversarial networks", in International Conference on Machine Learning, 2017, arXiv:1701.07875 [SEMANTIC SCHOLAR].
- [57] I. O. Tolstikhin, O. Bousquet, S. Gelly and B. Schölkopf, "Wasserstein auto-encoders", ArXiv (2017), arXiv:1711.01558 [SEMAN-TIC SCHOLAR].

- [58] I. Kobyzev, S. J. Prince and M. A. Brubaker, "Normalizing Flows: An Introduction and Review of Current Methods", IEEE Transactions on Pattern Analysis and Machine Intelligence 43 (2021) 3964 [SEMANTIC SCHOLAR].
- [59] D. P. Kingma, T. Salimans, R. Jozefowicz, X. Chen, I. Sutskever and M. Welling, "Improved Variational Inference with Inverse Autoregressive Flow", in Proceedings of the 30th International Conference on Neural Information Processing Systems, NIPS'16, p. 4743–4751, Curran Associates Inc., Red Hook, NY, USA, 2016, arXiv:1606.04934 [SEMANTIC SCHOLAR].
- [60] M. Germain, K. Gregor, I. Murray and H. Larochelle, "MADE: Masked Autoencoder for Distribution Estimation", in Proceedings of the 32nd International Conference on Machine Learning, arXiv, 2015, arXiv:1502.03509 [SEMANTIC SCHOLAR].
- [61] J. A. Gregory and R. Delbourgo, "Piecewise Rational Quadratic Interpolation to Monotonic Data", IMA Journal of Numerical Analysis 2 (1982) 123 [SEMANTIC SCHOLAR].
- [62] A. Kolmogorov-Smirnov, A. N. Kolmogorov and M. Kolmogorov, "Sulla determinazione empírica di uma legge di distribuzione", 1933 [SEMANTIC SCHOLAR].
- [63] N. Smirnov, "On the estimation of the discrepancy between empirical curves of distribution for two independent samples", Bull. Math. Univ. Moscou. 2 (1939) 2.
- [64] A. N. Kolmogoroff, "Confidence limits for an unknown distribution function", Annals of Mathematical Statistics 12 (1941) 461 [SEMANTIC SCHOLAR].
- [65] N. V. Smirnov, "Table for estimating the goodness of fit of empirical distributions", Annals of Mathematical Statistics 19 (1948) 279 [SEMANTIC SCHOLAR].
- [66] KStwobign Distribution, Scipy Python package, Scipy Documentation.

- [67] J. Rabin, G. Peyré, J. Delon and M. Bernot, "Wasserstein Barycenter and Its Application to Texture Mixing", in Scale Space and Variational Methods in Computer Vision, A. M. Bruckstein, B. M. ter Haar Romeny, A. M. Bronstein and M. M. Bronstein, eds., pp. 435–446, Springer Berlin Heidelberg, Berlin, Heidelberg, 2012 [SEMANTIC SCHOLAR].
- [68] N. Bonneel, J. Rabin, G. Peyré and H. Pfister, "Sliced and Radon Wasserstein Barycenters of Measures", Journal of Mathematical Imaging and Vision 51 (2015) 22 [SEMANTIC SCHOLAR].
- [69] L. V. Kantorovich, "On the translocation of masses", C. R. (Doklady) Acad. Sci. URSS (N. S.) 37 (1942) 199 [SEMANTIC SCHOLAR].
- [70] R. L. Wasserstein, "Markov processes over denumerable products of spaces, describing large systems of automata", Problemy Peredachi Informatsii 5 (1969) 64.
- [71] M. E. Muller, "A note on a method for generating points uniformly on n-dimensional spheres", Commun. ACM 2 (1959) 19–20 [SEMANTIC SCHOLAR].
- [72] Code repository for this paper on GITHUB \bigcirc .
- [73] NF4HEP code repository on GITHUB **(**).
- [74] Code repository for statistical inference and evaluation metrics on GITHUB **?**.
- [75] A. Coccaro, M. Pierini, L. Silvestrini and R. Torre, "The DNNLikelihood: enhancing likelihood distribution with Deep Learning", Eur.Phys.J.C 80 (2020) 664, arXiv:1911.03305 [SEMANTIC SCHOLAR].
- [76] H. Reyes-Gonzalez and R. Torre, "The NFLikelihood: an unsupervised DNN-Likelihood from Normalizing Flows", arXiv:2309.09743 [SEMANTIC SCHOLAR].
- [77] J. Friedman, "On Multivariate Goodnessof-Fit and Two-Sample Testing", in Statistical Problems in Particle Physics, Astrophysics, and Cosmology, L. Lyons, R. Mount

and R. Reitmeyer, eds., p. 311, Jan., 2003 [SEMANTIC SCHOLAR].

- [78] R. Kansal, A. Li, J. Duarte, N. Chernyavskaya, M. Pierini, B. Orzari et al., "On the Evaluation of Generative Models in High Energy Physics", arXiv:2211.10295 [SEMANTIC SCHOLAR].
- [79] R. T. D'Agnolo, G. Grosso, M. Pierini, A. Wulzer and M. Zanetti, "Learning multivariate new physics", Eur. Phys. J. C 81 (2021) 89, arXiv:1912.12155 [SEMANTIC SCHOLAR].
- [80] P. Chakravarti, M. Kuusela, J. Lei and L. Wasserman, "Model-Independent Detection of New Physics Signals Using Interpretable Semi-Supervised Classifier Tests", arXiv:2102.07679 [SEMANTIC SCHOLAR].
- [81] M. Letizia, G. Losapio, M. Rando, G. Grosso, A. Wulzer, M. Pierini et al., "Learning new physics efficiently with nonparametric methods", Eur. Phys. J. C 82 (2022) 879, arXiv:2204.02317 [SEMANTIC SCHOLAR].
- [82] L. Del Debbio, J. M. Rossney and M. Wilson, "Machine Learning Trivializing Maps: A First Step Towards Understanding How Flow-Based Samplers Scale Up", PoS LAT-TICE2021 (2022) 059, arXiv:2112.15532 [SEMANTIC SCHOLAR].
- [83] TENSORFLOW PROBABILITY MAF documentation.