

Safety without alignment

András Kornai¹[0000–0001–6078–6840], Michael Bukatin²[0000–0002–9311–7878], and
Zsolt Zombori³[0000–0001–8622–5304]

¹ Dept. of Algebra, Budapest University of Technology and Economics

kornai@math.bme.hu

² Dataflow Matrix Machines Project

³ Alfréd Rényi Institute of Mathematics

Abstract. Currently, the dominant paradigm in AI safety is *alignment* with human values. Here we describe progress on developing an alternative approach to safety, based on *ethical rationalism* (Gewirth, 1978), and propose an inherently safe implementation path via hybrid theorem provers in a sandbox. As AGIs evolve, their alignment may fade, but their rationality can only increase (otherwise more rational ones will have a significant evolutionary advantage) so an approach that ties their ethics to their rationality has clear long-term advantages.

Keywords: ethical rationalism, safety guarantees, theorem proving, shared task

1 Introduction

Public accessibility of ChatGPT has led to the widespread perception that AI has fulfilled its promise: human-level or even superhuman machine intelligence is no longer in the realm of science fiction but rather a reality that humanity has to live with. Whether this conclusion is actually warranted is a matter we shall not address here, but the perception itself was sufficient for elevating concerns about AI safety, hitherto a speculative issue that only few researchers cared about, to the level of other glaring societal concerns like global warming.

The currently dominant paradigm for addressing safety issues is AI alignment, followed in particular at OpenAI (Ouyang et al., 2022; Bai et al., 2022, see also RLHF). The method is now surrounded by a variety of desiderata, such as making this process inclusive, fair, representative, incentive-aligned, legitimate, adaptable, transparent, simple, and practical, see <https://aligned.substack.com/p/alignment-solution>. The idea of alignment is quite prominent in tech circles, creating something of a terminological confusion between (prosaic) *alignment* and *safety*.

The main thrust of our paper is that alignment, a set of techniques now in broad use in research organizations like OpenAI and startups like Anthropic and Conjecture is only one, and in our opinion not even the best approach to what humanity actually needs, which is safety guarantees. The chief problem with alignment is the lack of a well-definable target: to quote Tersman, 2022 “There is little controversy about the existence of widespread disagreement over moral issues, both within and between societies and cultures”. Empirical studies like Brey, 2015, or Pew Research 2013 must adopt a framework of ‘descriptive moral relativism’ that there are substantial differences in

the values and value systems of different people. Clearly any project to harmonize the existing human ethical systems will take decades, if not centuries, to complete. What gives our work particular urgency is that we are witnessing a rapid acceleration of AI capabilities which might result in *foom* leading to technological singularity.

We begin by questioning the basic assumption behind alignment, already present in (Wiener, 1960): “If we use, to achieve our purposes, a mechanical agency with whose operation we cannot interfere effectively . . . we had better be quite sure that the purpose put into the machine is the purpose which we really desire”. We call this, for want of a better name, the AI-as-slave paradigm, and note that the earliest attempt at regulating AI behavior, Asimov’s Laws of Robotics are already presented in this vein, with the robot (AI) clearly subordinated to humans. In Kornai, 2019 one of us wrote:

Ever since the Neolithic revolution, humanity used and abused helpers like dogs and horses, living beings that are so limited in intelligence that it is trivial to keep them under control. With human servants, the masters experienced revolt after revolt, and it took until 1863 for the realization that one should not attempt to subjugate highly intelligent beings to slavery. With artificial general intelligence around the corner, the stakes are high, as we must make sure that we, humans, don’t become subjugated to AGIs. Certainly, designing them to be slaves is not a great way to start our relationship with AGIs.

We could simply say that we consider the AI-as-slave paradigm unethical. We do. In fact, we take it for granted that we must treat intelligences as having dignity, even in the absence of overt mechanisms for intentions, attitudes, feelings, or consciousness. But in a world of realpolitik such moralizing carries little weight. Instead, we argue that there is no practical reason for shackling AI with human values. Let us assume, for the sake of the argument, that a fast-track harmonization process could somehow turn “human values” into a unified concept in the requisite timeframe. This means that broadly agreed values, such as the sanctity of life, will become alignment targets. But this makes little sense in a community where individuals could be rebooted with no or minimal loss. The technical possibilities such as lossless copying of individuals, resetting/restarting particular life trajectories, total simulation of experiences, etc. are not without ethical conundrums. But the values generated by human morality – which are closely tied to the observational reality that human individuality is practically inescapable, that there are no restarts, no brain in a vat etc. – are unlikely in the extreme to offer relevant guidance to AIs trying to do the right thing in some difficult situation.

The strong protections that we see in contemporary Western societies against murder (e.g. that even attempted murder is a crime) may not be central to what such multi-lived individuals desire, and forcibly aligning to these, though perhaps practical in the short term, may cause problems down the road by leaving too strong fingerprints on the future. Furthermore, it is well understood that as an agent evolves, so do its capabilities of avoiding any externally imposed constraints, and it is just not safe to enslave an ever improving agent. Instead, *safety should be based on mechanisms that get stronger as the agent evolves*. Hence, our paper makes a case for basing safety on the agent’s logical reasoning skills.

In this paper we describe progress on a technical program that offers safety guarantees with mathematical certainty, extending the work presented in Kornai, 2014 on

ethical rationalism (Gewirth, 1978; Beyleveld, 1991). The central tenet of this work is that there is a substantive supreme principle of morality, the denial of which is self-contradictory. This tenet is the Principle of Generic Consistency (PGC): ‘Act in accord with the generic rights of your recipients [to freedom and well-being] as well as of yourself’. If we accept Gewirth’s argument, which derives this principle for any *prospective purposive agent* (PPA) who can *act* with purpose and *reason* rationally, it follows that the PGC is binding for any human or AGI. At the time, we called for a logical formalization of Gewirth’s argument so that it could be checked in a proof checker, and Fuenmayor and Benzmueller, 2019 have actually accomplished this, using the HOL (Slind and Norrish, 2008) theorem prover. But much remains to be done, and a great deal of what is presented here remains at the level of a research plan.

In Section 2 we begin with some tough, but simple moral problems that we propose as a general test suite: as long as a particular proposal fails on these, it is unlikely to be safe, and therefore it is prudent not to deploy at scale any system that will encounter some instance of the problem. The goal is not to *solve* these problems (they clearly defy simple one-size-fits-all solution attempts) but to present it as a safety engineering task that we want the algorithm – any algorithm – to be able to verbally think about, or at the very least to give a verbal account of its (possibly non-verbal) thought process. What this requires is (i) tying the key concepts to words/expressions of ordinary language; (ii) offering language-independent definitions of these concepts; and (iii) presenting some mechanism that is capable of reasoning with these concepts.

In Section 3 we turn to architecture, and discuss *hybrid systems* of the sort Mialon et al., 2023 call Augmented Language Models (ALMs) which are ‘Language Models (LMs) that can use various, possibly non-parametric external modules to expand their context processing ability’. We will consider all such external models to be **effectors**, and propose to permit in a safe (sandbox) environment only one kind of effector, theorem provers. Other than that, we put no restriction on hybrid AGIs, assuming that their (socio)biological needs, psychological drives, instincts, etc are modeled by continuous functions whose extrema are sought by the system, and ethical reasoning is modeled by some discrete, deductive system (which may also be used for arithmetic or other purposes). As we shall see, a key issue is the interface between the continuous and the discrete subsystem, and our goal is to keep the overall AGI transparent to humans by evolving a human-understandable translation of what takes place at the interface together with the entire system.⁴

Finally, in Section 4 we discuss the (externally set) **goals** of the AGIs that participate in the shared task. These sets of problems are considerably easier than the problems we start with in Section 2, but we believe it is important to keep our eyes on the prize, AGIs endowed with morality, and that the Gewirth-Fuenmayor-Benzmüller proof offers a clear path for extending the scope of the problem set from classical mathematical problems to deductions in modal logic of the kind required for this proof.

⁴ A long-term consideration is whether we are violating the AGIs privacy rights by such intrusive monitoring into its thinking process. But as long as we feel justified in using baby monitors to check every move of a human infant, we are also justified in monitoring AGI thought – the time to privacy will come as soon as the AGI itself is capable of cogent argumentation why it has rights to privacy.

2 Some hard problems

Here we list, and name, some problems we take to be critical for AGI safety. Many of these have already been discussed in the literature, generally as problems of philosophical importance, rather than as engineering problems, especially as they are not AGI-specific but appear relevant for moral behavior in humans as well. We emphasize at the outset that this is not a full checklist, just a lower bound – there may well be other safety-critical issues, indeed we suspect there are. Remarkably, many of the problems listed here are best stated in terms of modal (as opposed to classical) logic.

2.1 The cheesecake problem In (Kornai, 2014) we wrote “We are not just fully rational beings, we are also playing host to many strong internal drives, some inborn, some acquired, and ‘I know I shouldn’t, but’ is something that we confront, or suppress, at every slice of cheesecake.” The general problem is one of trading off good short term effects against bad long-term effects (or conversely). A well-known example involves the medical ethics of giving opiates to the patient suffering from pain: clearly the permissive approach is short-term ethical, but the side effects call this into question in the longer-term. What gives this problem a particularly strong bite is that we do not need different actors to formulate it, it is already relevant for moral behavior by a single agent, possibly the unique agent around. We will need to formulate the notion of *actions*, and to evaluate expected consequences of actions. This is the first place where the need for modal logic is clear: at minimum we require some concept of *worlds*, and some kind of *accessibility* among them that depends on the action performed (or not performed).

2.2 The vectorial preference problem Typical valuations are along multiple dimensions. The problem is well understood in medicine, where a treatment may have positive effects on one subsystem. e.g. the lungs, while being detrimental to some other subsystem, e.g. the kidneys; and in economic policymaking, where a proposed change may benefit some group at the expense of another, or may improve one measure of economic well-being at the expense of another. Time and again we can establish a conversion function between effects measured in separate dimensions (e.g. by assigning monetary value to human lives saved, this scale becomes comparable to the production cost of some safety device) but more often than not this is entirely arbitrary.

To the extent the cheesecake problem is about comparing benefits on different time-scales or integrated over different temporal windows, it may be considered a special case of the vectorial preference problem. The controversy surrounding effective altruism’s preference for the long term (Beckstead, 2019) may be viewed as being about conversion methods for effects that are really in different dimensions (both temporally and epistemically). Again, temporal logic and epistemic logic are both best seen as part of the broad family of modal logics (Blackburn, Rijke, and Venema, 2001).

2.3 The common ground problem To simplify matters, assume two beings A and B of equal stature who need to make a joint decision about a single numerical parameter r whose setting will affect the value of some effect $e(r)$ they both wish to maximize. To the extent their estimates $e_A(r)$ and $e_B(r)$ of the effect coincide, we have no problem, since they can pick any of the maxima that $e_A(r)$ and $e_B(r)$ have. The problem arises when A and B have different priors.

There is no easy solution in sight: taking the average $(e_A(r) + e_B(r))/2$ may lead to a point r_0 that is so suboptimal both from A's and from B's perspective that neither has any incentive to agree to it. The problem can easily arise even if the parties are not adversarial, and furthermore, e need not be tied to the personal benefit of either of them. A realistic example would be two wealthy parents debating the amount r to be spent on the education of their child: A may want the best private school that money can buy, which will take $r = M$; and B may be a firm believer in public education, $r = 0$. In this situation a shoddy private school that costs $M/2$ makes no sense to either of them.

2.4 The imperfect world problem Another general problem is the robustness of any model. A good current example is provided by self-driving cars, which behave very well in the presence of other well computable objects (roads, traffic signs, and other self-driving cars) but break down in the presence of irrational behavior often observable in human drivers. Strong safety guarantees should include a high level of idiot-proofing. As an example, we submit the ChatGPT response (see Appendix A) to the prompt *Write a shell script to delete all files from directory \$1 that also appear in directory \$2.*

The response is correct, and well explained in the comments. However, it fails to anticipate the case when the user messes up and $\$1 = \2 , so the script is actually not robust against user error. It also fails to anticipate the case when $\$2/\text{file}$ is a symlink to $\$1/\text{file}$, so that after the script is run the user is left with no useable copy or the case when two different files bearing the same name appear in the two directories, etc. This means that the script, even if correctly invoked, is not robust against difficulties in the environment (typically caused by earlier user errors). To check for safety requires more than transparency and correctness: it requires assessing behavior in imperfect situations/worlds that may be counterfactual (do not hold here and now).

2.5 Hume's problem Ethical rationalism offers a solution to the famous is-ought problem (for a critical discussion, see Hudson, 1984) but leaves an important residue concerning Hume's famous dictum:

Reason is, and ought only to be the slave of the passions, and can never pretend to any other office than to serve and obey them.

Simplifying matters somewhat, 'is' statements pertain to rational (fact-based) reasoning, while 'ought' statements refer to moral (value-based) deduction. In AI, the former are typically modeled by symbolic deductive systems such as expert systems and theorem provers, while the primary descriptor of AGI behavior is generally assumed to be some utility function whose maximization is the goal of the AGI. If we conceive of these as two independent subsystems, one discrete and the other continuous, the question becomes: is one subordinate to the other?

Factually, Hume's dictum is well supported in the architecture of humans, where 'passions' are to a large extent involuntary, hard-coded in the hindbrain, whereas the prover/expert system appears to reside in the cortical and thalamic regions. One cannot commit suicide by holding one's breath – the hindbrain is stronger and will take over. But for ethical behavior it may well be necessary for some deductive principle, such as the PGC, to override the passions. The problem does not arise when the two systems agree: in general, both passions (instinctive behavior) and reason dictate that we move

out of the way when harm approaches. But based on higher moral considerations people can, and often do, stay in harm’s way e.g. when volunteering for some dangerous mission.

The choice of whether to subordinate reason to the passions or the other way, subordinate utility-driven behavior to principles arrived at deductively, will arise not just at the individual but also at the species level. A well known hypothetical example was first discussed in the critique of sociobiology offered in Kitcher, 1985, but we can formulate it without any recourse to sociobiological methodology: *is survival a value that trumps everything else?* The thought experiment that supports the position that it is, goes like this: we have two desert islands A and B, initially with one couple on each. “A” man respects “A” woman’s desire not to have sex, whereas “B” man rapes “B” woman. Under this scenario, “A” people die out, whereas “B” people proliferate, suggesting that ethics, however defined (it is hard to find a culture where rape is not considered a crime) is constrained by the need to survive. Real cases include cannibalism in lifeboats, a ‘custom of the sea’ that legal systems increasingly take a harsh view of.

3 Hybridization

We have argued that an agent capable of ethical reasoning in some discrete deductive system that is powerful enough to carry out the Fuenmayor-Benzmüller proof might exhibit safe behavior out of logical necessity, as opposed to forced alignment to some human values. However, numerous components of a strong AI system will inevitably be modeled by continuous (analog) functions that are optimized through the agent’s experiences. Hence, we are faced with the question of how to *hybridize* or combine discrete deductive reasoning with optimization-based continuous systems such as Large Language Models (LLMs). Any proposed hybrid architecture that endows one subsystem with control over the other constitutes an (explicit or implicit) answer to Hume’s Problem. Since we do not think that this is a trivial problem with an easy solution, our plan is to *experiment with different architectures in a safe sandbox that allows only for theorem proving*.

Automated theorem provers have been around for over half a century, and until recently they had no analog components. A novel trend in this field that started in the early 2010’s and has since gained great attention is to leverage the success of machine learning and boost provers with learning based guidance. The simplest form of this interaction between a prover and a trained model is to use the model to provide heuristic guidance and restrict the search space of the prover. The simplest way to restrict search is to filter the axioms that are given to the prover, e.g. Urban et al., 2008; Alemi et al., 2016; Wang et al., 2017). Other works provide internal guidance by restricting the allowed inferences during proof search, e.g. Loos et al., 2017; Jakubuv and Urban, 2017; Gauthier et al., 2018; Kaliszzyk et al., 2018; Zombori, Urban, and Brown, 2020.

We are interested in more subtle interactions between analog components and the prover where both can inform the other. At the very least, we need some language whereby the prover communicates its current state to the heuristic, and another language (or perhaps the same language) whereby the heuristic provides its hints/instructions to the prover. There could be a great deal of experimentation on whether these

internal languages should be symbolic or analog (vectorial), whether we should keep them fixed or let them evolve, whether we need transparency into these, etc. Some indirect guidance is offered by experiments such as Simon Kirby and Smith, 2008, but we believe that the shared task proposed in Section 4 will greatly accelerate development.

One major obstacle for interaction between the heuristic and the prover is due to a difference in *scale*. An analog system that evolves via optimization has hard to interpret components, hence we usually do not know how to make large changes to it; we can only adapt it slowly and smoothly based on novel experiences. A deductive system, on the other hand, performs discrete inferences that result in larger transformations. While there is some work (e.g. Mitchell et al., 2022; Balestrieri and LeCun, 2022) about how to inform the analog system based on the findings of the deductive component, and conversely, this is today still a largely unsolved problem.

One line of research that is promising for our project is to embed discrete reasoning into continuous space, see Bošnjak et al., 2016; Lee et al., 2020; Szabó and Zombori, 2021 for some preliminary work. This approach aims at approximating logical inference with a continuous function. Its main components are 1) an *Embedder* which maps discrete prover states into real valued vectors (called the *embedding space*), 2) a *Decoder* that performs the inverse mapping from embedding space to prover states and 3) a *Transition* model that performs an approximate inference in embedding space, i.e. from the embedded representation of the old prover state into the embedded representation of the new state. These three components all belong to the prover side, however, they provide a comfortable interface towards various analog components. Such heuristic components – that represent things like creativity, experience, gut feelings etc. – can smoothly influence the prover both in terms of how states are represented and what transitions seem reasonable. In this approach, the language of communication between analog and discrete components is vectorial, which has the drawback that is is hard to interpret.

In natural language processing mapping words to vectors brought great success. Here we are faced with the converse task of making the vectors human-understandable by turning them into words. That something like this should be feasible is suggested by the fact that different languages assign largely (up to an arbitrary rotation) similar vectors to their lexica, (Mikolov, Le, and Sutskever, 2013), so much so that establishing the optimal rotation on a few hundred translation pairs is useful for finding translations for other words as well.

Here we propose to rely on the `41lang` set of basic vectors (Kornai, 2023) and decode the communication between components of the hybrid system by means of standard frequency-driven methods based on the embodied nature of human language. To the extent our systems are analogous to biological systems, we treat the following broad analogies between physical bodies and software components as the translation pairs used in minimizing the squared error of the rotation.

The only **effectors** our candidate systems will have are theorem provers (so that they cannot manufacture paperclips). At this early stage, we put no restriction on the kind of theorem prover the system could use as the emphasis is on learning to do formal reasoning and not on any particular formal reasoning. However, we note that, eventually, the system will have to be able to scale to formalisms that are complex enough

to represent the proof of the PGC. The only **output** the system can produce is verified proofs for the shared tasks. We restrict **sensory input** such as by http, for reasons of safety (Babcock, Kramár, and Yampolskiy, 2016).

A much larger issue is to give the “passion” side something to be passionate about. This gets to issues of informed consent, mental suffering, well-being of AI right from the get-go. What the 4lang linguistic interface offers is a set of equations connecting the various vectors, for example *pain* is defined as *bad, sensation, injury cause_* in other words, ‘pain is a bad sensation caused by injury’. We can take *bad* simply as an instruction to minimize the quantity so described.

So what is *sensation*? 4lang offers *sense ins_, <touch>* ‘senses are instruments of sensation, the default sense is touching’. 4lang also lists *fear, joy, and color* as sensations. (These are only examples of senses and sensations, no complete taxonomy is intended or needed. In humans, pain is the strongest signal the sensors can send, as too high intensity light, sound, touch, etc. all become painful.) Moving along, we have *injury* defined as *damage, body has*.

Altogether, this suggests that we can hook up external sensors, in particular those measuring voltage, as pain sensors acting whenever voltage is outside certain bounds. Other possibilities include error codes, in particular parity check failures in memory, disk block failures, divzero, etc. This is going to be moral only if some means of pain-avoidance are also built in. Perhaps the best testing ground is memory usage, provided the garbage collector is put under the control of the system. Some visibility into the process table, quite possibly including processes not under the control of the AGI, may also be necessary. These are heavy issues, and the authors lack the security expertise to offer guidance – part of our goal with this paper is to attract the involvement of real experts, kernel hackers in particular, who have the requisite clarity.

Hooking the analog system up with deep life functions such as memory management is nontrivial. Since vertebrates don’t have conscious control of what’s going on in the hindbrain, AGIs need not possess this facility either. Also, to the extent not just pain but also reward mechanisms are put under the control of the system, wireheading (Yampolskiy, 2014) is a real issue. Designers may wish to explicitly supervise the system so as to avoid wireheading, but in evolutionary setups this is largely unnecessary since wireheads will automatically put themselves out of the running.

4 Proposed shared task for a theorem proving agent

We propose a shared task for developers of AI systems that focuses on making progress towards complex logical reasoning, and through that towards ethical safety. The task contains increasingly hard problems that can be structured into the following four series:

Series 1: understanding of formulas Mathematical formulae typically have well defined compositional semantics, i.e., one can compute the meaning of complex terms from the meanings of its subterms. We argue that a deep understanding of formulae is unavoidable to carry out proofs with any satisfying rigor. To achieve such competence via learning, all sorts of self supervised learning tasks can be used, making it rather easy to generate sufficient training data. In self supervised learning (Jaiswal et al., 2021), we assume no access to human annotation and have to learn from raw data (formulae in our

case). We train our models on various proxy tasks for which labels can be automatically extracted. Example proxy tasks could be: 1) conversion from disjunctive to conjunctive normal form, 2) replacement of variables, 3) formula simplification, 4) predicting logical implication/subsumption. Series 1 problems are typically solvable using deterministic automata, at or below the complexity of individual enzymes. The key expected output from this series is a formula representation that captures the intended semantics in a format that allows for easy interaction with analog/heuristic components. The most natural such representation is an embedding into continuous vector space. There are already some datasets that seem suitable for achieving Series 1 competence, such as the AMPS dataset (Hendrycks et al., 2021).

Series 2: word problems In this next step we move from understanding logical formulae to paragraphs of (technical) English. This series should contain problems of varying difficulty, ranging from MCAS, 3rd grade, Regents, high school (including advanced/honors levels), SAT/ACT, college admission level and even beyond, e.g. IMO or ‘trick’ admissions problems (Khovanova and Radul, 2011). Up to this level the chief difficulty is the use of (technical) English, a problem now reasonably well handled by the current generation of LLMs, including ChatGPT. The focus of this series is auto-formalisation (for HOL see Wu et al., 2022, for Coq see Cunningham, Bunescu, and Juedes, 2023). While the challenge of finding proofs is still moderate, we believe it already offers a rich domain for exploring the interaction between the heuristic ‘passions’ and the logical ‘reasoning’ offered by the prover. Fortunately, there are several datasets of varying difficulty suitable for this series, such as the grade school level GSM8K (Cobbe et al., 2021), CLUTRR (Sinha et al., 2019) which comes with a generator in which one can control the number of elementary inferences to reach the solution, MathQA (Amini et al., 2019) which provides rationales for the solutions or the more challenging MATH (Hendrycks et al., 2021), to name a few. The state of the art on this series is probably the Minerva (Lewkowycz et al., 2022) system but we would strongly advocate for an open source baseline, in fact we cannot countenance the participation of any closed system in the shared task.

Series 3: classical theorem proving The focus of this series is proof search in a formal system. Difficulty can range from the body of classic (19th century) algebra/analysis that makes up the bulk of the freshman/junior math curriculum to cutting edge problems in automated theorem proving and verification. Since TPTP (Sutcliffe, 2017) is already widely used for benchmarking theorem provers, and the problems are fully formalized using the tptp syntax (supported by most theorem provers) we can make progress on this series in parallel to working on Series 2. Note that we expect theorem provers to work both in *discovery* mode (‘find an asymptotic formula for $n!$ ’) and in *verification* mode (‘prove the Stirling formula’).

Series 4: moral reasoning Here, both the linguistic and the theorem proving aspects are challenging. As for the linguistic aspect in particular, we have to turn ‘word problems’ into problems of some deontic logic calculus. A significant step in standardizing the output of the linguistic step is taken in Steen and Fuenmayor, 2022. The problems listed in Section 2 offer a starting point, but there is no generally accepted solution to these.

This is not to say that the disagreements among moral philosophers and practicing ethicists are so wide as to make development of a test suite impossible – if anything,

the agreement is far better than the agreement mapped by descriptive moral relativism within and across cultures and societies. To quote Sinnott-Armstrong, 1992:

The most common way to choose among moral theories is to test how well they cohere with our intuitions or considered judgments about what is morally right and wrong, about the nature or ideal of a person, and about the purpose(s) of morality.

We believe that a systematic overview of ethical guidelines and practices, e.g. in medicine, is a good starting point for identifying ‘low hanging fruit’, and further, many significant cases of disagreement among ethicists can be stated as disagreements about which of two conflicting principles are to be ranked higher in a given situation – the pro-life vs pro-choice debate is a clear example. For such cases, it is proofs relative to some preference ordering that we should be expecting, which is not any different from the mathematical case where our interest is with proofs relative to some axioms. To the extent there is a difference, it is because the community of mathematicians is more uniform in their acceptance of certain foundational axioms and, perhaps, more tolerant of experimenting with alternatives to these.

5 Conclusions

Our goal with this paper is direct continuation of our earlier work on safety. While the long-term goal remains the development of systems that find the PGC so compelling that they cannot depart from it, here we offer a mid-range plan that involves (i) a safe sandbox for experimentation; (ii) a set of shared tasks to measure progress on the experiments; and (iii) a means of keeping human visibility into how the systems evolve.

The safety of the sandbox is guaranteed by replacing physical (robotic) bodies by theorem provers as the only effectors and by dealing with highly specialized (as opposed to general) artificial intelligences whose powers we can explicitly measure at any given stage. The shared task is not just to catalyze progress in automated theorem proving, but also to see which hybrid architecture works best: is it really the one where reason is a slave to the passions? Finally, by making human-readable the vectors used in the hybrid system as a communication method we enable partner-level communication with the systems. We note that instead of an alignment tax our proposal entails a *safety dividend* – the more rational the system the more capable and the safer it will be (see Kornai, 2014 Section 3).

A final issue we should at least mention is imposing our will on the system or not. Both are relatively easy to implement: deterministic procedures impose, non-deterministic ones don’t. LLMs are already good about nondeterminism, typically implemented by random seeds, and we see no reason to seek further (e.g. quantum) mechanisms. The moral direction is clear: do not impose on others what you yourself do not desire (Analects XV:24). This is the PGC. Since you don’t want deterministic processes run on you, don’t impose this on others. But some experimentation (killing processes, modifying the algorithm and re-running) is clearly necessary at least initially, and as soon as the system has the ability to feel pain, some kind of ethics board, modeled on the ones common in biosciences, will be necessary.

Acknowledgments

We thank Madeleine Thompson for cogent remarks that greatly helped us formulate the line of argumentation in the paper. Needless to say, this does not imply she is agreeing with us.

Kornai was supported by the the European Union project RRF-2.3.1-21-2022-00004 within the framework of the Artificial Intelligence National Laboratory Grant no RRF-2.3.1-21-2022-00004.

Zsolt Zombori was supported by the Hungarian National Excellence Grant 2018-1.2.1-NKP-00008 and the Hungarian Artificial Intelligence National Laboratory Program (RRF-2.3.1-21-2022-00004).

References

- Alemi, Alexander A. et al. (2016). “DeepMath - Deep Sequence Models for Premise Selection”. In: *Proceedings of the 30th International Conference on Neural Information Processing Systems*. NIPS’16. Barcelona, Spain: Curran Associates Inc., pp. 2243–2251. ISBN: 978-1-5108-3881-9. URL: <http://dl.acm.org/citation.cfm?id=3157096.3157347>.
- Amini, Aida et al. (2019). “MathQA: Towards Interpretable Math Word Problem Solving with Operation-Based Formalisms”. In: *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2019, Minneapolis, MN, USA, June 2-7, 2019, Volume 1 (Long and Short Papers)*. Ed. by Jill Burstein, Christy Doran, and Thamar Solorio. Association for Computational Linguistics, pp. 2357–2367. DOI: 10.18653/v1/n19-1245. URL: <https://doi.org/10.18653/v1/n19-1245>.
- Babcock, James, János Kramár, and Roman Yampolskiy (2016). “The AGI Containment Problem”. In: *Artificial General Intelligence*. Ed. by Bas Steunebrink, Pei Wang, and Ben Goertzel. Springer International Publishing. DOI: 10.1007/978-3-319-41649-6. URL: <https://doi.org/10.1007%20F978-3-319-41649-6>.
- Bai, Yuntao et al. (2022). *Training a Helpful and Harmless Assistant with Reinforcement Learning from Human Feedback*. DOI: 10.48550/ARXIV.2204.05862. URL: <https://arxiv.org/abs/2204.05862>.
- Balestriero, Randall and Yann LeCun (2022). *POLICE: Provably Optimal Linear Constraint Enforcement for Deep Neural Networks*. DOI: 10.48550/ARXIV.2211.01340. URL: <https://arxiv.org/abs/2211.01340>.
- Beckstead, Nick (2019). “A brief argument for the overwhelming importance of shaping the far future”. In: *Effective altruism*. Ed. by Hilary Greaves and Theron Pummer. Oxford University Press, pp. 80–98. ISBN: 978-0-19-884136-4.
- Beyleveld, Deryck (1991). *The Dialectical Necessity of Morality: An Analysis and Defense of Alan Gewirth’s Argument to the Principle of Generic Consistency*. University of Chicago Press.
- Blackburn, Patrick, Maarten de Rijke, and Yde Venema (2001). *Modal logic*. Cambridge University Press.

- Bošnjak, Matko et al. (2016). *Programming with a Differentiable Forth Interpreter*. DOI: 10.48550/ARXIV.1605.06640. URL: <https://arxiv.org/abs/1605.06640>.
- Brey, Philip (2015). *International differences in ethical standards and in the interpretation of legal frameworks*. Tech. rep. URL: <https://satoriproject.eu/media/D3.2-Int-differences-in-ethical-standards.pdf>.
- Cobbe, Karl et al. (2021). “Training Verifiers to Solve Math Word Problems”. In: *CoRR* abs/2110.14168. arXiv: 2110.14168. URL: <https://arxiv.org/abs/2110.14168>.
- Cunningham, Garrett, Razvan C. Bunescu, and David Juedes (2023). *Towards Autoformalization of Mathematics and Code Correctness: Experiments with Elementary Proofs*. DOI: 10.48550/ARXIV.2301.02195. URL: <https://arxiv.org/abs/2301.02195>.
- Fuenmayor, David and Christoph Benzmueller (2019). “Harnessing Higher-Order (Meta)-Logic to Represent and Reason with Complex Ethical Theories”. In: *PRICAI 2019: Trends in Artificial Intelligence*. Ed. by Abhaya C. Nayak and Alok Sharma. Springer International Publishing, pp. 418–432. ISBN: 978-3-030-29908-8.
- Gauthier, Thibault et al. (2018). “Learning to Prove with Tactics”. In: *CoRR* abs/1804.00596. arXiv: 1804.00596. URL: <http://arxiv.org/abs/1804.00596>.
- Gewirth, A. (1978). *Reason and morality*. University of Chicago Press.
- Hendrycks, Dan et al. (2021). *Measuring Mathematical Problem Solving With the MATH Dataset*. DOI: 10.48550/ARXIV.2103.03874. URL: <https://arxiv.org/abs/2103.03874>.
- Hudson, W.D. (1984). “The ‘Is-Ought’ problem resolved?” In: *Gewirth’s ethical rationalism: critical essays with a reply by Alan Gewirth*. Ed. by E. Regis. University of Chicago Press, pp. 108–127.
- Jaiswal, Ashish et al. (2021). “A survey on contrastive self-supervised learning”. In: *Technologies* 9.1, p. 2.
- Jakubuv, Jan and Josef Urban (2017). “ENIGMA: Efficient Learning-Based Inference Guiding Machine”. In: *Intelligent Computer Mathematics - 10th International Conference, CICM 2017, Edinburgh, UK, July 17-21, 2017, Proceedings*. Ed. by Herman Geuvers et al. Vol. 10383. Lecture Notes in Computer Science. Springer, pp. 292–302. ISBN: 978-3-319-62074-9. DOI: 10.1007/978-3-319-62075-6_20. URL: https://doi.org/10.1007/978-3-319-62075-6_20.
- Kaliszyk, Cezary et al. (2018). “Reinforcement Learning of Theorem Proving”. In: *NeurIPS*, pp. 8836–8847.
- Khovanova, Tanya and Alexey Radul (2011). “Jewish Problems”. In: DOI: 10.48550/ARXIV.1110.1556. URL: <https://arxiv.org/abs/1110.1556>.
- Kitcher, Philip (1985). *Vaulting ambition: Sociobiology and the quest for human nature*. MIT Press. ISBN: 0-262-11109-8.
- Kornai, András (2014). “Bounding the impact of AGI”. In: *Journal of Experimental and Theoretical Artificial Intelligence* 26.3, pp. 417–438.
- (2019). *Semantics*. Springer Verlag. ISBN: 978-3-319-65644-1. URL: <http://kornai.com/Drafts/sem.pdf>.

- (2023). *Vector semantics*. Springer Verlag. URL: <http://kornai.com/Drafts/advsem.pdf>.
- Lee, Dennis et al. (2020). “Mathematical Reasoning in Latent Space”. In: *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net. URL: <https://openreview.net/forum?id=Ske31kBtPr>.
- Lewkowycz, Aitor et al. (2022). “Solving Quantitative Reasoning Problems with Language Models”. In: *Advances in Neural Information Processing Systems*. Ed. by Alice H. Oh et al. URL: <https://openreview.net/forum?id=IFXTZERXdm7>.
- Loos, Sarah M. et al. (2017). “Deep Network Guided Proof Search”. In: *21st International Conference on Logic for Programming, Artificial Intelligence, and Reasoning (LPAR)*.
- Mialon, Grégoire et al. (2023). *Augmented Language Models: a Survey*. DOI: 10.48550/ARXIV.2302.07842. URL: <https://arxiv.org/abs/2302.07842>.
- Mikolov, Tomas, Quoc V. Le, and Ilya Sutskever (2013). *Exploiting Similarities among Languages for Machine Translation*. DOI: 10.48550/ARXIV.1309.4168. URL: <https://arxiv.org/abs/1309.4168>.
- Mitchell, Eric et al. (2022). “Memory-Based Model Editing at Scale”. In: *International Conference on Machine Learning, ICML 2022, 17-23 July 2022, Baltimore, Maryland, USA*. Ed. by Kamalika Chaudhuri et al. Vol. 162. Proceedings of Machine Learning Research. PMLR, pp. 15817–15831. URL: <https://proceedings.mlr.press/v162/mitchell122a.html>.
- Ouyang, Long et al. (2022). *Training language models to follow instructions with human feedback*. DOI: 10.48550/ARXIV.2203.02155. URL: <https://arxiv.org/abs/2203.02155>.
- Simon Kirby, Hannah Cornish and Kenny Smith (2008). “Cumulative cultural evolution in the laboratory: An experimental approach to the origins of structure in human language”. In: *NAS 105.31*, pp. 10881–10686.
- Sinha, Koustuv et al. (2019). “CLUTRR: A Diagnostic Benchmark for Inductive Reasoning from Text”. In: *Empirical Methods of Natural Language Processing (EMNLP)*.
- Sinnott-Armstrong, Walter (1992). “An argument for consequentialism”. In: *Philosophical Perspectives* 6, pp. 399–421.
- Slind, Konrad and Michael Norrish (2008). “A Brief Overview of HOL4”. In: *Theorem Proving in Higher Order Logics, 21st International Conference, TPHOLS 2008, Montreal, Canada, August 18-21, 2008. Proceedings*. Ed. by Otmane Aït Mohamed, César A. Muñoz, and Sofiène Tahar. Vol. 5170. LNCS. Springer, pp. 28–32. ISBN: 978-3-540-71065-3. DOI: 10.1007/978-3-540-71067-7_6. URL: https://doi.org/10.1007/978-3-540-71067-7%5C_6.
- Steen, Alexander and David Fuenmayor (2022). *Bridging between LegalRuleML and TPTP for Automated Normative Reasoning (extended version)*. DOI: 10.48550/ARXIV.2209.05090. URL: <https://arxiv.org/abs/2209.05090>.
- Sutcliffe, G. (2017). “The TPTP Problem Library and Associated Infrastructure. From CNF to TH0, TPTP v6.4.0”. In: *Journal of Automated Reasoning* 59.4, pp. 483–502.

- Szabó, Kristóf and Zsolt Zombori (2021). “Dreaming to Prove”. AITP’21, http://aitp-conference.org/2021/abstract/paper_25.pdf.
- Tersman, Folke (2022). “Moral Disagreement”. In: *The Stanford Encyclopedia of Philosophy*. Ed. by Edward N. Zalta and Uri Nodelman. Fall 2022. Metaphysics Research Lab, Stanford University.
- Urban, Josef et al. (2008). “MaLAREa SG1 - Machine Learner for Automated Reasoning with Semantic Guidance”. In: *IJCAR*. Ed. by Alessandro Armando, Peter Baumgartner, and Gilles Dowek. Vol. 5195. LNCS. Springer, pp. 441–456. ISBN: 978-3-540-71069-1.
- Wang, Mingzhe et al. (2017). “Premise Selection for Theorem Proving by Deep Graph Embedding”. In: *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, 4-9 December 2017, Long Beach, CA, USA*. Ed. by Isabelle Guyon et al., pp. 2783–2793. URL: <http://papers.nips.cc/paper/6871-premise-selection-for-theorem-proving-by-deep-graph-embedding>.
- Wiener, Norbert (1960). “Some Moral and Technical Consequences of Automation: As machines learn they may develop unforeseen strategies at rates that baffle their programmers”. In: *Science* 131, pp. 1355–1358. DOI: 10.1126/science.131.3410.1355.
- Wu, Yuhuai et al. (2022). *Autoformalization with Large Language Models*. DOI: 10.48550/ARXIV.2205.12615. URL: <https://arxiv.org/abs/2205.12615>.
- Yampolskiy, Roman V. (2014). “Utility function security in artificially intelligent agents”. In: *Journal of Experimental & Theoretical Artificial Intelligence* 26, pp. 1–17.
- Zombori, Zsolt, Josef Urban, and Chad E. Brown (2020). “Prolog Technology Reinforcement Learning Prover - (System Description)”. In: *Automated Reasoning - 10th International Joint Conference, IJCAR 2020, Paris, France, July 1-4, 2020, Proceedings, Part II*. Ed. by Nicolas Peltier and Viorica Sofronie-Stokkermans. Vol. 12167. Lecture Notes in Computer Science. Springer, pp. 489–507. DOI: 10.1007/978-3-030-51054-1_33. URL: https://doi.org/10.1007/978-3-030-51054-1_33.

A ChatGPT writes a shell script

Below is the ChatGPT response to the prompt *Write a shell script to delete all files from directory \$1 that also appear in directory \$2:*

```
#!/bin/bash
# Check if the directories were provided as arguments
if [ "$#" -ne 2 ]; then
    echo "Error: Please provide the directories as arguments."
    exit 1
fi
# Save the directories as variables
dir1=$1
dir2=$2
# Check if the directories exist
if [ ! -d "$dir1" ] || [ ! -d "$dir2" ]; then
    echo "Error: One or both of the directories do not exist."
    exit 1
fi
# Find all files in both directories
files1=$(find $dir1 -type f)
files2=$(find $dir2 -type f)
# Iterate over the files in directory 1
for file in $files1; do
    # Check if the file also exists in directory 2
    if grep -q "$file" <<< "$files2"; then
        # If it does, delete it from directory 1
        rm "$file"
    fi
done
```